

Muehlau, 05.25.2018

1 RF Exposure Considerations for the RRU4560

FCC ID: WJ9-RRU4560

The transmitter operation for the RRU4560 covers the 902 – 928MHz operating band. The RRU4560 supports up to four external antennas (non cascable) or up to 32 cascable (8 antennas per port), but operates on only one antenna at a time.

The following FCC Rule Parts and procedures are applicable:

Part 1.1310 – Radiofrequency radiation exposure limits

Part 2.1091 – Radiofrequency radiation exposure evaluation: mobile devices

KDB447498 D01 v06

Mobile and Portable Devices RF Exposure Procedures and Equipment Authorisation Policies

MPE CALCULATIONS

The MPE calculation used to calculate the safe operating distance for the user is:

$$S = \text{EIRP} / 4 \pi R^2$$

Where

S = Power density

EIRP = Effective Isotropic Radiated Power ($\text{EIRP} = P \times G$)

P = Conducted Transmitter Power

G = Antenna Gain (relative to an isotropic radiator)

R = distance to the centre of radiation of the antenna (safe operating distance)

RRU4560 Values:

Transmitter frequency range: 902 – 928MHz

Transmitter power:

(Ref 15.247 (b)(4) – Antennas with gains >6dBi)

- 1) For external 13dBi gain antenna use, 30dBm max. power is reduced by 7dB (13dBi – 6dB)

$$\text{EIRP}_{\text{max}} = +23\text{dBm} + 13\text{dBi antenna gain} = +36\text{dBm} (4.0\text{W})$$

- 2) For external 11dBi gain antenna use, 30dBm max. power is reduced by 5dB (11dBi – 6dB)

$$\text{EIRP}_{\text{max}} = +25\text{dBm} + 11\text{dBi antenna gain} = +36\text{dBm} (4.0\text{W})$$

- 3) For external 8dBi gain antenna use, 30dBm max. power is reduced by 2dB (8dBi – 6dB)

$$\text{EIRP}_{\text{max}} = +28\text{dBm} + 8\text{dBi antenna gain} = +36\text{dBm} (4.0\text{W})$$

KATHREIN Sachsen GmbH

Lindenstraße 3
09241 Mühlau
Germany

Phone: +49 3722 60 73 10
Fax: +49 3722 60 73 24
info@kathrein-sachsen.de
www.kathrein-sachsen.de

Your reference: Klicken Sie hier, um Ihr Zeichen einzubuchen.

Your letter: Klicken Sie hier, um Ihre Nachricht einzulegen.

Our reference: Klicken Sie hier, um Unser Zeichen einzubuchen.

VAT Reg. No.: DE 140 915 677

Company headquarters: Mühlau
HRB 2398 Chemnitz

Managing director(s): Daniel Schkalda

Bank details:

EUR-Accounts:

Deutsche Bank Chemnitz
IBAN: DE28 8707 0000 0263 7270 00
BIC: DEUTDE33XXX

Volksbank Chemnitz
IBAN: DE60 8709 6214 0320 0014 47
BIC: GENODEF1CH1

Sparkasse Mittelsachsen
IBAN: DE93 8705 2000 3545 0015 54
BIC: WELADED1FGX

Power Density Requirement

From table 1 (b) - Limits for General Population/ Uncontrolled Exposure of
FCC Rule Part 1.1310 for 2.4GHz

$$S_{\text{req1}} = f_{\text{MHz}}/1500 \text{ mW/cm}^2 = 902/1500 = 0.6 \text{ mW/cm}^2$$

Calculation:

$$S = \text{EIRP} / 4 \pi R^2$$

$$R = \sqrt{\text{EIRP} / 4 \pi S}$$

$$R = \sqrt{4000 / (4 \pi \times 0.6)}$$

$$R = \sqrt{4000 / (7.54)}$$

$$R = 23.0$$

$$R = 23\text{cm}$$

Conclusion

The safe operating distance for the RRU4560 for General Population/ Uncontrolled Exposure limits is a minimum of 23cm using for all antennas specified to be used with the equipment

Signature:  Date: 05/25/2018

Daniel Schkalda

Managing director