Test Report

No. 1-0702-25-02-08_TR1-R01

June 29. 2026

Applicant	Molex CVS Bochum GmbH
Product	Single Wireless Charger
Model	WCH-311 (tested variant WCH-311a)
Tested Technology	RFID (NFC)
Test Standards (3/6)	DIN EN IEC 62311:2020-01 IEEE C 95.3:2021 RSS-102:Issue 6 (2023-12)
Combined Test Report applicable for:	☑ EC ☑ FCC ☑ ISED
Verdict	PASS

The test results apply only to the equipment specified in this document.

This test report is electronically signed and valid without handwritten signature.
Public keys for verification of the electronic signatures can be requested at the testing laboratory.

Digitally signed by Alexander.Hnatovskiy@cetecomadvanced.com
Date: 2026.06.29 13:53:30

authorized by

Alexander Hnatovskiy

Coordinator Area
Regulatory Services Radio

Digitally signed by Marco.Scigliano@cetecomadvanced.com
Date: 2026.06.29 13:31:11

created by

Marco Scigliano

Testing Manager
Regulatory Services Radio

Table of Contents

1. Disclaimer 4
2. Related cetecom advanced documents 5
3. Document history 6
   3.1. Current release 6
   3.2. Previous releases 6
4. Test laboratory 7
   4.1. Contact information 7
   4.2. Involved test locations 7
   4.3. Subcontracted laboratories 7
   4.4. Laboratory listings and recognitions 7
5. Client information 8
   5.1. Applicant 8
   5.2. Manufacturer 8
6. Test sample information 9
   6.1. General Information 9
      6.1.1. General Data of Main EUT as Declared by Applicant 9
7. Test sample 13.56 MHz RFID 10
8. Application Details 11
   8.1. Scheduling 11
   8.2. Climatic data (Lab/Test environment) 11
   8.3. Options and interpretations 11
9. Measurement details 12
   9.1. Test methodology 12
10. Description of the test setup 13
   10.1. DASY8.2 SAR measurements 14
11. Additional documents 15
12. RF exposure limits (SAR) 17
   12.1. RF Exposure levels 17
13. Summary of measurement results 18
14. Test Setup 19
15. Tissue Simulating Liquids 31
   15.1. Tissue Simulating Liquids: Dielectric properties 31
   15.2. Tissue Simulating Liquids: Parameters 31
16. Measurement Uncertainties 32
   16.1. Measurement Uncertainty Evaluation for SAR Test 32
   16.2. Measurment Uncertainty Evaluation for System Check 33
17. System check and validation 34
   17.1. System Check 34
   17.2. System Check Procedure 34
   17.3. System Validation 34
18. Detailed test results 35
   18.1. Module description 35

18.2. SAR test results 36
18.2.1. General description of test procedures 36
18.2.2. Results overview 36
19. Liquid depth 37
20. Detailed test results 38

1. Disclaimer

The test results of this test report relate exclusively to the test item specified in chapter “Test sample information”. cetecom advanced does not assume responsibility for any conclusions and generalizations drawn from the test results regarding other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of cetecom advanced.

The testing service provided by cetecom advanced has been rendered under the current "General Terms and Conditions for cetecom advanced".

cetecom advanced will not be liable for any loss or damage resulting from false, inaccurate, inappropriate, or incomplete product information provided by the customer.

Under no circumstances does the cetecom advanced test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the cetecom advanced test report include or imply any product or service warranties from cetecom advanced, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by cetecom advanced.

All rights and remedies regarding vendor’s products and services for which cetecom advanced has prepared this test report shall be provided by the party offering such products or services and not by cetecom advanced. In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. Public keys for verification of the electronic signatures can be requested at the testing laboratory.

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at cetecom advanced.

2. Related cetecom advanced documents

Title	Description	Reference	Total Pages
1-0702-25-02-08_TR1-A101-R01	Photos of EUT and test positions	1-0702-25-02-08_TR1-A101-R01	5
1-0702-25-02-08_TR1-A201-R01	Detailed SAR System calibration data	1-0702-25-02-08_TR1-A201-R01	31

3. Document history

3.1. Current release

Release No.:	R01
Date of release:	June 29. 2026
Applied changes:	Initial release

3.2. Previous releases

Version	Applied change	Date of release
n/a		

4. Test laboratory

4.1. Contact information

cetecom advanced GmbH
Untertuerkheimer Str. 6-10
66117 Saarbruecken
Germany

4.2. Involved test locations

Saarbrücken Lab

Untertürkheimer Strasse 6 – 10
66117 Saarbrücken
Germany

4.3. Subcontracted laboratories

None.

4.4. Laboratory listings and recognitions

	Saarbrücken	Essen
FCC	DE0002	DE0003
ISED	DE0001 3462C	DE0001 3462D

5. Client information

5.1. Applicant

Name:	Molex CVS Bochum GmbH
Address:	GERMANY, 44807 Bochum, Meesmannstr. 103
Contact Person:	Ines Baufeld
Contact Person's Email:	Ines.Baufeld@molex.com

5.2. Manufacturer

Name:	Molex CVS Bochum GmbH
Address:	GERMANY, 44807 Bochum, Meesmannstr. 103
Contact Person:	Ines Baufeld
Contact Person's Email:	Ines.Baufeld@molex.com

6. Test sample information

The data about the test samples is given/supplied by the customer and not under control by cetecom advanced GmbH.

6.1. General Information

6.1.1. General Data of Main EUT as Declared by Applicant

Combined Test Report applicable for:	☑ EC ☑ FCC ☑ ISED

7. Test sample 13.56 MHz RFID

Kind of test item	Single Wireless Charger
Device Type	Automotive device
Model name	WCH-311
Type:	WCH-311a
S/N serial number	S8W-00115.04.2636155239
FCC-ID	WJLWCH-311
ISED-Number	7847A-WCH311
Hardware Version Identification Number (HVIN)	WCH-311a
Product Marketing Name (PMN)	WCH-311
Firmware Version Identification Number (FVIN)	-/-
Host Marketing Name (HMN)	-/-
Hardware status	CH 01
Software status	CS 01
Frequency	RFID 13.56 MHz
Antenna	Integrated antenna
Mounting position	Center console car
Power option	14.0 V DC bx external power supply
Accessories	--
Test sample status	Identical prototype
Exposure category	General public / uncontrolled environment

8. Application Details

8.1. Scheduling

Date of sample reception:	May 06.2026
Deate(s) of test:	May 12. 2026 to May 12. 2026

8.2. Climatic data (Lab/Test environment)

Ambient temperature:	20 - 24 °C
Relative humidity content:	40 - 50 %
Air pressure:	not relevant for this kind of testing
Power supply:	230 V / 50 Hz

8.3. Options and interpretations

None

9. Measurement details

9.1. Test methodology

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2018-03) by the Deutsche Akkreditierungsstelle GmbH (DAkkS).

The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number D-PL-12047-01-00.

Test method, standard, rule	Description
DIN EN IEC 62311:2020-01	Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz to 300 GHz) (IEC 62311:2019) German version EN IEC 62311:2020
IEEE C 95.3:2021	IEEE Recommended Practice For Measurements And Computations Of Electric, Magnetic, And Electromagnetic Fields With Respect To Human Exposure To Such Fields, 0 Hz To 300 GHz
RSS-102:Issue 6 (2023-12)	Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
RSS-102.SAR.MEAS:Issue 2 (2025-08)	Measurement Procedure for Assessing Specific Absorption Rate (SAR) Compliance in Accordance with RSS-102
Safety Code 6 (2015)	Limits of Human Exposure to Radiofrequency Electromagnetic Energy in the Frequency Range from 3 kHz to 300 GHz
EN IEC/IEEE 62209-1528:2021	Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1528: Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)

10. Description of the test setup

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).

Each block diagram listed can contain several test setup configurations. All devices belonging to a test setup are identified with the same letter syntax. For example: Column Setup and all devices with an A.

Note: Monitoring

Abbreviation	Explanation
cal	Calibration
calchk	Calibration and Validation
car	Calibration Restricted Use
chk	Validation
chr	Validation Restricted Use
cpu	Validation prior to Use
cnn	No Monitoring

10.4. **DASY8.2 SAR measurements**

SAR measurements between 4 MHz and 250 MHz



11. Additional documents

Further relevant measurement standards out of accreditation space

Test method, standard, rule	Description
FCC - CFR 47 § 2.1093	Radiofrequency radiation exposure evaluation: portable devices.

FCC KDB:	Description
KDB 865664D01v01	FCC OET SAR measurment requirements 100 MHz to 6 GHz
KDB 865664D02v01	RF Exposure Compliance Reporting Documentation Considerations
KDB 447498D01v06	Mobile and Portable Devices RF Exposure Procedures and Equipment Autorization Policies
KDB 680106D01v01	Equipment Authorization of Wireless Power Transfer devices

REMARK:
IEEE/IEC 62209-1528 implements all the measurement methods from EN 62209-2 release 2010 (including AMD 1 from 2019) adding further details and extends the SAR measurements range down to 4MHz. The used measurement methodology full-fills all neccessarities for EN 62209-2 (30MHz to 6 GHz SAR) and fully complies to IEEE/IES 62209-1529 (4MHz to 10 GHz) which also is needed for future Power density measurements (7 to 10 GHz). The neccessary statement of notified body is added in the foollowing chapter.

NB Statement for acceptance of IEC/IEEE 62209-1528 and EN/IEC 62311:2020 for RED 2014/53/EU

SAR measurments between 4MHz and 30 MHz

cetecom advanced GmbH · Untertuerkheimer Str. 6-10· 66117 Saarbruecken · Germany

Technical evaluation of SAR measurement standard IEC/IEEE 62209-1528 and EN IEC 62311:2020

After evaluation of technology and available measurement methods it was found that the most state-of-the-art measurement method for wireless applications in frequency range 4 – 30 MHz is described in unified SAR measurement standard IEC/IEEE 62209-1528, which inter alia incorporates the measurement methods of IEC 62209-1:2016/ EN 62209-1:2016 and IEC 62209-2:2010/EN 62209-2:2010.

EN/ IEC/IEEE 62209-1528, which is planned to replace IEC 62209-1:2016/ EN 62209-1:2016, respectively IEC 62209-2:2010/ EN 62209-2:2010, extends the minimum frequency from 30 MHz (IEC 62209-2:2010/ EN 62209-2:2010), respectively 300 MHz (IEC 62209-1:2016/ EN 62209-1:2016) down to 4 MHz, considering the relevant measurement methods.
As EN IEC 62311:2020 inter alia refers to IEC 62209-1:2016/ EN 62209-1:2016, respectively IEC 62209-2:2010/ EN 62209-2:2010 it is therefore to assume the replacement will also be considered for this reference.

It is therefore to assume the measurement results gained from measurements using methods according to IEC/IEEE 62209-1528 for evaluated frequency range cover the requirements of EN IEC 62311:2020 and may show compliance to Directive 2014/53/EU (RED) article 3.1a) Health which refer to SAR limits listed in table below:

Guideline / Standard	SAR limit, SAR_{max} W/kg	Averaging mass, m g	P_{max} mW	Exposure tier	Region of Body
ICNIRP	2	10	20	General public	Head and trunk
	4	10	40	General public	Limbs
	10	10	100	Occupational	Head and trunk
	20	10	200	Occupational	Limbs

Source: IEC 62479:2010, table A.1

cetecom advanced GmbH

cn=Uwe Nauerz, o=cetecom advanced GmbH, ou=NAU-230601, email=uwe.nauerz@cetecomadvanced.com, c=DE 2024.04.09 10:35:18 +02'00'

Uwe Nauerz / Notified Body RED

Managing Director: Andreas Ehre
Registered: Local Court of Saarbruecken
Reg.-No.: HRB 11298
VAT-IN: DE119671605
Tax ID: 05/112/5792/0297

cetecom advanced GmbH
Untertuerkheimer Str. 6-10
66117 Saarbruecken
Germany

Tel.: +49 (0) 681 598 0
Fax: +49 (0) 681 598 9075
mail@cetecomadvanced.com
www.cetecomadvanced.com/

12. RF exposure limits (SAR)

12.1. RF Exposure levels

In this report the RF Exposure levels of 1999/519/EC as well as the CFR 47 - Part 1, §1.1310 / RSS 102 Issue 06 and Safety Code 6 are applied to ensure the compliance with EC, FCC, ISED and further regimes.

Limit according	1999/519/EC	CFR 47 - Part 1, §1.1310	RSS-102 Issue 06 / Safety code 6
Human Exposure		Uncontrolle Environment General Population	
Spatial Peak SAR* (Head and trunk)	**2.00 W/kg**	**1.60 W/kg**	**1.60 W/kg**
Spatial Average SAR** (Whole Body)	0.08 W/kg	0.08 W/kg	0.08 W/kg
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)		**4.0 W/kg**	
Regimes	EC	FCC	ISED

Table 1: RF exposure limits

The limit applied in this test report is shown in bold letters

Notes:

*	The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate time.
**	The Spatial Average value of the SAR averaged over the whole body.
***	The Spatial Peak value of the SAR average over any 10 grams of tissue (defined as a tissue volume in shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

13. Summary of measurement results

☑ **No deviations from the technical specifications ascertained**		
☐ Deviations from the technical specifications ascertained		
Maximum SAR value (W/kg) for EC:		
	reported	**limit**
10g SAR for body with 0mm distance:	0.048	2
10g SAR for Hands/Feet/Ankle/Wrist with 0mm distance:	0.048	4
Maximum SAR value (W/kg) for FCC:		
	reported	**limit**
1g SAR for body with 0mm distance:	0.125	1.6
10g SAR for Hands/Feet/Ankle/Wrist with 0mm distance:	0.048	4
Maximum SAR value (W/kg) for ISED:		
	reported	**limit**
1g SAR for body with 0mm distance:	0.125	1.6
10g SAR for Hands/Feet/Ankle/Wrist with 0mm distance:	0.048	4

14. Test Setup

Measurement system description



The DASY system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX/TX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid.
- A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY measurement server.
- The DASY measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows.
- DASY software and SEMCAD data evaluation software.
- Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
- The generic twin phantom enabling the testing of left-hand and right-hand usage.
- The triple flat and eli phantom for the testing of handheld and body-mounted wireless devices.
- The device holder for handheld mobile phones and mounting device adaptor for laptops
- Tissue simulating liquid mixed according to the given recipes.
- System check dipoles allowing to validate the proper functioning of the system.

Test Environment

The DASY measurement system is placed in a laboratory room within an environment which avoids influence on SAR measurements by ambient electromagnetic fields and any reflection from the environment. The pictures at the beginning of the photo documentation show a complete view of the test environment. The system allows the measurement of SAR values larger than 0.005 W/kg

Probe Description

Isotropic E-Field Probe for Dosimetric Measurements	
Technical data according to manufacturer information	
Construction	**Symmetrical design with triangular core** **Interleaved sensors** **Built-in shielding against static charges** **PEEK enclosure material (resistant to organic solvents, e.g., DGBE)**
Frequency	**10 MHz to >6GHz (dosimetry); Linearity: ± 0.2 dB** **(30 MHz to 6 GHz)**
Directivity	**± 0.3 dB in HSL (rotation around probe axis)** **± 0.5 dB in tissue material (rotation normal to probe axis)**
Dynamic range	**10 µW/g to > 100 W/kg; Linearity: ± 0.2 dB (noise: typically <1 µW/g)**
Dimensions	**Overall length: 337 mm (Tip: 20mm)** **Tip length: 2.5 mm (Body: 12 mm)** **Typical distance from probe tip to dipole centers: 1mm**
Application	**High precision dosimetric measurments in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.**

Phantom Description

The used SAM Phantom meets the requirements specified in FCC KDB865664 D01 for Specific Absorption Rate (SAR) measurements.

The phantom consists of a fiberglass shell integrated in a wooden table. It allows left-hand and right-hand head as well as body-worn measurements with a maximum liquid depth of 18 cm in head position and 22 cm in planar position (body measurements). The thickness of the Phantom shell is 2 mm +/- 0.1 mm



Triple Modular Phantom consists of three identical modules which can be installed and removed separately without emptying the liquid. It includes three reference points for phantom installation. Covers prevent evaporation of the liquid. Phantom material is resistant to DGBE based tissue simulating liquids.



The used ELI Phantom is fully compatible with the IEC/IEEE 62209-1528 and all known tissue stimulating liquids. It meets the requirements specified in KDB865664 D01 for Specific Absorption Rate (SAR) measurements and is fully compatible with the standard IEC 62209-2. The phantom consists of a fibreglass shell integrated in a wooden table. The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 4MHz to 10 GHz.

Device Holder Description

The DASY device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65°. The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA's only. If necessary an additional support of polystyrene material is used.

Larger DUT's (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values.

Therefore those devices are normally only tested at the flat part of the SAM.

Scanning Procedure

The DASY installation includes predefined files with recommended procedures for measurements and system check. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

The „reference“ and „drift“ measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT’s output power and should vary max. +/- 5 %.

The highest integrated SAR value is the main concern in compliance test applications. These values can mostly be found at the inner surface of the phantom and cannot be measured directly due to the sensor offset in the probe. To extrapolate the surface values, the measurement distances to the surface must be known accurately. A distance error of 0.5mm could produce SAR errors of 6% at 1800 MHz. Measurements can be performed in a fixed plane or by following an arbitrary surface.

For an automatic and accurate detection of the phantom surface, the DASY system uses Mechanical Surface Detection:

Mechanical Surface Detection

Mechanical surface detection uses the probe collision detector built into the DAE. It is extremely accurate if the probe is normal to the surface (0.05 mm). For angled probes, the distance increases, because the detection is at the edge of the probe tip. It can be used in any liquid with any kind of probe. If the surface is strongly angled with respect to the probe, the probe slides along the surface and is defected sideways. The second switch system in the DAE will detect this situation and the probe will move backward until the touch condition is cleared. However, there will be some remaining uncertainty in the final probe position. In the job description, the desired distance from the probe sensors to the phantom surface can be entered. The detection is always at touch, but the probe will move backward from the surface the indicated distance before starting the measurement.

Mother Scan in cDASY6/DASY8 Module SAR

The cDASY6/DASY8 Module SAR provides the possibility to do a Mother Scan in which a high resolution Area Scan is done in the phantom filled with liquid to a fixed level using a special teaching probe. This mother scan data is used to recreate the phantom inner surface in software, and all future area and/or zoom scans, and a surface detection check is no longer required.

The „area scan“ measures the SAR above the DUT or verification dipole on a parallel plane to the surface. It is used to locate the approximate location of the peak SAR with 2D spline interpolation. The robot performs a stepped movement along one grid axis while the local electrical field strength is measured by the probe. The probe is touching the surface of the SAM during acquisition of measurement values. The scan uses different grid spacings for different frequency measurements. Standard grid spacing for head measurements in frequency ranges ≤ 2GHz is 15 mm in x- and y- dimension. For higher frequencies a finer resolution is needed, thus for the grid spacing is reduced according the following table:

Area scan grid for different frequency ranges

Frequency range	Grid Spacing
≤ 2 GHz	≤ 15 mm
2 - 4 GHz	≤ 12 mm
4 - 6 GHz	≤ 10 mm

Grid spacing and orientation have no influence on the SAR result. For special applications where the standard scan method does not find the peak SAR within the grid, e.g. mobile phones with flip cover, the grid can be adapted in orientation. Results of this coarse scan are shown in annex B.

A „zoom scan" measures the field in a volume around the 2D peak SAR value acquired in the previous „coarse" scan. It uses a fine meshed grid where the robot moves the probe in steps along all the 3 axis (x, y and z-axis) starting at the bottom of the Phantom. The grid spacing for the cube measurement is varied according to the measured frequency range, the dimensions are given in the following table:

Zoom scan grid spacing and volume for different frequency ranges

Frequency range	Grid spacing for x,y axis	Grid spacing for z axis	Minimum zoom scan volume
≤ 2 GHz	≤ 8 mm	≤ 5 mm	≥ 30 mm
2 - 3 GHz	≤ 5 mm*	≤ 5 mm	≥ 28 mm
3 - 4 GHz	≤ 5 mm*	≤ 4 mm	≥ 28 mm
4 - 5 GHz	≤ 4 mm*	≤ 3 mm	≥ 25 mm
5 - 6 GHz	≤ 4 mm*	≤ 2 mm	≥ 22 mm

* When zoom scan is required and the reported SAR from the area scan based 1-g SAR estimation procedures of KDB Publication 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

DASY provides an auto-extending feature to expand the size of the measurement area of the zoom scan as long as the maximum is found too close to the edge of the measured range, which eliminates the need to re-measure cubes whose maximum is found on the boundary of the defined measurement cube.

To meet the requirements of IEC 62209-2 AMD1 from 2019 it is necessary to perform graded grid measurements to avoid measurement mistakes.

Below 3 GHz it defines:
Horizontal grid step ≤ 8mm
Vertical grid step ≤ 5mm for uniform spacing

For variable spacing in vertical direction the maximum distance between the two closest measured points to the phantom shell (M1 and M2) shall be ≤ 4 mm and the spacing between farther points shall increase by a factor ≤ 1.5. Zoom Scan size ≤ 30 mm by 30 mm by 30 mm.

Above 3 GHz it defines:
Horizontal grid step ≤ (24/f [GHz]) mm
Vertical grid step ≤ (10/(f [GHz] − 1)) mm for uniform spacing

For variable spacing in vertical direction the maximum distance between the two closest measured points to the phantom shell (M1 and M2) shall be ≤ (12/f [GHz]) mm and the spacing between farther points shall increase by a factor ≤ 1.5. Zoom Scan size ≤ 22 mm by 22 mm by 22 mm.

If the zoom scan measured as defined above complies with both of the following criteria, or if the peak spatial-average SAR is below 0.1 W/kg, no additional measurements are needed:

1. the smallest horizontal distance from the local SAR peaks to all points 3 dB below the SAR peak shall be larger than the horizontal grid steps in both x and y directions (Δx, Δy). This shall be checked for the measured zoom scan plane conformal to the phantom at the distance zM1. The minimum distance shall be recorded in the SAR test report;
2. the ratio of the SAR at the second measured point (M2) to the SAR at the closest measured point (M1) at the x-y location of the measured maximum SAR value shall be at least 30 %. This ratio (in %) shall be recorded in the SAR test report.

If one or both of the above criteria are not met, the zoom scan measurement shall be repeated using a finer resolution while keeping the other zoom scan parameters compatible with the basic requirements for zoom scans.

New horizontal and vertical grid steps shall be determined from the measured SAR distribution so that the above criteria are met. Compliance with the above two criteria shall be demonstrated for the new measured zoom scan. The size of the higher resolution zoom scan and all other parameters shall apply. The closest point to the phantom shell shall be 2 mm or less for graded grids and the grading factor shall be 1.5 or less. Uncertainties due to field distortion between the media boundary and the dielectric enclosure of the probe should also be minimized, which is achieved if the distance between the phantom surface and physical tip of the probe is larger than the probe tip diameter. Other methods may utilize correction procedures to compensate for boundary effects that enable high precision measurements closer than half the probe tip diameter. For all measurement points, the angle of the probe normal to the flat phantom surface shall be less than 5°. If this cannot be achieved, an additional uncertainty evaluation is required.

Orientation of the probe with respect to the line normal to the phantom surface, shown at two different locations:



NOTE M1 to M8 are example measurement points used for extrapolation to the surface. The maximum of the angle α between the evaluation axis and the surface normal line is called the probe angle. The distance zM1 is from the phantom shell to the first measurement point M1, and its maximum value is 1.4mm fixed for the DASY system equipped with an EX-Probe. The distances Δzi (i = 1, 2, 3, ...) are the distances from measurement points Mi to Mi-1. For uniform grids, Δzi are equal. For graded grids, Δzi+1 > Δzi. Rz = Δzi+1/Δzi is a ratio with a maximum value (defined in the table below). The z direction corresponds to the vertical direction, the x direction is horizontal and the y direction is horizontal into the page.

NOTE 1: The evaluation of the zoom scan is typically done by the post-processor by interpolation and extrapolation and without reconstruction of the field. More focused induced SAR distributions (e.g., for more localized sources such as capacitively coupled sources) require a more dense grid such that the same integration and extrapolation algorithms can be used for the same assessment uncertainty.

NOTE 2: The minimum ratio of 30 % is derived from the plane wave penetration depth at 6 GHz.

Detailed parameters can be seen in the following tables:

Zoom scan parameters:

Parameter	DUT transmit frequency being tested	
	$f \leq 3$ GHz	3 GHz < $f \leq 6$ GHz (f in GHz)
Maximum distance between the closest measured points and the phantom surface (zM1 in Figure 18 and Table 1, in mm)	5	δ ln(2)/2*
Maximum angle between the probe axis and the phantom surface normal (α in Figure 20)	5° (flat phantom only) 30° (other phantoms)	5° (flat phantom only) 20° (other phantoms)
Maximum spacing between measured points in the x- and y-directions (Δx and Δy, in mm)	8	24 / f[b]
For uniform grids: Maximum spacing between measured points in the direction normal to the phantom shell (Δz_1 in Figure 20, in mm)	5	10 / (f − 1)
For graded grids: Maximum spacing between the two closest measured points in the direction normal to the phantom shell (Δz_1 in Figure 20, in mm)	4	12/f
For graded grids: Maximum incremental increase in the spacing between measured points in the direction normal to the phantom shell ($R_z = \Delta z_2/\Delta z_1$ in Figure 20)	1.5	1.5
Minimum edge length of the zoom scan volume in the x- and y-directions (L_x in O.8.3.2, in mm)	30	22
Minimum edge length of the zoom scan volume in the direction normal to the phantom shell (L_h in O.8.3.2 in mm)	30	22
Tolerance in the probe angle	1°	1°

* δ is the penetration depth for a plane-wave incident normally on a planar half-space.
[b] This is the maximum spacing allowed, which might not work for all circumstances.

Minimum probe requirements as a function of frequency and parameters of the tissue equivalent liquid

1	2	3	4	5	6	7	8
Frequency MHz	Relative permittivity	Conductivity S/m	Wavelength in the medium (λ) mm	Plane wave Skin Depth (δ) mm	Maximum Diameter mm	50% Distance for M1 ($z_{50\%} = \delta$ ln(2)/2) mm	Min. distance for M1 (z_{M1}) mm
300	45.3	0.87	148.6	46.1	8.0	16.0	5.0
450	43.5	0.87	101.1	42.9	8.0	14.9	5.0
750	41.9	0.89	61.8	39.8	8.0	13.8	5.0
835	41.5	0.90	55.8	38.9	8.0	13.5	5.0
900	41.5	0.97	51.7	36.1	8.0	12.5	5.0
1450	40.5	1.20	32.5	28.6	8.0	9.9	5.0
1800	40.0	1.40	26.4	24.3	8.0	8.4	5.0
2000	40.0	1.40	23.7	24.2	8.0	8.4	5.0
2450	39.2	1.80	19.6	18.7	6.5	6.5	5.0
2600	39.0	1.96	18.5	17.2	6.2	5.9	5.0
3000	38.5	2.40	16.1	13.9	5.4	4.8	5.0
4000	37.4	3.43	12.3	9.6	4.1	3.3	3.3
5000	36.2	4.45	10.0	7.3	3.3	2.5	2.5
5200	36.0	4.66	9.6	7.0	3.2	2.4	2.4
5400	35.8	4.86	9.3	6.7	3.1	2.3	2.3
5600	35.5	5.07	9.0	6.4	3.0	2.2	2.2
5800	35.3	5.27	8.7	6.1	2.9	2.1	2.1
6000	35.1	5.48	8.4	5.9	2.8	2.0	2.0

Further probe parameters can be seen in Annex M of IEC 62209-2.

Spatial Peak SAR Evolution

The cDASY6/DASY8 Module SAR software includes all numerical procedures necessary to evaluate the spatial peak SAR values. Based on the IEEE 1528 standard, a new algorithm has been implemented. The spatial-peak SAR can be computed over any required mass.

The base for the evaluation is a "cube" measurement in a volume of 30mm3 below 3GHz or 22mm³ above 3GHz. The measured volume must include the 1 g and 10 g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan. If the 10g cube or both cubes are not entirely inside the measured volumes, the system issues a warning regarding the evaluated spatial peak values within the post-processing engine. This means that if the measured volume is shifted, higher values might be possible. To get the correct values a finer measurement grid for the area scan is used. In complicated field distributions, a large grid spacing for the area scan might miss some details and give an incorrectly interpolated peak location. The cDASY6/DASY8 Module SAR allows to automatically extend the grid to make sure that both cubes are inside the measured volume.

The entire evaluation of the spatial peak values is performed within the application in case of cDASY6/DASY8 Module SAR software. The system always gives the maximum values for the 1 g and 10 g cubes. The cDASY6/DASY8 software allow to automatically extend the grid to make sure that both cubes are inside the measured volume. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

1. extraction of the measured data (grid and values) from the Zoom Scan
2. calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
3. generation of a high-resolution mesh within the measured volume
4. interpolation of all measured values from the measurement grid to the high-resolution grid
5. extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
6. calculation of the averaged SAR within masses of 1 g and 10 g The significant parts are outlined in more detail within the following sections.

Interpolation, Extrapolation and Detection of Maxima

The probe is calibrated at the center of the dipole sensors which is located 1 to 2.7mm away from the probe tip. During measurements, the probe stops shortly above the phantom surface, depending on the probe and the surface detecting system. Both distances are included as parameters in the probe configuration file. The software always knows exactly how far away the measured point is from the surface. As the probe cannot directly measure at the surface, the values between the deepest measured point and the surface must be extrapolated.

The choice of the coordinate system defining the location of the measurement points has no influence on the uncertainty of the interpolation, Maxima Search and extrapolation routines. The interpolation, extrapolation and maximum search routines are all based on the modified Quadratic Shepard's method [Robert J. Renka, "Multivariate Interpolation Of Large Sets Of Scattered Data", University of North Texas ACM Transactions on Mathematical Software, vol. 14, no. 2, June 1988, pp. 139-148.].

Thereby, the interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation. The cDASY6/DASY8 routines construct a once-continuously differentiable function that interpolates the measurement values as follows:

- For each measurement point a trivariate (3-D) / bivariate (2-D) quadratic is computed. It interpolates the measurement values at the data point and forms a least-square fit to neighbouring measurement values.

- the spatial location of the quadratic with respect to the measurement values is attenuated by an inverse distance weighting. This is performed since the calculated quadratic will fit measurement values at nearby points more accurate than at points located further away.
- After the quadratics are calculated at all measurement points, the interpolating function is calculated as a weighted average of the quadratics.

There are two control parameters that govern the behavior of the interpolation method.

One specifies the number of measurement points to be used in computing the least-square fits for the local quadratics. These measurement points are the ones nearest the input point for which the quadratic is being computed.

The second parameter specifies the number of measurement points that will be used in calculating the weights for the quadratics to produce the final function. The input data points used there are the ones nearest the point at which the interpolation is desired. Appropriate defaults are chosen for each of the control parameters.

The trivariate quadratics that have been previously computed for the 3-D interpolation and whose input data are at the closest distance from the phantom surface, are used in order to extrapolate the fields to the surface of the phantom.

In order to determine all the field maxima in 2-D (Area Scan) and 3-D (Zoom Scan), the measurement grid is refined by a default factor of 10 (area) and 5 (zoom), respectively, and the interpolation function is used to evaluate all field values between corresponding measurement points. Subsequently, a linear search is applied to find all the candidate maxima. In a last step, non physical maxima are removed and only those maxima which are within 2 dB of the global maximum value are retained.

Important: To be processable by the interpolation/extrapolation scheme, the Area Scan requires at least6 measurement points. The Zoom Scan requires at least 10 measurement points to allow the application of these algorithms.

In the Area Scan, the gradient of the interpolation function is evaluated to find all the extrema of the SAR distribution. The uncertainty on the locations of the extrema is less than 1/20 of the grid size. Only local maxima within 2 dB of the global maximum are searched and passed for the Zoom Scan measurement.

In the Zoom Scan, the interpolation function is used to extrapolate the Peak SAR from the lowest measurement points to the inner phantom surface (the extrapolation distance). The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

Averaging and Determination of spatial Peak SAR

Within cDASY6/DASY8 Module SAR software, the measured grid is interpolated to a high resolution grid, where the resolution is around 1mm and chosen such that the cube volume is a multiple of the resolution. Points which are outside of the measured grid are masked out and set to zero. Then, the antiderivative of the interpolated grid is computed by using a Gaussian quadrature consecutively for all spatial dimensions.

The antiderivative is used to compute all cube averages of the volume with the same resolution as the interpolated grid. The maximum of these SAR averages is reported. If the cube containing the maximum averaged SAR touches the surface of the measured volume, an appropriate warning is issued within the Post-processing engine.

Data Storage and Evaluation

Data Storage

The DASY software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DA4", ".DA5x". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [W/kg], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	$Norm_i$, a_{i0}, a_{i1}, a_{i2}
	- Conversion factor	$ConvF_i$
	- Diode compression point	Dcp_i
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	s
	- Density	r

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot c_f/dcp_i$$

with	V_i	= compensated signal of channel i	(i = x, y, z)
	U_i	= input signal of channel i	(i = x, y, z)
	c_f	= crest factor of exciting field	(DASY parameter)
	dcp_i	= diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be

evaluated:

E-field probes: $E_i = (V_i / Norm_i \cdot ConvF)^{1/2}$

H-field probes: $H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1f} + a_{i2f2})/f$

with V_i = compensated signal of channel i (i = x, y, z)
$Norm_i$ = sensor sensitivity of channel i (i = x, y, z)
[mV/(V/m)^2] for E-field Probes

ConvF = sensitivity enhancement in solution
a_{ij} = sensor sensitivity factors for H-field probes
f = carrier frequency [GHz]
E_i = electric field strength of channel i in V/m
H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_{x2} + E_{Y2} + E_{z2})^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot}^2 \cdot s) / (r \cdot 1000)$$

with SAR = local specific absorption rate in W/kg
Etot = total field strength in V/m
s = conductivity in [mho/m] or [Siemens/m]
r = equivalent tissue density in g/cm^3

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$P_{pwe} = E_{tot2} / 3770$ or $P_{pwe} = H_{tot2} \cdot 37.7$

with P_{pwe} = equivalent power density of a plane wave in mW/cm^2
E_{tot} = total electric field strength in V/m
H_{tot} = total magnetic field strength in A/m

<u>Data Evaluation in cDASY6/DASY8</u>
cDASY6/DASY8 features basic evaluation capabilities comparable to the above described SEMCAD evaluation.

15. Tissue Simulating Liquids

15.1. Tissue Simulating Liquids: Dielectric properties

The following materials are used for producing the tissue-equivalent materials.

HBBL4-250V3 Simulating Head Liquid, Manufactures by SPEAG:

Ingredients	(% by weight)
Water	50-90
Tween 20	5-50
Sodium salt	0-2
Preservatives	0.03-0.1

Table: Head tissue dielectric properties

15.2. Tissue Simulating Liquids: Parameters

Liquid	Freq.	Target head tissues		Measurement head tissue					
HSL	(MHz)	Permittivity	Conductivity [S/m]	Permittivity	Dev. (%)	Conductivity ε"	[S/m]	Dev. (%)	Measurement date
13	13.0	55.00	0.75	57.588	4.71	987.35	0.714	-4.79	2026-05-12
	13.5	55.00	0.75	56.908	3.47	699.10	0.714	-4.76	

Table: Parameter of the head tissue simulating liquid (HSL)

Note: The dielectric properties have been measured using the contact probe method at 22°C

*) as the liquid parameters deviation is ≥ ± 5% an extrapolation according IEC/IEEE 62209-1528 chapter 7.8.2 approach 3 is neccessary. The DASY software is capable to perform the neccessary corrections directly from the tissue and measurement data. The uncertainties in this document have been adjusted accordingly.

For detailed information see chapter SAR correction for deviations of complex permittivity from targets.

16. Measurement Uncertainties

16.1. Measurement Uncertainty Evaluation for SAR Test

DASY6/8 Uncertainty Budget According to IEC/IEEE 62209-1528 (Frequency band: 4 MHz - 300 MHz range)																
Symbol	Error Description	Uncertainty Value			Probability Distribution	Divisor		c_i	c_i	Standard Uncertainty						
								(1g)	(10g)	± %, (1g)			± %, (10g)			
Measurement System Errors																
CF	Probe Calibration Repeat.	±	13.3	%	Normal		2	1	1	±	6.7	%	±	6.7	%
CFdrift	Probe Calibration Drift	±	1.7	%	Rectangular	√	3	1	1	±	1.0	%	±	1.0	%
LIN	Probe linearity	±	4.7	%	Rectangular	√	3	1	1	±	2.7	%	±	2.7	%
BBS	Broadband Signal	±	0.8	%	Rectangular	√	3	1	1	±	0.5	%	±	0.5	%
ISO	Probe Isotropy (axial)	±	7.6	%	Rectangular	√	3	1	1	±	4.4	%	±	4.4	%
DAE	Data Acquisition	±	0.7	%	Normal		1	1	1	±	0.7	%	±	0.7	%
AMB	RF Ambient	±	1.8	%	Normal		1	1	1	±	1.8	%	±	1.8	%
Δ_{xyz}	Probe Positioning	±	0.006	mm	Normal		1	0.04	0.04	±	0.1	%	±	0.1	%
DAT	Data Processing	±	1.2	%	Normal		1	1	1	±	1.2	%	±	1.2	%
Phantom and Device Errors																
LIQ(σ)	Conductivity (meas.)[DAK]	±	2.5	%	Normal		1	0.78	0.71	±	2.0	%	±	1.8	%
LIQ(Tσ)	Conductivity (temp.)[BB]	±	5.4	%	Rectangular	√	3	0.78	0.71	±	2.4	%	±	2.2	%
EPS	Phantom Permittivity	±	14.0	%	Rectangular	√	3	0	0	±	0.0	%	±	0.0	%
DIS	Distance DUT - TSL	±	2.0	%	Normal		1	2	2	±	4.0	%	±	4.0	%
D_{rot}	Device Positioning	±	1.0	%	Normal		1	1	1	±	1.0	%	±	1.0	%
H	Device Holder	±	3.6	%	Normal		1	1	1	±	3.6	%	±	3.6	%
MOD	DUT Modulation[m]	±	2.4	%	Rectangular	√	3	1	1	±	1.4	%	±	1.4	%
TAS	Time-average SAR	±	1.7	%	Rectangular	√	3	1	1	±	1.0	%	±	1.0	%
RF_{drift}	DUT drift	±	2.5	%	Normal		1	1	1	±	2.5	%	±	2.5	%
VAL	Val Antenna Unc.[val]	±	0.0	%	Normal		1	1	1	±	0.0	%	±	0.0	%
RF_{in}	Unc. Input Power[val]	±	0.0	%	Normal		1	1	1	±	0.0	%	±	0.0	%
Correction to the SAR results																
C(ε, σ)	Deviation to Target	±	1.9	%	Normal		1	1	0.84	±	1.9	%	±	1.6	%
C(R)	SAR scaling[p]	±	0.0	%	Rectangular	√	3	1	1	±	0.0	%	±	0.0	%
u(ΔSAR)	**Combined Uncertainty**									±	11.4	%	±	11.3	%
U	**Expanded Uncertainty**									±	**22.8**	%	±	**22.5**	%

Table: Measurement uncertainties

Worst Case uncertainty budget for DASY6/8 assessed according to IEC/IEEE 62209-1528. The budget is valid for the frequency range 4 MHz - 300 MHz and represents a worst-case analysis. For specific tests and configurations, the uncertainty could be considerable smaller. All listed error components have V e f f equal to ∞.

Footnote details:

m SMC calibration is a new method for determining the total deviation from linearity.
The uncertainty is ≤ 2.4% for psSAR ≤ 2 W/kg, ≤ 4.8% for psSAR1g/10g ≤ 4 W/kg and ≤ 9.6% for psSAR1g/10g ≤ 10 W/kg (see modulation calibration parameter uncertainty in the probe calibration certificate);

BB if SPEAG's broad-band liquids (BBL) are used that have low temperature coefficients;

DAK if SPEAG's high precision dielectric probe kit (DAK) is applied;

p if power scaling is used, error item "SAR Scaling" must be adjusted accordingly;

val only applies in case of validation measurements.

16.2. Measurment Uncertainty Evaluation for System Check

Repeatability Budget for System Check (Frequency band: 4MHz - 300MHz range) with DASY6/8 System																
Symbol	Error Description	Uncertainty Value			Probability Distribution	Divisor		c_i (1g)	c_i (10g)	Standard Uncertainty ± %, (1g)			± %, (10g)		
Measurement System Errors															
CF	Probe Calibration Repeat.	±	13.3	%	Normal		2	1	1	±	6.7	%	±	6.7	%
CFdrift	Probe Calibration Drift	±	1.7	%	Rectangular	√	3	1	1	±	1.0	%	±	1.0	%
LIN	Probe linearity	±	4.7	%	Rectangular	√	3	1	1	±	2.7	%	±	2.7	%
BBS	Broadband Signal	±	0.0	%	Rectangular	√	3	1	1	±	0.0	%	±	0.0	%
ISO	Probe Isotropy (axial)	±	4.7	%	Rectangular	√	3	1	1	±	2.7	%	±	2.7	%
DAE	Data Acquisition	±	0.7	%	Normal		1	1	1	±	0.7	%	±	0.7	%
AMB	RF Ambient	±	0.6	%	Normal		1	1	1	±	0.6	%	±	0.6	%
Δ_{sys}	Probe Positioning	±	0.5	%	Normal		1	0.04	0.04	±	0.0	%	±	0.0	%
DAT	Data Processing	±	0.0	%	Normal		1	1	1	±	0.0	%	±	0.0	%
Phantom and Device Errors															
LIQ(σ)	Conductivity (meas.)[DAK]	±	2.5	%	Normal		1	0.78	0.71	±	2.0	%	±	1.8	%
LIQ(Tσ)	Conductivity (temp.)[BB]	±	3.4	%	Rectangular	√	3	0.78	0.71	±	1.5	%	±	1.4	%
EPS	Phantom Permittivity	±	14.0	%	Rectangular	√	3	0	0	±	0.0	%	±	0.0	%
DIS	Distance Phantom - DUT	±	1.0	%	Normal		1	2	2	±	2.0	%	±	2.0	%
MOD	DUT Modulation[m]	±	0.0	%	Rectangular	√	3	1	1	±	0.0	%	±	0.0	%
TAS	Time-average SAR	±	0.0	%	Rectangular	√	3	1	1	±	0.0	%	±	0.0	%
VAL	Validation antenna	±	3.2	%	Normal		1	1	1	±	3.2	%	±	3.2	%
P_{in}	Accepted power	±	2.0	%	Normal		1	1	1	±	2.0	%	±	2.0	%
Correction to the SAR results															
C(ε, σ)	Deviation to Target	±	1.9	%	Normal		1	1	0.84	±	1.9	%	±	1.6	%
u(ΔSAR)	**Combined Uncertainty**									±	9.4	%	±	9.3	%
U	**Expanded Uncertainty**									±	**18.8**	%	±	**18.6**	%

Table: Repeatability of the system check (4 MHz - 300 MHz)

The RF ambient noise uncertainty has been reduced to ±1.0, considering input power levels are ≥ 250mW. All listed error components have V e f f equal to ∞.

Footnote details:

[BB] if SPEAG's broad-band liquids (BBL) are used that have low temperature coefficients;

[DAK] if SPEAG's high precision dielectric probe kit (DAK) is applied.

Note: Worst case probe calibration uncertainty has been applied for all probes used during the measurements.

17. System check and validation

17.1. System Check

The system check is performed for verifying the accuracy of the complete measurement system and performance of the software. The following table shows system check results for all frequency bands and tissues liquids used during the tests (plots see external annex A201 - Detailed test results and system checks).

System performence check (1000 mW)

System validation Kit	Probe	Frequency	Target SAR_{1g} /mW/g (+/-10%)	Target SAR_{10g} /mW/g (+/- 10%)	Measured SAR_{1g} / mW/g	SAR_{1g} dev.	Measured SAR_{10g} / mW/g	SAR_{10g} dev.	Measured date
CLA 13 S/N: 1026	EX3DV4 S/N: 7635	13 MHz HSL	0.463	0.293	0.44	-5.0%	0.28	-4.4%	2026-05-12

Table: Results system check

17.2. System Check Procedure

The system check is performed by using a validation dipole which is positioned parallel to the planar part of the SAM phantom at the reference point. The distance of the dipole to the SAM phantom is determined by a plexiglass spacer. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100 mW or 50 mW if used Powersource1. To adjust this power a power meter is used. The power sensor is connected to the cable before the system check to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the validation to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

System check results have to be equal or near the values determined during dipole calibration (target SAR in table above) with the relevant liquids and test system.

17.3. System Validation

The system validation is performed in a similar way as a system check. It needs to be performed once a SAR measurement system has been established and allows an evaluation of the system accuracy with all components used together with the specified system. It has to be repeated at least once a year or when new system components are used (DAE, probe, phantom, dipole, liquid type).

In addition to the procedure used during system check a system validation also includes checks of probe isotropy, probe modulation factor and RF signal.

The following table lists the system validations relevant for this test report:

System Validations

Frequency (MHz)	Test System	DASY SW	Dipole Type /SN	Probe Type / SN	Calibrated signal type(s)	DAE unit Type / SN	head validation
13	Saarbrücken / DASY 8	DASY6 SAR V17.0.2.6775	CLA13 / 1026	EX3DV4 / 7635	CW	DAE4ip / 1842	2026-05-05

Table: System Validations

18. Detailed test results

18.1. Module description

The implemente NXP - NCF3321 processor has a max power dissipiation between 450 to 1650 mW

(according customer specification).

Declared max. power: 1650mW = 32.2 dBm

Declared min. power: 450mW = 26.5 dBm

NOTE:

A conducted sample is unreasonable for the EUT regarding 13.56 MHz feature. The antenna is designed by wired. It is a loop antenna type with some turns of track. The radiated power (Electric field) is very weak because there is not a real radiated element. That is why the antenna gain is very low (compared with a dipole antenna of the same frequency) and difficult to measure (gain is << 0dBi).

Instead the declared min. and max. power values of the module are used to upscale the SAR value according worst case conditions, what results in a overestimation of the reported SAR value. If the EUT still surpasses the restrictions, it is safe to assume that the EUT is not capable of producing SAR values above the reported SAR.

18.2. SAR test results

18.2.1. General description of test procedures

- The DUT is tested using a test software to control test channels and maximum output power of the DUT.
- For RFID tests the EUT was set to permanent active scanning (13.56 MHz). All EUT sides close to the RFID antenna were tested with 0mm distance to the phantom.
- For the extrapolation of the reported SAR (extrapolated), the following formula was used:

$$SAR_{reported} = \frac{decl.max.}{decl.min.} \cdot SAR_{meas.}$$

18.2.2. Results overview

13.56 MHz Radiated; Serial: S8W-00115.04.2636155239

Freq. (MHz)	Position	decl. P_{max} (dBm)		SAR_{1g} (W/kg)		SAR_{10g} (W/kg)		power drift (dB)	liquid (°C)	dist. (mm)
		max.	min.	meas.	extrap.	meas.	extrap.			
13.56	Top	32.2	26.5	0.035	0.129	0.013	0.048	-0.16	20.8	0

Table: Test results SAR RFID 13.56 MHz

*) reported SAR value, up scaled from the distance between min. and max. declared module power (see module description above)

19. Liquid depth

Photo: Liquid depth HBBL4-250V3 – 13MHz Simulating Head Liquid



20. Detailed test results

Date/Time: 2026-05-12, 13:16 2026-05-12, 13:26

SystemPerformanceCheck-D13

DUT: Dipole; Type: CLA13; Serial: SN1026

Communication System: Custom: CW_user; Communication System Frequency: 13.0 MHz

Medium parameters used: f = 13.0 MHz, σ = 0.714 S/m; εr=57.6; ρ= 1000 kg/m3

Phantom Section: Flat
Measurement Standard: DASY 8

DASY Configuration:
- Probe: EX3DV4 - SN7635; ConvF(18.92, 17.36, 18.54); Calibrated: 2026-01-19
- Sensor-Surface: 1.4 mm
- DAE: DAE4 Sn1387; Calibrated: 2025-08-06
- Phantom: ELI V8.0 (20deg probe tilt); Serial: 2101;
- Software: DASY8 Module SAR V17.0.4.7034

HBBL4-250V3/13.0MHz/Area Scan (15.0 x 15.0 x 1.0) :

Grid Extents [mm]: 270.0 x 270.0
Maximum value of SAR (interpolated) - SAR(1 g) = 0.045 W/kg; SAR(10 g) = 0.037 W/kg

HBBL4-250V3/13.0MHz/Zoom Scan (3.75 x 3.75 x 1.5) :

Grid Extents [mm]: 30.0 x 30.0 x 30.0

SPCPower = 20.0 dBm

Power Drift = -0.01 dB
SAR(1 g) = 0.044 W/kg; SAR(10 g) = 0.028 W/kg



Additional information:
ambient temperature: 23.1°C; liquid temperature: 20.8°C;

Date/Time: 2026-05-12, 13:40 2026-05-12, 13:56

IEC_IEEE 62209-1528 NFC

DUT: Molex; Type: MPP Single WCH-311a; Serial: S8W00115.04.2636155239

Communication System: Custom: CW_user; Communication System Band: Custom; Communication System Frequency: 13.6 MHz

Medium parameters used: f = 13.6 MHz, σ = 0.714 S/m; εr=56.9; ρ= 1000 kg/m3

Phantom Section: Flat
Measurement Standard: DASY 8

DASY Configuration:
- Probe: EX3DV4 - SN7635; ConvF(18.92, 17.36, 18.54); Calibrated: 2026-01-19
- Sensor-Surface: 1.4mm
- DAE: DAE4 Sn1387; Calibrated: 2025-08-06
- Phantom: ELI V8.0 (20deg probe tilt); Serial: 2101;
- Software: DASY8 Module SAR V17.0.4.7034

HBBL4-250V3/EDGE TOP, 0 mm - Channel 13550/Area Scan (15.0 x 15.0 x 1.0) :
Grid Extents [mm]: 150.0 x 180.0
Maximum value of SAR (interpolated) - SAR(1 g) = 0.032 W/kg; SAR(10 g) = 0.021 W/kg

HBBL4-250V3/EDGE TOP, 0 mm - Channel 13550/Zoom Scan (3.75 x 3.75 x 1.5) :
Grid Extents [mm]: 30.0 x 30.0 x 30.0
Graded Grid: Ratio 1.5 - Distance Sensor to Surface 1.4 mm
Power Drift = -0.16 dB
SAR(1 g) = 0.035 W/kg; SAR(10 g) = 0.013 W/kg

Additional Info for IEC 62209-2 AMD1:
TDist 3dB Peak [mm]: 4.4
M2/M1 [%]: 60.6



Additional information:
position or distance of DUT to SAM: 0 mm
ambient temperature: 23.1°C; liquid temperature: 20.8°C;

End of document