

FCC PART 15.249


TEST REPORT

For

Jiaxing Shufude Electric Bed Co., Ltd.

East No. 07 Provincial Road, Tengyun Village Wangjiangjing Development Zone, Jiaxing,
Zhejiang, China

FCC ID: WKZCU3582U

Report Type: Original Report		Product Type: Control UNIT	
Test Engineer:	Peter Jiang 		
Report Number:	RKS160929003-00A		
Report Date:	2016-10-20		
Reviewed By:	Jesse Huang EMC Manager		
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Kunshan) Chenghu Road,Kunshan Development Zone No.248,Kunshan, Jiangsu, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn		

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION.....	4
JUSTIFICATION	4
EUT EXERCISE SOFTWARE	4
SUPPORT EQUIPMENT LIST AND DETAILS	4
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS.....	6
FCC§15.203 - ANTENNA REQUIREMENT.....	7
APPLICABLE STANDARD	7
ANTENNA CONNECTOR CONSTRUCTION	7
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	8
APPLICABLE STANDARD	8
MEASUREMENT UNCERTAINTY	8
EUT SETUP	8
EMI TEST RECEIVER SETUP.....	9
TEST PROCEDURE	9
TEST EQUIPMENT LIST AND DETAILS.....	9
CORRECTED FACTOR & MARGIN CALCULATION	9
TEST RESULTS SUMMARY	10
TEST DATA	10
FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION.....	15
APPLICABLE STANDARD	15
MEASUREMENT UNCERTAINTY.....	15
EUT SETUP	16
TEST EQUIPMENT SETUP	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST EQUIPMENT LIST AND DETAILS.....	18
TEST RESULTS SUMMARY	18
TEST DATA	18
FCC §15.215(C) – 20 DB BANDWIDTH TESTING.....	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST EQUIPMENT LIST AND DETAILS.....	24
TEST DATA	24

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Jiaxing Shufude Electric Bed Co., Ltd.'s product, model number: CU358-2-U (FCC ID: WKZCU3582U) (the "EUT") in this report was a Control UNIT, was measured approximately: 120mm (L) x 100mm (W) x 44mm (H), rated input voltage: DC18-32V.

All measurement and test data in this report was gathered from production sample serial number: 20160926001.

(Assigned by BACL, Kunshan). The EUT was received on 2016-09-26.

Objective

This type approval report is prepared on behalf of Jiaxing Shufude Electric Bed Co., Ltd. in accordance with Part 2-Subpart J, and Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.249 DXX Grant with FCC ID: WKZ-RF258G.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the Chenghu Road, Kunshan Development Zone No.248, Kunshan, Jiangsu, China.

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Justification

The system was configured in testing mode which was provided by manufacturer.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2403	39	2441
2	2404	40	2442
...	...	...	...
...	...	...	...
37	2439	77	2479
38	2440	78	2480

EUT was tested with Channel 1, 40 and 78.

EUT Exercise Software


No software was used during the test.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
OKIN	Adapter1: AC/DC Switching Power Supply Input: AC100-240V 50/60Hz 1.5A Output: DC29V, 2A	SP2-A2	RBD507305854
	Adapter2: AC/DC Switching Power Supply Input: AC100-240V 50/60Hz 1.5A Output: DC29V, 2A	02-290020	RBD534100135
OKIN	Steering engine	B11318	73555
OKIN	Resistance	8 Ω	-

Block Diagram of Test Setup

For conducted emission



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	Conduction Emissions	Compliance
15.205, §15.209, §15.249	Radiated Emissions& Out of Band Emission	Compliance
§15.215 (c)	20 dB Bandwidth	Compliance

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Antenna Connector Construction

The EUT has a PCB antenna arrangement and antenna gain is 1dBi, which was permanently attached ,fulfill the requirement of this section, please refer to the EUT photos.

Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207


Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements may be receiver reading, attenuation of the connection between LISN and receiver, LISN voltage division factor, LISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2, the expanded combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Kunshan) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report.

Port	Expanded Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	934115/007	2015-11-12	2016-11-11
Rohde & Schwarz	LISN	ESH3-Z5	862770/011	2015-11-12	2016-11-11
Rohde & Schwarz	LISN	ESH3-Z5	892239/018	2016-06-23	2017-06-22
Rohde & Schwarz	Pulse limiter	ESH3-Z2	879940/0058	2016-06-19	2017-06-18
MICRO-COAX	Coaxial line	UFB-293B-1-0480-50X50	97F0173	2016-10-02	2017-10-01
Rohde & Schwarz	CE Test software	EMC 32	V 09.10.0	--	--

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, the worst margin reading as below:

Adapter 1: 11.63 dB at 0.545000 MHz in the Neutral conducted mode

Adapter 2: 14.90 dB at 0.400000 MHz in the Line conducted mode

Refer to CISPR16-4-2 and CISPR 16-4-1, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(L_m)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.


Test Data

Environmental Conditions


Temperature:	23 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Peter Jiang on 2016-10-20.

EUT operation mode: Transmitting

Adapter 1:**AC 120V/60 Hz, Line**


Frequency (MHz)	QuasiPeak (dBμV)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.155000	---	31.12	9.000	L1	11.0	24.61	55.73	Compliance
0.155000	46.26	---	9.000	L1	11.0	19.47	65.73	Compliance
0.430000	---	23.49	9.000	L1	11.0	23.76	47.25	Compliance
0.430000	28.87	---	9.000	L1	11.0	28.38	57.25	Compliance
0.545000	---	34.11	9.000	L1	11.0	11.89	46.00	Compliance
0.545000	35.31	---	9.000	L1	11.0	20.69	56.00	Compliance
1.480000	---	23.26	9.000	L1	11.1	22.74	46.00	Compliance
1.480000	23.90	---	9.000	L1	11.1	32.10	56.00	Compliance
2.125000	---	21.99	9.000	L1	11.2	24.01	46.00	Compliance
2.125000	23.41	---	9.000	L1	11.2	32.59	56.00	Compliance
8.890000	---	17.91	9.000	L1	11.4	32.09	50.00	Compliance
8.890000	22.05	---	9.000	L1	11.4	37.95	60.00	Compliance

AC 120V/60 Hz, Neutral


Frequency (MHz)	QuasiPeak (dBμV)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.155000	---	30.48	9.000	N	11.0	25.25	55.73	Compliance
0.155000	45.50	---	9.000	N	11.0	20.23	65.73	Compliance
0.180000	---	23.40	9.000	N	11.0	31.09	54.49	Compliance
0.180000	37.61	---	9.000	N	11.0	26.88	64.49	Compliance
0.545000	---	34.37	9.000	N	11.0	11.63	46.00	Compliance
0.545000	35.79	---	9.000	N	11.0	20.21	56.00	Compliance
1.560000	---	21.29	9.000	N	11.2	24.71	46.00	Compliance
1.560000	22.60	---	9.000	N	11.2	33.40	56.00	Compliance
2.065000	---	23.70	9.000	N	11.2	22.30	46.00	Compliance
2.065000	24.22	---	9.000	N	11.2	31.78	56.00	Compliance
8.770000	---	17.87	9.000	N	11.4	32.13	50.00	Compliance
8.770000	22.23	---	9.000	N	11.4	37.77	60.00	Compliance

Note:

- 1) Corr.=LISN VDF (Voltage Division Factor) + Cable Loss
- 2) Corrected Amplitude = Reading + Corr.
- 3) Margin = Limit –Corrected Amplitude

Adapter 2:**AC 120V/60 Hz, Line**

Frequency (MHz)	QuasiPeak (dBμV)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.230000	---	7.12	9.000	L1	11.0	45.33	52.45	Compliance
0.230000	31.43	---	9.000	L1	11.0	31.02	62.45	Compliance
0.400000	---	23.26	9.000	L1	11.0	24.59	47.85	Compliance
0.400000	42.95	---	9.000	L1	11.0	14.90	57.85	Compliance
0.470000	---	8.29	9.000	L1	11.0	38.22	46.51	Compliance
0.470000	28.79	---	9.000	L1	11.0	27.72	56.51	Compliance
0.640000	---	10.02	9.000	L1	11.1	35.98	46.00	Compliance
0.640000	30.36	---	9.000	L1	11.1	25.64	56.00	Compliance
1.215000	---	5.56	9.000	L1	11.1	40.44	46.00	Compliance
1.215000	22.22	---	9.000	L1	11.1	33.78	56.00	Compliance
5.460000	---	4.08	9.000	L1	11.3	45.92	50.00	Compliance
5.460000	19.94	---	9.000	L1	11.3	40.06	60.00	Compliance

AC 120V/60 Hz, Neutral

Frequency (MHz)	QuasiPeak (dBμV)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.155000	---	19.40	9.000	N	11.0	36.33	55.73	Compliance
0.155000	43.73	---	9.000	N	11.0	22.00	65.73	Compliance
0.180000	---	21.37	9.000	N	11.0	33.12	54.49	Compliance
0.180000	46.14	---	9.000	N	11.0	18.35	64.49	Compliance
0.355000	---	9.94	9.000	N	11.0	38.90	48.84	Compliance
0.355000	27.76	---	9.000	N	11.0	31.08	58.84	Compliance
0.560000	---	25.81	9.000	N	11.0	20.19	46.00	Compliance
0.560000	36.10	---	9.000	N	11.0	19.90	56.00	Compliance
2.295000	---	12.86	9.000	N	11.3	33.14	46.00	Compliance
2.295000	26.59	---	9.000	N	11.3	29.41	56.00	Compliance
8.845000	---	10.27	9.000	N	11.4	39.73	50.00	Compliance
8.845000	21.78	---	9.000	N	11.4	38.22	60.00	Compliance

Note:

- 1) Corr.=LISN VDF (Voltage Division Factor) + Cable Loss
- 2) Corrected Amplitude = Reading + Corr.
- 3) Margin = Limit –Corrected Amplitude

FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION

Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Kunshan) is:

30M~1GHz: 5.91 dB


Above 1G: 4.92 dB

Table 1 – Values of U_{cispr}


Measurement	U_{cispr}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

Test Equipment Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detection mode from 30MHz to 1GHz, Peak and average detection mode above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sonoma Instrument	Amplifier	330	171377	2016-07-04	2017-07-03
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2015-11-12	2016-11-11
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2015-11-07	2016-11-06
ETS	Horn Antenna	3115	6229	2015-11-07	2016-11-06
EMCO	Horn Antenna	3116	9510-2384	2015-11-7	2016-11-6
DUCOMMUN	Pre-amplifier	ALN-22093530-01	990147	2016-9-16	2017-9-15
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2015-11-12	2016-11-11
Rohde & Schwarz	SIGNAL ANALYZER	FSV40	101116	2016-07-04	2017-07-03
Mini	Pre-amplifier	ZVA-183-S+	857001418	2016-07-04	2017-07-03
R&S	Auto test Software	EMC32	V 09.10.0	-	-
BACL	RF cable	KS-LAB-012	KS-LAB-012	2015-12-16	2016-12-15
BACL	RF cable	KS-LAB-010	KS-LAB-010	2015-12-16	2016-12-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 & 15.205 & 15.249, with the worst margin reading of:

2.63dB at 2403 MHz in the **Vertical** polarization for Low Channel


Test Data**Environmental Conditions**

Temperature:	25.6°C
Relative Humidity:	52%
ATM Pressure:	101.2 kPa

The testing was performed by Peter Jiang on 2016-09-27.


30MHz-1GHz:

Adapter 1:



Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.249/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μV/m)	Margin (dB)
34.326250	23.26	QP	353.0	101.0	V	-7.4	15.86	40.00	24.14
61.437500	39.27	QP	197.0	101.0	V	-16.9	22.37	40.00	17.63
96.763750	51.80	QP	293.0	101.0	V	-15.8	36.00	43.50	7.50
126.197500	44.80	QP	220.0	101.0	V	-13.9	30.90	43.50	12.60
208.238750	42.19	QP	171.0	101.0	V	-12.5	29.69	43.50	13.81
879.600000	21.75	QP	264.0	101.0	V	-1.0	20.75	46.00	25.25

Adapter 2:



Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.249/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μV/m)	Margin (dB)
42.897500	32.01	QP	241.0	101.0	V	-12.2	19.81	40.00	20.19
48.635000	37.14	QP	171.0	101.0	V	-15.7	21.44	40.00	18.56
61.236250	36.39	QP	147.0	101.0	V	-16.9	19.49	40.00	20.51
104.483750	33.76	QP	298.0	101.0	V	-13.3	20.46	43.50	23.04
127.085000	40.91	QP	250.0	101.0	V	-13.8	27.11	43.50	16.39
306.213750	33.68	QP	157.0	101.0	H	-10.3	23.38	46.00	22.62


Test Mode: Transmitting (Scan with X, Y, Z axis, the worst case is X axis)

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.249/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
Low Channel (2403 MHz)									
2403.0	95.92	PK	352	199	V	4.9	100.82	114.00	13.18
2403.0	86.47	Ave	352	199	V	4.9	91.37	94.00	2.63
2403.0	97.14	PK	50	169	H	4.9	102.04	114.00	11.96
2403.0	82.59	Ave	50	169	H	4.9	87.49	94.00	6.51
2390.0	33.86	PK	351	232	V	4.9	38.76	74.00	35.24
2390.0	19.98	Ave	351	232	V	4.9	24.88	54.00	29.12
2400.0	34.29	PK	342	217	V	4.9	39.19	74.00	34.81
2400.0	28.54	Ave	342	217	V	4.9	33.44	54.00	20.56
1210.0	33.55	PK	37	232	H	1.4	34.95	74.00	39.05
1210.0	26.89	Ave	37	232	H	1.4	28.29	54.00	25.71
4806.0	31.37	PK	11	163	H	13.3	44.67	74.00	29.33
4806.0	25.41	Ave	11	163	H	13.3	38.71	54.00	15.29
7209.0	29.67	PK	283	177	H	19.7	49.37	74.00	24.63
7209.0	21.84	Ave	283	177	H	19.7	41.54	54.00	12.46
Middle Channel (2442MHz)									
2442.0	96.57	PK	174	233	V	4.9	101.47	114.00	12.53
2442.0	85.98	Ave	174	233	V	4.9	90.88	94.00	3.12
2442.0	96.18	PK	334	195	H	4.9	101.08	114.00	12.92
2442.0	83.50	Ave	334	195	H	4.9	88.40	94.00	5.60
1210.0	33.48	PK	345	213	H	1.4	34.88	74.00	39.12
1210.0	19.43	Ave	345	213	H	1.4	20.83	54.00	33.17
4884.0	35.09	PK	286	215	H	13.6	48.69	74.00	25.31
4884.0	28.18	Ave	286	215	H	13.6	41.78	54.00	12.22
6681.0	32.79	PK	190	153	V	17.9	50.69	74.00	23.31
6681.0	27.16	Ave	190	153	V	17.9	45.06	54.00	8.94
6948.0	31.63	PK	267	184	H	18.8	50.43	74.00	23.57
6948.0	25.76	Ave	267	184	H	18.8	44.56	54.00	9.44
7326.0	29.18	PK	177	242	H	20.0	49.18	74.00	24.82
7326.0	21.78	Ave	177	242	H	20.0	41.78	54.00	12.22

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.249/15.205/15.209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
High Channel (2480MHz)									
2480.0	95.59	PK	344	233	V	5.0	100.59	114.00	13.41
2480.0	85.57	Ave	344	233	V	5.0	90.57	94.00	3.43
2480.0	96.67	PK	182	215	H	5.0	101.67	114.00	12.33
2480.0	82.61	Ave	182	215	H	5.0	87.61	94.00	6.39
2483.5	34.02	PK	270	246	H	5.0	39.02	74.00	34.98
2483.5	19.75	Ave	270	246	H	5.0	24.75	54.00	29.25
2489.0	35.56	PK	277	237	H	5.0	40.56	74.00	33.44
2489.0	27.93	Ave	277	237	H	5.0	32.93	54.00	21.07
1238.0	33.48	PK	139	216	H	1.5	34.98	74.00	39.02
1238.0	26.73	Ave	139	216	H	1.5	28.23	54.00	25.77
4960.0	30.68	PK	66	186	H	13.9	44.58	74.00	29.42
4960.0	24.79	Ave	66	186	H	13.9	38.69	54.00	15.31
7440.0	29.40	PK	174	209	H	20.4	49.80	74.00	24.20
7440.0	21.50	Ave	174	209	H	20.4	41.90	54.00	12.10


Out of Band Emission

Band Edge, Left Side



Date: 27 SEP 2016 16:21:01

Band Edge, Right Side



Date: 27 SEP 2016 16:23:39

FCC §15.215(c) – 20 dB BANDWIDTH TESTING

Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	SIGNAL ANALYZER	FSV40	101116	2016-07-04	2017-07-03
BACL	RF cable	KS-LAB-012	KS-LAB-012	2015-12-16	2016-12-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.6°C
Relative Humidity:	51 %
ATM Pressure:	101.2kPa


* The testing was performed by Peter Jiang on 2016-09-27.

Test Result: Compliant.

Please refer to following tables and plots


Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2403	1.09
Middle	2442	1.10
High	2480	1.10

Low Channel


Date: 27_SEP_2016 16:47:37

Middle Channel



Date: 27 SEP 2016 16:49:42

High Channel



Date: 27 SEP 2016 16:52:21

***** END OF REPORT *****