

Dates of Tests: Aug 21, 2025 ~ Sep 22, 2025
Test Report S/N: LR500112510B
Test Site : LTA CO., LTD

CERTIFICATION OF COMPLIANCE

FCC ID.

WLD-VB60

APPLICANT

DUNAN. Co., Ltd.

Equipment Class	:	Security/Remote Control Transmitter (DSC)
Manufacturing Description	:	VelluxBell
Manufacturer	:	DUNAN. Co., Ltd.
Model name	:	VB60
Variant Model name	:	VB20 / VBS10 / VBS112 / VBS10
Test Device Serial No.:	:	Identical prototype
Rule Part(s)	:	FCC Part 15 Subpart C ; ANSI C63.10 - 2020
Frequency Range	:	433.05 MHz ~ 434.79 MHz
Max. Output Power	:	Max 78.57 dBuV/m – Radiated
Data of issue	:	Oct 01, 2025

This test report is issued under the authority of:



Eun-Hwan Jung, Manager

The test was supervised by:



In-Sun Lee, Test Engineer

Revision history

Revision	Date of issue	Description	Revised by
--	Oct 01 ,2025	Initial	-

TABLE OF CONTENTS

1. GENERAL INFORMATION ----- 3

2. INFORMATION ABOUT TEST ITEM ----- 4

3. TEST REPORT ----- 5

 3.1 SUMMARY OF TESTS ----- 5

 3.2 RF EXPOSURE EVULATION----- 6

1. General information

1-1 Test Performed

Company name : LTA Co., Ltd.
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2027-03-29	FCC CAB
VCCI	JAPAN	C-4948,	2026-09-10	VCCI registration
VCCI	JAPAN	T-2416,	2026-09-10	VCCI registration
VCCI	JAPAN	R-4483(10 m),	2026-10-15	VCCI registration
VCCI	JAPAN	G-847	2025-12-13	VCCI registration
IC	CANADA	5799A-1	2026-08-15	IC filing

2. Information about test item

2-1 Client & Manufacturer

Client Company name : DUNAN. Co., Ltd.

Address : B-1303, Woolim Lions Valley 5th, 302, Galmachi-ro, Jungwon-gu,
Seongnam-si, Gyeonggi-do, South Korea 462-739

Tel / Fax : +82-31-715-4513 / +82-31-715-4531

Manufacturer : DUNAN. Co., Ltd.

Address : B-1303, Woolim Lions Valley 5th, 302, Galmachi-ro, Jungwon-gu,
Seongnam-si, Gyeonggi-do, South Korea 462-739

Tel / Fax : +82-31-715-4513 / +82-31-715-4531

2-2 Equipment Under Test (EUT)

Model name : VB60

Variant Model name : VB20 / VBS10 / VBS112 / VBS10

Serial number : Identical prototype

Date of receipt : Aug 21, 2025

EUT condition : Pre-production, not damaged

Antenna type : PCB Antenna (Max Gain : 0.63 dBi)

Frequency Range : 433.05 MHz ~ 434.79 MHz

RF output power : Max 78.57 dBuV/m – Radiated

Type of Modulation : FSK

Power Source : DC 12 V

2-3 Tested frequency

Bluetooth	LOW	MID	HIGH
Frequency (MHz)	433.05	433.92	434.79

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
-	-	-	-

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
§1.1310 and §2.1091	RF EXPOSURE EVULATION	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

3.2 RF EXPOSURE EVULATION

1.1 Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength	Magnetic field Strength	Power density (mW/cm ²)	Averaging time
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 - 100.000.....			1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

1.2 MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

Power density at the specific separation:

$S = PG/(4R^2\pi)$ $S = (0.001 * 1.16) / (4 * 5^2 * \pi)$ $S = 0.000\ 000\ 3\ \text{mW/cm}^2$	Where, S = Maximum power density (mW/cm ²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (5 mm = limit for MPE)
---	---

1.3 MAXIMUM PERMISSIBLE EXPOSURE Prediction

Max Peak output Power at antenna input terminal	-28.42	dBm
Max Peak output Power at antenna input terminal	0.001	mW
Prediction distance	5	mm
Prediction frequency	433.92	MHz
Antenna Gain(typical)	0.63	dBi
Antenna Gain(numeric)	1.16	-

SAR Test exclusion thresholds for 100MHz to 6GHz at test separation distance ≤ 5 mm = **Used**

$[(\text{max.power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f}(\text{GHz})]$

$= [0.001 / 5] * [\sqrt{0.43392}] = 0.0002 \leq 3.0$, for 1g SAR

Thus, SAR for this device is not required.