

FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

DEI Sales, Inc., dba Polk Audio

MAGNIFI ONE SYSTEM

Model Number: MAGNIFI ONE X SUBWOOFER

FCC ID: WLQAM8114BRX

Prepared for : DEI Sales, Inc., dba Polk Audio
1 Viper Way Vista, California 92081, United States

Prepared By : EST Technology Co., Ltd.
San Tun Management Zone, Houjie Town, Dongguan,
Guangdong, China

Tel: 86-769-83081888-808

Report Number: ESTE-R1612048
Date of Test : December 08 ~ 27, 2016
Date of Report : December 28, 2016

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	4
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT)	5
2. SUMMARY OF TEST	6
2.1. Summary of test result.....	6
2.2. Test Facilities	7
2.3. Measurement uncertainty	8
2.4. Assistant equipment used for test	8
2.5. Block Diagram	8
2.6. Test mode	9
2.7. Channel List for Bluetooth	9
2.8. Test Equipment.....	10
3. MAXIMUM PEAK OUTPUT POWER	11
3.1. Limit	11
3.2. Test Procedure	11
3.3. Test Result.....	11
3.4. Test Data	12
4. 20 DB BANDWIDTH.....	16
4.1. Limit	16
4.2. Test Procedure	16
4.3. Test Result.....	16
4.4. Test Data	17
5. CARRIER FREQUENCY SEPARATION	21
5.1. Limit	21
5.2. Test Procedure	21
5.3. Test Result.....	21
5.4. Test Data	22
6. NUMBER OF HOPPING CHANNEL	26
6.1. Limit	26
6.2. Test Procedure	26
6.3. Test Result.....	26
6.4. Test Data	27
7. DWELL TIME	29
7.1. Limit	29
7.2. Test Procedure	29
7.3. Test Result.....	29
7.4. Test Data	30
8. RADIATED EMISSIONS.....	36
8.1. Limit	36
8.2. Block Diagram of Test setup	37
8.3. Test Procedure	38
8.4. Test Result.....	38
8.5. Test Data	39
9. BAND EDGE COMPLIANCE	58

9.1. Limit 58

9.2. Block Diagram of Test setup 58

9.3. Test Procedure 58

9.4. Test Result 58

9.5. Test Data 59

10. POWER LINE CONDUCTED EMISSIONS 75

10.1. Limit 75

10.2. Test Procedure 75

11. ANTENNA REQUIREMENTS 80


11.1. Limit 80

11.2. Result 80

12. TEST SETUP PHOTO 81

13. PHOTOS OF EUT 83

Test Report Verification

Applicant:	DEI Sales, Inc., dba Polk Audio		
Address:	1 Viper Way Vista, California 92081, United States		
Manufacturer	DEI Sales, Inc., dba Polk Audio		
Address:	1 Viper Way Vista, California 92081, United States		
Factory	Zhao Yang Electronic (ShenZhen) Co.,Ltd.		
Address:	Building 2, De Yong Jia Industrial Park, Guang Qiao Road, Yu Lv Community, Gong Ming Street, Guang Ming New District, Shenzhen, 518132, China		
E.U.T:	MAGNIFI ONE SYSTEM		
Model Number:	MAGNIFI ONE X SUBWOOFER		
Power Supply:	AC 100-240V ~ 50Hz-60Hz		
Test Voltage:	AC 100-240V ~ 50Hz-60Hz		
Trade Name:	Polk	Serial No.:	-----
Date of Receipt:	December 08, 2016	Date of Test:	December 09 ~ 27, 2016
Test Specification:	FCC Rules and Regulations Part 15 Subpart C:2016 ANSI C63.10:2013		
Test Result:	The device described above is tested by EST Technology Co., Ltd.. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart C requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd. Date: December 28, 2016		
Prepared by:	Tested by:	Approved by:	
			
Ada / Assistant	Tony.Tang / Engineer	Iceman.Hu / Manager	
Other Aspects:	None.		
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Product Name	:	MAGNIFI ONE SYSTEM
FCC ID	:	WLQAM8114BRX
Model Number	:	MAGNIFI ONE X SUBWOOFER
Operation frequency	:	2402MHz~2480MHz
Number of channel	:	79
Antenna	:	Internal antenna, 0dBi gain
Modulation	:	BT BDR: GFSK BT EDR: $\pi/4$ -DQPSK BT EDR: 8-DPSK
Sample Type	:	Prototype production

2. SUMMARY OF TEST

2.1. Summary of test result

Description of Test Item	Standard	Results
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) DA 00-705	PASS
20dB Bandwidth	FCC Part 15: 15.247a1 DA 00-705	PASS
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) DA 00-705	PASS
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) DA 00-705	PASS
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) DA 00-705	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10:2013 DA 00-705	PASS
Band Edge Compliance	FCC Part 15: 15.247(d) DA 00-705	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10:2013 DA 00-705	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

2.2. Test Facilities

EMC Lab	:	Certificated by CNAL, CHINA Registration No.: L5288 Date of registration: December 07, 2015 Certificated by FCC, USA Registration No.: 989591 Date of registration: November 15, 2016 Certificated by Industry Canada Registration No.: 9405A-1 Date of registration: December 30, 2015 Certificated by VCCI, Japan Registration No.: R-3663 & C-4103 Date of registration: July 25, 2011 Certificated by TUV Rheinland, Germany Registration No.: UA 50195514 0001 Date of registration: January 07, 2011 Certificated by TUV/PS, Shenzhen Registration No.: SCN1017 Date of registration: January 27, 2011 Certificated by Intertek ETL SEMKO Registration No.: 2011-RTL-L1-18 Date of registration: April 28, 2011 Certificated by Siemic, Inc. Registration No.: SLCN021 Date of registration: November 8, 2011 Certificated by Nemko, Hong Kong Registration No.: 175193 Date of registration: May 4, 2011
Name of Firm	:	EST Technology Co., Ltd.
Site Location	:	San Tun Management Zone, Houjie Town, Dongguan, Guangdong, China

2.3. Measurement uncertainty

Test Item	Uncertainty
Uncertainty for Conduction emission test	2.54dB
Uncertainty for Radiation Emission test (30MHz-1GHz)	3.62dB
Uncertainty for Radiation Emission test (1GHz to 18GHz)	4.86dB
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	0.20dB
Uncertainty for Power density test	0.26dB


Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

2.4. Assistant equipment used for test

2.4.1. N/A

2.5. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground. EUT was be set into BT test mode by software before test.



(EUT: MAGNIFI ONE SYSTEM)

2.6. Test mode

The test software was used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Mode	Channel	Frequency
GFSK	Low	2402MHz
	Middle	2441MHz
	High	2480MHz
8-DPSK	Low	2402MHz
	Middle	2441MHz
	High	2480MHz

2.7. Channel List for Bluetooth

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2402	2	2403	3	2404	4	2405
5	2406	6	2407	7	2408	8	2409
9	2410	10	2411	11	2412	12	2413
13	2414	14	2415	15	2416	16	2417
17	2418	18	2419	19	2420	20	2421
21	2422	22	2423	23	2424	24	2425
25	2426	26	2427	27	2428	28	2429
29	2430	30	2431	31	2432	32	2433
33	2434	34	2435	35	2436	36	2437
37	2438	38	2439	39	2440	40	2441
41	2442	42	2443	43	2444	44	2445
45	2446	46	2447	47	2448	48	2449
49	2450	50	2451	51	2452	52	2453
53	2454	54	2455	55	2456	56	2457
57	2458	58	2459	59	2460	60	2461
61	2462	62	2463	63	2464	64	2465
65	2466	66	2467	67	2468	68	2469
69	2470	70	2471	71	2472	72	2473
73	2474	74	2475	75	2476	76	2477
77	2478	78	2479	79	2480	-	-

2.8. Test Equipment

2.8.1. For conducted emissions test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	832354	June 25,16	1 Year
Artificial Mains Networ	Rohde & Schwarz	ENV216	101260	June 25,16	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101100	June 25,16	1 Year
RF Cable	Fujikura	3D-2W	844 Chamber No.1	June 25,16	1 Year

2.8.2. For radiated emission test(9 kHz-30MHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESCI	100435	June 25,16	1 Year
Loop Antenna	ETS-LINDGREN	6502	00071730	June,29,15	3 Year
RF Cable	MIYAZAKI	5D-2W	966 Chamber No.1	June 25,16	1 Year

2.8.3. For radiated emissions test (30-1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESVS10	100004	June 25,16	1 Year
Spectrum Analyzer	Agilent	E4411B	MY50140697	June 25,16	1 Year
Bilog Antenna	Teseq	CBL 6111D	27090	June 28,15	3 Year
Signal Amplifier	Agilent	310N	187037	June 25,16	1 Year
RF Cable	MIYAZAKI	5D-2W	966 Chamber No.1	June 25,16	1 Year

2.8.4. For radio & radiated emissions test (above 1GHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA 9120 D	BBHA9120D1002	June 25,16	1 Year
Board-Band Horn Antenna	SCHWARZB ECK	BBHA 9170	9170-497	June 28,15	3 Year
Signal Amplifier	SCHWARZB ECK	BBV9718	9718-212	June 25,16	1 Year
Spectrum Analyzer	Agilent	E4408B	MY44211139	June 25,16	1 Year
Spectrum Analyzer	Rohde &Schwarz	FSV	103173	June 25,16	1 Year
RF Cable	Hubersuhner	RG 214/U	513423	June 25,16	1 Year

3. MAXIMUM PEAK OUTPUT POWER

3.1. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2. Test Procedure


The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable.

3.3. Test Result


EUT: MAGNIFI ONE SYSTEM					
M/N: MAGNIFI ONE X SUBWOOFER					
Test date: 2016-12-13		Test site: RF site		Tested by: Tony Tang	
Mode	Freq (MHz)	Result (dBm)	Limit		Margin (dB)
			dBm	W	
GFSK	2402	0.038	30.00	1	29.962
	2441	0.236	30.00	1	29.764
	2480	0.533	30.00	1	29.467
8-DPSK	2402	-0.417	21.00	0.125	21.417
	2441	0.034	21.00	0.125	20.966
	2480	0.056	21.00	0.125	20.944
Conclusion: PASS					

3.4. Test Data


GFSK 2402 MHz




GFSK 2441 MHz




GFSK 2480 MHz




8-DPSK 2402 MHz



8-DPSK 2441 MHz



8-DPSK 2480 MHz



4. 20 DB BANDWIDTH

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2. Test Procedure


The transmitter output (antenna port) was connected to the spectrum analyzer. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result


EUT: MAGNIFI ONE SYSTEM				
M/N: MAGNIFI ONE X SUBWOOFER				
Test date: 2016-12-13		Test site: RF site		Tested by: Tony Tang
Mode	Freq (MHz)	20dB Bandwidth (MHz)	Limit (kHz)	Conclusion
GFSK	2402	0.835	/	PASS
	2441	0.834	/	PASS
	2480	0.831	/	PASS
8-DPSK	2402	1.213	/	PASS
	2441	1.212	/	PASS
	2480	1.217	/	PASS

4.4. Test Data


GFSK 2402MHz




GFSK 2441MHz




GFSK 2480MHz




8-DPSK 2402MHz



8-DPSK 2441MHz



8-DPSK 2480MHz



5. CARRIER FREQUENCY SEPARATION

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

5.2. Test Procedure


The transmitter output (antenna port) was connected to the spectrum analyzer. The carrier frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW.

5.3. Test Result


EUT: MAGNIFI ONE SYSTEM				
M/N: MAGNIFI ONE X SUBWOOFER				
Test date: 2016-12-13			Test site: RF site	Tested by: Tony Tang
Mode	Channel	Channel separation (MHz)	Limit	Conclusion
GFSK	Low CH	1.000	0.835 MHz	PASS
	Mid CH	1.000	0.834 MHz	PASS
	High CH	1.000	0.831 MHz	PASS
8-DPSK	Low CH	1.000	> 2/3 of the 20dB Bandwidth or 25[kHz](whichever is greater)	PASS
	Mid CH	1.000		PASS
	High CH	1.000		PASS


5.4. Test Data

GFSK
Low Channel




Mid Channel







8-DPSK
Low Channel



Mid Channel





6. NUMBER OF HOPPING CHANNEL

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

6.2. Test Procedure




The transmitter output (antenna port) was connected to the spectrum analyzer. The number of hopping channel was measured by spectrum analyzer with 300kHz RBW and 300kHz VBW.

6.3. Test Result




EUT: MAGNIFI ONE SYSTEM			
M/N: MAGNIFI ONE X SUBWOOFER			
Test date: 2016-12-13		Test site: RF site	Tested by: Tony.Tang
Mode	Number of hopping channel	Limit	Conclusion
GFSK	79	>15	PASS
8-DPSK	79	>15	PASS

6.4. Test Data

GFSK



8-DPSK



7. DWELL TIME

7.1. Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.



7.2. Test Procedure

1. The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable.
2. Set the EUT to proper test mode with relative test software and hardware.
3. Spectrum analyzer setting: Centered Frequency = measured channel, RBW = 1MHz, VBW= 1MHz, Frequency Span = 0 Hz.
4. Set sweep time properly to capture the entire dwell time per hopping channel.
5. Set detector type to Peak and trace mode to Max Hold and make the measurement.
6. Repeat step 3-5 until all channels measured were complete.



7.3. Test Result

EUT: MAGNIFI ONE SYSTEM			
M/N: MAGNIFI ONE X SUBWOOFER			
Test date: 2016-12-13		Test site: RF site	Tested by: Tony Tang
Mode	Dwell time (ms)	Limit	Conclusion
GFSK DH1	148.52	<400ms	PASS
GFSK DH3	273.34	<400ms	PASS
GFSK DH5	318.02	<400ms	PASS
8-DPSK 3DH1	145.36	<400ms	PASS
8-DPSK 3DH3	270.18	<400ms	PASS
8-DPSK 3DH5	318.02	<400ms	PASS



7.4. Test Data





GFSK DH3 : 25hop/5s * 0.4 * 79 * 1.73ms= 273.34





GSFK DH5 : 17hop/5s * 0.4 * 79 *2.96ms = 318.02





8-DPSK 3DH1 : 50hop/5s * 0.4 * 79 * 0.46ms = 145.36



8-DPSK 3DH3 : 25hop/5s * 0.4 * 79 * 1.71ms= 270.18



8-DPSK 3DH5 : 17hop/5s * 0.4 * 79 *2.96ms = 318.02



8. RADIATED EMISSIONS

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

15.209 Limit


FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Remark : (1) Emission level dBμV = 20 log Emission level μV/m

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

8.2. Block Diagram of Test setup



8.3. Test Procedure

EUT was placed on a turn table, which is 0.8 meter high above ground for 9kHz~1000MHz test, and which is 1.5 meter high above ground for above 1GHz test. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

The test frequency analyzer system was set to Peak Detect (300Hz RBW in 9kHz to 150kHz and 10kHz RBW in 150kHz to 30MHz) Function and Specified Bandwidth with Maximum Hold Mode.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 1MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

PEAK detector, 1MHz/1MHz for PAEK measurement,

PEAK detector, 1MHz/10Hz for Average measurement

The frequency range from 30MHz to 10th harmonic (25GHz) are checked.

8.4. Test Result

PASS.

All the emissions from 30MHz to 25 GHz were comply with 15.209 limits.

Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

2、 The frequency 2402MHz 、2441MHz and 2480MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.


8.5. Test Data

9 kHz – 30 MHz

Pass


Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

30 MHz – 1000 MHz




Site no. : 966 1# chamber Data no. : 307
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	39.70	12.90	0.81	17.53	31.24	40.00	8.76	QP
2	93.05	8.59	1.27	16.00	25.86	43.50	17.64	QP
3	144.46	11.26	1.54	17.06	29.86	43.50	13.64	QP
4	396.66	15.91	2.63	4.89	23.43	46.00	22.57	QP
5	542.16	19.46	3.24	2.71	25.41	46.00	20.59	QP
6	563.50	19.67	3.28	4.19	27.14	46.00	18.86	QP




Site no. : 966 1# chamber Data no. : 308
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	93.05	8.59	1.27	14.01	23.87	43.50	19.63	QP
2	115.36	10.93	1.46	11.10	23.49	43.50	20.01	QP
3	144.46	11.26	1.54	19.69	32.49	43.50	11.01	QP
4	274.44	12.39	2.22	9.00	23.61	46.00	22.39	QP
5	325.85	13.74	2.43	9.83	26.00	46.00	20.00	QP
6	406.36	16.20	2.64	8.84	27.68	46.00	18.32	QP




Site no. : 966 1# chamber
 Dis. / Ant. : 3m 27137
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2441MHz
 Data no. : 309
 Ant. pol. : HORIZONTAL

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	93.05	8.59	1.27	14.48	24.34	43.50	19.16	QP
2	144.46	11.26	1.54	19.95	32.75	43.50	10.75	QP
3	313.24	13.31	2.44	9.70	25.45	46.00	20.55	QP
4	393.75	15.78	2.58	8.28	26.64	46.00	19.36	QP
5	406.36	16.20	2.64	7.10	25.94	46.00	20.06	QP
6	563.50	19.67	3.28	0.67	23.62	46.00	22.38	QP




Site no. : 966 1# chamber Data no. : 310
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2441MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	39.70	12.90	0.81	16.77	30.48	40.00	9.52	QP
2	107.60	10.24	1.39	12.84	24.47	43.50	19.03	QP
3	144.46	11.26	1.54	10.95	23.75	43.50	19.75	QP
4	542.16	19.46	3.24	2.67	25.37	46.00	20.63	QP
5	563.50	19.67	3.28	2.62	25.57	46.00	20.43	QP
6	587.75	19.44	3.40	0.69	23.53	46.00	22.47	QP




Site no. : 966 1# chamber Data no. : 311
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6'; Humi:56%; Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	34.85	15.55	0.72	14.96	31.23	40.00	8.77	QP
2	93.05	8.59	1.27	14.72	24.58	43.50	18.92	QP
3	144.46	11.26	1.54	17.11	29.91	43.50	13.59	QP
4	396.66	15.91	2.63	5.79	24.33	46.00	21.67	QP
5	542.16	19.46	3.24	4.30	27.00	46.00	19.00	QP
6	563.50	19.67	3.28	3.35	26.30	46.00	19.70	QP




Site no. : 966 1# chamber Data no. : 312
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	93.05	8.59	1.27	11.85	21.71	43.50	21.79	QP
2	119.24	11.11	1.42	9.31	21.84	43.50	21.66	QP
3	144.46	11.26	1.54	18.79	31.59	43.50	11.91	QP
4	338.46	14.10	2.50	7.25	23.85	46.00	22.15	QP
5	406.36	16.20	2.64	6.02	24.86	46.00	21.14	QP
6	563.50	19.67	3.28	1.68	24.63	46.00	21.37	QP




Site no. : 966 1# chamber Data no. : 313
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2402MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	144.46	11.26	1.54	18.21	31.01	43.50	12.49	QP
2	313.24	13.31	2.44	11.33	27.08	46.00	18.92	QP
3	393.75	15.78	2.58	9.24	27.60	46.00	18.40	QP
4	406.36	16.20	2.64	9.19	28.03	46.00	17.97	QP
5	468.44	17.14	3.09	3.91	24.14	46.00	21.86	QP
6	564.47	19.66	3.30	0.75	23.71	46.00	22.29	QP




Site no. : 966 1# chamber Data no. : 314
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2402MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	37.76	14.05	0.79	16.84	31.68	40.00	8.32	QP
2	107.60	10.24	1.39	11.90	23.53	43.50	19.97	QP
3	144.46	11.26	1.54	12.91	25.71	43.50	17.79	QP
4	542.16	19.46	3.24	2.33	25.03	46.00	20.97	QP
5	563.50	19.67	3.28	5.08	28.03	46.00	17.97	QP
6	587.75	19.44	3.40	3.58	26.42	46.00	19.58	QP




Site no. : 966 1# chamber Data no. : 315
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2441MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	39.70	12.90	0.81	16.32	30.03	40.00	9.97	QP
2	109.54	10.44	1.40	12.33	24.17	43.50	19.33	QP
3	144.46	11.26	1.54	10.46	23.26	43.50	20.24	QP
4	542.16	19.46	3.24	2.17	24.87	46.00	21.13	QP
5	563.50	19.67	3.28	5.38	28.33	46.00	17.67	QP
6	587.75	19.44	3.40	3.51	26.35	46.00	19.65	QP




Site no. : 966 1# chamber Data no. : 316
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2441MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	93.05	8.59	1.27	12.09	21.95	43.50	21.55	QP
2	144.46	11.26	1.54	19.17	31.97	43.50	11.53	QP
3	313.24	13.31	2.44	10.03	25.78	46.00	20.22	QP
4	406.36	16.20	2.64	8.20	27.04	46.00	18.96	QP
5	578.05	19.52	3.32	0.16	23.00	46.00	23.00	QP
6	612.00	19.91	3.33	0.64	23.88	46.00	22.12	QP



Site no. : 966 1# chamber Data no. : 317
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2480MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	93.05	8.59	1.27	13.33	23.19	43.50	20.31	QP
2	144.46	11.26	1.54	19.17	31.97	43.50	11.53	QP
3	260.86	12.96	2.22	5.30	20.48	46.00	25.52	QP
4	313.24	13.31	2.44	9.04	24.79	46.00	21.21	QP
5	406.36	16.20	2.64	8.05	26.89	46.00	19.11	QP
6	445.16	16.36	2.92	5.70	24.98	46.00	21.02	QP



Site no. : 966 1# chamber Data no. : 318
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6°;Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2480MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	39.70	12.90	0.81	18.29	32.00	40.00	8.00	QP
2	93.05	8.59	1.27	16.33	26.19	43.50	17.31	QP
3	119.24	11.11	1.42	12.13	24.66	43.50	18.84	QP
4	515.00	17.95	3.17	4.40	25.52	46.00	20.48	QP
5	563.50	19.67	3.28	4.36	27.31	46.00	18.69	QP
6	612.00	19.91	3.33	2.76	26.00	46.00	20.00	QP

Above 1GHz

Site no. : 966 1# chamber Data no. : 279
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.61	6.62	34.64	95.82	95.41	74.00	-21.41	Peak
2	4026.00	29.71	10.86	36.28	36.59	40.88	74.00	33.12	Peak
3	4804.00	31.25	11.77	35.64	38.64	46.02	74.00	27.98	Peak
4	7206.00	36.52	11.54	33.95	28.77	42.88	74.00	31.12	Peak
5	8684.00	37.32	11.45	33.66	28.43	43.54	74.00	30.46	Peak
6	11200.00	39.39	11.14	33.24	25.32	42.61	74.00	31.39	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 966 1# chamber Data no. : 280
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.61	6.62	34.64	94.01	93.60	74.00	-19.60	Peak
2	4804.00	31.25	11.77	35.64	36.73	44.11	74.00	29.89	Peak
3	7206.00	36.52	11.54	33.95	31.61	45.72	74.00	28.28	Peak
4	8650.00	37.27	11.45	33.68	27.13	42.17	74.00	31.83	Peak
5	11234.00	39.37	11.12	33.25	25.31	42.55	74.00	31.45	Peak
6	13461.00	39.99	11.50	32.71	25.87	44.65	74.00	29.35	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 966 1# chamber
 Dis. / Ant. : 3m ANT 1-18G
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2441MHz

Data no. : 281
 Ant. pol. : VERTICAL

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.60	6.67	34.85	91.29	90.71	74.00	-16.71	Peak
2	4882.00	31.37	12.07	35.76	39.27	46.95	74.00	27.05	Peak
3	7323.00	36.55	11.57	34.14	31.40	45.38	74.00	28.62	Peak
4	8514.00	36.96	11.45	34.07	29.45	43.79	74.00	30.21	Peak
5	10180.00	38.42	11.49	34.53	26.44	41.82	74.00	32.18	Peak
6	13376.00	39.78	11.48	32.91	26.78	45.13	74.00	28.87	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 966 1# chamber
 Dis. / Ant. : 3m ANT 1-18G
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2441MHz

Data no. : 282
 Ant. pol. : HORIZONTAL

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.60	6.67	34.85	89.29	88.71	74.00	-14.71	Peak
2	4882.00	31.37	12.07	35.76	41.27	48.95	74.00	25.05	Peak
3	7323.00	36.55	11.57	34.14	32.40	46.38	74.00	27.62	Peak
4	8616.00	37.22	11.45	33.77	29.77	44.67	74.00	29.33	Peak
5	10180.00	38.42	11.49	34.53	28.44	43.82	74.00	30.18	Peak
6	10826.00	39.33	11.30	34.00	27.13	43.76	74.00	30.24	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : site Data no. : 283
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	35.11	98.28	97.46	74.00	-23.46	Peak
2	4960.00	31.49	12.44	36.01	38.81	46.73	74.00	27.27	Peak
3	7440.00	36.54	11.61	34.22	31.78	45.71	74.00	28.29	Peak
4	8684.00	37.32	11.45	33.66	28.68	43.79	74.00	30.21	Peak
5	10690.00	39.18	11.30	34.22	25.84	42.10	74.00	31.90	Peak
6	14260.00	41.68	10.92	33.42	24.76	43.94	74.00	30.06	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 966 1# chamber Data no. : 284
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	35.11	100.83	100.01	74.00	-26.01	Peak
2	4960.00	31.49	12.44	36.01	35.38	43.30	74.00	30.70	Peak
3	7440.00	36.54	11.61	34.22	29.64	43.57	74.00	30.43	Peak
4	8905.00	37.45	11.46	34.37	26.81	41.35	74.00	32.65	Peak
5	11285.00	39.33	11.08	33.32	24.66	41.75	74.00	32.25	Peak
6	14379.00	41.77	10.92	33.39	24.61	43.91	74.00	30.09	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 966 1# chamber Data no. : 285
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.61	6.62	34.64	87.02	86.61	74.00	-12.61	Peak
2	4804.00	31.25	11.77	35.64	36.88	44.26	74.00	29.74	Peak
3	7206.00	36.52	11.54	33.95	26.18	40.29	74.00	33.71	Peak
4	8684.00	37.32	11.45	33.66	27.15	42.26	74.00	31.74	Peak
5	10656.00	39.15	11.30	34.31	26.18	42.32	74.00	31.68	Peak
6	11285.00	39.33	11.08	33.32	25.70	42.79	74.00	31.21	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 966 1# chamber Data no. : 286
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.61	6.62	34.64	90.45	90.04	74.00	-16.04	Peak
2	4804.00	31.25	11.77	35.64	32.16	39.54	74.00	34.46	Peak
3	7206.00	36.52	11.54	33.95	28.12	42.23	74.00	31.77	Peak
4	8684.00	37.32	11.45	33.66	28.19	43.30	74.00	30.70	Peak
5	11574.00	39.12	10.99	33.27	24.38	41.22	74.00	32.78	Peak
6	13546.00	40.21	11.44	32.61	25.68	44.72	74.00	29.28	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 966 1# chamber Data no. : 287
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.60	6.67	34.85	87.11	86.53	74.00	-12.53	Peak
2	4882.00	31.37	12.07	35.76	36.19	43.87	74.00	30.13	Peak
3	7323.00	36.55	11.57	34.14	27.70	41.68	74.00	32.32	Peak
4	9245.00	37.83	11.58	34.37	27.32	42.36	74.00	31.64	Peak
5	11200.00	39.39	11.14	33.24	25.27	42.56	74.00	31.44	Peak
6	13954.00	41.35	10.96	32.99	25.60	44.92	74.00	29.08	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 966 1# chamber Data no. : 288
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.60	6.67	34.85	90.39	89.81	74.00	-15.81	Peak
2	4882.00	31.37	12.07	35.76	35.78	43.46	74.00	30.54	Peak
3	7323.00	36.55	11.57	34.14	28.76	42.74	74.00	31.26	Peak
4	9194.00	37.75	11.55	34.18	28.04	43.16	74.00	30.84	Peak
5	13070.00	39.05	11.44	32.84	26.22	43.87	74.00	30.13	Peak
6	14345.00	41.76	10.92	33.39	28.21	47.50	74.00	26.50	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 966 1# chamber
 Dis. / Ant. : 3m ANT 1-18G
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2480MHz

Data no. : 289

Ant. pol. : VERTICAL

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	35.11	96.75	95.93	74.00	-21.93	Peak
2	4960.00	31.49	12.44	36.01	35.18	43.10	74.00	30.90	Peak
3	7440.00	36.54	11.61	34.22	29.99	43.92	74.00	30.08	Peak
4	8735.00	37.40	11.45	33.76	28.87	43.96	74.00	30.04	Peak
5	10554.00	39.04	11.31	34.45	27.89	43.79	74.00	30.21	Peak
6	13070.00	39.05	11.44	32.84	25.62	43.27	74.00	30.73	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Site no. : 966 1# chamber
 Dis. / Ant. : 3m ANT 1-18G
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2480MHz

Data no. : 290

Ant. pol. : HORIZONTAL

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	35.11	96.34	95.52	74.00	-21.52	Peak
2	4960.00	31.49	12.44	36.01	35.03	42.95	74.00	31.05	Peak
3	7440.00	36.54	11.61	34.22	29.06	42.99	74.00	31.01	Peak
4	8684.00	37.32	11.45	33.66	28.76	43.87	74.00	30.13	Peak
5	11200.00	39.39	11.14	33.24	25.48	42.77	74.00	31.23	Peak
6	14056.00	41.51	10.90	33.06	25.63	44.98	74.00	29.02	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

9. BAND EDGE COMPLIANCE

9.1. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

9.2. Block Diagram of Test setup



9.3. Test Procedure

EUT was placed on a turn table, which is 1.5 m high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of emissions

Peak : RBW = 1MHz, VBW = 1MHz, Detector=PEAK detector, Sweep time = auto.

AV : RBW = 1MHz, VBW = 10Hz, Detector=PEAK detector, Sweep time = auto.


9.4. Test Result


Pass

Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

2、 The frequency 2402MHz 、2441MHz and 2480MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

9.5. Test Data






Site no. : 966 1# chamber Data no. : 300
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2402MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2354.01	27.70	6.58	34.57	37.12	36.83	74.00	37.17	Peak
2	2390.00	27.64	6.62	34.62	35.97	35.61	74.00	38.39	Peak
3	2400.00	27.61	6.62	34.64	50.60	50.19	54.00	3.81	Average
4	2400.00	27.61	6.62	34.64	56.60	56.19	74.00	17.81	Peak
5	2402.08	27.61	6.62	34.64	100.34	99.93	74.00	-25.93	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 301
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2480MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.13	27.58	6.71	35.11	104.03	103.21	74.00	-29.21	Peak
2	2483.50	27.58	6.71	35.11	48.36	47.54	54.00	6.46	Average
3	2483.50	27.58	6.71	35.11	54.36	53.54	74.00	20.46	Peak
4	2484.50	27.58	6.71	35.11	44.91	44.09	74.00	29.91	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 302
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2480MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	35.11	102.12	101.30	74.00	-27.30	Peak
2	2483.50	27.58	6.71	35.11	49.83	49.01	54.00	4.99	Average
3	2483.50	27.58	6.71	35.11	55.83	55.01	74.00	18.99	Peak
4	2484.45	27.58	6.71	35.11	46.87	46.05	74.00	27.95	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 303
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2402MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2354.12	27.70	6.58	34.57	37.85	37.56	74.00	36.44	Peak
2	2389.98	27.64	6.62	34.62	31.86	31.50	74.00	42.50	Peak
3	2399.99	27.61	6.62	34.64	49.43	49.02	54.00	4.98	Average
4	2399.99	27.61	6.62	34.64	58.43	58.02	74.00	15.98	Peak
5	2402.30	27.61	6.62	34.64	99.02	98.61	74.00	-24.61	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 304
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6°;Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2402MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2353.79	27.70	6.58	34.57	38.29	38.00	74.00	36.00	Peak
2	2389.98	27.64	6.62	34.62	32.98	32.62	74.00	41.38	Peak
3	2399.99	27.61	6.62	34.64	50.48	50.07	54.00	3.93	Average
4	2399.99	27.61	6.62	34.64	55.48	55.07	74.00	18.93	Peak
5	2402.08	27.61	6.62	34.64	98.01	97.60	74.00	-23.60	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 305
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6°;Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2480MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.13	27.58	6.71	35.11	101.28	100.46	74.00	-26.46	Peak
2	2483.50	27.58	6.71	35.11	50.50	49.68	54.00	4.32	Average
3	2483.50	27.58	6.71	35.11	57.50	56.68	74.00	17.32	Peak
4	2484.30	27.58	6.71	35.11	50.25	49.43	74.00	24.57	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 966 1# chamber
 Dis. / Ant. : 3m ANT 1-18G
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2480MHz (No Hopping)

Data no. : 306
Ant. pol. : VERTICAL


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	35.11	103.46	102.64	74.00	-28.64	Peak
2	2483.50	27.58	6.71	35.11	51.10	50.28	54.00	3.72	Average
3	2483.50	27.58	6.71	35.11	58.10	57.28	74.00	16.72	Peak
4	2484.30	27.58	6.71	35.11	50.88	50.06	74.00	23.94	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2369.08	27.67	6.60	34.59	49.57	49.25	74.00	24.75	Peak
2	2390.00	27.64	6.62	34.62	42.30	41.94	74.00	32.06	Peak
3	2400.00	27.61	6.62	34.64	51.19	50.78	54.00	3.22	Average
4	2400.00	27.61	6.62	34.64	60.19	59.78	74.00	14.22	Peak
5	2406.15	27.61	6.64	34.64	102.00	101.61	74.00	-27.61	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2381.18	27.64	6.60	34.62	47.25	46.87	74.00	27.13	Peak
2	2389.98	27.64	6.62	34.62	42.19	41.83	74.00	32.17	Peak
3	2399.99	27.61	6.62	34.64	44.97	44.56	74.00	29.44	Peak
4	2403.18	27.61	6.64	34.64	99.28	98.89	74.00	-24.89	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 293
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2480MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	35.11	102.00	101.18	74.00	-27.18	Peak
2	2483.50	27.58	6.71	35.11	50.70	49.88	54.00	4.12	Average
3	2483.50	27.58	6.71	35.11	57.70	56.88	74.00	17.12	Peak
4	2485.95	27.58	6.71	35.11	46.44	45.62	74.00	28.38	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 294
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : GFSK TX 2480MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2478.13	27.58	6.71	35.11	105.12	104.30	74.00	-30.30	Peak
2	2483.50	27.58	6.71	35.11	49.69	48.87	54.00	5.13	Average
3	2483.50	27.58	6.71	35.11	57.69	56.87	74.00	17.13	Peak
4	2485.10	27.58	6.71	35.11	52.56	51.74	74.00	22.26	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 295
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2402MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2369.08	27.67	6.60	34.59	46.82	46.50	74.00	27.50	Peak
2	2389.98	27.64	6.62	34.62	41.86	41.50	74.00	32.50	Peak
3	2399.99	27.61	6.62	34.64	47.62	47.21	54.00	6.79	Average
4	2399.99	27.61	6.62	34.64	52.62	52.21	74.00	21.79	Peak
5	2408.02	27.61	6.64	34.64	100.88	100.49	74.00	-26.49	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 296
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2402MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2378.98	27.64	6.60	34.59	46.45	46.10	74.00	27.90	Peak
2	2390.00	27.64	6.62	34.62	44.71	44.35	74.00	29.65	Peak
3	2400.00	27.61	6.62	34.64	48.37	47.96	54.00	6.04	Average
4	2400.00	27.61	6.62	34.64	52.37	51.96	74.00	22.04	Peak
5	2408.90	27.60	6.64	34.64	96.74	96.34	74.00	-22.34	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 297
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2480MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.00	27.58	6.71	35.11	101.01	100.19	74.00	-26.19	Peak
2	2483.50	27.58	6.71	35.11	49.48	48.66	54.00	5.34	Average
3	2483.50	27.58	6.71	35.11	57.48	56.66	74.00	17.34	Peak
4	2484.30	27.58	6.71	35.11	49.89	49.07	74.00	24.93	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 298
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : 8-DPSK TX 2480MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2479.13	27.58	6.71	35.11	102.56	101.74	74.00	-27.74	Peak
2	2483.50	27.58	6.71	35.11	48.03	47.21	54.00	6.79	Average
3	2483.50	27.58	6.71	35.11	54.03	53.21	74.00	20.79	Peak
4	2483.63	27.58	6.71	35.11	52.11	51.29	74.00	22.71	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

10. POWER LINE CONDUCTED EMISSIONS

10.1. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

10.2. Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT power mains through a line impedance stabilization network (L.I.S.N. 1#). Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.


The bandwidth of test receiver (R & S ESHS30) is set at 10kHz.

The frequency range from 150kHz to 30MHz is checked.

10.3. Test Result


PASS. (All emissions not reported below are too low against the prescribed limits.)

10.4. Test data




Site no : 844 Shield Room Data no. : 463
Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
Limit : FCC PART 15B QP
Engineer : Bible
EUT : MAGNIFI ONE SYSTEM
Power : AC 240V/50Hz
M/N : MAGNIFI ONE X SUBWOOFER
Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15	9.46	9.81	16.63	35.90	55.91	20.01	Average
2	0.15	9.46	9.81	24.63	43.90	65.91	22.01	QP
3	0.17	9.53	9.80	12.98	32.31	54.77	22.46	Average
4	0.17	9.53	9.80	21.98	41.31	64.77	23.46	QP
5	0.39	9.59	9.82	4.96	24.37	48.12	23.75	Average
6	0.39	9.59	9.82	13.96	33.37	58.12	24.75	QP




Site no : 844 Shield Room Data no. : 465
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : Bible
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 240V/50Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV)	Limits (dBUV)	Margin (dB)	Remark
1	0.15	9.61	9.81	16.84	36.26	55.91	19.65	Average
2	0.15	9.61	9.81	25.84	45.26	65.91	20.65	QP
3	0.19	9.61	9.80	15.54	34.95	53.98	19.03	Average
4	0.19	9.61	9.80	24.54	43.95	63.98	20.03	QP
5	0.25	9.61	9.82	11.26	30.69	51.86	21.17	Average
6	0.25	9.61	9.82	19.26	38.69	61.86	23.17	QP



Site no : 844 Shield Room Data no. : 467
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : Bible
 EUT : MAGNIFI ONE SYSTEM
 Power : AC 120V/60Hz
 M/N : MAGNIFI ONE X SUBWOOFER
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.16	9.61	9.81	14.65	34.07	55.65	21.58	Average
2	0.16	9.61	9.81	24.65	44.07	65.65	21.58	QP
3	0.20	9.61	9.80	11.82	31.23	53.62	22.39	Average
4	0.20	9.61	9.80	19.82	39.23	63.62	24.39	QP
5	0.25	9.61	9.82	6.65	26.08	51.86	25.78	Average
6	0.25	9.61	9.82	14.65	34.08	61.86	27.78	QP



	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.16	9.48	9.81	15.98	35.27	55.65	20.38	Average
2	0.16	9.48	9.81	24.98	44.27	65.65	21.38	QP
3	0.18	9.56	9.80	11.13	30.49	54.37	23.88	Average
4	0.18	9.56	9.80	24.13	43.49	64.37	20.88	QP
5	0.27	9.60	9.83	4.84	24.27	51.07	26.80	Average
6	0.27	9.60	9.83	14.84	34.27	61.07	26.80	QP

11. ANTENNA REQUIREMENTS

11.1. Limit


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2. Result

The antennas used for this product are internal Antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 0dBi.

12. TEST SETUP PHOTO


Conducted Test



Radiated Test (30-1000 MHz)



Radiated Test (1000-25000 MHz)



13. PHOTOS OF EUT


External Photos
M/N: MAGNIFI ONE X SUBWOOFER




External Photos
M/N: MAGNIFI ONE X SUBWOOFER





External Photos
M/N: MAGNIFI ONE X SUBWOOFER





Internal Photos
M/N: MAGNIFI ONE X SUBWOOFER



Internal Photos
M/N: MAGNIFI ONE X SUBWOOFER



Internal Photos
M/N: MAGNIFI ONE X SUBWOOFER



Bluetooth
Antenna

Power Cord

