

TEST REPORT

Applicant	DEI Sales Inc., dba Polk Audio
Address	5541 Fermi Court Carlsbad CA 92008 United States Of America

Manufacturer or Supplier	DEI Sales Inc., dba Polk Audio
Address	5541 Fermi Court Carlsbad CA 92008 United States Of America
Product	Magnifi Mini AX Ultra-Compact Sound Bar System
Brand Name	polk
Model	MAGNIFI MINI AX SOUND BAR
Additional Model & Model Difference	N/A
Date of tests	Apr. 30, 2021 ~ Oct. 11, 2021

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 15, Subpart C, Section 15.247**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Lucas Chen Project Engineer / EMC Department	Approved by Glyn He Assistant Manager / EMC Department
	 Date: Dec. 09, 2021

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <https://www.cps.bureauveritas.com/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS.....	5
2 MEASUREMENT UNCERTAINTY	5
3 GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF EUT	6
3.2 DESCRIPTION OF TEST MODES	8
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST	9
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	9
3.3 DUTY CYCLE OF TEST SIGNAL	11
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS	12
3.5 DESCRIPTION OF SUPPORT UNITS	12
4 TEST TYPES AND RESULTS.....	13
4.1. CONDUCTED EMISSION MEASUREMENT	13
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	13
4.1.2 TEST INSTRUMENTS.....	13
4.1.3 TEST PROCEDURES	14
4.1.4 DEVIATION FROM TEST STANDARD	14
4.1.5 TEST SETUP.....	15
4.1.6 EUT OPERATING CONDITIONS	15
4.1.7 TEST RESULTS	16
4.2. RADIATED EMISSION MEASUREMENT	18
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	18
4.2.2 TEST INSTRUMENTS.....	19
4.2.3 TEST PROCEDURES	20
4.2.4 DEVIATION FROM TEST STANDARD	21
4.2.5 TEST SETUP.....	21
4.2.6 EUT OPERATING CONDITIONS	22
4.2.7 TEST RESULTS	23
4.3 6DB BANDWIDTH MEASUREMENT	37
4.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT	37
4.3.2 TEST INSTRUMENTS.....	37
4.3.3 TEST PROCEDURE.....	37
4.3.4 DEVIATION FROM TEST STANDARD	37
4.3.5 TEST SETUP.....	38
4.3.6 EUT OPERATING CONDITIONS	38

4.3.7	TEST RESULTS	39
4.4	CONDUCTED OUTPUT POWER.....	49
4.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	49
4.4.2	TEST SETUP.....	49
4.4.3	TEST INSTRUMENTS.....	49
4.4.4	TEST PROCEDURES	49
4.4.5	DEVIATION FROM TEST STANDARD	49
4.4.6	EUT OPERATING CONDITIONS	49
4.4.7	TEST RESULTS	50
4.5	POWER SPECTRAL DENSITY MEASUREMENT	54
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	54
4.5.2	TEST SETUP.....	54
4.5.3	TEST INSTRUMENTS.....	54
4.5.4	TEST PROCEDURE.....	54
4.5.5	DEVIATION FROM TEST STANDARD	54
4.5.6	EUT OPERATING CONDITION	55
4.5.7	TEST RESULTS	55
4.6	OUT OF BAND EMISSION MEASUREMENT	59
4.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT.....	59
4.6.2	TEST SETUP.....	59
4.6.3	TEST INSTRUMENTS.....	59
4.6.4	TEST PROCEDURE.....	59
4.6.5	DEVIATION FROM TEST STANDARD	60
4.6.6	EUT OPERATING CONDITION	60
4.6.7	TEST RESULTS	61
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	72
6	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	73



Test Report No.: RF2104WDG0365-3

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF2104WDG0365-3	Original release	Dec. 09, 2021

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is i-pex not a standard connector.

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	3.05dB
Radiated emissions	9KHz ~ 30MHz	2.16dB
	30MHz ~ 1GMHz	3.82dB
	1GHz ~ 18GHz	4.94dB
	18GHz ~ 40GHz	5.07dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Magnifi Mini AX Ultra-Compact Sound Bar System
BRAND	polk
MODEL NO.	MAGNIFI MINI AX SOUND BAR
ADDITIONAL NO.	N/A
FCC ID	WLQMINIAXSB
NOMINAL VOLTAGE	DC 15V from Adapter
MODULATION TECHNOLOGY	DSSS, OFDM
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
OPERATING FREQUENCY	2412MHz ~ 2462MHz for 11b/g/n(HT20) 2422MHz ~ 2452MHz for 11n(HT40)
PEAK OUTPUT POWER	139.959mW (Measured Max.)
ANTENNA TYPE	Chain 0: FPCB Antenna, with 3.4dBi gain Chain 1: FPCB Antenna, with 3.6dBi gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	Refer to user's manual

NOTES:

1. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.
2. Please refer to the EUT photo document (Reference No.: 2104WDG0365-1) for detailed product photo.
3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
4. The EUT was powered by the following adapter:

ADAPTER	
BRAND:	polk
MODEL:	S065-1A150400M2
INPUT:	AC 100-240V 50/60Hz 1.5A
OUTPUT:	DC 15V/4A 60W
AC LINE:	Unshielded, detachable, 1.5m
DC LINE:	Unshielded, Non-detachable, 1.5m

5. The working status of the two antennas is as follows.

MODULATION MODE	FUNCTION
802.11b	2 Chains (SISO)
802.11g	2 Chains (SISO)
802.11n (HT20)	2 Chains (MIMO)
802.11n (HT40)	2 Chains (MIMO)

* 802.11b/g provided a SISO function, the radiated emission above 1GHz and conducted emission test items are carried out on the maximum power “chain 1” antenna.

3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, power supply voltage range and antenna ports. The worst case was found when positioned on X axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	√	√	Adapter with WIFI function

Where **RE<1G**: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

RE≥1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

POWER LINE CONDUCTED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CONDITION
A	WIFI (2.4G) Link

RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1	DSSS	DBPSK	1.0

For the test results, only the worst case was shown in test report.

RADIATED EMISSION TEST (ABOVE 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
A	802.11n HT40	3 to 9	3, 6, 9	OFDM	BPSK	13.5

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
A	802.11n HT40	3 to 9	3, 6, 9	OFDM	BPSK	13.5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER(ADAPTER)	TESTED BY
RE<1G	25deg. C, 55%RH	DC 15V from Adapter	Jelly
RE≥1G	25deg. C, 55%RH	DC 15V from Adapter	Jelly
PLC	23deg. C, 56%RH	DC 15V from Adapter	Ming Bai
APCM	25deg. C, 58%RH	DC 15V from Adapter	Vincent


3.3 DUTY CYCLE OF TEST SIGNAL

802.11b: Duty cycle = $1.392/1.447 = 96.2\%$

802.11g: Duty cycle = $1.299/1.354 = 96.0\%$

802.11n (HT20): Duty cycle = $0.647/0.709 = 91.3\%$

802.11n (HT40): Duty cycle = 100%



3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 15.247 Meas Guidance v05r02

KDB 662911 D01 Multiple Transmitter Output v02r01

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as a dependent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Dummy Load	N/A	N/A	N/A	N/A
2	USB Driver	Kingston	DataTraveler	3RJD8-68DC4U-3VFUW	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	Optical Cable: Unshielded, detachable, 1.8m. HDMI Cable: Shielded, detachable, 200cm with two cores; AC Cable: Unshielded, detachable, 180cm
2	N/A

4 TEST TYPES AND RESULTS

4.1. CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTES:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Mar. 07,22
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	Mar. 07,22
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	Mar. 07,22
Voltage probe	SCHWARZBECK	TK 9421	TK 9421-176	Sep. 17,22
Test software	ADT	ADT_Conc_V7.3.7	N/A	N/A

- NOTES:**
1. The test was performed in shielded room 553.
 2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

4.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.


4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA: WIFI Link

PHASE	Line	6dB BANDWIDTH	9kHz
--------------	------	----------------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.66	37.61	19.12	47.27	28.78	66.00	56.00	-18.73	-27.22
2	0.17011	9.68	34.95	16.55	44.63	26.23	64.96	54.96	-20.33	-28.73
3	0.19275	9.70	32.68	15.21	42.38	24.91	63.92	53.92	-21.53	-29.00
4	0.58220	9.82	22.31	14.81	32.13	24.63	56.00	46.00	-23.87	-21.37
5	1.04349	9.81	4.28	-1.23	14.09	8.58	56.00	46.00	-41.91	-37.42
6	14.66025	10.07	13.35	6.44	23.42	16.51	60.00	50.00	-36.58	-33.49


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral	6dB BANDWIDTH	9kHz
-------	---------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.66	37.61	18.87	47.27	28.53	66.00	56.00	-18.73	-27.47
2	0.17025	9.68	35.05	16.74	44.73	26.42	64.95	54.95	-20.22	-28.53
3	0.19500	9.71	32.07	15.38	41.78	25.09	63.82	53.82	-22.04	-28.73
4	0.58875	9.84	23.86	16.49	33.70	26.33	56.00	46.00	-22.30	-19.67
5	2.22675	9.85	0.46	-3.46	10.31	6.39	56.00	46.00	-45.69	-39.61
6	14.52525	10.11	13.06	6.11	23.17	16.22	60.00	50.00	-36.83	-33.78

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2. RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTES:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Mar. 07,22
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	May 09, 22
Active Loop Antenna (9KHz -30MHz)	SCHWARZBECK	FMZB 1519B	1519B-045	May 29,22
Amplifier (9KHz -1GHz)	Burgeon	BPA-530	100210	Mar. 13,22
Bilog Antenna (20MHz -2GHz)	Teseq	CBL 6111D	30643	May 29,22
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 29,22
Horn Antenna (18GHz -40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170147	May 09, 22
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	May 22,22
Test Software	ADT	ADT_Radiated_V 7.6.15.9.2	N/A	N/A
Broadband Preamplifier (1GHz~18GHz)	SCHWARZBECK	BBV9718	305	May 08,22
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Mar. 13,22
Test Software	ADT	ADT_Radiated_V 7.6.15.9.2	N/A	N/A

NOTES:

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 749762.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters (above 1GHz) and 0.8 meters (below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. For below 1GHz was used bilog antenna, and above 1GHz was used horn antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.
- g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTES:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes, the worst-case test configuration was reported on the file test setup photo.

4.2.4 DEVIATION FROM TEST STANDARD


No deviation.

4.2.5 TEST SETUP

Below 30MHz test setup




Below 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

Above 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

- Placed the EUT on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:


802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	89.07	18.25 QP	43.50	-25.25	1.50 H	24	40.79	-22.54
2	140.37	21.03 QP	43.50	-22.47	1.50 H	87	39.19	-18.16
3	194.78	17.52 QP	43.50	-25.98	1.50 H	72	38.33	-20.81
4	389.09	29.40 QP	46.00	-16.60	1.50 H	116	43.54	-14.14
5	417.07	23.51 QP	46.00	-22.49	1.50 H	102	36.42	-12.91
6	561.63	19.11 QP	46.00	-26.89	1.50 H	58	27.69	-8.58

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value.




CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.00	31.72 QP	40.00	-8.28	1.50 V	265	44.72	-13.00
2	89.07	24.01 QP	43.50	-19.49	1.50 V	289	46.55	-22.54
3	129.49	22.48 QP	43.50	-21.02	1.50 V	301	41.83	-19.35
4	323.80	21.24 QP	46.00	-24.76	1.50 V	313	37.30	-16.06
5	389.09	22.81 QP	46.00	-23.19	1.50 V	324	36.95	-14.14
6	504.12	22.65 QP	46.00	-23.35	1.50 V	336	33.79	-11.14

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value.



ABOVE 1GHz DATA
802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	47.90 PK	74.00	-26.10	1.00 H	155	42.84	5.06
2	2390.00	35.26 AV	54.00	-18.74	1.00 H	155	30.20	5.06
3	*2412.00	101.17 PK			1.00 H	155	95.98	5.19
4	*2412.00	97.03 AV			1.00 H	155	91.84	5.19
5	4824.00	51.69 PK	74.00	-22.31	1.00 H	0	41.00	10.69
6	4824.00	40.74 AV	54.00	-13.26	1.00 H	0	30.05	10.69
7	#7236.00	56.14 PK	74.00	-17.86	1.00 H	0	39.19	16.95
8	#7236.00	44.89 AV	54.00	-9.11	1.00 H	0	27.94	16.95
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	49.57 PK	74.00	-24.43	1.00 V	177	44.51	5.06
2	2390.00	38.51 AV	54.00	-15.49	1.00 V	177	33.45	5.06
3	*2412.00	108.36 PK			1.00 V	177	103.17	5.19
4	*2412.00	103.62 AV			1.00 V	177	98.43	5.19
5	4824.00	52.29 PK	74.00	-21.71	1.00 V	0	41.60	10.69
6	4824.00	42.97 AV	54.00	-11.03	1.00 V	0	32.28	10.69
7	#7236.00	57.54 PK	74.00	-16.46	1.00 V	0	40.59	16.95
8	#7236.00	46.63 AV	54.00	-7.37	1.00 V	0	29.68	16.95

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	102.84 PK			1.00 H	103	97.52	5.32
2	*2437.00	98.54 AV			1.00 H	103	93.22	5.32
3	4874.00	50.26 PK	74.00	-23.74	1.00 H	0	39.36	10.90
4	4874.00	38.57 AV	54.00	-15.43	1.00 H	0	27.67	10.90
5	7311.00	53.37 PK	74.00	-20.63	1.00 H	0	36.21	17.16
6	7311.00	42.87 AV	54.00	-11.13	1.00 H	0	25.71	17.16
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	107.54 PK			1.00 V	20	102.22	5.32
2	*2437.00	102.26 AV			1.00 V	20	96.94	5.32
3	4874.00	52.26 PK	74.00	-21.74	1.00 V	0	41.36	10.90
4	4874.00	40.19 AV	54.00	-13.81	1.00 V	0	29.29	10.90
5	7311.00	54.51 PK	74.00	-19.49	1.00 V	0	37.35	17.16
6	7311.00	43.42 AV	54.00	-10.58	1.00 V	0	26.26	17.16

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	102.51 PK			1.00 H	84	97.06	5.45
2	*2462.00	98.54 AV			1.00 H	84	93.09	5.45
3	2483.50	48.67 PK	74.00	-25.33	1.00 H	84	43.10	5.57
4	2483.50	38.10 AV	54.00	-15.90	1.00 H	84	32.53	5.57
5	4924.00	54.43 PK	74.00	-19.57	1.00 H	0	43.34	11.09
6	4924.00	42.29 AV	54.00	-11.71	1.00 H	0	31.20	11.09
7	7386.00	57.69 PK	74.00	-16.31	1.00 H	0	40.33	17.36
8	7386.00	45.55 AV	54.00	-8.45	1.00 H	0	28.19	17.36
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	108.81 PK			1.00 V	123	103.36	5.45
2	*2462.00	104.27 AV			1.00 V	123	98.82	5.45
3	2483.50	50.67 PK	74.00	-23.33	1.00 V	123	45.10	5.57
4	2483.50	39.21 AV	54.00	-14.79	1.00 V	123	33.64	5.57
5	4924.00	56.51 PK	74.00	-17.49	1.00 V	0	45.42	11.09
6	4924.00	43.26 AV	54.00	-10.74	1.00 V	0	32.17	11.09
7	7386.00	58.51 PK	74.00	-15.49	1.00 V	0	41.15	17.36
8	7386.00	46.58 AV	54.00	-7.42	1.00 V	0	29.22	17.36

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. "*" : Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.29 PK	74.00	-17.71	1.00 H	135	51.23	5.06
2	2390.00	45.10 AV	54.00	-8.90	1.00 H	135	40.04	5.06
3	*2412.00	100.75 PK			1.00 H	135	95.56	5.19
4	*2412.00	95.68 AV			1.00 H	135	90.49	5.19
5	4824.00	53.84 PK	74.00	-20.16	1.00 H	0	43.15	10.69
6	4824.00	42.18 AV	54.00	-11.82	1.00 H	0	31.49	10.69
7	#7236.00	56.41 PK	74.00	-17.59	1.00 H	0	39.46	16.95
8	#7236.00	44.79 AV	54.00	-9.21	1.00 H	0	27.84	16.95
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.42 PK	74.00	-16.58	1.00 V	257	52.36	5.06
2	2390.00	45.51 AV	54.00	-8.49	1.00 V	257	40.45	5.06
3	*2412.00	104.69 PK			1.00 V	257	99.50	5.19
4	*2412.00	100.54 AV			1.00 V	257	95.35	5.19
5	4824.00	54.55 PK	74.00	-19.45	1.00 V	0	43.86	10.69
6	4824.00	43.69 AV	54.00	-10.31	1.00 V	0	33.00	10.69
7	#7236.00	56.69 PK	74.00	-17.31	1.00 V	0	39.74	16.95
8	#7236.00	45.89 AV	54.00	-8.11	1.00 V	0	28.94	16.95

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	99.26 PK			1.00 H	177	93.94	5.32
2	*2437.00	94.10 AV			1.00 H	177	88.78	5.32
3	4874.00	50.26 PK	74.00	-23.74	1.00 H	0	39.36	10.90
4	4874.00	39.84 AV	54.00	-14.16	1.00 H	0	28.94	10.90
5	7311.00	53.26 PK	74.00	-20.74	1.00 H	0	36.10	17.16
6	7311.00	44.17 AV	54.00	-9.83	1.00 H	0	27.01	17.16
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	104.01 PK			1.00 V	69	98.69	5.32
2	*2437.00	100.36 AV			1.00 V	69	95.04	5.32
3	4874.00	52.27 PK	74.00	-21.73	1.00 V	0	41.37	10.90
4	4874.00	40.03 AV	54.00	-13.97	1.00 V	0	29.13	10.90
5	7311.00	53.96 PK	74.00	-20.04	1.00 V	0	36.80	17.16
6	7311.00	45.51 AV	54.00	-8.49	1.00 V	0	28.35	17.16

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	99.54 PK			1.00 H	201	94.09	5.45
2	*2462.00	95.20 AV			1.00 H	201	89.75	5.45
3	2483.50	54.48 PK	74.00	-19.52	1.00 H	201	48.91	5.57
4	2483.50	42.29 AV	54.00	-11.71	1.00 H	201	36.72	5.57
5	4924.00	55.84 PK	74.00	-18.16	1.00 H	3	44.75	11.09
6	4924.00	41.29 AV	54.00	-12.71	1.00 H	3	30.20	11.09
7	7386.00	57.41 PK	74.00	-16.59	1.00 H	0	40.05	17.36
8	7386.00	45.54 AV	54.00	-8.46	1.00 H	0	28.18	17.36
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	103.78 PK			1.00 V	185	98.33	5.45
2	*2462.00	99.38 AV			1.00 V	185	93.93	5.45
3	2483.50	59.67 PK	74.00	-14.33	1.00 V	185	54.10	5.57
4	2483.50	46.40 AV	54.00	-7.60	1.00 V	185	40.83	5.57
5	4924.00	56.51 PK	74.00	-17.49	1.00 V	3	45.42	11.09
6	4924.00	42.29 AV	54.00	-11.71	1.00 V	3	31.20	11.09
7	7386.00	58.51 PK	74.00	-15.49	1.00 V	0	41.15	17.36
8	7386.00	46.69 AV	54.00	-7.31	1.00 V	0	29.33	17.36

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11n HT20

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.42 PK	74.00	-18.58	1.00 H	109	50.36	5.06
2	2390.00	44.37 AV	54.00	-9.63	1.00 H	109	39.31	5.06
3	*2412.00	102.98 PK			1.00 H	109	97.79	5.19
4	*2412.00	98.62 AV			1.00 H	109	93.43	5.19
5	4824.00	53.36 PK	74.00	-20.64	1.00 H	0	42.67	10.69
6	4824.00	42.07 AV	54.00	-11.93	1.00 H	0	31.38	10.69
7	#7236.00	55.76 PK	74.00	-18.24	1.00 H	0	38.81	16.95
8	#7236.00	43.03 AV	54.00	-10.97	1.00 H	0	26.08	16.95
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.62 PK	74.00	-16.38	1.00 V	221	52.56	5.06
2	2390.00	45.35 AV	54.00	-8.65	1.00 V	221	40.29	5.06
3	*2412.00	106.48 PK			1.00 V	221	101.29	5.19
4	*2412.00	102.57 AV			1.00 V	221	97.38	5.19
5	4824.00	54.25 PK	74.00	-19.75	1.00 V	0	43.56	10.69
6	4824.00	42.21 AV	54.00	-11.79	1.00 V	0	31.52	10.69
7	#7236.00	56.96 PK	74.00	-17.04	1.00 V	0	40.01	16.95
8	#7236.00	44.10 AV	54.00	-9.90	1.00 V	0	27.15	16.95

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	101.62 PK			1.00 H	54	96.30	5.32
2	*2437.00	97.42 AV			1.00 H	54	92.10	5.32
3	4874.00	53.26 PK	74.00	-20.74	1.00 H	0	42.36	10.90
4	4874.00	42.98 AV	54.00	-11.02	1.00 H	0	32.08	10.90
5	7311.00	55.96 PK	74.00	-18.04	1.00 H	0	38.80	17.16
6	7311.00	45.74 AV	54.00	-8.26	1.00 H	0	28.58	17.16
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	105.62 PK			1.00 V	105	100.30	5.32
2	*2437.00	101.21 AV			1.00 V	105	95.89	5.32
3	4874.00	54.47 PK	74.00	-19.53	1.00 V	0	43.57	10.90
4	4874.00	43.31 AV	54.00	-10.69	1.00 V	0	32.41	10.90
5	7311.00	56.69 PK	74.00	-17.31	1.00 V	0	39.53	17.16
6	7311.00	46.87 AV	54.00	-7.13	1.00 V	0	29.71	17.16

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	101.42 PK			1.00 H	102	95.97	5.45
2	*2462.00	97.45 AV			1.00 H	102	92.00	5.45
3	2483.50	57.54 PK	74.00	-16.46	1.00 H	102	51.97	5.57
4	2483.50	45.10 AV	54.00	-8.90	1.00 H	102	39.53	5.57
5	4924.00	52.29 PK	74.00	-21.71	1.00 H	0	41.20	11.09
6	4924.00	40.27 AV	54.00	-13.73	1.00 H	0	29.18	11.09
7	7386.00	54.48 PK	74.00	-19.52	1.00 H	0	37.12	17.36
8	7386.00	44.95 AV	54.00	-9.05	1.00 H	0	27.59	17.36
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	102.21 PK			1.00 V	87	96.76	5.45
2	*2462.00	106.24 AV			1.00 V	87	100.79	5.45
3	2483.50	58.54 PK	74.00	-15.46	1.00 V	87	52.97	5.57
4	2483.50	46.61 AV	54.00	-7.39	1.00 V	87	41.04	5.57
5	4924.00	53.39 PK	74.00	-20.61	1.00 V	0	42.30	11.09
6	4924.00	42.28 AV	54.00	-11.72	1.00 V	0	31.19	11.09
7	7386.00	54.63 PK	74.00	-19.37	1.00 V	0	37.27	17.36
8	7386.00	45.58 AV	54.00	-8.42	1.00 V	0	28.22	17.36

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. "*" : Fundamental frequency.

802.11n HT40

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.36 PK	74.00	-17.64	1.00 H	101	51.30	5.06
2	2390.00	43.96 AV	54.00	-10.04	1.00 H	101	38.90	5.06
3	*2422.00	100.85 PK			1.00 H	101	95.61	5.24
4	*2422.00	95.56 AV			1.00 H	101	90.32	5.24
5	4844.00	52.69 PK	74.00	-21.31	1.00 H	0	41.92	10.77
6	4844.00	40.76 AV	54.00	-13.24	1.00 H	0	29.99	10.77
7	7266.00	53.87 PK	74.00	-20.13	1.00 H	0	36.83	17.04
8	7266.00	44.59 AV	54.00	-9.41	1.00 H	0	27.55	17.04
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.45 PK	74.00	-16.55	1.00 V	203	52.39	5.06
2	2390.00	44.85 AV	54.00	-9.15	1.00 V	203	39.79	5.06
3	*2422.00	105.12 PK			1.00 V	203	99.88	5.24
4	*2422.00	101.98 AV			1.00 V	203	96.74	5.24
5	4844.00	53.23 PK	74.00	-20.77	1.00 V	0	42.46	10.77
6	4844.00	41.13 AV	54.00	-12.87	1.00 V	0	30.36	10.77
7	7266.00	54.15 PK	74.00	-19.85	1.00 V	0	37.11	17.04
8	7266.00	44.96 AV	54.00	-9.04	1.00 V	0	27.92	17.04

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	101.02 PK			1.00 H	30	95.70	5.32
2	*2437.00	97.26 AV			1.00 H	30	91.94	5.32
3	4874.00	53.26 PK	74.00	-20.74	1.00 H	0	42.36	10.90
4	4874.00	41.08 AV	54.00	-12.92	1.00 H	0	30.18	10.90
5	7311.00	57.42 PK	74.00	-16.58	1.00 H	0	40.26	17.16
6	7311.00	46.39 AV	54.00	-7.61	1.00 H	0	29.23	17.16
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	104.26 PK			1.00 V	109	98.94	5.32
2	*2437.00	100.54 AV			1.00 V	109	95.22	5.32
3	4874.00	53.65 PK	74.00	-20.35	1.00 V	0	42.75	10.90
4	4874.00	42.75 AV	54.00	-11.25	1.00 V	0	31.85	10.90
5	7311.00	57.84 PK	74.00	-16.16	1.00 V	0	40.68	17.16
6	7311.00	46.88 AV	54.00	-7.12	1.00 V	0	29.72	17.16

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	100.85 PK			1.00 H	75	95.45	5.40
2	*2452.00	95.21 AV			1.00 H	95	89.81	5.40
3	2483.50	57.41 PK	74.00	-16.59	1.00 H	95	51.84	5.57
4	2483.50	44.12 AV	54.00	-9.88	1.00 H	95	38.55	5.57
5	4904.00	53.37 PK	74.00	-20.63	1.00 H	0	42.36	11.01
6	4904.00	40.87 AV	54.00	-13.13	1.00 H	0	29.86	11.01
7	7356.00	56.24 PK	74.00	-17.76	1.00 H	0	38.95	17.29
8	7356.00	44.27 AV	54.00	-9.73	1.00 H	0	26.98	17.29
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	103.69 PK			1.00 V	124	98.29	5.40
2	*2452.00	99.75 AV			1.00 V	124	94.35	5.40
3	2483.50	59.54 PK	74.00	-14.46	1.00 V	124	53.97	5.57
4	2483.50	45.10 AV	54.00	-8.90	1.00 V	124	39.53	5.57
5	4904.00	54.26 PK	74.00	-19.74	1.00 V	0	43.25	11.01
6	4904.00	41.18 AV	54.00	-12.82	1.00 V	0	30.17	11.01
7	7356.00	56.96 PK	74.00	-17.04	1.00 V	0	39.67	17.29
8	7356.00	44.75 AV	54.00	-9.25	1.00 V	0	27.46	17.29

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	N/A
Power Sensor	Keysight	U2021XA	MY55060018	May 09, 22
Power Meter	Anritsu	ML2495A	1139001	Feb. 24,22
Power Sensor	Anritsu	MA2411B	1531155	Feb. 24,22
Digital Multimeter	FLUKE	15B	A1220010DG	N/A
Humid & Temp Programmable Tester	Haida	HD-225T	110807201	Nov. 03,21
Oscilloscope	Agilent	DSO9254A	MY51260160	Aug. 10,22
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101094	Feb. 24,22
Signal Generator	Agilent	N5183A	MY50140980	Aug. 10,22
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Sep. 04,22
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A
DC Source	Keysight	E3642A	MY56146098	N/A

NOTES: 1. The test was performed in RF Oven room.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.


4.3.3 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 100KHz
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b Chain 0

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	9.09	0.5	PASS
6	2437	9.12	0.5	PASS
11	2462	9.12	0.5	PASS

Chain 1

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	9.10	0.5	PASS
6	2437	9.11	0.5	PASS
11	2462	9.11	0.5	PASS

802.11g Chain 0

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	15.18	0.5	PASS
6	2437	15.17	0.5	PASS
11	2462	15.18	0.5	PASS

Chain 1

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	15.19	0.5	PASS
6	2437	15.18	0.5	PASS
11	2462	15.18	0.5	PASS


802.11n HT20

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		Chain0	Chain1		
1	2412	15.16	15.17	0.5	PASS
6	2437	15.17	15.19	0.5	PASS
11	2462	15.16	15.17	0.5	PASS


802.11n HT40

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		Chain0	Chain1		
3	2422	35.25	35.21	0.5	PASS
6	2437	35.23	35.23	0.5	PASS
9	2452	35.24	35.26	0.5	PASS


Chain 0




Chain 1




Chain 0




Chain 1




Chain 0




Chain 1



Chain 0



Chain 1




4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm).

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A peak power meter was used to read the response of the peak power sensor. Record the peak power level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.4.7 TEST RESULTS

MAXIMUM PEAK OUTPUT POWER

802.11b Chain 0

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
1	2412	16.25	42.170	1	PASS
6	2437	16.33	42.954	1	PASS
11	2462	16.65	46.238	1	PASS

Chain 1

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
1	2412	17.03	50.466	1	PASS
6	2437	17.58	57.280	1	PASS
11	2462	17.29	53.580	1	PASS

802.11g Chain 0

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
1	2412	20.83	121.060	1	PASS
6	2437	20.62	115.345	1	PASS
11	2462	20.87	122.180	1	PASS

Chain 1

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
1	2412	21.38	137.404	1	PASS
6	2437	21.44	139.316	1	PASS
11	2462	21.46	139.959	1	PASS

802.11n HT20

CHAN.	FRE. (MHz)	PEAK POWER (dBm)		PEAK POWER (mW)		TOTAL POWER (mW)	TOTAL POWER (dBm)	PEAK POWER LIMIT (W)	PASS/ FAIL
		CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1				
1	2412	17.65	18.41	58.21	69.343	127.553	21.06	1	PASS
6	2437	17.81	18.65	60.395	73.282	133.677	21.26	1	PASS
11	2462	17.92	18.74	61.944	74.817	136.761	21.36	1	PASS

Note: 1. Directional Gain = $3.6 + 10 \cdot \log(2) = 6.61 \text{ dBi}$, not exceed 3dB, so the limit is no need to be reduced.

802.11n HT40

CHAN.	FRE. (MHz)	PEAK POWER (dBm)		PEAK POWER (mW)		TOTAL POWER (mW)	TOTAL POWER (dBm)	PEAK POWER LIMIT (W)	PASS/ FAIL
		CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1				
3	2422	16.86	17.53	48.529	56.624	105.153	20.22	1	PASS
6	2437	16.98	17.71	49.888	59.020	108.908	20.37	1	PASS
9	2452	16.99	17.81	50.003	60.395	110.398	20.43	1	PASS

Note: 1. Directional Gain = $3.6 + 10 \cdot \log(2) = 6.61 \text{ dBi}$, not exceed 3dB, so the limit is no need to be reduced.

AVERAGE OUTPUT POWER (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

802.11b Chain 0

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)
1	2412	13.25	21.135
6	2437	13.37	21.727
11	2462	13.63	23.067

Chain 1

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)
1	2412	14.05	25.410
6	2437	14.61	28.907
11	2462	14.32	27.040

802.11g Chain 0

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)
1	2412	12.70	18.621
6	2437	12.60	18.197
11	2462	12.82	19.143

Chain 1

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)
1	2412	13.36	21.677
6	2437	13.41	21.928
11	2462	13.43	22.029

802.11n HT20

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)		AVG. POWER (mW)		TOTAL POWER (dBm)	TOTAL POWER (mW)
		CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1		
1	2412	9.67	10.46	9.268	11.117	13.09	20.385
6	2437	9.85	10.69	9.661	11.722	13.30	21.383
11	2462	9.95	10.77	9.886	11.940	13.39	21.826

802.11n HT40


CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)		AVG. POWER (mW)		TOTAL POWER (dBm)	TOTAL POWER (mW)
		CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1		
3	2422	8.84	9.61	7.656	9.141	12.25	16.797
6	2437	9.07	9.77	8.072	9.484	12.44	17.556
9	2452	9.08	9.85	8.091	9.661	12.49	17.752

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

- Set instrument center frequency to DTS channel center frequency.
- Set span to 1.5 times the DTS bandwidth.
- Set RBW to: 3KHz
- Set VBW $\geq 3 \times$ RBW.
- Detector = peak
- Ensure that the number of measurement points in the sweep $\geq 2 \times$ span/RBW.
- Sweep time = auto couple.
- Use the peak marker function to determine the maximum amplitude level.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

Same as item 4.3.6.

4.5.7 TEST RESULTS

802.11b

Chain 0

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	2.28	8.00	PASS
6	2437	1.09	8.00	PASS
11	2462	1.17	8.00	PASS

Chain 1

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	2.48	8.00	PASS
6	2437	2.99	8.00	PASS
11	2462	3.67	8.00	PASS

802.11g

Chain 0

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-14.45	8.00	PASS
6	2437	-14.78	8.00	PASS
11	2462	-15.33	8.00	PASS

Chain 1

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-13.12	8.00	PASS
6	2437	-13.28	8.00	PASS
11	2462	-12.96	8.00	PASS

802.11n HT20


Channel	FREQ. (MHz)	PSD (dBm/3kHz)		TOTAL (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
		Chain 0	Chain 1			
1	2412	-16.94	-12.19	-10.94	8.00	PASS
6	2437	-16.71	-13.16	-11.57	8.00	PASS
11	2462	-17.30	-13.63	-12.08	8.00	PASS

Note: 1. Directional Gain = $3.6 + 10 \cdot \log(2) = 6.61 \text{ dBi}$, not exceed 3dB, so the limit is no need to be reduced.



802.11n HT40

Channel	FREQ. (MHz)	PSD (dBm/3kHz)		TOTAL (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
		Chain 0	Chain 1			
3	2422	-20.14	-19.34	-16.71	8.00	PASS
6	2437	-19.99	-19.15	-16.54	8.00	PASS
9	2452	-19.78	-19.81	-16.78	8.00	PASS

Note: 1. Directional Gain = $3.6 + 10 \cdot \log(2) = 6.61 \text{ dBi}$, not exceed 3dB, so the limit is no need to be reduced.



802.11n HT40



4.6 OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

Measurement Procedure - Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

Measurement Procedure –Unwanted Emission Level

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION


Same as item 4.3.6

4.6.7 TEST RESULTS


802.11b

Chain 0


CH 1




CH 6



CH 11





Chain 1





802.11g
Chain 0



CH 1




CH 6



CH 11




Chain 1




802.11n HT20

Chain 0


CH 1



CH 6





CH 11





Chain 1



CH 1



CH 6




CH 11




802.11n HT40

Chain 0


CH 3



CH 6




CH 9




Chain 1


CH 3



CH 6




CH 9




802.11b.

Chain 0




Chain 1




802.11g

Chain 0




Chain 1




802.11n HT20

Chain 0




Chain 1




802.11n HT40

Chain 0



Chain 1





Test Report No.: RF2104WDG0365-3

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---