

OS-11 User Manual

Installation:

1. Install the battery and power on the OS-11 sensor.
2. Mount the sensor on the door frame.
3. Mount the magnet bar on the door to align with the sensor.

Pairing to the Receiver:

1. Close the door.
2. Put the receiver into Pairing mode.

If using the NGM-21 receiver, press and hold the "PROGRAM" button located on the back of the device.

A "beep-beep-beep" sound indicates that it has entered Pairing mode.

3. Open the door. The sensor will transmit an RF signal to the receiver.
A "beep-beep-beep" sound indicates that the pairing was successful.
4. Press the "PROGRAM" button on the NGM-21 again.
A "beep-beep-beep" sound indicates that it has exited Pairing mode.

Normal Operation:

1. The OS-11 will transmit an alarm signal when the door opens.
2. The receiver (e.g., NGM-21) will sound an alarm upon receiving the signal from the OS-11.
3. Press the "RESET" button on the NGM-21 to silence and reset the alarm.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential

installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.