

FCC TEST REPORT

For

Autel Intelligent Technology Corp., Ltd.

AUTOMOTIVE DIAGNOSTIC & ANALYSIS SYSTEM

Model No.: MaxiSys Elite

Prepared For : Autel Intelligent Technology Corp., Ltd.
Address : 6th - 10th Floor, Bldg. B1, Zhiyuan, Xueyuan Rd., Xili, Nanshan,
Shenzhen, 518055, China

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited
Address : 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan
District, Shenzhen, Guangdong, China
Tel: (86) 755-26066544 Fax: (86) 755-26014772

Report Number : R0217100099W3
Date of Test : Oct. 11~Nov. 13, 2017
Date of Report : Dec. 02, 2017

Contents

1. General Information.....	4
1.1. Client Information.....	4
1.2. Description of Device (EUT).....	4
1.3. Auxiliary Equipment Used During Test.....	4
1.4. Description of Test Modes.....	5
1.5. List of channels.....	6
1.6. Description Of Test Setup.....	7
1.7. Test Equipment List.....	7
1.8. Measurement Uncertainty.....	9
1.9. Description of Test Facility.....	9
2. Summary of Test Results.....	10
3. Conducted Emission Test.....	11
3.1. Test Standard and Limit.....	11
3.2. Test Setup.....	11
3.3. Test Procedure.....	11
3.4. Test Data.....	11
4. Radiation Spurious Emission and Band Edge.....	16
4.1. Test Standard and Limit.....	16
4.2. Test Setup.....	16
4.3. Test Procedure.....	17
4.4. Test Data.....	18
5. Maximum Peak Output Power Test.....	35
5.1. Test Standard and Limit.....	35
5.2. Test Setup.....	35
5.3. Test Procedure.....	35
5.4. Test Data.....	35
6. Occupy Bandwidth Test.....	37
6.1. Test Standard.....	37
6.2. Test Setup.....	37
6.3. Test Procedure.....	37
6.4. Test Data.....	37
7. Power Spectral Density Test.....	51
7.1. Test Standard and Limit.....	51
7.2. Test Setup.....	51
7.3. Test Procedure.....	51
7.4. Test Data.....	51
8. Antenna Requirement.....	59
8.1. Test Standard and Requirement.....	59
8.2. Antenna Connected Construction.....	60
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	61
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	61
APPENDIX III -- INTERNAL PHOTOGRAPH.....	62

TEST REPORT

Applicant : Autel Intelligent Technology Corp., Ltd.
Manufacturer : Autel Intelligent Technology Corp., Ltd.
Product Name : AUTOMOTIVE DIAGNOSTIC & ANALYSIS SYSTEM
Model No. : MaxiSys Elite
Trade Mark : Autel
Rating(s) : Input DC 12V, 3A (with DC 3.7V, 15400 mAh Battery inside)

Test Standard(s) : FCC Part15 Subpart E 2017, Paragraph 15.407

Test Method(s) : ANSI C63.10: 2013,
KDB 789033 D02 General UNII Test Procedures New Rules v01r04

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart E requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test : Oct. 11~Nov. 13, 2017

Prepared by :



Winkey Wang

(Tested Engineer / Winkey Wang)

Reviewer :

Tangcy. T.

(Project Manager / Tangcy. T)

Approved & Authorized Signer :

Tom Chen

(Manager / Tom Chen)

1. General Information

1.1. Client Information

Applicant	:	Autel Intelligent Technology Corp., Ltd.
Address	:	6th - 10th Floor, Bldg. B1, Zhiyuan, Xueyuan Rd.,Xili, Nanshan, Shenzhen, 518055, China
Manufacturer	:	Autel Intelligent Technology Corp., Ltd.
Address	:	6th - 10th Floor, Bldg. B1, Zhiyuan, Xueyuan Rd.,Xili, Nanshan, Shenzhen, 518055, China

1.2. Description of Device (EUT)

Product Name	:	AUTOMOTIVE DIAGNOSTIC & ANALYSIS SYSTEM	
Model No.	:	MaxiSys Elite	
Trade Mark	:	Autel	
Test Power Supply	:	AC 120V, 60Hz for adapter/AC 240V, 60Hz for adapter DC 3.7V Battery inside	
Product Description	:	Operation Frequency:	5180MHz~5240MHz / 5190MHz~5230MHz/ 5210MHz
	:	Number of Channel:	4 Channels for 802.11a 4 Channels for 802.11n(HT20) 4 Channels for 802.11ac(HT20) 2 Channels for 802.11ac(HT40) 1 Channels for 802.11ac(HT80)
	:	Modulation Type:	OFDM with BPSK/QPSK/16QAM/64QAM for 802.11a/b/g/n; OFDM with BPSK/QPSK/16QAM/64QAM/ 256QAM for 802.11ac
	:	Antenna Type:	PIFA Antenna
	:	Antenna Gain(Peak):	0.85 dBi
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2)This report is for WIFI 5.1G.			

1.3. Auxiliary Equipment Used During Test

Adapter	:	Model: GME36A-120300FDS Input: 100-240V~50-60Hz, 1.2A Output: 12V, 3A
---------	---	---

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Mode	Test channel	Frequency (MHz)
OFDM(802.11a/n20/ac20)	CH 36	5180MHz
	CH 40	5200MHz
	CH 48	5240MHz
OFDM(802.11ac40)	CH 38	5190MHz
	CH 46	5230MHz
OFDM(802.11ac80)	CH 42	5210MHz

Note:

1. The measurements are performed at the highest, middle, lowest available channels.
2. The EUT has been tested as an independent unit. And Continual Transmitting in maximum power.
3. For the relevant Conducted Measurement, the temporary antenna connector is used during the measurement. Antenna Connector Impedance: 50 Ω , Cable Loss: 1.0 dB
4. The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is more than 98%

1.5. List of channels

802.11a/n20/ac20

Channel	Freq. (MHz)	Channel	Freq. (MHz)
36	5180	44	5220
40	5200	48	5240

802.11ac40


Channel	Freq. (MHz)	Channel	Freq. (MHz)
38	5190	46	5230

802.11ac80


Channel	Freq. (MHz)
42	5210

1.6. Description Of Test Setup

CE



RE



1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	May 27, 2017	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	May 27, 2017	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	May 27, 2017	1 Year
4.	Spectrum Analysis	Agilent	E4407B	US39390582	May 27, 2017	1 Year
5.	Spectrum Analysis	Agilent	N9038A	MY53227295	May 27, 2017	1 Year
6.	Preamplifier	SKET Electronic	BK1G18G30 D	KD17503	May 27, 2017	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	May 27, 2017	1 Year
8.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	May 31, 2017	1 Year
9.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	May 31, 2017	1 Year
10.	Loop Antenna	Schwarzbeck	HFH2-Z2	100047	Apr. 03, 2017	1 Year
11.	Horn Antenna	Schwarzbeck	BBHA9170	9170-375	May 27, 2017	1 Year
12.	Pre-amplifier	SONOMA	310N	186860	May 27, 2017	1 Year
13.	Pre-amplifier	SKET Electronic	BK1G40G50 A	KD25352	May 27, 2017	1 Year
14.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
15.	Power Sensor	DAER	RPR3006W	15I00041SN045	May 27, 2017	1 Year
16.	Power Sensor	DAER	RPR3006W	15I00041SN046	May 27, 2017	1 Year
17.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	May 27, 2017	1 Year
18.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	May 27, 2017	1 Year
19.	Signal Generator	Agilent	E4421B	MY41000743	May 27, 2017	1 Year
20.	DC Power supply	IVYTECH	IV6003	1601D6030007	May 26, 2017	1 Year
21.	TEMP&HUMI PROGRAMMABLE CHAMBER	Sertep	ZJ-HWHS80 B	ZJ-17042804	Mar. 03, 2017	1 Year

1.8. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 4.1 dB (Horizontal)
		Ur = 4.3 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4dB

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

ShenzhenAnbotekComplianceLaboratoryLimited,EMCLaboratoryhasbeenregisteredandfullydescribedinareportfiled withthe(FCC)FederalCommunicationsCommission.TheacceptanceletterfromtheFCCismaintainedinourfiles.Registr ation No. 184111,July31,2017.

ISED-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A-1, June 13, 2016.

Test Location

All Emissions tests were performed at
Shenzhen Anbotek Compliance Laboratory Limited. at 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China

2. Summary of Test Results

Standard	Test Type	Result
15.207 & 15.407	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.407(b)	Band Edge	PASS
15.407(a)(5)	Occupy Bandwidth	PASS
15.407(a)(1)(3)	Maximum Conducted Output Power	PASS
15.407(a)(1)(3)	Peak Power Spectral Density	PASS
15.203/15.407g	Antenna Requirement	PASS


3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207&15.407		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.


The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

Please to see the following pages

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Keeping TX mode
Test Specification: AC 120V, 60Hz for adapter
Comment: Live Line
Tem.:25℃ Hum.:50%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1660	31.44	19.90	51.34	65.15	-13.81	QP	
2	0.1660	17.81	19.90	37.71	55.15	-17.44	AVG	
3	0.1740	17.73	19.90	37.63	54.76	-17.13	AVG	
4	0.1940	13.37	19.90	33.27	53.86	-20.59	AVG	
5	0.2380	12.07	19.89	31.96	52.16	-20.20	AVG	
6	0.2740	22.06	19.89	41.95	60.99	-19.04	QP	
7	0.3899	15.73	19.93	35.66	58.06	-22.40	QP	
8	0.5020	12.85	19.98	32.83	56.00	-23.17	QP	
9	0.5020	5.57	19.98	25.55	46.00	-20.45	AVG	
10	0.8820	0.85	20.09	20.94	46.00	-25.06	AVG	
11	1.3900	10.83	20.13	30.96	56.00	-25.04	QP	
12	1.9940	10.91	20.14	31.05	56.00	-24.95	QP	

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Keeping TX mode
Test Specification: AC 120V, 60Hz for adapter
Comment: Neutral Line
Tem.:25℃ Hum.:50%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1539	34.86	19.90	54.76	65.78	-11.02	QP	
2	0.1539	19.12	19.90	39.02	55.78	-16.76	AVG	
3	0.1819	15.00	19.90	34.90	54.39	-19.49	AVG	
4	0.2660	23.74	19.89	43.63	61.24	-17.61	QP	
5	0.5020	16.59	19.98	36.57	56.00	-19.43	QP	
6	0.5020	7.54	19.98	27.52	46.00	-18.48	AVG	
7	3.4540	1.91	20.17	22.08	46.00	-23.92	AVG	
8	3.6860	11.17	20.17	31.34	56.00	-24.66	QP	
9	4.7340	10.51	20.20	30.71	56.00	-25.29	QP	
10	9.1580	4.71	20.32	25.03	50.00	-24.97	AVG	
11	13.7580	16.23	20.28	36.51	60.00	-23.49	QP	
12	14.3260	6.97	20.27	27.24	50.00	-22.76	AVG	

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Keeping TX mode
Test Specification: AC 240V, 60Hz for adapter
Comment: Live Line
Tem.:25℃ Hum.:50%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1660	35.33	19.90	55.23	65.15	-9.92	QP	
2	0.1660	18.33	19.90	38.23	55.15	-16.92	AVG	
3	0.2660	22.43	19.89	42.32	61.24	-18.92	QP	
4	0.4900	14.53	19.98	34.51	56.17	-21.66	QP	
5	0.5140	6.82	19.98	26.80	46.00	-19.20	AVG	
6	1.0740	12.75	20.12	32.87	56.00	-23.13	QP	
7	1.4020	12.57	20.13	32.70	56.00	-23.30	QP	
8	1.4260	4.10	20.13	24.23	46.00	-21.77	AVG	
9	1.9220	3.77	20.14	23.91	46.00	-22.09	AVG	
10	2.3340	12.51	20.15	32.66	56.00	-23.34	QP	
11	2.3460	3.23	20.15	23.38	46.00	-22.62	AVG	
12	4.9220	2.95	20.20	23.15	46.00	-22.85	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Keeping TX mode
Test Specification: AC 240V, 60Hz for adapter
Comment: Neutral Line
Tem.:25℃ Hum.:50%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1500	36.47	19.90	56.37	65.99	-9.62	QP	
2	0.1500	20.22	19.90	40.12	55.99	-15.87	AVG	
3	0.1819	31.93	19.90	51.83	64.39	-12.56	QP	
4	0.1860	16.22	19.90	36.12	54.21	-18.09	AVG	
5	0.2180	13.20	19.90	33.10	52.89	-19.79	AVG	
6	0.2819	19.91	19.89	39.80	60.76	-20.96	QP	
7	0.4980	17.02	19.98	37.00	56.03	-19.03	QP	
8	0.4980	8.32	19.98	28.30	46.03	-17.73	AVG	
9	3.3380	13.06	20.17	33.23	56.00	-22.77	QP	
10	3.6380	5.04	20.17	25.21	46.00	-20.79	AVG	
11	13.2180	7.52	20.29	27.81	50.00	-22.19	AVG	
12	13.7820	16.09	20.28	36.37	60.00	-23.63	QP	

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209, 15.205 and 15.407				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	68.2	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

(3)Above 1GHz limit: $E[dBuV/m] = EIRP[dBm] + 95.2 = 68.2 \text{ dBuV/m}$, for $EIPR[dBm] = -27dBm$.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying

aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW =1MHz, VBW =10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.


4.4. Test Data

PASS

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Test Results (30~1000MHz)


Job No.: 0217100099W3 Temp.(°C)/Hum.(%RH): 24.3°C/55%RH
Standard: FCC PART 15C Power Source: DC 3.7V
Test Mode: TX Mode Polarization: Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	39.1616	32.14	-11.48	20.66	40.00	-19.34	QP	300	65	
2	150.0108	45.35	-23.34	22.01	43.50	-21.49	QP	300	94	
3	207.8501	51.97	-20.57	31.40	43.50	-12.10	QP	300	141	
4	262.8955	50.09	-18.89	31.20	46.00	-14.80	QP	300	196	
5	432.5457	44.13	-12.27	31.86	46.00	-14.14	QP	300	214	
6	750.1083	42.31	-7.49	34.82	46.00	-11.18	QP	300	252	

Test Results (30~1000MHz)

Job No.: 0217100099W3 Temp.(°C)/Hum.(%RH): 24.3°C/55%RH
Standard: FCC PART 15C Power Source: DC 3.7V
Test Mode: TX Mode Polarization: Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	31.7313	45.84	-16.12	29.72	40.00	-10.28	QP	300	19	
2	71.8320	42.59	-19.98	22.61	40.00	-17.39	QP	300	95	
3	207.8501	37.67	-15.57	22.10	43.50	-21.40	QP	300	114	
4	383.9318	42.28	-12.19	30.09	46.00	-15.91	QP	300	176	
5	432.5457	41.40	-11.24	30.16	46.00	-15.84	QP	300	241	
6	750.1083	40.74	-6.99	33.75	46.00	-12.25	QP	300	296	

Test Results (Above 1000MHz)

Test mode:	IEEE 802.11a	Test channel:	Low CH
------------	--------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10360.00	43.55	31.98	17.08	33.91	58.70	68.20	-9.50	V
15540.00	34.67	32.65	20.03	34.85	52.50	68.20	-15.70	V
10360.00	35.46	31.98	17.08	33.91	50.61	68.20	-17.59	H
15540.00	36.74	32.65	20.03	34.85	54.57	68.20	-13.63	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10360.00	32.95	31.98	17.08	33.91	48.10	54.00	-5.90	V
15540.00	29.66	32.65	20.03	34.85	47.49	54.00	-6.51	V
10360.00	27.68	31.98	17.08	33.91	42.83	54.00	-11.17	H
15540.00	29.63	32.65	20.03	34.85	47.46	54.00	-6.54	H

Test mode:	IEEE 802.11a	Test channel:	Mid CH
------------	--------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10400.00	41.69	32.44	17.18	33.91	57.40	68.20	-10.80	V
15600.00	37.48	32.78	20.12	34.86	55.52	68.20	-12.68	V
10400.00	37.63	32.44	17.18	33.91	53.34	68.20	-14.86	H
15600.00	36.55	32.78	20.12	34.86	54.59	68.20	-13.61	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10400.00	29.88	32.44	17.18	33.91	45.59	54.00	-8.41	V
15600.00	29.01	32.78	20.12	34.86	47.05	54.00	-6.95	V
10400.00	30.41	32.44	17.18	33.91	46.12	54.00	-7.88	H
15600.00	28.56	32.78	20.12	34.86	46.60	54.00	-7.40	H

Test mode:	IEEE 802.11a	Test channel:	High CH
------------	--------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10480.00	43.00	32.59	18.02	33.92	59.69	68.20	-8.51	V
15720.00	38.48	32.87	20.15	34.88	56.62	68.20	-11.58	V
10480.00	39.60	32.59	18.02	33.92	56.29	68.20	-11.91	H
15720.00	39.34	32.87	20.15	34.88	57.48	68.20	-10.72	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10480.00	32.94	32.59	18.02	33.92	49.63	54.00	-4.37	V
15720.00	29.78	32.87	20.15	34.88	47.92	54.00	-6.08	V
10480.00	29.04	32.59	18.02	33.92	45.73	54.00	-8.27	H
15720.00	31.71	32.87	20.15	34.88	49.85	54.00	-4.15	H

Test mode:	IEEE 802.11n(HT20)	Test channel:	Low CH
------------	--------------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10360.00	42.56	31.98	17.08	33.91	57.71	68.20	-10.49	V
15540.00	38.99	32.65	20.03	34.85	56.82	68.20	-11.38	V
10360.00	38.97	31.98	17.08	33.91	54.12	68.20	-14.08	H
15540.00	39.72	32.65	20.03	34.85	57.55	68.20	-10.65	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10360.00	32.45	31.98	17.08	33.91	47.60	54.00	-6.40	V
15540.00	31.89	32.65	20.03	34.85	49.72	54.00	-4.28	V
10360.00	31.34	31.98	17.08	33.91	46.49	54.00	-7.51	H
15540.00	31.94	32.65	20.03	34.85	49.77	54.00	-4.23	H

Test mode:	IEEE 802.11n(HT20)	Test channel:	Mid CH
------------	--------------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10400.00	41.93	32.44	17.18	33.91	57.64	68.20	-10.56	V
15600.00	39.82	32.78	20.12	34.86	57.86	68.20	-10.34	V
10400.00	38.79	32.44	17.18	33.91	54.50	68.20	-13.70	H
15600.00	37.34	32.78	20.12	34.86	55.38	68.20	-12.82	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10400.00	31.23	32.44	17.18	33.91	46.94	54.00	-7.06	V
15600.00	31.63	32.78	20.12	34.86	49.67	54.00	-4.33	V
10400.00	31.33	32.44	17.18	33.91	47.04	54.00	-6.96	H
15600.00	30.04	32.78	20.12	34.86	48.08	54.00	-5.92	H

Test mode:	IEEE 802.11n(HT20)	Test channel:	High CH
------------	--------------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10480.00	42.71	32.59	18.02	33.92	59.40	68.20	-8.80	V
15720.00	37.82	32.87	20.15	34.88	55.96	68.20	-12.24	V
10480.00	38.75	32.59	18.02	33.92	55.44	68.20	-12.76	H
15720.00	38.63	32.87	20.15	34.88	56.77	68.20	-11.43	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10480.00	32.21	32.59	18.02	33.92	48.90	54.00	-5.10	V
15720.00	30.99	32.87	20.15	34.88	49.13	54.00	-4.87	V
10480.00	29.29	32.59	18.02	33.92	45.98	54.00	-8.02	H
15720.00	29.35	32.87	20.15	34.88	47.49	54.00	-6.51	H

Test mode:	IEEE 802.11n(ac20)	Test channel:	Low CH
------------	--------------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10360.00	42.63	31.98	17.08	33.91	57.78	68.20	-10.42	V
15540.00	37.02	32.65	20.03	34.85	54.85	68.20	-13.35	V
10360.00	38.11	31.98	17.08	33.91	53.26	68.20	-14.94	H
15540.00	37.07	32.65	20.03	34.85	54.90	68.20	-13.30	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10360.00	31.84	31.98	17.08	33.91	46.99	54.00	-7.01	V
15540.00	31.25	32.65	20.03	34.85	49.08	54.00	-4.92	V
10360.00	29.62	31.98	17.08	33.91	44.77	54.00	-9.23	H
15540.00	28.83	32.65	20.03	34.85	46.66	54.00	-7.34	H

Test mode:	IEEE 802.11n(ac20)	Test channel:	Mid CH
------------	--------------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10400.00	42.06	32.44	17.18	33.91	57.77	68.20	-10.43	V
15600.00	39.39	32.78	20.12	34.86	57.43	68.20	-10.77	V
10400.00	37.74	32.44	17.18	33.91	53.45	68.20	-14.75	H
15600.00	37.73	32.78	20.12	34.86	55.77	68.20	-12.43	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10400.00	31.05	32.44	17.18	33.91	46.76	54.00	-7.24	V
15600.00	31.62	32.78	20.12	34.86	49.66	54.00	-4.34	V
10400.00	29.86	32.44	17.18	33.91	45.57	54.00	-8.43	H
15600.00	29.01	32.78	20.12	34.86	47.05	54.00	-6.95	H

Test mode:	IEEE 802.11n(ac20)	Test channel:	High CH
------------	--------------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10480.00	42.60	32.59	18.02	33.92	59.29	68.20	-8.91	V
15720.00	38.63	32.87	20.15	34.88	56.77	68.20	-11.43	V
10480.00	37.97	32.59	18.02	33.92	54.66	68.20	-13.54	H
15720.00	38.77	32.87	20.15	34.88	56.91	68.20	-11.29	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10480.00	32.34	32.59	18.02	33.92	49.03	54.00	-4.97	V
15720.00	31.50	32.87	20.15	34.88	49.64	54.00	-4.36	V
10480.00	31.69	32.59	18.02	33.92	48.38	54.00	-5.62	H
15720.00	30.95	32.87	20.15	34.88	49.09	54.00	-4.91	H

Test mode:	IEEE 802.11ac(HT40)	Test channel:	Low CH
------------	---------------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10380.00	42.93	31.98	17.08	33.91	58.08	68.20	-10.12	V
15570.00	37.87	32.65	20.03	34.85	55.70	68.20	-12.50	V
10380.00	37.76	31.98	17.08	33.91	52.91	68.20	-15.29	H
15570.00	38.32	32.65	20.03	34.85	56.15	68.20	-12.05	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10380.00	32.20	31.98	17.08	33.91	47.35	54.00	-6.65	V
15570.00	29.54	32.65	20.03	34.85	47.37	54.00	-6.63	V
10380.00	30.84	31.98	17.08	33.91	45.99	54.00	-8.01	H
15570.00	29.30	32.65	20.03	34.85	47.13	54.00	-6.87	H

Test mode:	IEEE 802.11ac(HT40)	Test channel:	High CH
------------	---------------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10460.00	42.68	32.59	18.02	33.92	59.37	68.20	-8.83	V
15690.00	38.29	32.87	20.15	34.88	56.43	68.20	-11.77	V
10460.00	38.45	32.59	18.02	33.92	55.14	68.20	-13.06	H
15690.00	38.98	32.87	20.15	34.88	57.12	68.20	-11.08	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10460.00	31.97	32.59	18.02	33.92	48.66	54.00	-5.34	V
15690.00	30.25	32.87	20.15	34.88	48.39	54.00	-5.61	V
10460.00	31.79	32.59	18.02	33.92	48.48	54.00	-5.52	H
15690.00	30.30	32.78	20.12	34.86	48.34	54.00	-5.66	H

Test mode:	IEEE 802.11ac(HT80)	Test channel:	
------------	---------------------	---------------	--

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10420.00	41.04	32.44	17.18	33.91	56.75	68.20	-11.45	V
15630.00	38.24	32.78	20.12	34.86	56.28	68.20	-11.92	V
10420.00	38.45	32.44	17.18	33.91	54.16	68.20	-14.04	H
15630.00	38.44	32.78	20.12	34.86	56.48	68.20	-11.72	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
10420.00	32.35	32.44	17.18	33.91	48.06	54.00	-5.94	V
15630.00	31.50	32.78	20.12	34.86	49.54	54.00	-4.46	V
10420.00	30.81	32.44	17.18	33.91	46.52	54.00	-7.48	H
15630.00	31.56	32.78	20.12	34.86	49.60	54.00	-4.40	H

Note:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss - Preamplifier Factor

Radiated Band Edge:

Test Mode: 802.11a								
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
5150.00	41.49	28.65	13.58	31.04	52.68	68.20	-15.52	H
5350.00	42.87	29.16	14.68	31.96	54.75	68.20	-13.45	H
5150.00	41.60	28.65	13.58	31.04	52.79	68.20	-15.41	V
5350.00	41.74	29.16	14.68	31.96	53.62	68.20	-14.58	V
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
5150.00	35.59	28.65	13.58	31.04	46.78	54.00	-7.22	H
5350.00	35.51	29.16	14.68	31.96	47.39	54.00	-6.61	H
5150.00	34.75	28.65	13.58	31.04	45.94	54.00	-8.06	V
5350.00	34.14	29.16	14.68	31.96	46.02	54.00	-7.98	V

Test Mode: 802.11n20								
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
5150.00	41.72	28.65	13.58	31.04	52.91	68.20	-15.29	H
5350.00	41.84	29.16	14.68	31.96	53.72	68.20	-14.48	H
5150.00	42.00	28.65	13.58	31.04	53.19	68.20	-15.01	V
5350.00	42.52	29.16	14.68	31.96	54.40	68.20	-13.80	V
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
5150.00	34.81	28.65	13.58	31.04	46.00	54.00	-8.00	H
5350.00	35.90	29.16	14.68	31.96	47.78	54.00	-6.22	H
5150.00	35.85	28.65	13.58	31.04	47.04	54.00	-6.96	V
5350.00	35.88	29.16	14.68	31.96	47.76	54.00	-6.24	V


Test Mode: 802.11ac20								
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
5150.00	42.83	28.65	13.58	31.04	54.02	68.20	-14.18	H
5350.00	42.29	29.16	14.68	31.96	54.17	68.20	-14.03	H
5150.00	41.91	28.65	13.58	31.04	53.10	68.20	-15.10	V
5350.00	42.97	29.16	14.68	31.96	54.85	68.20	-13.35	V
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
5150.00	34.96	28.65	13.58	31.04	46.15	54.00	-7.85	H
5350.00	34.20	29.16	14.68	31.96	46.08	54.00	-7.92	H
5150.00	35.00	28.65	13.58	31.04	46.19	54.00	-7.81	V
5350.00	35.21	29.16	14.68	31.96	47.09	54.00	-6.91	V

Test Mode: 802.11ac40								
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
5150.00	41.59	28.65	13.58	31.04	52.78	68.20	-15.42	H
5350.00	42.46	29.16	14.68	31.96	54.34	68.20	-13.86	H
5150.00	41.82	28.65	13.58	31.04	53.01	68.20	-15.19	V
5350.00	41.85	29.16	14.68	31.96	53.73	68.20	-14.47	V
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
5150.00	34.93	28.65	13.58	31.04	46.12	54.00	-7.88	H
5350.00	35.49	29.16	14.68	31.96	47.37	54.00	-6.63	H
5150.00	35.48	28.65	13.58	31.04	46.67	54.00	-7.33	V
5350.00	35.70	29.16	14.68	31.96	47.58	54.00	-6.42	V


Test Mode: 802.11ac80								
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
5150.00	41.31	28.65	13.58	31.04	52.50	68.20	-15.70	H
5350.00	42.26	29.16	14.68	31.96	54.14	68.20	-14.06	H
5150.00	41.79	28.65	13.58	31.04	52.98	68.20	-15.22	V
5350.00	41.43	29.16	14.68	31.96	53.31	68.20	-14.89	V
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
5150.00	35.16	28.65	13.58	31.04	46.35	54.00	-7.65	H
5350.00	34.05	29.16	14.68	31.96	45.93	54.00	-8.07	H
5150.00	35.33	28.65	13.58	31.04	46.52	54.00	-7.48	V
5350.00	34.03	29.16	14.68	31.96	45.91	54.00	-8.09	V

For conducted test:


802.11a: Band Edge, Left Side




802.11a: Band Edge, Right Side




802.11n(20): Band Edge, Left Side




802.11n(20): Band Edge, Right Side




802.11ac(20): Band Edge, Left Side




802.11ac(20): Band Edge, Right Side





802.11ac(40): Band Edge, Left Side



802.11ac(40): Band Edge, Right Side



802.11ac(80): Band Edge, Left Side&Right Side




5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.407 (a)(1) (3)
Test Limit	24dBm

5.2. Test Setup



5.3. Test Procedure

1. The Transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the power value.
3. Repeat above procedures on all channels needed to be tested.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

5.4. Test Data

Test Item	:	Max. peak output power	Test Mode	:	CH Low ~ CH High
Test Voltage	:	AC 120V/60Hz	Temperature	:	24℃
Test Result	:	PASS	Humidity	:	55%RH


Mode	Channel Frequency (MHz)	Peak Power output (dBm)	Limit (dBm)	Results
802.11a	5180	16.06	24.00	PASS
	5200	14.87	24.00	PASS
	5240	15.78	24.00	PASS
802.11n20	5180	15.22	24.00	PASS
	5200	15.18	24.00	PASS
	5240	15.77	24.00	PASS
802.11ac20	5180	15.33	24.00	PASS
	5200	15.13	24.00	PASS
	5240	15.04	24.00	PASS
802.11ac40	5190	15.22	24.00	PASS
	5230	15.28	24.00	PASS
802.11ac80	5210	15.57	24.00	PASS

6. Occupy Bandwidth Test

6.1. Test Standard

Test Standard	FCC Part15 C Section 15.407 (a)(5)
---------------	------------------------------------

6.2. Test Setup



6.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

3. Set the spectrum analyzer as:

26 dB & 99% bandwidth

RBW = approximately 1% of the emission bandwidth;
Set the VBW > RBW;
Detector= Peak
Trace mode= Max hold.
Sweep- auto couple.

6 dB bandwidth

RBW = 100kHz;
Set the video bandwidth (VBW) ≥ 3 RBW;
Detector= Peak
Trace mode= Max hold.
Sweep- auto couple.

4. Measure the maximum width of the emission that is 26dB /6dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer.
5. Repeat until all the rest channels are investigated.

6.4. Test Data


Test Item : 6dB &26dB BW
Test Voltage : AC 120V/60Hz
Test Result : PASS

Test Mode : CH Low ~ CH High
Temperature : 24℃
Humidity : 55%RH


Mode	Channel Frequency (MHz)	6dB BW(MHz)	Limit	Results
802.11a	5180	16.46	>0.5MHz	PASS
	5200	16.49		PASS
	5240	16.44		PASS
802.11n20	5180	17.67		PASS
	5200	17.65		PASS
	5240	17.66		PASS
802.11ac20	5180	15.17		PASS
	5200	15.18		PASS
	5240	15.17		PASS
802.11ac40	5190	35.20		PASS
	5230	35.21		PASS
802.11ac80	5210	75.37		PASS

Mode	Channel Frequency (MHz)	26dB BW(MHz)	99%Bandwidth (MHz)
802.11a	5180	22.86	16.999
	5200	22.75	16.869
	5240	23.05	16.936
802.11n20	5180	23.09	17.971
	5200	21.56	17.851
	5240	23.42	18.052
802.11ac20	5180	22.14	17.690
	5200	21.95	17.676
	5240	22.93	17.657
802.11ac40	5190	41.19	36.079
	5230	41.58	36.070
802.11ac80	5210	97.73	75.501

6dB Bandwidth




Test Mode: 802.11a--Low




Test Mode: 802.11a---Middle




Test Mode: 802.11a---High




Test Mode: 802.11n20---Low




Test Mode: 802.11n20---Middle




Test Mode: 802.11n20---High




Test Mode: 802.11ac20--Low




Test Mode: 802.11ac20---Middle




Test Mode: 802.11ac20---High



Test Mode: 802.11ac40---Low



Test Mode: 802.11ac40---High




Test Mode: 802.11ac80


26dB & 99% Bandwidth




Test Mode: 802.11a--Low




Test Mode: 802.11a---Middle




Test Mode: 802.11a---High




Test Mode: 802.11n20---Low




Test Mode: 802.11n20---Middle




Test Mode: 802.11n20---High




Test Mode: 802.11ac20--Low




Test Mode: 802.11ac20---Middle




Test Mode: 802.11ac20---High



Test Mode: 802.11ac40---Low



Test Mode: 802.11ac40---High




Test Mode: 802.11ac80

7. Power Spectral Density Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.407 (a) (1) (2) (3)
Test Limit	11dBm

7.2. Test Setup



7.3. Test Procedure

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz).

1. The EUT is directly connected to the spectrum analyzer;
2. Set RBW =1MHz;
3. Set VBW $\geq$ 3 RBW=3MHz;
3. Set the span to encompass the entire emissions bandwidth (EBW) of the signal;
5. Detector=RMS;
6. Sweep time= auto couple;
7. Trace mode=max. hold;

7.4. Test Data

Test Item	: Power Spectral Density	Test Mode	: CH Low ~ CH High
Test Voltage	: AC 120V/60HZ	Temperature	: 24°C
Test Result	: PASS	Humidity	: 55%RH


Mode	Channel Frequency (MHz)	Final Power Spectral Density (dBm)	Limit	Results
802.11a	5180	-1.584	11dBm	PASS
	5200	-0.329		PASS
	5240	-0.674		PASS
802.11n20	5180	1.211		PASS
	5200	1.768		PASS
	5240	0.084		PASS
802.11ac20	5180	3.518		PASS
	5200	5.097		PASS
	5240	4.223		PASS
802.11ac40	5190	0.214		PASS
	5230	0.533		PASS
802.11ac80	5210	-1.327		PASS




Test Mode: 802.11a--Low




Test Mode: 802.11a---Middle




Test Mode: 802.11a---High




Test Mode: 802.11n20---Low




Test Mode: 802.11n20---Middle




Test Mode: 802.11n20---High




Test Mode: 802.11ac20--Low




Test Mode: 802.11ac20---Middle




Test Mode: 802.11ac20---High



Test Mode: 802.11ac40---Low



Test Mode: 802.11ac40---High



Test Mode: 802.11ac80


8. Antenna Requirement

8.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /15.407
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.407 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

8.2. Antenna Connected Construction

The WIFI antenna is a PIFA Antenna which permanently attached, and the best case gain of the antenna is 0.85 dBi. It complies with the standard requirement.



APPENDIX I -- TEST SETUP PHOTOGRAPH

Please see the test report of R0217100099W1

Anbotek

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please see the test report of R0217100099W1

Anbotek

APPENDIX III -- INTERNAL PHOTOGRAPH

Please see the test report of R0217100099W1

Anbotek

End of Report