

RF Exposure Report

Report No.: SABHLU-WTW-P22010749

FCC ID: WQJ-VP3300BT

Test Model: IDMR-BT93133PV2D

Series Model: IDMR-BT93133XXXXXXX (refer to item 3.1 for more details)

Received Date: Jan. 21, 2022

Date of Evaluation: Mar. 14, 2022

Issued Date: Mar. 25, 2022

Applicant: ID TECH

Address: 10721 Walker St. Cypress, CA 90630

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SABHLU-WTW-P22010749	Original Release	Mar. 25, 2022

1 Certificate of Conformity

Product: ViVOpay VP3300BT

Brand: ID TECH

Test Model: IDMR-BT93133PV2D

Series Model: IDMR-BT93133XXXXXXX (refer to item 3.1 for more details)

Sample Status: Engineering Sample

Applicant: ID TECH

Date of Evaluation: Mar. 14, 2022

Standards: FCC Part 2 (Section 2.1091)

References Test Guidance : KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :

Lena Wang

Date: Mar. 25, 2022

Lena Wang / Specialist

Approved by :

Jeremy Lin

Date: Mar. 25, 2022

Jeremy Lin / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.
So, this device is classified as **Mobile Device**.

2.4 Calculation Result of Maximum Conducted Power

Frequency (MHz)	Max. Field Strength (dBuV/m)@3m	Max. Power (mW)	Min. test separation distance (mm)	SAR test exclusion calculation value ^(NOTE)	1-g SAR test exclusion thresholds
13.56	75.67	0.01107	5	0.01107	1107.433774

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. Calculate SAR test exclusion thresholds from condition "3" formulas.
3. Field Strength (dBuV/m@3m) = Field Strength (dBuV/m@30m) + 40*log(30/3).
4. Max Power (dBm) = Field Strength of Fundamental (dBuV/m@3m) – 95.23,
Max Power (mW) = $10^{(\text{Max power (dBm)}/10)}$
5. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible
6. EUT model definition list.

Model definition		Character	Description
1st X	MSR Encryption	blank	TDES
	Method	A	AES
2nd X	MSR Data format	blank	Enhanced
		O	Original
3rd X	Encryption	blank	N/A
		P	Encrypts all transaction methods (MSR, EMV, Ctls)
4th X	Enclosure color	blank	Black
		W	White
		C	Custom Color other than Black and White
5th X	BT CHIP	V	Avnet Chip set
6th X	Firmware version on the AS3911 Rev A Chip	blank	NEO 1.01
		2	NEO 1.10
7th X	Demo Key	blank	N/A
		D	Demo Key injected

--- END ---