

TEST REPORT



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2021-04178
Page (1) / (36) Pages

1. Client

- Name : KAONMEDIA Co., Ltd.
- Address : KAONMEDIA Building, 884-3 Seongnam-daero, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea
- Date of Receipt : 2021-09-16

2. Manufacturer

- Name : KAONMEDIA Co., Ltd.
- Address : KAONMEDIA Building, 884-3, Seongnam-daero, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea

3. Use of Report : For FCC Conformance

4. Test Sample / Model: IP Set-top-box(OTT STB) / KSTB2100

5. Date of Test : 2021-10-22 to 2021-11-02

6. Test Standard(method) used : FCC 47 CFR part 15 subpart C 15.247

7. Testing Environment: Temp.: (23 ± 1) °C, Humidity: (49 ± 3) % R.H.

8. Test Results : Compliance

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full.

Affirmation	Tested by	Technical Manager
	Ji-Hye, Kim: (Signature) 	Won-Jae, Hwang: (Signature) 

2021-11-18

Republic of KOREA **CTK Co., Ltd.**



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2021-04178
Page (2) / (36) Pages

REPORT REVISION HISTORY

Date	Revision	Page No
2021-11-18	Issued (CTK-2021-04178)	all

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.

CONTENTS

1. General Product Description	4
1.1 Client Information	4
1.2 Product Information	4
1.3 Peripheral Devices	4
1.4 Model Differences	4
2. Facility and Accreditations	5
2.1 Test Facility	5
2.2 Laboratory Accreditations and Listings	5
2.3 Calibration Details of Equipment Used for Measurement	5
3. Test Specifications	6
3.1 Standards	6
3.2 Mode of operation during the test	6
3.3 Device Modifications	6
3.4 Maximum Measurement Uncertainty	7
3.5 Test Software	7
4. Technical Characteristic Test	8
4.1 6dB Bandwidth	8
4.2 Maximum peak Conducted Output Power	12
4.3 Transmitter Power Spectral Density	16
4.4 Conducted Spurious emission	19
4.5 Radiated Emission	22
4.6 AC Conducted Emissions	33
APPENDIX A – Test Equipment Used For Tests	36

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	Report No.: CTK-2021-04178 Page (4) / (36) Pages	
--	--	---	--

1. General Product Description

1.1 Client Information

Company	KAONMEDIA Co., Ltd.
Contact Point	KAONMEDIA Building, 884-3 Seongnam-daero, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea
Contact Person	Name : Minseok Choi E-mail : minseok.choi@kaonmedia.com Tel : +82-31-724-8683 Fax : -

1.2 Product Information

FCC ID	WQTKSTB2100R
Product Description	IP Set-top-box(OTT STB)
Model name	KSTB2100
Variant Model name	-
Operating Frequency	2 402 MHz - 2 480 MHz
RF Output Power	1 Mbps : 8.179 dBm (6.575 mW) 2 Mbps : 8.167 dBm (6.557 mW)
Antenna Specification	Antenna type : PCB Antenna Peak Gain : 1.74 dBi
Number of channels	40
Channel Spacing	1 MHz
Type of Modulation	GFSK (Bluetooth 5.0 - LE)
Power Source	DC 12 V (Adapter)
Hardware Rev	Rev 1.1
Software Rev	1.1.9

1.3 Peripheral Devices

Device	Manufacturer	Model No.	Serial No.
Note Computer	HP	15-bs563TU	CND7253R6N
AC/DC Adapter	HP	HSTNN-CA40	-
Switching Mode Power Adaptor	CHENAHOU FRECOM ELECTRONICS CO., LTD.	F18L16-120150SPAU	-

1.4 Model Differences

Not applicable

2. Facility and Accreditations

2.1 Test Facility

The radiated measurement facility is located at (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yong-in-si, Gyeonggi-do, Korea.

The conducted measurement facility is located at 5, Dongbu-ro 221beon-gil, Cheoin-gu, Yong-in-si, Gyeonggi-do, Korea.

2.2 Laboratory Accreditations and Listings

Country	Agency	Registration Number
USA	FCC	805871
CANADA	ISED	8737A-2
KOREA	NRRA	KR0025

2.3 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

3. Test Specifications

3.1 Standards

FCC Part Section(s)	Requirement(s)	Status (Note 1)	Test Condition
15.247(a)	6 dB Bandwidth	C	Conducted
15.247(b)	Maximum Output Power	C	
15.247(d)	Conducted Spurious emission	C	
15.247(d)	Unwanted Emission(Conducted)	C	
15.247(e)	Transmitter Power Spectral Density	C	
15.209	Radiated Emissions	C	Radiated
15.207	AC Conducted Emissions	C	Line Conducted
<i>Note 1:</i> C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable			
<i>Note 2:</i> The data in this test report are traceable to the national or international standards.			
<i>Note 3:</i> The sample was tested according to the following specification: FCC Part 15.247			
<i>Note 4:</i> The tests were performed according to the method of measurements prescribed in KDB No.558074, ANSI C63.10-2013			

3.2 Mode of operation during the test

The EUT is operated in a manner representative of the typical of the equipments.
During at testing, system components were manipulated within the confines of typical usage to maximize each emission. All modulation modes were tests.
The results are only attached worst cases.

Test Frequency

Lowest channel	Middle channel	Highest channel
2 402 MHz	2 440 MHz	2 480 MHz

Test mode

Mode	Duty Cycle	Duty Cycle Factor
1 Mbps	86.1 %	0.65 dB
2 Mbps	58.6 %	2.32 dB

3.3 Device Modifications

The following modifications were necessary for compliance:

Not applicable

3.4 Maximum Measurement Uncertainty

The value of the measurement uncertainty for the measurement of each parameter.
Coverage factor $k = 2$, Confidence levels of 95 %

Description	Uncertainty
Conducted RF Output Power	1.5 dB (C.L.: Approx. 95 %, $k = 2$)
Power Spectral Density	1.5 dB (C.L.: Approx. 95 %, $k = 2$)
Occupied Bandwidth	0.1 MHz (C.L.: Approx. 95 %, $k = 2$)
Unwanted Emission(conducted)	3.0 dB (C.L.: Approx. 95 %, $k = 2$)
Radiated Emissions ($f \leq 1$ GHz)	4.66 dB (C.L.: Approx. 95 %, $k = 2$)
Radiated Emissions ($f > 1$ GHz)	4.76 dB (C.L.: Approx. 95 %, $k = 2$)
Line Conducted Emission	1.96 dB (C.L.: Approx. 95 %, $k = 2$)

3.5 Test Software

Conducted Test	Ics Pro Ver. 6.0.3
Radiated Test	TOYO EMI software EP5RE Ver. 6.0.1.0
Line Conducted Test	ESCI7, ESCI3 : EMC32 Ver. 8.50.0 ESR7 : EMC32 Ver. 8.53.0

4. Technical Characteristic Test

4.1 6dB Bandwidth

Test Procedures

KDB 558074 - Section 8.2
ANSI C63.10-2013 - Section 11.8.2

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Procedures

ANSI C63.10-2013 - Section 6.9

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.

Use the 99% power bandwidth function of the instrument and report the measured bandwidth.

Test Settings :

Center frequency = the highest, middle and the lowest channels

- | | |
|--|----------------------------|
| a) RBW = 100 kHz | b) VBW $\geq 3 \times$ RBW |
| c) Detector = peak | d) Trace mode = Max hold |
| e) Sweep = auto couple | |
| f) Allow trace to fully stabilize | |
| g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. | |

Minimum Standard :

6 dB Bandwidth > 500kHz

Test Data :

Test mode : 1 Mbps


Frequency (MHz)	6dB Bandwidth (MHz)	99 % Bandwidth (MHz)	Result
2 402	0.667	1.044	Complies
2 440	0.665	1.046	Complies
2 480	0.667	1.047	Complies

Test mode : 2 Mbps


Frequency (MHz)	6dB Bandwidth (MHz)	99 % Bandwidth (MHz)	Result
2 402	1.139	2.083	Complies
2 440	1.165	2.071	Complies
2 480	1.161	2.076	Complies

See next pages for actual measured spectrum plots.

Test mode : 1 Mbps



Test mode : 2 Mbps



4.2 Maximum peak Conducted Output Power

Test Procedures

KDB 558074 - Section 8.3.1.1

ANSI C63.10-2013 - Section 11.9.1.1

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Test Settings:

Center frequency = the highest, middle and the lowest channels

- | | |
|--|-----------------------------|
| a) RBW $\geq$ DTS bandwidth | b) VBW $\geq 3 \times$ RBW |
| c) span $\geq 3 \times$ RBW | d) Sweep time = auto couple |
| e) Detector = peak | f) Trace mode = max hold |
| g) Allow trace to fully stabilize | |
| h) Use peak marker function to determine the peak amplitude level. | |

Limit :

Maximum Output Power < 1 W (30 dBm)

Test Data :

Test mode : 1 Mbps


Frequency (MHz)	Maximum peak Conducted Output Power		Result
	(dBm)	(mW)	
2 402	7.583	5.732	Complies
2 440	7.304	5.375	Complies
2 480	8.179	6.575	Complies

Test mode : 2 Mbps

Frequency (MHz)	Maximum peak Conducted Output Power		Result
	(dBm)	(mW)	
2 402	8.167	6.557	Complies
2 440	7.753	5.961	Complies
2 480	8.153	6.536	Complies

See next pages for actual measured spectrum plots.

Test mode : 1 Mbps



Test mode : 2 Mbps



4.3 Transmitter Power Spectral Density

Test Procedures

KDB 558074 - Section 8.4

ANSI C63.10-2013 - Section 11.10.2

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance.

Test Settings:

Center frequency = the highest, middle and the lowest channels

- a) RBW : $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- b) VBW $\geq 3 \times \text{RBW}$
- c) span $\geq 1.5 \times \text{DTS bandwidth}$
- d) Sweep time = auto couple
- e) Detector = peak
- f) Trace mode = max hold
- g) Allow trace to fully stabilize
- h) Use the peak marker function to determine the maximum amplitude level within the RBW.

Limit :

Power Spectral Density < 8dBm @ 3 kHz BW

Test Data :

Test mode : 1 Mbps


Frequency (MHz)	Power Spectral Density	Result
	(dBm)	
2 402	-9.141	Complies
2 440	-8.993	Complies
2 480	-7.845	Complies

Test mode : 2 Mbps


Frequency (MHz)	Power Spectral Density	Result
	(dBm)	
2 402	-9.889	Complies
2 440	-9.761	Complies
2 480	-10.269	Complies

See next pages for actual measured spectrum plots.

Test mode : 1 Mbps



Test mode : 2 Mbps



4.4 Conducted Spurious emission

Test Procedures

KDB 558074 - Section 8.5

ANSI C63.10-2013 - Section 11.11.3

The Unwanted emission from the EUT were measured according to the dictates PKPSD measurement procedure in section 11.11 of ANSI C63.10-2013.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB.

Test Settings:

Center frequency = the highest, middle and the lowest channels

- | | |
|---|-----------------------------|
| a) RBW = 100 kHz | b) VBW $\geq 3 \times$ RBW |
| c) Detector = peak | d) Sweep time = auto couple |
| e) Trace mode = max hold | |
| f) Allow trace to fully stabilize | |
| g) Use the peak marker function to determine the maximum amplitude level. | |

Limit :






Emission level < 20 dBc

Test results: Complies





- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest in-band spectral density. Therefore the applying equipment meets the requirement.

See next pages for actual measured spectrum plots.

Test mode : 1 Mbps



Test mode : 2 Mbps



4.5 Radiated Emission

Test Location

- ☒ 10 m SAC (test distance : ☐ 10 m, ☒ 3 m)
☒ 3 m SAC (test distance : 3 m)

Test Procedures

KDB 558074 - Section 8.5, 8.6
ANSI C63.10-2013 - Section 11.11, 11.12

- 1) In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- 2) In the frequency range above 30 MHz, Bi-Log Test Antenna(30 MHz to 1 GHz) and Horn Test Antenna(above 1 GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is carried from 1m to 4m above the ground to determine the maximum value of the field strength. The emissions levels at both horizontal and vertical polarizations should be tested.

Test Settings:

Frequency Range = 9 kHz ~ 1 GHz

- a) RBW = 100 kHz for $f < 1$ GHz, 9 kHz for $f < 30$ MHz
b) VBW $\geq$ RBW
c) Detector = CISPR Quasi-peak
d) Sweep time = auto couple

- Peak

Frequency Range = 1 GHz ~ 25 GHz (2.4 GHz 10th harmonic)

- a) RBW = 1 MHz
b) VBW $\geq 3 \times$ RBW
c) Detector = Peak
d) Sweep time = auto
e) Trace mode = max hold

- Average (duty cycle $\geq 98\%$)

Frequency Range = 1 GHz ~ 25 GHz (2.4 GHz 10th harmonic)

- a) RBW = 1 MHz
b) VBW $\geq 3 \times$ RBW
c) Detector = RMS
d) Sweep time = auto
e) Averaging type = power (i.e., RMS)
f) Trace mode = average (at least 100 traces)

- Average (duty cycle < 98%, duty cycle variations are less than $\pm 2\%$)

Frequency Range = 1 GHz ~ 25 GHz (2.4 GHz 10th harmonic)

a) RBW = 1 MHz

b) VBW $\geq 3 \times$ RBW

c) Detector = RMS

d) Sweep time = auto

e) Averaging type = power (i.e., RMS)

f) Trace mode = average (at least 100 traces)

A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 % duty cycle.

If power averaging (RMS) mode, then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.

Mode	Duty Cycle Factor
1 Mbps	0.65 dB
2 Mbps	2.32 dB

Limit :

FCC Part 15 § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	MHz	MHz	GHz
0.09-0.11	8.37626-8.38675	73-74.6	399.9-410	2690-2900	10.6-12.7
¹ 0.495-0.505	8.41425-8.41475	74.8-75.2	608-614	3260-3267	13.25-13.4
2.1735-2.1905	12.29-12.293	108-121.94	960-1240	3332-3339	14.47-14.5
4.125-4.128	12.51975-12.52025	123-138	1300-1427	3345.8-3358	15.35-16.2
4.17725-4.17775	12.57675-12.57725	149.9-150.05	1435-1626.5	3600-4400	17.7-21.4
4.20725-4.20775	13.36-13.41	156.52475-156.52525	1645.5-1646.5	4500-5150	22.01-23.12
6.215-6.218	16.42-16.423	156.7-156.9	1660-1710	5350-5460	23.6-24
6.26775-6.26825	16.69475-16.69525	162.0125-167.17	1718.8-1722.2	7250-7750	31.2-31.8
6.31175-6.31225	16.80425-16.80475	167.72-173.2	2200-2300	8025-8500	36.43-36.5
8.291-8.294	25.5-25.67	240-285	2310-2390	9000-9200	² Above 38.6
8.362-8.366	37.5-38.25	322-335.4	2483.5-2500	9300-9500	

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

§ 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

FCC Part 15 § 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits shown in Table 2. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.

Table 2. General Field Strength Limits for Licence-Exempt Transmitters

Frequency(MHz)	Field Strength uV/m@3m	Field Strength dBuV/m@3m	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705-30	30	-	30
30-88	100**	40	3
88-216	150**	43.5	3
216-960	200**	46	3
Above 960	500	54	3


** Except as provided in 15.209(g).fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72MHz, 76-88MHz, 174-216MHz, 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g.15.231 and 15.241.

Note :


- 1) For above 1 GHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
- 2) For above 1 GHz, limit field strength of harmonics : 54 dBuV/m@3m (AV) and 74 dBuV/m@3m (PK)

Test Setup:


- 1) For field strength of emissions from 9 kHz to 30 MHz



- 2) For field strength of emissions from 30 MHz to 1 GHz



3) For field strength of emissions above 1 GHz



Test results


1) 9 kHz to 30 MHz

Test mode : Transmitter (Worst Case)

The requirements are:

☒ Complies

Test Data



Frequency [MHz]	(P)	Reading [dBuV]	c.f [dB(1/m)]	Level [dB(uV/m)]	Limit [dB(uV/m)]	Margin [dB]
-----------------	-----	----------------	---------------	------------------	------------------	-------------

The emissions 9 kHz to 30 MHz were 20 dB lower than the limit.

Remark :

1. The unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(X axis) and the worst case was recorded.
2. Result = Reading + c.f(Correction factor)
3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator
4. This data is the Peak(PK) value.


2) 30 MHz to 1 GHz

Test mode : Transmitter (Worst Case)

The requirements are:

☒ Complies

Test Data



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	32.636	V	33.2	-7.1	26.1	40.0	13.9	101.0	54.0
2	121.071	V	36.9	-12.3	24.6	43.5	18.9	101.0	25.0
3	127.453	V	37.4	-11.9	25.5	43.5	18.0	101.0	25.0
4	137.318	V	36.8	-11.7	25.1	43.5	18.4	101.0	78.0
5	145.970	V	37.3	-11.8	25.5	43.5	18.0	101.0	101.0
6	847.386	H	30.5	4.7	35.2	46.0	10.8	100.0	293.0

Remark :



1. The unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(X axis) and the worst case was recorded.
2. Result = Reading + c.f(Correction factor)
3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator - Amp Gain


3) above 1 GHz

The requirements are:

☒ Complies

Test Data





Test mode : 1 Mbps

Low (2 402 MHz)

Frequency [MHz]	(P)	Reading PK [dBuV]	Reading AV [dBuV]	c.f [dB(1/m)]	Duty Cycle Factor [dB]	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]
-----------------	-----	-------------------	-------------------	---------------	------------------------	---------------------	---------------------	---------------------	---------------------	----------------	----------------

The emissions above 1 GHz were 20 dB lower than the limit.

Mid (2 440 MHz)

Frequency [MHz]	(P)	Reading PK [dBuV]	Reading AV [dBuV]	c.f [dB(1/m)]	Duty Cycle Factor [dB]	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]
4 879.59	H	45.7	-----	1.8	-----	47.5	-----	74.0	-----	26.5	-----
4 880.60	H	-----	32.8	1.8	0.65	-----	35.3	-----	54.0	-----	18.8
4 880.35	V	45.2	-----	1.8	-----	47.0	-----	74.0	-----	27.0	-----
4 880.24	V	-----	33.5	1.8	0.65	-----	36.0	-----	54.0	-----	18.1

High (2 480 MHz)

Frequency [MHz]	(P)	Reading PK [dBuV]	Reading AV [dBuV]	c.f [dB(1/m)]	Duty Cycle Factor [dB]	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]
4 960.23	H	46.8	-----	1.8	-----	48.6	-----	74.0	-----	25.4	-----
4 960.25	H	-----	33.9	1.8	0.65	-----	36.4	-----	54.0	-----	17.7
4 959.74	V	46.4	-----	1.8	-----	48.2	-----	74.0	-----	25.8	-----
4 960.13	V	-----	35	1.8	0.65	-----	37.5	-----	54.0	-----	16.6

Remarks

1. The unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(X axis) and the worst case was recorded.
2. Peak Result = Reading + c.f(Correction factor)
Average Result = Reading + c.f(Correction factor) + Duty Cycle Factor
3. Correction factor = Antenna factor + Cable loss - Amp Gain

Test mode : 2 Mbps

Low (2 402 MHz)

Frequency [MHz]	(P)	Reading PK [dBuV]	Reading AV [dBuV]	c.f [dB(1/m)]	Duty Cycle Factor [dB]	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]
-----------------	-----	-------------------	-------------------	---------------	------------------------	---------------------	---------------------	---------------------	---------------------	----------------	----------------

The emissions above 1 GHz were 20 dB lower than the limit.

Mid (2 440 MHz)

Frequency [MHz]	(P)	Reading PK [dBuV]	Reading AV [dBuV]	c.f [dB(1/m)]	Duty Cycle Factor [dB]	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]
-----------------	-----	-------------------	-------------------	---------------	------------------------	---------------------	---------------------	---------------------	---------------------	----------------	----------------

The emissions above 1 GHz were 20 dB lower than the limit.

High (2 480 MHz)

Frequency [MHz]	(P)	Reading PK [dBuV]	Reading AV [dBuV]	c.f [dB(1/m)]	Duty Cycle Factor [dB]	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]
4 961.19	H	45.7	-----	1.8	-----	47.5	-----	74.0	-----	26.5	-----
4 961.14	H	-----	32.7	1.8	2.32	-----	36.8	-----	54.0	-----	17.2
4 960.76	V	45.7	-----	1.8	-----	47.5	-----	74.0	-----	26.5	-----
4 959.47	V	-----	33.4	1.8	2.32	-----	37.5	-----	54.0	-----	16.5

Remarks

1. The unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(X axis) and the worst case was recorded.
2. Peak Result = Reading + c.f(Correction factor)
Average Result = Reading + c.f(Correction factor) + Duty Cycle Factor
3. Correction factor = Antenna factor + Cable loss - Amp Gain

4.6 AC Conducted Emissions

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Procedures

ANSI C63.10-2013 - Section 6.2

The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m.

Amplitude measurements were performed with a quasi-peak detector and an average detector.

Limit

- 15.207(a)

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average**
0.15 ~ 0.5	66 to 56*	56 to 46*
0.5 ~ 5	56	46
5 ~ 30	60	50

* The level decreases linearly with the logarithm of the frequency.

** A linear average detector is required.

Test Results


The requirements are:

☒ Complies

Test Data

[LINE]

(with EC)3CE_Class B_L1



Final Result 1


Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.163500	52.6	1000.0	9.000	On	L1	9.9	12.7	65.3
0.199500	49.6	1000.0	9.000	On	L1	10.0	14.0	63.6
0.249000	45.5	1000.0	9.000	On	L1	9.7	16.3	61.8
0.285000	42.8	1000.0	9.000	On	L1	9.8	17.9	60.7
0.366000	37.2	1000.0	9.000	On	L1	10.0	21.4	58.6
0.438000	32.7	1000.0	9.000	On	L1	10.0	24.4	57.1

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.177000	26.5	1000.0	9.000	On	L1	10.0	28.1	54.6
0.217500	24.6	1000.0	9.000	On	L1	9.9	28.3	52.9
0.235500	23.0	1000.0	9.000	On	L1	9.8	29.3	52.3
0.406500	18.7	1000.0	9.000	On	L1	10.0	29.1	47.7
0.523500	28.9	1000.0	9.000	On	L1	10.0	17.1	46.0
0.541500	25.9	1000.0	9.000	On	L1	10.0	20.1	46.0

[NEUTRAL]

(with EC)3CE_Class B_N



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	54.1	1000.0	9.000	On	N	9.9	11.9	66.0
0.186000	50.8	1000.0	9.000	On	N	9.9	13.4	64.2
0.235500	46.4	1000.0	9.000	On	N	9.8	15.8	62.3
0.285000	42.8	1000.0	9.000	On	N	9.9	17.8	60.7
0.375000	37.4	1000.0	9.000	On	N	10.1	20.9	58.4
0.442500	33.1	1000.0	9.000	On	N	10.1	23.9	57.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.168000	23.7	1000.0	9.000	On	N	9.9	31.4	55.1
0.186000	21.2	1000.0	9.000	On	N	9.9	33.0	54.2
0.235500	20.1	1000.0	9.000	On	N	9.8	32.2	52.3
0.285000	15.4	1000.0	9.000	On	N	9.9	35.3	50.7
0.528000	18.8	1000.0	9.000	On	N	10.1	27.2	46.0
0.550500	12.2	1000.0	9.000	On	N	10.1	33.8	46.0

APPENDIX A – Test Equipment Used For Tests

	Name of Equipment	Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date
1	Signal Analyzer	Agilent	N9020A	MY50200512	2021-04-07	2022-04-07
2	Signal Generator	Rohde & Schwarz	SMB100A	175528	2021-04-12	2022-04-12
3	EMI Test Receiver	Rohde & Schwarz	ESCI7	100814	2021-10-20	2022-10-20
4	BILOG ANTENNA	TESEQ	CBL6111D	58490	2021-03-03	2023-03-03
5	Active Loop Antenna	SCHWARZBECK	FMZB 1513	1513-126	2020-05-20	2022-05-20
6	6dB Attenuator	R&S	DNF	272.4110.50-2	2021-10-22	2022-10-22
7	ATTENUATOR	PASTERNAK	PE7047-6	NONE	2021-02-26	2022-02-26
8	6dB Attenuator	BIRD	5W 6dB	1744	2020-12-16	2021-12-16
9	AMPLIFIER	SONOMA	310	291721	2021-01-22	2022-01-22
10	EMI Test Receiver	Rohde & Schwarz	ESU40	100336	2021-01-12	2022-01-12
11	Preamplifier	Agilent	8449B	3008A01504	2020-12-17	2021-12-17
12	Horn Antenna	ETS-Lindgren	3117	00140387	2021-02-23	2022-02-23
13	Horn Antenna	SCHWARZBECK	BBHA9170	00967	2021-05-25	2022-05-25
14	Low Noise Amplifier	TESTEK	TK-PA1840H	200115-L	2021-05-21	2022-05-21
15	Band Reject Filter	Micro Tronics	BRM50702	G233	2021-01-14	2022-01-14
16	LISN	Rohde & Schwarz	ENV216	101236	2021-10-20	2022-10-20
17	EMI Test Receiver	Rohde & Schwarz	ESC13	100032	2021-01-15	2022-01-15

	Cable	Manufacturer	Model No.	Serial No.	Check Date
1	RF Cable (Conducted)	Junkosha Inc.	MWX221	2008S259	2021-10-22
2	RF Cable (Line Conducted)	Canare Corporation	L-5D2W	N/A	2021-10-20
3	RF Cable (9kHz-30MHz Radiated)	HUBER+SUHNER	NA	NA	2021-02-20
4	RF Cable (9kHz-1GHz Below Radiated)	HUBER+SUHNER	SUCOFLEX 104	MY27558/4	2021-02-20
5	RF Cable (30MHz-1GHz Below Radiated)	HUBER+SUHNER	SUCOFLEX 104	N/A	2021-02-20
6	RF Cable (1GHz-18GHz Radiated)	HUBER+SUHNER	SUCOFLEX 102	MY2374/2	2021-02-20
7	RF Cable (1GHz-40GHz Radiated)	HUBER+SUHNER	SUCOFLEX 102	MY4728/2	2021-02-20
8	RF Cable (18GHz-40GHz Radiated)	HUBER+SUHNER	SUCOFLEX 102	803010/2	2021-10-27