TEST REPORT

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2018-01334

1. Client

◦ Name : KAONMEDIA Co., Ltd.

◦ Address : KAONMEDIA Building, 884-3 Seongnam-daero, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea

◦ Date of Receipt : 2018-02-14

2. Manufacturer

◦ Name : KAONMEDIA Co., Ltd.

◦ Address : KAONMEDIA Building, 884-3 Seongnam-daero, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea

3. Use of Report : For FCC Certification

4. Test Sample / Model: Layer3 TV / Client VM3000C

5. Date of Test : 2018-05-08 to 2018-05-16

6. Test Standard(method) used : FCC 47 CFR part 15 subpart C 15.247

7. Testing Environment: Temp.: (23 ± 5) ℃, Humidity: (50 ± 3) % R.H.

8. Test Results : Compliance

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full.

Affirmation	Tested by Ji-Hye Kim: (Signature)	Technical Manager Won-Jae, Hwang: (Signature)

2018-05-18

Republic of KOREA **CTK Co., Ltd.**

REPORT REVISION HISTORY

Date	Revision	Page No
2018-05-18	Issued (CTK-2018-01334)	all

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.

CONTENTS

1. General Product Description 4
1.1 Client Information 4
1.2 Product Information 4
1.3 Peripheral Devices 4
2. Facility and Accreditations 5
2.1 Test Facility 5
2.2 Laboratory Accreditations and Listings 5
2.3 Calibration Details of Equipment Used for Measurement 5
3. Test Specifications 6
3.1 Standards 6
3.2 Mode of operation during the test 7
3.3 Device Modifications 7
3.4 Maximum Measurement Uncertainty 7
3.5 Test Software 7
4. Technical Characteristic Test 8
4.1 6dB Bandwidth 8
4.2 Maximum peak Conducted Output Power 14
4.3 Transmitter Power Spectral Density 19
4.4 Band Edge & Conducted Spurious emission 24
4.5 Field Strength of Harmonics 27
4.6 AC Conducted Emissions 37
APPENDIX A – Test Equipment Used For Tests 40

1. General Product Description

1.1 Client Information

Company	KAONMEDIA Co., Ltd.
Contact Point	KAONMEDIA Building, 884-3 Seongnam-daero, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea
Contact Person	Name : Kim tae-Sung E-mail : kkam@kaonmedia.com Tel : +82-31-724-8861

1.2 Product Information

FCC ID	WQTVM3000C
Product Description	Layer3 TV
Model name	Client VM3000C
Variant Model name	-
Operating Frequency	2 405 MHz – 2 480 MHz
RF Output Power	-2.69 dBm (0.54 mW)
Antenna Specification	Antenna type : PCB Antenna Peak Gain : 3.25 dBi
Type of Modulation	DSSS
Power Source	DC 12 V (Adapter)
Hardware Rev	V1.0
Software Rev	V1.0

1.3 Peripheral Devices

Device	Manufacturer	Model No.	Serial No.
Note Computer	HP	15-bs563TU	CND7253R6N
AC/DC Adapter	HP	HSTNN-CA40	-
AD/DC Adapter	I.T.E POWER SUPPLY ALSO LISTED	SQUS50-120333	-

2. Facility and Accreditations

2.1 Test Facility

The measurement facility is located at (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yong-in-si, Gyeonggi-do, Korea.

2.2 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Registration Number	Logo
USA	**FCC**	FCC Part 15 & 18 EMI (Electromagnetic Interference / Emission)	805871	
CANADA	**ISED**	ISED EMI (3/10m test site)	8737A-2	
JAPAN	**VCCI**	VCCI V-3 EMI (Electromagnetic Interference / Emission)	C-986 T-1843 R-3627 G-387	
KOREA	**MSIP**	EMI (Electromagnetic Interference / Emission) EMS (Electromagnetic Susceptibility / Immunity)	KR0025	

2.3 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

3. Test Specifications

3.1 Standards

FCC Part Section(s)	Requirement(s)	Limit	Status (Note 1)	Test Condition
15.247(a)	6 dB Bandwidth	> 500 kHz	C	Conducted
15.247(b)	Maximum Output Power	< 1 Watt	C	
15.247(d)	Conducted Spurious emission	> 20 dBc	C	
15.247(d)	Band Edge	> 20 dBc	C	
15.247(e)	Transmitter Power Spectral Density	< 8 dBm @ 3 kHz	C	
15.209	Field Strength of Harmonics	15.209(a)	C	Radiated
15.207	AC Conducted Emissions	15.207(a)	C	Line Conducted

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

Note 3: The sample was tested according to the following specification: FCC Part 15.247, ANSI C63.10-2013

Note 4: The tests were performed according to the method of measurements prescribed in KDB No.558074.

3.2 Mode of operation during the test

The EUT is operated in a manner representative of the typical of the equipments.
During at testing, system components were manipulated within the confines of typical usage to maximize each emission. All modulation modes were tests.
The results are only attached worst cases.

Test Frequency

Lowest channel	Middle channel	Highest channel
2 405 MHz	2 445 MHz	2 480 MHz

Test mode

Modulation	Duty Cycle
DSSS	100%

3.3 Device Modifications

The following modifications were necessary for compliance:

Not applicable

3.4 Maximum Measurement Uncertainty

The value of the measurement uncertainty for the measurement of each parameter.
Coverage factor k = 2, Confidence levels of 95 %

Description	Uncertainty
Conducted RF Output Power	± 1.5 dB
Power Spectral Density	± 1.5 dB
Occupied Bandwidth	± 0.1 MHz
Unwanted Emission(conducted)	± 3.0 dB
Radiated Emissions (f ≤ 1 GHz)	± 4.0 dB
Radiated Emissions (f > 1 GHz)	± 5.0 dB

3.5 Test Software

Conducted Test	Ics Pro Ver. 6.0.3
Radiated Test	TOYO EMI software EP5RE Ver. 5.1.0
Line Conducted Test	ESCI7, ESCI3 : EMC32 Ver. 8.50.0 ESR7 : EMC32 Ver. 8.53.0

4. Technical Characteristic Test

4.1 6dB Bandwidth

Test Procedures

ANSI C63.10-2013 6.9.2

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Procedures

ANSI C63.10-2013 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.
Use the 99% power bandwidth function of the instrument and report the measured bandwidth.

Test Settings :

Center frequency = the highest, middle and the lowest channels

a) RBW = 100 kHz
b) VBW ≥ 3 x RBW
c) Detector = peak
d) Trace mode = Max hold
e) Sweep = auto couple
f) Allow trace to fully stabilize
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Minimum Standard :

6 dB Bandwidth	>	500kHz

Test Data :

ANT0

Frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Result
2 405	1.55	2.22	Complies
2 445	1.57	2.21	Complies
2 480	1.59	2.23	Complies

ANT1

Frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Result
2 405	1.59	2.23	Complies
2 445	1.58	2.24	Complies
2 480	1.58	2.23	Complies

See next pages for actual measured spectrum plots.

ANT0

Low channel (2 405 MHz)



Middle channel (2 445MHz)



High channel (2 480 MHz)



ANT1

Low channel (2 405 MHz)



Middle channel (2 445MHz)



High channel (2 480 MHz)



4.2 Maximum peak Conducted Output Power

Test Procedures

Procedure 9.1.1 in KDB 558074

Maximum Peak Output Power from the EUT were measured according to the dictates power measurement procedure in section 9.1.1 of KDB 558074.

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Test Settings:

Center frequency = the highest, middle and the lowest channels

a) RBW ≥ DTS bandwidth

b) VBW ≥ 3 x RBW

c) span ≥ 3 x RBW

d) Sweep time = auto couple

e) Detector = peak

f) Trace mode= max hold

g) Allow trace to fully stabilize

h) Use peak marker function to determine the peak amplitude level.

Limit :

Maximum Output Power < 1 W (30 dBm)

Test Data :

ANT0

Frequency (MHz)	Maximum peak Conducted Output Power		
	Output power (dBm)	Output power (mW)	Result
2 405	-2.88	0.52	Complies
2 445	-2.69	0.54	Complies
2 480	-2.79	0.53	Complies

ANT1

Frequency (MHz)	Maximum peak Conducted Output Power		
	Output power (dBm)	Output power (mW)	Result
2 405	-6.10	0.25	Complies
2 445	-5.95	0.25	Complies
2 480	-5.97	0.25	Complies

See next pages for actual measured spectrum plots.

ANT0

Low channel (2 405 MHz)



Middle channel (2 445 MHz)



High channel (2 480 MHz)



ANT1

Low channel (2 405 MHz)



Middle channel (2 445 MHz)



High channel (2 480 MHz)



4.3 Transmitter Power Spectral Density

Test Procedures

Procedure 10.2 in KDB 558074, Method Peak PSD

Power Spectral Density from the EUT were measured according to the dictates PKPSD measurement procedure in 10.2 of KDB 558074.
This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance.

Test Settings:

Center frequency = the highest, middle and the lowest channels

a) RBW : 3 kHz ≤ RBW ≤ 100 kHz

b) VBW ≥ 3 x RBW

c) span ≥ 1.5 x DTS bandwidth

d) Sweep time = auto couple

e) Detector = peak

f) Trace mode= max hold

g) Allow trace to fully stabilize

h) Use the peak marker function to determine the maximum amplitude level within the RBW.

Limit :

Power Spectral Density < 8dBm @ 3 kHz BW

Test Data :

ANT0

Frequency (MHz)	Power Spectral Density	
	dBm	Result
2 405	-17.98	Complies
2 445	-17.48	Complies
2 480	-17.62	Complies

ANT1

Frequency (MHz)	Power Spectral Density	
	dBm	Result
2 405	-20.67	Complies
2 445	-20.17	Complies
2 480	-21.05	Complies

See next pages for actual measured spectrum plots.

ANT0

Low channel (2 405 MHz)



Middle channel (2 445 MHz)



High channel (2 480 MHz)



ANT1

Low channel (2 405 MHz)



Middle channel (2 445 MHz)



High channel (2 480 MHz)



4.4 Band Edge & Conducted Spurious emission

Test Procedures

The Unwanted emission from the EUT were measured according to the dictates PKPSD measurement procedure in section 11.11 of ANSI C63.10-2013.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Test Settings:

Center frequency = the highest, middle and the lowest channels

a) RBW = 100 kHz
b) VBW ≥ 3 x RBW
c) Detector = peak
d) Sweep time = auto couple
e) Trace mode= max hold
f) Allow trace to fully stabilize
g) Use the peak marker function to determine the maximum amplitude level.

Limit :

Emission level	<	20 dBc

Test results: Complies

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest in-band spectral density. Therefore the applying equipment meets the requirement.

See next pages for actual measured spectrum plots.

Agilent Spectrum Analyzer - Swept SA
Center Freq 2.400000000 GHz
Mkr1 2.404 73 GHz
-6.081 dBm
Ref 6.00 dBm
Center 2.400000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 10.00 MHz
Sweep 1.000 ms (1001 pts)

Agilent Spectrum Analyzer - Swept SA
Center Freq 2.483500000 GHz
Mkr1 2.479 77 GHz
-6.157 dBm
Ref 6.00 dBm
Center 2.483500 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 10.00 MHz
Sweep 1.000 ms (1001 pts)

Agilent Spectrum Analyzer - Swept SA
Input Mech Atten 12 dB
Mkr1 4.799 GHz
-48.068 dBm
Ref 2.57 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.386 s (1001 pts)


Agilent Spectrum Analyzer - Swept SA
Input Mech Atten 12 dB
Mkr1 4.899 GHz
-47.492 dBm
Ref 2.57 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.386 s (1001 pts)


Agilent Spectrum Analyzer - Swept SA
Start Freq 30.000000 MHz
Mkr1 4.949 GHz
-46.809 dBm
Ref 2.57 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.386 s (1001 pts)

ANT0


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.400000000 GHz
Mkr1 2.404 73 GHz
-9.225 dBm
Ref 6.00 dBm
Center 2.400000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 10.00 MHz
Sweep 1.000 ms (1001 pts)

Agilent Spectrum Analyzer - Swept SA
Center Freq 2.483500000 GHz
Mkr1 2.479 76 GHz
-8.699 dBm
Ref 6.00 dBm
Center 2.483500 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 10.00 MHz
Sweep 1.000 ms (1001 pts)


Agilent Spectrum Analyzer - Swept SA
Start Freq 30.000000 MHz
Mkr1 4.799 GHz
-42.493 dBm
Ref 0.57 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.386 s (1001 pts)


Agilent Spectrum Analyzer - Swept SA
Start Freq 30.000000 MHz
Mkr1 4.899 GHz
-40.290 dBm
Ref 0.57 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.386 s (1001 pts)


Agilent Spectrum Analyzer - Swept SA
Start Freq 30.000000 MHz
Mkr1 4.949 GHz
-40.150 dBm
Ref 0.57 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.386 s (1001 pts)

ANT1

4.5 Field Strength of Harmonics

Test Location

☒ 10 m SAC (test distance : ☐ 10 m, ☒ 3 m)
☒ 3 m SAC (test distance : 3 m)

Test Procedures

1) In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
2) In the frequency rage above 30 MHz, Bi-Log Test Antenna(30 MHz to 1 GHz) and Horn Test Antenna(above 1 GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is carried from 1m to 4m above the ground to determine the maximum value of the field strength. The emissions levels at both horizontal and vertical polarizations should be tested.

Test Settings:

Frequency Range = 9 kHz ~ 1 GHz

a) RBW = 100 kHz for f < 1 GHz, 9 kHz for f < 30 MHz

b) VBW ≥ RBW

c) Detector = CISPR Quasi-peak

d) Sweep time = auto couple

- Peak

Frequency Range = 1 GHz ~ 25 GHz (2.4 GHz 10th harmonic)

a) RBW = 1 MHz

b) VBW ≥ 3 x RBW

c) Detector = Peak

d) Sweep time = auto

e) Trace mode = max hold

- Average (duty cycle ≥ 98%)

Frequency Range = 1 GHz ~ 25 GHz (2.4 GHz 10th harmonic)

a) RBW = 1 MHz

b) VBW ≥ 3 x RBW

c) Detector = RMS

d) Sweep time = auto

e) Averaging type = power (i.e., RMS)

f) Trace mode = average (at least 100 traces)

- Average (duty cycle < 98%, duty cycle variations are less than ±2%)

Frequency Range = 1 GHz ~ 25 GHz (2.4 GHz 10th harmonic)

a) RBW = 1 MHz

b) VBW ≥ 3 x RBW

c) Detector = RMS

d) Sweep time = auto

e) Averaging type = power (i.e., RMS)

f) Trace mode = average (at least 100 traces)

A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 % duty cycle.
If power averaging (RMS) mode, then the applicable correction factor is
10 log(1/x), where x is the duty cycle.

Limit :

FCC Part 15 § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	MHz	MHz	GHz
0.09-0.11	8.37626-8.38675	73-74.6	399.9-410	2690-2900	10.6-12.7
[1]0.495-0.505	8.41425-8.41475	74.8-75.2	608-614	3260-3267	13.25-13.4
2.1735-2.1905	12.29-12.293	108-121.94	960-1240	3332-3339	14.47-14.5
4.125-4.128	12.51975-12.52025	123-138	1300-1427	3345.8-3358	15.35-16.2
4.17725-4.17775	12.57675-12.57725	149.9-150.05	1435-1626.5	3600-4400	17.7-21.4
4.20725-4.20775	13.36-13.41	156.52475-156.52525	1645.5-1646.5	4500-5150	22.01-23.12
6.215-6.218	16.42-16.423	156.7-156.9	1660-1710	5350-5460	23.6-24
6.26775-6.26825	16.69475-16.69525	162.0125-167.17	1718.8-1722.2	7250-7750	31.2-31.8
6.31175-6.31225	16.80425-16.80475	167.72-173.2	2200-2300	8025-8500	36.43-36.5
8.291-8.294	25.5-25.67	240-285	2310-2390	9000-9200	[2]Above 38.6
8.362-8.366	37.5-38.25	322-335.4	2483.5-2500	9300-9500	

[1] Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

[2] Above 38.6

§ 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown is Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

FCC Part 15 § 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Frequency(MHz)	Field Strength uV/m@3m	Field Strength dBuV/m@3m	Deasurement Distance (meters)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705-30	30	-	30
30-88	100**	40	3
88-216	150**	43.5	3
216-960	200**	46	3
Above 960	500	54	3

** Except as provided in 15.209(g).fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72MHz, 76-88MHz, 174-216MHz, 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g.15.231 and 15.241.

Note :

1) For above 1 GHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
2) For above 1 GHz, limit field strength of harmonics : 54 dBuV/m@3m (AV) and 74 dBuV/m@3m (PK)
3) For measurement above 1GHz, the resolution bandwidth is set to 1 MHz and video bandwidth is set to 1 MHz for peak measurement and 10 Hz for average measurement.(Duty Cycle is > 98%,)

Test Setup:

1) For field strength of emissions from 9 kHz to 30 MHz



2) For field strength of emissions from 30 MHz to 1 GHz



3) For field strength of emissions above 1 GHz



Test results

1) 9 kHz to 30 MHz

The requirements are:
☒ Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
-	-	-	See note

Note :
The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = 40 log (specific distance / test distance) (dB)

2) 30 MHz to 1 GHz

Test mode : ANT0_Middle Channel(Worst Case)

The requirements are:
☒ Complies

Test Data



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	43.826	V	51.0	-12.5	38.5	40.0	1.5	99.8	16.5	
2	149.537	V	54.9	-17.4	37.5	43.5	6.0	99.8	136.5	
3	149.537	H	52.3	-17.4	34.9	43.5	8.6	99.8	258.8	
4	201.358	V	54.5	-14.1	40.4	43.5	3.1	99.8	190.5	
5	201.467	H	54.3	-14.1	40.2	43.5	3.3	99.8	170.4	
6	800.021	V	44.2	-5.4	38.8	46.0	7.2	99.8	332.7	

Remark :
1. The EUT was tested in three orientations in order to determine that "Z axis" was the worst case.
2. Result = Reading + c.f(Correction factor)
3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator - Amp Gain

3) above 1 GHz

ANT0

The requirements are:
☒ Complies

Test Data

Low (2 405 MHz)

Frequency [MHz]	(P)	Limit AV [dBuV/m]	Limit PK [dBuV/m]	Result AV [dBuV/m]	Result PK [dBuV/m]	Margin AV [dB]	Margin PK [dB]
1 094.00	H	54.00	74.00	41.40	44.30	12.60	29.70
1 094.00	V	54.00	74.00	37.90	41.30	16.10	32.70
3 875.00	H	54.00	74.00	36.50	43.90	17.50	30.10
3 875.00	V	54.00	74.00	39.70	45.00	14.30	29.00
4 810.00	H	54.00	74.00	37.69	45.90	16.31	28.10
4 810.00	V	54.00	74.00	42.10	48.50	11.90	25.50
7 215.00	H	54.00	74.00	40.10	49.20	13.90	24.80
7 215.00	V	54.00	74.00	38.30	47.90	15.70	26.10

Mid (2 445 MHz)

Frequency [MHz]	(P)	Limit AV [dBuV/m]	Limit PK [dBuV/m]	Result AV [dBuV/m]	Result PK [dBuV/m]	Margin AV [dB]	Margin PK [dB]
1 094.00	H	54.00	74.00	41.30	44.40	12.70	29.60
1 094.00	V	54.00	74.00	37.80	41.40	16.20	32.60
3 875.00	H	54.00	74.00	36.80	43.80	17.20	30.20
3 875.00	V	54.00	74.00	39.50	45.30	14.50	28.70
4 890.00	H	54.00	74.00	37.80	46.00	16.20	28.00
4 890.00	V	54.00	74.00	40.20	47.70	13.80	26.30
7 335.00	H	54.00	74.00	40.20	48.50	13.80	25.50
7 335.00	V	54.00	74.00	37.90	47.50	16.10	26.50

High (2 480 MHz)

Frequency [MHz]	(P)	Limit AV [dBuV/m]	Limit PK [dBuV/m]	Result AV [dBuV/m]	Result PK [dBuV/m]	Margin AV [dB]	Margin PK [dB]
1 094.00	H	54.00	74.00	41.20	44.10	12.80	29.90
1 094.00	V	54.00	74.00	37.80	41.20	16.20	32.80
3 875.00	H	54.00	74.00	37.00	44.00	17.00	30.00
3 875.00	V	54.00	74.00	39.60	45.40	14.40	28.60
4 960.00	H	54.00	74.00	36.90	45.50	17.10	28.50
4 960.00	V	54.00	74.00	40.80	48.00	13.20	26.00
7 440.00	H	54.00	74.00	39.20	48.70	14.80	25.30
7 440.00	V	54.00	74.00	39.20	47.40	14.80	26.60
2 483.50	H	54.00	74.00	52.60	61.10	1.40	12.90
2 483.50	V	54.00	74.00	51.00	59.40	3.00	14.60

Remarks

1. The EUT was tested in three orientations in order to determine that "Z axis" was the worst case.

ANT1

The requirements are:
☒ Complies

Test Data

Low (2 405 MHz)

Frequency [MHz]	(P)	Limit AV [dBuV/m]	Limit PK [dBuV/m]	Result AV [dBuV/m]	Result PK [dBuV/m]	Margin AV [dB]	Margin PK [dB]
1 094.00	H	54.00	74.00	41.00	44.10	13.00	29.90
1 094.00	V	54.00	74.00	37.90	40.90	16.10	33.10
3 875.00	H	54.00	74.00	37.10	44.80	16.90	29.20
3 875.00	V	54.00	74.00	39.50	45.50	14.50	28.50
4 810.00	H	54.00	74.00	44.40	50.80	9.60	23.20
4 810.00	V	54.00	74.00	40.70	48.70	13.30	25.30
7 215.00	H	54.00	74.00	38.00	47.50	16.00	26.50
7 215.00	V	54.00	74.00	37.20	47.20	16.80	26.80

Mid (2 445 MHz)

Frequency [MHz]	(P)	Limit AV [dBuV/m]	Limit PK [dBuV/m]	Result AV [dBuV/m]	Result PK [dBuV/m]	Margin AV [dB]	Margin PK [dB]
1 094.00	H	54.00	74.00	40.80	44.00	13.20	30.00
1 094.00	V	54.00	74.00	37.80	41.00	16.20	33.00
3 875.00	H	54.00	74.00	36.90	44.90	17.10	29.10
3 875.00	V	54.00	74.00	39.70	45.30	14.30	28.70
4 890.00	H	54.00	74.00	45.60	51.90	8.40	22.10
4 890.00	V	54.00	74.00	38.60	47.30	15.40	26.70
7 335.00	H	54.00	74.00	38.30	48.90	15.70	25.10
7 335.00	V	54.00	74.00	37.10	47.10	16.90	26.90

High (2 480 MHz)

Frequency [MHz]	(P)	Limit AV [dBuV/m]	Limit PK [dBuV/m]	Result AV [dBuV/m]	Result PK [dBuV/m]	Margin AV [dB]	Margin PK [dB]
1 094.00	H	54.00	74.00	41.30	44.40	12.70	29.60
1 094.00	V	54.00	74.00	38.00	41.20	16.00	32.80
3 875.00	H	54.00	74.00	36.70	44.60	17.30	29.40
3 875.00	V	54.00	74.00	39.80	45.10	14.20	28.90
4 960.00	H	54.00	74.00	46.30	51.20	7.70	22.80
4 960.00	V	54.00	74.00	35.90	45.20	18.10	28.80
7 440.00	H	54.00	74.00	37.30	47.40	16.70	26.60
7 440.00	V	54.00	74.00	36.60	48.20	17.40	25.80
2 483.50	H	54.00	74.00	51.10	58.60	2.90	15.40
2 483.50	V	54.00	74.00	49.50	56.80	4.50	17.20

Remarks

1. The EUT was tested in three orientations in order to determine that "Z axis" was the worst case.

4.6 AC Conducted Emissions

Frequency Range of Measurement
150 kHz to 30 MHz

Instrument Settings
IF Band Width: 9 kHz

Test Procedures

Module has been tested by mounting the End product(Printer).
The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m.
Amplitude measurements were performed with a quasi-peak detector and an average detector.

Limit
- **15.207(a)**

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average**
0.15 ~ 0.5	66 to 56*	56 to 46*
0.5 ~ 5	56	46
5 ~ 30	60	50

* The level decreases linearly with the logarithm of the frequency.
** A linear average detector is required.

Test Results

The requirements are:
☒ Complies

Test Data

[LINE]

3CE_Class B_L1



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.163500	43.6	1000.0	9.000	On	L1	9.8	21.7	65.3
0.190500	43.6	1000.0	9.000	On	L1	9.8	20.5	64.0
0.348000	38.5	1000.0	9.000	On	L1	9.9	20.5	59.0
0.366000	40.2	1000.0	9.000	On	L1	9.9	18.4	58.6
0.505500	45.7	1000.0	9.000	On	L1	10.0	10.3	56.0
4.947000	30.1	1000.0	9.000	On	L1	9.8	25.9	56.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.195000	34.1	1000.0	9.000	On	L1	9.8	19.7	53.8
0.339000	30.5	1000.0	9.000	On	L1	9.9	18.7	49.2
0.429000	30.6	1000.0	9.000	On	L1	10.0	16.7	47.3
0.505500	41.4	1000.0	9.000	On	L1	10.0	4.6	46.0
0.942000	22.4	1000.0	9.000	On	L1	9.8	23.6	46.0
17.601000	28.6	1000.0	9.000	On	L1	10.0	21.4	50.0

[NEUTRAL]

3CE_Class B_N



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.172500	46.0	1000.0	9.000	On	N	9.8	18.9	64.8
0.226500	36.7	1000.0	9.000	On	N	9.8	25.8	62.6
0.348000	38.3	1000.0	9.000	On	N	9.9	20.7	59.0
0.366000	39.7	1000.0	9.000	On	N	9.9	18.9	58.6
0.505500	45.0	1000.0	9.000	On	N	9.9	11.0	56.0
20.067000	34.0	1000.0	9.000	On	N	10.1	26.0	60.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.217500	32.5	1000.0	9.000	On	N	9.8	20.4	52.9
0.343500	31.1	1000.0	9.000	On	N	9.9	18.0	49.1
0.393000	26.6	1000.0	9.000	On	N	9.9	21.4	48.0
0.505500	41.3	1000.0	9.000	On	N	9.9	4.7	46.0
0.910500	27.4	1000.0	9.000	On	N	9.8	18.6	46.0
17.484000	29.4	1000.0	9.000	On	N	10.1	20.6	50.0

APPENDIX A – Test Equipment Used For Tests

	Name of Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Signal Analyzer	Agilent	N9020A	MY48011598	2017-11-01	2018-11-01
2	Signal Generator	Rohde & Schwarz	SMB100A	175528	2017-11-01	2018-11-01
3	EMI Test Receiver	Rohde & Schwarz	ESCI7	100814	2017-10-25	2018-10-25
4	Bilog Antenna	Schaffner	CBL6111C	2551	2018-05-10	2020-05-10
5	Active Loop Antenna	SCHWARZBECK	FMZB 1513	1513-125	2018-05-02	2020-05-02
6	6dB Attenuator	R&S	DNF	272.4110.50-2	2017-10-25	2018-10-25
7	AMPLIFIER	SONOMA	310	291721	2018-02-02	2019-02-02
8	EMI Test Receiver	Rohde & Schwarz	ESU40	100336	2018-02-01	2019-02-01
9	Preamplifier	Agilent	8449B	3008A02011	2017-11-30	2018-11-30
10	Horn Antenna	ETS-Lindgren	3116	00062504	2017-12-04	2019-12-04
11	Horn Antenna	ETS-Lindgren	3117	00154525	2017-02-17	2019-02-17
12	Band Reject Filter	Micro Tronics	BRM50702	G233	2018-01-26	2019-01-26
13	LISN	Rohde & Schwarz	ENV216	101235	2018-01-31	2019-01-31
14	Singnal Canditioning Unit	R&S	SCU-40	10023	2017-11-01	2018-11-01