



FCC RADIO TEST REPORT

FCC ID : WR92221123114
Equipment : thermostat
Brand Name : ecobee
Model name : ECB402
Applicant : ecobee Inc.
207 Queens Quay West, Suite 600, Toronto, ON, Canada
Manufacturer : ecobee Inc.
207 Queens Quay West, Suite 600, Toronto, ON, Canada
Standard : FCC Part 15 Subpart E §15.407

The product was received on Jan. 17, 2019 and testing was started from Feb. 13, 2019 and completed on Mar. 29, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	9
2.6 Measurement Results Explanation Example.....	10
3 Test Result	11
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	11
3.2 Maximum Conducted Output Power Measurement	14
3.3 Power Spectral Density Measurement	15
3.4 Unwanted Emissions Measurement.....	17
3.5 AC Conducted Emission Measurement.....	22
3.6 Automatically Discontinue Transmission	24
3.7 Antenna Requirements.....	25
4 List of Measuring Equipment.....	26
5 Uncertainty of Evaluation.....	28
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	



History of this test report

Report No.	Version	Description	Issued Date
FR911708F	01	Initial issue of report	Apr. 18, 2019

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403 (i)	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.407 (a)	Maximum Conducted Output Power	Pass	-
3.3	15.407 (a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	Under limit 3.27 dB at 11490.000 MHz
3.5	15.207	AC Conducted Emission	Pass	Under limit 21.76 dB at 3.984 MHz
3.6	15.407 (c)	Automatically Discontinue Transmission	Pass	-
3.7	15.203 & 15.407 (a)	Antenna Requirement	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Natasha Hsieh



1 General Description

1.1 Product Feature of Equipment Under Test

Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, and Proprietary Sensor

Product Specification subjective to this standard	
Antenna Type	WLAN: Ceramic Chip Antenna Bluetooth: FPC Antenna Proprietary Sensor: IFA Meander Printed PCB Type Antenna

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH13-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No. TW1190 and TW0007



1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "[#]" were 802.11ac VHT80.

2.2 Test Mode


Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20 (Covered by HT20)	MCS0
802.11ac VHT40 (Covered by HT40)	MCS0
802.11ac VHT80	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : WLAN (5GHz) Link + Bluetooth Link + Sub-gigahertz on + Infrared on + PEK with Adapter

Ch. #		Band IV : 5725-5850 MHz			
		802.11a	802.11n HT20	802.11n HT40	802.11ac VHT80
L	Low	149	149	151	-
M	Middle	157	157	-	155
H	High	165	165	159	-

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
2.	Adapter	Jameco	ADU240050	FCC DoC	N/A	AC I/P: Unshielded, 6m
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

2.5 EUT Operation Test Setup

The RF test items, utility "Putty" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures



1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.


3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.





Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures


The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


- Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 300 kHz.
 - Set VBW $\geq$ 1 MHz.
 - Number of points in sweep $\geq$ 2 Span / RBW.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.
-
1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \quad \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

- (i) Section 15.407(b)(1) to (b)(3) specify the unwanted emission limits for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.³
- (ii) Section 15.407(b)(4) specifies the unwanted emission limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are in terms of a Peak detector. An alternative to the band emissions mask is specified in Section 15.407(b)(4)(ii). The alternative limits are based on the highest antenna gain specified in the filing. There are also marketing and importation restrictions for the devices using the alternative limit.⁴

Note 3: An out-of-band emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit.

Note 4: Only devices with antenna gains of 10 dBi or less may be approved using the emission limits specified in Section 15.247(d) till March 2, 2018; all other devices operating in this band must use the mask specified in Section 15.407(b)(4)(i).

3.4.2 Measuring Instruments


See list of measuring equipment of this test report.

3.4.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
(1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C and D.

3.4.7 Duty Cycle

Please refer to Appendix E.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Automatically Discontinue Transmission

3.6.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1132003	N/A	Aug. 16, 2018	Feb. 13, 2019~ Mar. 08, 2019	Aug. 15, 2019	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1126017	300MHz~40GHz	Aug. 16, 2018	Feb. 13, 2019~ Mar. 08, 2019	Aug. 15, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV 30	100895	9kHz~30GHz	Apr. 20, 2018	Feb. 13, 2019~ Mar. 08, 2019	Apr. 19, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC1300484	N/A	Apr. 17, 2018	Feb. 13, 2019~ Mar. 08, 2019	Apr. 16, 2019	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Mar. 05, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Nov. 12, 2018	Mar. 05, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Mar. 05, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	Mar. 05, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Mar. 05, 2019	N/A	Conduction (CO05-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Sep. 14, 2018	Mar. 05, 2019	Sep. 13, 2019	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBE CK	VTSD 9561-F N	9561-F N00373	9kHz~200MHz	Nov. 08, 2018	Mar. 05, 2019	Nov. 07, 2019	Conduction (CO05-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 07, 2019	Feb. 15, 2019~ Mar. 29, 2019	Jan. 06, 2020	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1241	1GHz ~ 18GHz	Jun. 29, 2018	Feb. 15, 2019~ Mar. 29, 2019	Jun. 28, 2019	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	37059&01	30MHz~1GHz	Oct. 13, 2018	Feb. 15, 2019~ Mar. 29, 2019	Oct. 12, 2019	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA91705 84	18GHz~ 40GHz	Dec. 05, 2018	Feb. 15, 2019~ Mar. 29, 2019	Dec. 04, 2019	Radiation (03CH13-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 14, 2018	Feb. 15, 2019~ Mar. 29, 2019	Nov. 13, 2020	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-00101 800-30-10P	1590074	1GHz~18GHz	May 21, 2018	Feb. 15, 2019~ Mar. 29, 2019	May 20, 2019	Radiation (03CH13-HY)
Amplifier	Sonoma-Instrument	310 N	187282	9KHz~1GHz	Dec. 18, 2018	Feb. 15, 2019~ Mar. 29, 2019	Dec. 17, 2019	Radiation (03CH13-HY)
Amplifier	MITEQ	TTA1840-35-H G	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 16, 2018	Feb. 15, 2019~ Mar. 29, 2019	Jul. 15, 2019	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0030/126E	30M-18G	Feb. 13, 2019	Feb. 15, 2019~ Mar. 29, 2019	Feb. 12, 2020	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	804793/4	30M-18G	Feb. 13, 2019	Feb. 15, 2019~ Mar. 29, 2019	Feb. 12, 2020	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/4	30M-18G	Feb. 13, 2019	Feb. 15, 2019~ Mar. 29, 2019	Feb. 12, 2020	Radiation (03CH13-HY)
Spectrum Analyzer	Agilent	N9010A	MY53470118	10Hz~44GHz	Apr. 17, 2018	Feb. 15, 2019~ Mar. 29, 2019	Apr. 16, 2019	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Feb. 15, 2019~ Mar. 29, 2019	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Feb. 15, 2019~ Mar. 29, 2019	N/A	Radiation (03CH13-HY)
Software	AUDIX	E3 6.2009-8-24c	RK-001124	N/A	N/A	Feb. 15, 2019~ Mar. 29, 2019	N/A	Radiation (03CH13-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	20Hz ~ 8.4GHz	Nov. 01, 2018	Feb. 15, 2019~ Mar. 29, 2019	Oct. 31, 2019	Radiation (03CH13-HY)
Filter	Woken	WHKX8-5872. 5-6750-18000- 40ST	SN3	6.75G Highpass	Sep.17, 2018	Feb. 15, 2019~ Mar. 29, 2019	Sep.16, 2019	Radiation (03CH13-HY)
Filter	Wainwright	WHKX12-1080 -1200-15000-6 OST	SN3	1.2G Low Pass	Jul. 05, 2018	Feb. 15, 2019~ Mar. 29, 2019	Jul. 04, 2019	Radiation (03CH13-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.2
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.4
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.3
---	-----

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Howard Lin	Temperature:	21~25	°C
Test Date:	2019/2/13~2019/3/8	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	149	5745	23.73	-	41.96	-	16.33	-	0.5	Pass
11a	6Mbps	1	157	5785	27.97	-	45.09	-	16.33	-	0.5	Pass
11a	6Mbps	1	165	5825	27.02	-	43.62	-	16.33	-	0.5	Pass
HT20	MCS0	1	149	5745	24.58	-	43.45	-	17.58	-	0.5	Pass
HT20	MCS0	1	157	5785	29.12	-	48.11	-	17.58	-	0.5	Pass
HT20	MCS0	1	165	5825	25.18	-	43.47	-	17.53	-	0.5	Pass
HT40	MCS0	1	151	5755	47.45	-	86.69	-	36.32	-	0.5	Pass
HT40	MCS0	1	159	5795	57.64	-	93.32	-	36.32	-	0.5	Pass
VHT80	MCS0	1	155	5775	78.76	-	170.71	-	76.40	-	0.5	Pass

TEST RESULTS DATA
Average Power Table

Band IV												
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	18.60	-		30.00	-	4.50	-	Pass
11a	6Mbps	1	157	5785	19.10	-		30.00	-	4.50	-	Pass
11a	6Mbps	1	165	5825	19.00	-		30.00	-	4.50	-	Pass
HT20	MCS0	1	149	5745	18.40	-		30.00	-	4.50	-	Pass
HT20	MCS0	1	157	5785	18.40	-		30.00	-	4.50	-	Pass
HT20	MCS0	1	165	5825	18.10	-		30.00	-	4.50	-	Pass
HT40	MCS0	1	151	5755	17.90	-		30.00	-	4.50	-	Pass
HT40	MCS0	1	159	5795	17.70	-		30.00	-	4.50	-	Pass
VHT20	MCS0	1	149	5745	18.30	-		30.00	-	4.50	-	Pass
VHT20	MCS0	1	157	5785	18.30	-		30.00	-	4.50	-	Pass
VHT20	MCS0	1	165	5825	18.00	-		30.00	-	4.50	-	Pass
VHT40	MCS0	1	151	5755	17.80	-		30.00	-	4.50	-	Pass
VHT40	MCS0	1	159	5795	17.60	-		30.00	-	4.50	-	Pass
VHT80	MCS0	1	155	5775	16.30	-		30.00	-	4.50	-	Pass

TEST RESULTS DATA
Power Spectral Density

Band IV																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	0.00	-	2.22	-	3.95	-		30.00	-	4.50	-	Pass
11a	6Mbps	1	157	5785	0.00	-	2.22	-	4.45	-		30.00	-	4.50	-	Pass
11a	6Mbps	1	165	5825	0.00	-	2.22	-	4.63	-		30.00	-	4.50	-	Pass
HT20	MCS0	1	149	5745	0.00	-	2.22	-	3.43	-		30.00	-	4.50	-	Pass
HT20	MCS0	1	157	5785	0.00	-	2.22	-	4.01	-		30.00	-	4.50	-	Pass
HT20	MCS0	1	165	5825	0.00	-	2.22	-	3.39	-		30.00	-	4.50	-	Pass
HT40	MCS0	1	151	5755	0.00	-	2.22	-	-0.30	-		30.00	-	4.50	-	Pass
HT40	MCS0	1	159	5795	0.00	-	2.22	-	0.11	-		30.00	-	4.50	-	Pass
VHT80	MCS0	1	155	5775	0.00	-	2.22	-	-4.82	-		30.00	-	4.50	-	Pass




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Jimmy Chang	Temperature :	24~26℃
		Relative Humidity :	51~53%

EUT Information

Report NO : 911708
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	28.22	---	65.63	37.41	L1	OFF	19.5
0.156750	---	26.35	55.63	29.28	L1	OFF	19.5
0.226500	24.46	---	62.58	38.12	L1	OFF	19.5
0.226500	---	23.37	52.58	29.20	L1	OFF	19.5
0.618000	23.46	---	56.00	32.54	L1	OFF	19.6
0.618000	---	22.31	46.00	23.69	L1	OFF	19.6
3.696000	24.91	---	56.00	31.09	L1	OFF	19.7
3.696000	---	24.04	46.00	21.96	L1	OFF	19.7
7.941750	26.09	---	60.00	33.91	L1	OFF	19.8
7.941750	---	24.98	50.00	25.02	L1	OFF	19.8
20.323500	25.40	---	60.00	34.60	L1	OFF	20.3
20.323500	---	24.43	50.00	25.57	L1	OFF	20.3

EUT Information

Report NO : 911708
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154500	30.07	---	65.75	35.68	N	OFF	19.5
0.154500	---	27.89	55.75	27.87	N	OFF	19.5
0.314250	23.99	---	59.86	35.87	N	OFF	19.5
0.314250	---	22.75	49.86	27.11	N	OFF	19.5
1.041000	23.36	---	56.00	32.64	N	OFF	19.6
1.041000	---	22.33	46.00	23.67	N	OFF	19.6
2.514750	24.24	---	56.00	31.76	N	OFF	19.6
2.514750	---	23.36	46.00	22.64	N	OFF	19.6
3.984000	25.43	---	56.00	30.57	N	OFF	19.7
3.984000	---	24.24	46.00	21.76	N	OFF	19.7
20.481000	25.61	---	60.00	34.39	N	OFF	20.3
20.481000	---	24.51	50.00	25.49	N	OFF	20.3



Appendix C. Radiated Spurious Emission

Test Engineer :	Alex Jheng, Fu Chen, and Wilson Wu	Temperature :	24~26°C
		Relative Humidity :	50~55%

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		5627.6	51.58	-16.62	68.2	42.73	32.07	6.33	29.55	227	35	P	H
		5698.8	51.3	-53.02	104.32	42.32	32.17	6.36	29.55	227	35	P	H
		5719.4	64.84	-45.79	110.63	55.81	32.21	6.37	29.55	227	35	P	H
		5724.8	76.41	-45.33	121.74	67.38	32.21	6.37	29.55	227	35	P	H
	*	5745	108.21	-	-	99.14	32.24	6.38	29.55	227	35	P	H
	*	5745	100.36	-	-	91.29	32.24	6.38	29.55	227	35	A	H
													H
													H
		5646.2	52.57	-15.63	68.2	43.69	32.09	6.34	29.55	257	155	P	V
		5696.8	54.71	-48.13	102.84	45.73	32.17	6.36	29.55	257	155	P	V
		5719.8	66.94	-43.8	110.74	57.91	32.21	6.37	29.55	257	155	P	V
		5724.8	78.2	-43.54	121.74	69.17	32.21	6.37	29.55	257	155	P	V
	*	5745	110.48	-	-	101.41	32.24	6.38	29.55	257	155	P	V
	*	5745	103.03	-	-	93.96	32.24	6.38	29.55	257	155	A	V
													V
													V



FCC RADIO TEST REPORT

Report No. : FR911708F

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 157 5785MHz		5617.6	50.07	-18.13	68.2	41.22	32.07	6.33	29.55	222	35	P	H
		5690.2	50.1	-47.87	97.97	41.12	32.17	6.36	29.55	222	35	P	H
		5715.4	51.03	-58.48	109.51	42.02	32.19	6.37	29.55	222	35	P	H
		5724.8	50.6	-71.14	121.74	41.57	32.21	6.37	29.55	222	35	P	H
	*	5785	109.44	-	-	100.32	32.29	6.39	29.56	222	35	P	H
	*	5785	101.91	-	-	92.79	32.29	6.39	29.56	222	35	A	H
		5850.6	48.04	-72.79	120.83	38.78	32.38	6.44	29.56	222	35	P	H
		5856.4	49.43	-60.98	110.41	40.13	32.41	6.45	29.56	222	35	P	H
		5924.2	49.48	-19.31	68.79	40.04	32.5	6.5	29.56	222	35	P	H
		5925.4	49.96	-18.24	68.2	40.52	32.5	6.5	29.56	222	35	P	H
													H
													H
		5613.8	51.46	-16.74	68.2	42.64	32.04	6.33	29.55	263	155	P	V
		5695.6	51.03	-50.93	101.96	42.05	32.17	6.36	29.55	263	155	P	V
		5700.8	53.16	-52.26	105.42	44.16	32.19	6.36	29.55	263	155	P	V
		5723.6	51.53	-67.48	119.01	42.5	32.21	6.37	29.55	263	155	P	V
	*	5785	112.31	-	-	103.19	32.29	6.39	29.56	263	155	P	V
	*	5785	104.57	-	-	95.45	32.29	6.39	29.56	263	155	A	V
		5853	50.72	-64.64	115.36	41.46	32.38	6.44	29.56	263	155	P	V
		5861.2	49.94	-59.12	109.06	40.64	32.41	6.45	29.56	263	155	P	V
		5905.4	51.22	-31.45	82.67	41.82	32.48	6.48	29.56	263	155	P	V
		5944.4	49.16	-19.04	68.2	39.67	32.53	6.52	29.56	263	155	P	V
													V
													V



FCC RADIO TEST REPORT

Report No. : FR911708F

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 165 5825MHz	*	5825	109.27	-	-	100.05	32.36	6.42	29.56	224	34	P	H
	*	5825	101.6	-	-	92.38	32.36	6.42	29.56	224	34	A	H
		5852.6	76.38	-39.89	116.27	67.12	32.38	6.44	29.56	224	34	P	H
		5858.2	70.92	-38.98	109.9	61.62	32.41	6.45	29.56	224	34	P	H
		5876.6	55.81	-48.2	104.01	46.48	32.43	6.46	29.56	224	34	P	H
		5932	49.13	-19.07	68.2	39.68	32.5	6.51	29.56	224	34	P	H
													H
													H
	*	5825	112.29	-	-	103.07	32.36	6.42	29.56	262	156	P	V
	*	5825	104.39	-	-	95.17	32.36	6.42	29.56	262	156	A	V
		5852.2	77.85	-39.33	117.18	68.59	32.38	6.44	29.56	262	156	P	V
		5855.6	72.7	-37.93	110.63	63.41	32.41	6.44	29.56	262	156	P	V
		5875.4	55.24	-49.66	104.9	45.91	32.43	6.46	29.56	262	156	P	V
		5946.4	49	-19.2	68.2	39.51	32.53	6.52	29.56	262	156	P	V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		11490	59.82	-14.18	74	65.74	39.92	10.46	56.3	100	223	P	H
		11490	49.44	-4.56	54	55.36	39.92	10.46	56.3	100	223	A	H
		17235	51.8	-16.4	68.2	54.58	40.84	12.95	56.57	100	0	P	H
													H
		11490	61.24	-12.76	74	67.16	39.92	10.46	56.3	100	217	P	V
		11490	50.73	-3.27	54	56.65	39.92	10.46	56.3	100	217	A	V
		17235	51.55	-16.65	68.2	54.33	40.84	12.95	56.57	100	0	P	V
													V
802.11a CH 157 5785MHz		11570	60.58	-13.42	74	66.62	39.76	10.5	56.3	100	224	P	H
		11570	49.99	-4.01	54	56.03	39.76	10.5	56.3	100	224	A	H
		17355	54.04	-14.16	68.2	56.51	41.26	13.08	56.81	100	0	P	H
													H
		11570	60.06	-13.94	74	66.1	39.76	10.5	56.3	100	217	P	V
		11570	49.33	-4.67	54	55.37	39.76	10.5	56.3	100	217	A	V
		17355	52.91	-15.29	68.2	55.38	41.26	13.08	56.81	100	0	P	V
													V
802.11a CH 165 5825MHz		11650	60.83	-13.17	74	66.97	39.62	10.54	56.3	100	220	P	H
		11650	49.51	-4.49	54	55.65	39.62	10.54	56.3	100	220	A	H
		17475	54.65	-13.55	68.2	56.81	41.68	13.21	57.05	100	0	P	H
													H
		11650	59.79	-14.21	74	65.93	39.62	10.54	56.3	100	213	P	V
		11650	48.27	-5.73	54	54.41	39.62	10.54	56.3	100	213	A	V
		17475	54.22	-13.98	68.2	56.38	41.68	13.21	57.05	100	0	P	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 149 5745MHz		5629.6	50.28	-17.92	68.2	41.43	32.07	6.33	29.55	225	35	P	H
		5697.8	53.26	-50.32	103.58	44.28	32.17	6.36	29.55	225	35	P	H
		5717.2	70.59	-39.43	110.02	61.58	32.19	6.37	29.55	225	35	P	H
		5724.6	80.57	-40.72	121.29	71.54	32.21	6.37	29.55	225	35	P	H
	*	5745	109.11	-	-	100.04	32.24	6.38	29.55	225	35	P	H
	*	5745	101.13	-	-	92.06	32.24	6.38	29.55	225	35	A	H
													H
													H
		5640.2	52.16	-16.04	68.2	43.28	32.09	6.34	29.55	252	158	P	V
		5698.6	56.64	-47.53	104.17	47.66	32.17	6.36	29.55	252	158	P	V
		5716.8	74.9	-35.01	109.91	65.89	32.19	6.37	29.55	252	158	P	V
		5724.8	81.78	-39.96	121.74	72.75	32.21	6.37	29.55	252	158	P	V
	*	5745	111.76	-	-	102.69	32.24	6.38	29.55	252	158	P	V
	*	5745	103.94	-	-	94.87	32.24	6.38	29.55	252	158	A	V
													V
													V



WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 157 5785MHz		5644.4	49.28	-18.92	68.2	40.4	32.09	6.34	29.55	222	35	P	H
		5682.4	50.59	-41.62	92.21	41.65	32.14	6.35	29.55	222	35	P	H
		5714.4	50.84	-58.39	109.23	41.83	32.19	6.37	29.55	222	35	P	H
		5721.6	50.14	-64.31	114.45	41.11	32.21	6.37	29.55	222	35	P	H
	*	5785	108.81	-	-	99.69	32.29	6.39	29.56	222	35	P	H
	*	5785	100.89	-	-	91.77	32.29	6.39	29.56	222	35	A	H
		5851.4	49.39	-69.62	119.01	40.13	32.38	6.44	29.56	222	35	P	H
		5858.2	49.79	-60.11	109.9	40.49	32.41	6.45	29.56	222	35	P	H
		5881.8	49.41	-50.74	100.15	40.07	32.43	6.47	29.56	222	35	P	H
		5929.6	49.38	-18.82	68.2	39.94	32.5	6.5	29.56	222	35	P	H
													H
													H
		5643.8	50.61	-17.59	68.2	41.73	32.09	6.34	29.55	264	156	P	V
		5687.8	51.62	-44.58	96.2	42.64	32.17	6.36	29.55	264	156	P	V
		5714.4	51.86	-57.37	109.23	42.85	32.19	6.37	29.55	264	156	P	V
		5722.4	51.13	-65.14	116.27	42.1	32.21	6.37	29.55	264	156	P	V
	*	5785	111.26	-	-	102.14	32.29	6.39	29.56	264	156	P	V
	*	5785	103.82	-	-	94.7	32.29	6.39	29.56	264	156	A	V
		5851.4	49.75	-69.26	119.01	40.49	32.38	6.44	29.56	264	156	P	V
		5855.8	50.6	-59.98	110.58	41.31	32.41	6.44	29.56	264	156	P	V
		5900.2	51.27	-35.24	86.51	41.89	32.46	6.48	29.56	264	156	P	V
		5926.6	50.26	-17.94	68.2	40.82	32.5	6.5	29.56	264	156	P	V
													V
													V



WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 165 5825MHz	*	5825	107.61	-	-	98.39	32.36	6.42	29.56	226	35	P	H
	*	5825	100.35	-	-	91.13	32.36	6.42	29.56	226	35	A	H
		5852.6	71.12	-45.15	116.27	61.86	32.38	6.44	29.56	226	35	P	H
		5855.8	66.91	-43.67	110.58	57.62	32.41	6.44	29.56	226	35	P	H
		5879.6	50.96	-50.82	101.78	41.63	32.43	6.46	29.56	226	35	P	H
		5949.8	49.31	-18.89	68.2	39.82	32.53	6.52	29.56	226	35	P	H
													H
													H
	*	5825	111.13	-	-	101.91	32.36	6.42	29.56	264	155	P	V
	*	5825	103.25	-	-	94.03	32.36	6.42	29.56	264	155	A	V
		5852.2	73.87	-43.31	117.18	64.61	32.38	6.44	29.56	264	155	P	V
		5856	68.53	-41.99	110.52	59.24	32.41	6.44	29.56	264	155	P	V
		5875.2	52.74	-52.31	105.05	43.41	32.43	6.46	29.56	264	155	P	V
		5925.2	49.58	-18.62	68.2	40.14	32.5	6.5	29.56	264	155	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 149 5745MHz		11490	58.49	-15.51	74	64.41	39.92	10.46	56.3	100	223	P	H
		11490	48.51	-5.49	54	54.43	39.92	10.46	56.3	100	223	A	H
		17235	52.18	-16.02	68.2	54.96	40.84	12.95	56.57	100	0	P	H
													H
		11490	59.3	-14.7	74	65.22	39.92	10.46	56.3	100	217	P	V
		11490	48.86	-5.14	54	54.78	39.92	10.46	56.3	100	217	A	V
		17235	50.96	-17.24	68.2	53.74	40.84	12.95	56.57	100	0	P	V
													V
802.11n HT20 CH 157 5785MHz		11570	59.79	-14.21	74	65.83	39.76	10.5	56.3	100	224	P	H
		11570	48.81	-5.19	54	54.85	39.76	10.5	56.3	100	224	A	H
		17355	53.32	-14.88	68.2	55.79	41.26	13.08	56.81	100	0	P	H
													H
		11570	58.73	-15.27	74	64.77	39.76	10.5	56.3	100	211	P	V
		11570	47.97	-6.03	54	54.01	39.76	10.5	56.3	100	211	A	V
		17355	52.75	-15.45	68.2	55.22	41.26	13.08	56.81	100	0	P	V
													V
802.11n HT20 CH 165 5825MHz		11650	58.21	-15.79	74	64.35	39.62	10.54	56.3	100	224	P	H
		11650	47.56	-6.44	54	53.7	39.62	10.54	56.3	100	224	A	H
		17475	52.86	-15.34	68.2	55.02	41.68	13.21	57.05	100	0	P	H
													H
		11650	56.87	-17.13	74	63.01	39.62	10.54	56.3	100	213	P	V
		11650	46.59	-7.41	54	52.73	39.62	10.54	56.3	100	213	A	V
		17475	53.22	-14.98	68.2	55.38	41.68	13.21	57.05	100	0	P	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 151 5755MHz		5608.8	50.81	-17.39	68.2	42	32.04	6.32	29.55	229	35	P	H
		5695.2	68.4	-33.26	101.66	59.42	32.17	6.36	29.55	229	35	P	H
		5717	81	-28.96	109.96	71.99	32.19	6.37	29.55	229	35	P	H
		5724.4	83.33	-37.5	120.83	74.3	32.21	6.37	29.55	229	35	P	H
	*	5755	106.13	-	-	97.05	32.26	6.38	29.56	229	35	P	H
	*	5755	97.67	-	-	88.59	32.26	6.38	29.56	229	35	A	H
		5853.8	50.17	-63.37	113.54	40.88	32.41	6.44	29.56	229	35	P	H
		5855.2	50.6	-60.14	110.74	41.31	32.41	6.44	29.56	229	35	P	H
		5896.6	49.79	-39.39	89.18	40.41	32.46	6.48	29.56	229	35	P	H
		5930.8	48.9	-19.3	68.2	39.46	32.5	6.5	29.56	229	35	P	H
													H
													H
		5645.8	52.83	-15.37	68.2	43.95	32.09	6.34	29.55	272	158	P	V
		5699.8	70.6	-34.45	105.05	61.62	32.17	6.36	29.55	272	158	P	V
		5718.8	86.15	-24.31	110.46	77.12	32.21	6.37	29.55	272	158	P	V
		5722.6	85.74	-30.99	116.73	76.71	32.21	6.37	29.55	272	158	P	V
	*	5755	108.54	-	-	99.46	32.26	6.38	29.56	272	158	P	V
	*	5755	100.39	-	-	91.31	32.26	6.38	29.56	272	158	A	V
		5851.6	51.04	-67.51	118.55	41.78	32.38	6.44	29.56	272	158	P	V
		5866.4	50.13	-57.48	107.61	40.83	32.41	6.45	29.56	272	158	P	V
		5880.8	50.48	-50.41	100.89	41.15	32.43	6.46	29.56	272	158	P	V
		5931	50.27	-17.93	68.2	40.83	32.5	6.5	29.56	272	158	P	V
													V
													V



WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 159 5795MHz		5640.2	50.41	-17.79	68.2	41.53	32.09	6.34	29.55	215	34	P	H
		5699.8	51.76	-53.29	105.05	42.78	32.17	6.36	29.55	215	34	P	H
		5717.2	56.9	-53.12	110.02	47.89	32.19	6.37	29.55	215	34	P	H
		5723.2	61.62	-56.48	118.1	52.59	32.21	6.37	29.55	215	34	P	H
	*	5795	105.3	-	-	96.15	32.31	6.4	29.56	215	34	P	H
	*	5795	97.19	-	-	88.04	32.31	6.4	29.56	215	34	A	H
		5850.8	64.39	-55.99	120.38	55.13	32.38	6.44	29.56	215	34	P	H
		5856.8	65.77	-44.53	110.3	56.47	32.41	6.45	29.56	215	34	P	H
		5876.2	52.37	-51.94	104.31	43.04	32.43	6.46	29.56	215	34	P	H
		5927	48.87	-19.33	68.2	39.43	32.5	6.5	29.56	215	34	P	H
													H
													H
		5603.8	50.86	-17.34	68.2	42.05	32.04	6.32	29.55	254	156	P	V
		5698.6	53.73	-50.44	104.17	44.75	32.17	6.36	29.55	254	156	P	V
		5718.4	60.04	-50.31	110.35	51.01	32.21	6.37	29.55	254	156	P	V
		5723.4	65.73	-52.82	118.55	56.7	32.21	6.37	29.55	254	156	P	V
	*	5795	108.25	-	-	99.1	32.31	6.4	29.56	254	156	P	V
	*	5795	99.92	-	-	90.77	32.31	6.4	29.56	254	156	A	V
		5852.2	69.7	-47.48	117.18	60.44	32.38	6.44	29.56	254	156	P	V
		5856.4	65.03	-45.38	110.41	55.73	32.41	6.45	29.56	254	156	P	V
		5875.2	54.6	-50.45	105.05	45.27	32.43	6.46	29.56	254	156	P	V
		5925.8	50.32	-17.88	68.2	40.88	32.5	6.5	29.56	254	156	P	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preampl Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 151 5755MHz		11510	57.19	-16.81	74	63.12	39.9	10.47	56.3	100	223	P	H
		11510	45.84	-8.16	54	51.77	39.9	10.47	56.3	100	223	A	H
		17265	50.45	-17.75	68.2	53.14	40.96	12.98	56.63	100	0	P	H
													H
		11510	56.27	-17.73	74	62.2	39.9	10.47	56.3	100	214	P	V
		11510	45.81	-8.19	54	51.74	39.9	10.47	56.3	100	214	A	V
		17265	50.12	-18.08	68.2	52.81	40.96	12.98	56.63	100	0	P	V
													V
802.11n HT40 CH 159 5795MHz		11590	54.92	-19.08	74	60.98	39.73	10.51	56.3	100	221	P	H
		11590	44.53	-9.47	54	50.59	39.73	10.51	56.3	100	221	A	H
		17385	52.18	-16.02	68.2	54.56	41.38	13.11	56.87	100	0	P	H
													H
		11590	54.47	-19.53	74	60.53	39.73	10.51	56.3	100	214	P	V
		11590	44.05	-9.95	54	50.11	39.73	10.51	56.3	100	214	A	V
		17385	50.93	-17.27	68.2	53.31	41.38	13.11	56.87	100	0	P	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac VHT80 CH 155 5775MHz		5648.4	61.58	-6.62	68.2	52.7	32.09	6.34	29.55	226	34	P	H
		5692.2	76.15	-23.3	99.45	67.17	32.17	6.36	29.55	226	34	P	H
		5707.6	80.83	-26.5	107.33	71.83	32.19	6.36	29.55	226	34	P	H
		5723	79.91	-37.73	117.64	70.88	32.21	6.37	29.55	226	34	P	H
	*	5775	100.93	-	-	91.81	32.29	6.39	29.56	226	34	P	H
	*	5775	92.61	-	-	83.49	32.29	6.39	29.56	226	34	A	H
		5850.6	74.13	-46.7	120.83	64.87	32.38	6.44	29.56	226	34	P	H
		5861.2	70.16	-38.9	109.06	60.86	32.41	6.45	29.56	226	34	P	H
		5879	66.15	-36.08	102.23	56.82	32.43	6.46	29.56	226	34	P	H
		5939.4	50.2	-18	68.2	40.72	32.53	6.51	29.56	226	34	P	H
													H
													H
		5649	64.63	-3.57	68.2	55.75	32.09	6.34	29.55	270	157	P	V
		5684.6	77.93	-15.91	93.84	68.96	32.17	6.35	29.55	270	157	P	V
		5705.4	81.83	-24.88	106.71	72.83	32.19	6.36	29.55	270	157	P	V
		5722.4	82.24	-34.03	116.27	73.21	32.21	6.37	29.55	270	157	P	V
	*	5775	103.96	-	-	94.84	32.29	6.39	29.56	270	157	P	V
	*	5775	95.03	-	-	85.91	32.29	6.39	29.56	270	157	A	V
		5850.2	73.33	-48.41	121.74	64.07	32.38	6.44	29.56	270	157	P	V
		5855.8	73.8	-36.78	110.58	64.51	32.41	6.44	29.56	270	157	P	V
		5877.2	64.13	-39.44	103.57	54.8	32.43	6.46	29.56	270	157	P	V
		5929.2	52.09	-16.11	68.2	42.65	32.5	6.5	29.56	270	157	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		11550	48.76	-25.24	74	54.77	39.8	10.49	56.3	100	0	P	H
		17325	49.4	-18.8	68.2	51.97	41.14	13.04	56.75	100	0	P	H
													H
													H
		11550	49.7	-24.3	74	55.71	39.8	10.49	56.3	100	0	P	V
		17325	49.36	-18.84	68.2	51.93	41.14	13.04	56.75	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



5GHz WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11a LF		32.97	24.36	-15.64	40	33.36	22.86	0.43	32.29	-	-	P	H
		51.33	25.25	-14.75	40	43.31	13.69	0.54	32.29	-	-	P	H
		84.27	34.83	-5.17	40	52.42	13.91	0.74	32.24	-	-	P	H
		349	32.35	-13.65	46	42.62	20.35	1.53	32.15	-	-	P	H
		663.3	42.71	-3.29	46	46.29	26.36	2.21	32.15	100	0	P	H
		944.7	32.86	-13.14	46	30.95	30.35	2.59	31.03	-	-	P	H
													H
													H
													H
													H
													H
													H
		32.97	36.39	-3.61	40	45.39	22.86	0.43	32.29	100	0	P	V
		52.68	28.74	-11.26	40	47.36	13.12	0.55	32.29	-	-	P	V
		85.89	23.27	-16.73	40	40.6	14.16	0.74	32.23	-	-	P	V
		343.4	28.43	-17.57	46	38.9	20.16	1.52	32.15	-	-	P	V
		663.3	36	-10	46	39.58	26.36	2.21	32.15	-	-	P	V
		950.3	33.12	-12.88	46	30.97	30.54	2.59	30.98	-	-	P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	H orizontal or V ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
 = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
 = 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
 = 55.45 (dBμV/m)
2. Over Limit(dB)
 = Level(dBμV/m) – Limit Line(dBμV/m)
 = 55.45(dBμV/m) – 74(dBμV/m)
 = -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
 = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
 = 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
 = 43.54 (dBμV/m)
2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)
 = 43.54(dBμV/m) – 54(dBμV/m)
 = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.





Appendix D. Radiated Spurious Emission Plots



Test Engineer :	Alex Jheng, Fu Chen, and Wilson Wu	Temperature :	24~26°C
		Relative Humidity :	50~55%




Note symbol




-L	Low channel location
-R	High channel location



Band 4 - 5725~5850MHz
WIFI 802.11a (Band Edge @ 3m)



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1241 HORIZONTAL : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto	 Site : 03CH13-HY Condition : PEAK(FUND) 3m HORN_91200_1241 HORIZONTAL : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE(94)_16-24 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH13-HY Condition : PEAK(FUND) 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH13-HY Condition : PEAK(LINE) 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Peak	 Site : 03CH13-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE(84)_16-24 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Peak	 Site : 03CH13-HY Condition : PEAK_BE(84)_16-24 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE[94]_16-24 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH13-HY Condition : PEAK[UNIT] 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE(94)_16-24 3m HORN_9120D_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_9120D_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto








Band 4 5725~5850MHz
WIFI 802.11n HT20 (Band Edge @ 3m)



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1	Horizontal	Fundamental
Peak	 Site Condition : 03CH13-HY : PEAK_BE(84)_16-24 3m HORN_91200_1241 HORIZONTAL : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto	 Site Condition : 03CH13-HY : PEAK(UNIT) 3m HORN_91200_1241 HORIZONTAL : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE[94]_16-24 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH13-HY Condition : PEAK(FUND) 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH13-HY Condition : PEAK(LINE) 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Peak	 Site : 03CH13-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE(84)_16-24 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Peak	 Site : 03CH13-HY Condition : PEAK_BE(84)_16-24 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BES[4]_16-24 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH13-HY Condition : PEAK_BES[4]_16-24 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE(94)_16-24 3m HORN_9120D_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_9120D_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto




Band 4 5725~5850MHz
WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1	Horizontal	Fundamental
Peak	 Site Condition : 03CH13-HY : PEAK_BE(B4)_16-24 3m HORN_91200_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site Condition : 03CH13-HY : PEAK(UNIT) 3m HORN_91200_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
	 Site Condition : 03CH13-HY : PEAK_BE(B4)_16-24 3m HORN_91200_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE(84)_16-24 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Peak	 Site : 03CH13-HY Condition : PEAK_BE(84)_16-24 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH13-HY Condition : PEAK(LINE) 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Peak	 Site : 03CH13-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH13-HY Condition : PEAK(LINE) 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Peak	 Site : 03CH13-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank



Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Band Edge @ 3m)



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1	Horizontal	Fundamental
Peak	 Site Condition : 03CH13-HY : PEAK_BE(B4)_16-24 3m HORN_91200_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site Condition : 03CH13-HY : PEAK(UNIT) 3m HORN_91200_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
	 Site Condition : 03CH13-HY : PEAK_BE(B4)_16-24 3m HORN_91200_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH13-HY Condition : PEAK(LNB) 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Peak	 Site : 03CH13-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank

Band 4 - 5725~5850MHz
WIFI 802.11a (Harmonic @ 3m)



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 HORIZONTAL Detector : Peak	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 VERTICAL Detector : Peak

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 HORIZONTAL Detector : Peak	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 VERTICAL Detector : Peak







WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK(UM) 3m HORN_91200_1241 HORIZONTAL Detector : Peak	 Site : 03CH13-HY Condition : PEAK(UM) 3m HORN_91200_1241 VERTICAL Detector : Peak

Band 4 5725~5850MHz
WIFI 802.11n HT20 (Harmonic @ 3m)



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 HORIZONTAL Detector : Peak	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 VERTICAL Detector : Peak





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 HORIZONTAL Detector : Peak	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 VERTICAL Detector : Peak



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 HORIZONTAL Detector : Peak	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 VERTICAL Detector : Peak

Band 4 5725~5850MHz
WIFI 802.11n HT40 (Harmonic @ 3m)



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 HORIZONTAL Detector : Peak	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 VERTICAL Detector : Peak

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 HORIZONTAL Detector : Peak	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 VERTICAL Detector : Peak

Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 HORIZONTAL Detector : Peak	 Site : 03CH13-HY Condition : PEAK(UNIT) 3m HORN_91200_1241 VERTICAL Detector : Peak

Emission below 1GHz
5GHz WIFI 802.11a (LF)

WIFI	5GHz 5725~5850MHz	
ANT	802.11a LF	
1	Horizontal	Vertical
QP / Peak	 Site : 03CH13-HY Condition : QP 3m B1LOG_37059401 HORIZONTAL Detector : Peak Project : 911708 Mode : Z0	 Site : 03CH13-HY Condition : QP 3m B1LOG_37059401 VERTICAL Detector : Peak Project : 911708 Mode : Z0




Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
802.11a	100.00	350	2.86	10Hz	0.00
5GHz 802.11n HT20	100.00	7280	0.14	10Hz	0.00
5GHz 802.11n HT40	100.00	5330	0.19	10Hz	0.00
5GHz 802.11ac VHT20	100.00	2520	0.40	10Hz	0.00
5GHz 802.11ac VHT40	100.00	2200	0.45	10Hz	0.00
5GHz 802.11ac VHT80	100.00	150	6.67	10Hz	0.00




802.11a



Date: 13.FEB.2019 09:13:34


802.11n HT20



Date: 13.FEB.2019 09:15:17




802.11n HT40



Date: 13.FEB.2019 09:18:09


802.11ac VHT20



Date: 13.FEB.2019 09:16:42




802.11ac VHT40



Date: 13.FEB.2019 09:19:03

802.11ac VHT80



Date: 13.FEB.2019 09:22:09

—THE END—