

Declaration letter

Dear Sir/Madam:

We, SICK AG (Merkurring 20, 22143 Hamburg, Germany), declare the following:

Model names	RFH505-1004301 RFH510-1004301 RFH515-1004301																																						
FCC ID	WRMRFH5																																						
IC	10066A-RFH5																																						
Difference	Schematic & PCB All models share the same schematic and BOM. RFH505 and RFH510 use the same PCB while RFH515 has a dedicated PCB design due to the difference in form factor, which does not influence the RF behaviour. All 3 models have different PCBs for the magnetic loop antenna which results in different magnetic field strengths. • RFH505: antenna radius 7mm • RFH510: antenna radius 12mm • RFH515: antenna radius 17.05mm Other properties Table 2: Differences between the device variants <table> <tr> <th>Feature</th><th>RFH505-1004301</th><th>RFH510-1004301</th><th>RFH515-1004301</th></tr> <tr> <td>Write/Read range ¹⁾</td><td>Max. 35 mm</td><td>Max. 60 mm</td><td>Max. 80 mm</td></tr> <tr> <td>Optical indicators</td><td colspan="2">4 x LEDs, identical display function for events during operation</td><td>4 x LEDs, each with different display function for events during operation with fixed assignment</td></tr> <tr> <td>Housing design</td><td colspan="2">Cylindrical</td><td>Cubic</td></tr> <tr> <td>Housing material</td><td colspan="2">Metal and plastic</td><td>Plastic</td></tr> <tr> <td>Enclosure rating</td><td colspan="2">IP67</td><td>IP68</td></tr> <tr> <td>Design</td><td>M18</td><td>M30</td><td>C44</td></tr> <tr> <td>Dimensions</td><td>M18 x 63.5 mm</td><td>M30 x 63.5 mm</td><td>40 x 40 x 40 mm³</td></tr> <tr> <td>Weight</td><td>37 g</td><td>87 g</td><td>108 g ²⁾</td></tr> </table> ¹⁾ With plane-parallel alignment of the RFID transponder (disk 50 mm, part number 6033781) to the device cap. Reading distance achieved depends on dimensions and quality of the transponder. ²⁾ Including clamping bracket			Feature	RFH505-1004301	RFH510-1004301	RFH515-1004301	Write/Read range ¹⁾	Max. 35 mm	Max. 60 mm	Max. 80 mm	Optical indicators	4 x LEDs, identical display function for events during operation		4 x LEDs, each with different display function for events during operation with fixed assignment	Housing design	Cylindrical		Cubic	Housing material	Metal and plastic		Plastic	Enclosure rating	IP67		IP68	Design	M18	M30	C44	Dimensions	M18 x 63.5 mm	M30 x 63.5 mm	40 x 40 x 40 mm ³	Weight	37 g	87 g	108 g ²⁾
Feature	RFH505-1004301	RFH510-1004301	RFH515-1004301																																				
Write/Read range ¹⁾	Max. 35 mm	Max. 60 mm	Max. 80 mm																																				
Optical indicators	4 x LEDs, identical display function for events during operation		4 x LEDs, each with different display function for events during operation with fixed assignment																																				
Housing design	Cylindrical		Cubic																																				
Housing material	Metal and plastic		Plastic																																				
Enclosure rating	IP67		IP68																																				
Design	M18	M30	C44																																				
Dimensions	M18 x 63.5 mm	M30 x 63.5 mm	40 x 40 x 40 mm ³																																				
Weight	37 g	87 g	108 g ²⁾																																				

	RFH515-1004301	RFH510-1004301	RFH505-1004301
Appearance			

Regards,

SICK AG

Merkurring 20

D-22143 Hamburg, Germany

Tel: +49 40 6116800

Fax: +49 40 611680201

i.A. Dirk Struve

Group Manager Software RFID
Research & Development

SICK AG

Merkurring 20

22143 Hamburg / Germany