

IEEE C95.1

KDB 447498 D03

47 C.F.R. Part 1, Subpart I, Section 1.1310

47 C.F.R. Part 2, Subpart J, Section 2.1091

RF EXPOSURE REPORT

For

Wireless module

Model: WG7833-B0, WG7833BEM2A, WG7833BEM2B

Trade Name: Jorjin

Issued to

Jorjin Technologies INC
17F, No. 239, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 22161

Issued by

Compliance Certification Services Inc.
No. 11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891, Taiwan. (R.O.C.)
<http://www.ccsrf.com>
service@ccsrf.com
Issued Date: July 20, 2015



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	2015/07/20	Initial Issue	ALL	Becca Chen

TABLE OF CONTENTS

1. LIMIT	4
2. EUT SPECIFICATION.....	4
3. TEST RESULTS.....	6
4. MAXIMUM PERMISSIBLE EXPOSURE.....	7

1. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

2. EUT SPECIFICATION

EUT	Wireless module		
Model	WG7833-B0, WG7833BEM2A, WG7833BEM2B		
RF Module	TI	Model:	WL1833
Frequency band (Operating)	☒ Bluetooth 2.1 + EDR / 4.0: 2402 ~ 2480 MHz 802.11b/g/n HT20: 2.412GHz ~ 2.462GHz 802.11n HT40: 2.422GHz ~ 2.452GHz 802.11a/n HT20: 5.180GHz ~ 5.240GHz / 5.745 ~ 5.825GHz 802.11n HT40: 5.190GHz ~ 5.230GHz / 5.755 ~ 5.795GHz ☐ Others		
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others		
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW}/\text{cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)		
Antenna Specification	1. PCB Antenna: Unictron / H2B1BE1A1B0200 2.4GHz: Antenna Gain : 4.13 dBi (Numeric gain 2.59) PCB Antenna: Unictron / H2B1BB1A1Q0100 5GHz: Antenna Gain : 4.59 dBi (Numeric gain 2.88) 2. Dipole Antenna: WIESON / GPOT155-002 2.4GHz: Antenna Gain : 1.60 dBi (Numeric gain 1.45) 5GHz: Antenna Gain : 2.08 dBi (Numeric gain 1.61)		
Maximum Average output power	Bluetooth 2.0 Mode : 11.31 dBm (13.521 mW) Bluetooth 4.0 Mode : 8.25 dBm (6.683 mW) IEEE 802.11b Mode: 15.63 dBm (36.559 mW) IEEE 802.11g Mode: 13.76 dBm (23.768 mW) IEEE 802.11n HT 20 Mode: 12.51 dBm (17.824 mW) IEEE 802.11n HT 40 Mode: 11.10 dBm (12.882 mW) IEEE 802.11a Mode: 16.29 dBm (42.560 mW) IEEE 802.11n HT 20 Mode: 15.98 dBm (39.628 mW) IEEE 802.11n HT 40 Mode: 14.08 dBm (25.586 mW)		

Maximum Tune up Power	Bluetooth 2.0 Mode : 13.00 dBm (19.953 mW) Bluetooth 4.0 Mode : 10.00 dBm (10.000 mW) IEEE 802.11b Mode: 17.50 dBm (56.234 mW) IEEE 802.11g Mode: 15.50 dBm (35.481 mW) IEEE 802.11n HT 20 Mode: 14.50 dBm (28.184 mW) IEEE 802.11n HT 40 Mode: 13.00 dBm (19.953 mW) IEEE 802.11a Mode: 18.00 dBm (63.096 mW) IEEE 802.11n HT 20 Mode: 17.50 dBm (56.234 mW) IEEE 802.11n HT 40 Mode: 16.00 dBm (39.811 mW)
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

3. TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \textbf{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

4. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

Bluetooth 2.0 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
40	2441	19.953	2.59	20	0.0103	1

Bluetooth 4.0 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
39	2480	10.000	2.59	20	0.0052	1

IEEE 802.11b mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
11	2462	56.234	2.59	20	0.0290	1

IEEE 802.11g mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	35.481	2.59	20	0.0183	1

IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
11	2462	28.184	2.59	20	0.0145	1

IEEE 802.11n HT40 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
9	2452	19.953	2.59	20	0.0103	1

IEEE 802.11a mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
44	5220	63.096	2.88	20	0.0362	1

IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
36	5180	56.234	2.88	20	0.0322	1

IEEE 802.11n HT40 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
38	5190	39.811	2.88	20	0.0228	1