EX3DV4– SN:3801 June 26, 2018

10303-AAA	IEEE 802.16e WiMAX (31:15, 5ms, 10MHz, 64QAM, PUSC)	X	5.02	66.03	17.86	4.96	50.0	± 9.6 %
		Y	5.30	66.93	18.58		50.0	
		Z	4.98	65.85	17.79		50.0	
10304-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, 64QAM, PUSC)	X	4.79	65.79	17.29	4.17	50.0	± 9.6 %
		Y	5.06	66.59	17.94		50.0	
		Z	4.76	65.63	17.23		50.0	
10305-AAA	IEEE 802.16e WiMAX (31:15, 10ms, 10MHz, 64QAM, PUSC, 15 symbols)	X	4.90	69.87	20.22	6.02	35.0	± 9.6 %
		Y	5.31	71.48	21.54		35.0	
		Z	4.75	69.22	19.95		35.0	
10306-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 64QAM, PUSC, 18 symbols)	X	4.99	68.00	19.55	6.02	35.0	± 9.6 %
		Y	5.28	69.01	20.47		35.0	
		Z	4.90	67.60	19.37		35.0	
10307-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, PUSC, 18 symbols)	X	4.92	68.28	19.55	6.02	35.0	± 9.6 %
		Y	5.25	69.46	20.56		35.0	
		Z	4.82	67.84	19.36		35.0	
10308-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, PUSC)	X	4.92	68.59	19.73	6.02	35.0	± 9.6 %
		Y	5.26	69.83	20.78		35.0	
		Z	4.82	68.12	19.53		35.0	
10309-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, AMC 2x3, 18 symbols)	X	5.04	68.19	19.68	6.02	35.0	± 9.6 %
		Y	5.35	69.29	20.64		35.0	
		Z	4.95	67.79	19.50		35.0	
10310-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, AMC 2x3, 18 symbols)	X	4.96	68.14	19.55	6.02	35.0	± 9.6 %
		Y	5.25	69.19	20.50		35.0	
		Z	4.87	67.72	19.37		35.0	
10311-AAC	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	2.77	67.21	15.18	0.00	150.0	± 9.6 %
		Y	3.07	68.80	16.10		150.0	
		Z	2.77	67.19	15.17		150.0	
10313-AAA	iDEN 1:3	X	4.50	74.82	16.72	6.99	70.0	± 9.6 %
		Y	8.14	81.70	19.31		70.0	
		Z	4.21	74.79	16.81		70.0	
10314-AAA	iDEN 1:6	X	6.62	83.57	22.82	10.00	30.0	± 9.6 %
		Y	15.63	96.40	26.94		30.0	
		Z	6.51	84.13	23.15		30.0	
10315-AAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	X	1.00	62.64	14.01	0.17	150.0	± 9.6 %
		Y	1.09	64.02	15.23		150.0	
		Z	0.99	62.54	13.97		150.0	
10316-AAB	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)	X	4.44	66.34	15.98	0.17	150.0	± 9.6 %
		Y	4.58	66.68	16.29		150.0	
		Z	4.45	66.32	15.98		150.0	
10317-AAC	IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	X	4.44	66.34	15.98	0.17	150.0	± 9.6 %
		Y	4.58	66.68	16.29		150.0	
		Z	4.45	66.32	15.98		150.0	
10400-AAD	IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)	X	4.51	66.55	15.91	0.00	150.0	± 9.6 %
		Y	4.66	66.92	16.21		150.0	
		Z	4.52	66.54	15.91		150.0	
10401-AAD	IEEE 802.11ac WiFi (40MHz, 64-QAM, 99pc duty cycle)	X	5.26	66.85	16.18	0.00	150.0	± 9.6 %
		Y	5.36	67.11	16.38		150.0	
		Z	5.27	66.86	16.18		150.0	

Certificate No: EX3-3801_Jun18 Page 24 of 39

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EX3DV4– SN:3801 June 26, 2018

10402-AAD	IEEE 802.11ac WiFi (80MHz, 64-QAM, 99pc duty cycle)	X	5.49	67.07	16.16	0.00	150.0	± 9.6 %
		Y	5.61	67.41	16.38		150.0	
		Z	5.50	67.07	16.16		150.0	
10403-AAB	CDMA2000 (1xEV-DO, Rev. 0)	X	0.97	64.08	10.61	0.00	115.0	± 9.6 %
		Y	1.37	68.00	13.49		115.0	
		Z	0.98	64.13	10.68		115.0	
10404-AAB	CDMA2000 (1xEV-DO, Rev. A)	X	0.97	64.08	10.61	0.00	115.0	± 9.6 %
		Y	1.37	68.00	13.49		115.0	
		Z	0.98	64.13	10.68		115.0	
10406-AAB	CDMA2000, RC3, SO32, SCH0, Full Rate	X	30.79	107.36	27.23	0.00	100.0	± 9.6 %
		Y	100.00	120.16	29.82		100.0	
		Z	19.65	100.98	25.49		100.0	
10410-AAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subframe Conf=4)	X	100.00	124.91	31.71	3.23	80.0	± 9.6 %
		Y	100.00	121.32	30.41		80.0	
		Z	100.00	125.61	31.93		80.0	
10415-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	X	0.92	61.75	13.36	0.00	150.0	± 9.6 %
		Y	0.98	62.81	14.44		150.0	
		Z	0.92	61.72	13.35		150.0	
10416-AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	X	4.37	66.26	15.86	0.00	150.0	± 9.6 %
		Y	4.50	66.58	16.15		150.0	
		Z	4.38	66.25	15.86		150.0	
10417-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	X	4.37	66.26	15.86	0.00	150.0	± 9.6 %
		Y	4.50	66.58	16.15		150.0	
		Z	4.38	66.25	15.86		150.0	
10418-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preambule)	X	4.36	66.42	15.89	0.00	150.0	± 9.6 %
		Y	4.49	66.74	16.17		150.0	
		Z	4.37	66.40	15.88		150.0	
10419-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preambule)	X	4.38	66.37	15.89	0.00	150.0	± 9.6 %
		Y	4.51	66.69	16.17		150.0	
		Z	4.39	66.35	15.89		150.0	
10422-AAB	IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)	X	4.50	66.38	15.91	0.00	150.0	± 9.6 %
		Y	4.63	66.69	16.18		150.0	
		Z	4.51	66.36	15.91		150.0	
10423-AAB	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	X	4.64	66.66	16.02	0.00	150.0	± 9.6 %
		Y	4.79	67.00	16.30		150.0	
		Z	4.65	66.65	16.02		150.0	
10424-AAB	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	X	4.57	66.61	15.99	0.00	150.0	± 9.6 %
		Y	4.72	66.95	16.27		150.0	
		Z	4.58	66.60	15.99		150.0	
10425-AAB	IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)	X	5.19	66.94	16.22	0.00	150.0	± 9.6 %
		Y	5.31	67.25	16.45		150.0	
		Z	5.20	66.93	16.22		150.0	
10426-AAB	IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	X	5.21	67.03	16.26	0.00	150.0	± 9.6 %
		Y	5.32	67.28	16.46		150.0	
		Z	5.22	67.02	16.26		150.0	

Certificate No: EX3-3801_Jun18 Page 25 of 39

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EX3DV4– SN:3801 June 26, 2018

10427-AAB	IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)	X	5.21	66.94	16.22	0.00	150.0	± 9.6 %
		Y	5.33	67.26	16.44		150.0	
		Z	5.22	66.94	16.22		150.0	
10430-AAB	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	X	4.02	70.30	17.56	0.00	150.0	± 9.6 %
		Y	4.18	70.49	17.96		150.0	
		Z	4.02	70.25	17.56		150.0	
10431-AAB	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	X	4.00	66.69	15.72	0.00	150.0	± 9.6 %
		Y	4.18	67.12	16.13		150.0	
		Z	4.01	66.67	15.72		150.0	
10432-AAB	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)	X	4.33	66.63	15.89	0.00	150.0	± 9.6 %
		Y	4.48	67.00	16.21		150.0	
		Z	4.33	66.61	15.89		150.0	
10433-AAB	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	X	4.58	66.64	16.01	0.00	150.0	± 9.6 %
		Y	4.73	66.99	16.29		150.0	
		Z	4.59	66.63	16.01		150.0	
10434-AAA	W-CDMA (BS Test Model 1, 64 DPCH)	X	4.06	70.92	17.34	0.00	150.0	± 9.6 %
		Y	4.27	71.30	17.90		150.0	
		Z	4.06	70.88	17.35		150.0	
10435-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	124.67	31.60	3.23	80.0	± 9.6 %
		Y	100.00	121.12	30.31		80.0	
		Z	100.00	125.37	31.82		80.0	
10447-AAB	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	3.24	66.36	14.69	0.00	150.0	± 9.6 %
		Y	3.47	67.09	15.42		150.0	
		Z	3.25	66.35	14.70		150.0	
10448-AAB	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clippin 44%)	X	3.86	66.46	15.57	0.00	150.0	± 9.6 %
		Y	4.02	66.90	15.99		150.0	
		Z	3.86	66.45	15.58		150.0	
10449-AAB	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Cliping 44%)	X	4.15	66.44	15.77	0.00	150.0	± 9.6 %
		Y	4.29	66.82	16.11		150.0	
		Z	4.16	66.43	15.77		150.0	
10450-AAB	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	4.36	66.40	15.85	0.00	150.0	± 9.6 %
		Y	4.49	66.75	16.14		150.0	
		Z	4.37	66.38	15.84		150.0	
10451-AAA	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	X	3.07	66.27	14.09	0.00	150.0	± 9.6 %
		Y	3.35	67.23	15.01		150.0	
		Z	3.09	66.28	14.12		150.0	
10456-AAB	IEEE 802.11ac WiFi (160MHz, 64-QAM, 99pc duty cycle)	X	6.10	67.60	16.46	0.00	150.0	± 9.6 %
		Y	6.17	67.80	16.60		150.0	
		Z	6.11	67.59	16.46		150.0	
10457-AAA	UMTS-FDD (DC-HSDPA)	X	3.68	64.94	15.56	0.00	150.0	± 9.6 %
		Y	3.76	65.22	15.86		150.0	
		Z	3.68	64.92	15.56		150.0	
10458-AAA	CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	X	3.64	69.83	16.43	0.00	150.0	± 9.6 %
		Y	3.92	70.59	17.30		150.0	
		Z	3.65	69.81	16.46		150.0	
10459-AAA	CDMA2000 (1xEV-DO, Rev. B, 3 carriers)	X	4.90	68.31	17.78	0.00	150.0	± 9.6 %
		Y	4.99	68.05	17.92		150.0	
		Z	4.90	68.27	17.79		150.0	

Certificate No: EX3-3801_Jun18 Page 26 of 39

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EX3DV4– SN:3801 June 26, 2018

10460-AAA	UMTS-FDD (WCDMA, AMR)	X	0.70	64.51	13.31	0.00	150.0	± 9.6 %
		Y	0.86	67.82	15.75		150.0	
		Z	0.70	64.47	13.28		150.0	
10461-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	128.99	33.67	3.29	80.0	± 9.6 %
		Y	100.00	126.52	32.84		80.0	
		Z	100.00	129.61	33.85		80.0	
10462-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	11.24	85.71	18.56	3.23	80.0	± 9.6 %
		Y	100.00	107.01	23.71		80.0	
		Z	7.60	81.91	17.44		80.0	
10463-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.22	68.12	12.22	3.23	80.0	± 9.6 %
		Y	8.52	79.99	16.22		80.0	
		Z	1.89	66.79	11.65		80.0	
10464-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	126.35	32.27	3.23	80.0	± 9.6 %
		Y	100.00	124.09	31.55		80.0	
		Z	100.00	126.89	32.42		80.0	
10465-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	5.43	78.04	16.22	3.23	80.0	± 9.6 %
		Y	61.58	101.53	22.35		80.0	
		Z	4.13	75.48	15.36		80.0	
10466-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.84	66.23	11.40	3.23	80.0	± 9.6 %
		Y	5.22	75.15	14.66		80.0	
		Z	1.61	65.19	10.92		80.0	
10467-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	126.67	32.42	3.23	80.0	± 9.6 %
		Y	100.00	124.36	31.67		80.0	
		Z	100.00	127.22	32.57		80.0	
10468-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	6.42	79.84	16.80	3.23	80.0	± 9.6 %
		Y	95.13	106.08	23.39		80.0	
		Z	4.76	76.99	15.88		80.0	
10469-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.85	66.30	11.43	3.23	80.0	± 9.6 %
		Y	5.30	75.30	14.71		80.0	
		Z	1.62	65.24	10.95		80.0	
10470-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	126.70	32.42	3.23	80.0	± 9.6 %
		Y	100.00	124.39	31.67		80.0	
		Z	100.00	127.26	32.58		80.0	
10471-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	6.33	79.66	16.73	3.23	80.0	± 9.6 %
		Y	93.01	105.78	23.31		80.0	
		Z	4.69	76.83	15.81		80.0	
10472-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.84	66.22	11.39	3.23	80.0	± 9.6 %
		Y	5.23	75.17	14.65		80.0	
		Z	1.60	65.17	10.90		80.0	
10473-AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	100.00	126.67	32.40	3.23	80.0	± 9.6 %
		Y	100.00	124.35	31.66		80.0	
		Z	100.00	127.22	32.56		80.0	
10474-AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	6.23	79.51	16.69	3.23	80.0	± 9.6 %
		Y	89.77	105.43	23.23		80.0	
		Z	4.63	76.70	15.77		80.0	
10475-AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.83	66.18	11.37	3.23	80.0	± 9.6 %
		Y	5.17	75.07	14.62		80.0	
		Z	1.59	65.13	10.89		80.0	

Certificate No: EX3-3801_Jun18 Page 27 of 39

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EX3DV4– SN:3801 June 26, 2018

10477-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	5.49	78.15	16.23	3.23	80.0	± 9.6 %
		Y	65.26	102.05	22.44		80.0	
		Z	4.15	75.54	15.36		80.0	
10478-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.81	66.09	11.33	3.23	80.0	± 9.6 %
		Y	5.09	74.88	14.55		80.0	
		Z	1.58	65.06	10.85		80.0	
10479-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	18.48	99.99	27.17	3.23	80.0	± 9.6 %
		Y	22.20	101.96	27.87		80.0	
		Z	14.17	96.33	26.21		80.0	
10480-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	14.09	89.36	21.95	3.23	80.0	± 9.6 %
		Y	20.63	93.88	23.53		80.0	
		Z	11.71	87.23	21.36		80.0	
10481-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	9.14	82.86	19.53	3.23	80.0	± 9.6 %
		Y	14.27	88.02	21.43		80.0	
		Z	7.91	81.27	19.06		80.0	
10482-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.52	69.21	14.96	2.23	80.0	± 9.6 %
		Y	5.13	78.71	19.34		80.0	
		Z	2.46	69.28	15.12		80.0	
10483-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.99	74.88	17.01	2.23	80.0	± 9.6 %
		Y	7.65	80.31	19.44		80.0	
		Z	4.60	74.09	16.78		80.0	
10484-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.44	73.15	16.36	2.23	80.0	± 9.6 %
		Y	6.72	78.36	18.77		80.0	
		Z	4.14	72.49	16.16		80.0	
10485-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.13	72.16	17.32	2.23	80.0	± 9.6 %
		Y	5.32	79.69	20.70		80.0	
		Z	3.02	71.96	17.37		80.0	
10486-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.95	68.06	15.01	2.23	80.0	± 9.6 %
		Y	4.18	72.74	17.56		80.0	
		Z	2.88	68.00	15.09		80.0	
10487-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.94	67.68	14.83	2.23	80.0	± 9.6 %
		Y	4.10	72.11	17.30		80.0	
		Z	2.88	67.63	14.91		80.0	
10488-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.50	71.98	18.18	2.23	80.0	± 9.6 %
		Y	4.95	77.05	20.46		80.0	
		Z	3.37	71.66	18.14		80.0	
10489-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.43	68.78	16.82	2.23	80.0	± 9.6 %
		Y	4.19	71.55	18.33		80.0	
		Z	3.34	68.53	16.79		80.0	
10490-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.52	68.64	16.78	2.23	80.0	± 9.6 %
		Y	4.25	71.23	18.22		80.0	
		Z	3.43	68.39	16.75		80.0	
10491-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.74	70.64	17.84	2.23	80.0	± 9.6 %
		Y	4.79	74.22	19.51		80.0	
		Z	3.63	70.36	17.79		80.0	
10492-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.79	68.16	16.96	2.23	80.0	± 9.6 %
		Y	4.41	70.27	18.11		80.0	
		Z	3.70	67.92	16.91		80.0	

Certificate No: EX3-3801_Jun18 Page 28 of 39

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EX3DV4– SN:3801 June 26, 2018

10493-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.85	68.05	16.92	2.23	80.0	± 9.6 %
		Y	4.46	70.06	18.03		80.0	
		Z	3.76	67.81	16.88		80.0	
10494-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.02	71.95	18.24	2.23	80.0	± 9.6 %
		Y	5.39	76.25	20.12		80.0	
		Z	3.90	71.68	18.20		80.0	
10495-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.82	68.49	17.15	2.23	80.0	± 9.6 %
		Y	4.47	70.75	18.33		80.0	
		Z	3.72	68.24	17.10		80.0	
10496-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.90	68.26	17.09	2.23	80.0	± 9.6 %
		Y	4.51	70.34	18.20		80.0	
		Z	3.81	68.02	17.05		80.0	
10497-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	1.64	63.93	11.45	2.23	80.0	± 9.6 %
		Y	3.48	72.94	16.17		80.0	
		Z	1.62	64.10	11.64		80.0	
10498-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.36	60.00	8.37	2.23	80.0	± 9.6 %
		Y	2.11	64.18	11.38		80.0	
		Z	1.34	60.00	8.46		80.0	
10499-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.38	60.00	8.24	2.23	80.0	± 9.6 %
		Y	2.00	63.38	10.85		80.0	
		Z	1.36	60.00	8.32		80.0	
10500-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.25	71.93	17.62	2.23	80.0	± 9.6 %
		Y	4.97	78.02	20.41		80.0	
		Z	3.13	71.66	17.62		80.0	
10501-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.19	68.55	15.79	2.23	80.0	± 9.6 %
		Y	4.19	72.26	17.86		80.0	
		Z	3.11	68.40	15.83		80.0	
10502-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.23	68.38	15.66	2.23	80.0	± 9.6 %
		Y	4.22	71.98	17.69		80.0	
		Z	3.16	68.25	15.70		80.0	
10503-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.45	71.77	18.08	2.23	80.0	± 9.6 %
		Y	4.88	76.80	20.35		80.0	
		Z	3.33	71.45	18.04		80.0	
10504-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.41	68.67	16.76	2.23	80.0	± 9.6 %
		Y	4.17	71.45	18.27		80.0	
		Z	3.32	68.43	16.73		80.0	
10505-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.50	68.54	16.72	2.23	80.0	± 9.6 %
		Y	4.23	71.13	18.16		80.0	
		Z	3.41	68.30	16.69		80.0	
10506-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.99	71.81	18.17	2.23	80.0	± 9.6 %
		Y	5.34	76.07	20.04		80.0	
		Z	3.87	71.54	18.13		80.0	
10507-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.80	68.43	17.11	2.23	80.0	± 9.6 %
		Y	4.45	70.68	18.30		80.0	
		Z	3.71	68.18	17.07		80.0	

Certificate No: EX3-3801_Jun18 Page 29 of 39

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EX3DV4– SN:3801 June 26, 2018

10508-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.89	68.19	17.05	2.23	80.0	± 9.6 %
		Y	4.50	70.26	18.15		80.0	
		Z	3.79	67.95	17.00		80.0	
10509-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.34	70.70	17.76	2.23	80.0	± 9.6 %
		Y	5.36	73.79	19.16		80.0	
		Z	4.23	70.47	17.73		80.0	
10510-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.29	68.19	17.17	2.23	80.0	± 9.6 %
		Y	4.88	70.06	18.13		80.0	
		Z	4.20	67.96	17.12		80.0	
10511-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.35	67.98	17.12	2.23	80.0	± 9.6 %
		Y	4.91	69.72	18.03		80.0	
		Z	4.26	67.75	17.07		80.0	
10512-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	4.50	72.02	18.14	2.23	80.0	± 9.6 %
		Y	5.87	75.98	19.85		80.0	
		Z	4.38	71.80	18.12		80.0	
10513-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	4.18	68.39	17.24	2.23	80.0	± 9.6 %
		Y	4.80	70.47	18.29		80.0	
		Z	4.08	68.16	17.19		80.0	
10514-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.21	68.03	17.15	2.23	80.0	± 9.6 %
		Y	4.78	69.92	18.12		80.0	
		Z	4.11	67.80	17.09		80.0	
10515-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	X	0.88	61.83	13.34	0.00	150.0	± 9.6 %
		Y	0.94	62.98	14.49		150.0	
		Z	0.88	61.80	13.32		150.0	
10516-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	X	0.41	64.58	12.89	0.00	150.0	± 9.6 %
		Y	0.57	70.03	16.74		150.0	
		Z	0.41	64.53	12.84		150.0	
10517-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	X	0.70	62.81	13.29	0.00	150.0	± 9.6 %
		Y	0.79	64.81	15.03		150.0	
		Z	0.70	62.78	13.27		150.0	
10518-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	X	4.36	66.33	15.84	0.00	150.0	± 9.6 %
		Y	4.49	66.65	16.13		150.0	
		Z	4.37	66.32	15.84		150.0	
10519-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	X	4.53	66.54	15.95	0.00	150.0	± 9.6 %
		Y	4.68	66.89	16.24		150.0	
		Z	4.54	66.53	15.95		150.0	
10520-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	X	4.38	66.47	15.86	0.00	150.0	± 9.6 %
		Y	4.53	66.84	16.16		150.0	
		Z	4.39	66.46	15.86		150.0	
10521-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	X	4.31	66.44	15.83	0.00	150.0	± 9.6 %
		Y	4.46	66.84	16.15		150.0	
		Z	4.32	66.44	15.83		150.0	
10522-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	X	4.37	66.58	15.94	0.00	150.0	± 9.6 %
		Y	4.52	66.93	16.24		150.0	
		Z	4.38	66.57	15.94		150.0	

Certificate No: EX3-3801_Jun18 Page 30 of 39

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EX3DV4– SN:3801 June 26, 2018

10523-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	X	4.27	66.46	15.79	0.00	150.0	± 9.6 %
		Y	4.40	66.80	16.08		150.0	
		Z	4.28	66.44	15.79		150.0	
10524-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	X	4.32	66.49	15.90	0.00	150.0	± 9.6 %
		Y	4.47	66.85	16.20		150.0	
		Z	4.32	66.48	15.90		150.0	
10525-AAB	IEEE 802.11ac WiFi (20MHz, MCS0, 99pc duty cycle)	X	4.32	65.56	15.51	0.00	150.0	± 9.6 %
		Y	4.45	65.90	15.80		150.0	
		Z	4.33	65.54	15.51		150.0	
10526-AAB	IEEE 802.11ac WiFi (20MHz, MCS1, 99pc duty cycle)	X	4.47	65.88	15.64	0.00	150.0	± 9.6 %
		Y	4.62	66.26	15.94		150.0	
		Z	4.47	65.87	15.64		150.0	
10527-AAB	IEEE 802.11ac WiFi (20MHz, MCS2, 99pc duty cycle)	X	4.39	65.83	15.57	0.00	150.0	± 9.6 %
		Y	4.54	66.22	15.88		150.0	
		Z	4.40	65.82	15.57		150.0	
10528-AAB	IEEE 802.11ac WiFi (20MHz, MCS3, 99pc duty cycle)	X	4.40	65.85	15.60	0.00	150.0	± 9.6 %
		Y	4.56	66.24	15.91		150.0	
		Z	4.41	65.83	15.60		150.0	
10529-AAB	IEEE 802.11ac WiFi (20MHz, MCS4, 99pc duty cycle)	X	4.40	65.85	15.60	0.00	150.0	± 9.6 %
		Y	4.56	66.24	15.91		150.0	
		Z	4.41	65.83	15.60		150.0	
10531-AAB	IEEE 802.11ac WiFi (20MHz, MCS6, 99pc duty cycle)	X	4.38	65.90	15.59	0.00	150.0	± 9.6 %
		Y	4.55	66.34	15.92		150.0	
		Z	4.39	65.89	15.59		150.0	
10532-AAB	IEEE 802.11ac WiFi (20MHz, MCS7, 99pc duty cycle)	X	4.25	65.75	15.52	0.00	150.0	± 9.6 %
		Y	4.41	66.19	15.85		150.0	
		Z	4.26	65.74	15.52		150.0	
10533-AAB	IEEE 802.11ac WiFi (20MHz, MCS8, 99pc duty cycle)	X	4.41	65.91	15.60	0.00	150.0	± 9.6 %
		Y	4.57	66.29	15.90		150.0	
		Z	4.42	65.89	15.60		150.0	
10534-AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 99pc duty cycle)	X	4.96	66.00	15.73	0.00	150.0	± 9.6 %
		Y	5.09	66.34	15.97		150.0	
		Z	4.97	65.99	15.73		150.0	
10535-AAB	IEEE 802.11ac WiFi (40MHz, MCS1, 99pc duty cycle)	X	5.03	66.17	15.81	0.00	150.0	± 9.6 %
		Y	5.16	66.52	16.05		150.0	
		Z	5.03	66.17	15.81		150.0	
10536-AAB	IEEE 802.11ac WiFi (40MHz, MCS2, 99pc duty cycle)	X	4.90	66.11	15.76	0.00	150.0	± 9.6 %
		Y	5.03	66.47	16.01		150.0	
		Z	4.91	66.11	15.76		150.0	
10537-AAB	IEEE 802.11ac WiFi (40MHz, MCS3, 99pc duty cycle)	X	4.95	66.08	15.75	0.00	150.0	± 9.6 %
		Y	5.08	66.43	16.00		150.0	
		Z	4.96	66.07	15.75		150.0	
10538-AAB	IEEE 802.11ac WiFi (40MHz, MCS4, 99pc duty cycle)	X	5.04	66.10	15.80	0.00	150.0	± 9.6 %
		Y	5.17	66.45	16.05		150.0	
		Z	5.04	66.09	15.80		150.0	
10540-AAB	IEEE 802.11ac WiFi (40MHz, MCS6, 99pc duty cycle)	X	4.97	66.08	15.81	0.00	150.0	± 9.6 %
		Y	5.11	66.47	16.07		150.0	
		Z	4.97	66.08	15.81		150.0	

Certificate No: EX3-3801_Jun18 Page 31 of 39

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EX3DV4– SN:3801 June 26, 2018

10541-AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 99pc duty cycle)	X	4.95	65.97	15.74	0.00	150.0	± 9.6 %
		Y	5.08	66.34	16.00		150.0	
		Z	4.95	65.97	15.74		150.0	
10542-AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 99pc duty cycle)	X	5.10	66.08	15.81	0.00	150.0	± 9.6 %
		Y	5.23	66.41	16.05		150.0	
		Z	5.11	66.07	15.81		150.0	
10543-AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 99pc duty cycle)	X	5.17	66.10	15.85	0.00	150.0	± 9.6 %
		Y	5.31	66.44	16.09		150.0	
		Z	5.18	66.09	15.85		150.0	
10544-AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 99pc duty cycle)	X	5.30	66.13	15.75	0.00	150.0	± 9.6 %
		Y	5.40	66.46	15.97		150.0	
		Z	5.30	66.12	15.75		150.0	
10545-AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 99pc duty cycle)	X	5.48	66.56	15.92	0.00	150.0	± 9.6 %
		Y	5.59	66.86	16.12		150.0	
		Z	5.49	66.55	15.92		150.0	
10546-AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 99pc duty cycle)	X	5.34	66.28	15.79	0.00	150.0	± 9.6 %
		Y	5.46	66.66	16.04		150.0	
		Z	5.35	66.28	15.79		150.0	
10547-AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 99pc duty cycle)	X	5.41	66.35	15.82	0.00	150.0	± 9.6 %
		Y	5.53	66.70	16.05		150.0	
		Z	5.42	66.35	15.82		150.0	
10548-AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 99pc duty cycle)	X	5.62	67.15	16.20	0.00	150.0	± 9.6 %
		Y	5.76	67.56	16.45		150.0	
		Z	5.63	67.16	16.20		150.0	
10550-AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 99pc duty cycle)	X	5.38	66.38	15.86	0.00	150.0	± 9.6 %
		Y	5.49	66.68	16.06		150.0	
		Z	5.39	66.37	15.85		150.0	
10551-AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 99pc duty cycle)	X	5.37	66.33	15.80	0.00	150.0	± 9.6 %
		Y	5.50	66.72	16.04		150.0	
		Z	5.38	66.34	15.80		150.0	
10552-AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 99pc duty cycle)	X	5.30	66.20	15.73	0.00	150.0	± 9.6 %
		Y	5.41	66.53	15.95		150.0	
		Z	5.31	66.19	15.73		150.0	
10553-AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 99pc duty cycle)	X	5.37	66.20	15.77	0.00	150.0	± 9.6 %
		Y	5.50	66.56	16.00		150.0	
		Z	5.38	66.20	15.77		150.0	
10554-AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 99pc duty cycle)	X	5.71	66.50	15.85	0.00	150.0	± 9.6 %
		Y	5.81	66.82	16.06		150.0	
		Z	5.72	66.50	15.85		150.0	
10555-AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 99pc duty cycle)	X	5.83	66.78	15.97	0.00	150.0	± 9.6 %
		Y	5.93	67.11	16.18		150.0	
		Z	5.83	66.78	15.98		150.0	
10556-AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 99pc duty cycle)	X	5.85	66.84	16.00	0.00	150.0	± 9.6 %
		Y	5.95	67.16	16.20		150.0	
		Z	5.86	66.84	16.00		150.0	
10557-AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 99pc duty cycle)	X	5.81	66.72	15.96	0.00	150.0	± 9.6 %
		Y	5.92	67.07	16.18		150.0	
		Z	5.82	66.71	15.96		150.0	

Certificate No: EX3-3801_Jun18 Page 32 of 39

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EX3DV4– SN:3801 June 26, 2018

10558-AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 99pc duty cycle)	X	5.85	66.86	16.05	0.00	150.0	± 9.6 %
		Y	5.96	67.22	16.27		150.0	
		Z	5.86	66.86	16.05		150.0	
10560-AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 99pc duty cycle)	X	5.85	66.73	16.02	0.00	150.0	± 9.6 %
		Y	5.96	67.08	16.24		150.0	
		Z	5.85	66.73	16.02		150.0	
10561-AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 99pc duty cycle)	X	5.78	66.71	16.04	0.00	150.0	± 9.6 %
		Y	5.88	67.05	16.26		150.0	
		Z	5.79	66.71	16.04		150.0	
10562-AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 99pc duty cycle)	X	5.86	66.98	16.18	0.00	150.0	± 9.6 %
		Y	6.00	67.41	16.44		150.0	
		Z	5.87	66.99	16.18		150.0	
10563-AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 99pc duty cycle)	X	5.96	66.91	16.11	0.00	150.0	± 9.6 %
		Y	6.20	67.62	16.50		150.0	
		Z	5.97	66.93	16.12		150.0	
10564-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	X	4.70	66.44	16.03	0.46	150.0	± 9.6 %
		Y	4.82	66.76	16.31		150.0	
		Z	4.70	66.43	16.03		150.0	
10565-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	X	4.91	66.87	16.35	0.46	150.0	± 9.6 %
		Y	5.05	67.19	16.62		150.0	
		Z	4.91	66.86	16.35		150.0	
10566-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	X	4.74	66.69	16.15	0.46	150.0	± 9.6 %
		Y	4.89	67.04	16.44		150.0	
		Z	4.75	66.68	16.15		150.0	
10567-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	X	4.77	67.08	16.52	0.46	150.0	± 9.6 %
		Y	4.91	67.41	16.78		150.0	
		Z	4.78	67.07	16.52		150.0	
10568-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	X	4.65	66.47	15.92	0.46	150.0	± 9.6 %
		Y	4.80	66.85	16.23		150.0	
		Z	4.66	66.47	15.92		150.0	
10569-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	X	4.74	67.23	16.61	0.46	150.0	± 9.6 %
		Y	4.87	67.51	16.84		150.0	
		Z	4.75	67.21	16.60		150.0	
10570-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	X	4.76	67.06	16.53	0.46	150.0	± 9.6 %
		Y	4.90	67.36	16.78		150.0	
		Z	4.77	67.05	16.53		150.0	
10571-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	X	1.10	63.42	14.47	0.46	130.0	± 9.6 %
		Y	1.22	65.16	15.85		130.0	
		Z	1.08	63.24	14.41		130.0	
10572-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	X	1.11	63.89	14.77	0.46	130.0	± 9.6 %
		Y	1.24	65.79	16.22		130.0	
		Z	1.09	63.70	14.70		130.0	
10573-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	X	1.08	73.84	17.41	0.46	130.0	± 9.6 %
		Y	4.49	96.37	26.07		130.0	
		Z	1.00	73.13	17.22		130.0	
10574-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	X	1.13	68.08	16.84	0.46	130.0	± 9.6 %
		Y	1.43	72.28	19.34		130.0	
		Z	1.10	67.75	16.73		130.0	

Certificate No: EX3-3801_Jun18 Page 33 of 39

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EX3DV4– SN:3801 June 26, 2018

10575-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	X	4.50	66.27	16.10	0.46	130.0	± 9.6 %
		Y	4.63	66.61	16.40		130.0	
		Z	4.50	66.26	16.10		130.0	
10576-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	X	4.52	66.45	16.17	0.46	130.0	± 9.6 %
		Y	4.65	66.77	16.46		130.0	
		Z	4.52	66.43	16.17		130.0	
10577-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	X	4.70	66.71	16.33	0.46	130.0	± 9.6 %
		Y	4.85	67.04	16.62		130.0	
		Z	4.71	66.70	16.33		130.0	
10578-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	X	4.60	66.85	16.43	0.46	130.0	± 9.6 %
		Y	4.75	67.20	16.72		130.0	
		Z	4.61	66.83	16.43		130.0	
10579-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	X	4.36	66.09	15.70	0.46	130.0	± 9.6 %
		Y	4.52	66.52	16.06		130.0	
		Z	4.37	66.07	15.70		130.0	
10580-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	X	4.41	66.16	15.74	0.46	130.0	± 9.6 %
		Y	4.57	66.57	16.09		130.0	
		Z	4.42	66.15	15.74		130.0	
10581-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	X	4.50	66.88	16.37	0.46	130.0	± 9.6 %
		Y	4.65	67.26	16.67		130.0	
		Z	4.51	66.86	16.37		130.0	
10582-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	X	4.30	65.86	15.49	0.46	130.0	± 9.6 %
		Y	4.47	66.30	15.86		130.0	
		Z	4.31	65.85	15.49		130.0	
10583-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	X	4.50	66.27	16.10	0.46	130.0	± 9.6 %
		Y	4.63	66.61	16.40		130.0	
		Z	4.50	66.26	16.10		130.0	
10584-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	X	4.52	66.45	16.17	0.46	130.0	± 9.6 %
		Y	4.65	66.77	16.46		130.0	
		Z	4.52	66.43	16.17		130.0	
10585-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	X	4.70	66.71	16.33	0.46	130.0	± 9.6 %
		Y	4.85	67.04	16.62		130.0	
		Z	4.71	66.70	16.33		130.0	
10586-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	X	4.60	66.85	16.43	0.46	130.0	± 9.6 %
		Y	4.75	67.20	16.72		130.0	
		Z	4.61	66.83	16.43		130.0	
10587-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	X	4.36	66.09	15.70	0.46	130.0	± 9.6 %
		Y	4.52	66.52	16.06		130.0	
		Z	4.37	66.07	15.70		130.0	
10588-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	X	4.41	66.16	15.74	0.46	130.0	± 9.6 %
		Y	4.57	66.57	16.09		130.0	
		Z	4.42	66.15	15.74		130.0	
10589-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	X	4.50	66.88	16.37	0.46	130.0	± 9.6 %
		Y	4.65	67.26	16.67		130.0	
		Z	4.51	66.86	16.37		130.0	
10590-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	X	4.30	65.86	15.49	0.46	130.0	± 9.6 %
		Y	4.47	66.30	15.86		130.0	
		Z	4.31	65.85	15.49		130.0	

Certificate No: EX3-3801_Jun18 Page 34 of 39

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EX3DV4– SN:3801 June 26, 2018

10591-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS0, 90pc duty cycle)	X	4.65	66.36	16.22	0.46	130.0	± 9.6 %
		Y	4.78	66.66	16.49		130.0	
		Z	4.65	66.34	16.22		130.0	
10592-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS1, 90pc duty cycle)	X	4.79	66.67	16.35	0.46	130.0	± 9.6 %
		Y	4.93	66.99	16.62		130.0	
		Z	4.79	66.66	16.35		130.0	
10593-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS2, 90pc duty cycle)	X	4.70	66.55	16.21	0.46	130.0	± 9.6 %
		Y	4.85	66.90	16.51		130.0	
		Z	4.71	66.54	16.21		130.0	
10594-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS3, 90pc duty cycle)	X	4.76	66.73	16.38	0.46	130.0	± 9.6 %
		Y	4.91	67.07	16.66		130.0	
		Z	4.76	66.72	16.38		130.0	
10595-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS4, 90pc duty cycle)	X	4.72	66.69	16.28	0.46	130.0	± 9.6 %
		Y	4.87	67.03	16.56		130.0	
		Z	4.73	66.67	16.28		130.0	
10596-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS5, 90pc duty cycle)	X	4.66	66.67	16.27	0.46	130.0	± 9.6 %
		Y	4.81	67.03	16.56		130.0	
		Z	4.66	66.65	16.27		130.0	
10597-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS6, 90pc duty cycle)	X	4.61	66.55	16.13	0.46	130.0	± 9.6 %
		Y	4.76	66.93	16.45		130.0	
		Z	4.61	66.53	16.13		130.0	
10598-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS7, 90pc duty cycle)	X	4.59	66.77	16.39	0.46	130.0	± 9.6 %
		Y	4.74	67.15	16.70		130.0	
		Z	4.60	66.76	16.39		130.0	
10599-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc duty cycle)	X	5.32	66.88	16.47	0.46	130.0	± 9.6 %
		Y	5.44	67.19	16.70		130.0	
		Z	5.33	66.88	16.48		130.0	
10600-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS1, 90pc duty cycle)	X	5.45	67.29	16.65	0.46	130.0	± 9.6 %
		Y	5.56	67.56	16.85		130.0	
		Z	5.45	67.29	16.66		130.0	
10601-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS2, 90pc duty cycle)	X	5.34	67.05	16.54	0.46	130.0	± 9.6 %
		Y	5.46	67.33	16.76		130.0	
		Z	5.35	67.04	16.55		130.0	
10602-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS3, 90pc duty cycle)	X	5.46	67.19	16.54	0.46	130.0	± 9.6 %
		Y	5.55	67.37	16.70		130.0	
		Z	5.47	67.18	16.53		130.0	
10603-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS4, 90pc duty cycle)	X	5.52	67.44	16.80	0.46	130.0	± 9.6 %
		Y	5.63	67.66	16.97		130.0	
		Z	5.53	67.43	16.80		130.0	
10604-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS5, 90pc duty cycle)	X	5.40	67.11	16.62	0.46	130.0	± 9.6 %
		Y	5.45	67.17	16.71		130.0	
		Z	5.40	67.08	16.61		130.0	
10605-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS6, 90pc duty cycle)	X	5.45	67.23	16.67	0.46	130.0	± 9.6 %
		Y	5.55	67.47	16.87		130.0	
		Z	5.46	67.22	16.67		130.0	
10606-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS7, 90pc duty cycle)	X	5.18	66.51	16.16	0.46	130.0	± 9.6 %
		Y	5.31	66.84	16.41		130.0	
		Z	5.19	66.49	16.16		130.0	

Certificate No: EX3-3801_Jun18 Page 35 of 39

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EX3DV4– SN:3801 June 26, 2018

10607-AAB	IEEE 802.11ac WiFi (20MHz, MCS0, 90pc duty cycle)	X	4.48	65.64	15.83	0.46	130.0	± 9.6 %
		Y	4.61	65.97	16.11		130.0	
		Z	4.49	65.63	15.83		130.0	
10608-AAB	IEEE 802.11ac WiFi (20MHz, MCS1, 90pc duty cycle)	X	4.64	66.01	15.99	0.46	130.0	± 9.6 %
		Y	4.80	66.37	16.28		130.0	
		Z	4.65	66.00	15.99		130.0	
10609-AAB	IEEE 802.11ac WiFi (20MHz, MCS2, 90pc duty cycle)	X	4.54	65.84	15.81	0.46	130.0	± 9.6 %
		Y	4.69	66.23	16.12		130.0	
		Z	4.54	65.83	15.81		130.0	
10610-AAB	IEEE 802.11ac WiFi (20MHz, MCS3, 90pc duty cycle)	X	4.59	66.00	15.98	0.46	130.0	± 9.6 %
		Y	4.74	66.38	16.28		130.0	
		Z	4.59	65.99	15.98		130.0	
10611-AAB	IEEE 802.11ac WiFi (20MHz, MCS4, 90pc duty cycle)	X	4.50	65.80	15.82	0.46	130.0	± 9.6 %
		Y	4.66	66.19	16.13		130.0	
		Z	4.51	65.79	15.82		130.0	
10612-AAB	IEEE 802.11ac WiFi (20MHz, MCS5, 90pc duty cycle)	X	4.50	65.94	15.85	0.46	130.0	± 9.6 %
		Y	4.67	66.35	16.18		130.0	
		Z	4.51	65.93	15.86		130.0	
10613-AAB	IEEE 802.11ac WiFi (20MHz, MCS6, 90pc duty cycle)	X	4.50	65.79	15.72	0.46	130.0	± 9.6 %
		Y	4.67	66.23	16.06		130.0	
		Z	4.51	65.78	15.72		130.0	
10614-AAB	IEEE 802.11ac WiFi (20MHz, MCS7, 90pc duty cycle)	X	4.45	65.99	15.96	0.46	130.0	± 9.6 %
		Y	4.61	66.40	16.28		130.0	
		Z	4.46	65.98	15.96		130.0	
10615-AAB	IEEE 802.11ac WiFi (20MHz, MCS8, 90pc duty cycle)	X	4.50	65.64	15.59	0.46	130.0	± 9.6 %
		Y	4.66	66.04	15.92		130.0	
		Z	4.50	65.63	15.59		130.0	
10616-AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 90pc duty cycle)	X	5.13	66.09	16.06	0.46	130.0	± 9.6 %
		Y	5.26	66.43	16.30		130.0	
		Z	5.14	66.09	16.06		130.0	
10617-AAB	IEEE 802.11ac WiFi (40MHz, MCS1, 90pc duty cycle)	X	5.20	66.29	16.13	0.46	130.0	± 9.6 %
		Y	5.32	66.60	16.36		130.0	
		Z	5.21	66.29	16.14		130.0	
10618-AAB	IEEE 802.11ac WiFi (40MHz, MCS2, 90pc duty cycle)	X	5.09	66.30	16.15	0.46	130.0	± 9.6 %
		Y	5.21	66.61	16.38		130.0	
		Z	5.10	66.29	16.15		130.0	
10619-AAB	IEEE 802.11ac WiFi (40MHz, MCS3, 90pc duty cycle)	X	5.10	66.08	15.98	0.46	130.0	± 9.6 %
		Y	5.23	66.42	16.22		130.0	
		Z	5.11	66.08	15.98		130.0	
10620-AAB	IEEE 802.11ac WiFi (40MHz, MCS4, 90pc duty cycle)	X	5.18	66.12	16.05	0.46	130.0	± 9.6 %
		Y	5.32	66.47	16.30		130.0	
		Z	5.19	66.12	16.05		130.0	
10621-AAB	IEEE 802.11ac WiFi (40MHz, MCS5, 90pc duty cycle)	X	5.20	66.27	16.24	0.46	130.0	± 9.6 %
		Y	5.32	66.58	16.46		130.0	
		Z	5.20	66.27	16.25		130.0	
10622-AAB	IEEE 802.11ac WiFi (40MHz, MCS6, 90pc duty cycle)	X	5.21	66.44	16.32	0.46	130.0	± 9.6 %
		Y	5.33	66.73	16.53		130.0	
		Z	5.22	66.44	16.33		130.0	

Certificate No: EX3-3801_Jun18 Page 36 of 39

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EX3DV4– SN:3801 June 26, 2018

10623-AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 90pc duty cycle)	X	5.08	65.93	15.93	0.46	130.0	± 9.6 %
		Y	5.21	66.29	16.19		130.0	
		Z	5.09	65.93	15.94		130.0	
10624-AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 90pc duty cycle)	X	5.27	66.16	16.11	0.46	130.0	± 9.6 %
		Y	5.40	66.47	16.35		130.0	
		Z	5.28	66.15	16.12		130.0	
10625-AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 90pc duty cycle)	X	5.52	66.79	16.49	0.46	130.0	± 9.6 %
		Y	5.74	67.39	16.86		130.0	
		Z	5.54	66.83	16.51		130.0	
10626-AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle)	X	5.45	66.17	16.04	0.46	130.0	± 9.6 %
		Y	5.55	66.49	16.26		130.0	
		Z	5.46	66.17	16.04		130.0	
10627-AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 90pc duty cycle)	X	5.69	66.77	16.30	0.46	130.0	± 9.6 %
		Y	5.78	67.03	16.49		130.0	
		Z	5.69	66.76	16.31		130.0	
10628-AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 90pc duty cycle)	X	5.46	66.20	15.95	0.46	130.0	± 9.6 %
		Y	5.58	66.58	16.20		130.0	
		Z	5.47	66.20	15.96		130.0	
10629-AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 90pc duty cycle)	X	5.54	66.30	15.99	0.46	130.0	± 9.6 %
		Y	5.66	66.63	16.22		130.0	
		Z	5.55	66.30	16.00		130.0	
10630-AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 90pc duty cycle)	X	5.89	67.55	16.62	0.46	130.0	± 9.6 %
		Y	6.06	68.03	16.92		130.0	
		Z	5.91	67.58	16.64		130.0	
10631-AAB	IEEE 802.11ac WiFi (80MHz, MCS5, 90pc duty cycle)	X	5.82	67.43	16.76	0.46	130.0	± 9.6 %
		Y	5.97	67.86	17.02		130.0	
		Z	5.83	67.44	16.77		130.0	
10632-AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 90pc duty cycle)	X	5.66	66.86	16.49	0.46	130.0	± 9.6 %
		Y	5.75	67.08	16.64		130.0	
		Z	5.67	66.85	16.49		130.0	
10633-AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)	X	5.53	66.40	16.08	0.46	130.0	± 9.6 %
		Y	5.65	66.74	16.31		130.0	
		Z	5.53	66.39	16.09		130.0	
10634-AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)	X	5.51	66.41	16.15	0.46	130.0	± 9.6 %
		Y	5.63	66.76	16.38		130.0	
		Z	5.51	66.41	16.15		130.0	
10635-AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)	X	5.38	65.73	15.53	0.46	130.0	± 9.6 %
		Y	5.52	66.14	15.81		130.0	
		Z	5.39	65.73	15.54		130.0	
10636-AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 90pc duty cycle)	X	5.88	66.55	16.14	0.46	130.0	± 9.6 %
		Y	5.96	66.85	16.34		130.0	
		Z	5.88	66.55	16.15		130.0	
10637-AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 90pc duty cycle)	X	6.02	66.92	16.31	0.46	130.0	± 9.6 %
		Y	6.11	67.22	16.51		130.0	
		Z	6.03	66.93	16.32		130.0	
10638-AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 90pc duty cycle)	X	6.02	66.89	16.27	0.46	130.0	± 9.6 %
		Y	6.12	67.20	16.48		130.0	
		Z	6.02	66.89	16.28		130.0	

Certificate No: EX3-3801_Jun18 Page 37 of 39

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EX3DV4– SN:3801 June 26, 2018

10639-AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 90pc duty cycle)	X	5.99	66.82	16.28	0.46	130.0	± 9.6 %
		Y	6.09	67.15	16.50		130.0	
		Z	6.00	66.82	16.29		130.0	
10640-AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 90pc duty cycle)	X	5.99	66.81	16.22	0.46	130.0	± 9.6 %
		Y	6.10	67.17	16.45		130.0	
		Z	5.99	66.82	16.23		130.0	
10641-AAC	IEEE 802.11ac WiFi (160MHz, MCS5, 90pc duty cycle)	X	6.05	66.80	16.24	0.46	130.0	± 9.6 %
		Y	6.14	67.07	16.42		130.0	
		Z	6.06	66.80	16.24		130.0	
10642-AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 90pc duty cycle)	X	6.08	67.00	16.51	0.46	130.0	± 9.6 %
		Y	6.18	67.31	16.70		130.0	
		Z	6.09	67.00	16.51		130.0	
10643-AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	X	5.93	66.71	16.25	0.46	130.0	± 9.6 %
		Y	6.02	67.01	16.46		130.0	
		Z	5.93	66.71	16.25		130.0	
10644-AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	X	6.03	67.03	16.43	0.46	130.0	± 9.6 %
		Y	6.18	67.49	16.72		130.0	
		Z	6.04	67.04	16.44		130.0	
10645-AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	X	6.17	67.10	16.43	0.46	130.0	± 9.6 %
		Y	6.47	67.97	16.92		130.0	
		Z	6.18	67.13	16.45		130.0	
10646-AAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	X	19.17	110.50	37.83	9.30	60.0	± 9.6 %
		Y	100.00	147.85	47.85		60.0	
		Z	16.64	107.87	37.15		60.0	
10647-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	X	16.90	108.32	37.31	9.30	60.0	± 9.6 %
		Y	88.18	146.06	47.63		60.0	
		Z	14.61	105.54	36.57		60.0	
10648-AAA	CDMA2000 (1x Advanced)	X	0.50	60.79	7.93	0.00	150.0	± 9.6 %
		Y	0.64	62.89	10.17		150.0	
		Z	0.50	60.83	7.99		150.0	
10652-AAB	LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	3.55	66.61	16.13	2.23	80.0	± 9.6 %
		Y	3.97	68.09	17.10		80.0	
		Z	3.49	66.41	16.10		80.0	
10653-AAB	LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	X	4.10	66.10	16.44	2.23	80.0	± 9.6 %
		Y	4.44	67.21	17.15		80.0	
		Z	4.04	65.91	16.40		80.0	
10654-AAB	LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	X	4.10	65.77	16.48	2.23	80.0	± 9.6 %
		Y	4.40	66.84	17.14		80.0	
		Z	4.04	65.58	16.43		80.0	
10655-AAB	LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	4.17	65.74	16.53	2.23	80.0	± 9.6 %
		Y	4.46	66.82	17.18		80.0	
		Z	4.11	65.55	16.47		80.0	
10658-AAA	Pulse Waveform (200Hz, 10%)	X	75.07	110.20	27.10	10.00	50.0	± 9.6 %
		Y	100.00	114.77	28.62		50.0	
		Z	100.00	113.64	27.73		50.0	
10659-AAA	Pulse Waveform (200Hz, 20%)	X	100.00	110.55	25.39	6.99	60.0	± 9.6 %
		Y	100.00	111.82	26.31		60.0	
		Z	100.00	110.88	25.38		60.0	

Certificate No: EX3-3801_Jun18 Page 38 of 39

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

EX3DV4– SN:3801 June 26, 2018

10660-AAA	Pulse Waveform (200Hz, 40%)	X	100.00	107.54	22.75	3.98	80.0	± 9.6 %
		Y	100.00	110.49	24.46		80.0	
		Z	100.00	108.31	22.90		80.0	
10661-AAA	Pulse Waveform (200Hz, 60%)	X	100.00	104.54	20.30	2.22	100.0	± 9.6 %
		Y	100.00	111.15	23.54		100.0	
		Z	100.00	104.99	20.30		100.0	
10662-AAA	Pulse Waveform (200Hz, 80%)	X	5.09	77.36	11.00	0.97	120.0	± 9.6 %
		Y	100.00	111.11	21.88		120.0	
		Z	1.05	68.52	8.18		120.0	

[E] Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

ANNEX E: D1900V2 Dipole Calibration Certificate

In Collaboration with
s p e a g
CALIBRATION LABORATORY

中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Client TA(Shanghai) Certificate No: Z17-97115

CALIBRATION CERTIFICATE

Object	D1900V2 - SN: 5d060
Calibration Procedure(s)	FF-Z11-003-01 Calibration Procedures for dipole validation kits
Calibration date:	August 26, 2017

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)℃ and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRVD	102083	22-Sep-16 (CTTL, No.J16X06809)	Sep-17
Power sensor NRV-Z5	100595	22-Sep-16 (CTTL, No.J16X06809)	Sep-17
Reference Probe EX3DV4	SN 3617	23-Jan-17(SPEAG,No.EX3-3617_Jan17)	Jan-18
DAE4	SN 1331	19-Jan-17(CTTL-SPEAG,No.Z17-97015)	Jan-18
Secondary Standards	**ID #**	**Cal Date(Calibrated by, Certificate No.)**	**Scheduled Calibration**
Signal Generator E4438C	MY49071430	13-Jan-17 (CTTL, No.J17X00286)	Jan-18
Network Analyzer E5071C	MY46110673	13-Jan-17 (CTTL, No.J17X00285)	Jan-18

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: August 30, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z17-97115 Page 1 of 8

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

In Collaboration with
s p e a g
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORMx,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013

b) IEC 62209-1, "Measurement procedure for assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices- Part 1: Device used next to the ear (Frequency range of 300MHz to 6GHz)", July 2016

c) IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010

d) KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:

e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor k=2, which for a normal distribution Corresponds to a coverage probability of approximately 95%.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

In Collaboration with
s p e a g
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.10.0.1446
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1900 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	39.9 ± 6 %	1.41 mho/m ± 6 %
Head TSL temperature change during test	<1.0 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm^3 (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	10.1 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	**40.1 mW /g ± 18.8 % (k=2)**
SAR averaged over 10 cm^3 (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	5.19 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	**20.7 mW /g ± 18.7 % (k=2)**

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.3	1.52 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	53.6 ± 6 %	1.53 mho/m ± 6 %
Body TSL temperature change during test	<1.0 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm^3 (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	9.90 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	**39.5 mW /g ± 18.8 % (k=2)**
SAR averaged over 10 cm^3 (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	5.21 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	**20.8 mW /g ± 18.7 % (k=2)**

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

In Collaboration with
s p e a g
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Appendix (Additional assessments outside the scope of CNAS L0570)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	52.0Ω+ 6.59jΩ
Return Loss	- 23.4dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	52.7Ω+ 8.35jΩ
Return Loss	- 21.4dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.302 ns

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.
No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.