



TEST REPORT

No. I17N00290-GSM

for

CK TELECOM LTD.

LTE phone

Model Name: DSB-0090

FCC ID: WS5DSB0090

with

Hardware Version: 1011

Software Version: FRANK01A-S10A_DSB0090_201_USER_170503

Issued Date: 2017-04-26

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

FCC 2.948 Listed: No. 342690

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: cttl_terminals@catr.cn, website: www.chinattl.com

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I17N00290-GSM	Rev.0	1st edition	2017-04-26

CONTENTS

1. TEST LABORATORY	4
1.1. TESTING LOCATION	4
1.2. TESTING ENVIRONMENT	4
1.3. PROJECT DATA	4
1.4. SIGNATURE	4
2. CLIENT INFORMATION	5
2.1. APPLICANT INFORMATION	5
2.2. MANUFACTURER INFORMATION	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1. ABOUT EUT	6
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	6
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	6
3.4. NORMAL ACCESSORY SETTING	6
3.5. GENERAL DESCRIPTION	6
4. REFERENCE DOCUMENTS	7
4.1. REFERENCE DOCUMENTS FOR TESTING	7
5. LABORATORY ENVIRONMENT	8
6. SUMMARY OF TEST RESULTS	9
7. TEST EQUIPMENTS UTILIZED	10
ANNEX A: MEASUREMENT RESULTS.....	11
A.1 OUTPUT POWER	11
A.2 EMISSION LIMIT	17
A.3 FREQUENCY STABILITY	23
A.4 OCCUPIED BANDWIDTH	26
A.5 EMISSION BANDWIDTH.....	38
A.6 BAND EDGE COMPLIANCE	50
A.7 CONDUCTED SPURIOUS EMISSION.....	57



1. Test Laboratory

1.1. Testing Location

Company Name: CTTL ShenZhen, Telecommunication Technology Labs, Academy of
Telecommunication Research, MIIT
Address: TCL International E city No. 1001 Zhongshanyuan Road, Nanshan
District, Shenzhen, Guangdong, China
Postal Code: 518048
Telephone: +86(755)33322000
Fax: +86(755)33322000

1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%
Air pressure 980 - 1040 hPa

The climatic requirements above are general exclude the special requirements for dedicated test environments listed in section 5 and some specific test cases in other parts of this report.

1.3. Project data

Testing Start Date: 2017-03-17
Testing End Date: 2017-04-26

1.4. Signature

Lai Minghua

(Prepared this test report)

Yang Zi'an

(Reviewed this test report)

Zhang Bojun

Deputy Director of the laboratory
(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: Doro AB
Address /Post: Magistratsvägen 10 SE-226 43 Lund Sweden
Contact Person: Per Carlenhag
Contact Email per.carlenhag@doro.com
Telephone: +46 46 280 5000
Fax: +46 46 280 5001

2.2. Manufacturer Information

Company Name: CK TELECOM LTD.
Address /Post: Technology Road.High-Tech Development Zone. Heyuan,
Guangdong, P.R.China
Contact Person: Xin Li
Contact Email xin.li@ck-telecom.com
Telephone: 0086-0755-26739100-8515
Fax: 0086-0755-26739600

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	LTE phone
Model Name	DSB-0090
FCC ID	WS5DSB0090
Antenna	Integrated
Output power	25.08dBm maximum ERP measured for PCS1900
Extreme vol. Limits	3.6VDC to 4.2VDC (nominal: 3.8VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version	Sample Arrival Date
S01	3551150800 09167	1011	FRANK01A-S10A_DSB0090 _201_USER_170503	2017-03-17
S02	3551150800 09142	1011	FRANK01A-S10A_DSB0090 _201_USER_170503	2017-03-17

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description
AE1	Battery
AE2	Charger1
AE3	Charger2

AE1

Model	DBN-2920A
Manufacturer	Coslight Technology International Group Co., Ltd.
Capacitance	2920mAh

AE2

Model	A2-3762-501000
Manufacturer	Dongguan Aohai Power Techonolgy Co.,LTD

AE3

Model	A806A-050100U-UK1
Manufacturer	Dongguan Aohai Power Techonolgy Co.,LTD

*AE ID: is used to identify the test sample in the lab internally.

3.4. Normal Accessory setting

Fully charged battery was used during the test.

3.5. General Description

The Equipment Under Test (EUT) is a model LTE mobile phone with integrated antenna. Manual and specifications of the EUT were provided to fulfil the test.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-15 Edition
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-15 Edition
FCC Part 2	FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS	10-1-15 Edition
ANSI/TIA-603-D	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2010
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014
KDB 971168 D01	Power Meas License Digital Systems	v02r02

5. LABORATORY ENVIRONMENT

Control room / conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber 2 (8.6 meters X 6.1 meters X 3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 1 Ω
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

Semi-anechoic chamber 2 / Fully-anechoic chamber 3 (10 meters X 6.7 meters X 6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.5 dB, 3 m distance
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz



6. SUMMARY OF TEST RESULTS

Items	List	Clause in FCC rules	Verdict
1	Output Power	22.913(a)/24.232(c)	P
2	Emission Limit	2.1051/22.917/24.238	P
3	Frequency Stability	2.1055/24.235	P
4	Occupied Bandwidth	2.1049(h)(i)	P
5	Emission Bandwidth	22.917(b)/24.238(b)	P
6	Band Edge Compliance	22.917(b)/24.238(b)	P
7	Conducted Spurious Emission	2.1057/22.917/24.238	P

7. Test Equipments Utilized

NO.	Description	TYPE	Manufacture	series number	CAL DUE DATE
1	Test Receiver	ESR7	R&S	101675	2017-07-21
2	BiLog Antenna	VULB9163	Schwarzbeck	9163 329	2020-02-17
3	Horn Antenna	3117	ETS-Lindgren	00066585	2019-03-05
4	Antenna	SBA 9113	814	Schwarzbeck	/
5	Antenna	SBA 9112	302	Schwarzbeck	/
6	Antenna	3160-09	LM4750/00118388	ETS-Lindgren	2018.07.14
7	preamplifier	83017A	MY39501110	Agilent	/
8	Signal Generator	SMR40	R&S	100541	2017-06-27
9	Fully Anechoic Chamber	FACT5-2.0	ETS-Lindgren	4166	2018-05-13
10	Spectrum Analyzer	FSP40	R&S	100378	2017-12-15
11	Universal Radio Communication Tester	CMU200	R&S	114544	2017-09-09
12	Universal Radio Communication Tester	CMU200	R&S	123210	2017-12-25
13	Spectrum Analyzer	FSU	R&S	200679	2017-12-25
14	Temperature Chamber	SH-241	ESPECs	92007516	2017-11-29
15	DC Power Supply	U3606A	Agilent Technologies	MY50450012	2017-11-22

Test software

Item	Name	Vesion
Radiated	EMC32	Version 10.01.00

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation.

This result contains output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

These measurements were done at 3 frequencies, 1850.2 MHz, 1880.0MHz and 1909.8MHz for PCS1900 band; 824.2MHz, 836.6MHz and 848.8MHz for GSM850 band. (bottom, middle and top of operational frequency range).

GSM850

	Power step	Nominal Peak output power (dBm)
GSM	5	33dBm(2W)
GPRS	3	33dBm(2W)
EGPRS	6	27dBm(0.5W)

Measurement result

GSM(GMSK)

Frequency(MHz)	Power Step	Output power(dBm)
824.2	5	33.22
836.6	5	32.58
848.8	5	31.95

GPRS(GMSK,1Slot)

Frequency(MHz)	Power Step	Output power(dBm)
824.2	3	32.94
836.6	3	32.22
848.8	3	31.83

EGPRS(8PSK,1Slot)

Frequency(MHz)	Power Step	Output power(dBm)
824.2	6	27.13
836.6	6	26.36
848.8	6	26.07

PCS1900

	Power step	Nominal Peak output power (dBm)
GSM	0	30dBm(1W)
GPRS	3	30dBm(1W)
EGPRS	5	26dBm(0.4W)

Measurement result

GSM(GMSK)

Frequency(MHz)	Power Step	Output power(dBm)
1850.2	0	29.35
1880.0	0	29.79
1909.8	0	29.77

GPRS(GMSK,1Slot)

Frequency(MHz)	Power Step	Output power(dBm)
1850.2	3	29.41
1880.0	3	29.77
1909.8	3	29.77

EGPRS(8PSK,1Slot)

Frequency(MHz)	Power Step	Output power(dBm)
1850.2	5	25.69
1880.0	5	26.03
1909.8	5	25.90

A.1.3 Radiated

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


A.1.3.2 Method of Measurement

The measurements procedures in TIA-603-D-2010 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is

connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna.

The cable loss (P_{cl}) ,the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

GSM 850-ERP 22.913(a)

Limits

	Power Step	Burst Peak ERP (dBm)
GSM	5	≤38.45dBm (7W)
GPRS	3	≤38.45dBm (7W)
EGPRS	6	≤38.45dBm (7W)

Measurement result

GSM

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	G _a Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Polarization
824.20	-9.21	-33.60	0.28	2.15	22.52	38.45	V
836.60	-9.86	-33.50	0.25	2.15	21.74	38.45	V
848.80	-9.95	-33.50	0.21	2.15	21.61	38.45	V

GPRS

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	G _a Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Polarization
824.20	-8.72	-33.60	0.28	2.15	23.01	38.45	V
836.60	-9.65	-33.50	0.25	2.15	21.95	38.45	V
848.80	-10.13	-33.50	0.21	2.15	21.43	38.45	V

EGPRS-8PSK

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	G _a Antenna Gain(dB)	Correction (dB)	ERP(dBm)	Limit(dBm)	Polarization
824.20	-8.97	-33.60	0.28	2.15	22.76	38.45	V
836.60	-9.98	-33.50	0.25	2.15	21.62	38.45	V
848.80	-10.01	-33.50	0.21	2.15	21.55	38.45	V

Frequency: 848.80MHz

Peak ERP(dBm)=P_{Mea}(-8.72dBm)- (P_{cl}+P_{Ag}) (-33.60dB)+G_a(0.28dB)-2.15dB=23.01Bm

ANALYZER SETTINGS: RBW = VBW = 3MHz

PCS1900-EIRP 24.232(c)

Limits

	Power Step	Burst Peak EIRP (dBm)
GSM	0	≤33dBm (2W)
GPRS	3	≤33dBm (2W)
EGPRS	5	≤33dBm (2W)

Measurement result

GSM

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Polarization
1850.20	-4.47	-29.40	0.15	25.08	33.00	V
1880.00	-5.96	-29.30	0.25	23.59	33.00	V
1909.80	-6.58	-29.30	0.35	23.07	33.00	V

GPRS

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Polarization
1850.20	-4.55	-29.40	0.15	25.00	33.00	V
1880.00	-6.37	-29.30	0.25	23.18	33.00	V
1909.80	-6.63	-29.30	0.35	23.02	33.00	V

EGPRS-8PSK

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)+ P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Polarization
1850.20	-5.03	-29.40	0.15	24.52	33.00	V
1880.00	-6.18	-29.30	0.25	23.37	33.00	V
1909.80	-6.87	-29.30	0.35	22.78	33.00	V

Frequency: 1909.80MHz

Peak EIRP(dBm)= P_{Mea}(-4.47dBm) - (P_{cl}+P_{Ag}) (-29.40dB)+G_a (0.15dB) =25.08dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

A.2 EMISSION LIMIT


A.2.1 Measurement Method

The measurement procedures in TIA-603-D-2010 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (P_r).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the

receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{pl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

A.2.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz) and GSM850 band (824.2MHz, 836.6MHz, 848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 ,GSM850 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result
GSM 850MHz	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
GSM 1900MHz	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

A.2.5 Sweep Table

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
850MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
1900MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

GSM Mode Channel 128/824.2MHz

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain	Peak ERP(dBm)	Limit (dBm)	Polarization
7044.00	-41.74	1.80	-2.85	-48.54	-13.00	V
7079.00	-41.79	1.80	-2.85	-48.59	-13.00	H
8082.50	-42.37	1.80	-2.18	-48.50	-13.00	H
8543.50	-42.16	2.00	-1.77	-48.08	-13.00	H
8641.00	-41.80	2.00	-1.64	-47.59	-13.00	V
9065.00	-42.53	2.10	-1.42	-48.20	-13.00	H

GSM Mode Channel 190/836.6MHz

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain	Peak ERP(dBm)	Limit (dBm)	Polarization
7069.00	-41.03	1.80	-2.85	-47.83	-13.00	V
7576.00	-41.14	1.80	-2.57	-47.66	-13.00	V
8572.50	-41.64	2.00	-1.77	-47.56	-13.00	V
8670.50	-41.53	2.00	-1.64	-47.32	-13.00	H
9158.00	-42.09	2.10	-1.36	-47.70	-13.00	V
9247.50	-41.95	2.10	-1.16	-47.36	-13.00	H

GSM Mode Channel 251/848.8MHz

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain	Peak ERP(dBm)	Limit (dBm)	Polarization
8099.00	-42.30	1.80	-2.18	-48.43	-13.00	H
8510.50	-42.02	2.00	-1.77	-47.94	-13.00	V
8652.50	-42.35	2.00	-1.64	-48.14	-13.00	H
8730.50	-42.79	2.00	-1.63	-48.57	-13.00	V
9058.50	-42.88	2.10	-1.42	-48.55	-13.00	H
9402.00	-43.40	2.10	-0.86	-48.51	-13.00	V

GSM Mode Channel 512/1850.2MHz

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain	Peak ERP(dBm)	Limit (dBm)	Polarization
16878.47	-34.16	2.90	-0.26	-37.32	-13.00	H
17204.63	-33.86	2.90	-1.01	-37.77	-13.00	H
17366.06	-33.66	2.90	-0.98	-37.54	-13.00	H
17448.09	-32.96	3.20	-1.08	-37.24	-13.00	H
17772.28	-32.69	3.20	-0.75	-36.64	-13.00	H
17921.91	-32.55	3.20	-0.64	-36.39	-13.00	H

GSM Mode Channel 661/1880.0MHz

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain	Peak ERP(dBm)	Limit (dBm)	Polarization
17126.53	-33.13	2.90	-0.79	-36.82	-13.00	H
17289.28	-32.64	2.90	-1.01	-36.55	-13.00	H
17432.34	-31.88	3.20	-1.08	-36.16	-13.00	H
17625.94	-31.48	3.20	-1.01	-35.69	-13.00	H
17791.97	-31.98	3.20	-0.75	-35.93	-13.00	H
17933.06	-31.29	3.20	-0.64	-35.13	-13.00	H

GSM Mode Channel 810/1909.8MHz

Frequency(MHz)	P _{Mea} (dBm)	Path loss	Antenna Gain	Peak ERP(dBm)	Limit (dBm)	Polarization
16808.91	-35.46	2.90	-0.26	-38.62	-13.00	H
17202.00	-33.48	2.90	-1.01	-37.39	-13.00	H
17272.22	-34.04	2.90	-1.01	-37.95	-13.00	H
17611.50	-33.65	3.20	-1.01	-37.86	-13.00	H
17785.41	-32.94	3.20	-0.75	-36.89	-13.00	H
17924.53	-33.60	3.20	-0.64	-37.44	-13.00	H

A.3 FREQUENCY STABILITY

A.3.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of PCS 1900 and GSM850, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.3.2 Measurement Limit

A.3.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.6VDC and 4.2VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

A.3.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the

nominal value for other than hand carried battery equipment.

A.3.3 Measurement results

GSM 850

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.6	16	0.019
3.8	40	0.048
4.2	13	0.015

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	44	0.052
-20	14	0.017
-10	14	0.016
0	14	0.016
10	16	0.019
20	13	0.016
30	14	0.016
40	13	0.015
50	16	0.019

EGPRS 850 - 8PSK

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.6	11	0.013
3.8	13	0.016
4.2	23	0.027

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	34	0.041
-20	22	0.026
-10	16	0.019
0	37	0.044
10	25	0.030
20	26	0.031
30	17	0.020
40	19	0.023
50	6	0.007

PCS 1900

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.6	23	0.012
3.8	45	0.024
4.2	11	0.006

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	22	0.012
-20	43	0.023
-10	34	0.018
0	36	0.019
10	44	0.023
20	11	0.006
30	43	0.023
40	24	0.013
50	27	0.014

EGPRS 1900 - 8PSK

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.6	-48	0.025
3.8	-49	0.026
4.2	-51	0.027

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-49	0.026
-20	-56	0.030
-10	-62	0.033
0	-50	0.026
10	-51	0.027
20	-58	0.031
30	-58	0.031
40	-55	0.029
50	-60	0.032

A.4 OCCUPIED BANDWIDTH

Reference

FCC: CFR Part 2.1049(h)(i)

A.4.1 Occupied Bandwidth Results

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the US Cellular/PCS frequency bands. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

The measurement method is from KDB 971168 4.2:


- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the OBW).
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least $10\log(\text{OBW} / \text{RBW})$ below the reference level.
- Set the detection mode to peak, and the trace mode to max hold.
- Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

GSM 850(99% BW)

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
824.2	241.99
836.6	245.19
848.8	245.19


GSM 850

Channel 128-Occupied Bandwidth (99% BW)




Date: 2.APR.2017 12:11:47

Channel 190-Occupied Bandwidth (99% BW)



Date: 2.APR.2017 12:14:39

Channel 251-Occupied Bandwidth (99% BW)




Date: 2.APR.2017 12:15:32

GPRS 850(99% BW)

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
824.2	246.79
836.6	246.79
848.8	245.19


GPRS 850

Channel 128-Occupied Bandwidth (99% BW)




Date: 2.APR.2017 12:33:18

Channel 190-Occupied Bandwidth (99% BW)



Date: 2.APR.2017 12:35:57



Ref 32 dBm
 * Att 30 dB
 RBW 5 kHz
 VBW 10 kHz
 SWT 40 ms

Marker 1 [T1]
 26.87 dBm
 848.775961538 MHz

Offset 6.0 dB
 T1
 T2
 T3
 T4
 T5
 T6
 T7
 T8
 T9
 T10
 T11
 T12
 T13
 T14
 T15
 T16
 T17
 T18
 T19
 T20
 T21
 T22
 T23
 T24
 T25
 T26
 T27
 T28
 T29
 T30
 T31
 T32
 T33
 T34
 T35
 T36
 T37
 T38
 T39
 T40
 T41
 T42
 T43
 T44
 T45
 T46
 T47
 T48
 T49
 T50
 T51
 T52
 T53
 T54
 T55
 T56
 T57
 T58
 T59
 T60
 T61
 T62
 T63
 T64
 T65
 T66
 T67
 T68
 T69
 T70
 T71
 T72
 T73
 T74
 T75
 T76
 T77
 T78
 T79
 T80
 T81
 T82
 T83
 T84
 T85
 T86
 T87
 T88
 T89
 T90
 T91
 T92
 T93
 T94
 T95
 T96
 T97
 T98
 T99
 T100

08.245.192307692 kHz
 Temp 1 [T1 0BW]
 13.15 dBm
 848.676602564 MHz
 Temp 2 [T1 0BW]
 12.52 dBm
 848.921794872 MHz

LVL
 EXT
 30dB

Center 848.8 MHz
 100 kHz/
 Span 1 MHz


©Copyright. All rights reserved by CCTL.

EGPRS 850-8PSK(99% BW)

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
824.2	245.19
836.6	245.19
848.8	246.79


EGPRS 850-8PSK

Channel 128-Occupied Bandwidth (99% BW)




Date: 2.APR.2017 12:40:30

Channel 190-Occupied Bandwidth (99% BW)



Date: 2.APR.2017 12:42:29

Channel 251-Occupied Bandwidth (99% BW)




Date: 2.APR.2017 12:45:41

PCS 1900(99% BW)

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
1850.2	245.19
1880.0	243.59
1909.8	245.19


PCS 1900

Channel 512-Occupied Bandwidth (99% BW)




Date: 2.APR.2017 12:57:03

Channel 661-Occupied Bandwidth (99% BW)



Date: 2.APR.2017 12:59:58

Channel 810-Occupied Bandwidth (99% BW)




Date: 2.APR.2017 13:01:42

GPRS 1900(99% BW)

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
1850.2	245.19
1880.0	246.79
1909.8	243.59


GPRS 1900

Channel 512-Occupied Bandwidth (99% BW)




Date: 2.APR.2017 13:46:42

Channel 661-Occupied Bandwidth (99% BW)



Date: 2.APR.2017 13:56:54

Channel 810-Occupied Bandwidth (99% BW)




Date: 2.APR.2017 13:58:02

EGPRS 1900-8PSK(99% BW)

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
1850.2	245.19
1880.0	243.59
1909.8	245.19


EGPRS 1900-8PSK

Channel 512-Occupied Bandwidth (99% BW)




Date: 2.APR.2017 13:47:10

Channel 661-Occupied Bandwidth (99% BW)



Date: 2.APR.2017 13:54:50

Channel 810-Occupied Bandwidth (99% BW)



Date: 2.APR.2017 13:58:39

A.5 EMISSION BANDWIDTH

Reference

FCC: CFR Part 22.917(b), 24.238(a)

A.5.1 Emission Bandwidth Results

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of PCS1900 band and GSM850 band. Table below lists the measured -26dB BW. Spectrum analyzer plots are included on the following pages.

GSM 850(-26dB BW)

Frequency(MHz)	Emission Bandwidth (-26dB BW)(kHz)
824.2	317.31
836.6	317.31
848.8	317.31


GSM 850

Channel 128-Emission Bandwidth (-26dB BW)




Date: 2.APR.2017 12:13:00

Channel 190-Emission Bandwidth (-26dB BW)



Date: 2.APR.2017 12:14:04

Channel 251-Emission Bandwidth (-26dB BW)




Date: 2.APR.2017 12:16:11

GPRS 850(-26dB BW)

Frequency(MHz)	Emission Bandwidth (-26dB BW)(kHz)
824.2	317.31
836.6	317.31
848.8	317.31


GPRS 850

Channel 128-Emission Bandwidth (-26dB BW)




Date: 2.APR.2017 12:34:05

Channel 190-Emission Bandwidth (-26dB BW)



Date: 2.APR.2017 12:35:21

Channel 251-Emission Bandwidth (-26dB BW)




Date: 2.APR.2017 12:37:26

EGPRS 850-8PSK(-26dB BW)

Frequency(MHz)	Emission Bandwidth (-26dB BW)(kHz)
824.2	320.51
836.6	317.31
848.8	318.91


EGPRS 850-8PSK

Channel 128-Emission Bandwidth (-26dB BW)




Date: 2.APR.2017 12:39:35

Channel 190-Emission Bandwidth (-26dB BW)



Date: 2.APR.2017 12:43:13

Channel 251-Emission Bandwidth (-26dB BW)




Date: 2.APR.2017 12:44:44

PCS 1900(-26dB BW)

Frequency(MHz)	Emission Bandwidth (-26dB BW)(kHz)
1850.2	318.91
1880.0	317.31
1909.8	315.71


PCS 1900

Channel 512-Emission Bandwidth (-26dB BW)




Date: 2.APR.2017 12:57:44

Channel 661-Emission Bandwidth (-26dB BW)



Date: 2.APR.2017 12:59:15

Channel 810-Emission Bandwidth (-26dB BW)




Date: 2.APR.2017 13:02:56

GPRS 1900(-26dB BW)

Frequency(MHz)	Emission Bandwidth (-26dB BW)(kHz)
1850.2	315.71
1880.0	317.31
1909.8	323.72


GPRS 1900

Channel 512-Emission Bandwidth (-26dB BW)




Date: 2.APR.2017 13:50:52

Channel 661-Emission Bandwidth (-26dB BW)



Date: 2.APR.2017 13:51:48

Channel 810-Emission Bandwidth (-26dB BW)




Date: 2.APR.2017 14:00:10

EGPRS 1900-8PSK(-26dB BW)

Frequency(MHz)	Emission Bandwidth (-26dB BW)(kHz)
1850.2	315.71
1880.0	320.91
1909.8	315.71


EGPRS 1900-8PSK

Channel 512-Emission Bandwidth (-26dB BW)




Date: 2.APR.2017 13:50:02

Channel 661-Emission Bandwidth (-26dB BW)



Date: 2.APR.2017 13:54:08

Channel 810-Emission Bandwidth (-26dB BW)



Date: 2.APR.2017 13:59:24

A.6 BAND EDGE COMPLIANCE

Reference


FCC: CFR Part 22.917(b), 24.238(a)

Measurement limit

On any frequency outside frequency band of the US Cellular/PCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43+10\log(P)$ dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm. According to KDB 971168 6.0, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.


GSM 850

LOW BAND EDGE BLOCK-A (GSM850)-Channel 128



Date: 2.APR.2017 12:17:58


HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251



Date: 2.APR.2017 12:17:15


GPRS 850

LOW BAND EDGE BLOCK-A (GSM850)-Channel 128




Date: 2.APR.2017 12:30:14

HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251




Date: 2.APR.2017 12:31:21

EGPRS 850-8PSK LOW BAND EDGE BLOCK-A (GSM850)-Channel 128



Date: 2.APR.2017 12:53:20


HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251



Date: 2.APR.2017 12:49:28


PCS 1900

LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 2.APR.2017 13:05:38


HIGH BAND EDGE BLOCK-C (PCS-1900) -Channel 810



Date: 2.APR.2017 13:04:25


GPRS 1900

LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 2.APR.2017 13:44:51


HIGH BAND EDGE BLOCK-C (PCS-1900) -Channel 810



Date: 2.APR.2017 13:42:16


EGPRS 1900-8PSK

LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 2.APR.2017 13:35:18

HIGH BAND EDGE BLOCK-C (PCS-1900) -Channel 810



Date: 2.APR.2017 13:39:18

A.7 CONDUCTED SPURIOUS EMISSION

Reference

FCC: CFR Part 2.1057, 22.917, 24.238.

A.7.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 9 GHz, data taken from 10 MHz to 25 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
3. According to KDB 971168 6.0, the applicable rule part specifies the reference bandwidth for measuring unwanted emission levels (typically, 100 kHz if the authorized frequency band/block is at or below 1 GHz and 1 MHz if the authorized frequency band/block is above 1 GHz)

GSM850 Transmitter

Channel	Frequency (MHz)
128	824.2
190	836.6
251	848.8

PCS1900 Transmitter

Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

A. 7.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.


A.7.3 Measurement result

GSM850

Channel 128: 30MHz – 1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 2.APR.2017 12:19:36


Channel 128: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 2.APR.2017 12:22:43

Channel 128: 2.5GHz – 7.5GHz
Spurious emission limit –13dBm.



Date: 2.APR.2017 12:23:27

Channel 128: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 5.MAR.2017 09:18:33

Channel 190: 30MHz – 1GHz

Spurious emission limit –13dBm


NOTE: peak above the limit line is the carrier frequency.



Date: 2.APR.2017 12:20:50


Channel 190: 1GHz –2.5GHz

Spurious emission limit –13dBm




Date: 2.APR.2017 12:22:25

Channel 190: 2.5GHz –7.5GHz
Spurious emission limit –13dBm



Date: 2.APR.2017 12:23:45

Channel 190: 7.5GHz –10GHz
Spurious emission limit –13dBm




Date: 2.APR.2017 12:25:16

Channel 251: 30MHz – 1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 2.APR.2017 12:21:28

Channel 251: 1GHz – 2.5GHz


Spurious emission limit –13dBm.



Date: 2.APR.2017 12:22:03

Channel 251:2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 2.APR.2017 12:24:00

Channel 251: 7.5GHz – 10GHz

Spurious emission limit –13dBm.




Date: 2.APR.2017 12:24:44

PCS1900

Channel 512: 30MHz – 1GHz

Spurious emission limit –13dBm.




Date: 2.APR.2017 13:08:01

Channel 512: 1GHz – 2.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 2.APR.2017 13:11:20

Channel 512: 2.5GHz – 7.5GHz
Spurious emission limit –13dBm.



Date: 2.APR.2017 13:12:08


Channel 512: 7.5GHz –10GHz
Spurious emission limit –13dBm.



Date: 2.APR.2017 13:14:39

Channel 512: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 2.APR.2017 13:15:31


Channel 512: 15GHz –20GHz

Spurious emission limit –13dBm.



Date: 2.APR.2017 13:18:34


Channel 661: 30MHz – 1GHz
Spurious emission limit –13dBm



Date: 2.APR.2017 13:08:38


Channel 661: 1GHz –2.5GHz
Spurious emission limit –13dBm

NOTE: peak above the limit line is the carrier frequency.




Date: 2.APR.2017 13:10:37

Channel 661: 2.5GHz –7.5GHz
Spurious emission limit –13dBm



Date: 2.APR.2017 13:12:27


Channel 661: 7.5GHz –10GHz
Spurious emission limit –13dBm



Date: 2.APR.2017 13:14:08

Channel 661: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 2.APR.2017 13:16:09

Channel 661: 15GHz –20GHz


Spurious emission limit –13dBm.



Date: 2.APR.2017 13:18:00

Channel 810: 30MHz – 1GHz

Spurious emission limit –13dBm.




Date: 2.APR.2017 13:09:09

Channel 810: 1GHz – 2.5GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 2.APR.2017 13:10:07

Channel 810: 2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 2.APR.2017 13:12:59

Channel 810: 7.5GHz – 10GHz


Spurious emission limit –13dBm.



Date: 2.APR.2017 13:13:37

Channel 810: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 2.APR.2017 13:16:43

Channel 810: 15GHz –20GHz

Spurious emission limit –13dBm.



Date: 2.APR.2017 13:17:27

END OF REPORT