

Assessment report No:

NIE: 56182RAN.001

Assessment report RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1091 ISED RSS -102 Issue 5:2015

Identification of item tested.....:	RF Transceiver / Base Station Repeater	
Trademark	PowerTrunk	
Model and /or type reference	BSR75 -8	
Other identification of the product	D138861PT FCC ID: WT7PTBSR75450B IC: 8624A-PTBSR75450B	
Final HW version	CCP: 0.03.35.34.36	
Final SW version	CCP: 0.03.35.34.36	
Features	TETRA and TI D-LMR	
Manufacturer	TELTRONIC, S.A.U. Polígono Malpica, Calle C/F-Oeste (50016). Zaragoza (SPAIN)	
Test method requested, standard.....:	FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices. ISED RSS-102 Issue 5 (2015-03) – Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)	
Summary	IN COMPLIANCE	
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager	 MIGUEL LACAVE GARCÍA 2018.03.02 10:34:44 +01'00'
Date of issue	2018-03-02	
Report template No.....:	FAN24_01	

Index

Competences and guarantees.....	3
General conditions.....	3
Identification of the client	3
General description of the device under evaluation	4
Assessment summary	5
Appendix A – FCC RF Exposure	6
FCC RF Exposure evaluation for mobile devices.....	7
FCC MPE Evaluation Results.....	8
Appendix B – ISED RF Exposure.....	10
ISED RF Exposure evaluation for mobile devices	11
ISED MPE Evaluation Results	12

Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General conditions

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This assessment report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA and the Accreditation Bodies.

Identification of the client

TELTRONIC, S.A.U.

Polígono Malpica, Calle C/F-Oeste (50016). Zaragoza (SPAIN)

General description of the device under evaluation

The device under evaluation consists of a digital RF transceiver aimed at providing the PowerTrunk-T Infrastructure with a TETRA carrier. It has been conceived as a module to be integrated in a PowerTrunk-T Cabinet with an SBS configuration (Site Base Station). The BSR75 -8 operates in the frequency band 450-470 MHz and provides an RF output power of 75 W in the whole band.

The device is intended to be used only for occupational use, persons will be exposed as a consequence of their employment, and will be fully aware of, and can exercise control over, their exposure. It is not intended for use by members of the general public. During its normal use the separation distance between the antenna and the user will be greater than 550 cm.

Regulation Body	Modulation	Band (MHz)	RF output power (dBm)	Max. antenna gain (dBi)	Maximum Radiated power (E.I.R.P.) (dBm)	Maximum Radiated power (E.I.R.P.) (mW)
FCC	TETRA, TI D-LMR	450.0–470.0	48.75±1	15.0	64.75	2985382.6
ISED	TETRA	450.0–470.0	48.75±1	15.0	64.75	2985382.6

Table 1: Maximum radiated output power

Assessment summary

Radiofrequency radiation exposure limits			
FCC 47 CFR § 2.1091 & ISED RSS-102 Issue 5 (2015-03)			
Regulation Body	Modulation	Band (MHz)	VERDICT (Pass/Fail)
FCC	TETRA, TI D-LMR	450.0-470.0	Pass
ISED	TETRA	450.0-470.0	Pass

Table 2: Assessment summary

Appendix A – FCC RF Exposure

FCC RF Exposure evaluation for mobile devices

Devices operating in standalone mobile device exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated. The minimum test separation distance required for a device to comply with mobile device exposure conditions must be clearly identified in the installation and operating instructions, for all installation and exposure conditions, to enable users and installers to comply with RF exposure requirements. For mobile devices that have the potential to operate in portable device exposure conditions, similar to the configurations described in § 2.1091(d)(4), a KDB inquiry is required to determine the SAR test requirements for demonstrating compliance.

When a device qualifies for the categorical exclusion provision of § 2.1091(c), the minimum test separation distance may be estimated, when applicable, by simple calculations according to plane-wave equivalent conditions, to ensure the transmitter and its antenna(s) can operate in manners that meet or exceed the estimated distance. The source-based time-averaged maximum radiated power, according to the maximum antenna gain, must be applied to calculate the field strength and power density required to establish the minimum test separation distance. When the estimated test separation distance becomes overly conservative and does not support compliance, MPE measurement or computational modeling may be used to determine the required minimum separation distance.

According to §1.1310 Radiofrequency radiation exposure limits, paragraph (e), the limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields are:

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*100	6
3.0–30	1842/f	4.89/f	*900/f ²	6
30–300	61.4	0.163	1.0	6
300–1,500			f/300	6
1,500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*100	30
1.34–30	824/f	2.19/f	*180/f ²	30
30–300	27.5	0.073	0.2	30
300–1,500			f/1500	30
1,500–100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

FCC MPE Evaluation Results

Each supported transmission technology will be evaluated to determine if they are in compliance with limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields for Occupational/Controlled Exposure.

In order to perform the assessment, the following equations have been used for the calculations:

$$\text{Power density: } S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2}$$

$$\text{Minimum compliance distance: } R_{\min}[cm] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW/cm^2]}}$$

Where:

S = power density

$P_{E.I.R.P.}$ = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

$R_{\min}$ = distance to the center of radiation of the antenna

TETRA and TI D-LMR – 450 MHz Band

Maximum output power (dBm):	49.75
Maximum output power (mW):	94406
Maximum antenna gain (dBi):	15.0
Maximum antenna gain (numerical):	31.62
Worst Case Frequency (MHz):	450.0
Maximum EIRP (dBm):	64.75
Maximum EIRP (mW):	2985382.6
Minimum use distance (cm):	550.0

Power density at minimum use distance:

Power density (mW/cm2):	0.785
Occupational/Controlled Exposure - Power density limit (mW/cm2):	1.50
Verdict for Occupational/Controlled Exposure:	PASS

The power density level for TETRA and TI D-LMR transmission modes is below the Occupational/Controlled Exposure power density limit.

Minimum compliance distance for this technology:

Minimum compliance distance for Occupational/Controlled Exposure (cm):	397.97
Minimum use distance (cm):	550
Verdict for Occupational/Controlled Exposure:	PASS

The minimum use distance is greater than the Occupational/Controlled Exposure minimum compliance distance.

Appendix B – ISED RF Exposure

ISED RF Exposure evaluation for mobile devices

According to RSS-102 Issue 5, Paragraph “4. Exposure Limits”, Industry of Canada has adopted the RF field strength limits established in Health Canada’s RF exposure guideline, Safety code 6. The limits for Controlled Environment are:

Table 6: RF Field Strength Limits for Controlled Use Devices (Controlled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²³	170	180	-	Instantaneous*
0.1-10	-	1.6/ f	-	6**
1.29-10	193/ $f^{0.5}$	-	-	6**
10-20	61.4	0.163	10	6
20-48	129.8/ $f^{0.25}$	0.3444/ $f^{0.25}$	44.72/ $f^{0.5}$	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 $f^{0.25}$	0.04138 $f^{0.25}$	0.6455 $f^{0.5}$	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000/ $f^{1.2}$
150000-300000	0.354 $f^{0.5}$	9.40 x 10 ⁻⁴ $f^{0.5}$	3.33 x 10 ⁻⁴ f	616000/ $f^{1.2}$
Note: f is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

ISED MPE Evaluation Results

Each supported transmission technology will be evaluated to determine if it is in compliance with RSS102 Issue 5, RF Field Strength Limits for Controlled Environment.

In order to perform the assessment, the following equations have been used for the calculations:

$$\text{Power density: } S[W/m^2] = \frac{P_{E.I.R.P.}[W]}{4\pi R[m]^2}$$

$$\text{Minimum compliance distance: } R_{\min}[m] = \sqrt{\frac{P_{E.I.R.P.}[W]}{4\pi S[W/m^2]}}$$

Where:

S = power density

$P_{E.I.R.P.}$ = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

$R_{\min}$ = distance to the center of radiation of the antenna

TETRA – 450 MHz Band

Maximum output power (dBm):	49.75
Maximum output power (W):	94.41
Maximum antenna gain (dBi):	15.0
Maximum antenna gain (numerical):	31.62
Worst Case Frequency (MHz):	450.0
Maximum EIRP (dBm):	64.75
Maximum EIRP (W):	2985.38
Minimum use distance (m):	5.5

Power density at minimum use distance:

Power density (W/m ²):	7.86
Controlled Environment - Power density limit (W/m ²):	13.69
Verdict for Controlled Environment exposure:	PASS

The power density level for TETRA transmission mode is below the Controlled Environment power density limit.

Minimum compliance distance for this technology:

Minimum compliance distance for Controlled Environment (m):	4.17
Minimum use distance (m):	5.5
Verdict for Controlled Environment exposure:	PASS

The minimum use distance is greater than the Controlled Environment minimum compliance distance.