

Assessment report No:

NIE: 51555RAN.002

Assessment report RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1091 ISED RSS -102 Issue 5:2015

Identification of item tested.....:	Radio car with Bluetooth handsfree
Trademark	Panasonic
Model and /or type reference	NTG5*2 US, NTG5*2 BASE, NTG5*2 CD
Other identification of the product	FCC ID: WUQ-NTG5STAR2 IC: 216R- NTG5STAR2
Final HW version	C3 samples
Final SW version	E528.0
Features	NTG5*2 US: Bluetooth EDR, GPS, AM/FM receiver NTG5*2 BASE: Bluetooth EDR, AM/FM receiver NTG5*2 CD: Bluetooth EDR, GPS, AM/FM receiver
Manufacturer	Panasonic Automotive & Industrial Systems Europe GmbH Robert Bosch Str. 27-29 – 63225 Langen. Germany
Test method requested, standard.....:	FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices. ISED RSS-102 Issue 5 (2015-03) – Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager 
Date of issue	2017-02-24
Report template No.....:	FAN24_01

MIGUEL LACAVE
GARCÍA
2017.02.24 14:01:10
+01'00'

Index

Competences and guarantees.....	3
General conditions.....	3
Identification of the client	3
General description of the device under evaluation	3
Remarks and comments.....	4
Assessment summary	6
Appendix A – FCC RF Exposure	7
FCC RF Exposure evaluation for mobile devices.....	8
FCC MPE Evaluation Results.....	9
Appendix B – ISED RF Exposure.....	11
ISED RF Exposure evaluation for mobile devices	12
ISED MPE Evaluation Results	13

Competences and guarantees

In order to assure the traceability to other national and international laboratories, AT4 wireless has a calibration and maintenance program for its measurement equipment.

AT4 wireless guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at AT4 wireless at the time of performance of the test.

AT4 wireless is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of AT4 wireless.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of AT4 wireless.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of AT4 wireless and the Accreditation Bodies.

Identification of the client

Panasonic Automotive & Industrial Systems Europe GmbH

Robert Bosch Str. 27-29 – 63225 Langen.

Germany

General description of the device under evaluation

The device under evaluation consists on a radio car with Bluetooth handsfree interface. The device will be installed in a car, and there will be a distance greater than 20 cm from any passenger inside the car; therefore the evaluation distance used for this assessment has been 20 cm.

The equipment specifications declared by the manufacturer for the Bluetooth technology are:

Frequency Range (MHz)	Technology	Maximum RF output power (dBm)	Maximum RF output power (mW)	Maximum Antenna gain (dBi)	Maximum E.I.R.P. (dBm)	Maximum E.I.R.P. (mW)
2408-2480	Bluetooth EDR	3.979	2.5	+2.4	6.38	4.34

Table 1: Output power and antenna gain values

Remarks and comments

The assessment included in this document is valid for models NTG5*2 CD and NTG5*2 BASE which, according to manufacturer's declaration, presents no RF and EMC functional differences with respect to each other. See declaration below.

Panasonic

Panasonic Automotive & Industrial Systems Europe GmbH
Office Langen

Panasonic Automotive & Industrial Systems Europe • Robert-Bosch-Straße 27-29, D-63225 Langen

Panasonic Automotive & Industrial Systems Europe GmbH
Robert-Bosch-Straße 27-29, D-63225 Langen

Telefon: +49 (0) 6103/ 3759 - 198
Telefax: +49 (0) 6103/ 3759 - 343

Ihr Zeichen

Ihre Nachricht vom

Unser Zeichen

Sachbearbeiter
Mario Mueller

☎
-306

Datum
22.12.2016

ATTESTATION STATEMENT
Declaration on Electrically Identical Models


TO WHOM IT MAY CONCERN

We, Panasonic Automotive & Industrial Systems Europe GmbH, located in Robert-Bosch Str.27-29, Langen, 63225, Germany, declare on our sole responsibility that the equipment NTG5*2 US is identical in hardware and software to the equipment family models NTG5*2 CD. Model NTG5*2 BASE is a depopulated version of NTG5*2 CD.

Model name change is due to NTG5*2 US is only going to be imported and commercialized in USA, Canada and Mexico.

Model name	Diference between models
NTG5*2 US	FCC ID: WUQ-NTG5STAR2 Model product with the same RF feature as NTG5*2 CD.
NTG5*2 CD	FCC ID: WUQ-NTG5STAR2 Original base model with same RF feature as NTG5*2 US.
NTG5*2 BASE	FCC ID: WUQ-NTG5STAR2 Family model of NTG5*2 CD. Differences from original base model are: - CD feature is removed - GPS navigation is removed - MOST IF is removed

We attest that above changes are not relevant for any RF behaviour subject to regulatory items.



By: Reza Malekzadeh
Title: Manager
Company: Panasonic Automotive & Industrial Systems Europe GmbH
Telephone: +49 (0)711 79723 439
e-mail: reza.malekzadeh@eu.panasonic.com

Panasonic Automotive & Industrial Systems Europe GmbH
(Headquarters)

Robert-Bosch-Straße 27-29

63225 Langen, Germany

Vorsitzender des Aufsichtsrats:
Geschäftsführer:

Laurent Abadie
Masahisa Shibata
Johannes Spatz
Takeyuki Yamanaka

Bankverbindung:
Deutsche Bank Hamburg
IBAN: DE 57 2007 0000 0061 4123 00
BIC: DEUTDE33HAN

Amtsgericht
Offenbach
HRB-43170

Assessment summary

Radiofrequency radiation exposure limits		
FCC 47 CFR § 2.1091 & ISSED RSS-102 Issue 5 (2015-03)		
Band (MHz)	Technology	VERDICT (Pass/Fail)
2450	Bluetooth EDR	Pass

Table 2: Assessment summary.

Appendix A – FCC RF Exposure

FCC RF Exposure evaluation for mobile devices

Devices operating in standalone mobile device exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated. The minimum test separation distance required for a device to comply with mobile device exposure conditions must be clearly identified in the installation and operating instructions, for all installation and exposure conditions, to enable users and installers to comply with RF exposure requirements. For mobile devices that have the potential to operate in portable device exposure conditions, similar to the configurations described in § 2.1091(d)(4), a KDB inquiry is required to determine the SAR test requirements for demonstrating compliance.

When a device qualifies for the categorical exclusion provision of § 2.1091(c), the minimum test separation distance may be estimated, when applicable, by simple calculations according to plane-wave equivalent conditions, to ensure the transmitter and its antenna(s) can operate in manners that meet or exceed the estimated distance. The source-based time-averaged maximum radiated power, according to the maximum antenna gain, must be applied to calculate the field strength and power density required to establish the minimum test separation distance. When the estimated test separation distance becomes overly conservative and does not support compliance, MPE measurement or computational modeling may be used to determine the required minimum separation distance.

According to §1.1310 Radiofrequency radiation exposure limits, paragraph (e), the limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields are:

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	* 100	6
3.0–30	1842/f	4.89/f	* 900/f ²	6
30–300	61.4	0.163	1.0	6
300–1,500			f/300	6
1,500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	* 100	30
1.34–30	824/f	2.19/f	* 180/f ²	30
30–300	27.5	0.073	0.2	30
300–1,500			f/1500	30
1,500–100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

FCC MPE Evaluation Results

In order to perform the assessment, the following equations have been used for the calculations:

$$\text{Power density: } S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2}$$

$$\text{Minimum compliance distance: } R_{\min}[m] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW/cm^2]}}$$

Where:

S = power density

$P_{E.I.R.P.}$ = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

$R_{\min}$ = distance to the center of radiation of the antenna

Assessment for Bluetooth EDR– 2450 Mhz Band

Maximum output power (dBm):	3.98
Antenna Gain (dBi):	+2.40
Minimum use distance (cm):	0.20
Worst Case Frequency (MHz):	2408
Maximum EIRP (dBm):	6.38
Maximum EIRP (mW):	4.34
General public - Power density limit (mW/cm2):	1.00

Power density at minimum use distance:

Power density (mW/cm2):	0.001
Verdict for general public:	PASS

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

Minimum distance for general public (cm):	0.59
Verdict for general public:	PASS

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.

Appendix B – ISED RF Exposure

ISED RF Exposure evaluation for mobile devices

According to RSS-102 Issue 5, Paragraph “4. Exposure Limits”, Industry of Canada has adopted the RF field strength limits established in Health Canada’s RF exposure guideline, Safety code 6:

**Table 4: RF Field Strength Limits for Devices Used by the General Public
(Uncontrolled Environment)**

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ $f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ $f^{0.25}$	0.1540/ $f^{0.25}$	8.944/ $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 x 10 ⁻⁴ $f^{0.5}$	6.67 x 10 ⁻⁵ f	616000/ $f^{1.2}$
Note: f is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

Table 6: RF Field Strength Limits for Controlled Use Devices (Controlled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²³	170	180	-	Instantaneous*
0.1-10	-	1.6/ f	-	6**
1.29-10	193/ $f^{0.5}$	-	-	6**
10-20	61.4	0.163	10	6
20-48	129.8/ $f^{0.25}$	0.3444/ $f^{0.25}$	44.72/ $f^{0.5}$	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 $f^{0.25}$	0.04138 $f^{0.25}$	0.6455 $f^{0.5}$	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000/ $f^{1.2}$
150000-300000	0.354 $f^{0.5}$	9.40 x 10 ⁻⁴ $f^{0.5}$	3.33 x 10 ⁻⁴ f	616000/ $f^{1.2}$
Note: f is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

ISED MPE Evaluation Results

In order to perform the assessment, the following equations have been used for the calculations:

$$\text{Power density: } S[W/m^2] = \frac{P_{E.I.R.P.}[W]}{4\pi R[m]^2}$$

$$\text{Minimum compliance distance: } R_{\min}[m] = \sqrt{\frac{P_{E.I.R.P.}[W]}{4\pi S[W/m^2]}}$$

Where:

S = power density

$P_{E.I.R.P.}$ = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

$R_{\min}$ = distance to the center of radiation of the antenna

Assessment for Bluetooth EDR– 2450 Mhz Band

Maximum output power (dBm):	3.98
Antenna Gain (dBi):	+2.40
Minimum use distance (cm):	0.20
Worst Case Frequency (MHz):	2408
Maximum EIRP (dBm):	6.38
Maximum EIRP (mW):	4.34
General public - Power density limit (W/m2):	5.36

Power density at minimum use distance:

Power density (W/m2):	0.01
Verdict for general public:	PASS

The power density level for this transmission mode is below general public and controlled exposure power density limits.

Minimum compliance distance for this technology:

Minimum distance for general public (cm):	0.80
Verdict for general public:	PASS

The minimum use distance is larger than general public and controlled exposure minimum compliance distances.