



# FCC RF Test Report

APPLICANT : Brightstar Corporation  
EQUIPMENT : Smart phone  
BRAND NAME : Avvio  
MODEL NAME : Avvio 787S, Avvio 787  
FCC ID : WVBA787X  
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)  
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Mar. 12, 2015 and testing was completed on Mar. 18, 2015. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (SHENZHEN) INC.**

1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,  
Nanshan District, Shenzhen, Guangdong, P. R. China



## TABLE OF CONTENTS

|                                                                                       |           |
|---------------------------------------------------------------------------------------|-----------|
| <b>REVISION HISTORY.....</b>                                                          | <b>3</b>  |
| <b>SUMMARY OF TEST RESULT .....</b>                                                   | <b>4</b>  |
| <b>1 GENERAL DESCRIPTION .....</b>                                                    | <b>5</b>  |
| 1.1 Applicant.....                                                                    | 5         |
| 1.2 Manufacturer .....                                                                | 5         |
| 1.3 Product Feature of Equipment Under Test .....                                     | 5         |
| 1.4 Product Specification subjective to this standard.....                            | 6         |
| 1.5 Modification of EUT .....                                                         | 6         |
| 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator .....        | 6         |
| 1.7 Testing Location .....                                                            | 7         |
| 1.8 Applicable Standards .....                                                        | 7         |
| <b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>                             | <b>8</b>  |
| 2.1 Test Mode.....                                                                    | 8         |
| 2.2 Connection Diagram of Test System .....                                           | 11        |
| 2.3 Support Unit used in test configuration .....                                     | 11        |
| 2.4 Measurement Results Explanation Example .....                                     | 12        |
| <b>3 TEST RESULT .....</b>                                                            | <b>13</b> |
| 3.1 Conducted Output Power Measurement.....                                           | 13        |
| 3.2 Peak-to-Average Ratio .....                                                       | 15        |
| 3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement ..... | 21        |
| 3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....                        | 25        |
| 3.5 Band Edge Measurement.....                                                        | 39        |
| 3.6 Conducted Spurious Emission Measurement.....                                      | 48        |
| 3.7 Field Strength of Spurious Radiation Measurement .....                            | 61        |
| 3.8 Frequency Stability Measurement.....                                              | 67        |
| <b>4 LIST OF MEASURING EQUIPMENT .....</b>                                            | <b>72</b> |
| <b>5 UNCERTAINTY OF EVALUATION .....</b>                                              | <b>73</b> |
| <b>APPENDIX A. SETUP PHOTOGRAPHS</b>                                                  |           |



## REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION             | ISSUED DATE   |
|------------|---------|-------------------------|---------------|
| FG531211   | Rev. 01 | Initial issue of report | Mar. 27, 2015 |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |

## SUMMARY OF TEST RESULT

| Report Section | FCC Rule                            | Description                                   | Limit                                           | Result | Remark                                     |
|----------------|-------------------------------------|-----------------------------------------------|-------------------------------------------------|--------|--------------------------------------------|
| 3.1            | §2.1046                             | Conducted Output Power                        | N/A                                             | PASS   | -                                          |
| 3.2            | §24.232(d)                          | Peak-to-Average Ratio                         | <13 dB                                          | PASS   | -                                          |
| 3.3            | §22.913(a)(2)                       | Effective Radiated Power                      | < 7 Watts                                       | PASS   | -                                          |
|                | §24.232(c)                          | Equivalent Isotropic Radiated Power           | < 2 Watts                                       | PASS   | -                                          |
| 3.4            | §2.1049<br>§22.917(b)<br>§24.238(b) | Occupied Bandwidth                            | N/A                                             | PASS   | -                                          |
| 3.5            | §2.1051<br>§22.917(a)<br>§24.238(a) | Band Edge Measurement                         | $< 43 + 10\log_{10}(P[\text{Watts}])$           | PASS   | -                                          |
| 3.6            | §2.1051<br>§22.917(a)<br>§24.238(a) | Conducted Spurious Emission                   | $< 43 + 10\log_{10}(P[\text{Watts}])$           | PASS   | -                                          |
| 3.7            | §2.1053<br>§22.917(a)<br>§24.238(a) | Field Strength of Spurious Radiation          | $< 43 + 10\log_{10}(P[\text{Watts}])$           | PASS   | Under limit<br>27.91 dB at<br>3760.000 MHz |
| 3.8            | §2.1055<br>§22.355                  | Frequency Stability for Temperature & Voltage | < 2.5 ppm for Part 22<br>Within Authorized Band | PASS   | -                                          |
|                | §2.1055<br>§24.235                  |                                               |                                                 |        |                                            |



# 1 General Description

## 1.1 Applicant

**Brightstar Corporation**

9725 NW 117th Ave., Miami, Florida, FL 33178, United States

## 1.2 Manufacturer

**KCMobile Co., Ltd.**

#1305-1, Kolon Digital Tower Villant II, 31, Digital-ro 30-gil, Guro-Gu, Seoul, KOREA (152-727)

## 1.3 Product Feature of Equipment Under Test

| Product Feature                 |                                                                                                                         |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Equipment                       | Smart phone                                                                                                             |
| Brand Name                      | Avvio                                                                                                                   |
| Model Name                      | Avvio 787S, Avvio 787                                                                                                   |
| FCC ID                          | WVBA787X                                                                                                                |
| EUT supports Radios application | GSM/GPRS/EGPRS(Downlink Only)/WCDMA/HSPA<br>WLAN 2.4GHz 802.11b/g/n HT20/HT40<br>Bluetooth v3.0 + EDR/Bluetooth v4.0 LE |
| HW Version                      | M7206_V1.5                                                                                                              |
| EUT Stage                       | Production Unit                                                                                                         |

### Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two different types of EUT. They are single SIM card mobile (Model Name: Avvio 787) and dual SIM card mobile (Model Name: Avvio 787S). The others are the same including circuit design, PCB board, structure and all components. It is special to declare. After pre-scan two types of EUT, we found test result of the sample that dual SIM (Model Name: Avvio 787S) was the worst, so we chose dual SIM card mobile to perform all test.

## 1.4 Product Specification subjective to this standard

| Product Specification subjective to this standard |                                                                                                                                                    |
|---------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Tx Frequency</b>                               | GSM850: 824.2 MHz ~ 848.8 MHz<br>GSM1900: 1850.2 MHz ~ 1909.8MHz<br>WCDMA Band V: 826.4 MHz ~ 846.6 MHz<br>WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz  |
| <b>Rx Frequency</b>                               | GSM850: 869.2 MHz ~ 893.8 MHz<br>GSM1900: 1930.2 MHz ~ 1989.8 MHz<br>WCDMA Band V: 871.4 MHz ~ 891.6 MHz<br>WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz |
| <b>Maximum Output Power to Antenna</b>            | GSM850 : 32.99 dBm<br>GSM1900 : 30.25 dBm<br>WCDMA Band V : 22.85 dBm<br>WCDMA Band II : 23.51 dBm                                                 |
| <b>Antenna Type</b>                               | FIFA Antenna                                                                                                                                       |
| <b>Type of Modulation</b>                         | GSM: GMSK<br>GPRS: GMSK<br>EDGE: GMSK / 8PSK (Downlink Only)<br>WCDMA: QPSK (Uplink)<br>HSDPA: QPSK (Uplink)<br>HSUPA: QPSK (Uplink)               |

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

| FCC Rule | System                     | Type of Modulation | Maximum ERP/EIRP (W) | Frequency Tolerance (ppm) | Emission Designator |
|----------|----------------------------|--------------------|----------------------|---------------------------|---------------------|
| Part 22  | GSM850 GSM                 | GMSK               | 0.7192               | 0.0096 ppm                | 248KGXW             |
| Part 22  | WCDMA Band V RMC 12.2Kbps  | QPSK               | 0.0622               | 0.0227 ppm                | 4M16F9W             |
| Part 24  | GSM1900 GSM                | GMSK               | 0.9251               | 0.0064 ppm                | 250KGXW             |
| Part 24  | WCDMA Band II RMC 12.2Kbps | QPSK               | 0.2047               | 0.0048 ppm                | 4M16F9W             |

## 1.7 Testing Location

|                           |                                                                                                                                                                                     |          |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| <b>Test Site</b>          | SPORTON INTERNATIONAL (SHENZHEN) INC.                                                                                                                                               |          |
| <b>Test Site Location</b> | 1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China<br>TEL: +86-755-8637-9589<br>FAX: +86-755-8637-9595 |          |
| <b>Test Site No.</b>      | <b>Sporton Site No.</b>                                                                                                                                                             |          |
|                           | TH01-SZ                                                                                                                                                                             | OTA02-SZ |

|                           |                                                                                                                                                                 |                             |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| <b>Test Site</b>          | SPORTON INTERNATIONAL (SHENZHEN) INC.                                                                                                                           |                             |
| <b>Test Site Location</b> | No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China<br>TEL: +86-755- 3320-2398 |                             |
| <b>Test Site No.</b>      | <b>Sporton Site No.</b>                                                                                                                                         | <b>FCC Registration No.</b> |
|                           | 03CH02-SZ                                                                                                                                                       | 831040                      |

**Note:** The test site complies with ANSI C63.4 2009 requirement.

## 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

| Test Modes    |                     |                     |
|---------------|---------------------|---------------------|
| Band          | Radiated TCs        | Conducted TCs       |
| GSM 850       | ■ GSM Link          | ■ GSM Link          |
| GSM 1900      | ■ GSM Link          | ■ GSM Link          |
| WCDMA Band V  | ■ RMC 12.2Kbps Link | ■ RMC 12.2Kbps Link |
| WCDMA Band II | ■ RMC 12.2Kbps Link | ■ RMC 12.2Kbps Link |

**Conducted Power Measurement Results:**
**For SIM1:**

| Conducted Power (*Unit: dBm) |        |       |       |         |        |        |
|------------------------------|--------|-------|-------|---------|--------|--------|
| Band                         | GSM850 |       |       | GSM1900 |        |        |
| Channel                      | 128    | 189   | 251   | 512     | 661    | 810    |
| Frequency                    | 824.2  | 836.4 | 848.8 | 1850.2  | 1880.0 | 1909.8 |
| GSM                          | 32.99  | 32.98 | 32.95 | 30.24   | 30.12  | 30.25  |
| GPRS class 8                 | 32.95  | 32.94 | 32.89 | 30.21   | 30.03  | 30.23  |
| GPRS class 10                | 30.56  | 30.52 | 30.45 | 28.62   | 28.55  | 28.72  |
| GPRS class 11                | 28.59  | 28.54 | 28.47 | 26.58   | 26.54  | 26.72  |
| GPRS class 12                | 27.58  | 27.55 | 27.48 | 24.53   | 24.46  | 24.66  |


| Conducted Power (*Unit: dBm) |              |       |       |               |        |        |
|------------------------------|--------------|-------|-------|---------------|--------|--------|
| Band                         | WCDMA Band V |       |       | WCDMA Band II |        |        |
| Channel                      | 4132         | 4182  | 4233  | 9262          | 9400   | 9538   |
| Frequency                    | 826.4        | 836.4 | 846.6 | 1852.4        | 1880.0 | 1907.6 |
| AMR 12.2K                    | 22.84        | 22.75 | 22.59 | 23.22         | 23.50  | 23.09  |
| RMC 12.2K                    | 22.85        | 22.76 | 22.60 | 23.23         | 23.51  | 23.10  |
| HSDPA Subtest-1              | 21.59        | 21.41 | 21.43 | 21.56         | 21.91  | 21.61  |
| HSDPA Subtest-2              | 21.58        | 21.43 | 21.48 | 21.56         | 21.91  | 21.65  |
| HSDPA Subtest-3              | 21.13        | 20.97 | 21.02 | 21.09         | 21.46  | 21.16  |
| HSDPA Subtest-4              | 21.10        | 20.96 | 20.96 | 21.05         | 21.44  | 21.12  |
| HSUPA Subtest-1              | 19.54        | 19.43 | 19.57 | 19.60         | 19.92  | 19.70  |
| HSUPA Subtest-2              | 19.55        | 19.46 | 19.55 | 19.59         | 19.93  | 19.72  |
| HSUPA Subtest-3              | 20.58        | 20.47 | 20.52 | 20.58         | 20.91  | 20.64  |
| HSUPA Subtest-4              | 19.05        | 18.95 | 18.99 | 19.04         | 19.41  | 19.14  |
| HSUPA Subtest-5              | 21.60        | 21.40 | 21.50 | 21.60         | 21.90  | 21.60  |

For SIM2:

| Conducted Power (*Unit: dBm) |        |       |       |         |        |        |
|------------------------------|--------|-------|-------|---------|--------|--------|
| Band                         | GSM850 |       |       | GSM1900 |        |        |
| Channel                      | 128    | 189   | 251   | 512     | 661    | 810    |
| Frequency                    | 824.2  | 836.4 | 848.8 | 1850.2  | 1880.0 | 1909.8 |
| GSM                          | 32.98  | 32.96 | 32.94 | 30.22   | 30.11  | 30.23  |
| GPRS class 8                 | 32.93  | 32.92 | 32.88 | 30.20   | 30.01  | 30.22  |
| GPRS class 10                | 30.54  | 30.51 | 30.43 | 28.60   | 28.54  | 28.71  |
| GPRS class 11                | 28.57  | 28.52 | 28.46 | 26.57   | 26.52  | 26.70  |
| GPRS class 12                | 27.57  | 27.52 | 27.46 | 24.50   | 24.44  | 24.65  |

| Conducted Power (*Unit: dBm) |              |       |       |               |        |        |
|------------------------------|--------------|-------|-------|---------------|--------|--------|
| Band                         | WCDMA Band V |       |       | WCDMA Band II |        |        |
| Channel                      | 4132         | 4182  | 4233  | 9262          | 9400   | 9538   |
| Frequency                    | 826.4        | 836.4 | 846.6 | 1852.4        | 1880.0 | 1907.6 |
| AMR 12.2K                    | 22.81        | 22.73 | 22.56 | 23.20         | 23.47  | 23.06  |
| RMC 12.2K                    | 22.82        | 22.74 | 22.58 | 23.21         | 23.48  | 23.07  |
| HSDPA Subtest-1              | 21.58        | 21.40 | 21.42 | 21.54         | 21.90  | 21.60  |
| HSDPA Subtest-2              | 21.56        | 21.40 | 21.46 | 21.53         | 21.88  | 21.63  |
| HSDPA Subtest-3              | 21.10        | 20.96 | 20.98 | 21.07         | 21.45  | 21.15  |
| HSDPA Subtest-4              | 21.08        | 20.95 | 20.95 | 21.03         | 21.43  | 21.10  |
| HSUPA Subtest-1              | 19.53        | 19.42 | 19.55 | 19.56         | 19.90  | 19.68  |
| HSUPA Subtest-2              | 19.54        | 19.44 | 19.54 | 19.57         | 19.90  | 19.70  |
| HSUPA Subtest-3              | 20.56        | 20.46 | 20.50 | 20.57         | 20.90  | 20.63  |
| HSUPA Subtest-4              | 19.03        | 18.92 | 18.96 | 19.03         | 19.40  | 19.12  |
| HSUPA Subtest-5              | 21.59        | 21.38 | 21.48 | 21.58         | 21.88  | 21.59  |

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration

| Item | Equipment        | Trade Name | Model No. | FCC ID | Data Cable | Power Cord        |
|------|------------------|------------|-----------|--------|------------|-------------------|
| 1.   | System Simulator | R&S        | CMU 200   | N/A    | N/A        | Unshielded, 1.8 m |
| 2.   | DC Power Supply  | GW         | GPS-3030D | N/A    | N/A        | Unshielded, 1.8 m |



## 2.4 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

The following shows an offset computation example with RF cable loss 4.5 dB and a 10dB attenuator.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.5 + 10 = 14.5 \text{ (dB)}\end{aligned}$$

### **3 Test Result**

#### **3.1 Conducted Output Power Measurement**

##### **3.1.1 Description of the Conducted Output Power Measurement**

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


##### **3.1.2 Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

##### **3.1.3 Test Procedures**

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

##### **3.1.4 Test Setup**



### 3.1.5 Test Result of Conducted Output Power

| Cellular Band            |              |              |               |                             |               |                |
|--------------------------|--------------|--------------|---------------|-----------------------------|---------------|----------------|
| Modes                    | GSM850 (GSM) |              |               | WCDMA Band V (RMC 12.2Kbps) |               |                |
| Channel                  | 128<br>(Low) | 189<br>(Mid) | 251<br>(High) | 4132<br>(Low)               | 4182<br>(Mid) | 4233<br>(High) |
| Frequency<br>(MHz)       | 824.2        | 836.4        | 848.8         | 826.4                       | 836.4         | 846.6          |
| Conducted<br>Power (dBm) | 32.99        | 32.98        | 32.95         | 22.85                       | 22.76         | 22.60          |

| PCS Band                 |               |              |               |                              |               |                |
|--------------------------|---------------|--------------|---------------|------------------------------|---------------|----------------|
| Modes                    | GSM1900 (GSM) |              |               | WCDMA Band II (RMC 12.2Kbps) |               |                |
| Channel                  | 512<br>(Low)  | 661<br>(Mid) | 810<br>(High) | 9262<br>(Low)                | 9400<br>(Mid) | 9538<br>(High) |
| Frequency<br>(MHz)       | 1850.2        | 1880         | 1909.8        | 1852.4                       | 1880          | 1907.6         |
| Conducted<br>Power (dBm) | 30.24         | 30.12        | 30.25         | 23.23                        | 23.51         | 23.10          |

**Note:** maximum burst average power for GSM and maximum average power for WCDMA.

## 3.2 Peak-to-Average Ratio

### 3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.7.1.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. For GSM/EGPRS operating modes:
  - a. Set EUT in maximum power output.
  - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector on spectrum analyzer for first trace.
  - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector on spectrum analyzer for second trace.
  - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator has synchronized with the spectrum analyzer.
4. For UMTS operating modes:
  - a. Set the CCDF (Complementary Cumulative Distribution Function) option on the spectrum analyzer.
  - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Peak-to-Average Ratio


| PCS Band                      |               |              |               |                              |               |                |
|-------------------------------|---------------|--------------|---------------|------------------------------|---------------|----------------|
| Modes                         | GSM1900 (GSM) |              |               | WCDMA Band II (RMC 12.2Kbps) |               |                |
| Channel                       | 512<br>(Low)  | 661<br>(Mid) | 810<br>(High) | 9262<br>(Low)                | 9400<br>(Mid) | 9538<br>(High) |
| Frequency<br>(MHz)            | 1850.2        | 1880         | 1909.8        | 1852.4                       | 1880          | 1907.6         |
| Peak-to-Average<br>Ratio (dB) | 0.29          | 0.28         | 0.28          | 3.84                         | 3.56          | 3.48           |




## 3.2.6 Test Result (Plots) of Peak-to-Average Ratio

|        |          |             |                 |
|--------|----------|-------------|-----------------|
| Band : | GSM 1900 | Test Mode : | GSM Link (GMSK) |
|--------|----------|-------------|-----------------|

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Peak-to-Average Ratio on Channel 661 (1880.0 MHz)






Peak-to-Average Ratio on Channel 810 (1909.8 MHz)






|        |               |             |                          |
|--------|---------------|-------------|--------------------------|
| Band : | WCDMA Band II | Test Mode : | RMC 12.2Kbps Link (QPSK) |
|--------|---------------|-------------|--------------------------|

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)




Date: 18.MAR.2015 00:58:05

Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 18.MAR.2015 00:58:22

### Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 18.MAR.2015 00:58:43

### 3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

#### 3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-C-2004 Section 2.2.17.
2. The EUT was placed on a turntable 1.5 meters high in a fully anechoic chamber.
3. The EUT was placed 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;  
UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per KDB 971168 D01.
5. The table was rotated 360 degrees to determine the position of the highest radiated power.
6. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
7. Taking the record of maximum ERP/EIRP.
8. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
9. The conducted power at the terminal of the dipole antenna is measured.
10. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
11.  $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$   
 $P_s$  (dBm) : Input power to substitution antenna.  
 $G_s$  (dBi or dBd) : Substitution antenna Gain.  
 $E_t = R_t + AF$   
 $E_s = R_s + AF$   
 $AF$  (dB/m) : Receive antenna factor  
 $R_t$  : The highest received signal in spectrum analyzer for EUT.  
 $R_s$  : The highest received signal in spectrum analyzer for substitution antenna.

### 3.3.4 Test Setup



### 3.3.5 Test Result of ERP

| GSM850 (GSM) Radiated Power ERP |          |          |          |          |           |         |
|---------------------------------|----------|----------|----------|----------|-----------|---------|
| Horizontal Polarization         |          |          |          |          |           |         |
| Frequency (MHz)                 | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.20                          | -18.47   | -48.12   | 0.00     | -1.08    | 28.57     | 0.7192  |
| 836.40                          | -18.82   | -48.28   | 0.00     | -0.93    | 28.53     | 0.7126  |
| 848.80                          | -19.30   | -48.35   | 0.00     | -0.76    | 28.29     | 0.6738  |
| Vertical Polarization           |          |          |          |          |           |         |
| Frequency (MHz)                 | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.20                          | -34.44   | -47.97   | 0.00     | -1.08    | 12.45     | 0.0176  |
| 836.40                          | -35.06   | -48.01   | 0.00     | -0.93    | 12.02     | 0.0159  |
| 848.80                          | -35.50   | -48.05   | 0.00     | -0.76    | 11.79     | 0.0151  |

| WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP |          |          |          |          |           |         |
|------------------------------------------------|----------|----------|----------|----------|-----------|---------|
| Horizontal Polarization                        |          |          |          |          |           |         |
| Frequency (MHz)                                | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 826.40                                         | -29.10   | -48.12   | 0.00     | -1.08    | 17.94     | 0.0622  |
| 836.40                                         | -30.42   | -48.28   | 0.00     | -0.93    | 16.93     | 0.0493  |
| 846.60                                         | -29.71   | -48.35   | 0.00     | -0.76    | 17.88     | 0.0614  |
| Vertical Polarization                          |          |          |          |          |           |         |
| Frequency (MHz)                                | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 826.40                                         | -44.93   | -47.97   | 0.00     | -1.08    | 1.96      | 0.0016  |
| 836.40                                         | -46.46   | -48.01   | 0.00     | -0.93    | 0.62      | 0.0012  |
| 846.60                                         | -45.52   | -48.05   | 0.00     | -0.76    | 1.77      | 0.0015  |



## 3.3.6 Test Result of EIRP

| GSM1900 (GSM) Radiated Power EIRP |          |          |          |          |            |          |
|-----------------------------------|----------|----------|----------|----------|------------|----------|
| Horizontal Polarization           |          |          |          |          |            |          |
| Frequency (MHz)                   | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.20                           | -24.56   | -51.88   | 0.00     | 1.96     | 29.28      | 0.8470   |
| 1880.00                           | -25.33   | -52.99   | 0.00     | 2.00     | 29.66      | 0.9251   |
| 1909.80                           | -27.29   | -54.28   | 0.00     | 1.98     | 28.97      | 0.7896   |
| Vertical Polarization             |          |          |          |          |            |          |
| Frequency (MHz)                   | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.20                           | -25.59   | -52.13   | 0.00     | 1.96     | 28.50      | 0.7077   |
| 1880.00                           | -25.73   | -53.17   | 0.00     | 2.00     | 29.44      | 0.8795   |
| 1909.80                           | -27.32   | -54.13   | 0.00     | 1.98     | 28.79      | 0.7575   |

| WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP |          |          |          |          |            |          |
|--------------------------------------------------|----------|----------|----------|----------|------------|----------|
| Horizontal Polarization                          |          |          |          |          |            |          |
| Frequency (MHz)                                  | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1852.40                                          | -30.94   | -51.88   | 0.00     | 1.96     | 22.90      | 0.1948   |
| 1880.00                                          | -31.88   | -52.99   | 0.00     | 2.00     | 23.11      | 0.2047   |
| 1907.60                                          | -33.47   | -54.28   | 0.00     | 1.98     | 22.79      | 0.1903   |
| Vertical Polarization                            |          |          |          |          |            |          |
| Frequency (MHz)                                  | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1852.40                                          | -31.98   | -52.13   | 0.00     | 1.96     | 22.11      | 0.1627   |
| 1880.00                                          | -32.40   | -53.17   | 0.00     | 2.00     | 22.77      | 0.1893   |
| 1907.60                                          | -33.53   | -54.13   | 0.00     | 1.98     | 22.58      | 0.1813   |

### 3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

#### 3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3\*RBW, peak detector, trace maximum hold.
5. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3\*RBW, peak detector, trace maximum hold.

#### 3.4.4 Test Setup



**3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth**

| Cellular Band   |              |           |            |
|-----------------|--------------|-----------|------------|
| Modes           | GSM850 (GSM) |           |            |
| Channel         | 128 (Low)    | 189 (Mid) | 251 (High) |
| Frequency (MHz) | 824.2        | 836.4     | 848.8      |
| 99% OBW (kHz)   | 244.00       | 245.00    | 248.00     |
| 26dB BW (kHz)   | 309.00       | 309.00    | 310.00     |

| PCS Band        |               |           |            |
|-----------------|---------------|-----------|------------|
| Modes           | GSM1900 (GSM) |           |            |
| Channel         | 512 (Low)     | 661 (Mid) | 810 (High) |
| Frequency (MHz) | 1850.2        | 1880      | 1909.8     |
| 99% OBW (kHz)   | 250.00        | 247.00    | 245.00     |
| 26dB BW (kHz)   | 312.00        | 310.00    | 308.00     |


| Cellular Band   |                             |            |             |
|-----------------|-----------------------------|------------|-------------|
| Modes           | WCDMA Band V (RMC 12.2Kbps) |            |             |
| Channel         | 4132 (Low)                  | 4182 (Mid) | 4233 (High) |
| Frequency (MHz) | 826.4                       | 836.4      | 846.6       |
| 99% OBW (MHz)   | 4.16                        | 4.16       | 4.14        |
| 26dB BW (MHz)   | 4.69                        | 4.68       | 4.69        |

| PCS Band        |                              |            |             |
|-----------------|------------------------------|------------|-------------|
| Modes           | WCDMA Band II (RMC 12.2Kbps) |            |             |
| Channel         | 9262 (Low)                   | 9400 (Mid) | 9538 (High) |
| Frequency (MHz) | 1852.4                       | 1880       | 1907.6      |
| 99% OBW (MHz)   | 4.16                         | 4.16       | 4.16        |
| 26dB BW (MHz)   | 4.69                         | 4.69       | 4.69        |

### 3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


|               |         |                    |                 |
|---------------|---------|--------------------|-----------------|
| <b>Band :</b> | GSM 850 | <b>Test Mode :</b> | GSM Link (GMSK) |
|---------------|---------|--------------------|-----------------|

#### 99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 17.MAR.2015 22:13:43


#### 26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 17.MAR.2015 21:59:57




### 99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 17.MAR.2015 22:15:01


### 26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 17.MAR.2015 22:04:25




### 99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 17.MAR.2015 22:16:04

### 26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 17.MAR.2015 22:19:18




|        |          |             |                 |
|--------|----------|-------------|-----------------|
| Band : | GSM 1900 | Test Mode : | GSM Link (GMSK) |
|--------|----------|-------------|-----------------|

## 99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 17.MAR.2015 23:25:16


## 26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 17.MAR.2015 23:23:02




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 17.MAR.2015 23:26:01


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 17.MAR.2015 23:23:37




### 99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 17.MAR.2015 23:26:37

### 26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 17.MAR.2015 23:24:24




|        |              |             |                          |
|--------|--------------|-------------|--------------------------|
| Band : | WCDMA Band V | Test Mode : | RMC 12.2Kbps Link (QPSK) |
|--------|--------------|-------------|--------------------------|

## 99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 18.MAR.2015 01:03:11


## 26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 18.MAR.2015 01:00:40




99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 18.MAR.2015 01:03:46


26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 18.MAR.2015 01:01:43




### 99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 18.MAR.2015 01:04:19

### 26dB Bandwidth Plot on Channel 4233 (846.6 MHz)




Date: 18.MAR.2015 01:02:18




|        |               |             |                          |
|--------|---------------|-------------|--------------------------|
| Band : | WCDMA Band II | Test Mode : | RMC 12.2Kbps Link (QPSK) |
|--------|---------------|-------------|--------------------------|

## 99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)




Date: 18.MAR.2015 00:42:13


## 26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 18.MAR.2015 00:40:07

**99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)**



Date: 18.MAR.2015 00:42:49

**26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)**


Date: 18.MAR.2015 00:40:54




## 99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 18.MAR.2015 00:43:56

## 26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 18.MAR.2015 00:41:32

### 3.5 Band Edge Measurement

#### 3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.


#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.5.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$   
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$   
 $= -13\text{dBm}.$


#### 3.5.4 Test Setup



### 3.5.5 Test Result (Plots) of Conducted Band Edge

|               |        |                    |                 |
|---------------|--------|--------------------|-----------------|
| <b>Band :</b> | GSM850 | <b>Test Mode :</b> | GSM Link (GMSK) |
|---------------|--------|--------------------|-----------------|

### Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 17.MAR.2015 22:28:49



|        |        |             |                 |
|--------|--------|-------------|-----------------|
| Band : | GSM850 | Test Mode : | GSM Link (GMSK) |
|--------|--------|-------------|-----------------|

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 17.MAR.2015 22:33:17



|        |         |             |                 |
|--------|---------|-------------|-----------------|
| Band : | GSM1900 | Test Mode : | GSM Link (GMSK) |
|--------|---------|-------------|-----------------|

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 17.MAR.2015 22:45:53



|        |         |             |                 |
|--------|---------|-------------|-----------------|
| Band : | GSM1900 | Test Mode : | GSM Link (GMSK) |
|--------|---------|-------------|-----------------|

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 17.MAR.2015 22:51:50



|        |              |             |                          |
|--------|--------------|-------------|--------------------------|
| Band : | WCDMA Band V | Test Mode : | RMC 12.2Kbps Link (QPSK) |
|--------|--------------|-------------|--------------------------|

Lower Band Edge Plot on Channel 4132 (826.4 MHz)




Date: 18.MAR.2015 01:10:17



|        |              |             |                          |
|--------|--------------|-------------|--------------------------|
| Band : | WCDMA Band V | Test Mode : | RMC 12.2Kbps Link (QPSK) |
|--------|--------------|-------------|--------------------------|

Higher Band Edge Plot on Channel 4233 (846.6 MHz)




Date: 18.MAR.2015 01:15:15



|        |               |             |                          |
|--------|---------------|-------------|--------------------------|
| Band : | WCDMA Band II | Test Mode : | RMC 12.2Kbps Link (QPSK) |
|--------|---------------|-------------|--------------------------|

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)




Date: 18.MAR.2015 00:49:28



|        |               |             |                          |
|--------|---------------|-------------|--------------------------|
| Band : | WCDMA Band II | Test Mode : | RMC 12.2Kbps Link (QPSK) |
|--------|---------------|-------------|--------------------------|

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 18.MAR.2015 00:55:07

## 3.6 Conducted Spurious Emission Measurement

### 3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.


### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$   
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$   
 $= -13\text{dBm}.$


### 3.6.4 Test Setup



### 3.6.5 Test Result (Plots) of Conducted Spurious Emission

|                    |                 |                    |           |
|--------------------|-----------------|--------------------|-----------|
| <b>Band :</b>      | GSM850          | <b>Channel :</b>   | CH128     |
| <b>Test Mode :</b> | GSM Link (GMSK) | <b>Frequency :</b> | 824.2 MHz |

**Conducted Spurious Emission Plot between 30MHz ~ 9GHz**




Date: 17.MAR.2015 22:33:56



|             |                 |             |           |
|-------------|-----------------|-------------|-----------|
| Band :      | GSM850          | Channel :   | CH189     |
| Test Mode : | GSM Link (GMSK) | Frequency : | 836.4 MHz |

## Conducted Spurious Emission Plot between 30MHz ~ 9GHz




Date: 17.MAR.2015 22:35:07



|             |                 |             |           |
|-------------|-----------------|-------------|-----------|
| Band :      | GSM850          | Channel :   | CH251     |
| Test Mode : | GSM Link (GMSK) | Frequency : | 848.8 MHz |

Conducted Spurious Emission Plot between 30MHz ~ 9GHz




Date: 17.MAR.2015 22:36:48



|             |                 |             |            |
|-------------|-----------------|-------------|------------|
| Band :      | GSM1900         | Channel :   | CH512      |
| Test Mode : | GSM Link (GMSK) | Frequency : | 1850.2 MHz |

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz




Date: 17.MAR.2015 23:27:13



|             |                 |             |            |
|-------------|-----------------|-------------|------------|
| Band :      | GSM1900         | Channel :   | CH661      |
| Test Mode : | GSM Link (GMSK) | Frequency : | 1880.0 MHz |

## Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz




Date: 17.MAR.2015 23:27:43



|             |                 |             |            |
|-------------|-----------------|-------------|------------|
| Band :      | GSM1900         | Channel :   | CH810      |
| Test Mode : | GSM Link (GMSK) | Frequency : | 1909.8 MHz |

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz




Date: 17.MAR.2015 23:28:14




|             |                             |             |           |
|-------------|-----------------------------|-------------|-----------|
| Band :      | WCDMA Band V                | Channel :   | CH4132    |
| Test Mode : | RMC 12.2Kbps Link<br>(QPSK) | Frequency : | 826.4 MHz |

Conducted Spurious Emission Plot between 30MHz ~ 9GHz



Date: 18.MAR.2015 01:15:53

|                    |                             |                    |           |
|--------------------|-----------------------------|--------------------|-----------|
| <b>Band :</b>      | WCDMA Band V                | <b>Channel :</b>   | CH4182    |
| <b>Test Mode :</b> | RMC 12.2Kbps Link<br>(QPSK) | <b>Frequency :</b> | 836.4 MHz |


**Conducted Spurious Emission Plot between 30MHz ~ 9GHz**


Date : 18.MAR.2015 01:16:39



|             |                             |             |           |
|-------------|-----------------------------|-------------|-----------|
| Band :      | WCDMA Band V                | Channel :   | CH4233    |
| Test Mode : | RMC 12.2Kbps Link<br>(QPSK) | Frequency : | 846.6 MHz |

## Conducted Spurious Emission Plot between 30MHz ~ 9GHz




Date: 18.MAR.2015 01:17:06



|             |                             |             |            |
|-------------|-----------------------------|-------------|------------|
| Band :      | WCDMA Band II               | Channel :   | CH9262     |
| Test Mode : | RMC 12.2Kbps Link<br>(QPSK) | Frequency : | 1852.4 MHz |

## Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz




Date: 18.MAR.2015 00:55:42



|             |                             |             |            |
|-------------|-----------------------------|-------------|------------|
| Band :      | WCDMA Band II               | Channel :   | CH9400     |
| Test Mode : | RMC 12.2Kbps Link<br>(QPSK) | Frequency : | 1880.0 MHz |

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz




Date: 18.MAR.2015 00:56:17



|             |                             |             |            |
|-------------|-----------------------------|-------------|------------|
| Band :      | WCDMA Band II               | Channel :   | CH9538     |
| Test Mode : | RMC 12.2Kbps Link<br>(QPSK) | Frequency : | 1907.6 MHz |

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Date : 18.MAR.2015 00:56:50

## 3.7 Field Strength of Spurious Radiation Measurement

### 3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 3.7.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

### 3.7.3 Test Procedures


1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-C-2004 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12.  $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$   
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$   
 $= -13\text{dBm}.$

### 3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





## 3.7.5 Test Result of Field Strength of Spurious Radiated

|                 |                                                                                  |         |                 |                    |                  |                     |                 |              |        |
|-----------------|----------------------------------------------------------------------------------|---------|-----------------|--------------------|------------------|---------------------|-----------------|--------------|--------|
| Band :          | GSM850                                                                           |         |                 |                    |                  | Temperature :       | 23~25°C         |              |        |
| Test Mode :     | GSM Link (GMSK)                                                                  |         |                 |                    |                  | Relative Humidity : | 42~58%          |              |        |
| Test Engineer : | Sam Li                                                                           |         |                 |                    |                  | Polarization :      | Horizontal      |              |        |
| Remark :        | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. |         |                 |                    |                  |                     |                 |              |        |
| Frequency       | ERP                                                                              | Limit   | Over            | SPA                | S.G.             | TX Cable            | TX Antenna      | Polarization | Result |
| ( MHz )         | ( dBm )                                                                          | ( dBm ) | Limit<br>( dB ) | Reading<br>( dBm ) | Power<br>( dBm ) | loss<br>( dB )      | Gain<br>( dBi ) | (H/V)        |        |
| 1672            | -59.81                                                                           | -13     | -46.81          | -57.16             | -64.80           | 0.66                | 7.80            | H            | Pass   |
| 2510            | -42.71                                                                           | -13     | -29.71          | -42.89             | -49.11           | 0.85                | 9.40            | H            | Pass   |
| 3346            | -58.76                                                                           | -13     | -45.76          | -58.57             | -64.83           | 0.98                | 9.20            | H            | Pass   |
| 4182            | -53.21                                                                           | -13     | -40.21          | -55.44             | -59.45           | 1.01                | 9.40            | H            | Pass   |
| 5018            | -57.43                                                                           | -13     | -44.43          | -64.07             | -64.67           | 1.11                | 10.50           | H            | Pass   |
| 5854            | -57.84                                                                           | -13     | -44.84          | -63.61             | -63.41           | 1.28                | 9.00            | H            | Pass   |
| 6691            | -52.83                                                                           | -13     | -39.83          | -59.79             | -58.77           | 1.31                | 9.40            | H            | Pass   |

|                 |                                                                                  |         |                 |                    |                  |                     |                 |              |        |
|-----------------|----------------------------------------------------------------------------------|---------|-----------------|--------------------|------------------|---------------------|-----------------|--------------|--------|
| Band :          | GSM850                                                                           |         |                 |                    |                  | Temperature :       | 23~25℃          |              |        |
| Test Mode :     | GSM Link (GMSK)                                                                  |         |                 |                    |                  | Relative Humidity : | 42~58%          |              |        |
| Test Engineer : | Sam Li                                                                           |         |                 |                    |                  | Polarization :      | Vertical        |              |        |
| Remark :        | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. |         |                 |                    |                  |                     |                 |              |        |
| Frequency       | ERP                                                                              | Limit   | Over            | SPA                | S.G.             | TX Cable            | TX Antenna      | Polarization | Result |
| ( MHz )         | ( dBm )                                                                          | ( dBm ) | Limit<br>( dB ) | Reading<br>( dBm ) | Power<br>( dBm ) | loss<br>( dB )      | Gain<br>( dBi ) | (H/V)        |        |
| 1672            | -55.64                                                                           | -13     | -42.64          | -52.12             | -60.63           | 0.66                | 7.80            | V            | Pass   |
| 2510            | -49.50                                                                           | -13     | -36.50          | -50.18             | -55.90           | 0.85                | 9.40            | V            | Pass   |
| 3346            | -55.30                                                                           | -13     | -42.30          | -56.16             | -61.37           | 0.98                | 9.20            | V            | Pass   |
| 4182            | -55.91                                                                           | -13     | -42.91          | -57.40             | -62.15           | 1.01                | 9.40            | V            | Pass   |
| 5018            | -54.95                                                                           | -13     | -41.95          | -61.78             | -62.19           | 1.11                | 10.50           | V            | Pass   |
| 5854            | -57.32                                                                           | -13     | -44.32          | -62.11             | -62.89           | 1.28                | 9.00            | V            | Pass   |
| 6691            | -50.91                                                                           | -13     | -37.91          | -59.56             | -56.85           | 1.31                | 9.40            | V            | Pass   |



|                 |                                                                                  |         |                 |                  |                  |                     |               |              |        |
|-----------------|----------------------------------------------------------------------------------|---------|-----------------|------------------|------------------|---------------------|---------------|--------------|--------|
| Band :          | GSM1900                                                                          |         |                 |                  |                  | Temperature :       | 23~25℃        |              |        |
| Test Mode :     | GSM Link (GMSK)                                                                  |         |                 |                  |                  | Relative Humidity : | 42~58%        |              |        |
| Test Engineer : | Sam Li                                                                           |         |                 |                  |                  | Polarization :      | Horizontal    |              |        |
| Remark :        | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. |         |                 |                  |                  |                     |               |              |        |
| Frequency       | EIRP                                                                             | Limit   | Over            | SPA              | S.G.             | TX Cable            | TX Antenna    | Polarization | Result |
| ( MHz )         | ( dBm )                                                                          | ( dBm ) | Limit<br>( dB ) | Reading<br>(dBm) | Power<br>( dBm ) | loss<br>( dB )      | Gain<br>(dBi) | (H/V)        |        |
| 3760            | -52.51                                                                           | -13     | -39.51          | -60.07           | -63.86           | 1.25                | 12.60         | H            | Pass   |
| 5640            | -44.80                                                                           | -13     | -31.80          | -58.48           | -56.47           | 1.43                | 13.10         | H            | Pass   |
| 7520            | -49.63                                                                           | -13     | -36.63          | -63.68           | -58.67           | 2.26                | 11.30         | H            | Pass   |

|                 |                                                                                  |         |                 |                  |                  |                     |               |              |        |
|-----------------|----------------------------------------------------------------------------------|---------|-----------------|------------------|------------------|---------------------|---------------|--------------|--------|
| Band :          | GSM1900                                                                          |         |                 |                  |                  | Temperature :       | 23~25°C       |              |        |
| Test Mode :     | GSM Link (GMSK)                                                                  |         |                 |                  |                  | Relative Humidity : | 42~58%        |              |        |
| Test Engineer : | Sam Li                                                                           |         |                 |                  |                  | Polarization :      | Vertical      |              |        |
| Remark :        | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. |         |                 |                  |                  |                     |               |              |        |
| Frequency       | EIRP                                                                             | Limit   | Over            | SPA              | S.G.             | TX Cable            | TX Antenna    | Polarization | Result |
| ( MHz )         | ( dBm )                                                                          | ( dBm ) | Limit<br>( dB ) | Reading<br>(dBm) | Power<br>( dBm ) | loss<br>( dB )      | Gain<br>(dBi) | (H/V)        |        |
| 3760            | -50.99                                                                           | -13     | -37.99          | -59.85           | -62.34           | 1.25                | 12.6          | V            | Pass   |
| 5640            | -50.51                                                                           | -13     | -37.51          | -64.65           | -62.18           | 1.43                | 13.1          | V            | Pass   |
| 7520            | -49.76                                                                           | -13     | -36.76          | -64.29           | -58.80           | 2.26                | 11.3          | V            | Pass   |



|                 |                                                                                  |         |        |         |         |                     |            |              |        |
|-----------------|----------------------------------------------------------------------------------|---------|--------|---------|---------|---------------------|------------|--------------|--------|
| Band :          | WCDMA Band V                                                                     |         |        |         |         | Temperature :       | 23~25°C    |              |        |
| Test Mode :     | RMC 12.2Kbps Link (QPSK)                                                         |         |        |         |         | Relative Humidity : | 42~58%     |              |        |
| Test Engineer : | Sam Li                                                                           |         |        |         |         | Polarization :      | Horizontal |              |        |
| Remark :        | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. |         |        |         |         |                     |            |              |        |
| Frequency       | ERP                                                                              | Limit   | Over   | SPA     | S.G.    | TX Cable            | TX Antenna | Polarization | Result |
| ( MHz )         | ( dBm )                                                                          | ( dBm ) | Limit  | Reading | Power   | loss                | Gain       | (H/V)        |        |
| ( dB )          |                                                                                  |         | ( dB ) | ( dBm ) | ( dBm ) | ( dB )              | ( dBi )    |              |        |
| 1672            | -63.69                                                                           | -13     | -50.69 | -61.04  | -68.68  | 0.66                | 7.80       | H            | Pass   |
| 2510            | -57.13                                                                           | -13     | -44.13 | -57.31  | -63.53  | 0.85                | 9.40       | H            | Pass   |
| 3346            | -62.69                                                                           | -13     | -49.69 | -62.50  | -68.76  | 0.98                | 9.20       | H            | Pass   |

|                 |                                                                                  |         |                 |                  |                  |                     |               |              |        |
|-----------------|----------------------------------------------------------------------------------|---------|-----------------|------------------|------------------|---------------------|---------------|--------------|--------|
| Band :          | WCDMA Band V                                                                     |         |                 |                  |                  | Temperature :       | 23~25°C       |              |        |
| Test Mode :     | RMC 12.2Kbps Link (QPSK)                                                         |         |                 |                  |                  | Relative Humidity : | 42~58%        |              |        |
| Test Engineer : | Sam Li                                                                           |         |                 |                  |                  | Polarization :      | Vertical      |              |        |
| Remark :        | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. |         |                 |                  |                  |                     |               |              |        |
| Frequency       | ERP                                                                              | Limit   | Over            | SPA              | S.G.             | TX Cable            | TX Antenna    | Polarization | Result |
| ( MHz )         | ( dBm )                                                                          | ( dBm ) | Limit<br>( dB ) | Reading<br>(dBm) | Power<br>( dBm ) | loss<br>( dB )      | Gain<br>(dBi) | (H/V)        |        |
| 1672            | -61.71                                                                           | -13     | -48.71          | -58.19           | -66.70           | 0.66                | 7.80          | V            | Pass   |
| 2510            | -61.02                                                                           | -13     | -48.02          | -61.70           | -67.42           | 0.85                | 9.40          | V            | Pass   |
| 3346            | -62.68                                                                           | -13     | -49.68          | -63.54           | -68.75           | 0.98                | 9.20          | V            | Pass   |



|                 |                                                                                  |         |                 |                    |                  |                     |                 |              |        |
|-----------------|----------------------------------------------------------------------------------|---------|-----------------|--------------------|------------------|---------------------|-----------------|--------------|--------|
| Band :          | WCDMA Band II                                                                    |         |                 |                    |                  | Temperature :       | 23~25°C         |              |        |
| Test Mode :     | RMC 12.2Kbps Link (QPSK)                                                         |         |                 |                    |                  | Relative Humidity : | 42~58%          |              |        |
| Test Engineer : | Sam Li                                                                           |         |                 |                    |                  | Polarization :      | Horizontal      |              |        |
| Remark :        | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. |         |                 |                    |                  |                     |                 |              |        |
| Frequency       | EIRP                                                                             | Limit   | Over            | SPA                | S.G.             | TX Cable            | TX Antenna      | Polarization | Result |
| ( MHz )         | ( dBm )                                                                          | ( dBm ) | Limit<br>( dB ) | Reading<br>( dBm ) | Power<br>( dBm ) | loss<br>( dB )      | Gain<br>( dBi ) | ( H/V )      |        |
| 3760            | -49.02                                                                           | -13     | -36.02          | -56.58             | -60.37           | 1.25                | 12.60           | H            | Pass   |
| 5640            | -45.05                                                                           | -13     | -32.05          | -58.73             | -56.72           | 1.43                | 13.10           | H            | Pass   |
| 7520            | -50.23                                                                           | -13     | -37.23          | -64.28             | -59.27           | 2.26                | 11.30           | H            | Pass   |

|                 |                                                                                  |         |                 |                    |                  |                     |                 |              |        |
|-----------------|----------------------------------------------------------------------------------|---------|-----------------|--------------------|------------------|---------------------|-----------------|--------------|--------|
| Band :          | WCDMA Band II                                                                    |         |                 |                    |                  | Temperature :       | 23~25°C         |              |        |
| Test Mode :     | RMC 12.2Kbps Link (QPSK)                                                         |         |                 |                    |                  | Relative Humidity : | 42~58%          |              |        |
| Test Engineer : | Sam Li                                                                           |         |                 |                    |                  | Polarization :      | Vertical        |              |        |
| Remark :        | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. |         |                 |                    |                  |                     |                 |              |        |
| Frequency       | EIRP                                                                             | Limit   | Over            | SPA                | S.G.             | TX Cable            | TX Antenna      | Polarization | Result |
| ( MHz )         | ( dBm )                                                                          | ( dBm ) | Limit<br>( dB ) | Reading<br>( dBm ) | Power<br>( dBm ) | loss<br>( dB )      | Gain<br>( dBi ) | (H/V)        |        |
| 3760            | -40.91                                                                           | -13     | -27.91          | -53.08             | -52.26           | 1.25                | 12.6            | V            | Pass   |
| 5640            | -50.52                                                                           | -13     | -37.52          | -64.66             | -62.19           | 1.43                | 13.1            | V            | Pass   |
| 7520            | -50.04                                                                           | -13     | -37.04          | -64.57             | -59.08           | 2.26                | 11.3            | V            | Pass   |

### 3.8 Frequency Stability Measurement

#### 3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

#### 3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


#### 3.8.3 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  steps up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

#### 3.8.4 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at  $25\pm 5^{\circ}\text{C}$  and connected with the system simulator.
3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

### 3.8.5 Test Setup



### 3.8.6 Test Result of Temperature Variation

|                      |         |                    |           |
|----------------------|---------|--------------------|-----------|
| <b>Band :</b>        | GSM 850 | <b>Channel :</b>   | 189       |
| <b>Limit (ppm) :</b> | 2.5     | <b>Frequency :</b> | 836.4 MHz |

| Temperature (°C) | GSM             |                 | Result |
|------------------|-----------------|-----------------|--------|
|                  | Freq. Dev. (Hz) | Deviation (ppm) |        |
| 50               | -17             | 0.0036          | PASS   |
| 40               | -16             | 0.0024          |        |
| 30               | -15             | 0.0012          |        |
| 20(Ref.)         | -14             | 0.0000          |        |
| 10               | -16             | 0.0024          |        |
| 0                | -17             | 0.0036          |        |
| -10              | -20             | 0.0072          |        |
| -20              | -21             | 0.0084          |        |
| -30              | -22             | 0.0096          |        |

|                      |                        |                    |            |
|----------------------|------------------------|--------------------|------------|
| <b>Band :</b>        | GSM 1900               | <b>Channel :</b>   | 661        |
| <b>Limit (ppm) :</b> | within authorized band | <b>Frequency :</b> | 1880.0 MHz |

| Temperature (°C) | GSM             |                 | Result |
|------------------|-----------------|-----------------|--------|
|                  | Freq. Dev. (Hz) | Deviation (ppm) |        |
| 50               | -48             | 0.0064          | PASS   |
| 40               | -42             | 0.0032          |        |
| 30               | -38             | 0.0011          |        |
| 20(Ref.)         | -36             | 0.0000          |        |
| 10               | -34             | 0.0011          |        |
| 0                | -32             | 0.0021          |        |
| -10              | -30             | 0.0032          |        |
| -20              | -28             | 0.0043          |        |
| -30              | -26             | 0.0053          |        |

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

|                      |              |                    |           |
|----------------------|--------------|--------------------|-----------|
| <b>Band :</b>        | WCDMA Band V | <b>Channel :</b>   | 4182      |
| <b>Limit (ppm) :</b> | 2.5          | <b>Frequency :</b> | 836.4 MHz |

| Temperature (°C) | RMC 12.2Kbps    |                 | Result |
|------------------|-----------------|-----------------|--------|
|                  | Freq. Dev. (Hz) | Deviation (ppm) |        |
| 50               | -10             | 0.0060          | PASS   |
| 40               | -8              | 0.0036          |        |
| 30               | -6              | 0.0012          |        |
| 20(Ref.)         | -5              | 0.0000          |        |
| 10               | -7              | 0.0024          |        |
| 0                | 8               | 0.0155          |        |
| -10              | 10              | 0.0179          |        |
| -20              | 12              | 0.0203          |        |
| -30              | 14              | 0.0227          |        |

|                      |                        |                    |            |
|----------------------|------------------------|--------------------|------------|
| <b>Band :</b>        | WCDMA Band II          | <b>Channel :</b>   | 9400       |
| <b>Limit (ppm) :</b> | within authorized band | <b>Frequency :</b> | 1880.0 MHz |

| Temperature (°C) | RMC 12.2Kbps    |                 | Result |
|------------------|-----------------|-----------------|--------|
|                  | Freq. Dev. (Hz) | Deviation (ppm) |        |
| 50               | -11             | 0.0027          | PASS   |
| 40               | -10             | 0.0021          |        |
| 30               | -8              | 0.0011          |        |
| 20(Ref.)         | -6              | 0.0000          |        |
| 10               | -8              | 0.0011          |        |
| 0                | -9              | 0.0016          |        |
| -10              | -11             | 0.0027          |        |
| -20              | -13             | 0.0037          |        |
| -30              | -15             | 0.0048          |        |

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

### 3.8.7 Test Result of Voltage Variation

| Band & Channel          | Mode            | Voltage (Volt) | Freq. Dev. (Hz) | Deviation (ppm) | Limit (ppm) | Result |
|-------------------------|-----------------|----------------|-----------------|-----------------|-------------|--------|
| GSM 850<br>CH189        | GSM             | 3.8            | -14             | 0.0000          | 2.5         | PASS   |
|                         |                 | BEP            | -13             | 0.0012          |             |        |
|                         |                 | 4.2            | -15             | 0.0012          |             |        |
| GSM 1900<br>CH661       | GSM             | 3.8            | -36             | 0.0000          | (Note 3.)   |        |
|                         |                 | BEP            | -34             | 0.0011          |             |        |
|                         |                 | 4.2            | -37             | 0.0005          |             |        |
| WCDMA Band V<br>CH4182  | RMC<br>12.2Kbps | 3.8            | -5              | 0.0000          | 2.5         |        |
|                         |                 | BEP            | -6              | 0.0012          |             |        |
|                         |                 | 4.2            | -6              | 0.0012          |             |        |
| WCDMA Band II<br>CH9400 | RMC<br>12.2Kbps | 3.8            | -6              | 0.0000          | (Note 3.)   |        |
|                         |                 | BEP            | -5              | 0.0005          |             |        |
|                         |                 | 4.2            | -7              | 0.0005          |             |        |

**Note:**

1. Normal Voltage = 3.8V.
2. Battery End Point (BEP) = 3.5 V.
3. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



## 4 List of Measuring Equipment

| Instrument                 | Manufacturer         | Model No.         | Serial No.       | Characteristics | Calibration Date | Test Date                       | Due Date      | Remark                |
|----------------------------|----------------------|-------------------|------------------|-----------------|------------------|---------------------------------|---------------|-----------------------|
| Spectrum Analyzer          | R&S                  | FSV40             | 101078           | 10Hz~40GHz      | May 08, 2014     | Mar. 17, 2015~<br>Mar. 18, 2015 | May 07, 2015  | Conducted (TH01-SZ)   |
| Spectrum Analyzer          | R&S                  | FSP30             | 101400           | 9kHz~30GHz      | Jan. 28, 2015    | Mar. 17, 2015~<br>Mar. 18, 2015 | Jan. 27, 2016 | Conducted (TH01-SZ)   |
| Thermal Chamber            | Hongzhangroup        | LP-150U           | HD20120425       | -40℃~150℃       | Jan. 28, 2015    | Mar. 17, 2015~<br>Mar. 18, 2015 | Jan. 27, 2016 | Conducted (TH01-SZ)   |
| EMI TEST Receiver          | R&S                  | ESC17             | 100768           | 9kHz~3GHz       | May 04, 2014     | Mar. 13, 2015                   | May 03, 2015  | Radiation (03CH02-SZ) |
| Spectrum Analyzer          | Agilent Technologies | N9038A            | MY52260185       | 20Hz~26.5GHz    | May 26, 2014     | Mar. 13, 2015                   | May 25, 2015  | Radiation (03CH02-SZ) |
| Bilog Antenna              | TESEQ                | CBL 6112D         | 37877            | 30MHz~2GHz      | Oct. 15, 2014    | Mar. 13, 2015                   | Oct. 14, 2015 | Radiation (03CH02-SZ) |
| Double Ridge Horn Antenna  | SCHWARZBECK          | BBHA 9120D        | 9120D-1285       | 1GHz~18GHz      | Jan. 20, 2015    | Mar. 13, 2015                   | Jan. 19, 2016 | Radiation (03CH02-SZ) |
| Double Ridged Horn Antenna | COM-POWER            | AH-840            | 101071           | 18GHz~40GHz     | Sep. 04, 2014    | Mar. 13, 2015                   | Sep. 03, 2015 | Radiation (03CH02-SZ) |
| Amplifier                  | com-power            | PA-103A           | 161069           | 1~1000MHz       | May 04, 2014     | Mar. 13, 2015                   | May 03, 2015  | Radiation (03CH02-SZ) |
| Amplifier                  | Agilent              | 8449B             | 3008A01023       | 1GHz~26.5GHz    | Oct. 29, 2014    | Mar. 13, 2015                   | Oct. 28, 2015 | Radiation (03CH02-SZ) |
| AC Source(AVR)             | CHROMA               | 61601ACSO<br>URCE | 61601000247<br>0 | 100Vac~240Vac   | NCR              | Mar. 13, 2015                   | NCR           | Radiation (03CH02-SZ) |
| Turn Table                 | Qiangdian            | 3000              | N/A              | 0~360 degree    | NCR              | Mar. 13, 2015                   | NCR           | Radiation (03CH02-SZ) |
| Antenna Mast               | Qiangdian            | 3000              | N/A              | 1 m~4 m         | NCR              | Mar. 13, 2015                   | NCR           | Radiation (03CH02-SZ) |
| Spectrum Analyzer          | R&S                  | FSP 7             | 100818           | 9kHz~7GHz       | Jul. 17, 2014    | Mar. 18, 2015                   | Jul. 16, 2015 | ERP/EIRP (OTA02-SZ)   |
| Quad-Ridged Horn           | ETS-Lindgren         | 3164-08           | 00102954         | 700MHz~10000MHz | N/A              | Mar. 18, 2015                   | N/A           | ERP/EIRP (OTA02-SZ)   |
| Multi-Devices Controller   | ETS-Lindgren         | 2090-OPT1         | 00108147         | N/A             | N/A              | Mar. 18, 2015                   | N/A           | ERP/EIRP (OTA02-SZ)   |
| Switch Control Mainframe   | Agilent              | 3499A             | MY42005451       | N/A             | N/A              | Mar. 18, 2015                   | N/A           | ERP/EIRP (OTA02-SZ)   |



## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

|                                                                         |       |
|-------------------------------------------------------------------------|-------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ ) | 4.5dB |
|-------------------------------------------------------------------------|-------|