



FCC PART 15.247 TEST REPORT

For

Quanzhou Wouxun Electronics Co., Ltd.

Jiangnan High Technology Industry Park, No.928 Nanhuan Road, Quanzhou, Fujian, China

FCC ID: WVTWOXUN31


Report Type: Original Report	Product Name: TWO WAY RADIO(GMRS RADIO)
Report Number:	2507A33238E-RF-03
Report Date:	2026-02-26
Reviewed By:	Ash Lin 
Approved By:	Miles Chen 
Prepared By:	Bay Area Compliance Laboratories Corp. (Xiamen) Unit 102, No. 902 Meifeng South Road, Binhai West Avenue, Science and Technology Innovation Park, Torch High tech Zone XiaMen Tel: +86-592-3200111 www.baclcorp.com.cn

TABLE OF CONTENTS

REPORT REVISION HISTORY.....	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
TEST FACILITY	6
MEASUREMENT UNCERTAINTY	6
SYSTEM TEST CONFIGURATION.....	7
TEST MODE AND VOLTAGE.....	7
DESCRIPTION OF TEST CONFIGURATION	7
★EUT EXERCISE SOFTWARE	7
SPECIAL ACCESSORIES	7
EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS.....	12
TEST EQUIPMENT LIST	13
FCC §15.203 – ANTENNA REQUIREMENT.....	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP.....	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	16
RESULT & MARGIN CALCULATION.....	16
TEST DATA	17
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	21
APPLICABLE STANDARD	21
TEST SYSTEM SETUP.....	21
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	23
FINAL MEASUREMENT FOR EMISSION IDENTIFIED DURING THE PRE-SCAN:	23
TEST PROCEDURE	23
RESULT & MARGIN CALCULATION.....	24
TEST DATA	25
FCC §15.247(a) (1) – CHANNEL SEPARATION TEST.....	70
APPLICABLE STANDARD	70
EUT SETUP.....	70
TEST PROCEDURE	70
TEST DATA	71
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	73
APPLICABLE STANDARD	73
EUT SETUP.....	73
TEST PROCEDURE	73
TEST DATA	74
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	78

APPLICABLE STANDARD	78
EUT SETUP	78
TEST PROCEDURE	78
TEST DATA	79
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	81
APPLICABLE STANDARD	81
EUT SETUP	81
TEST PROCEDURE	81
TEST DATA	82
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	85
APPLICABLE STANDARD	85
EUT SETUP	85
TEST PROCEDURE	85
TEST DATA	86
FCC §15.247(d) - BAND EDGES TESTING	90
APPLICABLE STANDARD	90
EUT SETUP	90
TEST PROCEDURE	90
TEST DATA	91
EUT PHOTOGRAPHS	96
TEST SETUP PHOTOGRAPHS	97

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	2507A33238E-RF-03	R1V1	2026-02-26	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:		Quanzhou Wouxun Electronics Co., Ltd.
Product Name:		TWO WAY RADIO(GMRS RADIO)
Tested Model:		KG-UV96G
Multiple Model(s):		KG-UV96G+, KG-UV96G Mate, KG-UV96G Pro, KG-UV98G, KG-UV98G+
Trade Mark:		WOUXUN
Power Supply:		DC 5V from USB port or DC 8.4V from charger or DC 7.4V from battery
Adapter Information	Model:	DSX-120100-US
	Input:	AC 100-240V, 50/60Hz, 0.3A
	Output:	DC 12V, 1A
Charger Information	Model:	CH-015
	Input:	DC 12V, 1A
	Output:	DC 8.4V, 0.8A
Maximum Peak Output Power:		1.26dBm
RF Function:		Classic BT
Operating Band/Frequency:		2402-2480 MHz
Channel Number:		79
Channel Separation:		1 MHz
Modulation Type:		GFSK, $\pi/4$ -DQPSK
Antenna Type:		PCB antenna
★Maximum Antenna Gain:		2.39dBi
EUT Received Status:		Good
<i>Note:</i> 1. The Maximum Antenna Gain was declared by manufacturer. 2. The difference between tested model and series model are model name and appearance (Printing on the surface of buttons), please refer to declaration letter for more detail. 3. All measurement and test data in this report was gathered from production sample serial number: 3E9C-16(RF conducted), 3E9C-17(Conducted Emission and Radiated Spurious Emission) (Assigned by the BACL(Xiamen). The EUT supplied by the applicant was received on 2025-12-10)		

Objective

This test report is prepared for *Quanzhou Wouxun Electronics Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and KDB 558074 D01 15.247 Meas Guidance v05r02.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Xiamen) to collect test data is located on the Unit 102, No. 902 Meifeng South Road, Binhai West Avenue, Science and Technology Innovation Park, Torch High tech Zone XiaMen.

Bay Area Compliance Laboratories Corp. (Xiamen) Lab is accredited to ISO/IEC 17025 by A2LA (Certificate Number: 7134.01) and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No. : CN1384.

Measurement Uncertainty

Item		U_{lab}
Conducted Emissions	150kHz-30MHz	2.45dB
Radiated Spurious Emission	9kHz-150kHz	2.82dB
	150kHz-30MHz	2.74dB
	30MHz~1GHz	4.68dB
	1GHz~18GHz	5.00dB
	18GHz~26.5GHz	4.90dB
Occupied Channel Bandwidth		2%
Transmitter Conducted Power(Conducted RF power)		± 1.49 dB
Conducted Spurious Emission		± 2.92 dB
Duty Cycle		1%
Temperature		$\pm 1^{\circ}\text{C}$
Humidity		$\pm 5\%$
Supply voltages		$\pm 0.4\%$

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

SYSTEM TEST CONFIGURATION

Test Mode and Voltage

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.	
Test mode:	Test Mode: Transmitting
Test voltage:	DC 5V from USB port or DC 8.4V from charger
Remark:	During all emission tests, the EUT was configured to measure its highest possible emission level and the worst case's test data was presented in this test report.

Description of Test Configuration

Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	...	...
...	...	...	...
...	...	78	2480
39	2441	/	/

EUT was tested with Channel 0, 39 and 78.

★EUT Exercise Software

BT test in the engineer mode.

RF Test Tool: FCC_assist_1.0.2.2.exe

Test Modes	Power Level Setting		
	Lowest Channel	Middle Channel	Highest Channel
BDR(GFSK)	10	10	10
EDR($\pi/4$ -DQPSK)	10	10	10

Note: The power level was declared by the applicant.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

For USB port

Manufacturer	Description	Model	Serial Number
Lenovo	Laptop	T480	PF1P5K4F
HONOTO	Adapter 1	ADS-12B-06	Unknown
Unknown	Debug board	Unknown	Unknown
Unknown	earphone	Unknown	Unknown

For Charger


Manufacturer	Description	Model	Serial Number
Lenovo	Laptop	T480	PF1P5K4F
Unknown	Debug board	Unknown	Unknown
Unknown	earphone	Unknown	Unknown

External I/O Cable

Cable Description	Length (m)	From Port	To
Jumper Wire	0.1	EUT	Debug board
USB cable	1	EUT	Adapter 1
USB cable	10	Laptop	Debug board
RF Cable	0.1	EUT antenna port	Spectrum Analyzer



Block Diagram of Test Setup

Conducted Emission:




Radiated Emission:

Below 1GHz



Above 1GHz



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions & Restricted Bands Emissions & Antenna-port conducted emission	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

TEST EQUIPMENT LIST

Test Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions					
EMI Test Receiver	Rohde & Schwarz	ESR	103105	2026/1/21	2027/1/20
LISN	Rohde & Schwarz	ENV216	100129	2026/1/21	2027/1/20
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	0357.8810.54	2026/1/21	2027/1/20
Coaxial Cable	XINHANGWEIBO	XH400T-N-4M	CC001	2026/1/20	2027/1/19
EMI Test software	Audix	E3	18621a	N/A	N/A
Radiated Emissions Below 1GHz					
EMI Test Receiver	Rohde & Schwarz	ESR	103103	2026/1/21	2027/1/20
Loop Antenna	Rohde & Schwarz	HFH2-Z2	830749/001	2023/7/27	2026/7/26
Antenna	Sunol Sciences	JB6	A122022-5	2023/7/27	2026/7/26
Amplifier	Sonoma	310B	120903	2026/1/22	2027/1/21
Coaxial Cable	XINHANGWEIBO	XH400T-N-4M	CC002	2026/1/20	2027/1/19
Coaxial Cable	XINHANGWEIBO	XH460B-N-2M	CC006	2026/1/20	2027/1/19
Coaxial Cable	XINHANGWEIBO	XH460B-N-12M	CC007	2026/1/20	2027/1/19
Coaxial Cable	XINHANGWEIBO	HFH2-CC	335.3609	2026/1/20	2027/1/19
Test Software	Audix	E3	18621a	N/A	N/A
Radiated Emissions Above 1 GHz					
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102051	2026/1/21	2027/1/20
Filter Switch Unit	Decentest	DT7220FSU	DS79904	2026/1/20	2027/1/19
Multiplex Switch Test Control Set	Decentest	DT7220SCU	DS79901	2026/1/20	2027/1/19
Horn Antenna	EMCO	3115	9002-3355	2024/11/19	2027/11/18
Preamplifier	GLOBAL	1313-A100M18G	4121301	2026/1/14	2027/1/13
Coaxial Cable	XINHANGWEIBO	XH800A-N-6M	CC003	2026/1/20	2027/1/19
Coaxial Cable	XINHANGWEIBO	XH800A-N-1M	CC005	2026/1/20	2027/1/19
Horn Antenna	EMCO	3116	9407-2232	2023/7/31	2026/7/30
Preamplifier	A.H.Systems	PAM-1840	200	2026/1/20	2027/1/19
Coaxial Cable	XINHANGWEIBO	XH360A-2.92-3M	CC008	2026/1/20	2027/1/19
Coaxial Cable	XINHANGWEIBO	XH360A-2.92-1M	CC009	2026/1/20	2027/1/19
Test Software	Audix	E3	18621a	N/A	N/A
RF Conducted Test					
Spectrum Analyzer	Rohde & Schwarz	FSU	100405	2025/2/20	2026/2/19
Test Software	JD	JDAutoTestSystem	1.0.0.3813	N/A	N/A

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Xiamen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


Antenna Connector Construction

The EUT has one PCB antenna for Bluetooth, which was permanently attached and the Max. antenna gain is 2.39dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS**Applicable Standard**

FCC§15.207

EUT Setup

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

If the maximum peak value of the emissions is below the average limit, the QP value and average value measurement will not need to be performed and only record the maximum peak measured value to meet the requirements.

Result & Margin Calculation

The Result is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

Result (dB μ V) = Reading (dB μ V) + Factor (dB)

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V) – Result (dB μ V)

Test Data


Frequency Range:	150kHz~30MHz
Temperature:	24.5°C
Relative Humidity:	62%
ATM Pressure:	100.1kPa
Test Date:	2026-02-24
Test Engineer:	Wlif Wu

Note: The maximum output power mode: EDR($\pi/4$ -DQPSK) high channel was tested.

For USB port

Project No.: 2507A33238E-RF
 Test Mode: EDR 2DH5 2480MHz
 EUT Model: KG-UV96G

Temp/Humi/ATM: 24.5°C/62%/100.1kPa
 Tested by: Wlif Wu
 Power Source: AC 120V/60Hz



Trace: 1


Condition: IF B/W 9kHz PK/AV

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.158	-0.51	20.87	20.36	55.56	35.20	Line	Average
0.158	18.14	20.87	39.01	65.56	26.55	Line	QP
0.176	3.50	20.73	24.23	54.67	30.44	Line	Average
0.176	17.62	20.73	38.35	64.67	26.32	Line	QP
0.265	0.52	20.48	21.00	51.28	30.28	Line	Average
0.265	13.94	20.48	34.42	61.28	26.86	Line	QP
0.445	6.65	20.33	26.98	46.96	19.98	Line	Average
0.445	14.34	20.33	34.67	56.96	22.29	Line	QP
1.754	-5.80	21.09	15.29	46.00	30.71	Line	Average
1.754	3.40	21.09	24.49	56.00	31.51	Line	QP
3.520	-6.90	20.75	13.85	46.00	32.15	Line	Average
3.520	1.75	20.75	22.50	56.00	33.50	Line	QP

Project No.: 2507A33238E-RF
 Test Mode: EDR 2DH5 2480MHz
 EUT Model: KG-UV96G

Temp/Humi/ATM: 24.5°C/62%/100.1kPa
 Tested by: Wlif Wu
 Power Source: AC 120V/60Hz

Date: 2026-02-24



Trace: 1


Condition: IF B/W 9kHz PK/AV

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.155	9.32	20.72	30.04	55.72	25.68	Neutral	Average
0.155	19.96	20.72	40.68	65.72	25.04	Neutral	QP
0.184	4.25	20.69	24.94	54.28	29.34	Neutral	Average
0.184	15.86	20.69	36.55	64.28	27.73	Neutral	QP
0.249	2.70	20.60	23.30	51.80	28.50	Neutral	Average
0.249	14.97	20.60	35.57	61.80	26.23	Neutral	QP
0.443	9.67	20.43	30.10	47.01	16.91	Neutral	Average
0.443	20.50	20.43	40.93	57.01	16.08	Neutral	QP
1.562	-3.55	20.99	17.44	46.00	28.56	Neutral	Average
1.562	8.33	20.99	29.32	56.00	26.68	Neutral	QP
5.368	-2.80	20.89	18.09	50.00	31.91	Neutral	Average
5.368	10.84	20.89	31.73	60.00	28.27	Neutral	QP

For Charger

Project No.: 2507A33238E-RF
 Test Mode: EDR 2DH5 2480MHz
 EUT Model: KG-UV96G

Temp/Humi/ATM: 24.5°C/62%/100.1kPa
 Tested by: Wlif Wu
 Power Source: AC 120V/60Hz



Trace: 1


Condition: IF B/W 9kHz PK/AV

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.155	26.66	20.89	47.55	55.75	8.20	Line	Average
0.155	40.99	20.89	61.88	65.75	3.87	Line	QP
0.192	20.65	20.61	41.26	53.94	12.68	Line	Average
0.192	35.36	20.61	55.97	63.94	7.97	Line	QP
0.231	15.39	20.52	35.91	52.41	16.50	Line	Average
0.231	30.11	20.52	50.63	62.41	11.78	Line	QP
0.269	10.96	20.47	31.43	51.15	19.72	Line	Average
0.269	25.85	20.47	46.32	61.15	14.83	Line	QP
0.344	3.48	20.40	23.88	49.11	25.23	Line	Average
0.344	20.52	20.40	40.92	59.11	18.19	Line	QP
0.591	6.07	20.40	26.47	46.00	19.53	Line	Average
0.591	17.99	20.40	38.39	56.00	17.61	Line	QP

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G

Temp/Humi/ATM: 24.5°C/62%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz

Date: 2026-02-24



Trace: 1


Condition: IF B/W 9kHz PK/AV



Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.154	23.35	20.72	44.07	55.76	11.69	Neutral	Average
0.154	36.79	20.72	57.51	65.76	8.25	Neutral	QP
0.192	17.26	20.67	37.93	53.93	16.00	Neutral	Average
0.192	31.20	20.67	51.87	63.93	12.06	Neutral	QP
0.231	13.43	20.62	34.05	52.41	18.36	Neutral	Average
0.231	25.93	20.62	46.55	62.41	15.86	Neutral	QP
0.274	16.35	20.57	36.92	50.99	14.07	Neutral	Average
0.274	21.86	20.57	42.43	60.99	18.56	Neutral	QP
0.585	22.29	20.35	42.64	46.00	3.36	Neutral	Average
0.585	26.40	20.35	46.75	56.00	9.25	Neutral	QP
1.464	8.75	20.98	29.73	46.00	16.27	Neutral	Average
1.464	15.36	20.98	36.34	56.00	19.66	Neutral	QP

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test System Setup**9 kHz-30MHz**

Below 1 GHz:**Above 1GHz:**

The radiated emission tests using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, and FCC 15.247 limits.

NOTE: d is testing distance;


For Radiated Emission test (1GHz-18GHz) and Bandedge Emission test, which was performed at 3 m distance.

For Radiated Emission test (18GHz-25GHz), which was performed at 1.5 m distance, according to ANSI

C63.10-2020, the test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.5m.

Distance extrapolation Factor = $20 \log (\text{specific distance [3m]}/\text{test distance [1.5m]})$ dB = 6 dB

Antenna-port conducted emission:



Note: A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable was TDF into the setting of test equipment:

TDF = Insert loss of RF cable

★ The Insert loss was declared by manufacturer.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & spectrum analyzer setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	300Hz	1 kHz	200Hz	QP
150 kHz – 30 MHz	10 kHz	30 kHz	9 kHz	QP
30 MHz – 1000 MHz	100 kHz	300 kHz	/	PK
	/	/	120kHz	QP

1GHz~25GHz:

Pre-scan:

Measurement	RBW	Video B/W	Detector
PK	1MHz	3MHz	PK
AV	1MHz	5kHz	PK

Final measurement for emission identified during the pre-scan:

Measurement	RBW	Video B/W	Detector
PK	1MHz	3MHz	PK
AV	1MHz	10Hz	PK

Test Procedure

Radiated Emissions:

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

For each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable. The report shall list the six emissions with the smallest margin relative to the limit, for each of the three

antenna orientations (parallel, perpendicular, and ground parallel) unless the margin is greater than 20 dB, then the following statement shall be made: “all emissions were greater than 20 dB below the limit.”

Below 1GHz, if the measured peak level of the emissions that the measuring receiver reading level plus corrected factor is at least 6 dB below the QP emission limit, there's no need to record the measured QP level of the emissions in the report.

Above 1GHz, if the measured peak level of the emissions that the measuring receiver reading level plus corrected factor is below the AV emission limit, there's no need to record the measured AV level of the emissions in the report.

Antenna-port conducted emission:

Connect the primary antenna port through an attenuator to the spectrum analyzer input; in the results, account for all losses between the unlicensed wireless device output and the spectrum analyzer. The frequency range of testing shall span 30 MHz to 10 times the operating frequency and this may be done in a single sweep or, to aid resolution, across a number of sweeps. The resolution bandwidth shall be 100 kHz, video bandwidth 300 kHz, and a coupled sweep time with a peak detector.

The limit is based on the highest in-band level across all channels measured using the same instrument settings (resolution bandwidth of 100 kHz, video bandwidth of 300 kHz, and a coupled sweep time with a peak detector). To help clearly demonstrate compliance a display line may be set at the required offset (typically 20 dB) below the highest in-band level. Where the highest in-band level is not clearly identified in the out-of-band measurements a separate spectral plot showing the in-band level shall be provided. When conducted measurements cannot be made (for example a device with integrated, non-removable antenna) radiated measurements shall be used. The reference level for determining the limit shall be established by maximizing the field strength from the highest power channel and measuring using the resolution and video bandwidth settings and peak detector as described above. The field strength limit for spurious emissions outside of restricted-bands shall then be set at the required offset (typically 20 dB) below the highest in-band level. Radiated measurements will follow the standards measurement procedures described in Clause 6 with the exception that the resolution bandwidth shall be 100 kHz, video bandwidth 300 kHz, and a coupled sweep time with a peak detector. Note that use of wider measurement bandwidths are acceptable for measuring the spurious emissions provided that the peak detector is used and that the measured value of spurious emissions are compared to the highest in-band level measured with the 100 kHz / 300 kHz bandwidth settings to determine compliance.

Result &Margin Calculation

The Result is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

For 9 kHz to 18GHz Radiated emission test and Bandedge emissions test
Factor (dB/m) =Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

For 18GHz to 25GHz Radiated emission test
Factor (dB/m) =Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB) - Extrapolation factor (dB)

Extrapolation factor=6dB (distance=1.5m)

Result (dBμV/m) = Reading (dBμV) + Factor (dB/m)

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dBμV/m) –Result (dBμV/m)

Test Data

Please refer to the below table and plots.

Frequency Range:	Below 1 GHz	Above 1 GHz	Antenna-port conducted emission
Temperature:	23.4°C	23.4°C	22.6°C
Relative Humidity:	51 %	51 %	46%
ATM Pressure:	100.1kPa	100.1kPa	100.1kPa
Test Date:	2026-02-07	2026-02-07	2026-01-04
Test Engineer:	Wlif Wu	Wlif Wu	Jenphy Zeng

Note: Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.

1) 9 kHz ~30MHz


Pre-scan in parallel, ground-parallel and perpendicular of orientation of loop antenna, parallel is worst case.

Note: The maximum output power mode: EDR($\pi/4$ -DQPSK) high channel was tested.

For USB port

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:300Hz VBW:1kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
0.029	8.23	19.90	28.13	118.26	90.13	Peak
0.044	6.15	19.91	26.06	114.80	88.74	Peak
0.071	5.13	19.80	24.93	110.57	85.64	Peak
0.109	5.29	19.73	25.02	106.84	81.82	Peak
0.126	4.01	19.73	23.74	105.58	81.84	Peak
0.145	3.84	19.73	23.57	104.38	80.81	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:10kHz VBW:30kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
0.153	16.87	19.72	36.59	103.91	67.32	Peak
4.290	14.67	19.73	34.40	69.54	35.14	Peak
12.783	14.53	19.73	34.26	69.54	35.28	Peak
18.245	15.32	19.97	35.29	69.54	34.25	Peak
23.132	14.13	20.17	34.30	69.54	35.24	Peak
24.576	15.51	20.21	35.72	69.54	33.82	Peak

For Charger

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:300Hz VBW:1kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
0.029	8.18	19.90	28.08	118.29	90.21	Peak
0.042	7.06	19.91	26.97	115.21	88.24	Peak
0.063	5.39	19.88	25.27	111.60	86.33	Peak
0.084	4.63	19.75	24.38	109.08	84.70	Peak
0.105	4.65	19.73	24.38	107.16	82.78	Peak
0.128	4.25	19.73	23.98	105.45	81.47	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz



Condition: PK RBW:10kHz VBW:30kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
0.150	17.48	19.72	37.20	104.08	66.88	Peak
4.562	14.48	19.71	34.19	69.54	35.35	Peak
14.233	14.63	19.75	34.38	69.54	35.16	Peak
18.245	15.90	19.97	35.87	69.54	33.67	Peak
23.132	14.97	20.17	35.14	69.54	34.40	Peak
24.579	14.86	20.21	35.07	69.54	34.47	Peak


2) 30MHz-1GHz

Note: The maximum output power mode: EDR($\pi/4$ -DQPSK) high channel was tested.

For USB port

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
110.03	30.47	-11.88	18.59	43.50	24.91	Horizontal	Peak
238.65	37.59	-11.78	25.81	46.00	20.19	Horizontal	Peak
324.88	41.72	-8.64	33.08	46.00	12.92	Horizontal	Peak
674.18	27.99	-0.61	27.38	46.00	18.62	Horizontal	Peak
755.46	28.33	0.48	28.81	46.00	17.19	Horizontal	Peak
818.03	27.52	1.53	29.05	46.00	16.95	Horizontal	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
34.37	38.28	-7.70	30.58	40.00	9.42	Vertical	Peak
42.03	39.56	-13.13	26.43	40.00	13.57	Vertical	Peak
96.54	36.36	-15.89	20.47	43.50	23.03	Vertical	Peak
223.71	33.74	-12.55	21.19	46.00	24.81	Vertical	Peak
325.17	36.97	-8.64	28.33	46.00	17.67	Vertical	Peak
810.07	27.55	1.39	28.94	46.00	17.06	Vertical	Peak

For Charger

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
114.20	35.72	-11.15	24.57	43.50	18.93	Horizontal	Peak
137.48	34.27	-10.48	23.79	43.50	19.71	Horizontal	Peak
202.37	36.88	-11.88	25.00	43.50	18.50	Horizontal	Peak
423.82	40.38	-5.54	34.84	46.00	11.16	Horizontal	Peak
752.75	27.89	0.51	28.40	46.00	17.60	Horizontal	Peak
824.04	27.81	1.64	29.45	46.00	16.55	Horizontal	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz

Date: 2026-02-07




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
33.49	40.70	-7.22	33.48	40.00	6.52	Vertical	QP
68.41	47.32	-17.14	30.18	40.00	9.82	Vertical	Peak
114.88	46.80	-10.94	35.86	43.50	7.64	Vertical	QP
139.13	46.08	-10.62	35.46	43.50	8.04	Vertical	QP
204.02	42.89	-12.00	30.89	43.50	12.61	Vertical	Peak
423.82	42.88	-5.54	37.34	46.00	8.66	Vertical	Peak

3) 1 GHz-3 GHz

Project No.: 2507A33238E-RF
Test Mode: BDR DH5 2402MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2535.00	46.89	-10.63	36.26	74.00	37.74	horizontal	Peak
2666.00	48.53	-10.14	38.39	74.00	35.61	horizontal	Peak
2879.80	47.29	-9.58	37.71	74.00	36.29	horizontal	Peak

Project No.: 2507A33238E-RF
Test Mode: BDR DH5 2402MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2604.20	47.25	-10.38	36.87	74.00	37.13	vertical	Peak
2789.20	47.41	-9.82	37.59	74.00	36.41	vertical	Peak
2983.20	46.74	-9.04	37.70	74.00	36.30	vertical	Peak

Project No.: 2507A33238E-RF
Test Mode: BDR DH5 2441MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2578.40	47.45	-10.49	36.96	74.00	37.04	horizontal	Peak
2787.00	47.37	-9.83	37.54	74.00	36.46	horizontal	Peak
2980.20	47.16	-9.05	38.11	74.00	35.89	horizontal	Peak

Project No.: 2507A33238E-RF
Test Mode: BDR DH5 2441MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2660.60	48.92	-10.16	38.76	74.00	35.24	vertical	Peak
2863.60	47.44	-9.60	37.84	74.00	36.16	vertical	Peak
2979.60	47.28	-9.05	38.23	74.00	35.77	vertical	Peak

Project No.: 2507A33238E-RF
Test Mode: BDR DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2667.00	48.74	-10.13	38.61	74.00	35.39	horizontal	Peak
2861.60	47.67	-9.61	38.06	74.00	35.94	horizontal	Peak
2989.80	47.24	-9.00	38.24	74.00	35.76	horizontal	Peak

Project No.: 2507A33238E-RF
Test Mode: BDR DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2655.00	48.14	-10.18	37.96	74.00	36.04	vertical	Peak
2739.20	47.21	-9.96	37.25	74.00	36.75	vertical	Peak
2909.80	47.70	-9.48	38.22	74.00	35.78	vertical	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2402MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2654.40	47.91	-10.18	37.73	74.00	36.27	horizontal	Peak
2783.80	47.60	-9.83	37.77	74.00	36.23	horizontal	Peak
2978.60	47.45	-9.06	38.39	74.00	35.61	horizontal	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2402MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2520.00	47.67	-10.66	37.01	74.00	36.99	vertical	Peak
2663.80	49.52	-10.14	39.38	74.00	34.62	vertical	Peak
2850.20	47.37	-9.62	37.75	74.00	36.25	vertical	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2441MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2531.20	48.21	-10.64	37.57	74.00	36.43	horizontal	Peak
2669.60	47.70	-10.12	37.58	74.00	36.42	horizontal	Peak
2897.40	47.74	-9.56	38.18	74.00	35.82	horizontal	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2441MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2665.40	48.26	-10.14	38.12	74.00	35.88	vertical	Peak
2810.20	47.24	-9.76	37.48	74.00	36.52	vertical	Peak
2933.00	47.35	-9.32	38.03	74.00	35.97	vertical	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2678.00	48.14	-10.10	38.04	74.00	35.96	horizontal	Peak
2867.20	47.44	-9.60	37.84	74.00	36.16	horizontal	Peak
2975.60	46.72	-9.07	37.65	74.00	36.35	horizontal	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz



Condition: PK RBW:1MHz VBW:3MHz SWT:auto


Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2660.20	49.14	-10.16	38.98	74.00	35.02	vertical	Peak
2821.60	47.43	-9.71	37.72	74.00	36.28	vertical	Peak
2918.20	47.38	-9.42	37.96	74.00	36.04	vertical	Peak

4) 3 GHz-18 GHz

Project No.: 2507A33238E-RF
 Test Mode: BDR DH5 2402MHz
 EUT Model: KG-UV96G
 Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
 Tested by: Wlif Wu
 Power Source: AC 120V/60Hz

Date: 2026-02-07



Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto
 AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4804.00	49.52	-5.24	44.28	74.00	29.72	horizontal	Peak
7206.00	43.28	-2.55	40.73	74.00	33.27	horizontal	Peak
14212.50	46.94	5.36	52.30	74.00	21.70	horizontal	Peak
17916.00	35.44	6.82	42.26	54.00	11.74	horizontal	Average
17916.00	45.73	6.82	52.55	74.00	21.45	horizontal	Peak

Project No.: 2507A33238E-RF

Test Mode: BDR DH5 2402MHz

EUT Model: KG-UV96G


Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa

Tested by: Wlif Wu

Power Source: AC 120V/60Hz

Date: 2026-02-07



Trace: 1


Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4804.00	44.68	-5.24	39.44	74.00	34.56	vertical	Peak
7206.00	43.59	-2.55	41.04	74.00	32.96	vertical	Peak
13608.00	47.10	4.71	51.81	74.00	22.19	vertical	Peak
17917.50	35.69	6.82	42.51	54.00	11.49	vertical	Average
17917.50	45.59	6.82	52.41	74.00	21.59	vertical	Peak

Project No.: 2507A33238E-RF
Test Mode: BDR DH5 2441MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz



Trace: 1


Condition: PK RBW:1MHz VBW:3MHz SWT:auto
AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4882.00	50.66	-5.31	45.35	74.00	28.65	horizontal	Peak
7323.00	44.53	-2.24	42.29	74.00	31.71	horizontal	Peak
14071.50	46.50	5.29	51.79	74.00	22.21	horizontal	Peak
17970.00	35.11	6.88	41.99	54.00	12.01	horizontal	Average
17970.00	47.12	6.88	54.00	74.00	20.00	horizontal	Peak

Project No.: 2507A33238E-RF
Test Mode: BDR DH5 2441MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz

Date: 2026-02-07




Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto
AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4882.00	46.21	-5.31	40.90	74.00	33.10	vertical	Peak
7323.00	44.35	-2.24	42.11	74.00	31.89	vertical	Peak
14068.50	46.37	5.29	51.66	74.00	22.34	vertical	Peak
17974.50	34.97	6.88	41.85	54.00	12.15	vertical	Average
17974.50	47.21	6.88	54.09	74.00	19.91	vertical	Peak

Project No.: 2507A33238E-RF
Test Mode: BDR DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz



Trace: 1


Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4960.00	50.86	-5.11	45.75	74.00	28.25	horizontal	Peak
7440.00	48.06	-2.03	46.03	74.00	27.97	horizontal	Peak
14542.50	46.99	5.05	52.04	74.00	21.96	horizontal	Peak
17976.00	35.59	6.89	42.48	54.00	11.52	horizontal	Average
17976.00	45.66	6.89	52.55	74.00	21.45	horizontal	Peak

Project No.: 2507A33238E-RF
Test Mode: BDR DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz



Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto


AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4960.00	47.56	-5.11	42.45	74.00	31.55	vertical	Peak
7440.00	45.58	-2.03	43.55	74.00	30.45	vertical	Peak
14070.00	46.67	5.29	51.96	74.00	22.04	vertical	Peak
17989.50	34.95	6.90	41.85	54.00	12.15	vertical	Average
17989.50	46.14	6.90	53.04	74.00	20.96	vertical	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2402MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz

Date: 2026-02-07



Trace: 1


Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4804.00	50.14	-5.24	44.90	74.00	29.10	horizontal	Peak
7206.00	43.68	-2.55	41.13	74.00	32.87	horizontal	Peak
14512.50	46.43	5.07	51.50	74.00	22.50	horizontal	Peak
17934.00	35.44	6.83	42.27	54.00	11.73	horizontal	Average
17934.00	46.77	6.83	53.60	74.00	20.40	horizontal	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2402MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz



Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4804.00	44.52	-5.24	39.28	74.00	34.72	vertical	Peak
7206.00	43.57	-2.55	41.02	74.00	32.98	vertical	Peak
14064.00	45.74	5.28	51.02	74.00	22.98	vertical	Peak
17955.00	35.33	6.87	42.20	54.00	11.80	vertical	Average
17955.00	46.19	6.87	53.06	74.00	20.94	vertical	Peak

Project No.: 2507A33238E-RF

Test Mode: EDR 2DH5 2441MHz

EUT Model: KG-UV96G


Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa

Tested by: Wlif Wu

Power Source: AC 120V/60Hz

Date: 2026-02-07



Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4882.00	51.40	-5.31	46.09	74.00	27.91	horizontal	Peak
7323.00	44.93	-2.24	42.69	74.00	31.31	horizontal	Peak
14515.50	47.84	5.06	52.90	74.00	21.10	horizontal	Peak
17916.00	34.17	6.82	40.99	54.00	13.01	horizontal	Average
17916.00	46.40	6.82	53.22	74.00	20.78	horizontal	Peak

Project No.: 2507A33238E-RF

Test Mode: EDR 2DH5 2441MHz

EUT Model: KG-UV96G


Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa

Tested by: Wlif Wu

Power Source: AC 120V/60Hz

Date: 2026-02-07



Trace: 1


Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4882.00	45.68	-5.31	40.37	74.00	33.63	vertical	Peak
7323.00	43.93	-2.24	41.69	74.00	32.31	vertical	Peak
13828.50	46.87	5.09	51.96	74.00	22.04	vertical	Peak
17995.50	35.68	6.91	42.59	54.00	11.41	vertical	Average
17995.50	46.58	6.91	53.49	74.00	20.51	vertical	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz



Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4960.00	50.09	-5.11	44.98	74.00	29.02	horizontal	Peak
7440.00	46.60	-2.03	44.57	74.00	29.43	horizontal	Peak
13552.50	46.96	4.67	51.63	74.00	22.37	horizontal	Peak
17994.00	35.73	6.90	42.63	54.00	11.37	horizontal	Average
17994.00	45.74	6.90	52.64	74.00	21.36	horizontal	Peak

Project No.: 2507A33238E-RF

Test Mode: EDR 2DH5 2480MHz

EUT Model: KG-UV96G


Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa

Tested by: Wlif Wu

Power Source: AC 120V/60Hz

Date: 2026-02-07



Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto


Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4960.00	46.21	-5.11	41.10	74.00	32.90	vertical	Peak
7440.00	45.64	-2.03	43.61	74.00	30.39	vertical	Peak
14551.50	46.85	5.04	51.89	74.00	22.11	vertical	Peak
17934.00	34.88	6.83	41.71	54.00	12.29	vertical	Average
17934.00	47.06	6.83	53.89	74.00	20.11	vertical	Peak

5) 18 GHz-25 GHz

Note: The maximum output power mode: EDR($\pi/4$ -DQPSK) high channel was tested.

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 1.5m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto
AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
21791.90	38.06	4.94	43.00	54.00	11.00	horizontal	Average
21791.90	51.55	4.94	56.49	74.00	17.51	horizontal	Peak
23898.20	36.62	5.37	41.99	54.00	12.01	horizontal	Average
23898.20	50.33	5.37	55.70	74.00	18.30	horizontal	Peak
24915.30	37.40	6.31	43.71	54.00	10.29	horizontal	Average
24915.30	50.27	6.31	56.58	74.00	17.42	horizontal	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 1.5m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz



Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto


AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
21863.30	38.06	5.14	43.20	54.00	10.80	vertical	Average
21863.30	51.15	5.14	56.29	74.00	17.71	vertical	Peak
23107.20	37.60	4.93	42.53	54.00	11.47	vertical	Average
23107.20	51.55	4.93	56.48	74.00	17.52	vertical	Peak
24423.20	37.25	6.11	43.36	54.00	10.64	vertical	Average
24423.20	50.63	6.11	56.74	74.00	17.26	vertical	Peak

Restricted Bands Emissions:

Project No.: 2507A33238E-RF
Test Mode: BDR DH5 2402MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz



Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2378.86	50.40	-1.20	49.20	74.00	24.80	horizontal	Peak
2390.00	45.18	-1.15	44.03	74.00	29.97	horizontal	Peak

Project No.: 2507A33238E-RF

Test Mode: BDR DH5 2402MHz

EUT Model: KG-UV96G


Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa

Tested by: Wlif Wu

Power Source: AC 120V/60Hz

Date: 2026-02-07




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2383.18	48.53	-1.19	47.34	74.00	26.66	vertical	Peak
2390.00	45.95	-1.15	44.80	74.00	29.20	vertical	Peak

Project No.: 2507A33238E-RF
Test Mode: BDR DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2483.50	48.93	-0.77	48.16	74.00	25.84	horizontal	Peak
2491.55	51.05	-0.73	50.32	74.00	23.68	horizontal	Peak

Project No.: 2507A33238E-RF
Test Mode: BDR DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2483.50	46.05	-0.77	45.28	74.00	28.72	vertical	Peak
2490.37	49.90	-0.75	49.15	74.00	24.85	vertical	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2402MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2379.85	50.13	-1.20	48.93	74.00	25.07	horizontal	Peak
2390.00	45.70	-1.15	44.55	74.00	29.45	horizontal	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2402MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2381.54	48.81	-1.19	47.62	74.00	26.38	vertical	Peak
2390.00	47.43	-1.15	46.28	74.00	27.72	vertical	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m

Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2483.50	49.06	-0.77	48.29	74.00	25.71	horizontal	Peak
2494.13	51.46	-0.72	50.74	74.00	23.26	horizontal	Peak

Project No.: 2507A33238E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: KG-UV96G
Test distance: 3m


Temp/Humi/ATM: 23.4°C/51%/100.1kPa
Tested by: Wlif Wu
Power Source: AC 120V/60Hz




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2483.50	46.62	-0.77	45.85	74.00	28.15	vertical	Peak
2486.30	49.31	-0.75	48.56	74.00	25.44	vertical	Peak


Antenna-port conducted emission:




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:47:58




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:53:03




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:58:05



ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 16:03:05



ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 16:08:09




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 16:13:22

FCC §15.247(a) (1) –CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

EUT Setup



Note: A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable was offset into the setting of test equipment:

Offset = Insert loss of RF cable

★ The Insert loss was declared by manufacturer.

Test Procedure

According to ANSI C63.10-2020 Section 7.8.2

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) $\geq$ RBW.
- d) Sweep: No faster than coupled (auto) time.
- e) Detector function: Peak.
- f) Trace: Max-hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

Where the device shares the same channel plan (carrier frequencies and number of channels) across multiple data rates or modulation schemes then the carrier separation need only be measured for one of those modulation schemes or data rates.

Test Mode:		Transmitting		Test Engineer:		Jenphy Zeng	
Test Date:		2026-01-04		Environment:		Temp.: 22.6°C Humi.: 46% Atm.: 100.1 kPa	
Mode	Channel		Channel Separation (MHz)		Limit (MHz)	Result	
BDR (GFSK)	Low		1.002		0.839	Pass	
	Middle		1.000		0.835	Pass	
	High		1.000		0.837	Pass	

2. Only BDR (GFSK) mode result is reported since EDR ($\pi/4$ -DQPSK) has the same channel plan.

Ref 20.5 dBm * Att 30 dB SWT 10 ms Delta 1 [T1] -0.01 dB 1.001600000 MHz


20 Offset 0.1 dB Marker 1 [T1] -2.64 dBm 2.401845600 GHz

1 pp MAGN

Center 2.4025 GHz 200 kHz/ Span 2 MHz


ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:01:02

BDR (GFSK): Middle Channel



ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:01:55

BDR (GFSK): High Channel




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:02:44

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

EUT Setup

Note: A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable was offset into the setting of test equipment:

Offset = Insert loss of RF cable

★ The Insert loss was declared by manufacturer.

Test Procedure

According to ANSI C63.10-2020 Section 6.9.2

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be at least three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.6.2
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “–xx dB down” requirement; that is, if the requirement calls for measuring the –20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max-hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “–xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and

either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.


k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Test Data

Test Mode:	Transmitting	Test Engineer:	Jenphy Zeng
Test Date:	2026-01-04	Environment:	Temp.: 22.6°C Humi.: 46% Atm.: 100.1 kPa
Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.890
	Middle	2441	0.890
	High	2480	0.888
EDR ($\pi/4$-DQPSK)	Low	2402	1.258
	Middle	2441	1.253
	High	2480	1.255


Please refer to below plots:

BDR (GFSK): Low Channel




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:27:13


BDR (GFSK): Middle Channel




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:29:17

BDR (GFSK): High Channel


ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:30:16

EDR ($\pi/4$ -DQPSK): Low Channel

ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:31:29

EDR ($\pi/4$ -DQPSK): Middle Channel

ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:32:33


EDR ($\pi/4$ -DQPSK): High Channel

ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:33:32

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

EUT Setup

Note: A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable was offset into the setting of test equipment:

Offset = Insert loss of RF cable

★ The Insert loss was declared by manufacturer.

Test Procedure

According to ANSI C63.10-2020 Section 7.8.3

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW $\geq$ RBW.
- d) Sweep: No faster than coupled (auto) time.
- e) Detector function: Peak.
- f) Trace: Max-hold.
- g) Allow the trace to stabilize

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.


Where the device shares the same channel plan (carrier frequencies and number of channels) across multiple data rates or modulation schemes then the number of channels need only be measured for one of those modulation schemes or data rates.

Test Mode:	Transmitting	Test Engineer:	Jenphy Zeng
Test Date:	2026-01-04	Environment:	Temp.: 22.6°C Humi.: 46% Atm.: 100.1 kPa
Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR ($\pi/4$ -DQPSK)	2400-2483.5	79	≥15

[illegible]

ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:25:58


EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:29:43

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

EUT Setup

Note: A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable was offset into the setting of test equipment:

Offset = Insert loss of RF cable

★ The Insert loss was declared by manufacturer.

Test Procedure

According to ANSI C63.10-2020 Section 7.8.4

Use the following spectrum analyzer settings to determine the dwell time per hop:

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected transmission time per hop.
- c) Sweep time: Set so that the start of the first transmission and end of the last transmission for the hop are clearly captured. Setting the sweep time to be slightly longer than the hopping period per channel (hopping period = $1/\text{hopping rate}$) should achieve this.
- d) Use a video trigger, where possible with a trigger delay, so that the start of the transmission is clearly observed. The trigger level might need adjustment to reduce the chance of triggering when the system hops on an adjacent channel.
- e) Detector function: Peak.
- f) Trace: Clear-write, single sweep.
- g) Place markers at the start of the first transmission on the channel and at the end of the last transmission. The dwell time per hop is the time between these two markers.

To determine the number of hops on a channel in the regulatory observation period repeat the measurement using a longer sweep time. When the device uses a single hopping sequence the period of measurement should be sufficient to capture at least 2 hops. When the device uses a dynamic hopping sequence, or the sequence varies, the period of measurement may need to capture multiple hops to better determine the average time of occupancy. Count the number of hops on the channel across the sweep time.


The average number of hops on the same channel within the regulatory observation period is calculated from the number of hops on the channel divided by the spectrum analyzer sweep time multiplied by the regulatory observation period. For example, if three hops are counted with an analyzer sweep time of 500 ms and the regulatory observation period is 10 s, then the number of hops in that ten seconds is $3 / 0.5 \times 10$, or 60 hops.

The average time of occupancy is calculated by multiplying the dwell time per hop by the number of hops in the observation period.

Test Data


Test Mode:		Transmitting		Test Engineer:		Jenphy Zeng
Test Date:		2026-01-04		Environment:		Temp.: 22.6°C Humi.: 46% Atm.: 100.1 kPa
Mode	Packet Type	Test Frequency (MHz)	BurstWidth (ms)	TotalHops (Num)	Result (s)	Limit (s)
BDR (GFSK)	DH1	2441	0.380	235	0.089	0.400
	DH3	2441	1.644	135	0.222	0.400
	DH5	2441	2.900	104	0.302	0.400
EDR ($\pi/4$ -DQPSK)	2DH1	2441	0.394	241	0.095	0.400
	2DH3	2441	1.651	148	0.244	0.400
	2DH5	2441	2.908	99	0.288	0.400
Note: Note 1: A period time = $0.4 \times 79 = 31.6(S)$, Result = BurstWidth * Totalhops Note 2: Totalhops = Hopping Number in 31.6s Note 3: Hopping Number in 31.6s = Total of highest signals in 31.6s(Second high signals were other channel)						

DH1_Hopping




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:21:10

DH1_Hopping




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:21:34

DH3_Hopping




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:32:30

DH3_Hopping




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:32:56

DH5_Hopping




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:33:58

DH5_Hopping




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:34:28

2DH1_Hopping




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:35:38

2DH1_Hopping




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:36:03

2DH3_Hopping




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:37:17

2DH3_Hopping




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:37:46

2DH5_Hopping



ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:39:03

2DH5_Hopping




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:39:29

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

EUT Setup

Note: A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable was offset into the setting of test equipment:

Offset = Insert loss of RF cable

★ The Insert loss was declared by manufacturer.

Test Procedure

According to ANSI C63.10-2020 Section 7.8.5

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. Frequency hopping shall be disabled for this test. Use the following spectrum analyzer setting:


- a) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- b) RBW > 20 dB bandwidth of the emission being measured.
- c) VBW $\geq$ RBW.
- d) Sweep: No faster than coupled (auto) time.
- e) Detector function: Peak.
- f) Trace: Max-hold.
- g) Allow trace to stabilize.
- h) Use the marker-to-peak function to set the marker to the peak of the emission.
- i) The indicated level is the peak output power, after any corrections for external attenuators and cables.
- j) A plot of the test results and setup description shall be included in the test report.

Test Data

Test Mode:	Transmitting	Test Engineer:	Jenphy Zeng
Test Date:	2026-01-04	Environment:	Temp.: 22.6°C Humi.: 46% Atm.: 100.1kPa
Mode	Frequency (MHz)	Peak Conducted Output Power (dBm)	Limit (dBm)
BDR (GFSK)	2402	-0.52	21
	2441	0.39	21
	2480	0.58	21
EDR ($\pi/4$-DQPSK)	2402	0.14	21
	2441	1.09	21
	2480	1.26	21


Please refer to below plots:

BDR (GFSK): 2402MHz




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:37:46

BDR (GFSK): 2441MHz




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:42:20

BDR (GFSK): 2480MHz




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:44:16

EDR ($\pi/4$ -DQPSK): 2402MHz




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:49:32

EDR ($\pi/4$ -DQPSK): 2441MHz



ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:53:48

EDR ($\pi/4$ -DQPSK): 2480MHz




ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:55:49

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

EUT Setup



Note: A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable was offset into the setting of test equipment:

Offset = Insert loss of RF cable

★ The Insert loss was declared by manufacturer.

Test Procedure

According to ANSI C63.10-2020 Section 7.8.7.2 & Claus 6.10

- 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products that fall outside of the authorized band of operation.
- 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW/RBW})]$ below the reference level. Specific guidance is given in 4.1.6.2.
- 3) Attenuation: Auto (at least 10 dB preferred).
- 4) Sweep time: No faster than coupled (auto) time.
- 5) Resolution bandwidth: 100 kHz.
- 6) Video bandwidth: 300 kHz.
- 7) Detector: Peak.
- 8) Trace: Max-hold.


Test Data

Test Mode:	Transmitting	Test Engineer:	Jenphy Zeng
Test Date:	2026-01-04	Environment:	Temp.: 22.6°C Humi.: 46% Atm.: 100.1 kPa


Please refer to the below plots:

Band Edge


BDR (GFSK): Left Side



ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:40:12

BDR (GFSK): Right Side

ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:46:43

BDR (GFSK): Left Side - Hopping

ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:05:54

* RBW 100 kHz Delta 1 [T1]
 * VBW 300 kHz -49.66 dB
 Ref 20 dBm * Att 30 dB
 SWT 10 ms 13.488000000 MHz

20 Offset 0.1 dB
 -19.59 dBm
 Marker 1 [T1]
 2.47684000 GHz 0.41 dBm
 2.4835 GHz
 SWP 2500 Hz 2500 Hz
 1
 1
 1

Center 2.4835 GHz 2 MHz/
 Span 20 MHz

ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:08:47

1. PNA MAGN

Ref 20 dBm Att 30 dB SWT 10 ms

Delta 1 [T1] -36.56 dB

VBW 300 kHz


-2.70400000 MHz

Marker 1 [T1] -0.74 dBm 2.40187000 GHz


SWP 2500 cF 2500

Center 2.4 GHz 2 MHz/ Span 20 MHz

ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:51:58


EDR ($\pi/4$ -DQPSK): Right Side

ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 14:58:16

EDR ($\pi/4$ -DQPSK): Left Side - Hopping

ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:11:51

EDR ($\pi/4$ -DQPSK): Right Side - Hopping



ProjectNo.:2507A33238E-RF Tester:Jenphy Zeng
Date: 4.JAN.2026 15:16:58

EUT PHOTOGRAPHS

Please refer to the attachment 2507A33238E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2507A33238E-RF-INP EUT INTERNAL PHOTOGRAPHS.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2507A33238E-RF-TSP-02 TEST SETUP PHOTOGRAPHS.

Declarations

1. Bay Area Compliance Laboratories Corp. (Xiamen) is not responsible for authenticity of any information provided by the applicant. Information from the applicant that may affect test results are marked with an asterisk “★”.
2. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
3. Unless required by the rule provided by the applicant or product regulations, then decision rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor k with the 95% confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of Bay Area Compliance Laboratories Corp. (Xiamen).
6. This report is valid only with a valid digital signature. The digital signature may be available only under the adobe software above version 7.0.

******* END OF REPORT *******