

Maximum Permissible Exposure Evaluation

FCC ID: WY2703AC6

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

EUT Specification

Product Name:	COCKPIT DOMAIN CONTROLLER
Trade Mark:	clarion
Model/Type Reference:	703AC6
Model Differences:	/
Frequency Band (Operating)	BT: 2402MHz ~ 2480MHz BLE: 2402MHz ~ 2480MHz WLAN: 2412MHz ~ 2462MHz U-NII-1: 5180MHz ~ 5240MHz U-NII-3: 5745MHz ~ 5825MHz
Device Category	☐ Portable (<5mm separation) ☐ Mobile (>20cm separation) ☒ Fixed (>20cm separation) ☐ Others ____
Exposure Classification	☐ Occupational/Controlled exposure (S=5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna Diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Antenna Gain (Max)	BLE/BT: 2.9dBi WLAN: 3.32dBi U-NII-1: 4.55dBi U-NII-3: 3.23dBi
Evaluation Applied	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposure				
300-1500	--	--	F/300	<6
1500-100000	--	--	5	<6
(B) Limits for General Population/Uncontrolled Exposure				
300-1500	--	--	F/1500	<30
1500-100000	--	--	1	<30

Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where:

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d limit of MPE is 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Mode	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Max. Tune Up Power (dBm)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
BT/EDR	2441	2.9	8.72	9	0.003081	1
BLE	2440	2.9	4.03	4.5	0.001093	1
WLAN 802.11b	2437	3.32	16.71	17	0.021416	1
WLAN 802.11g	2437	3.32	13.14	13.5	0.009566	1
WLAN 802.11n(HT20)	2437	3.32	10.98	11	0.005380	1
WLAN 802.11n(HT40)	2437	3.32	11.18	11.5	0.006036	1
RLAN U-NII-1 802.11a	5200	4.55	18.55	19	0.045055	1
RLAN U-NII-1 802.11n(HT20)	5200	4.55	18.26	18.5	0.040155	1
RLAN U-NII-1 802.11n(HT40)	5230	4.55	14.78	15	0.017937	1
RLAN U-NII-1 802.11ac(VHT20)	5240	4.55	17.42	17.5	0.031896	1
RLAN U-NII-1 802.11ac(VHT40)	5230	4.55	16.92	17	0.028428	1
RLAN U-NII-1 802.11ac(VHT80)	5210	4.55	14.22	14.5	0.015986	1
RLAN U-NII-3 802.11a	5825	3.23	13.56	14	0.010513	1
RLAN U-NII-3 802.11n(HT20)	5825	3.23	13.34	13.5	0.009370	1

CTC Laboratories, Inc.

Room 107, 108, 207, 208 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

RLAN U-NII-3 802.11n(HT40)	5755	3.23	12.49	12.5	0.007443	1
RLAN U-NII-3 802.11ac(VHT20)	5825	3.23	13.29	13.5	0.009370	1
RLAN U-NII-3 802.11ac(VHT40)	5755	3.23	12.47	12.5	0.007443	1
RLAN U-NII-3 802.11ac(VHT80)	5775	3.23	11.76	12	0.006634	1

The WLAN and BT can transmit simultaneously.

RLAN Power density at 20cm (mW/cm ²)	BT Power density at 20cm (mW/cm ²)	Total Power density at 20cm (mW/cm ²)	Power density Limit (mW/cm ²)
0.045055	0.003081	0.048136	1

Note:

1. Calculate in the worst-case mode.
2. Max. Tune Up Power is declared by manufacturer, and used to calculate.
3. For a more detailed features description, please refer to the RF Test Report.

*****THE END*****