

TEST REPORT

Report No. : **CTC2026281305**

FCC ID : **WY2703AC6**

Applicant : **Faurecia Clarion Electronics (Xiamen) Co., Ltd.**

Address : 6F, No.40, Guanri Road, Software Park Stage II, Xiamen, China

Manufacturer : Faurecia Clarion Electronics (Xiamen) Co., Ltd.

Address : 6F, No.40, Guanri Road, Software Park Stage II, Xiamen, China

Product Name : **COCKPIT DOMAIN CONTROLLER**

Trade Mark : clarion

Model/Type reference : 703AC6

Listed Model : /

Standard : **FCC CFR Title 47 Part 15 Subpart E Section 15.407**

Test Report Form No : CTC-TR-062_A5

Master TRF : Dated 2026-06-01

Date of receipt of test sample : Jun. 2, 2026

Date of testing : Jun. 2, 2026~ Jun. 18, 2026

Date of issue : Jul. 1, 2026

Result : **PASS**

Compiled by:		
(Printed name+signature)	Alicia Liu	<i>Alicia Liu</i>
Supervised by:		
(Printed name+signature)	Eric Zhang	<i>Eric Zhang</i>
Approved by:		
(Printed name+signature)	Totti Zhao	<i>Totti Zhao</i>

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CTC. The test result in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CTC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.

Table of Contents	Page
1. TEST SUMMARY	3
1.1. TEST STANDARDS.....	3
1.2. REPORT VERSION	3
1.3. TEST DESCRIPTION.....	4
1.4. TEST FACILITY	5
1.5. MEASUREMENT UNCERTAINTY	6
1.6. ENVIRONMENTAL CONDITIONS.....	6
2. GENERAL INFORMATION	7
2.1. CLIENT INFORMATION	7
2.2. GENERAL DESCRIPTION OF EUT	7
2.3. ACCESSORY EQUIPMENT INFORMATION	9
2.4. OPERATION STATE	10
2.5. MEASUREMENT INSTRUMENTS LIST	12
3. TEST ITEM AND RESULTS	14
3.1. RADIATED EMISSION.....	14
3.2. BAND EDGE EMISSIONS.....	37
3.3. BANDWIDTH.....	67
3.4. OUTPUT POWER	94
3.5. POWER SPECTRAL DENSITY	96
3.6. FREQUENCY STABILITY	108
3.7. ANTENNA REQUIREMENT.....	111

1. TEST SUMMARY

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.407](#): for 802.11a/n/ac/ax, the test procedure follows the FCC KDB 789033 D02 General UNII Test Procedures New Rules V02r01.

[ANSI C63.10-2020](#): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

1.2. Report Version

Revised No.	Report No.	Date of issue	Description
01	CTC2026281305	Jul. 1, 2026	Original

1.3. Test Description

FCC Part 15 Subpart E (15.407)			
Test Item	Standard Section	Result	Note
Antenna Requirement	15.203	Pass	/
Conducted Emission	15.207	N/A	N/A
Band Edge Emissions	15.407(b)	Pass	/
26dB Bandwidth & 99% Bandwidth	15.407(a)	Pass	/
6dB Bandwidth (only for UNII-3)	15.407(e)	Pass	/
Peak Output Power	15.407(a)	Pass	/
Power Spectral Density	15.407(a)	Pass	/
Transmitter Radiated Spurious Emission	15.407(b) & 15.209	Pass	/
Frequency Stability	15.407(g)	Pass	/
Dynamic Frequency Selection (DFS)	15.407(h)	N/A	N/A
Automatically Discontinue Transmission	15.407(c)	Pass	Note 3

Note:

1. The measurement uncertainty is not included in the test result.
2. N/A: means this test item is not applicable for this device according to the technology characteristic of device.
3. During no any information transmission, the EUT can automatically discontinue transmission and become standby mode for power saving. the EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

1.4. Test Facility

Address of the report laboratory

CTC Laboratories, Inc.

Add: Room 107, 108, 207, 208 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luh Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China

Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

A2LA-Lab Cert. No.: 4340.01

CTC Laboratories, Inc. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

Industry Canada (Registration No.: 9783A, CAB Identifier: CN0029)

CTC Laboratories, Inc. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 9783A on Jan, 2016.

FCC (Registration No.: 951311, Designation Number CN1208)

CTC Laboratories, Inc. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 951311, Aug 26, 2017.

1.5. Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the CTC Laboratories, Inc. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Below is the best measurement capability for CTC Laboratories, Inc.

Test Items	Measurement Uncertainty	Notes
Emission Bandwidth	$\pm 0.0196\%$	(1)
Maximum Conduct Output Power	$\pm 0.766\text{dB}$	(1)
Power Spectral Density	$\pm 1.22\text{dB}$	(1)
Band Edge Measurements	$\pm 1.328\text{dB}$	(1)
Unwanted Emissions Measurement	9kHz-1GHz: $\pm 0.746\text{dB}$ 1GHz-26GHz: $\pm 1.328\text{dB}$	(1)
Frequency Stability	$\pm 2.76\%$	(1)
Conducted Emissions 9kHz~30MHz	$\pm 3.08\text{ dB}$	(1)
Radiated Emissions 30~1000MHz	$\pm 4.51\text{ dB}$	(1)
Radiated Emissions 1~18GHz	$\pm 5.84\text{ dB}$	(1)
Radiated Emissions 18~40GHz	$\pm 6.12\text{ dB}$	(1)

Note (1): This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

1.6. Environmental Conditions

Normal Condition	Temperature	15 °C to 35 °C
	Relative Humidity	20 % to 75 %
	Air Pressure	101 kPa
	Voltage	The normal test voltage for the equipment shall be the nominal voltage for which the equipment was designed.
Extreme Condition	Temperature	Measurements shall be made over the extremes of the operating temperature range as declared by the manufacturer.
	Voltage	Measurements shall be made over the extremes of the operating temperature range as declared by the manufacturer.

Normal Condition	T_N =Normal Temperature	25 °C
Extreme Condition	T_L =Lower Temperature	0 °C
	T_H =Higher Temperature	45 °C

2. GENERAL INFORMATION

2.1. Client Information

Applicant:	Faurecia Clarion Electronics (Xiamen) Co., Ltd.
Address:	6F, No.40, Guanri Road, Software Park Stage II, Xiamen, China
Manufacturer:	Faurecia Clarion Electronics (Xiamen) Co., Ltd.
Address:	6F, No.40, Guanri Road, Software Park Stage II, Xiamen, China
Factory:	Faurecia Clarion Electronics (Fengcheng) Co., Ltd.
Address:	No. 12 High-Tech Road, Fengcheng High Technology Industry Park, Yichun City, Jiangxi Province, P.R. China

2.2. General Description of EUT

Product Name:	COCKPIT DOMAIN CONTROLLER
Trade Mark:	clarion
Model/Type reference:	703AC6
Listed Model:	/
Model Difference:	/
Sample ID:	CTC-GC260407-001-S001
Power Supply:	Input: DC13.5V
Hardware Version:	/
Software Version:	/

5G Wi-Fi					
Operation Band:	☒ U-NII-1	☐ U-NII-2A	☐ U-NII-2C	☒ U-NII-3	
Operation Frequency:	U-NII-1	5180MHz~5240MHz			
	U-NII-3	5745MHz~5825MHz			
Support Bandwidth:	802.11a	☒ 20MHz			
	802.11n	☒ 20MHz	☒ 40MHz		
	802.11ac	☒ 20MHz	☒ 40MHz	☒ 80MHz	
Modulation:	802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)				
Antenna Type:	PCB Antenna				
Antenna Gain:	U-NII-1	4.55dBi			
	U-NII-3	3.23dBi			

2.3. Accessory Equipment Information

Equipment Information			
Name	Model	S/N	Manufacturer
Notebook	ThinkBook 14 G3 ACL	MP246Q6S	Lenovo
HP502 CC&CV DC POWER SUPPLY	HP502	/	HP
Cable Information			
Name	Shielded Type	Ferrite Core	Length
/	/	/	/
Test Software Information			
Name	Version	/	/
/	/	/	/

2.4. Operation State

Operation Frequency List: The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting.

Operation Frequency List:

Operating Band	20MHz Bandwidth		40MHz Bandwidth		80MHz Bandwidth		160MHz Bandwidth	
	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
U-NII-1	36	5180	38	5190	42	5210	50	5250
	40	5200						
	44	5220	46	5230				
	48	5240						
U-NII-3	149	5745	151	5755	155	5775	/	
	153	5765						
	157	5785	159	5795				
	161	5805						
	165	5825						

Test channel is below:

Operating Band	Test Channel	20MHz Bandwidth		40MHz Bandwidth		80MHz Bandwidth		160MHz Bandwidth	
		Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
U-NII-1	CH _L	36	5180	38	5190	/	/	50	5250
	CH _M	40	5200	/	/	42	5210		
	CH _H	48	5240	46	5230	/	/		
U-NII-3	CH _L	149	5745	151	5755	/	/	/	/
	CH _M	157	5785	/	/	155	5775	/	/
	CH _H	165	5825	159	5795	/	/	/	/

Data Rated:

Preliminary tests were performed in different data rate, and found which the below bit rate is worst case mode, so only show data which it is a worst case mode.

Test Mode	Data Rate (worst mode)
802.11a	6Mbps
802.11n(HT20)/ 802.11n(HT40)	HT-MCS0
802.11ac(VHT20)/ 802.11ac(VHT40)/ 802.11ac(VHT80)	VHT-MCS0

Test Mode:

For RF test items:
1. The engineering test program was provided and enabled to make EUT continuous transmit.
2. The measurements for Output Power are tested, the worst case is IEEE 802.11a mode, IEEE 802.11n(HT20) mode, IEEE 802.11n(HT40) mode, IEEE 802.11ac (VHT80) mode, only the worst cases are documented for other test items.
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.
For DFS test items:
The EUT has been tested under test mode condition. The Applicant provides software to control the EUT for staying in DFS mode for testing.

2.5. Measurement Instruments List

Radiated emission						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	9168-759	Oct. 17, 2025	Oct. 16, 2027
2	Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-648	Dec. 12, 2024	Dec. 11, 2026
3	Test Receiver	Keysight	N9038A	MY56400071	Dec. 13, 2025	Dec. 12, 2026
4	Broadband Amplifier	Schwarzbeck	BBV9743B	259	Dec. 13, 2025	Dec. 12, 2026
5	Mirowave Broadband Amplifier	Schwarzbeck	BBV9718C	111	Dec. 13, 2025	Dec. 12, 2026
6	RE33L-001	COMM	/	014 (9kHz-1GHz)	Feb. 09, 2026	Feb. 08, 2027
7	RE33L-002	COMM	/	015 (9kHz-1GHz)	Feb. 09, 2026	Feb. 08, 2027
8	RE33H-001	SUHBER SUCOFLEX	/	016 (1GHz-18GHz)	Feb. 09, 2026	Feb. 08, 2027
9	RE33H-002	HUBENR	/	017 (1GHz-18GHz)	Feb. 09, 2026	Feb. 08, 2027
10	RE33H-003	HUBENR	/	018 (1GHz-18GHz)	Feb. 09, 2026	Feb. 08, 2027
11	RE33H-003	HUBENR	/	019 (18GHz-40GHz)	Feb. 09, 2026	Feb. 08, 2027
12	3m chamber 3	YIHENG	EE106	/	Aug. 29, 2023	Aug. 28, 2026
Test Software						
Name		Manufacturer		Software Version		
EZ-EMC		FARA		FA-03A2		

Radiated emission						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	9168-1013	Dec. 18, 2024	Dec. 17, 2026
2	Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-647	Oct. 17, 2025	Oct. 16, 2027
3	Spectrum Analyzer	R&S	FSV40-N	101654	Dec. 13, 2025	Dec. 12, 2026
4	Pre-Amplifier	SONOMA	310	186194	Dec. 13, 2025	Dec. 12, 2026
5	Low Noise Pre-Amplifier	EMCI	EMC051835	980075	Dec. 13, 2025	Dec. 12, 2026
6	Test Receiver	R&S	ESCI7	100967	Dec. 13, 2025	Dec. 12, 2026
7	RE32L-001	HUBENR	/	009 (9kHz-1GHz)	Feb. 09, 2026	Feb. 08, 2027
8	RE32L-002	HUBENR	/	010 (9kHz-1GHz)	Feb. 09, 2026	Feb. 08, 2027
9	RE32L-003	HUBENR	/	011 (9kHz-1GHz)	Feb. 09, 2026	Feb. 08, 2027
10	RE32H-001	HUBENR	/	012 (1GHz-18GHz)	Feb. 09, 2026	Feb. 08, 2027
11	RE32H-002	HUBENR	/	013 (1GHz-18GHz)	Feb. 09, 2026	Feb. 08, 2027
12	3m chamber 2	Frankonia	EE025	/	Oct. 19, 2024	Oct. 18, 2027
Test Software						
Name		Manufacturer		Software Version		
EZ-EMC		FARA		FA-03A2		

CTC Laboratories, Inc.

Room 107, 108, 207, 208 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A5

Master TRF : Dated 2026-06-01

RF Test System – SRD						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
1	Spectrum Analyzer	R&S	FSV40-N	101654	Dec. 13, 2025	Dec. 12, 2026
2	MXG Vector Signal Generator	Agilent	N5182A	MY47420864	Dec. 13, 2025	Dec. 12, 2026
3	PSG Analog Signal Generator	Agilent	E8257D	MY46521908	Dec. 13, 2025	Dec. 12, 2026
4	USB Wideband Power Sensor	Keysight	U2021XA	MY55130004	Mar. 25, 2026	Mar. 24, 2027
5	USB Wideband Power Sensor	Keysight	U2021XA	MY55130006	Mar. 25, 2026	Mar. 24, 2027
6	Wideband Radio Communication Tester	R&S	CMW500	102257	Mar. 25, 2026	Mar. 24, 2027
7	RF Control Unit	Tonscend	JS0806-2	/	Mar. 25, 2026	Mar. 24, 2027
8	High and low temperature test chamber	ESPEC	MT3035	/	Mar. 25, 2026	Mar. 24, 2027
9	RF Cable	HUBER+SUHNER	SUCOFLEX101PE	RF-08	Apr. 16, 2026	Apr. 15, 2027
Test Software						
Name		Manufacturer		Software Version		
JS1120-3		Tonscend		V2.6.88.0346		

Note: 1. The Cal. Interval was one year.

2. The Cal. Interval was three years of the antenna.

3. The cable loss has been calculated in test result which connection between each test instruments.

3. TEST ITEM AND RESULTS

3.1. Radiated Emission

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F (kHz)	300
0.490~1.705	24000/F (kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Frequency Range (MHz)	dBμV/m (at 3 meters)	
	Peak	Average
Above 1000	74	54

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBμV/m)=20log Emission Level (μV/m).

Limits of unwanted emission out of the restricted bands

FCC CFR Title 47 Part 15 Subpart E Section 15.407(b)

Frequency (MHz)	EIRP Limits (dBm)	Equivalent Field Strength at 3m (dBμV/m)
5150~5250	-27	68.2
5250~5350	-27	68.2
5470~5725	-27	68.2
5725~5825	-27 (Note 2)	68.2
	10 (Note 2)	105.2
	15.6 (Note 2)	110.8
	27 (Note 2)	122.2

Note:

1. The following formula is used to convert the equipment isotropic radiated power (eirp) to field

strength: $E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m}$, where P is the eirp (Watts).


2. According to FCC 16-24, all emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

CTC Laboratories, Inc.


Room 107, 108, 207, 208 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A5


Master TRF : Dated 2026-06-01

Test Configuration

Below 30MHz Test Setup



30-1000MHz Test Setup



Above 1GHz Test Setup

Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2020.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) 9k – 150kHz:
RBW=300 Hz, VBW=1 kHz, Sweep=auto, Detector function=peak, Trace=max hold
 - (3) 0.15M – 30MHz:
RBW=10 kHz, VBW=30 kHz, Sweep=auto, Detector function=peak, Trace=max hold
 - (4) 30M - 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max holdIf the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
- (5) From 1 GHz to 10th harmonic:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW see note 1 with Peak Detector for Average Value.
Note 1: For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause Duty Cycle.

Test Mode

Please refer to the clause 2.4.

Test Result


9 kHz~30 MHz

From 9 kHz to 30 MHz: The conclusion is PASS.

- Note: 1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Pre-scan all antenna, only show the test data for worse case antenna on the test report.

30MHz-1GHz

Ant. No.	Ant 1
Ant. Pol.	Horizontal
Test Mode:	TX 802.11a Mode 5180MHz (U-NII-1)
Remark:	Only worse case is reported.




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	34.6385	40.31	-18.68	21.63	40.00	-18.37	QP
2	143.3260	40.98	-17.88	23.10	43.50	-20.40	QP
3 *	226.0994	56.63	-19.84	36.79	46.00	-9.21	QP
4	299.3158	52.09	-16.78	35.31	46.00	-10.69	QP
5	324.4560	51.60	-16.36	35.24	46.00	-10.76	QP
6	406.0880	45.92	-14.50	31.42	46.00	-14.58	QP

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor

2. Margin value = Level - Limit value

Ant. No.	Ant 1
Ant. Pol.	Vertical
Test Mode:	TX 802.11a Mode 5180MHz (U-NII-1)
Remark:	Only worse case is reported.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	34.6385	52.90	-18.68	34.22	40.00	-5.78	QP
2	144.3348	44.26	-17.83	26.43	43.50	-17.07	QP
3	226.0994	56.63	-19.84	36.79	46.00	-9.21	QP
4	299.3158	52.09	-16.78	35.31	46.00	-10.69	QP
5	408.9460	46.12	-14.41	31.71	46.00	-14.29	QP
6	900.1474	35.88	-4.82	31.06	46.00	-14.94	QP

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2. Margin value = Level -Limit value

Above 1GHz

Ant. No.	Ant 1																														
Ant. Pol.	Horizontal																														
Test Mode:	TX 802.11a Mode 5180MHz (U-NII-1)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBUV)</td><td>Factor (dB/m)</td><td>Level (dBUV/m)</td><td>Limit (dBUV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1 *</td><td>10359.583</td><td>23.07</td><td>12.64</td><td>35.71</td><td>54.00</td><td>-18.29</td><td>AVG</td></tr><tr><td>2</td><td>10359.955</td><td>37.49</td><td>12.64</td><td>50.13</td><td>74.00</td><td>-23.87</td><td>peak</td></tr></table>								No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	1 *	10359.583	23.07	12.64	35.71	54.00	-18.29	AVG	2	10359.955	37.49	12.64	50.13	74.00	-23.87	peak
No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector																								
1 *	10359.583	23.07	12.64	35.71	54.00	-18.29	AVG																								
2	10359.955	37.49	12.64	50.13	74.00	-23.87	peak																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11a Mode 5180MHz (U-NII-1)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						

Ant. No.	Ant 1																														
Ant. Pol.	Horizontal																														
Test Mode:	TX 802.11a Mode 5200MHz (U-NII-1)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr><tr><td>1</td><td>10399.122</td><td>38.02</td><td>12.69</td><td>50.71</td><td>74.00</td><td>-23.29</td><td>peak</td></tr><tr><td>2 *</td><td>10400.597</td><td>23.80</td><td>12.69</td><td>36.49</td><td>54.00</td><td>-17.51</td><td>AVG</td></tr></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10399.122	38.02	12.69	50.71	74.00	-23.29	peak	2 *	10400.597	23.80	12.69	36.49	54.00	-17.51	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10399.122	38.02	12.69	50.71	74.00	-23.29	peak																								
2 *	10400.597	23.80	12.69	36.49	54.00	-17.51	AVG																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11a Mode 5200MHz (U-NII-1)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						

Ant. No.	Ant 1																														
Ant. Pol.	Horizontal																														
Test Mode:	TX 802.11a Mode 5240MHz (U-NII-1)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr><tr><td>1 *</td><td>10479.085</td><td>24.04</td><td>12.80</td><td>36.84</td><td>54.00</td><td>-17.16</td><td>AVG</td></tr><tr><td>2</td><td>10480.478</td><td>39.42</td><td>12.80</td><td>52.22</td><td>74.00</td><td>-21.78</td><td>peak</td></tr></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10479.085	24.04	12.80	36.84	54.00	-17.16	AVG	2	10480.478	39.42	12.80	52.22	74.00	-21.78	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10479.085	24.04	12.80	36.84	54.00	-17.16	AVG																								
2	10480.478	39.42	12.80	52.22	74.00	-21.78	peak																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11a Mode 5240MHz (U-NII-1)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						

Ant. No.	Ant 1																														
Ant. Pol.	Horizontal																														
Test Mode:	TX 802.11n(HT20) Mode 5180MHz (U-NII-1)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBUV)</td><td>Factor (dB/m)</td><td>Level (dBUV/m)</td><td>Limit (dBUV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1</td><td>10360.497</td><td>38.40</td><td>12.64</td><td>51.04</td><td>74.00</td><td>-22.96</td><td>peak</td></tr><tr><td>2 *</td><td>10360.595</td><td>23.89</td><td>12.64</td><td>36.53</td><td>54.00</td><td>-17.47</td><td>AVG</td></tr></table>								No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	1	10360.497	38.40	12.64	51.04	74.00	-22.96	peak	2 *	10360.595	23.89	12.64	36.53	54.00	-17.47	AVG
No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector																								
1	10360.497	38.40	12.64	51.04	74.00	-22.96	peak																								
2 *	10360.595	23.89	12.64	36.53	54.00	-17.47	AVG																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11n(HT20) Mode 5180MHz (U-NII-1)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						
</							

Ant. No.	Ant 1																														
Ant. Pol.	Horizontal																														
Test Mode:	TX 802.11n(HT20) Mode 5200MHz (U-NII-1)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBUV)</td><td>Factor (dB/m)</td><td>Level (dBUV/m)</td><td>Limit (dBUV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1</td><td>10399.147</td><td>38.70</td><td>12.69</td><td>51.39</td><td>74.00</td><td>-22.61</td><td>peak</td></tr><tr><td>2 *</td><td>10399.429</td><td>23.90</td><td>12.69</td><td>36.59</td><td>54.00</td><td>-17.41</td><td>AVG</td></tr></table>								No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	1	10399.147	38.70	12.69	51.39	74.00	-22.61	peak	2 *	10399.429	23.90	12.69	36.59	54.00	-17.41	AVG
No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector																								
1	10399.147	38.70	12.69	51.39	74.00	-22.61	peak																								
2 *	10399.429	23.90	12.69	36.59	54.00	-17.41	AVG																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1																														
Ant. Pol.	Vertical																														
Test Mode:	TX 802.11n(HT20) Mode 5200MHz (U-NII-1)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBUV)</td><td>Factor (dB/m)</td><td>Level (dBUV/m)</td><td>Limit (dBUV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1</td><td>10399.049</td><td>39.09</td><td>12.69</td><td>51.78</td><td>74.00</td><td>-22.22</td><td>peak</td></tr><tr><td>2 *</td><td>10400.301</td><td>23.89</td><td>12.69</td><td>36.58</td><td>54.00</td><td>-17.42</td><td>AVG</td></tr></table>								No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	1	10399.049	39.09	12.69	51.78	74.00	-22.22	peak	2 *	10400.301	23.89	12.69	36.58	54.00	-17.42	AVG
No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector																								
1	10399.049	39.09	12.69	51.78	74.00	-22.22	peak																								
2 *	10400.301	23.89	12.69	36.58	54.00	-17.42	AVG																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1						
Ant. Pol.	Horizontal						
Test Mode:	TX 802.11n(HT20) Mode 5240MHz (U-NII-1)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						

Ant. No.	Ant 1						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11n(HT20) Mode 5240MHz (U-NII-1)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						

Ant. No.	Ant 1						
Ant. Pol.	Horizontal						
Test Mode:	TX 802.11n(HT40) Mode 5190MHz (U-NII-1)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						

Ant. No.	Ant 1																														
Ant. Pol.	Vertical																														
Test Mode:	TX 802.11n(HT40) Mode 5190MHz (U-NII-1)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBuV)</td><td>Factor (dB/m)</td><td>Level (dBuV/m)</td><td>Limit (dBuV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1 *</td><td>10379.819</td><td>24.39</td><td>12.67</td><td>37.06</td><td>54.00</td><td>-16.94</td><td>AVG</td></tr><tr><td>2</td><td>10380.669</td><td>38.40</td><td>12.67</td><td>51.07</td><td>74.00</td><td>-22.93</td><td>peak</td></tr></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10379.819	24.39	12.67	37.06	54.00	-16.94	AVG	2	10380.669	38.40	12.67	51.07	74.00	-22.93	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10379.819	24.39	12.67	37.06	54.00	-16.94	AVG																								
2	10380.669	38.40	12.67	51.07	74.00	-22.93	peak																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1						
Ant. Pol.	Horizontal						
Test Mode:	TX 802.11n(HT40) Mode 5230MHz (U-NII-1)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						

Ant. No.	Ant 1																														
Ant. Pol.	Vertical																														
Test Mode:	TX 802.11n(HT40) Mode 5230MHz (U-NII-1)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBuV)</td><td>Factor (dB/m)</td><td>Level (dBuV/m)</td><td>Limit (dBuV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1 *</td><td>10460.521</td><td>24.97</td><td>12.77</td><td>37.74</td><td>54.00</td><td>-16.26</td><td>AVG</td></tr><tr><td>2</td><td>10460.671</td><td>38.27</td><td>12.77</td><td>51.04</td><td>74.00</td><td>-22.96</td><td>peak</td></tr></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10460.521	24.97	12.77	37.74	54.00	-16.26	AVG	2	10460.671	38.27	12.77	51.04	74.00	-22.96	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10460.521	24.97	12.77	37.74	54.00	-16.26	AVG																								
2	10460.671	38.27	12.77	51.04	74.00	-22.96	peak																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1																														
Ant. Pol.	Horizontal																														
Test Mode:	TX 802.11ac(VHT80) Mode 5210MHz (U-NII-1)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr><tr><td>1</td><td>10419.387</td><td>38.79</td><td>12.71</td><td>51.50</td><td>74.00</td><td>-22.50</td><td>peak</td></tr><tr><td>2 *</td><td>10419.866</td><td>25.96</td><td>12.71</td><td>38.67</td><td>54.00</td><td>-15.33</td><td>AVG</td></tr></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10419.387	38.79	12.71	51.50	74.00	-22.50	peak	2 *	10419.866	25.96	12.71	38.67	54.00	-15.33	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10419.387	38.79	12.71	51.50	74.00	-22.50	peak																								
2 *	10419.866	25.96	12.71	38.67	54.00	-15.33	AVG																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11ac(VHT80) Mode 5210MHz (U-NII-1)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						

Ant. No.	Ant 1						
Ant. Pol.	Horizontal						
Test Mode:	TX 802.11a Mode 5745MHz (U-NII-3)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						

Ant. No.	Ant 1
Ant. Pol.	Vertical
Test Mode:	TX 802.11a Mode 5745MHz (U-NII-3)
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector
1	10359.922	40.67	12.64	53.31	74.00	-20.69	peak
2 *	10360.969	23.89	12.64	36.53	54.00	-17.47	AVG

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value

Ant. No.	Ant 1						
Ant. Pol.	Horizontal						
Test Mode:	TX 802.11a Mode 5785MHz (U-NII-3)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						

Ant. No.	Ant 1																														
Ant. Pol.	Vertical																														
Test Mode:	TX 802.11a Mode 5785MHz (U-NII-3)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBUV)</td><td>Factor (dB/m)</td><td>Level (dBUV/m)</td><td>Limit (dBUV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1</td><td>11569.272</td><td>39.66</td><td>14.01</td><td>53.67</td><td>74.00</td><td>-20.33</td><td>peak</td></tr><tr><td>2 *</td><td>11569.462</td><td>24.13</td><td>14.01</td><td>38.14</td><td>54.00</td><td>-15.86</td><td>AVG</td></tr></table>								No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	1	11569.272	39.66	14.01	53.67	74.00	-20.33	peak	2 *	11569.462	24.13	14.01	38.14	54.00	-15.86	AVG
No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector																								
1	11569.272	39.66	14.01	53.67	74.00	-20.33	peak																								
2 *	11569.462	24.13	14.01	38.14	54.00	-15.86	AVG																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1																														
Ant. Pol.	Horizontal																														
Test Mode:	TX 802.11a Mode 5825MHz (U-NII-3)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBUV)</td><td>Factor (dB/m)</td><td>Level (dBUV/m)</td><td>Limit (dBUV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1</td><td>11649.079</td><td>39.33</td><td>13.98</td><td>53.31</td><td>74.00</td><td>-20.69</td><td>peak</td></tr><tr><td>2 *</td><td>11649.616</td><td>23.87</td><td>13.98</td><td>37.85</td><td>54.00</td><td>-16.15</td><td>AVG</td></tr></table>								No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	1	11649.079	39.33	13.98	53.31	74.00	-20.69	peak	2 *	11649.616	23.87	13.98	37.85	54.00	-16.15	AVG
No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector																								
1	11649.079	39.33	13.98	53.31	74.00	-20.69	peak																								
2 *	11649.616	23.87	13.98	37.85	54.00	-16.15	AVG																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1																														
Ant. Pol.	Vertical																														
Test Mode:	TX 802.11a Mode 5825MHz (U-NII-3)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBUV)</td><td>Factor (dB/m)</td><td>Level (dBUV/m)</td><td>Limit (dBUV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1</td><td>11650.819</td><td>39.19</td><td>14.00</td><td>53.19</td><td>74.00</td><td>-20.81</td><td>peak</td></tr><tr><td>2 *</td><td>11650.819</td><td>21.68</td><td>14.00</td><td>35.68</td><td>54.00</td><td>-18.32</td><td>AVG</td></tr></table>								No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	1	11650.819	39.19	14.00	53.19	74.00	-20.81	peak	2 *	11650.819	21.68	14.00	35.68	54.00	-18.32	AVG
No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector																								
1	11650.819	39.19	14.00	53.19	74.00	-20.81	peak																								
2 *	11650.819	21.68	14.00	35.68	54.00	-18.32	AVG																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1																														
Ant. Pol.	Horizontal																														
Test Mode:	TX 802.11n(HT20) Mode 5745MHz (U-NII-3)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBUV)</td><td>Factor (dB/m)</td><td>Level (dBUV/m)</td><td>Limit (dBUV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1</td><td>11490.129</td><td>37.08</td><td>13.96</td><td>51.04</td><td>74.00</td><td>-22.96</td><td>peak</td></tr><tr><td>2 *</td><td>11490.654</td><td>22.57</td><td>13.96</td><td>36.53</td><td>54.00</td><td>-17.47</td><td>AVG</td></tr></table>								No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	1	11490.129	37.08	13.96	51.04	74.00	-22.96	peak	2 *	11490.654	22.57	13.96	36.53	54.00	-17.47	AVG
No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector																								
1	11490.129	37.08	13.96	51.04	74.00	-22.96	peak																								
2 *	11490.654	22.57	13.96	36.53	54.00	-17.47	AVG																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11n(HT20) Mode 5745MHz (U-NII-3)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						

Ant. No.	Ant 1																														
Ant. Pol.	Horizontal																														
Test Mode:	TX 802.11n(HT20) Mode 5785MHz (U-NII-3)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBUV)</td><td>Factor (dB/m)</td><td>Level (dBUV/m)</td><td>Limit (dBUV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1</td><td>11570.331</td><td>39.81</td><td>14.01</td><td>53.82</td><td>74.00</td><td>-20.18</td><td>peak</td></tr><tr><td>2 *</td><td>11570.903</td><td>24.64</td><td>14.01</td><td>38.65</td><td>54.00</td><td>-15.35</td><td>AVG</td></tr></table>								No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	1	11570.331	39.81	14.01	53.82	74.00	-20.18	peak	2 *	11570.903	24.64	14.01	38.65	54.00	-15.35	AVG
No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector																								
1	11570.331	39.81	14.01	53.82	74.00	-20.18	peak																								
2 *	11570.903	24.64	14.01	38.65	54.00	-15.35	AVG																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11n(HT20) Mode 5785MHz (U-NII-3)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						

Ant. No.	Ant 1																														
Ant. Pol.	Horizontal																														
Test Mode:	TX 802.11n(HT20) Mode 5825MHz (U-NII-3)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBUV)</td><td>Factor (dB/m)</td><td>Level (dBUV/m)</td><td>Limit (dBUV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1 *</td><td>11650.489</td><td>24.14</td><td>14.00</td><td>38.14</td><td>54.00</td><td>-15.86</td><td>AVG</td></tr><tr><td>2</td><td>11650.853</td><td>38.85</td><td>14.00</td><td>52.85</td><td>74.00</td><td>-21.15</td><td>peak</td></tr></table>								No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	1 *	11650.489	24.14	14.00	38.14	54.00	-15.86	AVG	2	11650.853	38.85	14.00	52.85	74.00	-21.15	peak
No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector																								
1 *	11650.489	24.14	14.00	38.14	54.00	-15.86	AVG																								
2	11650.853	38.85	14.00	52.85	74.00	-21.15	peak																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1																														
Ant. Pol.	Vertical																														
Test Mode:	TX 802.11n(HT20) Mode 5825MHz (U-NII-3)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBUV)</td><td>Factor (dB/m)</td><td>Level (dBUV/m)</td><td>Limit (dBUV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1 *</td><td>11649.483</td><td>24.07</td><td>13.98</td><td>38.05</td><td>54.00</td><td>-15.95</td><td>AVG</td></tr><tr><td>2</td><td>11649.617</td><td>38.41</td><td>13.98</td><td>52.39</td><td>74.00</td><td>-21.61</td><td>peak</td></tr></table>								No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	1 *	11649.483	24.07	13.98	38.05	54.00	-15.95	AVG	2	11649.617	38.41	13.98	52.39	74.00	-21.61	peak
No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector																								
1 *	11649.483	24.07	13.98	38.05	54.00	-15.95	AVG																								
2	11649.617	38.41	13.98	52.39	74.00	-21.61	peak																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1						
Ant. Pol.	Horizontal						
Test Mode:	TX 802.11n(HT40) Mode 5755MHz (U-NII-3)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						

Ant. No.	Ant 1																														
Ant. Pol.	Vertical																														
Test Mode:	TX 802.11n(HT40) Mode 5755MHz (U-NII-3)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBUV)</td><td>Factor (dB/m)</td><td>Level (dBUV/m)</td><td>Limit (dBUV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1</td><td>11510.107</td><td>39.36</td><td>13.99</td><td>53.35</td><td>74.00</td><td>-20.65</td><td>peak</td></tr><tr><td>2 *</td><td>11510.163</td><td>24.05</td><td>13.99</td><td>38.04</td><td>54.00</td><td>-15.96</td><td>AVG</td></tr></table>								No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	1	11510.107	39.36	13.99	53.35	74.00	-20.65	peak	2 *	11510.163	24.05	13.99	38.04	54.00	-15.96	AVG
No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector																								
1	11510.107	39.36	13.99	53.35	74.00	-20.65	peak																								
2 *	11510.163	24.05	13.99	38.04	54.00	-15.96	AVG																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1						
Ant. Pol.	Horizontal						
Test Mode:	TX 802.11n(HT40) Mode 5795MHz (U-NII-3)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						
</							

Ant. No.	Ant 1						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11n(HT40) Mode 5795MHz (U-NII-3)						
Remark:	No report for the emission which more than 20 dB below the prescribed limit.						

Ant. No.	Ant 1																														
Ant. Pol.	Horizontal																														
Test Mode:	TX 802.11ac(VHT80) Mode 5775MHz (U-NII-3)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBuV)</td><td>Factor (dB/m)</td><td>Level (dBuV/m)</td><td>Limit (dBuV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1</td><td>11549.389</td><td>39.73</td><td>13.99</td><td>53.72</td><td>74.00</td><td>-20.28</td><td>peak</td></tr><tr><td>2 *</td><td>11550.361</td><td>24.09</td><td>14.01</td><td>38.10</td><td>54.00</td><td>-15.90</td><td>AVG</td></tr></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11549.389	39.73	13.99	53.72	74.00	-20.28	peak	2 *	11550.361	24.09	14.01	38.10	54.00	-15.90	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11549.389	39.73	13.99	53.72	74.00	-20.28	peak																								
2 *	11550.361	24.09	14.01	38.10	54.00	-15.90	AVG																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

Ant. No.	Ant 1																														
Ant. Pol.	Vertical																														
Test Mode:	TX 802.11ac(VHT80) Mode 5775MHz (U-NII-3)																														
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																														
<table><tr><td>No.</td><td>Frequency (MHz)</td><td>Reading (dBUV)</td><td>Factor (dB/m)</td><td>Level (dBUV/m)</td><td>Limit (dBUV/m)</td><td>Margin (dB)</td><td>Detector</td></tr><tr><td>1 *</td><td>11550.671</td><td>24.39</td><td>14.01</td><td>38.40</td><td>54.00</td><td>-15.60</td><td>AVG</td></tr><tr><td>2</td><td>11550.744</td><td>39.43</td><td>14.01</td><td>53.44</td><td>74.00</td><td>-20.56</td><td>peak</td></tr></table>								No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	1 *	11550.671	24.39	14.01	38.40	54.00	-15.60	AVG	2	11550.744	39.43	14.01	53.44	74.00	-20.56	peak
No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector																								
1 *	11550.671	24.39	14.01	38.40	54.00	-15.60	AVG																								
2	11550.744	39.43	14.01	53.44	74.00	-20.56	peak																								
Remarks: 1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2.Margin value = Level -Limit value																															

3.2. Band Edge Emissions

Limit

Limits of unwanted emission out of the restricted bands

FCC CFR Title 47 Part 15 Subpart E Section 15. 407(b)

Frequency (MHz)	EIRP Limits (dBm)	Equivalent Field Strength at 3m (dBμV/m)
5150~5250	-27	68.2
5250~5350	-27	68.2
5470~5725	-27	68.2
5725~5825	-27 (Note 2)	68.2
	10 (Note 2)	105.2
	15.6 (Note 2)	110.8
	27 (Note 2)	122.2


Note:

1. The following formula is used to convert the equipment isotropic radiated power (eirp) to field

strength: $E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m}$, where P is the eirp (Watts).

2. According to FCC 16-24, all emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

Test Configuration



Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2020 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2020 on radiated measurement.
5. The receiver set as follow:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW see note 1 with Peak Detector for Average Value.


Note 1: For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause Duty Cycle.


Test Mode


Please refer to the clause 2.4.


Test Result


Note: 1. Pre-scan both 4500-5150MHz were investigated, report only shows the test data for worst case.
 2. Pre-scan all antenna, only show the test data for worse case antenna on the test report.



























Ant. No.	Ant 1
Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT40) Mode 5230MHz (U-NII-1)





No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.000	13.01	36.27	49.28	74.00	-24.72	peak
2 *	5350.000	3.70	36.27	39.97	54.00	-14.03	AVG


Remarks:


1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor


2. Margin value = Level - Limit value
















































3.3. Bandwidth

Limit

FCC CFR Title 47 Part 15 Subpart E Section 15.407(a) & (e)

Test Item	Limit	Frequency Range (MHz)
26dB Bandwidth& 99% Bandwidth	N/A	5150~5250
		5250~5350
		5500~5700
6 dB Bandwidth	≥500 kHz	5725~5850

Test Configuration



Test Procedure

Please refer to KDB789033 D02 for the measurement methods.

The setting of the spectrum analyzer as below:

26dB Bandwidth Test	
Spectrum Parameters	Setting
Attenuation	Auto
Span	>26 dB Bandwidth
RBW	Approximately 1% of the emission bandwidth
VBW	>RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

6dB Bandwidth Test	
Spectrum Parameters	Setting
Attenuation	Auto
Span	>6 dB Bandwidth
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth Test	
Spectrum Parameters	Setting
Attenuation	Auto
RBW	1% to 5% of the OBW
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold

NOTE: The EUT was set to continuously transmitting in each mode and low, middle and high channel for the test.

Test Mode


Please refer to the clause 2.4.

Test Result**26dB Bandwidth & 99% Bandwidth**

TestMode	Antenna	Freq(MHz)	26db EBW [MHz]	OCB [MHz]
11A	Ant1	5180	22.00	16.983
	Ant1	5200	21.24	16.743
	Ant1	5240	29.48	17.223
	Ant1	5745	22.04	17.023
	Ant1	5785	21.80	16.703
	Ant1	5825	21.76	16.903
11N20SISO	Ant1	5180	22.28	17.822
	Ant1	5200	22.16	17.902
	Ant1	5240	29.28	18.262
	Ant1	5745	22.56	18.022
	Ant1	5785	22.00	17.942
11N40SISO	Ant1	5825	21.96	17.982
	Ant1	5190	41.52	36.444
	Ant1	5230	42.40	36.603
	Ant1	5755	42.48	36.444
11AC20SISO	Ant1	5795	42.32	36.763
	Ant1	5180	21.44	17.942
	Ant1	5200	21.36	17.902
	Ant1	5240	21.76	17.982
	Ant1	5745	22.44	18.062
	Ant1	5785	21.84	18.022
11AC40SISO	Ant1	5825	21.92	17.822
	Ant1	5190	41.44	36.444
	Ant1	5230	42.72	36.603
	Ant1	5755	42.40	36.523
11AC80SISO	Ant1	5795	42.24	36.523
	Ant1	5210	82.56	75.924
	Ant1	5775	83.68	75.764

6dB Bandwidth

TestMode	Antenna	Freq(MHz)	6db EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5745	16.40	5736.84	5753.24	0.5	PASS
	Ant1	5785	16.36	5776.84	5793.20	0.5	PASS
	Ant1	5825	16.36	5816.84	5833.20	0.5	PASS
11N20SISO	Ant1	5745	17.56	5736.24	5753.80	0.5	PASS
	Ant1	5785	17.60	5776.20	5793.80	0.5	PASS
	Ant1	5825	17.60	5816.20	5833.80	0.5	PASS
11N40SISO	Ant1	5755	36.32	5736.84	5773.16	0.5	PASS
	Ant1	5795	36.40	5776.84	5813.24	0.5	PASS
11AC20SISO	Ant1	5745	17.56	5736.24	5753.80	0.5	PASS
	Ant1	5785	15.96	5776.64	5792.60	0.5	PASS
	Ant1	5825	17.60	5816.20	5833.80	0.5	PASS
11AC40SISO	Ant1	5755	36.32	5736.84	5773.16	0.5	PASS
	Ant1	5795	36.32	5776.84	5813.16	0.5	PASS
11AC80SISO	Ant1	5775	75.36	5737.24	5812.60	0.5	PASS

26dB Bandwidth:

CTC Laboratories, Inc.

Room 107, 108, 207, 208 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China


Tel.: (86)755-27521059

Fax: (86)755-27521011


Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A5


Master TRF : Dated 2026-06-01




11A_Ant1_5785




11A_Ant1_5825




11N20SISO_Ant1_5180




11N20SISO_Ant1_5200




11N20SISO_Ant1_5240




11N20SISO_Ant1_5745



11N20SISO_Ant1_5785



11N20SISO_Ant1_5825




11N40SISO_Ant1_5190

CTC Laboratories, Inc.


Room 107, 108, 207, 208 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A5


Master TRF : Dated 2026-06-01




11N40SISO_Ant1_5230




11N40SISO_Ant1_5755




11N40SISO_Ant1_5795




11AC20SISO_Ant1_5180




11AC20SISO_Ant1_5200




11AC20SISO_Ant1_5240



11AC20SISO_Ant1_5745



11AC20SISO_Ant1_5785




11AC20SISO_Ant1_5825

CTC Laboratories, Inc.


Room 107, 108, 207, 208 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A5


Master TRF : Dated 2026-06-01




11AC40SISO_Ant1_5190




11AC40SISO_Ant1_5230




11AC40SISO_Ant1_5755







11AC40SISO_Ant1_5795




11AC80SISO_Ant1_5210




11AC80SISO_Ant1_5775


**99% Bandwidth:**




11A_Ant1_5745




11A_Ant1_5785




11A_Ant1_5825




11N20SISO_Ant1_5180




11N20SISO_Ant1_5200




11N20SISO_Ant1_5240




11N20SISO_Ant1_5745




11N20SISO_Ant1_5785




11N20SISO_Ant1_5825




11N40SISO_Ant1_5190




11N40SISO_Ant1_5230




11N40SISO_Ant1_5755



11N40SISO_Ant1_5795



11AC20SISO_Ant1_5180



11AC20SISO_Ant1_5200

CTC Laboratories, Inc.

Room 107, 108, 207, 208 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-062_A5

Master TRF : Dated 2026-06-01