

FCC ID: WY7-0WG1

To whom it may concern,

We, UL Japan, Inc, hereby declare that Multi-purpose Switch: SW-UT600 (FCC ID: WY7-0WG1 of SHIMANO INC. is exempt from RF exposure SAR evaluation because the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula according to the Code of Federal Regulation title 47 section 1.1307(b)(3)(i)(B). This method is used at separation distances d (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive) for single RF sources. P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d / 20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$$

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

When the minimum separation distance is shorter than 0.5 cm, 0.5 cm is applied.

The SAR evaluation exemption threshold is calculated as below.

[SHIMANO ORIGINAL part]

P_{th} (mW) *1)	2.71
f (GHz)	2.478
$ERP_{20 \text{ cm}}$ (mW)	3060
d (cm)	0.50

Conducted Power (dBm)	6.00
(mW)	3.98
Antenna Gain (dBi)	0.96
EIRP (dBm)	6.96
ERP (dBm)	4.82
(mW)	3.03

*1) Since this device is used with only limbs, multiplying 2.71 mW by 2.5 yields 6.78 mW is applied as extremity SAR test exclusion.

The Maximum time-averaged power or ERP whichever greater is 4 mW.
(Rounded up to two decimals place)

[Bluetooth Low Energy part]

P_{th} (mW) *1)	2.71
f (GHz)	2.48
$ERP_{20\text{ cm}}$ (mW)	3060
d (cm)	0.50

Conducted Power (dBm)	6.00
(mW)	3.98
Antenna Gain (dBi)	1.86
EIRP (dBm)	7.86
ERP (dBm)	5.72
(mW)	3.73

*1) Since this device is used with only limbs, multiplying 2.71 mW by 2.5 yields 6.78 mW is applied as extremity SAR test exclusion.

The Maximum time-averaged power or ERP whichever greater is 4 mW.
(Rounded up to two decimals place)

Thank you for your attention to this matter.



Takayuki Shimada
Leader