

# FCC TEST REPORT

## (Part 15, Subpart C)

|            |                                                                     |
|------------|---------------------------------------------------------------------|
| Applicant: | Sonim Technologies, Inc.                                            |
| Address:   | 6836 Bee Cave Road, Building 1, Suite 279, Austin, Texas 78746, USA |

|                           |                                                                                                                      |
|---------------------------|----------------------------------------------------------------------------------------------------------------------|
| Manufacturer or Supplier: | Sonim Technologies (Shenzhen) Limited                                                                                |
| Address:                  | 2nd Floor, No. 2 Building Phase B, Daqian Industrial park, Longchang Road, 67 District, Baoan, Shenzhen, P. R. China |
| Product:                  | Mobile Phone                                                                                                         |
| Brand Name:               | Sonim                                                                                                                |
| Model Name:               | XP8800                                                                                                               |
| FCC ID:                   | WYPPG4032                                                                                                            |
| Date of tests:            | Jul. 01, 2020 ~ Jul. 08, 2020                                                                                        |

The tests have been carried out according to the requirements of the following standard:

- ☒ **FCC Part 15, Subpart C, Section 15.247**
- ☒ **ANSI C63.10-2013**

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

|                                                                                                            |                                                                                                              |
|------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Prepared by Alex Chen<br>Engineer / Mobile Department                                                      | Approved by Luke Lu<br>Manager / Mobile Department                                                           |
| <br>Date: Jul. 23, 2020 | <br>Date: Jul. 23, 2020 |

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



## TABLE OF CONTENTS

|                                                                                                  |           |
|--------------------------------------------------------------------------------------------------|-----------|
| RELEASE CONTROL RECORD.....                                                                      | 3         |
| <b>1 SUMMARY OF TEST RESULTS.....</b>                                                            | <b>4</b>  |
| <b>1.1 MEASUREMENT UNCERTAINTY.....</b>                                                          | <b>5</b>  |
| <b>2 GENERAL INFORMATION.....</b>                                                                | <b>5</b>  |
| <b>2.1 GENERAL DESCRIPTION OF EUT.....</b>                                                       | <b>5</b>  |
| <b>2.2 DESCRIPTION OF TEST MODES.....</b>                                                        | <b>8</b>  |
| 2.2.1 CONFIGURATION OF SYSTEM UNDER TEST.....                                                    | 9         |
| 2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....                                     | 9         |
| <b>2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS.....</b>                                         | <b>11</b> |
| <b>2.4 DESCRIPTION OF SUPPORT UNITS.....</b>                                                     | <b>11</b> |
| <b>3 TEST TYPES AND RESULTS.....</b>                                                             | <b>12</b> |
| <b>3.1 CONDUCTED EMISSION MEASUREMENT.....</b>                                                   | <b>12</b> |
| 3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT.....                                              | 12        |
| 3.1.2 TEST INSTRUMENTS.....                                                                      | 12        |
| 3.1.3 TEST PROCEDURES.....                                                                       | 12        |
| 3.1.4 DEVIATION FROM TEST STANDARD.....                                                          | 13        |
| 3.1.5 TEST SETUP.....                                                                            | 13        |
| 3.1.6 EUT OPERATING CONDITIONS.....                                                              | 13        |
| 3.1.7 TEST RESULTS.....                                                                          | 14        |
| <b>3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT.....</b>                                       | <b>16</b> |
| 3.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT.....                                  | 16        |
| 3.2.2 TEST INSTRUMENTS.....                                                                      | 17        |
| 3.2.3 TEST PROCEDURES.....                                                                       | 18        |
| 3.2.4 DEVIATION FROM TEST STANDARD.....                                                          | 18        |
| 3.2.5 TEST SETUP.....                                                                            | 18        |
| 3.2.6 EUT OPERATING CONDITIONS.....                                                              | 20        |
| 3.2.7 TEST RESULTS.....                                                                          | 21        |
| <b>4 PHOTOGRAPHS OF THE TEST CONFIGURATION.....</b>                                              | <b>24</b> |
| <b>5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....</b> | <b>25</b> |



Test Report No.: RF200702W001-1

## RELEASE CONTROL RECORD

| ISSUE NO.      | REASON FOR CHANGE                                                                                                             | DATE ISSUED   |
|----------------|-------------------------------------------------------------------------------------------------------------------------------|---------------|
| RF170730W002-1 | Original release                                                                                                              | Nov. 23, 2017 |
| RF171201W001-1 | Based on the original report RF170730W002-1 disable CDMA function.                                                            | Dec. 11, 2017 |
| RF200702W001-1 | Based on the original report RF171201W001-1 add a new charger, update SW version, change the address and add two type numbers | Jul. 23, 2020 |



**BUREAU  
VERITAS**

Test Report No.: RF200702W001-1

## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part 15, Subpart C |                                                                                                               |            |                                |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------|------------|--------------------------------|
| STANDARD                                 | TEST TYPE AND LIMIT                                                                                           | RESULT     | REMARK                         |
| 15.207                                   | AC Power Conducted Emission                                                                                   | Compliance | Meet the requirement of limit. |
| 15.247(a)(1)(iii)                        | Number of Hopping Frequency Used                                                                              | N.A        | See note 1                     |
| 15.247(a)(1)(iii)                        | Dwell Time on Each Channel                                                                                    | N.A        | See note 1                     |
| 15.247(a)(1)                             | 1. Hopping Channel Separation<br>2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System | N.A        | See note 1                     |
| 15.247(b)                                | Maximum Peak Output Power                                                                                     | N.A        | See note 1                     |
| 15.247(d)&15.209                         | Transmitter Radiated Emissions                                                                                | Compliance | Meet the requirement of limit. |
| 15.247(d)                                | Out of band Measurement                                                                                       | N.A        | See note 1                     |
| 15.203                                   | Antenna Requirement                                                                                           | N.A        | See note 1                     |

\* Refer to KDB 971168 D01 Power Meas License Digital Systems v03r01.

Note:

1. Per the change notice provide by manufactory, the difference is add a new charger and two type numbers, and change the address and SW version, all the change no effect any RF parameter, Therefore only verify the radiated emission and the AC Power Conducted emission, and show the verify test data on this report.

## 1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| MEASUREMENT                         | UNCERTAINTY           |
|-------------------------------------|-----------------------|
| AC Power Conducted emissions        | $\pm 2.70\text{dB}$   |
| Radiated emissions (30MHz~1GMHz)    | $\pm 4.98\text{dB}$   |
| Radiated emissions (1GMHz ~6GMHz)   | $\pm 4.70\text{dB}$   |
| Radiated emissions (6GMHz ~18GMHz)  | $\pm 4.60\text{dB}$   |
| Radiated emissions (18GMHz ~40GMHz) | $\pm 4.12\text{dB}$   |
| Conducted emissions                 | $\pm 4.01\text{dB}$   |
| Occupied Channel Bandwidth          | $\pm 43.58\text{KHz}$ |
| Conducted Output power              | $\pm 2.06\text{dB}$   |
| Power Spectral Density              | $\pm 0.85\text{ dB}$  |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

|                       |                                                                    |
|-----------------------|--------------------------------------------------------------------|
| PRODUCT               | Mobile Phone                                                       |
| MODEL NAME            | XP8800                                                             |
| TYPE NUMBER           | PG4032/PG4033/PG4034/PG4035/PG4012/PG4041/P<br>G4022/PG4011/PG4061 |
| POWER SUPPLY          | 5/9Vdc (adapter or host equipment)<br>3.85Vdc (Li-ion, battery)    |
| MODULATION TECHNOLOGY | FHSS                                                               |
| MODULATION TYPE       | GFSK, 8DPSK, $\pi/4$ DQPSK                                         |
| OPERATING FREQUENCY   | 2402MHz~2480MHz                                                    |
| NUMBER OF CHANNEL     | 79                                                                 |
| MAX. OUTPUT POWER     | 8.128mW (Max. Measured)                                            |
| ANTENNA TYPE          | PIFA Antenna with -1dBi gain                                       |
| HW VERSION            | A                                                                  |

**Test Report No.: RF200702W001-1****BUREAU**

|                       |                                                                                                   |
|-----------------------|---------------------------------------------------------------------------------------------------|
| <b>SW VERSION</b>     | 8A.0.0-00-10.0.0-00.34.01                                                                         |
| <b>I/O PORTS</b>      | Refer to user's manual                                                                            |
| <b>CABLE SUPPLIED</b> | USB cable 1: With shield, detachable, 1.5meter<br>USB cable 2: non-shielded, detachable, 1.0meter |

**NOTE:**

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT was powered by the following adapter:

| <b>ADAPTER 1</b> |                                                  |
|------------------|--------------------------------------------------|
| <b>BRAND:</b>    | Sonim                                            |
| <b>MODEL:</b>    | S42A02                                           |
| <b>INPUT:</b>    | AC 100-240V, 500mA                               |
| <b>OUTPUT:</b>   | DC 5V, 1500mA<br>DC 9V, 1500mA<br>DC 12V, 1100mA |

| <b>ADAPTER 2</b> |                    |
|------------------|--------------------|
| <b>BRAND:</b>    | Sonim              |
| <b>MODEL:</b>    | S84A02             |
| <b>INPUT:</b>    | AC 100-240V, 750mA |
| <b>OUTPUT:</b>   | DC 5V, 3000mA      |
|                  | DC 9V, 2220mA      |
|                  | DC 12V, 1670mA     |

3. The EUT matched the following USB cables:

| <b>USB CABLE 1</b>  |           |
|---------------------|-----------|
| <b>BRAND:</b>       | N/A       |
| <b>MODEL:</b>       | N/A       |
| <b>SIGNAL LINE:</b> | 1.5 METER |

| <b>USB CABLE 2</b>  |           |
|---------------------|-----------|
| <b>BRAND:</b>       | N/A       |
| <b>MODEL:</b>       | N/A       |
| <b>SIGNAL LINE:</b> | 1.0 METER |

4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

## 2.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

| CHANNEL | FREQ.<br>(MHz) | CHANNEL | FREQ.<br>(MHz) | CHANNEL | FREQ.<br>(MHz) | CHANNEL | FREQ.<br>(MHz) |
|---------|----------------|---------|----------------|---------|----------------|---------|----------------|
| 0       | 2402           | 20      | 2422           | 40      | 2442           | 60      | 2462           |
| 1       | 2403           | 21      | 2423           | 41      | 2443           | 61      | 2463           |
| 2       | 2404           | 22      | 2424           | 42      | 2444           | 62      | 2464           |
| 3       | 2405           | 23      | 2425           | 43      | 2445           | 63      | 2465           |
| 4       | 2406           | 24      | 2426           | 44      | 2446           | 64      | 2466           |
| 5       | 2407           | 25      | 2427           | 45      | 2447           | 65      | 2467           |
| 6       | 2408           | 26      | 2428           | 46      | 2448           | 66      | 2468           |
| 7       | 2409           | 27      | 2429           | 47      | 2449           | 67      | 2469           |
| 8       | 2410           | 28      | 2430           | 48      | 2450           | 68      | 2470           |
| 9       | 2411           | 29      | 2431           | 49      | 2451           | 69      | 2471           |
| 10      | 2412           | 30      | 2432           | 50      | 2452           | 70      | 2472           |
| 11      | 2413           | 31      | 2433           | 51      | 2453           | 71      | 2473           |
| 12      | 2414           | 32      | 2434           | 52      | 2454           | 72      | 2474           |
| 13      | 2415           | 33      | 2435           | 53      | 2455           | 73      | 2475           |
| 14      | 2416           | 34      | 2436           | 54      | 2456           | 74      | 2476           |
| 15      | 2417           | 35      | 2437           | 55      | 2457           | 75      | 2477           |
| 16      | 2418           | 36      | 2438           | 56      | 2458           | 76      | 2478           |
| 17      | 2419           | 37      | 2439           | 57      | 2459           | 77      | 2479           |
| 18      | 2420           | 38      | 2440           | 58      | 2460           | 78      | 2480           |
| 19      | 2421           | 39      | 2441           | 59      | 2461           |         |                |



**BUREAU  
VERITAS**

**Test Report No.: RF200702W001-1**

## 2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

## 2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on X axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

| EUT CONFIGURE<br>MODE | APPLICABLE TO |       |     |      | DESCRIPTION |
|-----------------------|---------------|-------|-----|------|-------------|
|                       | RE<1G         | RE≥1G | PLC | APCM |             |
| -                     | √             | -     | √   | -    | -           |

Where **RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission

**RE≥1G**: Radiated Emission above 1GHz  
**APCM**: Antenna Port Conducted Measurement

### RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE<br>MODE | AVAILABLE<br>CHANNEL | TESTED<br>CHANNEL | MODULATION<br>TECHNOLOGY | MODULATION<br>TYPE | PACKET<br>TYPE |
|-----------------------|----------------------|-------------------|--------------------------|--------------------|----------------|
| -                     | 0 to 78              | 78                | FHSS                     | GFSK               | DH5            |



**BUREAU  
VERITAS**

**Test Report No.: RF200702W001-1**

**POWER LINE CONDUCTED EMISSION TEST:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.

- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE<br>MODE | AVAILABLE<br>CHANNEL | TESTED<br>CHANNEL | MODULATION<br>TECHNOLOGY | MODULATION<br>TYPE | PACKET<br>TYPE |
|-----------------------|----------------------|-------------------|--------------------------|--------------------|----------------|
| -                     | 0 to 78              | 78                | FHSS                     | GFSK               | DH5            |

**TEST CONDITION:**

| APPLICABLE TO | ENVIRONMENTAL CONDITIONS | TEST VOLTAGE<br>(SYSTEM) | TESTED BY |
|---------------|--------------------------|--------------------------|-----------|
| RE<1G         | 23deg. C, 70%RH          | DC 5V/9V12V By Adapter   | Star Le   |
| PLC           | 25deg. C, 52%RH          | DC 5V/9V12V By Adapter   | Jocan Guo |

## 2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. Section 15.247**

**ANSI C63.10-2013**

- NOTE:**
1. All test items have been performed and recorded as per the above standards.
  2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

## 2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT | BRAND  | MODEL NO.     | SERIAL NO. | FCC ID |
|-----|---------|--------|---------------|------------|--------|
| 1   | Desktop | Lenovo | M73 SFF       | PC04GRQV   | N/A    |
| 2   | Desktop | Lenovo | M73 SFF       | PC06CS27   | N/A    |
| 3   | Laptop  | Lenovo | Thnikpad L440 | R90FTFKN   | N/A    |

| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS |
|-----|-----------------------------------------------------|
| 1   | AC Line: Unshielded, Detachable 1.5m                |
| 2   | AC Line: Unshielded, Detachable 1.5m                |
| 3   | AC Line: Unshielded, Detachable 1.5m                |



Test Report No.: RF200702W001-1

BUREAU  
VERITAS

### 3 TEST TYPES AND RESULTS

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

| FREQUENCY OF EMISSION (MHz) | CONDUCTED LIMIT (dB $\mu$ V) |          |
|-----------------------------|------------------------------|----------|
|                             | Quasi-peak                   | Average  |
| 0.15 ~ 0.5                  | 66 to 56                     | 56 to 46 |
| 0.5 ~ 5                     | 56                           | 46       |
| 5 ~ 30                      | 60                           | 50       |

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
  3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

##### 3.1.2 TEST INSTRUMENTS

| Equipment           | Manufacturer  | Model No. | Serial No. | Last Cal.  | Next Cal.  |
|---------------------|---------------|-----------|------------|------------|------------|
| EMI Test Receiver   | Rohde&Schwarz | ESR3      | 101900     | Feb. 26,20 | Feb. 25,21 |
| EMC32 test software | Rohde&Schwarz | EMC32     | NA         | NA         | NA         |
| LISN network        | Rohde&Schwarz | ENV216    | 101922     | Feb. 26,20 | Feb. 25,21 |

- NOTE:**
1. The test was performed in CE shielded room.
  2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

##### 3.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

### 3.1.4 DEVIATION FROM TEST STANDARD

No deviation.

### 3.1.5 TEST SETUP



**Note: 1. Support units were connected to second LISN.**

**2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.1.6 EUT OPERATING CONDITIONS

- Turned on the power and connected of all equipment.
- EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



BUREAU  
VERITAS

## Test Report No.: RF200702W001-1

### 3.1.7 TEST RESULTS


#### CONDUCTED WORST-CASE DATA:

|                 |                |                                          |                                       |
|-----------------|----------------|------------------------------------------|---------------------------------------|
| Frequency Range | 150KHz ~ 30MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9 kHz |
| Input Power     | 120Vac, 60Hz   | Environmental Conditions                 | 24deg. C, 55RH                        |
| Tested By       | Chase Zhou     | Test Date                                | 2020/07/06                            |

| Frequency (MHz) | QuasiPeak (dB $\mu$ V) | CAverage (dB $\mu$ V) | Limit (dB $\mu$ V) | Margin (dB) | Line | Filter | Corr. (dB) |
|-----------------|------------------------|-----------------------|--------------------|-------------|------|--------|------------|
| 0.150000        | ---                    | 38.43                 | 56.00              | -17.57      | L    | ON     | 9.7        |
| 0.150000        | 52.22                  | ---                   | 66.00              | -13.78      | L    | ON     | 9.7        |
| 0.216000        | ---                    | 29.16                 | 52.97              | -23.81      | L    | ON     | 9.7        |
| 0.216000        | 44.57                  | ---                   | 62.97              | -18.40      | L    | ON     | 9.7        |
| 0.512000        | ---                    | 28.92                 | 46.00              | -17.08      | L    | ON     | 9.7        |
| 0.512000        | 38.94                  | ---                   | 56.00              | -17.06      | L    | ON     | 9.7        |
| 1.152000        | ---                    | 18.67                 | 46.00              | -27.33      | L    | ON     | 9.7        |
| 1.152000        | 28.23                  | ---                   | 56.00              | -27.77      | L    | ON     | 9.7        |
| 17.136000       | ---                    | 26.42                 | 50.00              | -23.58      | L    | ON     | 10.0       |
| 17.136000       | 34.28                  | ---                   | 60.00              | -25.72      | L    | ON     | 10.0       |
| 18.024000       | ---                    | 28.16                 | 50.00              | -21.84      | L    | ON     | 10.0       |
| 18.024000       | 35.48                  | ---                   | 60.00              | -24.52      | L    | ON     | 10.0       |

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.

Full Spectrum






BUREAU  
VERITAS

# Test Report No.: RF200702W001-1

|                 |                |                                          |                                       |
|-----------------|----------------|------------------------------------------|---------------------------------------|
| Frequency Range | 150KHz ~ 30MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9 kHz |
| Input Power     | 120Vac, 60Hz   | Environmental Conditions                 | 24deg. C, 55RH                        |
| Tested By       | Chase Zhou     | Test Date                                | 2020/07/06                            |

| Frequency (MHz) | QuasiPeak (dB $\mu$ V) | CAverage (dB $\mu$ V) | Limit (dB $\mu$ V) | Margin (dB) | Line | Filter | Corr. (dB) |
|-----------------|------------------------|-----------------------|--------------------|-------------|------|--------|------------|
| 0.150000        | ---                    | 33.07                 | 56.00              | -22.93      | N    | ON     | 9.8        |
| 0.150000        | 46.86                  | ---                   | 66.00              | -19.14      | N    | ON     | 9.8        |
| 0.208000        | ---                    | 23.18                 | 53.28              | -30.11      | N    | ON     | 9.8        |
| 0.208000        | 37.75                  | ---                   | 63.28              | -25.53      | N    | ON     | 9.8        |
| 0.500000        | ---                    | 28.48                 | 46.00              | -17.52      | N    | ON     | 9.8        |
| 0.500000        | 35.55                  | ---                   | 56.00              | -20.45      | N    | ON     | 9.8        |
| 8.722000        | ---                    | 19.11                 | 50.00              | -30.89      | N    | ON     | 10.0       |
| 8.722000        | 29.02                  | ---                   | 60.00              | -30.98      | N    | ON     | 10.0       |
| 17.380000       | ---                    | 27.76                 | 50.00              | -22.24      | N    | ON     | 10.1       |
| 17.380000       | 36.26                  | ---                   | 60.00              | -23.74      | N    | ON     | 10.1       |
| 19.256000       | ---                    | 29.76                 | 50.00              | -20.24      | N    | ON     | 10.1       |
| 19.256000       | 37.65                  | ---                   | 60.00              | -22.35      | N    | ON     | 10.1       |

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.





BUREAU  
VERITAS

Test Report No.: RF200702W001-1

## 3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

### 3.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

| FREQUENCIES (MHz) | FIELD STRENGTH<br>(microvolts/meter) | MEASUREMENT DISTANCE<br>(meters) |
|-------------------|--------------------------------------|----------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                          | 300                              |
| 0.490 ~ 1.705     | 24000/F(kHz)                         | 30                               |
| 1.705 ~ 30.0      | 30                                   | 30                               |
| 30 ~ 88           | 100                                  | 3                                |
| 88 ~ 216          | 150                                  | 3                                |
| 216 ~ 960         | 200                                  | 3                                |
| Above 960         | 500                                  | 3                                |

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



**BUREAU  
VERITAS**

**Test Report No.: RF200702W001-1**

### 3.2.2 TEST INSTRUMENTS

| Equipment                  | Manufacturer | Model No.                   | Serial No.                  | Last Cal.   | Next Cal.   |
|----------------------------|--------------|-----------------------------|-----------------------------|-------------|-------------|
| 3m Semi-anechoic Chamber   | ETS-LINDGREN | 9m*6m*6m                    | Euroshieldpn-CT0001143-1216 | Feb. 26,20  | Feb. 25,21  |
| Bilog Antenna              | ETS-LINDGREN | 3143B                       | 00161965                    | Feb. 26,20  | Feb. 25,21  |
| Horn Antenna               | ETS-LINDGREN | 3117                        | 00168728                    | Feb. 26,20  | Feb. 25,21  |
| Horn Antenna (18GHz-40GHz) | N/A          | QWH-SL-18-40-K-SG/QMS-00361 | 15433                       | Nov. 21, 19 | Nov. 20, 20 |
| Test Software              | E3           | V 9.160323                  | N/A                         | N/A         | N/A         |
| Test Software              | ADT          | ADT_Radiated_V7.6.15.9.2    | N/A                         | N/A         | N/A         |
| 10dB Attenuator            | JFW/USA      | 50HF-010-SMA                | 1505                        | Jun. 03,20  | Jun. 03,21  |
| MXE EMI Receiver           | KEYSIGHT     | N9038A-544                  | MY54450026                  | Feb. 26,20  | Feb. 25,21  |
| Signal Pre-Amplifier       | EMSI         | EMC 9135                    | 980249                      | Jun. 21,20  | Jun. 20,21  |
| Signal Pre-Amplifier       | EMSI         | EMC 012645B                 | 980257                      | Jun. 21,20  | Jun. 20,21  |
| Signal Pre-Amplifier       | EMSI         | EMC 184045B                 | 980259                      | Jun. 21,20  | Jun. 20,21  |

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
  2. The test was performed in 3m Chamber.
  3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

### 3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

#### NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit.
5. All modes of operation were investigated and the worst-case emissions are reported.

### 3.2.4 DEVIATION FROM TEST STANDARD

No deviation.


### 3.2.5 TEST SETUP




BUREAU  
VERITAS

Test Report No.: RF200702W001-1

< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



**Note:** Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).



**Test Report No.: RF200702W001-1**



### **3.2.6 EUT OPERATING CONDITIONS**

- a. Set the EUT under full load condition and placed them on a testing table.
- b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.



**BUREAU  
VERITAS**

Test Report No.: RF200702W001-1

### 3.2.7 TEST RESULTS

#### BELOW 1GHz WORST-CASE DATA:

30 MHz – 1GHz data:


GFSK DH5

|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | Channel 78   | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 30MHz ~ 1GHz |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |        |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|--------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK |
| 33.85                                               | 21.69                         | 39.44                   | 40                | -18.31         | 18.98                        | 0.84                  | 37.57                    | 200                       | 360                        | QP     |
| 307.65                                              | 42.61                         | 63.16                   | 46                | -3.39          | 13.84                        | 2.24                  | 36.63                    | 200                       | 360                        | QP     |
| 370.26                                              | 38.71                         | 57.11                   | 46                | -7.29          | 15.85                        | 2.5                   | 36.75                    | 200                       | 360                        | QP     |
| 437.22                                              | 38.68                         | 55.12                   | 46                | -7.32          | 17.69                        | 2.76                  | 36.89                    | 200                       | 360                        | QP     |
| 633.52                                              | 39.8                          | 52.97                   | 46                | -6.2           | 20.87                        | 3.28                  | 37.32                    | 200                       | 360                        | QP     |
| 694.11                                              | 39.35                         | 50.63                   | 46                | -6.65          | 22.63                        | 3.51                  | 37.42                    | 200                       | 360                        | QP     |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | Channel 78   | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 30MHz ~ 1GHz |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |        |
|---------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|--------|
| FREQ.<br>(MHz)                                    | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK |
| 34.22                                             | 32.29                         | 50.22                   | 40                | -7.71          | 18.79                        | 0.85                  | 37.57                    | 100                       | 0                          | QP     |
| 117.69                                            | 32.82                         | 60.53                   | 43.5              | -10.68         | 7.77                         | 1.43                  | 36.91                    | 100                       | 0                          | QP     |
| 173.96                                            | 29.78                         | 54.66                   | 43.5              | -13.72         | 10.14                        | 1.69                  | 36.71                    | 100                       | 0                          | QP     |
| 208.16                                            | 29.77                         | 53.99                   | 43.5              | -13.73         | 10.57                        | 1.83                  | 36.62                    | 100                       | 0                          | QP     |
| 436.69                                            | 38.4                          | 54.85                   | 46                | -7.6           | 17.68                        | 2.76                  | 36.89                    | 100                       | 0                          | QP     |
| 631.11                                            | 39.65                         | 52.88                   | 46                | -6.35          | 20.8                         | 3.28                  | 37.31                    | 100                       | 0                          | QP     |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value





Test Report No.: RF200702W001-1

**ABOVE 1GHz WORST-CASE DATA:**

**Note:** For higher frequency, the emission is too low to be detected.

N/A



Test Report No.: RF200702W001-1

## 4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF200702W001-1

## **5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications are made to the EUT by the lab during the test.

**---END---**