FCC RF Test Report

APPLICANT	:	Sonim Technologies, Inc.
EQUIPMENT	:	Smartphone
BRAND NAME	:	Sonim
MODEL NAME	:	X802
FCC ID	:	WYPS3111
STANDARD	:	47 CFR Part 90(R)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S)	:	Nov. 26, 2024 ~ May 08, 2025

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

This report contains data that were produced under subcontract by Sporton International Inc. (ShenZhen)

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia

ACCREDITED
Cert #5145.02

Sporton International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Feature of Equipment Under Test 5
1.4 Maximum ERP Power, and Emission Designator 5
1.5 Testing Site 6
1.6 Test Software 6
1.7 Applied Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**

2.1 Test Mode 8
2.2 Connection Diagram of Test System 9
2.3 Support Unit used in test configuration and system 9
2.4 Measurement Results Explanation Example 9
2.5 Frequency List of Low/Middle/High Channels 10

3 CONDUCTED TEST ITEMS **11**

3.1 Measuring Instruments 11
3.2 Conducted Output Power and ERP 12
3.3 Peak-to-Average Ratio 13
3.4 Occupied Bandwidth 14
3.5 Conducted Band Edge Measurement 15
3.6 Emission Mask 16
3.7 Conducted Spurious Emission Measurement 17
3.8 Frequency Stability Measurement 18

4 RADIATED TEST ITEMS **19**

4.1 Measuring Instruments 19
4.2 Test Setup 19
4.3 Test Result of Radiated Test 20
4.4 Radiated Spurious Emission Measurement 21

5 LIST OF MEASURING EQUIPMENT **22**

6 MEASUREMENT UNCERTAINTY **23**

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG4O2403E	Rev. 01	Initial issue of report	May 22, 2025

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.2	§2.1046	Conducted Output Power	—	Reporting only	-
	§90.542 (a)(7)	Effective Radiated Power	ERP < 3Watt	PASS	-
3.3	-	Peak-to-Average Ratio	—	Reporting only	-
3.4	§2.1049	Occupied Bandwidth	—	Reporting only	-
3.5	§2.1053 §90.543 (e)(2)(3)	Conducted Band Edge Measurement	Refer standard	PASS	-
3.6	§2.1051 §90.210(n)	Emission Mask	Mask B	PASS	-
3.7	§2.1053 §90.543 (e)(3)	Conducted Spurious Emission	< $43+10\log_{10}$(P[Watts])	PASS	-
3.8	§2.1055 §90.539 (e)	Frequency Stability Temperature & Voltage	< ±1.25 ppm	PASS	-
4.4	§2.1053 §90.543 (e)(3) §90.543 (f)	Radiated Spurious Emission	< $43+10\log_{10}$(P[Watts])	PASS	Under limit 15.28 dB at 1581.50 MHz

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

Sonim Technologies, Inc.
4445 Eastgate Mall,Suite200,San Diego,CA92121,USA

1.2 Manufacturer

Sonim Technologies, Inc.
4445 Eastgate Mall,Suite200,San Diego,CA92121,USA

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Smartphone
Brand Name	Sonim
Model Name	X802
FCC ID	WYPS3111
Tx Frequency	LTE Band 14: 788 MHz ~ 798 MHz
Rx Frequency	LTE Band 14: 758 MHz ~ 768 MHz
Bandwidth	5MHz / 10MHz
Maximum Output Power to Antenna	<Ant1>: 23.82 dBm
Antenna Gain	<Ant1>: -4.41dBi
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM
HW Version	V1.0
SW Version	X80.0-01-14.0-42.18.00
EUT Stage	Identical Prototype

1.4 Maximum ERP Power, and Emission Designator

LTE Band 14		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	**Frequency Range (MHz)**	**Maximum ERP(W)**	**Emission Designator (99%OBW)**	**Maximum ERP(W)**	**Emission Designator (99%OBW)**
5	**790.5~795.5**	0.0520	4M50G7D	0.0414	4M49W7D
10	**793**	0.0532	8M97G7D	0.0415	8M95W7D

1.5 Testing Site

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	TH01-KS	CN1257	314309

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH01-SZ	CN1256	421272

Test data subcontracted: Radiated Spurious Emission test case in section 4 of this report

1.6 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH01-SZ	AUDIX	E3	6.2009-8-24

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 90(R)
- ANSI C63.26
- KDB 971168 D01 Power Meas License Digital Systems v03r01
- KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission. (Z Plane)

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	14	-	-	V		-	-	V	V	V	V	V	V	V	V	V	V
	14	-	-		V	-	-	V	V	V	V	V	V	V		V	
Peak-to-Average Ratio	14	-	-	V	V	-	-	V	V	V	V	V		V		V	
26dB and 99% Bandwidth	14	-	-	V		-	-	V	V					V	V	V	V
	14	-	-		V	-	-	V	V					V		V	
Conducted Band Edge	14	-	-	V		-	-	V	V	V	V	V		V	V		V
	14	-	-		V	-	-	V	V	V	V	V		V		V	
Emission Mask	14	-	-	V		-	-	V	V	V		V		V	V	V	V
	14	-	-		V	-	-	V	V	V		V		V		V	
Conducted Spurious Emission	14	-	-	V		-	-	V				V			V	V	V
	14	-	-		V	-	-	V				V				V	
Frequency Stability	14	-	-	V	V	-	-	V						V		V	
E.R.P	14	-	-	V		-	-	V	V	V	V	V	V	V	V	V	V
	14	-	-		V	-	-	V	V	V	V	V	V	V		V	
Radiated Spurious Emission	14	-	-	V	V	-	-	V				V			V	V	V
Note	1. The mark "v " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.																

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 4.6 dB.

Example :

Offset(dB) = RF cable loss(dB).

= 4.6 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 14 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
10	Channel	-	23330	-
	Frequency	-	793	-
5	Channel	23305	23330	23355
	Frequency	790.5	793	795.5

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.1.1 Test Setup

3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge, Emission Mask, and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.

3.2 Conducted Output Power and ERP

3.2.1 Description of the Conducted Output Power Measurement and ERP

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 14.

According to KDB 412172 D01 Power Approach,

EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.4 Occupied Bandwidth

3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.5 Conducted Band Edge Measurement

3.5.1 Description of Conducted Band Edge Measurement

For operations in the 758-768 MHz and the 788-798 MHz bands

(1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least 43 + 10 log (P) dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set spectrum analyzer with RMS detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. Checked that all the results comply with the emission limit line.

   Example:

   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

   = P(W)- [43 + 10log(P)] (dB)

   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB) = -13dBm.

3.6 Emission Mask

3.6.1 Description of Emission Mask

<Emission Mask B>.

For transmitters that are equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

(1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.

(2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB.

(3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least 43 + 10 log (P) dB.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
5. Set spectrum analyzer with RMS detector.
6. Taking the record of maximum spurious emission.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
   = P(W)- [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

3.7 Conducted Spurious Emission Measurement

3.7.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its 10th harmonic.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and base station via power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and power divider. The path loss was compensated to the results for each measurement.
   Path Loss Factor = Cable + Power Divider, Where the cable and power divider are the total path loss for the system calibration.
4. The low/middle/high channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's, for under 1GHz RBW = 100kHz, VBW = 300kHz and for above 1GHz RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. Set spectrum analyzer with RMS detector.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
   = P(W)- [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block.

3.8.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
3. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
4. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
3. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
5. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
10. ERP (dBm) = EIRP - 2.15
11. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
    The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [43 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
    = -13dBm.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 10, 2024	Nov. 26, 2024~ May 08, 2025	Oct. 09, 2025	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	NCR	Nov. 26, 2024~ May 08, 2025	NCR	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 04, 2024	Nov. 26, 2024~ May 08, 2025	Jul. 03, 2025	Conducted (TH01-KS)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 03, 2024	Jan. 24, 2025	Jul. 02, 2025	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 28, 2024	Jan. 24, 2025	Dec. 27, 2025	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 14, 2024	Jan. 24, 2025	Oct. 13, 2025	Radiation (03CH01-SZ
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz-2GHz	Oct. 24, 2023	Jan. 24, 2025	Oct. 23, 2025	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 04, 2024	Jan. 24, 2025	Jul. 03, 2025	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Apr. 09, 2024	Jan. 24, 2025	Apr. 08, 2025	Radiation (03CH01-SZ)
LF Amplifier	EM Electronics	EM330	060788	20MHz-3GHz	Dec. 25, 2024	Jan. 24, 2025	Dec. 24, 2025	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P-R	1943528	1GHz~18GHz	Oct. 14, 2024	Jan. 24, 2025	Oct. 13, 2025	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 03, 2024	Jan. 24, 2025	Jul. 02, 2025	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	Oct. 14, 2024	Jan. 24, 2025	Oct. 13, 2025	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jan. 24, 2025	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jan. 24, 2025	NCR	Radiation (03CH01-SZ)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±2.22 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.50 dB
Peak to Average Ratio	±0.90 dB
Frequency Stability	±0.04ppm

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.48 dB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.53 dB

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.02 dB

---------- THE END ----------

Appendix A. Test Results of Conducted Test

Test Engineer :	Smile Wang	Temperature :	22~23℃
		Relative Humidity :	40~42%

Conducted Output Power(Average power) and ERP

LTE Band 14_Ant1:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W)		
Channel				23330					
Frequency (MHz)				793				M	
10	QPSK	1	0		23.82			0.0532	
10	QPSK	1	25		23.55			0.0500	
10	QPSK	1	49		23.68			0.0515	
10	QPSK	25	0		22.86			0.0427	
10	QPSK	25	12		22.68			0.0409	
10	QPSK	25	25		22.68			0.0409	
10	QPSK	50	0		22.82			0.0423	
10	16QAM	1	0		22.53			0.0395	
10	16QAM	1	25		22.61			0.0403	
10	16QAM	1	49		22.74			0.0415	
10	16QAM	25	0		21.50			0.0312	
10	16QAM	25	12		21.51			0.0313	
10	16QAM	25	25		21.61			0.0320	
10	16QAM	50	0		21.67			0.0324	
10	64QAM	1	0		21.63			0.0321	
10	64QAM	1	25		21.72			0.0328	
10	64QAM	1	49		21.65			0.0323	
10	64QAM	25	0		20.62			0.0255	
10	64QAM	25	12		20.72			0.0261	
10	64QAM	25	25		20.42			0.0243	
10	64QAM	50	0		20.48			0.0247	
10	256QAM	1	0		18.49			0.0156	
10	256QAM	1	25		18.50			0.0156	
10	256QAM	1	49		18.62			0.0161	
10	256QAM	25	0		18.48			0.0156	
10	256QAM	25	12		18.68			0.0163	
10	256QAM	25	25		18.43			0.0154	
10	256QAM	50	0		18.50			0.0156	
Channel				23305	23330	23355	ERP(W)		
Frequency (MHz)				790.5	793	795.5	L	M	H

5	QPSK	1	0	23.66	23.72	23.71	0.0513	0.0520	0.0519
5	QPSK	1	12	23.56	23.62	23.54	0.0501	0.0508	0.0499
5	QPSK	1	24	23.51	23.64	23.66	0.0495	0.0511	0.0513
5	QPSK	12	0	22.51	22.70	22.48	0.0394	0.0411	0.0391
5	QPSK	12	7	22.64	22.63	22.77	0.0406	0.0405	0.0418
5	QPSK	12	13	22.54	22.76	22.61	0.0396	0.0417	0.0403
5	QPSK	25	0	22.67	22.64	22.45	0.0408	0.0406	0.0388
5	16QAM	1	0	22.64	22.56	22.67	0.0406	0.0398	0.0408
5	16QAM	1	12	22.66	22.56	22.60	0.0407	0.0398	0.0402
5	16QAM	1	24	22.73	22.69	22.45	0.0414	0.0410	0.0388
5	16QAM	12	0	21.59	21.52	21.73	0.0318	0.0313	0.0329
5	16QAM	12	7	21.75	21.51	21.66	0.0330	0.0313	0.0324
5	16QAM	12	13	21.68	21.58	21.64	0.0325	0.0318	0.0322
5	16QAM	25	0	21.67	21.68	21.57	0.0324	0.0325	0.0317
5	64QAM	1	0	21.55	21.66	21.57	0.0316	0.0324	0.0317
5	64QAM	1	12	21.59	21.55	21.45	0.0318	0.0316	0.0308
5	64QAM	1	24	21.52	21.61	21.73	0.0313	0.0320	0.0329
5	64QAM	12	0	20.41	20.51	20.73	0.0243	0.0248	0.0261
5	64QAM	12	7	20.72	20.68	20.71	0.0261	0.0258	0.0260
5	64QAM	12	13	20.65	20.51	20.58	0.0256	0.0248	0.0252
5	64QAM	25	0	20.49	20.65	20.57	0.0247	0.0256	0.0252
5	256QAM	1	0	18.31	18.56	18.31	0.0150	0.0158	0.0150
5	256QAM	1	12	18.35	18.38	18.42	0.0151	0.0152	0.0153
5	256QAM	1	24	18.44	18.49	18.26	0.0154	0.0156	0.0148
5	256QAM	12	0	18.39	18.40	18.57	0.0152	0.0153	0.0159
5	256QAM	12	7	18.51	18.62	18.55	0.0157	0.0161	0.0158
5	256QAM	12	13	18.49	18.40	18.32	0.0156	0.0153	0.0150
5	256QAM	25	0	18.41	18.67	18.32	0.0153	0.0163	0.0150

LTE Band 14

Peak-to-Average Ratio

Mode	LTE Band 14 / 5MHz				
Mod.	QPSK	16QAM	64QAM	256QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Full RB	Result
Middle CH	5.22	6.26	6.70	6.75	PASS

LTE Band 14 / 5MHz

Middle Channel / Full RB/ QPSK



Middle Channel / Full RB/ 16QAM



Middle Channel / Full RB/ 64QAM



Middle Channel / Full RB/ 256QAM



Mode	LTE Band 14 / 10MHz				
Mod.	QPSK	16QAM	64QAM	256QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Full RB	Result
Middle CH	5.19	6.17	6.61	6.93	PASS

LTE Band 14 / 5MHz

Middle Channel / Full RB/ QPSK



Middle Channel / Full RB/ 16QAM

Middle Channel / Full RB/ 64QAM



Middle Channel / Full RB/ 256QAM



26dB Bandwidth

Mode	LTE Band 14 : 26dB BW(MHz)	
BW	10MHz	
Mod.	QPSK	16QAM
Middle CH	9.81	9.81
BW	5MHz	
Mod.	QPSK	16QAM
Middle CH	4.90	5.02

LTE Band 14

Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



LTE Band 14

Middle Channel /5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Occupied Bandwidth

Mode	LTE Band 14 : 99%OBW(MHz)	
BW	10MHz	
Mod.	QPSK	16QAM
Middle CH	8.97	8.95
BW	5MHz	
Mod.	QPSK	16QAM
Middle CH	4.50	4.49

LTE Band 14

Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



LTE Band 14

Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Conducted Band Edge

LTE Band 14 / 5MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	756.30170 MHz	-64.47 dBm	-51.47 dB
758.000 MHz	769.000 MHz	100.000 kHz	761.54396 MHz	-63.31 dBm	-93.31 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.37662 MHz	-75.31 dBm	-40.31 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-19.00 dBm	-6.00 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.34615 MHz	22.24 dBm	-7.76 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.64436 MHz	-74.40 dBm	-39.40 dB
805.000 MHz	810.000 MHz	100.000 kHz	808.96853 MHz	-62.58 dBm	-49.58 dB

Date: 26.NOV.2024 22:14:24

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.93806 MHz	-64.47 dBm	-51.47 dB
758.000 MHz	769.000 MHz	100.000 kHz	767.25824 MHz	-63.42 dBm	-93.42 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.16983 MHz	-75.40 dBm	-40.40 dB
775.000 MHz	788.000 MHz	100.000 kHz	784.37013 MHz	-63.19 dBm	-50.19 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.66484 MHz	21.74 dBm	-8.26 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.00899 MHz	-56.90 dBm	-21.90 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.85564 MHz	-60.28 dBm	-47.28 dB

Date: 26.NOV.2024 22:30:57

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	753.86414 MHz	-64.60 dBm	-51.60 dB
758.000 MHz	769.000 MHz	100.000 kHz	768.51099 MHz	-63.46 dBm	-93.46 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.41558 MHz	-74.80 dBm	-39.80 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.98052 MHz	-23.68 dBm	-10.68 dB
788.000 MHz	799.000 MHz	100.000 kHz	792.14835 MHz	8.09 dBm	-21.91 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.03896 MHz	-56.51 dBm	-21.51 dB
805.000 MHz	810.000 MHz	100.000 kHz	808.19930 MHz	-63.25 dBm	-50.25 dB

Date: 26.NOV.2024 22:21:07

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	754.75125 MHz	-64.61 dBm	-51.61 dB
758.000 MHz	769.000 MHz	100.000 kHz	765.07143 MHz	-63.39 dBm	-93.39 dB
769.000 MHz	775.000 MHz	6.250 kHz	773.17483 MHz	-75.04 dBm	-40.04 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.96753 MHz	-41.51 dBm	-28.51 dB
788.000 MHz	799.000 MHz	100.000 kHz	793.80769 MHz	8.10 dBm	-21.90 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.01499 MHz	-44.91 dBm	-9.91 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.57592 MHz	-62.98 dBm	-49.98 dB

Date: 26.NOV.2024 22:36:45

LTE Band 14 / 5MHz / 16QAM

Lowest Band Edge /1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	752.87313 MHz	-64.55 dBm	-51.55 dB
758.000 MHz	769.000 MHz	100.000 kHz	762.93956 MHz	-63.52 dBm	-93.52 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.15485 MHz	-75.10 dBm	-40.10 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-19.58 dBm	-6.58 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.34615 MHz	21.44 dBm	-8.56 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.41658 MHz	-74.47 dBm	-39.47 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.54096 MHz	-62.98 dBm	-49.98 dB

Date: 26.NOV.2024 22:15:51

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.94605 MHz	-64.43 dBm	-51.43 dB
758.000 MHz	769.000 MHz	100.000 kHz	766.30220 MHz	-63.45 dBm	-93.45 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.15485 MHz	-75.23 dBm	-40.23 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.96753 MHz	-62.89 dBm	-49.89 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.69780 MHz	20.88 dBm	-9.12 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.00300 MHz	-58.87 dBm	-23.87 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.93556 MHz	-60.03 dBm	-47.03 dB

Date: 26.NOV.2024 22:32:23

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	750.67532 MHz	-64.63 dBm	-51.63 dB
758.000 MHz	769.000 MHz	100.000 kHz	761.88462 MHz	-63.52 dBm	-93.52 dB
769.000 MHz	775.000 MHz	6.250 kHz	773.97802 MHz	-75.17 dBm	-40.17 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-24.60 dBm	-11.60 dB
788.000 MHz	799.000 MHz	100.000 kHz	792.08242 MHz	7.36 dBm	-22.64 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.05694 MHz	-57.79 dBm	-22.79 dB
805.000 MHz	810.000 MHz	100.000 kHz	808.86364 MHz	-63.15 dBm	-50.15 dB

Date: 26.NOV.2024 22:22:34

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	753.32867 MHz	-64.60 dBm	-51.60 dB
758.000 MHz	769.000 MHz	100.000 kHz	762.12637 MHz	-63.10 dBm	-93.10 dB
769.000 MHz	775.000 MHz	6.250 kHz	772.85714 MHz	-75.16 dBm	-40.16 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.94156 MHz	-43.09 dBm	-30.09 dB
788.000 MHz	799.000 MHz	100.000 kHz	793.39011 MHz	7.74 dBm	-22.26 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.06893 MHz	-45.79 dBm	-10.79 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.78172 MHz	-62.87 dBm	-49.87 dB

Date: 26.NOV.2024 22:38:11

LTE Band 14 / 5MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	755.80619 MHz	-64.58 dBm	-51.58 dB
758.000 MHz	769.000 MHz	100.000 kHz	765.42308 MHz	-63.53 dBm	-93.53 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.96304 MHz	-75.22 dBm	-40.22 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-20.00 dBm	-7.00 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.33516 MHz	20.85 dBm	-9.15 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.69231 MHz	-74.47 dBm	-39.47 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.19231 MHz	-63.09 dBm	-50.09 dB

Date: 26.NOV.2024 22:17:18

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.95405 MHz	-64.58 dBm	-51.58 dB
758.000 MHz	769.000 MHz	100.000 kHz	760.62088 MHz	-63.35 dBm	-93.35 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.31369 MHz	-75.33 dBm	-40.33 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.96753 MHz	-63.64 dBm	-50.64 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.67582 MHz	20.24 dBm	-9.76 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.10490 MHz	-63.63 dBm	-28.63 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.90559 MHz	-61.28 dBm	-48.28 dB

Date: 26.NOV.2024 22:33:50

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	755.87812 MHz	-64.62 dBm	-51.62 dB
758.000 MHz	769.000 MHz	100.000 kHz	767.73077 MHz	-62.91 dBm	-92.91 dB
769.000 MHz	775.000 MHz	6.250 kHz	772.42557 MHz	-75.35 dBm	-40.35 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-25.72 dBm	-12.72 dB
788.000 MHz	799.000 MHz	100.000 kHz	792.28022 MHz	5.81 dBm	-24.19 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.15884 MHz	-59.83 dBm	-24.83 dB
805.000 MHz	810.000 MHz	100.000 kHz	809.10340 MHz	-63.27 dBm	-50.27 dB

Date: 26.NOV.2024 22:24:00

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	757.41259 MHz	-64.60 dBm	-51.60 dB
758.000 MHz	769.000 MHz	100.000 kHz	765.56593 MHz	-63.13 dBm	-93.13 dB
769.000 MHz	775.000 MHz	6.250 kHz	769.83017 MHz	-75.21 dBm	-40.21 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.86364 MHz	-45.76 dBm	-32.76 dB
788.000 MHz	799.000 MHz	100.000 kHz	793.95055 MHz	6.34 dBm	-23.66 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.13487 MHz	-46.71 dBm	-11.71 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.35614 MHz	-62.75 dBm	-49.75 dB

Date: 26.NOV.2024 22:39:38

LTE Band 14 / 5MHz / 256QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	752.82517 MHz	-64.54 dBm	-51.54 dB
758.000 MHz	769.000 MHz	100.000 kHz	759.17033 MHz	-63.26 dBm	-93.26 dB
769.000 MHz	775.000 MHz	6.250 kHz	772.27572 MHz	-75.23 dBm	-40.23 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-24.45 dBm	-11.45 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.32418 MHz	16.33 dBm	-13.67 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.90809 MHz	-74.52 dBm	-39.52 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.31618 MHz	-63.17 dBm	-50.17 dB

Date: 26.NOV.2024 22:18:44

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	756.78921 MHz	-64.70 dBm	-51.70 dB
758.000 MHz	769.000 MHz	100.000 kHz	767.31319 MHz	-63.26 dBm	-93.26 dB
769.000 MHz	775.000 MHz	6.250 kHz	769.87812 MHz	-75.24 dBm	-40.24 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.78571 MHz	-63.74 dBm	-50.74 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.68681 MHz	16.47 dBm	-13.53 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.75824 MHz	-64.48 dBm	-29.48 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.87562 MHz	-62.22 dBm	-49.22 dB

Date: 26.NOV.2024 22:35:16

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	750.82717 MHz	-64.68 dBm	-51.68 dB
758.000 MHz	769.000 MHz	100.000 kHz	768.44505 MHz	-63.23 dBm	-93.23 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.41159 MHz	-75.23 dBm	-40.23 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-27.95 dBm	-14.95 dB
788.000 MHz	799.000 MHz	100.000 kHz	791.55495 MHz	3.79 dBm	-26.21 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.06893 MHz	-61.02 dBm	-26.02 dB
805.000 MHz	810.000 MHz	100.000 kHz	808.30919 MHz	-63.15 dBm	-50.15 dB

Date: 26.NOV.2024 22:25:26

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	754.70330 MHz	-64.65 dBm	-51.65 dB
758.000 MHz	769.000 MHz	100.000 kHz	761.52198 MHz	-63.43 dBm	-93.43 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.02897 MHz	-75.21 dBm	-40.21 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.83766 MHz	-47.93 dBm	-34.93 dB
788.000 MHz	799.000 MHz	100.000 kHz	793.58791 MHz	4.25 dBm	-25.75 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.00300 MHz	-49.72 dBm	-14.72 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.17732 MHz	-63.23 dBm	-50.23 dB

Date: 26.NOV.2024 22:41:04

LTE Band 14 / 10MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	757.34865 MHz	-64.56 dBm	-51.56 dB
758.000 MHz	769.000 MHz	100.000 kHz	766.70879 MHz	-63.37 dBm	-93.37 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.39461 MHz	-75.07 dBm	-40.07 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-31.97 dBm	-18.97 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.62088 MHz	21.90 dBm	-8.10 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.39461 MHz	-73.92 dBm	-38.92 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.41708 MHz	-63.09 dBm	-50.09 dB

Date: 26.NOV.2024 22:45:11

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	755.38262 MHz	-64.57 dBm	-51.57 dB
758.000 MHz	769.000 MHz	100.000 kHz	765.88462 MHz	-63.57 dBm	-93.57 dB
769.000 MHz	775.000 MHz	6.250 kHz	773.22278 MHz	-75.24 dBm	-40.24 dB
775.000 MHz	788.000 MHz	100.000 kHz	784.59091 MHz	-58.38 dBm	-45.38 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.39011 MHz	21.71 dBm	-8.29 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.12887 MHz	-62.24 dBm	-27.24 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.62587 MHz	-60.10 dBm	-47.10 dB

Date: 26.NOV.2024 22:50:55

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	756.57343 MHz	-64.59 dBm	-51.59 dB
758.000 MHz	769.000 MHz	100.000 kHz	766.34615 MHz	-63.27 dBm	-93.27 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.60739 MHz	-73.33 dBm	-38.33 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-31.30 dBm	-18.30 dB
788.000 MHz	799.000 MHz	100.000 kHz	793.67582 MHz	5.36 dBm	-24.64 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.36863 MHz	-47.82 dBm	-12.82 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.20230 MHz	-62.62 dBm	-49.62 dB

Date: 26.NOV.2024 22:56:39

LTE Band 14 / 10MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	755.67033 MHz	-64.61 dBm	-51.61 dB
758.000 MHz	769.000 MHz	100.000 kHz	759.76374 MHz	-63.35 dBm	-93.35 dB
769.000 MHz	775.000 MHz	6.250 kHz	769.47053 MHz	-75.09 dBm	-40.09 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-30.30 dBm	-17.30 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.62088 MHz	20.59 dBm	-9.41 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.35664 MHz	-73.04 dBm	-38.04 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.27722 MHz	-62.89 dBm	-49.89 dB

Date: 26.NOV.2024 22:46:37

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.72228 MHz	-64.52 dBm	-51.52 dB
758.000 MHz	769.000 MHz	100.000 kHz	765.11538 MHz	-63.62 dBm	-93.62 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.85914 MHz	-75.13 dBm	-40.13 dB
775.000 MHz	788.000 MHz	100.000 kHz	784.65584 MHz	-58.01 dBm	-45.01 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.41209 MHz	20.39 dBm	-9.61 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.80020 MHz	-61.56 dBm	-26.56 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.63087 MHz	-60.23 dBm	-47.23 dB

Date: 26.NOV.2024 22:52:21

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	754.33566 MHz	-64.62 dBm	-51.62 dB
758.000 MHz	769.000 MHz	100.000 kHz	762.68681 MHz	-63.22 dBm	-93.22 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.49950 MHz	-74.03 dBm	-39.03 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-31.90 dBm	-18.90 dB
788.000 MHz	799.000 MHz	100.000 kHz	791.98352 MHz	4.34 dBm	-25.66 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.32068 MHz	-48.46 dBm	-13.46 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.47103 MHz	-62.82 dBm	-49.82 dB

Date: 26.NOV.2024 22:58:04

LTE Band 14 / 10MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	756.09391 MHz	-64.62 dBm	-51.62 dB
758.000 MHz	769.000 MHz	100.000 kHz	767.07143 MHz	-63.31 dBm	-93.31 dB
769.000 MHz	775.000 MHz	6.250 kHz	772.09590 MHz	-75.13 dBm	-40.13 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-33.33 dBm	-20.33 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.56593 MHz	19.89 dBm	-10.11 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.30470 MHz	-74.08 dBm	-39.08 dB
805.000 MHz	810.000 MHz	100.000 kHz	809.93756 MHz	-63.00 dBm	-50.00 dB

Date: 26.NOV.2024 22:48:04

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	757.79620 MHz	-64.61 dBm	-51.61 dB
758.000 MHz	769.000 MHz	100.000 kHz	761.59890 MHz	-63.28 dBm	-93.28 dB
769.000 MHz	775.000 MHz	6.250 kHz	769.93207 MHz	-75.38 dBm	-40.38 dB
775.000 MHz	788.000 MHz	100.000 kHz	784.59091 MHz	-59.63 dBm	-46.63 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.44505 MHz	19.64 dBm	-10.36 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.00300 MHz	-64.25 dBm	-29.25 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.66583 MHz	-61.03 dBm	-48.03 dB

Date: 26.NOV.2024 22:53:47

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	757.52448 MHz	-64.65 dBm	-51.65 dB
758.000 MHz	769.000 MHz	100.000 kHz	765.47802 MHz	-63.47 dBm	-93.47 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.70330 MHz	-73.98 dBm	-38.98 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-32.61 dBm	-19.61 dB
788.000 MHz	799.000 MHz	100.000 kHz	792.99451 MHz	3.10 dBm	-26.90 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.05095 MHz	-48.90 dBm	-13.90 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.02148 MHz	-62.94 dBm	-49.94 dB

Date: 26.NOV.2024 22:59:30

LTE Band 14 / 10MHz / 256QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	756.62138 MHz	-64.68 dBm	-51.68 dB
758.000 MHz	769.000 MHz	100.000 kHz	760.59890 MHz	-63.29 dBm	-93.29 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.56543 MHz	-75.33 dBm	-40.33 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-36.85 dBm	-23.85 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.58791 MHz	16.85 dBm	-13.15 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.80819 MHz	-74.38 dBm	-39.38 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.85564 MHz	-63.10 dBm	-50.10 dB

Date: 26.NOV.2024 22:49:29

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	755.76623 MHz	-64.67 dBm	-51.67 dB
758.000 MHz	769.000 MHz	100.000 kHz	766.55495 MHz	-63.39 dBm	-93.39 dB
769.000 MHz	775.000 MHz	6.250 kHz	773.27672 MHz	-75.32 dBm	-40.32 dB
775.000 MHz	788.000 MHz	100.000 kHz	784.17532 MHz	-54.31 dBm	-41.31 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.40110 MHz	16.48 dBm	-13.52 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.01499 MHz	-67.60 dBm	-32.60 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.68581 MHz	-61.93 dBm	-48.93 dB

Date: 26.NOV.2024 22:55:12

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	757.88412 MHz	-64.63 dBm	-51.63 dB
758.000 MHz	769.000 MHz	100.000 kHz	764.33516 MHz	-63.30 dBm	-93.30 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.68531 MHz	-74.65 dBm	-39.65 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-35.16 dBm	-22.16 dB
788.000 MHz	799.000 MHz	100.000 kHz	793.78571 MHz	1.46 dBm	-28.54 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.29071 MHz	-51.99 dBm	-16.99 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.24725 MHz	-63.17 dBm	-50.17 dB

Date: 26.NOV.2024 23:00:56

Conducted Spurious Emission

LTE Band 14 / 5MHz

Lowest Channel / QPSK



Item	Range Low	Range Up	RBW	VBW	Frequency	Power Abs	Limit	Limit	Path Loss Factor	DCC	APS
1	30.000 MHz	763.000 MHz	1 MHz	3 MHz	756.87000 MHz	-57.564 dBm	-44.564 dB	-13.000 dBm	4.973 dB	---	---
2	763.000 MHz	806.000 MHz	1 MHz	3 MHz	788.28000 MHz	24.660 dBm	-5.340 dB	30.000 dBm	4.984 dB	---	---
3	806.000 MHz	1.000 GHz	1 MHz	3 MHz	806.04000 MHz	-57.539 dBm	-44.539 dB	-13.000 dBm	5.055 dB	---	---
4	1.000 GHz	3.000 GHz	1 MHz	3 MHz	2.36500 GHz	-31.221 dBm	-18.221 dB	-13.000 dBm	6.486 dB	---	---
5	3.000 GHz	8.000 GHz	1 MHz	3 MHz	6.50500 GHz	-50.380 dBm	-37.380 dB	-13.000 dBm	8.294 dB	---	---

Note: DCC = Duty Cycle Correction / APS = Antenna Port Summation
Ver 1.1(20241209) 2025-05-06 14:02:00

Middle Channel / QPSK



Item	Range Low	Range Up	RBW	VBW	Frequency	Power Abs	Limit	Limit	Path Loss Factor	DCC	APS
1	30.000 MHz	763.000 MHz	1 MHz	3 MHz	760.56150 MHz	-52.647 dBm	-44.647 dB	-13.000 dBm	4.973 dB	---	---
2	763.000 MHz	806.000 MHz	1 MHz	3 MHz	790.82950 MHz	24.792 dBm	-5.208 dB	30.000 dBm	4.984 dB	---	---
3	806.000 MHz	1.000 GHz	1 MHz	3 MHz	814.50625 MHz	-66.245 dBm	-53.245 dB	-13.000 dBm	5.055 dB	---	---
4	1.000 GHz	3.000 GHz	1 MHz	3 MHz	2.37250 GHz	-30.299 dBm	-17.299 dB	-13.000 dBm	6.486 dB	---	---
5	3.000 GHz	8.000 GHz	1 MHz	3 MHz	6.44850 GHz	-50.199 dBm	-37.199 dB	-13.000 dBm	8.294 dB	---	---

Note: DCC = Duty Cycle Correction / APS = Antenna Port Summation
Ver 1.1(20241209) 2025-05-06 14:02:58

Highest Channel / QPSK



Item	Range Low	Range Up	RBW	VBW	Frequency	Power Abs	Limit	Limit	Path Loss Factor	DCC	APS
1	30.000 MHz	763.000 MHz	1 MHz	3 MHz	762.77050 MHz	-57.699 dBm	-44.699 dB	-13.000 dBm	4.973 dB	---	---
2	763.000 MHz	806.000 MHz	1 MHz	3 MHz	793.36750 MHz	24.850 dBm	-5.150 dB	30.000 dBm	4.984 dB	---	---
3	806.000 MHz	1.000 GHz	1 MHz	3 MHz	967.77625 MHz	-66.333 dBm	-53.333 dB	-13.000 dBm	5.055 dB	---	---
4	1.000 GHz	3.000 GHz	1 MHz	3 MHz	2.38050 GHz	-29.941 dBm	-16.941 dB	-13.000 dBm	6.486 dB	---	---
5	3.000 GHz	8.000 GHz	1 MHz	3 MHz	6.48400 GHz	-50.221 dBm	-37.221 dB	-13.000 dBm	8.294 dB	---	---

Note: DCC = Duty Cycle Correction / APS = Antenna Port Summation
Ver 1.1(20241209) 2025-05-06 14:03:07

LTE Band 14 / 10MHz

Middle Channel / QPSK



Item	Range Low	Range Up	RBW	VBW	Frequency	Power Abs	Limit	Limit	Path Loss Factor	DCC	APS
1	30.000 MHz	763.000 MHz	1 MHz	3 MHz	760.58500 MHz	-53.140 dBm	-40.140 dB	-13.000 dBm	4.973 dB	---	---
2	763.000 MHz	806.000 MHz	1 MHz	3 MHz	788.59700 MHz	25.034 dBm	-4.966 dB	30.000 dBm	4.984 dB	---	---
3	806.000 MHz	1.000 GHz	1 MHz	3 MHz	995.66125 MHz	-61.541 dBm	-48.541 dB	-13.000 dBm	5.055 dB	---	---
4	1.000 GHz	3.000 GHz	1 MHz	3 MHz	2.36600 GHz	-29.529 dBm	-16.529 dB	-13.000 dBm	6.486 dB	---	---
5	3.000 GHz	8.000 GHz	1 MHz	3 MHz	6.49650 GHz	-45.966 dBm	-32.966 dB	-13.000 dBm	8.294 dB	---	---

Note: DCC = Duty Cycle Correction / APS = Antenna Port Summation

Ver 1.1(20241209) 2025-05-06 14:03:14

Mask

LTE Band 14 / 5MHz / QPSK

Lowest Channel / 1RB





Lowest Channel / Full RB



LTE Band 14 / 5MHz / 16QAM

Lowest Channel / 1RB





Lowest Channel / Full RB