

TUV SUD BABT FCB  
Octagon House,  
Segensworth Road,  
Fareham,  
Hampshire,  
PO15 5RL

Date: January 22, 2015

**RF exposure analysis for the equipment DA312i (FCC ID: X26DA312i)**

**1. Introduction**

The device DA312i (FCC ID: X26DA312i) is a wireless hearing instrument used to amplify sound from the surrounding to the end user and also receive audio signals through wireless connection to accessories. It contains a multi-mode 2.4GHz radio which operates, time & frequency divided, in either BlueTooth Low Energy mode (BTLE) or a proprietary "Proximity" mode and is intended for use within 20 cm of humans.

**2. SAR limits**

According to § 2.1093 (d) (2) the limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and peak spatial-average SAR limit is 1.6 W/kg, averaged over any 1 gram of tissue over the whole body.

**3. Compliance criteria:**


Individual transmitters are deemed to comply with § 2.1093 requirements if the output power of the transmitter meets the conditions specified in section 4.3.1 (Standalone SAR test exclusion) considerations of the document "KDB 447498 D01 General RF Exposure Guidance v05r02".

**4. Compliance calculations:**

| Mode      | Sub-mode  | Frequency | Average field strength (dBµV/m) | Average output power (dBm) | Average output power (mW) | Evaluation distance per KDB 447498 D01 General RF Exposure Guidance v05r02 - 4.3.1 (mm) | SAR Test Exclusion Thresholds per KDB 447498 D01 General RF Exposure Guidance v05r02 - 4.3.1 - 1) (mW) | SAR Test Exclusion Thresholds per KDB 447498 D01 General RF Exposure Guidance v05r02 - 4.3.1 - 1) |
|-----------|-----------|-----------|---------------------------------|----------------------------|---------------------------|-----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| BLE       | BLE       | 2402      | 83,12                           | -12,11                     | 0,062                     | 5                                                                                       | 10                                                                                                     | COMPLIANT                                                                                         |
|           |           | 2440      | 82,64                           | -12,59                     | 0,055                     | 5                                                                                       | 10                                                                                                     | COMPLIANT                                                                                         |
|           |           | 2480      | 81,49                           | -13,74                     | 0,042                     | 5                                                                                       | 10                                                                                                     | COMPLIANT                                                                                         |
| Proximity | Proximity | 2404      | 79,90                           | -15,33                     | 0,029                     | 5                                                                                       | 10                                                                                                     | COMPLIANT                                                                                         |
|           |           | 2440      | 79,92                           | -15,31                     | 0,029                     | 5                                                                                       | 10                                                                                                     | COMPLIANT                                                                                         |
|           |           | 2478      | 78,16                           | -17,07                     | 0,020                     | 5                                                                                       | 10                                                                                                     | COMPLIANT                                                                                         |

Sincerely,

P.A.



By: Lars Hagander  
Title: Vice president, Corporate Quality  
Company: GN Hearing A/S, Lautrupbjerg 7, 2750 Ballerup, Denmark  
Telephone / Fax: +45 45 75 21 00 / +45 45 75 44 29  
e-mail: [lhagander@gnresound.dk](mailto:lhagander@gnresound.dk)