

RF TEST REPORT



Report No.: 16020759-FCC-R1

Supersede Report No.: N/A

Applicant	Shanghai Smarfid Security Equipment Co.,Ltd	
Product Name	Magic MINI Mifare Reader	
Main Model	MW382-8N	
Serial Model	N/A	
Test Standard	FCC Part 15.225: 2015, ANSI C63.10: 2013	
Test Date	July 22 to July 27, 2016	
Issue Date	August 04, 2016	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification	☒	
Equipment did not comply with the specification	☐	
<i>Louise Tu</i>	<i>Miro Bao</i>	
Louise Tu Test Engineer	Miro Bao Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:
SIEMIC (Nanjing-China) Laboratories
2-1 Longcang Avenue Yuhua Economic and
Technology Development Park, Nanjing, China
Tel:+86(25)86730128/86730129 Fax:+86(25)86730127 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	16020759-FCC-R1
Page	3 of 36

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY.....	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	7
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	8
6.1 ANTENNA REQUIREMENT	8
6.2 CONDUCTED EMISSIONS VOLTAGE	9
6.3 FUNDAMENTAL FIELD STRENGTH TEST RESULT	13
6.4 RADIATED SPURIOUS EMISSIONS.....	15
6.5 FREQUENCY STABILITY	20
6.6 20DB OCCUPIED BANDWIDTH.....	22
ANNEX A. TEST INSTRUMENT	24
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	25
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	32
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST.....	35
ANNEX E. DECLARATION OF SIMILARITY	36

Test Report No.	16020759-FCC-R1
Page	5 of 36

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16020759-FCC-R1	NONE	Original	August 04, 2016

2. Customer information

Applicant Name	Shanghai Smarfid Security Equipment Co.,Ltd
Applicant Address	Room 301,4th Bldg., No.4 TongLi Road, SongJiang District,Shanghai 201615,China
Manufacturer Name	Shanghai Smarfid Security Equipment Co.,Ltd
Manufacturer Address	Room 301,4th Bldg., No.4 TongLi Road, SongJiang District,Shanghai 201615,China

3. Test site information

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	986914
IC Test Site No.	4842B-1
Test Software	Labview of SIEMIC version 1.0

Test Report No.	16020759-FCC-R1
Page	6 of 36

4. Equipment Under Test (EUT) Information

Description of EUT:	Magic MINI Mifare Reader
Main Model:	MW382-8N
Serial Model:	N/A
Date EUT received:	July 21, 2016
Test Date(s):	July 22 to July 27, 2016
Antenna Gain:	13.56MHz: 6 dBi
Type of Modulation:	ASK
RF Operating Frequency (ies):	13.56MHz
Number of Channels:	1 CH
Input Power:	DC 12V
Trade Name :	N/A
FCC ID:	X3A-MG3821356M

5. Test Summary

The product was tested in accordance with the following specifications.
All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	Conducted Emissions Voltage	Compliance
§15.225(a)	Fundamental Field Strength	Compliance
§15.225(b)	Fundamental Field Strength	Compliance
§15.225(c)	Fundamental Field Strength	Compliance
§15.225(d), 15.209	Radiated Emissions	Compliance
§15.225(e)	Frequency Stability	Compliance
§15.215(c)	Occupied Bandwidth	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	3.952dB

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

Requirement(s): 47 CFR §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
- b) Antenna must use a unique type of connector to attach to the device.
- c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.

The antenna is permanently attached to the device which meets the requirement.


Result: Compliance.

6.2 Conducted Emissions Voltage

Temperature	25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	July 27, 2016
Tested By :	Louise Tu

Conducted Emission Limit

Frequency ranges (MHz)	Limit (dBμV)	
	QP	Average
0.15 ~ 0.5	66 – 56	56 – 46
0.5 ~ 5	56	46
5 ~ 30	60	50

Spec	Item	Requirement	Applicable
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [μ]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequency ranges.	☒
Test Setup		 Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.	
Procedure		- The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B. - The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. - The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable. - All other supporting equipment were powered separately from another main supply.	
Remark			
Result	☒ Pass ☐ Fail		

Test Report No.	16020759-FCC-R1
Page	10 of 36

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Data sample

Frequency (MHz)	Quasi-Peak (dBμV)	Limit (dBμV)	Margin (dB)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Factors (dB)
xxx	56.21	66.00	-9.79	39.20	56.00	-16.80	12.22

Frequency (MHz) = Emission frequency in MHz

Quasi-Peak/Average (dBμV)=Receiver Reading(dBμV)+ Factor(dB)


Limit(dBμV)=Limit stated in standard

Factor (dB)= cable loss+ Insertion loss of LISN+ Insertion loss of transient limiter (The transient limiter included 10dB attenuation)

Calculation Formula:

Margin (dB)=Quasi Peak / Average (dBμV) – limit (dBμV)

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBμV)	Limit (dBμV)	Margin (dB)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Factors (dB)
24.01	42.36	60.00	-17.64	36.53	50.00	-13.47	11.67
0.50	26.73	56.00	-29.27	21.35	46.00	-24.65	11.09
0.54	26.53	56.00	-29.47	21.13	46.00	-24.87	11.05
0.66	26.13	56.00	-29.87	21.02	46.00	-24.98	10.96
0.95	26.09	56.00	-29.91	21.30	46.00	-24.70	10.73
27.12	29.98	60.00	-30.02	29.51	50.00	-20.49	11.77

Test Mode: Transmitting Mode



Test Data

Phase Neutral Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBμV)	Limit (dBμV)	Margin (dB)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Factors (dB)
24.01	42.03	60.00	-17.97	36.15	50.00	-13.85	11.70
0.52	26.77	56.00	-29.23	21.26	46.00	-24.74	11.05
0.63	26.54	56.00	-29.46	21.39	46.00	-24.61	10.97
0.68	25.85	56.00	-30.15	20.87	46.00	-25.13	10.93
0.75	25.96	56.00	-30.04	20.87	46.00	-25.13	10.88
27.12	29.84	60.00	-30.16	29.33	50.00	-20.67	11.80

6.3 Fundamental Field Strength Test Result

Temperature	25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	July 22, 2016
Tested By :	Louise Tu

Requirement(s):

Spec	Item	Requirement	Applicable
§15.225(a) §15.225(b) §15.225(c)	a)	The field strength of any emissions within the band 13.553 –13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.	☒
	b)	The bands 13.410 –13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.	☐
	c)	The bands 13.110 –13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.	☐

Test Setup	
------------	--

Test Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: - Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen. - The EUT was then rotated to the direction that gave the maximum emission. - Finally, the antenna height was adjusted to the height that gave the maximum emission. - A peak measurement was then made for that frequency point. - Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
----------------	--

Remark	
--------	--

Result	☒ Pass ☐ Fail
--------	--

Test Data ☒ Yes


☒ N/A

Test Plot ☒ Yes


☐ N/A

Test Plots

Fundamental Field Strength Measurement Result:



Loop Antenna at 90 degree



Loop Antenna at 0 degree

6.4 Radiated Spurious Emissions

Temperature	25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	July 25, 2016
Tested By :	Louise Tu

Requirement(s):

Spec	Item	Requirement	Applicable																								
§15.225(d)	a)	The field strength of any emissions appearing outside of the 3.110–14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.	☒																								
		<table><tr><th>Fundamental frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100**</td><td>3</td></tr><tr><td>88-246</td><td>150**</td><td>3</td></tr><tr><td>216-960</td><td>200**</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table>		Fundamental frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100**	3	88-246	150**	3	216-960	200**	3	Above 960	500	3
		Fundamental frequency (MHz)		Field strength (microvolts/meter)	Measurement distance (meters)																						
		0.009-0.490		2400/F(kHz)	300																						
		0.490-1.705		24000/F(kHz)	30																						
		1.705-30.0		30	30																						
		30-88		100**	3																						
		88-246		150**	3																						
		216-960		200**	3																						
		Above 960		500	3																						

Test Setup	
------------	--

Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: - Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen. - The EUT was then rotated to the direction that gave the maximum emission. - Finally, the antenna height was adjusted to the height that gave the maximum emission. - A Quasi-peak measurement was then made for that frequency point. - Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
-----------	--

Remark	
Result	☒ Pass ☐ Fail

Test Report No.	16020759-FCC-R1
Page	16 of 36

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Data sample

Frequency (MHz)	Quasi Peak (dB μ V/m)	Azimuth	Polarity (H/V)	Height (cm)	Factors (dB)	Limit (dB μ V/m)	Margin (dB)
xxx	32.23	181.00	H	350.00	-38.23	40.00	-7.77

Frequency (MHz) = Emission frequency in MHz

Quais-Peak (dB μ V/m)= Receiver Reading(dB μ V/m)+ Factor(dB)

Azimuth=Position of turn table

Polarity=Polarity of Receiver antenna

Height(cm)= Height of Receiver antenna

Factor (dB)=Antenna factor + cable loss- antenna gain

Limit (dB μ V/m)=Limit stated in standard

Calculation Formula:

Margin (dB)=Quasi Peak (dB μ V/m) – limit (dB μ V/m)

Test Mode:	Transmitting
-------------------	---------------------

Loop Antenna at 0 degree:

@ 3M

Frequency	Peak (Corrected)	Factor	Height	Azimuth	Limits @ 3m	Margin
(MHz)	(dBμV/m)	(dB)	(cm)	(deg)	(dBμV/m)	(dB)
15.66	24.64	36.9	120	190	69.54	-44.90
27.12	28.03	37.2	109	177	69.54	-37.91
13.98	26.45	38.1	100	0	80.5	-54.05

Loop Antenna at 90 degree:


@ 3M

Frequency	Peak (Corrected)	Factor	Height	Azimuth	Limits @ 3m	Margin
(MHz)	(dBμV/m)	(dB)	(cm)	(deg)	(dBμV/m)	(dB)
27.12	25.04	37.2	109	178	69.54	-44.50
24.00	23.61	37.9	100	179	69.54	-45.93
1.81	20.72	52.4	133	177	69.54	-48.82

Test Mode:	Transmitting Mode
-------------------	--------------------------

Below 1GHz

Peak Detector 
Quasi Peak Limit 




Test Data

Vertical Polarity Plot at 3m

Frequency (MHz)	Quasi Peak (dBμV/m)	Azimuth	Polarity (H/V)	Height (cm)	Factors (dB)	Limit (dBμV/m)	Margin (dB)
379.71	30.75	204.00	V	100.00	-28.31	46.00	-15.25
722.21	31.25	359.00	V	105.00	-19.45	46.00	-14.75
199.24	27.15	18.00	V	105.00	-32.03	43.50	-16.35
791.14	24.78	358.00	V	156.00	-17.73	46.00	-21.22
821.93	29.02	67.00	V	173.00	-17.56	46.00	-16.98
406.85	28.82	136.00	V	154.00	-28.26	46.00	-17.18

Test Mode:	Transmitting Mode
-------------------	--------------------------

Below 1GHz



Horizontal Polarity Plot at 3m

Frequency (MHz)	Quasi Peak (dBμV/m)	Azimuth	Polarity (H/V)	Height (cm)	Factors (dB)	Limit (dBμV/m)	Margin (dB)
199.24	25.12	12.00	H	183.00	-31.54	43.50	-18.38
572.81	34.64	86.00	H	205.00	-22.65	46.00	-11.36
249.05	34.77	274.00	H	158.00	-28.59	46.00	-11.23
379.71	34.98	265.00	H	104.00	-28.59	46.00	-11.02
406.83	31.98	232.00	H	309.00	-28.00	46.00	-14.02
597.68	31.71	90.00	H	151.00	-20.89	46.00	-14.29


Note: The highest frequency of the internal sources of the EUT is less than 108MHz, so the measurement shall only be made up to 1GHz.

6.5 Frequency Stability

Temperature	25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	July 22, 2016
Tested By :	Louise Tu

Requirement(s):

Spec	Item	Requirement	Applicable
§15.225(e)	a)	The Frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20°C to +50°C at normal supply voltage.	☒
	b)	The frequency of the transmitter was measured at 85% and at 115% of the rated power supply voltage at 20°C environmental temperature.	☒

Test Setup	 <pre> graph LR SA[Spectrum Analyzer] --- EUT[EUT] subgraph Chamber [Temperature/Humidity Chamber] EUT end </pre>
------------	--

Test Procedure	1> Place the de-energized EUT in an environmental temperature test chamber. Supply the EUT with nominal ac voltage, or install a new or fully charged battery in the EUT. An antenna should be connected to the antenna output connector of the EUT if possible. Use of a dummy load could affect the output frequency of the EUT. If the EUT is equipped with or uses an adjustable-length antenna, it should be fully extended. 2> Turn the EUT on, and couple its output to a frequency counter or other frequency-measuring device of sufficient accuracy, considering the frequency tolerance with which the EUT shall comply. 3> Turn the EUT off, and place it inside an environmental chamber set to the highest temperature specified by the procuring or regulatory agency. For devices that are normally operated continuously, the EUT may be energized while inside the test chamber. For devices that have oscillator heaters, energize only the heater circuit while the EUT is inside the chamber. 4> Allow sufficient time (approximately 30 minutes) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the environmental chamber, turn the EUT on and measure the EUT operating frequency at startup, and two, five, and ten minutes after startup. Four measurements in total are made. 5> If 13.1.1 requires measurements on only one operating frequency, proceed to step f); otherwise, successively tune the EUT to each of the additional operating frequencies specified in 13.1.1 and repeat step d). 6> Repeat step d) and step e) with the temperature chamber set to the lowest temperature specified by the procuring or regulatory agency. Be sure to allow the environmental chamber temperature to stabilize before performing these measurements.
----------------	---

Test Report No.	16020759-FCC-R1
Page	21 of 36

Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes ☒ N/A

Carrier Frequency: 13.56MHz at -20°C to +50°C, DC12V

Temperature (oC)	Measured Freq. (MHz)	Freq. Drift (Hz)	Freq. Deviation (Limit: 0.01%)	Pass/Fail
50	13.56085	850	< 0.01	Pass
40	13.56084	840	< 0.01	Pass
30	13.56085	850	< 0.01	Pass
20	Reference			
10	13.56085	850	< 0.01	Pass
0	13.56085	850	< 0.01	Pass
-10	13.56086	860	< 0.01	Pass
-20	13.56085	850	< 0.01	Pass

Carrier Frequency: 13.56MHz at 20°C at DC12V

Measured Voltage $\pm 15\%$ of nominal	Measured Freq. (MHz)	Freq. Drift (Hz)	Freq. Deviation (Limit: 0.01%)	Pass/Fail
10.2	13.5610	1000	<0.01	Pass
13.8	13.5612	1200	<0.01	Pass

6.6 20dB Occupied Bandwidth

Temperature	25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
Test date :	July 22, 2016
Tested By :	Louise Tu

Requirement(s):

Spec	Item	Requirement	Applicable
§15.215(c)	a)	Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.	☒
Test Setup	Spectrum Analyzer EUT		
Test Procedure	<u>20dB Emission bandwidth measurement procedure</u> - Set RBW = 300 Hz. - Set the video bandwidth (VBW) ≥ 3 ´ RBW. - Detector = Peak. - Trace mode = max hold. - Sweep = auto couple. - Allow the trace to stabilize. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.		
Remark			
Result	☒ Pass ☐ Fail		

Test Report No.	16020759-FCC-R1
Page	23 of 36

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes ☐ N/A

20dB Bandwidth measurement result

Frequency (MHz)	20dB BW (kHz)	Frequency range (MHz) F Low	Frequency range (MHz) F High	Test Result
13.5609825	0.7775	13.5605825	13.561360	PASS

Test Plots

20dB Bandwidth measurement result



Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
RF Conducted Test					
R&S EMI Receiver	ESPI3	101216	03/31/2016	03/31/2017	☒
Power Splitter	1#	1#	02/02/2016	02/01/2017	☒
Agilent Technologies Spectrum Analyzer	N9010A	MY47191130	03/31/2016	03/31/2017	☒
Temperature/Humidity Chamber	1007H	N/A	01/07/2016	01/06/2017	☒
Radiated Emissions					
Agilent Technologies Spectrum Analyzer	N9010A	MY47191130	03/31/2016	03/31/2017	☒
R&S EMI Receiver	ESPI3	101216	03/31/2016	03/31/2017	☒
Antenna (30MHz~6GHz)	JB6	A121411	10/31/2015	10/31/2016	☒
EMCO Passive Loop Antenna	6509	9909-1469	10/09/2015	10/08/2016	☒
Hp Agilent Pre-Amplifier	8447F	1937A01160	10/27/2015	10/26/2016	☒
SIEMIC Radiated Labview Emissions software	V1.0	N/A	N/A	N/A	☒

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph EUT External Photo




Front View of EUT




Rear View of EUT

Test Report No.	16020759-FCC-R1
Page	26 of 36




Top View of EUT




Bottom View of EUT

Test Report No.	16020759-FCC-R1
Page	27 of 36



Left View of EUT



Right View of EUT


Annex B.ii. Photograph EUT Internal Photo




Uncover- Front View



Uncover- Rear View



EUT PCBA – Front View



13.56MHz
Antenna

EUT PCB – Rear View


Annex B.iii. Photograph Test Setup Photo




Conducted Emissions Setup Front View



Conducted Emissions Setup Side View



Front View of Radiated Emissions Test Setup below 30MHz




Front View of Radiated Emissions Test Setup (30MHz-1GHz)


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.i. TEST SET UP BLOCK

Block Configuration Diagram for Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Test Report No.	16020759-FCC-R1
Page	34 of 36

Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Manufacturer	Equipment Description	Model	Cal Date	Cal Due Date
BK PRECISION	DC Power Supply	1786B	N/A	N/A

Test Report No.	16020759-FCC-R1
Page	35 of 36

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Test Report No.	16020759-FCC-R1
Page	36 of 36

Annex E. DECLARATION OF SIMILARITY

N/A