



Prüfbericht-Nr.: Test Report No.:	15068732 001	Auftrags-Nr.: Order No.:	154036791	Seite 1 von 70 Page 1 of 70
Kunden-Referenz-Nr.: Client Reference No.:	460398	Auftragsdatum: Order date:	2013.10.17	
Auftraggeber: Client:	Amp'ed RF Technology Inc. 1879 Lundy Ave, Suite 138, San Jose, CA95131, USA			
Prüfgegenstand: Test item:	Bluetooth module			
Bezeichnung / Typ-Nr.: Identification / Type No.:	BT43 FCC ID :X3ZBTMOD7 IC :8828A-MOD7			
Auftrags-Inhalt: Order content:	Complete test			
Prüfgrundlage: Test specification:	FCC CFR47 Part 15, Subpart C, §15.247 ANSI C63.10-2009 ANSI C63.10-2009 KDB 558074 D01 DTS Meas Guidance v03 Public Notice DA 00-705: Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems (March 30, 2000)			
Wareneingangsdatum: Date of receipt:	17.10.2013			
Prüfmuster-Nr.: Test sample No.:	A000028691-001			
Prüfzeitraum: Testing period:	09.08.2013 – 01.03.2014			
Ort der Prüfung: Place of testing:	QuieTek Technology(Suzhou)Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von / tested by:		kontrolliert von / reviewed by:		
 11.03.2014 ShiLi / Project Engineer		 11.03.2014 Jesse huang / Project Manager		
Datum Date	Name / Stellung Name / Position	Unterschrift Signature	Datum Date	Name / Stellung Name / Position
Sonstiges / Other:				
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:		Prüfmuster vollständig und unbeschädigt Test item complete and undamaged		
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

V04

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 2 von 70
Page 2 of 70

TEST SUMMARY

3.2.1 VOLTAGE REQUIREMENTS, FCC 15.31(E)

RESULT: PASS

3.2.2 ANTENNA REQUIREMENTS, FCC 15.203, FCC 15.204 AND RSS-GEN 7.1.4

RESULT: PASS

5.1.1 CONDUCTED OUTPUT POWER, FCC 15.247(B)(1)& (3) AND RSS-210 A8.4(2)

RESULT: PASS

5.1.2 CARRIER FREQUENCY SEPARATION, FCC 15.247(A)(1) AND RSS-210 A8.1(B)

RESULT: PASS

5.1.3 20dB BANDWIDTH AND 6dB&99% BANDWIDTH, FCC 15.247(A)(1)& (2) AND RSS-210 A8.2(A)

5.1.4 NUMBER OF HOPPING FREQUENCIES, FCC 15.247(A)(1)(III) AND RSS-210 A8.1(D)

RESULT: PASS

5.1.5 AVERAGE TIME OF OCCUPANCY, FCC 15.247(A)(1)(III) AND RSS-210 A8.1(D)

RESULT: PASS

5.1.6 POWER SPECTRAL DENSITY (PSD), FCC 15.247(E) AND RSS-210 A8.2

RESULT: PASS

5.1.7 CONDUCTED SPURIOUS EMISSION, FCC 15.247(D) AND RSS-210 A8.5

RESULT: PASS

5.1.8 BAND EDGE COMPLIANCE OF RF CONDUCTED EMISSION, FCC 15.247(D) AND RSS-210 A8.5

RESULT: PASS

6.1.1 BAND EDGE RADIATED EMISSION, FCC 15.205, FCC 15.209, FCC 15.247(D), RSS-210 2.2, RSS-210 2.6 AND RSS-210 A8.5

RESULT: Pass

6.1.2 RADIATED SPURIOUS EMISSION OF TRANSMITTER, FCC 15.205, FCC 15.209, FCC 15.247(D), RSS-210 2.2, RSS-210 2.6 AND RSS-210 A8.5

RESULT: PASS

6.2.1 RADIATED SPURIOUS EMISSION OF RECEIVER, FCC 15.109, RSS-210 2.2, RSS-210 2.6, RSS-210 A8.5, RSS-GEN 7.2.3.2

RESULT: PASS

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 3 von 70
Page 3 of 70

CONTENTS

1.	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2.	TEST SITES	5
2.1	TEST FACILITIES	5
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS	6
2.3	MEASUREMENT UNCERTAINTY	6
3.	GENERAL PRODUCT INFORMATION	7
3.1	PRODUCT FUNCTION AND INTENDED USE	7
3.2	SYSTEM DETAILS	7
3.2.1	<i>Voltage Requirements, FCC 15.31(e)</i>	<i>7</i>
3.2.2	<i>Antenna Requirements, FCC 15.203, FCC 15.204 and RSS-Gen 7.1.4</i>	<i>8</i>
3.3	INDEPENDENT OPERATION MODES	8
3.4	NOISE SUPPRESSING PARTS	9
4.	TEST SET-UP AND OPERATION MODES	10
4.1	TEST METHODOLOGY	10
4.2	PHYSICAL CONFIGURATION FOR TESTING	10
4.3	TEST OPERATION AND TEST SOFTWARE	10
4.4	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	10
4.5	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	11
5.	TEST RESULTS OF CONDUCTED MEASUREMENTS AT ANTENNA PORT	12
5.1	TRANSMITTER PARAMETERS	12
5.1.1	<i>Conducted Output Power, FCC 15.247(b)(1)& (3) and RSS-210 A8.4(2)</i>	<i>12</i>
5.1.2	<i>Carrier Frequency Separation, FCC 15.247(a)(1) and RSS-210 A8.1(b)</i>	<i>19</i>
5.1.3	<i>20dB Bandwidth and 6dB&99% Bandwidth, FCC 15.247(a)(1)& (2) and RSS-210 A8.2(a)</i>	<i>22</i>
5.1.4	<i>Number of Hopping Frequencies, FCC 15.247(a)(1)(iii) and RSS-210 A8.1(d)</i>	<i>29</i>
5.1.5	<i>Average Time of Occupancy, FCC 15.247(a)(1)(iii) and RSS-210 A8.1(d)</i>	<i>32</i>
5.1.6	<i>Power Spectral Density (PSD), FCC 15.247(e) and RSS-210 A8.2</i>	<i>35</i>
5.1.7	<i>Conducted Spurious Emission, FCC 15.247(d) and RSS-210 A8.5</i>	<i>38</i>
5.1.8	<i>Band Edge Compliance of RF Conducted Emission, FCC 15.247(d) and RSS-210 A8.5</i>	<i>48</i>
6.	TEST RESULTS OF RADIATED MEASUREMENTS	52
6.1	TRANSMITTER PARAMETERS	52
6.1.1	<i>Band Edge Radiated Emission, FCC 15.205, FCC 15.209, FCC 15.247(d), RSS-210 2.2, RSS-210 2.6 and RSS-210 A8.5</i>	<i>52</i>
6.1.2	<i>Radiated Spurious Emission of Transmitter, FCC 15.205, FCC 15.209, FCC 15.247(d), RSS-210 2.2, RSS-210 2.6 and RSS-210 A8.5</i>	<i>63</i>
6.2	RECEIVER PARAMETERS	66

Prüfbericht - Nr.: 15068732 001

Test Report No.:

Seite 4 von 70

Page 4 of 70

6.2.1	<i>Radiated Spurious Emission of Receiver, FCC 15.109, RSS-210 2.2, RSS-210 2.6, RSS-210 A8.5, RSS-Gen 7.2.3.2</i>	<i>66</i>
7.	PHOTOGRAPHS OF THE TEST SETUP.....	67
8.	LIST OF TABLES.....	69
9.	LIST OF FIGURES	69
10.	LIST OF PHOTOGRAPHS.....	70

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 5 von 70
Page 5 of 70

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report.

2. Test Sites

2.1 Test Facilities

QuieTek Technology(Suzhou)Co.,Ltd.

No.99 Hongye RD.Suzhou Industnal Park Loufeng Hi-Tech Development
Zone.,Suzhou,China

The used test equipment is in accordance with CISPR 16 for measurement of radio
interference.

The Federal Communications Commission has reviewed the technical characteristics of
the radiated and conducted emission facility, and has found these test facilities to be in
compliance with the requirements of section 2.948 of the FCC rules. The description of
the test facility is listed under FCC registration number 800392.

The Industry Canada has reviewed the technical characteristics of the radiated and
conducted emission facility, and has found these test facilities to be in compliance. The
description of the test facility is listed under chambers filing number 4075B.

Prüfbericht - Nr.: 15068732 001

Test Report No.:

Seite 6 von 70

Page 6 of 70

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Equipment	Model	Serial no.	Cal. due date
3m modified semi-anechoic chamber	SAC	N/A	10.12.2014
EMI test receiver	ESCI	100280	08.11.2014
broadband antenna	BTA-H	040005H	28.07.2014
Spectrum analyzer	FSP30	100192	21.07.2014
Spectrum analyzer	E4440A	MY42510355	08.05.2014
Broadband coaxial preamplifier	BBV 9718	9718-012	04.07.2014
Double ridged broadband horn antenna	BBHA 9120 D	9120D-433	15.05.2014

2.3 Measurement Uncertainty

Table 2: Emission Measurement Uncertainty

Measurement Type	Frequency	Uncertainty
Antenna Port Conducted Emission	< 1GHz	±0.39dB
	> 1GHz	±0.68dB
Radiated Emission	30MHz - 1GHz	±5.34dB
	> 1GHz	±5.40dB

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 7 von 70
Page 7 of 70

3. General Product Information

3.1 Product Function and Intended Use

The EUT (Equipment Under Test) is a Bluetooth module.

3.2 System Details

Radio standard:	Bluetooth 4.0 dual mode
Max output power:	8.89dBm
Antenna gain:	0.5dBi
Antenna type:	Ceramic antenna
Antenna Manufactory:	Johanson Technology & ACX
Antenna cable length:	N/A
Frequency range:	2402 – 2480MHz
EDR Number of channels:	79
BLE Number of channels:	40
EDR Channel spacing:	1MHz
BLE Channel spacing:	2MHz
Modulation type:	EDR (GFSK; $\pi/4$ -DQPSK ;8DPSK) BLE (GFSK)
Rated voltage:	2.5V
Test voltage:	2.5V

3.2.1 Voltage Requirements, FCC 15.31(e)

RESULT:

PASS

All the tests were performed using steady DC 2.5V. Hence it complies with the power supply requirements.

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 8 von 70
Page 8 of 70

3.2.2 Antenna Requirements, FCC 15.203, FCC 15.204 and RSS-Gen 7.1.4

RESULT:

PASS

The EUT has an internal antenna which is not user accessible. Hence it complies with the requirements.

3.3 Independent Operation Modes

The EUT was tested on a stand-alone basis (only attached to the test jig) and the test system was configured in a typical fashion (as a customer would normally use it).

The justification and manipulation of cables and equipment in order to simulate a worst-case behavior of the test setup has been carried out as prescribed in ANSI C63.4:2009.

Bluetooth BDR and EDR mode :

Testing was performed at the lowest operating frequency (2402MHz), at the operating frequency in the middle of the specified frequency band (2441MHz) and at the highest operating frequency (2480MHz) with different modulation types.

Bluetooth LE 4.0 mode:

Testing was performed at the lowest operating frequency (2402MHz), at the operating frequency in the middle of the specified frequency band (2442MHz) and at the highest operating frequency (2480MHz) with different modulation types.

Bluetooth BDR and EDR mode basic operation in (GFSK; $\pi/4$ -DQPSK ;8DPSK) :

- A. EUT transmits (TX mode), with full power, at lowest channel (2402MHz), a continuous modulated signal streaming with 100% duty cycle.
- B. EUT transmits (TX mode), with full power, at middle channel (2441MHz), a continuous modulated signal streaming with 100% duty cycle.
- C. EUT transmits (TX mode), with full power, at highest channel (2480MHz), a continuous modulated signal streaming with 100% duty cycle.
- D. EUT receives (RX mode), at lowest channel (2402MHz), continuously.
- E. EUT receives (RX mode), at middle channel (2441MHz), continuously.
- F. EUT receives (RX mode), at highest channel (2480MHz), continuously.
- M. EUT transmits on pseudo-random sequence on all channels (hopping mode).

Bluetooth 4.0 BLE mode basic operation in :

- G. EUT transmits (TX mode), with full power, at lowest channel (2402MHz), a continuous modulated signal streaming with 100% duty cycle.

Prüfbericht - Nr.: 15068732 001

Test Report No.:

Seite 9 von 70

Page 9 of 70

- H. EUT transmits (TX mode), with full power, at middle channel (2442MHz), a continuous modulated signal streaming with 100% duty cycle.
- I. EUT transmits (TX mode), with full power, at highest channel (2480MHz), a continuous modulated signal streaming with 100% duty cycle.
- J. EUT receives (RX mode), at lowest channel (2402MHz), continuously.
- K. EUT receives (RX mode), at middle channel (2442MHz), continuously.
- L. EUT receives (RX mode), at highest channel (2480MHz), continuously.

3.4 Noise Suppressing Parts

Refer to schematics and internal photos.

4. Test Set-up and Operation Modes

4.1 Test Methodology

The test methodology used is based on the requirements of 47 CFR Part 15, Sections 15.31, 15.33, 15.35, 15.205, 15.207, 15.209

The test methods, which have been used, are based on ANSI C63.10-2009 and KDB 558074 D01 DTS Meas Guidance v03 and Public Notice DA 00-705 and ANSI C63.4-2009

For details, see under each test item.

Note : Bluetooth 4.0 BLE is following KDB 558074 D01 DTS Meas Guidance v03
Bluetooth 4.0 BDR and EDR is following Public Notice DA 00-705

4.2 Physical Configuration for Testing

The EUT was designed to get into related working mode with the control of a laptop computer through USB interface.

Notes:

Two test sample was available:

For antennas conducted measurements with 50Ω connector and radiated measurements.more details, refer to section: Photographs of the Test Set-Up.

4.3 Test Operation and Test Software

Software used for testing: Term_44

This software was running on the laptop computer connected to the EUT. It was used to enable the test operation modes listed in section 3.3 as appropriate.

4.4 Special Accessories and Auxiliary Equipment

The product has been tested together with a PCB Development kit (Control the module).

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 11 von 70
Page 11 of 70

4.5 Countermeasures to achieve EMC Compliance

No additional measures were employed to achieve compliance.

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 12 von 70
Page 12 of 70

5. Test Results of Conducted Measurements at Antenna Port

5.1 Transmitter Parameters

5.1.1 Conducted Output Power, FCC 15.247(b)(1)& (3) and RSS-210 A8.4(2)

RESULT:

PASS

Date of testing: 2013-12-19

Ambient temperature: 22.3°C

Relative humidity: 40.1%

Atmospheric pressure: 101.7hPa

Requirements:

For frequency hopping systems operating in the 2400-2483.5MHz band employing at least 75 non-overlapping hopping channels, the maximum peak output power shall be 1W (30dBm). For other hopping systems operating in the 2400-2483.5MHz band, the maximum peak output power shall be 0.125W (21dBm).

Test procedure:

ANSI C63.10-2009 and KDB 558074 D01 DTS Meas Guidance v03 and Public Notice DA 00-705 and ANSI C63.4-2009

The maximum peak output power (conducted) was measured at the antenna connector with a spectrum analyzer. The analyzer resolution bandwidth was set to 3MHz and the video bandwidth to 10MHz. The final measurement takes into account the loss generated by all the involved cables.

Prüfbericht - Nr.: 15068732 001

Test Report No.:


Seite 13 von 70

Page 13 of 70

Table 3: Conducted Output Power, Mode A

Data Rate [Mbps]	RBW [MHz]	Output Power [dBm]	Cable Loss [dBm]	Corrected Power [dBm]	Limit [dBm]
1	3	8.03	0.5	8.53	21
2	3	8.01	0.5	8.51	21
3	3	7.98	0.5	8.48	21

Figure 1: Conducted Output Power, Mode A



Prüfbericht - Nr.: 15068732 001

Test Report No.:


Seite 14 von 70

Page 14 of 70

Table 4: Conducted Output Power, Mode B

Data Rate [Mbps]	RBW [MHz]	Output Power [dBm]	Cable Loss [dBm]	Corrected Power [dBm]	Limit [dBm]
1	3	8.39	0.5	8.89	21
2	3	8.30	0.5	8.80	21
3	3	8.32	0.5	8.82	21

Figure 2: Conducted Output Power, Mode B



Prüfbericht - Nr.: 15068732 001

Test Report No.:


Seite 15 von 70

Page 15 of 70

Table 5: Conducted Output Power, Mode C

Data Rate [Mbps]	RBW [MHz]	Output Power [dBm]	Cable Loss [dBm]	Corrected Power [dBm]	Limit [dBm]
1	3	7.82	0.5	8.32	21
2	3	7.81	0.5	8.31	21
3	3	7.82	0.5	8.32	21

Figure 3: Conducted Output Power, Mode C




Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 16 von 70
Page 16 of 70

Table 6: Conducted Output Power, Mode G

RBW [MHz]	Output Power [dBm]	Cable Loss [dBm]	Corrected Power [dBm]	Limit [dBm]
3	6.12	0.5	6.62	30

Figure 4: Conducted Output Power, Mode G




Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 17 von 70
Page 17 of 70

Table 7: Conducted Output Power, Mode H

RBW [MHz]	Output Power [dBm]	Cable Loss [dBm]	Corrected Power [dBm]	Limit [dBm]
3	6.22	0.5	6.72	30

Figure 5: Conducted Output Power, Mode H



Prüfbericht - Nr.: 15068732 001

Test Report No.:


Seite 18 von 70

Page 18 of 70

Table 8: Conducted Output Power, Mode I

RBW [MHz]	Output Power [dBm]	Cable Loss [dBm]	Corrected Power [dBm]	Limit [dBm]
3	6.48	0.5	6.98	30

Figure 6: Conducted Output Power, Mode I



Remark:

The above results show that the BDR and EDR worst case output power is found at the data rate of 1Mbps. And the BLE worst case output power is High channel.

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 19 von 70
Page 19 of 70

5.1.2 Carrier Frequency Separation, FCC 15.247(a)(1) and RSS-210 A8.1(b)

RESULT:

PASS

Date of testing: 2013-12-19

Ambient temperature: 22.3°C
Relative humidity: 40.1%
Atmospheric pressure: 101.7hPa

Requirements:

Frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater. In case of an output power less than 125mW, the frequency hopping system may have channels separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

Test procedure:

ANSI C63.4-2009 and Public Notice DA 00-705.

A spectrum analyzer

was connected to the antenna port of the EUT. The analyzer resolution bandwidth was set to 30kHz and the video bandwidth to 100kHz. The Delta Marker function was used to determine the separation between the peaks of two adjacent channels.

Prüfbericht - Nr.: 15068732 001

Test Report No.:

Seite 20 von 70


Page 20 of 70

Table 9: Carrier Frequency Separation

Channel	Channel Separation [kHz]	20dB Bandwidth [kHz](8DPSK)	Limit [kHz]
Low	1002	1116	744
Middle	1020	1128	752
High	1001	1116	744

Notes: Limit = 20dB bandwidth * 2/3 since it is greater than 25kHz and the output power is less than 125mW.


Figure 7: Carrier Frequency Separation-Low Channel



Prüfbericht - Nr.: 15068732 001
Test Report No.:


Seite 21 von 70
Page 21 of 70

Figure 8: Carrier Frequency Separation-Middle Channel



Date: 10.JAN.2014 01:06:57

Figure 9: Carrier Frequency Separation-High Channel



Date: 10.JAN.2014 01:12:49

Prüfbericht - Nr.: 15068732 001

Test Report No.:

Seite 22 von 70

Page 22 of 70

5.1.3 20dB Bandwidth and 6dB&99% Bandwidth, FCC 15.247(a)(1)& (2) and RSS-210 A8.2(a)

Date of testing: 2013-12-19

Ambient temperature: 22.3°C

Relative humidity: 40.1%

Atmospheric pressure: 101.7hPa

Requirements:

For frequency hopping systems operating in the 2400-2483.5MHz band, no bandwidth limit is specified. Test data is provided for reference.

Test procedure:

ANSI C63.10-2009 and KDB 558074 D01 DTS Meas Guidance v03 and Public Notice DA 00-705 and ANSI C63.4-2009

A spectrum analyzer was connected to the antenna port of the EUT. The spectrum analyzer resolution bandwidth was set to 100kHz, the video bandwidth to 300kHz and the span to 2MHz.

Prüfbericht - Nr.: **15068732 001**

Test Report No.:


Seite 23 von 70

Page 23 of 70

Table 10: 20dB &99% Bandwidth (bluetooth 4.0 BDR and EDR)

Operating Frequency [MHz]	20dB Bandwidth [kHz](8DPSK)	20dB Bandwidth [kHz](GFSK)	99% Bandwidth [kHz](8DPSK)	99% Bandwidth [kHz](GFSK)
2402	1116	796	1080	844
2441	1128	844	1080	844
2480	1116	828	1068	848


Figure 10: 20dB &99% Bandwidth, Mode A (2402MHz 8DPSK and GFSK)



8DPSK


Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 24 von 70
Page 24 of 70



GFSK

Figure 11: 20dB Bandwidth, Mode B (2441MHz 8DPSK and GFSK)




Date: 10.JAN.2014 03:02:34

8DPSK


Prüfbericht - Nr.: **15068732 001**
Test Report No.:

Seite 25 von 70
Page 25 of 70



GFSK


Figure 12: 20dB Bandwidth, Mode C (2480MHz 8DPSK and GFSK)



8DPSK

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 26 von 70
Page 26 of 70




GFSK

Table 11: 6dB&99% Bandwidth (Bluetooth 4.0 BLE)


Operating Frequency [MHz]	99%dB Bandwidth[KHz]	6dB Bandwidth[KHz] limit 500KHz
2402	1098	666
2442	1086	666
2480	1086	672

Figure 13: 6dB &99%Bandwidth, Mode G



Date: 1.JAN.2000 04:47:37

Figure 14: 6dB &99%Bandwidth, Mode H




Date: 1.JAN.2000 05:13:56

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 28 von 70
Page 28 of 70

Figure 15: 6dB & 99% Bandwidth, Mode I



Date: 1.JAN.2000 05:37:09

Prüfbericht - Nr.: 15068732 001

Test Report No.:

Seite 29 von 70

Page 29 of 70

5.1.4 Number of Hopping Frequencies, FCC 15.247(a)(1)(iii) and RSS-210 A8.1(d)

RESULT:

PASS

Date of testing: 2013-12-19

Ambient temperature: 22.3°C

Relative humidity: 40.1%

Atmospheric pressure: 101.7hPa

Requirements:

Frequency hopping systems operating in the 2400-2483.5MHz band shall use at least 15 channels.

Test procedure:

ANSI C63.4-2009 and Public Notice DA 00-705.

A spectrum analyzer was connected to the antenna port of the EUT. The analyzer resolution bandwidth was set to 300kHz and video bandwidth was set to 1MHz. The spectrum was broken in three plots to show all the hopping frequencies.

Prüfbericht - Nr.: 15068732 001

Test Report No.:


Seite 30 von 70

Page 30 of 70

Table 12: Number of Hopping Frequencies


Number of Hopping Frequencies	Limit	BDR AND EDR
79	15	BLE
Number of Hopping Frequencies	Limit	
40	15	

Figure 16: Hopping Frequencies BDR and EDR



Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 31 von 70
Page 31 of 70



Prüfbericht - Nr.: 15068732 001

Test Report No.:

Seite 32 von 70

Page 32 of 70

5.1.5 Average Time of Occupancy, FCC 15.247(a)(1)(iii) and RSS-210 A8.1(d)

RESULT:

PASS

Date of testing: 2014-1-10

Ambient temperature: 22.3°C

Relative humidity: 40.1%

Atmospheric pressure: 101.7hPa

Requirements:

For frequency hopping systems operating in the 2400-2483.5MHz band, the average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

Test procedure:

ANSI C63.4-2009 and Public Notice DA 00-705.

A spectrum analyzer was connected to the antenna port of the EUT. The analyzer resolution bandwidth and video bandwidth were set to 1MHz. The average time of occupancy was obtained by measuring first the dwell time of a single packet with the Delta Marker function using a zero span centered on a hopping channel and by counting then the number of hops per channel in a 31.6s period (0.4s times the number of hopping channels).

Prüfbericht - Nr.: 15068732 001
Test Report No.:


Seite 33 von 70
Page 33 of 70

Table 13: Average Time of Occupancy

Channel	Packet Type	Packet Duration [ms]	Number of Hops per Channel in a 31.6s Period	Average Time of Occupancy [ms]	Limit [ms]
Low	1M-DH5	2.91	106.81	310.81	400
Mid	1M-DH5	2.91	106.81	310.81	400
High	1M-DH5	2.91	106.81	310.81	400

Notes: Average time of occupancy = Packet duration * Number of hops per channel in a 31.6s period

Figure 17: Dwell Time, Mode (Hopping), 1M-DH5, Low channel




Date: 10.JAN.2014 04:15:51

Prüfbericht - Nr.: 15068732 001
Test Report No.:


Seite 34 von 70
Page 34 of 70

Figure 18: Dwell Time, Mode (Hopping), 1M-DH5, Mid channel



Date: 10.JAN.2014 04:14:59

Figure 19: Dwell Time, Mode (Hopping), 1M-DH5, High channel



Date: 10.JAN.2014 04:13:47

Prüfbericht - Nr.: 15068732 001

Test Report No.:

Seite 35 von 70

Page 35 of 70

5.1.6 Power Spectral Density (PSD), FCC 15.247(e) and RSS-210 A8.2

RESULT:

PASS

Date of testing: 2013-12-19

Ambient temperature: 22.3°C

Relative humidity: 40.1%

Atmospheric pressure: 101.7hPa

Requirements:

According to FCC section 15.247(e) and RSS-A8.2(b), the same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

Test procedure:

KDB 558074 D01 DTS Meas Guidance v03

A spectrum analyzer was connected to the antenna port of the EUT. The analyzer resolution bandwidth was set to 3kHz.

The final measurement takes into account the loss generated by all the involved cables.


Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 36 von 70
Page 36 of 70

Table 14: Power spectral density

Frequency [MHz]	PSD [dBm/3KHz]	Limit [dBm/3kHz]
Low	-20.48	8
Middle	-18.03	8
High	-17.16	8

Figure 20: Power spectral density, Mode G




Date: 1.JAN.2000 06:08:15

Prüfbericht - Nr.: 15068732 001
Test Report No.:


Seite 37 von 70
Page 37 of 70

Figure 21: Power spectral density, Mode H



Date: 1.JAN.2000 07:21:01

Figure 22: Power spectral density, Mode I



Date: 1.JAN.2000 05:38:01

Prüfbericht - Nr.: 15068732 001

Test Report No.:

Seite 38 von 70

Page 38 of 70

5.1.7 Conducted Spurious Emission, FCC 15.247(d) and RSS-210 A8.5

RESULT:

PASS

Date of testing: 2013-12-19

Ambient temperature: 22.3°C

Relative humidity: 40.1%

Atmospheric pressure: 101.7hPa

Requirements:

In any 100kHz bandwidth outside the frequency band, the RF power shall be at least 20dB below that of the maximum in-band 100kHz emission.

Test procedure:

ANSI C63.10-2009, RSS-Gen 4.9 and KDB 558074 D01 DTS Meas Guidance v03

Public Notice DA 00-705.

.

A spectrum analyzer was connected to the antenna port of the EUT. The analyzer resolution bandwidth was set to 100kHz. For each channel investigated, the in-band and out-of-band emission measurements were performed. The out-of-band emissions were measured from 30MHz to 25GHz (10th harmonics).

The final measurement takes into account the loss generated by all the involved cables.

Prüfbericht - Nr.: 15068732 001
Test Report No.:


Seite 39 von 70
Page 39 of 70

Table 15: Conducted Spurious Emission, Mode A

Frequency [MHz]	Reading [dBm]	Cable Loss [dBm]	Emission Level [dBm]	Limit [dBm]	Margin [dB]
24210	-45.33	0.5	-44.83	-15.4	29.43
4806	-43.38	0.5	-42.88	-15.4	27.48
2398	4.62	0.5	5.12	N/A	N/A

Notes: Limit = Reading of fundamental + Correction factor – 20dB

Figure 23: Conducted Spurious Emission, 30MHz – 6GHz, Mode A



Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 40 von 70
Page 40 of 70

Figure 24: Conducted Spurious Emission, 6 – 26GHz, Mode A




Table 16: Conducted Spurious Emission, Mode B

Frequency [MHz]	Reading [dBm]	Cable Loss [dBm]	Emission Level [dBm]	Limit [dBm]	Margin [dB]
7330	-44.80	0.5	-44.30	-15	29.3
4886	-43.74	0.5	-43.24	-15	28.24
2438	4.96	0.5	5.46	NA	N/A

Notes: Limit = Reading of fundamental + Correction factor – 20dB

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 41 von 70
Page 41 of 70

Figure 25: Conducted Spurious Emission, 30MHz – 6GHz, Mode B





Figure 26: Conducted Spurious Emission, 6 – 26GHz, Mode B



Prüfbericht - Nr.: 15068732 001
Test Report No.:


Seite 42 von 70
Page 42 of 70

Table 17: Conducted Spurious Emission, Mode C

Frequency [MHz]	Reading [dBm]	Cable Loss [dBm]	Emission Level [dBm]	Limit [dBm]	Margin [dB]
7420	-42.14	0.5	-41.64	-15.1	26.54
4955	-43.32	0.5	-42.82	-15.1	27.72
2478	4.88	0.5	5.38	N/A	N/A

Notes: Limit = Reading of fundamental + Correction factor – 20dB

Figure 27: Conducted Spurious Emission, 30MHz – 6GHz, Mode C



Prüfbericht - Nr.: 15068732 001

Test Report No.:

Seite 43 von 70

Page 43 of 70

Figure 28: Conducted Spurious Emission, 6 – 26GHz, Mode C




Table 18: Conducted Spurious Emission, Mode G

Frequency [MHz]	Reading [dBm]	Cable Loss [dBm]	Emission Level [dBm]	Limit [dBm]	Margin [dB]
7330	-43.87	0.5	-43.37	-17.9	25.47
4806	-42.69	0.5	-42.19	-17.9	24.29
2402	2.09	0.5	2.59	N/A	N/A

Notes: Limit = Reading of fundamental + Correction factor – 20dB

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 44 von 70
Page 44 of 70

Figure 29: Conducted Spurious Emission, 30MHz – 6GHz, Mode G





Figure 30: Conducted Spurious Emission, 6 – 26GHz, Mode G



Prüfbericht - Nr.: 15068732 001
Test Report No.:


Seite 45 von 70
Page 45 of 70

Table 19: Conducted Spurious Emission, Mode H

Frequency [MHz]	Reading [dBm]	Cable Loss [dBm]	Emission Level [dBm]	Limit [dBm]	Margin [dB]
7420	-43.28	0.5	-42.78	-17.6	25.18
4886	-43.18	0.5	-42.68	-17.6	25.08
2442	2.38	0.5	2.88	NA	N/A

Notes: Limit = Reading of fundamental + Correction factor – 20dB

Figure 31: Conducted Spurious Emission, 30MHz – 6GHz, Mode H



Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 46 von 70
Page 46 of 70

Figure 32: Conducted Spurious Emission, 6 – 26GHz, Mode H




Table 20: Conducted Spurious Emission, Mode I

Frequency [MHz]	Reading [dBm]	Cable Loss [dBm]	Emission Level [dBm]	Limit [dBm]	Margin [dB]
7420	-43.28	0.5	-42.88	-17.8	24.98
4955	-43.75	0.5	-43.25	-17.8	25.45
2480	2.24	0.5	2.74	N/A	N/A

Notes: Limit = Reading of fundamental + Correction factor – 20dB

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 47 von 70
Page 47 of 70

Figure 33: Conducted Spurious Emission, 30MHz – 6GHz, Mode I





Figure 34: Conducted Spurious Emission, 6 – 26GHz, Mode I



Prüfbericht - Nr.: 15068732 001

Test Report No.:

Seite 48 von 70

Page 48 of 70

5.1.8 Band Edge Compliance of RF Conducted Emission, FCC 15.247(d) and RSS-210 A8.5

RESULT:

PASS

Date of testing: 2013-4-12

Ambient temperature: 20°C

Relative humidity: 39.6%

Atmospheric pressure: 101.5hPa

Requirements:

In any 100kHz bandwidth outside the frequency band, the RF power shall be at least 20dB below that of the maximum in-band 100kHz emission.

Test procedure:

ANSI C63.10-2009 and KDB 558074 D01 DTS Meas Guidance v03 and Public Notice DA 00-705.

A spectrum analyzer was connected to the antenna port of the EUT. The analyzer resolution bandwidth was set to 100kHz and video bandwidth was set to 300kHz. Allow the trace to stabilize. Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.

The final measurement takes into account the loss generated by all the involved cables.

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 49 von 70
Page 49 of 70

Figure 35: Lower Band Edge Conducted Mode A





Figure 36: Upper Band Edge Conducted Mode C



Prüfbericht - Nr.: 15068732 001

Test Report No.:

Seite 50 von 70

Page 50 of 70

Figure 37: Lower Band Edge Conducted Mode A(Hopping)






Figure 38: Lower Band Edge Conducted Mode C(Hopping)



Prüfbericht - Nr.: 15068732 001
Test Report No.:


Seite 51 von 70
Page 51 of 70

Figure 39: Lower Band Edge Conducted Mode G



Date: 1.JAN.2000 06:03:23

Figure 40: Lower Band Edge Conducted Mode I



Date: 1.JAN.2000 06:01:42

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 52 von 70
Page 52 of 70

6. Test Results of Radiated Measurements

6.1 Transmitter Parameters

6.1.1 Band Edge Radiated Emission, FCC 15.205, FCC 15.209, FCC 15.247(d), RSS-210 2.2, RSS-210 2.6 and RSS-210 A8.5

RESULT:

Pass

Date of testing: 2014-1-12

Ambient temperature: 22.3°C

Relative humidity: 40.1%

Atmospheric pressure: 101.7hPa

Measurement distance: 3m

Kind of test site: Semi Anechoic Chamber

Requirements:

Radiated emissions which fall in the restricted bands, as defined in FCC 15.205(a) and RSS-210 2.7 (Table 1), must comply with the radiated emission limits specified in FCC 15.209(a) and RSS-210 2.7 (Table 2 and 3).

Test procedure:

ANSI C63.10-2009, RSS-Gen 4.9 and KDB 558074 D01 DTS Meas Guidance v03
Public Notice DA 00-705.

The EUT was placed on a nonconductive turntable 0.8m above the ground plane. Measurements were made at 3m distance. The EUT was rotated 360° and the antenna was raised and lowered from 1 to 4m in order to determine the emission's maximum level.

Measurements were taken using both horizontal and vertical antenna polarization. The rotation through the three orthogonal axes is normally not needed for equipment that is not hand-held or body-worn. The EUT was pretested in floor-standing condition and in the table position and the worst case condition was table position which was used for the final measurements.

Measurements were performed using a spectrum analyzer with a suitable span to encompass the peak of the fundamental and using the following settings: Peak: RBW & VBW = 1MHz, Average: RBW = 1MHz, VBW = 10Hz.

The highest emission amplitudes relative to the appropriate limit were measured and recorded in this report.

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 53 von 70
Page 53 of 70

Table 21: Band Edge Radiated Emission

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Horizontal	2390	61.435	25.993	-12.565	74	35.442	PK
2	Horizontal	2399.898	62.224	26.702	-11.776	74	35.522	PK
3	Horizontal	2402.214	81.123	45.581	N/A	N/A	35.542	PK

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Horizontal	2390	45.567	10.125	-8.433	54	35.442	AV
2	Horizontal	2399.898	45.543	10.021	-8.457	54	35.522	AV
3	Horizontal	2401.885	76.546	41.007	N/A	N/A	35.539	AV

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Vertical	2390	63.456	28.674	-10.544	74	34.782	PK
2	Vertical	2399.898	62.567	27.744	-11.433	74	34.823	PK
3	Vertical	2402.026	80.585	45.753	N/A	N/A	34.832	PK

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Vertical	2390	48.345	13.563	-5.655	54	34.782	AV
2	Vertical	2399.898	45.563	10.74	-8.437	54	34.823	AV
3	Vertical	2401.744	75.541	40.71	N/A	N/A	34.831	AV

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Horizontal	2479.848	85.548	49.362	N/A	N/A	36.186	PK
2	Horizontal	2483.5	64.378	28.161	-9.622	74	36.217	PK
3	Horizontal	2484.9	64.571	28.343	-9.429	74	36.228	PK

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Horizontal	2479.881	75.647	39.459	N/A	N/A	36.188	AV
2	Horizontal	2483.5	47.569	11.352	-6.431	54	36.217	AV
3	Horizontal	2484.9	47.654	11.426	-6.346	54	36.228	AV

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Vertical	2479.782	84.436	49.269	N/A	N/A	35.167	PK
2	Vertical	2483.5	62.435	27.252	-11.565	74	35.183	PK
3	Vertical	2484.9	62.453	27.264	-11.547	74	35.189	PK

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Vertical	2479.914	77.345	42.177	N/A	N/A	35.168	AV
2	Vertical	2483.5	48.431	13.248	-5.569	54	35.183	AV
3	Vertical	2484.9	46.345	11.156	-7.655	54	35.189	AV

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 54 von 70
Page 54 of 70

Table 22: Band Edge Radiated Emission (BLE)

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Horizontal	2390	63.467	28.025	-10.533	74	35.442	PK
2	Horizontal	2399.898	64.356	28.834	-9.644	74	35.522	PK
3	Horizontal	2402.073	83.976	48.435	N/A	N/A	35.541	PK

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Horizontal	2390	46.567	11.125	-7.433	54	35.442	AV
2	Horizontal	2399.898	49.412	13.89	-4.588	54	35.522	AV
3	Horizontal	2402.026	71.456	35.916	N/A	N/A	35.54	AV

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Vertical	2390	63.565	28.783	-10.435	74	34.782	PK
2	Vertical	2399.898	62.456	27.633	-11.544	74	34.823	PK
3	Vertical	2402.12	83.567	48.734	N/A	N/A	34.833	PK

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Vertical	2390	46.562	11.78	-7.438	54	34.782	AV
2	Vertical	2399.898	48.562	13.739	-5.438	54	34.823	AV
3	Vertical	2402.026	71.564	36.732	N/A	N/A	34.832	AV

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Horizontal	2479.947	84.564	48.376	N/A	N/A	36.188	PK
2	Horizontal	2483.5	63.458	27.241	-10.542	74	36.217	PK
3	Horizontal	2484.9	63.427	27.199	-10.573	74	36.228	PK

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Horizontal	2479.98	74.458	38.27	N/A	N/A	36.188	AV
2	Horizontal	2483.5	49.431	13.214	-4.569	54	36.217	AV
3	Horizontal	2484.9	49.563	13.335	-4.437	54	36.228	AV

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Vertical	2479.98	83.541	48.372	N/A	N/A	35.169	PK
2	Vertical	2483.5	63.538	28.355	-10.462	74	35.183	PK
3	Vertical	2484.9	62.443	27.254	-11.557	74	35.189	PK

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Vertical	2479.98	70.345	35.176	N/A	N/A	35.169	AV
2	Vertical	2483.5	48.453	13.27	-5.547	54	35.183	AV
3	Vertical	2484.9	48.541	13.352	-5.459	54	35.189	AV


Notes: All correction factors (antenna, cable, pre-amplifier) are included in the measurement values.
Average limit in dBuV/m is calculated as follows: Average limit = 20 x log(500uV/m).
Peak limit in dBuV/m is calculated as follows: Peak limit = Average limit + 20dB.

Prüfbericht - Nr.: 15068732 001
Test Report No.:


Seite 55 von 70
Page 55 of 70

Figure 41: Band Edge Radiated Emission, Spectral Diagram, Mode A

Horizontal-PK




Horizontal-AV




Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 56 von 70
Page 56 of 70

Vertical-PK



Vertical-AV




Note: The upper diagram shows the vertical peak value and the lower diagram shows the horizontal value.

Prüfbericht - Nr.: 15068732 001
Test Report No.:


Seite 57 von 70
Page 57 of 70

Figure 42: Band Edge Radiated Emission, Spectral Diagram, Mode C

Horizontal-PK




Horizontal-AV




Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 58 von 70
Page 58 of 70

Vertical -PK



Vertical -AV




Note: The upper diagram shows the vertical peak value and the lower diagram shows the horizontal value.

Prüfbericht - Nr.: 15068732 001
Test Report No.:


Seite 59 von 70
Page 59 of 70

Figure 43: Band Edge Radiated Emission, Spectral Diagram, Mode G

Horizontal-PK




Horizontal-AV




Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 60 von 70
Page 60 of 70

Vertical -PK



Vertical -AV




Note: The upper diagram shows the vertical peak value and the lower diagram shows the horizontal value.

Prüfbericht - Nr.: 15068732 001
Test Report No.:


Seite 61 von 70
Page 61 of 70

Figure 44: Band Edge Radiated Emission, Spectral Diagram, Mode I

Horizontal-PK




Horizontal-AV




Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 62 von 70
Page 62 of 70

Vertical -PK



Vertical -AV



Note: The upper diagram shows the vertical peak value and the lower diagram shows the horizontal value.

Prüfbericht - Nr.: 15068732 001

Test Report No.:

Seite 63 von 70

Page 63 of 70

6.1.2 Radiated Spurious Emission of Transmitter, FCC 15.205, FCC 15.209, FCC 15.247(d), RSS-210 2.2, RSS-210 2.6 and RSS-210 A8.5

RESULT:

PASS

Date of testing: 2013-12-19

Ambient temperature: 22.3°C

Relative humidity: 40.1%

Atmospheric pressure: 101.7hPa

Frequency range: 30MHz – 25GHz

Measurement distance: 3m

Kind of test site: Semi Anechoic Chamber

Requirements:

Radiated emissions which fall in the restricted bands, as defined in FCC 15.205(a) and RSS-210 2.7 (Table 1), must comply with the radiated emission limits specified in FCC 15.209(a) and RSS-210 2.7 (Table 2 and 3).

Test procedure:

ANSI C63.10-2009, RSS-Gen 4.9 and KDB 558074 D01 DTS Meas Guidance v03 And Public Notice DA 00-705.

The EUT was placed on a nonconductive turntable 0.8m above the ground plane. Before final measurements of radiated emissions were performed, the EUT was scanned to determine its emission spectrum profile. The EUT was pretested in floor-standing condition and in the table position and the worst case condition was table position which was used for the final measurements. The rotation through the three orthogonal axes is normally not needed for equipment that is not hand-held or body-worn.

The spectrum was examined from 30MHz to the 10th harmonic of the highest fundamental transmitter frequency (25GHz). Final radiated emission measurements were made at 3m distance.

At each frequency where a spurious emission was found, the EUT was rotated 360° and the antenna was raised and lowered from 1 to 4m in order to determine the emission's maximum level. Measurements were taken using both horizontal and vertical antenna polarizations.

For frequencies between 30MHz and 1GHz, the spectrum analyzer's 6 dB bandwidth was set to 120 kHz, and the analyzer was operated in the CISPR quasi-peak detection mode. For emissions above 1GHz, measurements were performed using the following settings: Peak: RBW & VBW = 1MHz, Average: RBW = 1MHz, VBW = 10Hz.

The highest emission amplitudes relative to the appropriate limit were recorded in this report. Emissions other than those mentioned are small or not detectable.

Prüfbericht - Nr.: 15068732 001

Test Report No.:

Seite 64 von 70

Page 64 of 70

Table 23: Radiated Emission, Average and Peak Data, 1 – 25GHz, Horizontal and Vertical Antenna Orientations, Mode A (2402MHz)

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Horizontal	7618.8	42.92	10.93	-31.08	74	31.99	PK
2	Vertical	7818.4	44.73	12.4	-29.27	74	32.33	PK

Note: All correction factors (antenna, cable, pre-amplifier) are included in the measurement values.

Table 24: Radiated Emission, Average and Peak Data, 1 – 25GHz, Horizontal and Vertical Antenna Orientations, Mode B (2441MHz)

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Horizontal	7618.4	42.47	10.48	-31.53	74	31.99	PK
2	Vertical	7818.1	42.46	10.14	-31.54	74	32.32	PK

Table 25: Radiated Emission, Average and Peak Data, 1 – 25GHz, Horizontal and Vertical Antenna Orientations, Mode C (2442MHz)

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Horizontal	7618.5	42.56	10.57	-31.44	74	31.99	PK
2	Vertical	7818.2	42.97	10.63	-31.03	74	32.34	PK

Table 26: Radiated Emission, Average and Peak Data, 1 – 25GHz, Horizontal and Vertical Antenna Orientations, Mode G (2402MHz)

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Horizontal	7618.8	42.12	10.13	-31.88	74	31.99	PK
2	Vertical	7818.3	42.56	10.22	-31.44	74	32.34	PK

Note: All correction factors (antenna, cable, pre-amplifier) are included in the measurement values.

Table 27: Radiated Emission, Average and Peak Data, 1 – 25GHz, Horizontal and Vertical Antenna Orientations, Mode H (2442MHz)

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Horizontal	7618.5	42.45	10.46	-31.55	74	31.99	PK
2	Vertical	7818.5	42.57	10.24	-31.43	74	32.33	PK

Prüfbericht - Nr.: 15068732 001

Test Report No.:

Seite 65 von 70

Page 65 of 70

Table 28: Radiated Emission, Average and Peak Data, 1 – 25GHz, Horizontal and Vertical Antenna Orientations, Mode I (2442MHz)

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	Horizontal	7618.23	42.49	10.52	-31.51	74	31.97	PK
2	Vertical	7818.45	42.67	10.36	-31.33	74	32.31	PK

Note: All correction factors (antenna, cable, pre-amplifier) are included in the measurement values. Above 18 GHz emission far below limit

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 66 von 70
Page 66 of 70

6.2 Receiver Parameters

6.2.1 Radiated Spurious Emission of Receiver, FCC 15.109, RSS-210 2.2, RSS-210 2.6, RSS-210 A8.5, RSS-Gen 7.2.3.2

RESULT:

PASS

Date of testing:	2013-12-19
Ambient temperature:	22.3°C
Relative humidity:	40.1%
Atmospheric pressure:	101.7hPa
Frequency range:	30MHz – 12.5GHz
Measurement distance:	3m
Kind of test site:	Semi Anechoic Chamber

Requirements:

The emissions from the unintentional radiator shall not exceed the field strength specified in 15.109(a) and RSS-210 Table 2 (and RSS-Gen Table 1).

Test procedure:

ANSI C63.4-2009 and RSS-Gen 4.10.

The EUT was placed on a nonconductive turntable 0.8m above the ground plane. Before final measurements of radiated emissions were performed, the EUT was scanned to determine its emission spectrum profile. The EUT was pretested in floor-standing condition and in the table position and the worst case condition was table position which was used for the final measurements. The rotation through the three orthogonal axes is normally not needed for equipment that is not hand-held or body-worn. The spectrum was examined from 30MHz to the 5th harmonic of the highest fundamental operation frequency (12.5GHz). Final radiated emission measurements were made at 3m distance.

Measurements were taken using both horizontal and vertical antenna polarizations.

For frequencies between 30MHz and 1GHz, the spectrum analyzer's 6 dB bandwidth was set to 120 kHz, and the analyzer was operated in the CISPR quasi-peak detection mode. For emissions above 1GHz, measurements were performed using the following settings: Peak: RBW & VBW = 1MHz, Average: RBW = 1MHz, VBW = 10Hz. The highest emission amplitudes relative to the appropriate limit were recorded in this report. No spurious emission was found in the range 30MHz – 12500MHz. emission in mode D, E, F ,J,K,L. all signals found in the pre-testing were more than 20 dB below the limit .

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 67 von 70
Page 67 of 70

7. Photographs of the Test Setup


Photograph 1: Set-up for Conducted RF test at Antenna Port




Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 68 von 70
Page 68 of 70

Photograph 2: Set-up for Radiated Emission, 30MHz-1000MHz



Photograph 3: Set-up for Radiated Spurious Emission, Above 1GHz



8. List of Tables

Table 1: List of Test and Measurement Equipment	6
Table 2: Emission Measurement Uncertainty	6
Table 3: Conducted Output Power, Mode A	13
Table 4: Conducted Output Power, Mode B	14
Table 5: Conducted Output Power, Mode C	15
Table 6: Conducted Output Power, Mode G	16
Table 7: Conducted Output Power, Mode H	17
Table 8: Conducted Output Power, Mode I	18
Table 9: Carrier Frequency Separation	20
Table 10: 20dB &99% Bandwidth (bluetooth 4.0 BDR and EDR)	23
Table 11: 6dB&99% Bandwidth (Bluetooth 4.0 BLE)	26
Table 12: Number of Hopping Frequencies	30
Table 13: Average Time of Occupancy	33
Table 14: Power spectral density	36
Table 15: Conducted Spurious Emission, Mode A.....	39
Table 16: Conducted Spurious Emission, Mode B.....	40
Table 17: Conducted Spurious Emission, Mode C	42
Table 18: Conducted Spurious Emission, Mode G	43
Table 19: Conducted Spurious Emission, Mode H	45
Table 20: Conducted Spurious Emission, Mode I	46
Table 21: Band Edge Radiated Emission	53
Table 22: Band Edge Radiated Emission (BLE)	54
Table 23: Radiated Emission, Average and Peak Data, 1 – 25GHz, Horizontal and Vertical Antenna Orientations, Mode A (2402MHz)	64
Table 24: Radiated Emission, Average and Peak Data, 1 – 25GHz, Horizontal and Vertical Antenna Orientations, Mode B (2441MHz)	64
Table 25: Radiated Emission, Average and Peak Data, 1 – 25GHz, Horizontal and Vertical Antenna Orientations, Mode C (2480MHz)	64
Table 26: Radiated Emission, Average and Peak Data, 1 – 25GHz, Horizontal and Vertical Antenna Orientations, Mode G (2402MHz)	64
Table 27: Radiated Emission, Average and Peak Data, 1 – 25GHz, Horizontal and Vertical Antenna Orientations, Mode H (2442MHz)	64
Table 28: Radiated Emission, Average and Peak Data, 1 – 25GHz, Horizontal and Vertical Antenna Orientations, Mode I (2480MHz)	65

9. List of Figures

Figure 1: Conducted Output Power, Mode A	13
Figure 2: Conducted Output Power, Mode B	14
Figure 3: Conducted Output Power, Mode C	15
Figure 4: Conducted Output Power, Mode G	16
Figure 5: Conducted Output Power, Mode H	17
Figure 6: Conducted Output Power, Mode I	18
Figure 7: Carrier Frequency Separation-Low Channel	20
Figure 8: Carrier Frequency Separation-Middle Channel	21
Figure 9: Carrier Frequency Separation-High Channel.....	21
Figure 10: 20dB &99% Bandwidth, Mode A (2402MHz 8DPSK and GFSK)	23
Figure 11: 20dB Bandwidth, Mode B (2441MHz 8DPSK and GFSK)	24
Figure 12: 20dB Bandwidth, Mode C (2480MHz 8DPSK and GFSK)	25
Figure 13: 6dB &99%Bandwidth, Mode G	27

Prüfbericht - Nr.: 15068732 001
Test Report No.:

Seite 70 von 70
Page 70 of 70

Figure 14: 6dB &99%Bandwidth, Mode H.....	27
Figure 15: 6dB &99%Bandwidth, Mode I	28
Figure 16: Hopping Frequencies BDR and EDR.....	30
Figure 17: Dwell Time, Mode (Hopping), 1M-DH5, Low channel.....	33
Figure 18: Dwell Time, Mode (Hopping), 1M-DH5, Mid channel	34
Figure 19: Dwell Time, Mode (Hopping), 1M-DH5, High channel.....	34
Figure 20: Power spectral density, Mode G	36
Figure 21: Power spectral density, Mode H	37
Figure 22: Power spectral density, Mode I.....	37
Figure 23: Conducted Spurious Emission, 30MHz – 6GHz, Mode A.....	39
Figure 24: Conducted Spurious Emission, 6 – 26GHz, Mode A.....	40
Figure 25: Conducted Spurious Emission, 30MHz – 6GHz, Mode B.....	41
Figure 26: Conducted Spurious Emission, 6 – 26GHz, Mode B.....	41
Figure 27: Conducted Spurious Emission, 30MHz – 6GHz, Mode C	42
Figure 28: Conducted Spurious Emission, 6 – 26GHz, Mode C.....	43
Figure 29: Conducted Spurious Emission, 30MHz – 6GHz, Mode G	44
Figure 30: Conducted Spurious Emission, 6 – 26GHz, Mode G.....	44
Figure 31: Conducted Spurious Emission, 30MHz – 6GHz, Mode H	45
Figure 32: Conducted Spurious Emission, 6 – 26GHz, Mode H.....	46
Figure 33: Conducted Spurious Emission, 30MHz – 6GHz, Mode I.....	47
Figure 34: Conducted Spurious Emission, 6 – 26GHz, Mode I	47
Figure 35: Lower Band Edge Conducted Mode A.....	49
Figure 36: Upper Band Edge Conducted Mode C	49
Figure 37: Lower Band Edge Conducted Mode A(Hopping).....	50
Figure 38: Lower Band Edge Conducted Mode C(Hopping)	50
Figure 39: Lower Band Edge Conducted Mode G	51
Figure 40: Lower Band Edge Conducted Mode I.....	51
Figure 41: Band Edge Radiated Emission, Spectral Diagram, Mode A	55
Figure 42: Band Edge Radiated Emission, Spectral Diagram, Mode C.....	57
Figure 43: Band Edge Radiated Emission, Spectral Diagram, Mode G	59
Figure 44: Band Edge Radiated Emission, Spectral Diagram, Mode I	61

10. List of Photographs

Photograph 1: Set-up for Conducted RF test at Antenna Port.....	67
Photograph 2: Set-up for Radiated Emission, 30MHz-1000MHz.....	68
Photograph 3: Set-up for Radiated Spurious Emission,Above 1GHz	68