

IEEE C95.1**KDB 447498 D03****47 C.F.R. Part 1, Subpart I, Section 1.1310****47 C.F.R. Part 2, Subpart J, Section 2.1091****RF EXPOSURE REPORT****For****All In One Panel PC****Model: 3365-199****Trade Name:**  **ADLINK**
TECHNOLOGY INC.**Issued for****ADLINK TECHNOLOGY INC.****9F, No. 166, Jian Yi Road, Chungho City, Taipei, Taiwan ZIP:235, R.O.C****Issued by****Compliance Certification Services Inc.****Hsinchu Lab.****NO. 989-1, Wenshan Rd., Shangshan Village,
Qionglin Township, Hsinchu County 30741, Taiwan (R.O.C.)****<http://www.ccsrf.com>****service@ccsrf.com****Issued Date: April 22, 2016**

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF or any government agencies. The test results of this report relate only to the tested sample identified in this report.



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	01/05/2016	Initial Issue	All Page	Gloria Chang
01	04/22/2016	Revised Applicant Address & Antenna Information	All Page	Gloria Chang



TABLE OF CONTENTS

1. LIMIT	4
2. EUT SPECIFICATION.....	4
3. TEST RESULTS	6
4. MAXIMUM PERMISSIBLE EXPOSURE.....	7

1. Limit

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

2. EUT Specification

Product Name	All In One Panel PC
Model Number	3365-199
Identify Number	T150902D01
Received Date	September 02, 2015
Frequency band (Operating)	☒ 802.11b/g/gn HT20: 2412MHz ~ 2462MHz 802.11gn HT40: 2422MHz ~ 2452MHz 802.11a, 802.11an HT20: 5180 MHz ~ 5240 MHz / 5745 MHz ~ 5825 MHz 802.11an HT40: 5190 MHz ~ 5230 MHz / 5755 MHz ~ 5795 MHz ☐ Others
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW}/\text{cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)
Antenna Specification	WiFi (2.4GHz) Antenna 1 Gain 4.24 dBi (Numeric gain: 2.65) WiFi (2.4GHz) Antenna 2 Gain 4.69 dBi (Numeric gain: 2.94) WiFi (5GHz) Antenna 1 Gain 5.84 dBi (Numeric gain: 3.84) WiFi (5GHz) Antenna 2 Gain 7.41 dBi (Numeric gain: 5.51)

Maximum Average output power	IEEE 802.11b Mode: 14.40 dBm (27.542 mW) IEEE 802.11g Mode: 26.12 dBm (409.261 mW) IEEE 802.11n HT 20 Mode: 25.03 dBm (318.420 mW) IEEE 802.11n HT 40 Mode: 24.12 dBm (258.226 mW) 5G UNII Band 1: IEEE 802.11a Mode: 18.32 dBm (67.920 mW) IEEE 802.11n HT 20 Mode: 18.17 dBm (65.615 mW) IEEE 802.11n HT 40 Mode: 18.73 dBm (74.645 mW) 5G UNII Band 3: IEEE 802.11a Mode: 18.36 dBm (68.549 mW) IEEE 802.11n HT 20 Mode: 18.68 dBm (73.790 mW) IEEE 802.11n HT 40 Mode: 16.31 dBm (42.756 mW)
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

3. Test Results

No non-compliance noted.

Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{377}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in watts / meter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \textbf{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

4. Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

IEEE 802.11b mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2437	27.542	2.94	20	0.0161	1

IEEE 802.11g mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2437	409.261	2.94	20	0.2394	1

IEEE 802.11gn HT20 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2437	318.42	2.94	20	0.1863	1

IEEE 802.11gn HT40 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
2437	258.226	2.94	20	0.1511	1

5G UNII Band 1 :

IEEE 802.11a mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5240	67.92	5.51	20	0.0745	1

IEEE 802.11an HT20 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5785	65.615	5.51	20	0.0719	1

IEEE 802.11an HT40 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5230	74.645	5.51	20	0.0818	1

5G UNII Band 3 :**IEEE 802.11a mode:**

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5785	68.549	5.51	20	0.0752	1

IEEE 802.11an HT20 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5785	73.79	5.51	20	0.0809	1

IEEE 802.11an HT40 mode:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
5795	42.756	5.51	20	0.0469	1