



18/88 Merrindale Drive Croydon South, Victoria, 3136, Australia
Telephone: +61 3 9761 5888
Facsimile: +61 3 8761 6547
Email: sales@emcbayswater.com.au
ABN: 49 112 221 333

RF Radiation Exposure Evaluation

In accordance with:

FCC KDB 447498 D01 v06

Automatic Technology Australia Pty. Ltd.

KPX-7V4AM

Wireless Keypad Transmitter

FCC ID: X4K-KPX8100

REPORT: E2603-1957-4

DATE: July, 2026



RF Radiation Exposure Evaluation Report

EMC Bayswater Test Report: E2603-1957-4
Issue Date: July, 2026

Product(s): Wireless Keypad Transmitter
Model No: KPX-7V4AM
Serial No: None stated
Variant: KPX-7V4SM
The above listed model (KPX-7V4AM) was declared by the customer to be identical to the above listed variant (KPX-7V4SM). Please refer to Appendix D in this report for the customer variant declaration.

FCC ID: X4K-KPX8100

Customer Details: Mr. Nikolai Klepikov
Automatic Technology Australia Pty. Ltd.
6 – 8 Fiveways Boulevard
Keysborough
Victoria 3173, Australia
Phone No: +61 3 9795 0275
e-mail: Nikolai.Klepikov@bnd.com.au

Standard(s): FCC KDB 447498 D01 v06
RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES
CFR47 FCC Part 2, Subpart J, 2.1091
Radiofrequency radiation exposure evaluation: mobile devices.
CFR47 FCC Part 2, Subpart J, 2.1093
Radiofrequency radiation exposure evaluation: portable devices.

Results Summary: RF Radiation exposure requirements **Complied**

Test Date(s): 26th of March 2026

Test House (Issued By): EMC Bayswater Pty Ltd
18/88 Merrindale Drive
Croydon South, Victoria, 3136, Australia
FCC Accredited Test Firm Registration number: 527798
FCC Accredited Test Firm Designation number: AU0004
Phone No: +61 3 9761 5888 Email: sales@emcbayswater.com.au
Fax: +61 3 8761 6547 Web: www.emcbayswater.com.au

The Automatic Technology Australia Pty. Ltd. KPX-7V4AMKPX-7V4AM, Wireless Keypad Transmitter, measured EIRP is below the SAR exception threshold (5mm distance) and the calculated power density level at a distance of 20cm are below the maximum levels allowed by regulations therefore complied with the requirements of CFR47 FCC Part 2, Subpart J, 2.1091.

This is to certify that the necessary evaluations were made by EMC Bayswater Pty Ltd, and that the Automatic Technology Australia Pty. Ltd., KPX-7V4AM, Wireless Keypad Transmitter, has been tested in accordance with requirements contained in the appropriate commission regulations.

Prepared by:

Approved by:

Fabio D'Amico
(Senior Test Engineer)Neville Liyanapatabendige
(Manager)

02/07/2026 13:20

Date

RF Radiation Exposure Evaluation *for* Automatic Technology Australia Pty. Ltd.

Contents

1. Introduction	4
2. Test Report Revision History	4
3. Report Information	4
4. Product Details	5
4.1. Product Sample Details	5
4.2. Product description	5
5. SAR and RF Exposure exception evaluation	6
5.1. SAR exception evaluation	6
5.2. RF Exposure Evaluation (MPE)	7
6. Conclusion	7

1. Introduction

RF Radiation Exposure evaluation was performed on an Automatic Technology Australia Pty. Ltd., KPX-7V4AM, Wireless Keypad Transmitter in accordance with CFR47 FCC Part 2, Subpart J, 2.1091.

2. Test Report Revision History

None.

3. Report Information

EMC Bayswater Pty Ltd reports apply only to the specific samples tested under the stated test conditions. All samples tested were in good operating condition throughout the entire test program unless otherwise stated. EMC Bayswater Pty Ltd does not in any way guarantee the later performance of the product/equipment. It is the manufacturer's responsibility to ensure that additional production units of the tested model are manufactured with identical electrical and mechanical components. EMC Bayswater Pty Ltd shall have no liability for any deductions, inference or generalisations drawn by the clients or others from EMC Bayswater Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Bayswater Pty Ltd. This report shall not be reproduced except in full, without the written approval of EMC Bayswater Pty Ltd. This document may be altered or revised by EMC Bayswater Pty Ltd personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by EMC Bayswater Pty Ltd will nullify the document.

4. Product Details

4.1. Product Sample Details

The device, as supplied, is described as follows:

Product:	Wireless Keypad Transmitter	
Model No:	KPX-7V4AM	
Variant:	KPX-7V4SM	
	<i>The above listed model (KPX-7V4AM) was declared by the customer to be identical to the above listed variant (KPX-7V4SM). Please refer to Appendix E in this report for the customer variant declaration.</i>	
Serial No:	None stated	
Firmware:	Not stated	
Dimensions:	13.5cm x 7.5cm x 3cm	
Weight:	0.15kg	
Power Specifications:	2 Batteries 1.5V Size AAA	
EUT Orientation	Only in one EUT orientation for the typical user case	
Transmitter details:	Description:	Wireless Keypad Transmitter
	Type:	Transmitter
	Modulation:	FSK/OOK
	Channels:	3
	Max Power:	-10.1 dBm measured EIRP
	Antenna:	PCB Antenna
	FCC ID	X4K-KPX8100
	IC	8880A-KPX8100

(Customer supplied product information)

4.2. Product description

The device has been described by the customer as follows:

“The KPX-7V4 is the weatherproof wireless keypad device, which allows secure access without a wireless handheld transmitter. With backlit numbers for night use, multiple users can have unique codes for garage door, specific door or gate access.”

(Customer supplied product description information)

5. SAR and RF Exposure exception evaluation

5.1. SAR exception evaluation

As per Appendix A of KDB 447498 D01 General RF Exposure Guidance v06

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table. The equation and threshold in 4.3.1 must be applied to determine SAR test exclusion.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	<i>SAR Test Exclusion Threshold (mW)</i>
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

SAR test exclusion threshold for 433.4MHz to 434.4MHz transmitter is 22.5mW for 5mm distance.

- The Measured maximum EIRP is 0.097mW (Worst-case, Without Duty Cycle correction factor).

(The measurement uncertainty was calculated at ± 4.65 dB. The reported uncertainty is an expanded uncertainty calculated using a coverage factor of approximately $k=2$ which gives a level of confidence of approximately 95%).

The measured EIRP is below the SAR exception threshold for 5mm distance.

5.2. RF Exposure Evaluation (MPE)

As per section 1.1310 of CFR 47 following Maximum Permissible Exposure (MPE) limits are applicable.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

Limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields for 433.9MHz as per Table 1 of Section 15.1310 is 0.29mW/cm² (General Population/Uncontrolled).

Prediction Worst case:

Using equation

$$S = PG / 4\pi R^2$$

where: S = Power density

P = Power input to the antenna

G = Antenna gain

R = Distance to the center of radiation of the antenna

Band	Maximum EIRP* (dBm)	Maximum EIRP (mW)	Distance (cm)	Calculated Power Density at 20cm (mW/cm ²)	Power Density Limit** (mW/cm ²)	Percentage of Limit %
433.870MHz	-10.1	0.097	20	0.0000194	0.29	0.0067

*Worst-case, Without Duty Cycle correction factor

** MPE limit for General Population/Un-controlled exposure

Table 1: Results for MPE Evaluation

6. Conclusion

The measured EIRP is below the SAR exception threshold (5mm distance) and the calculated power density level at a distance of 20cm are below the maximum levels allowed by regulations.