

Maximum Permissible Exposure

1. Introduction

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC), and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

2. Description of EUT

Equipment	Martian Notifier
Applicant Name	SilverPlus, Inc.
Applicant Address	17F., No.659, Sec. 1, Neihu Rd., Taipei City 114, Taiwan
Manufacturer Name	SilverPlus, Inc.
Manufacturer Address	17F., No.659, Sec. 1, Neihu Rd., Taipei City 114, Taiwan
Model No	T200
FCC ID	X4LT200

3. Classification

The antenna of this product, under normal use condition, is at least 5cm away from the body of the user. Warning statement to the user for keeping at least 5cm or more separation distance with the antenna should be included in users manual. So, this device is classified as Mobile Device.

4. Friis Formula

Friis transmission formula : $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm (20cm)

5. RF Exposure Limit :

According to FCC 1. 1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm^2)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
300-1500			F/300	6
1500-100,000			5	6
(B)Limits For General Population / Uncontrolled Exposure				
300-1500			F/1500	30
1500-100,000			1	30

6. Test Result:

BT

Frequency (MHz)	Max RF Power (mW)	TX Antenna Gain (dBi)	Testing Result (mW/cm^2)	MPE Limit (mW/cm^2)
2402	1.169	2.2	0.0062	1
2441	1.349	2.2	0.0071	1
2480	1.315	2.2	0.0069	1

BLE

Frequency (MHz)	Max RF Power (mW)	TX Antenna Gain (dBi)	Testing Result (mW/cm^2)	MPE Limit (mW/cm^2)
2402	1.426	2.2	0.0075	1
2440	1.538	2.2	0.0081	1
2480	1.607	2.2	0.0085	1