

# Test Report

of

## FCC RF Exposure

**Product :** Bluetooth 4.2 Module  
**Brand:** FANSTEL  
**Model Name:** BC832  
**Model Difference:** N/A  
**FCC ID:** X8WBC832  
**FCC Rule Part:** §15.247, Cat: DTS  
**Applicant:** Fanstel Corporation, Taipei  
**Address:** 10F-10, No. 79, Sec. 1, Hsin Tai Wu Rd., Hsi-Chih, New Taipei City 221 Taiwan

Test Performed by:



**International Standards Laboratory Corp. LT Lab.**

TEL: +886-3-263-8888 FAX: +886-3-263-8899

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan

**Report No.: ISL-16LR342FMPE-MA**  
**Issue Date : 2021/04/07**



Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein. The uncertainty of the measurement does not include in consideration of the test result unless the customer required the determination of uncertainty via the agreement, regulation or standard document specification. This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.


## VERIFICATION OF COMFORMITY

**Applicant:** Fanstel Corporation, Taipei  
**Product Description:** Bluetooth 4.2 Module  
**Brand:** FANSTEL  
**Model Name:** BC832  
**Model Difference:** N/A  
**FCC ID:** X8WBC832  
**Date of test:** 2016/12/17 ~ 2016/12/23  
**Date of EUT Received:** 2016/12/17

### We hereby certify that:

All the tests in this report have been performed and recorded in accordance with the standards described above and performed by an independent electromagnetic compatibility consultant, International Standards Laboratory Corp.

The test results contained in this report accurately represent the measurements of the characteristics and the energy generated by sample equipment under test at the time of the test. The sample equipment tested as described in this report is in compliance with the limits of above standards.

|                     |                                                                                     |              |            |
|---------------------|-------------------------------------------------------------------------------------|--------------|------------|
| <b>Test By:</b>     |  | <b>Date:</b> | 2021/04/07 |
|                     | <hr/>                                                                               |              | <hr/>      |
|                     | <b>Dino Chen / Supervisor</b>                                                       |              |            |
| <b>Prepared By:</b> |  | <b>Date:</b> | 2021/04/07 |
|                     | <hr/>                                                                               |              | <hr/>      |
|                     | <b>Elisa Chen / Senior Engineer</b>                                                 |              |            |
| <b>Approved By:</b> |  | <b>Date:</b> | 2021/04/07 |
|                     | <hr/>                                                                               |              | <hr/>      |
|                     | <b>Jerry Liu / Assistant Manager</b>                                                |              |            |

## Radio Frequency Exposure Evaluation

### Standard Applicable

#### FCC SAR test exclusion

According to KDB 447498 Section: 4.3.1. Standalone SAR test exclusion considerations

a) For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\left[ \frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot [\sqrt{f(\text{GHz})}]$$

$\leq 3.0$  for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

### SAR Exclusion Calculation Table

| Frequency<br>(MHz) | Max power<br>(dBm) | Antenna<br>Gain(dBi) | EIRP<br>Power<br>(dBm) | tune-up<br>tolerance<br>(dB) | Max power<br>(mW) | Min<br>Distance<br>(mm) | Result | Limit<br>(3.0 @ 1g<br>SAR) |
|--------------------|--------------------|----------------------|------------------------|------------------------------|-------------------|-------------------------|--------|----------------------------|
| 2480               | 2.61               | 1.00                 | 3.61                   | 1                            | 2.890680          | 5.00                    | 0.910  | 3.0                        |
|                    |                    |                      |                        |                              |                   |                         |        |                            |

~ End of Report ~