

TEST REPORT

of

FCC CFR Title 47 Part 15 Subpart C & CANADA RSS-247

Product: **WiFi6 Combo Module**
Brand: **Fanstel**
Main Model: **WT02C40C**
Series Model: **WT02E40E; WT02V40V; WT02E40C; WT02P40P**
Model Difference: **Antenna differences**
FCC ID: **X8WWT02C40C**
IC: **4100A-WT02C40C**
FCC Rule Part: **§15.247, Cat: DTS**
IC Rule Part: **RSS-247 issue 2: 2017**
RSS-Gen issue 5: 2018
Reference: **ANSI C63.10: 2013**
KDB 558074 D01 v05r02
Applicant: **Fanstel Corporation, Taipei**
Address: **10F-10, No. 79, Sec. 1, Hsin Tai Wu Rd., Hsi-Chih, New Taipei City 221 Taiwan**

Test Performed by:



International Standards Laboratory Corp. LT Lab.

TEL: +886-3-263-8888 FAX: +886-3-263-8899

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan

Report No.: **ISL-24LR0141FC DTS**
Issue Date : **November 5, 2024**



FCC Registration Number: 487532

Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein. According to customer agreement, the laboratory issues test reports based on the regulations or standards specifications, the measurement uncertainty is not considered in conformity decision rules. This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.

VERIFICATION OF COMPLIANCE

Applicant: Fanstel Corporation, Taipei
Equipment Under Test: WiFi6 Combo Module
Brand: Fanstel
Main Model: WT02C40C
Series Model: WT02E40E; WT02V40V; WT02E40C; WT02P40P
Model Difference: Antenna differences
FCC ID: X8WWT02C40C
IC: 4100A-WT02C40C
Date of Test: September 20, 2024 ~ November 5, 2024
Date of EUT Received: September 20, 2024

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC Part 15.247 RSS-247	Complied

We hereby certify that:

All the tests in this report have been performed and recorded in accordance with the standards described above and performed by an independent electromagnetic compatibility consultant, International Standards Laboratory Corp.

The test results contained in this report accurately represent the measurements of the characteristics and the energy generated by sample equipment under test at the time of the test. The sample equipment tested as described in this report is in compliance with the limits of above standards.

Prepared By: Gigi Yeh / Senior Engineer

Test By: Barry Lee
Barry Lee/Technical Supervisor

Approved By: Jerry Liu
Jerry Liu / Manager

Version

Version No.	Date	Description
00	November 5, 2024	Initial creation of document

TABLE OF CONTENTS

1. General.....	6
1.1 DESCRIPTION OF EUT	6
1.2 SPECIAL ACCESSORIES	7
1.3 EQUIPMENT MODIFICATIONS	7
2. System Test Configuration.....	8
2.1 EUT CONFIGURATION.....	8
2.2 EUT EXERCISE	8
2.3 TEST PROCEDURE.....	8
2.4 CONFIGURATION OF TESTED SYSTEM.....	8
2.5 DUTY FACTOR	9
3. Summary of Test Results.....	13
4. Description of Test Modes.....	13
5. AC Line Conduced Emission Test.....	15
5.1 STANDARD APPLICABLE	15
5.2 MEASUREMENT PROCEDURE.....	15
5.3 MEASUREMENT RESULT.....	16
6. Peak Output Power Measurement	18
6.1 STANDARD APPLICABLE	18
6.2 MEASUREMENT PROCEDURE.....	18
6.3 MEASUREMENT RESULT.....	19
7. Radiated Spurious Emission Test.....	20
7.1 STANDARD APPLICABLE	20
7.2 MEASUREMENT PROCEDURE.....	20
7.3 FIELD STRENGTH CALCULATION	21
7.4 MEASUREMENT RESULT.....	22
8. 100kHz Bandwidth of Band Edges Measurement	126
8.1 STANDARD APPLICABLE	126
8.2 MEASUREMENT PROCEDURE.....	126
8.3 FIELD STRENGTH CALCULATION	126
8.4 MEASUREMENT RESULT.....	127
9. 6dB Bandwidth.....	159
9.1 STANDARD APPLICABLE	159
9.2 MEASUREMENT PROCEDURE.....	159
9.3 MEASUREMENT RESULT.....	159
10. Peak Power Spectral Density	166
10.1 STANDARD APPLICABLE	166
10.2 MEASUREMENT PROCEDURE.....	166
10.3 MEASUREMENT RESULT.....	166
11. Appendix	173
11.1 APPENDIX A: EQUIPMENT LIST	173
11.2 APPENDIX B: UNCERTAINTY OF MEASUREMENT.....	175

11.3	APPENDIX C: TEST SETUP	176
11.4	APPENDIX D: PHOTOGRAPHS OF SETUP	179
11.5	APPENDIX E: PHOTOGRAPHS OF EUT	184

1. General

1.1 Description of EUT

General Information	
Product Name:	WiFi6 Combo Module
Brand Name:	Fanstel
Model Name:	WT02C40C; WT02E40E; WT02V40V; WT02E40C; WT02P40P
Model Difference:	Antenna different
Temperature Range	-40°C to +85°C
Power Supply:	5VDC
WiFi Information	
WLAN Modular	WT02
Frequency Range:	802.11b/g 2412~2462MHz 802.11n(HT20) 2412~2462MHz 802.11ax(HE20) 2412~2462MHz
Output Power:	22.10 dBm (Peak) 16.09 dBm (Average)
Channel number:	802.11b/g : 11 802.11n(HT20) : 11 802.11ax(HE20) : 11
PMN (Product Marketing Name)	WT02C40C
HVIN (Hardware Version Identification Number)	WT02C40C; WT02E40E; WT02V40V; WT02E40C; WT02P40P
FVIN (Firmware Version Identification Number)	nRF Connect SDK V2.7.0
TEST SW Version:	DockLight V2.2.8
RF power setting:	wifi_radio_test set_ant_gain 0 802.11b : wifi_radio_test set_edge_bo 5 802.11g : wifi_radio_test set_edge_bo 5 802.11n20 : wifi_radio_test set_edge_bo 4 802.11HE20 : wifi_radio_test set_edge_bo 6

	Antenna Type	Brand	Model	Peak Gain (dBi)	Frequency Range (MHz)	Connector Type
1	Dipole	Fanstel	ANT036	1.52dBi	2400-2500 MHz	RP.SMA.J
2	Chip	OneWave	WAN007030JD251SN03	2.95dBi	2400-2500 MHz	N/A

Model Summaries

module	WT02E40E	WT02C40C	WT02V40V	WT02E40C	WT02P40P
Size W(antenna)xHxT, mm	14.0(15.5)x23.0x2.0	14.0(25.0)x24.8x2.0	14.0(16.4)x30.5x2.0	14.0(15.5)x24.5x2.0	14(14)x18.5x2.0
SoCs	nRF5340+nRF7002	nRF5340+nRF7002	nRF5340+nRF7002	nRF5340+nRF7002	nRF5340+nRF7002
Embedded crystals	40M+32M+32K	40M+32M+32K	40M+32M+32K	40M+32M+32K	40M+32M+32K
BT/WiFi Antenna	u.FL/u.FL	Chip/Chip	Chip/chip	u.FL/Chip	Pads/pads
Operating temp.	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C
Evaluation board	EV-WT02E40E	EV-WT02C40C	EV-WT02V40V	EV-WT02E40C	EV-WT02P40P
Availability	Q1, 2025	Q1, 2025	Q1, 2025	Q1, 2025	Q1, 2025

1.2 Special Accessories

Not available for this EUT intended for grant.

1.3 Equipment Modifications

Not available for this EUT intended for grant.

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT (Transmitter) was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 AC Line Conducted Emissions


The EUT is placed on a turn table which is 0.8 m above ground plane. According to ANSI C63.10 and RSS-Gen. AC Line Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR 16-1-1 Quasi-Peak and Average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8 m/1.5m (Frequency above 1 GHz) above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to ANSI C63.10.

2.4 Configuration of Tested System

Configuration of Tested System (Fixed channel)



Equipment Used in Tested System

Item	Equipment	Brand	Model	S/N.	Data Cable	Power Cord
1	NB	HP	N5 13	NA	200cm	150cm

2.5 Duty factor

Mode	ON time (ms)	Total time (ms)	Duty Cycle	Duty Factor	1/Ton	VBW (kHz)
b	11.640	11.880	97.980%	0.089	0.086	0.10
g	1.921	2.147	89.474%	0.483	0.521	0.60
HT20	1.793	2.019	88.806%	0.516	0.558	0.60
HE20	1.627	1.853	87.804%	0.565	0.615	0.66


If duty cycle of test signal is $\geq 98\%$, duty factor is not required.

If duty cycle of test signal is $< 98\%$, duty factor shall be considered.


The output power = measured power + duty factor

For frequency above 1GHz, the video bandwidth setting for average detector: $VBW \geq 1/Ton$


Test Data: b mode Duty




Test Data: g mode Duty



Test Data: 2.4G HT20 mode Duty



Test Data: 2.4G HE20 mode Duty



3. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207(a) RSS-Gen §8.8	AC Power Line Conducted Emission	Compliant
§15.247(b) (3), (4) RSS-247 issue 2, §5.4(4)	Peak Output Power/ EIRP	Compliant
§15.247(a)(2) RSS-247 issue 2, §5.2(1) RSS-Gen §6.6	6dB & 99% Power Bandwidth	Compliant
§15.247(d) RSS-247 issue 2, §5.5	100 kHz Bandwidth of Frequency Band Edges	Compliant
§15.247(d) RSS-247 issue 2, §5.5	Spurious Emission	Compliant
§15.247(e) RSS-247 issue 2, §5.2	Peak Power Density	Compliant
§15.203 RSS-GEN 8.3	Antenna Requirement	Compliant

4. Description of Test Modes

The EUT has been tested under engineering operating condition.

Test program used to control the EUT for staying in continuous transmitting mode is programmed.

802.11 b mode: Channel low (2412MHz), mid (2437MHz), high (2462MHz) with 1Mbps lowest data rate are chosen for full testing.

802.11 g mode: Channel low (2412MHz), mid (2437MHz), high (2462MHz) with 6Mbps lowest data rate are chosen for full testing.

802.11 n HT20: Channel low (2412MHz), mid (2437MHz), high (2462MHz) with 6.5Mbps lowest data rate are chosen for full testing.

802.11 ax HE20: Channel low (2412MHz), mid (2437MHz), high (2462MHz) with 6.5Mbps lowest data rate are chosen for full testing.

4.1 Test Plan:

Radiated Test	Model				
Test Item	WT02E40E	WT02C40C	WT02E40C	WT02P40P	WT02V40V
Band Edge	V	V	Δ	Δ	Δ
Spurious emission	V	V	Δ	Δ	Δ
Note: V: final test Δ: pre-scan The antenna type of WT02P40P is same as WT02E40E. The antenna type of WT02V40V is same as WT02C40C. The antenna type of WT02E40C is same as WT02E40E and WT02C40C					

Conducted Test	Model				
Test Item	WT02E40E	WT02C40C	WT02E40C	WT02P40P	WT02V40V
Output Power	V	Δ	Δ	Δ	Δ
6dB Bandwidth	V	Δ	Δ	Δ	Δ
26dB Bandwidth	V	Δ	Δ	Δ	Δ
Conducted Band Edge	V	Δ	Δ	Δ	Δ
Conducted RSE	V	Δ	Δ	Δ	Δ
Duty factor	V	Δ	Δ	Δ	Δ
Power Density	V	Δ	Δ	Δ	Δ
AC Line Conduction	V	Δ	Δ	Δ	Δ
Note: V: final test Δ: pre-scan The antenna type of WT02P40P is same as WT02E40E. The antenna type of WT02V40V is same as WT02C40C. The antenna type of WT02E40C is same as WT02E40E and WT02C40C					

5. AC Line Conduced Emission Test

5.1 Standard Applicable

According to §15.207 and RSS-Gen §7.2.4, frequency range within 150kHz to 30MHz shall not exceed the Limit table as below.


Frequency range MHz	Limits dB(μV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
Note 1.The lower limit shall apply at the transition frequencies 2.The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.		

5.2 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.
4. Both 120V & 240V have been verified, and 120V/60Hz was defined as the worst-case and record in the report.

5.3 Measurement Result


- Line



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.161	25.24	7.62	9.64	34.88	65.40	-30.52	17.26	55.40	-38.14
2	0.685	18.22	8.35	9.65	27.87	56.00	-28.13	18.00	46.00	-28.00
3*	0.766	22.54	16.29	9.66	32.20	56.00	-23.80	25.95	46.00	-20.05
4	4.092	13.05	7.62	9.75	22.80	56.00	-33.20	17.37	46.00	-28.63
5	4.902	13.26	8.31	9.77	23.03	56.00	-32.97	18.08	46.00	-27.92
6	13.560	15.58	7.14	9.89	25.47	60.00	-34.53	17.03	50.00	-32.97

Note:
Margin = QP/AVG Emission - Limit
QP/AVG Emission = QP_R/AVG_R + Correct Factor
Correct Factor = LISN Loss + Cable Loss
The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.
If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

- Neutral



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.161	25.37	7.58	9.65	35.02	65.40	-30.38	17.23	55.40	-38.17
2	0.238	19.91	4.01	9.64	29.55	62.18	-32.63	13.65	52.18	-38.53
3	0.503	14.51	2.85	9.65	24.16	56.00	-31.84	12.50	46.00	-33.50
4	0.688	18.37	7.54	9.66	28.03	56.00	-27.97	17.20	46.00	-28.80
5*	0.766	23.91	15.11	9.67	33.58	56.00	-22.42	24.78	46.00	-21.22
6	4.902	11.46	6.69	9.78	21.24	56.00	-34.76	16.47	46.00	-29.53

Note:
Margin = QP/AVG Emission - Limit
QP/AVG Emission = QP_R/AVG_R + Correct Factor
Correct Factor = LISN Loss + Cable Loss
The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.
If peak data can pass, it will be shown in “QP/AVG Correct” column, if not, QP/AVG data will instead.

6. Peak Output Power Measurement

6.1 Standard Applicable

According to §15.247

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(c) Operation with directional antenna gains greater than 6 dBi.

(1) Fixed point-to-point operation:

(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

(ii) Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

According to RSS-247 issue 2, §5.4

(D)For DTSSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e)

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

6.2 Measurement Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter or spectrum analyzer with proper instrument's parameters.
3. Record the max. reading.
4. Repeat above procedures until all frequency measured were complete.

6.3 Measurement Result

CDD mode - Peak Power

Mode	Freq. (MHz)	Output Power (dBm)				Duty Factor (dB)	Total Output Power (dBm)	Output Power Limit (dBm)
		Chain 0	Chain 1	Chain 2	Chain 3			
802.11b	2412	18.52				-----	18.52	30
	2437	19.90				-----	19.90	30
	2462	13.86				-----	13.86	30
802.11g	2412	19.17				-----	19.17	30
	2437	21.56				-----	21.56	30
	2462	18.53				-----	18.53	30
802.11n HT20	2412	19.59				-----	19.59	30
	2437	22.10				-----	22.10	30
	2462	18.54				-----	18.54	30
802.11ax HE20	2412	16.97				-----	16.97	30
	2437	21.71				-----	21.71	30
	2462	18.46				-----	18.46	30

CDD mode - Average Power

Mode	Freq. (MHz)	Output Power (dBm)				Duty Factor (dB)	Total Output Power (dBm)	Output Power Limit (dBm)
		Chain 0	Chain 1	Chain 2	Chain 3			
802.11b	2412	13.00				0.089	13.09	30
	2437	16.00				0.089	16.09	30
	2462	11.82				0.089	11.91	30
802.11g	2412	10.45				0.483	10.93	30
	2437	12.18				0.483	12.66	30
	2462	11.87				0.483	12.35	30
802.11n HT20	2412	10.58				0.516	11.10	30
	2437	14.94				0.516	15.46	30
	2462	7.86				0.516	8.38	30
802.11ax HE20	2412	10.20				0.565	10.77	30
	2437	15.24				0.565	15.81	30
	2462	11.46				0.564	12.02	30

7. Radiated Spurious Emission Test

7.1 Standard Applicable

According to §15.247(d), all other emissions outside these bands shall not exceed the general radiated emission limits specified in §15.209(a). And according to §15.33(a)(1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

According to RSS-247 issue 2, §5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the de-sired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

7.2 Measurement Procedure

1. The EUT was placed on a turn table which is 0.8m/1.5m above ground plane in 966 chamber.
2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
4. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. Repeat above procedures until all frequency measured were complete.

Test receiver setting	: Blew 1GHz
Detector	: Average (9kHz – 90kHz, 110kHz – 90kHz), Quasi-Peak
Bandwidth	: 200Hz, 120kHz
Test spectrum setting	: Above 1GHz
Peak	: RBW=1MHz, VBW $\geq$ 3*RBW, Sweep=auto
Average	: RBW=1MHz, VBW $\geq$ 1/T _{on} , Sweep=auto

7.3 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

Remark:

<1GHz

1. No further spurious emissions detected from the lowest internal frequency and 30MHz.
2. Measuring frequencies from the lowest internal frequency to the 1GHz.
3. Radiated emissions measured in frequency range from 9kHz to 1000MHz were made with an instrument detector setting 9-90kHz/110-490kHz using PK/AV and other Frequency Band using PK/QP
4. Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

>1GHz


- 5 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 6 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 7 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

7.4 Measurement Result

7.4.1 Radiated Spurious Emission Measurement Result (below 1GHz)


International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Tx Low Ch Tested by : Barry Lee



International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBUV	Factor dB/m	Level dBUV/m	Limit dBUV/m	Margin dB	Remark	Pol V/H
1	191.99	41.73	-11.21	30.52	43.50	-12.98	Peak	HORIZONTAL
2	239.52	41.76	-10.03	31.73	46.00	-14.27	Peak	HORIZONTAL
3	448.07	31.51	-3.51	28.00	46.00	-18.00	Peak	HORIZONTAL
4	592.60	31.14	-0.47	30.67	46.00	-15.33	Peak	HORIZONTAL
5	761.38	30.72	2.94	33.66	46.00	-12.34	Peak	HORIZONTAL
6	937.92	30.20	5.02	35.22	46.00	-10.78	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	143.49	32.61	-8.79	23.82	43.50	-19.68	Peak	VERTICAL
2	288.02	32.40	-7.99	24.41	46.00	-21.59	Peak	VERTICAL
3	457.77	31.43	-3.28	28.15	46.00	-17.85	Peak	VERTICAL
4	616.85	30.82	0.18	31.00	46.00	-15.00	Peak	VERTICAL
5	745.86	35.16	2.48	37.64	46.00	-8.36	Peak	VERTICAL
6	914.64	30.21	4.75	34.96	46.00	-11.04	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	191.99	41.14	-11.21	29.93	43.50	-13.57	Peak	HORIZONTAL
2	239.52	41.57	-10.03	31.54	46.00	-14.46	Peak	HORIZONTAL
3	464.56	30.89	-3.12	27.77	46.00	-18.23	Peak	HORIZONTAL
4	620.73	30.56	0.21	30.77	46.00	-15.23	Peak	HORIZONTAL
5	767.20	30.99	3.03	34.02	46.00	-11.98	Peak	HORIZONTAL
6	927.25	30.14	5.01	35.15	46.00	-10.85	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	163.86	32.86	-8.54	24.32	43.50	-19.18	Peak	VERTICAL
2	303.54	32.21	-7.62	24.59	46.00	-21.41	Peak	VERTICAL
3	466.50	30.51	-3.10	27.41	46.00	-18.59	Peak	VERTICAL
4	575.14	32.23	-0.98	31.25	46.00	-14.75	Peak	VERTICAL
5	756.53	30.10	2.83	32.93	46.00	-13.07	Peak	VERTICAL
6	904.94	30.42	4.52	34.94	46.00	-11.06	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	191.99	41.40	-11.21	30.19	43.50	-13.31	Peak	HORIZONTAL
2	239.52	41.23	-10.03	31.20	46.00	-14.80	Peak	HORIZONTAL
3	451.95	30.93	-3.42	27.51	46.00	-18.49	Peak	HORIZONTAL
4	615.88	30.26	0.17	30.43	46.00	-15.57	Peak	HORIZONTAL
5	774.96	30.38	2.96	33.34	46.00	-12.66	Peak	HORIZONTAL
6	945.68	30.42	5.21	35.63	46.00	-10.37	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	159.98	32.98	-8.45	24.53	43.50	-18.97	Peak	VERTICAL
2	239.52	35.13	-10.03	25.10	46.00	-20.90	Peak	VERTICAL
3	455.83	31.15	-3.32	27.83	46.00	-18.17	Peak	VERTICAL
4	629.46	31.79	0.33	32.12	46.00	-13.88	Peak	VERTICAL
5	745.86	36.34	2.48	38.82	46.00	-7.18	Peak	VERTICAL
6	922.40	30.48	4.94	35.42	46.00	-10.58	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	191.99	41.03	-11.21	29.82	43.50	-13.68	Peak	HORIZONTAL
2	239.52	41.46	-10.03	31.43	46.00	-14.57	Peak	HORIZONTAL
3	452.92	30.83	-3.39	27.44	46.00	-18.56	Peak	HORIZONTAL
4	624.61	30.20	0.31	30.51	46.00	-15.49	Peak	HORIZONTAL
5	741.98	37.27	2.32	39.59	46.00	-6.41	Peak	HORIZONTAL
6	937.92	29.63	5.02	34.65	46.00	-11.35	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	156.10	32.28	-8.39	23.89	43.50	-19.61	Peak	VERTICAL
2	323.91	31.08	-6.90	24.18	46.00	-21.82	Peak	VERTICAL
3	421.88	32.00	-4.30	27.70	46.00	-18.30	Peak	VERTICAL
4	620.73	30.46	0.21	30.67	46.00	-15.33	Peak	VERTICAL
5	784.66	30.43	2.91	33.34	46.00	-12.66	Peak	VERTICAL
6	902.03	30.96	4.38	35.34	46.00	-10.66	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	191.99	41.10	-11.21	29.89	43.50	-13.61	Peak	HORIZONTAL
2	239.52	41.46	-10.03	31.43	46.00	-14.57	Peak	HORIZONTAL
3	448.07	32.14	-3.51	28.63	46.00	-17.37	Peak	HORIZONTAL
4	619.76	30.69	0.19	30.88	46.00	-15.12	Peak	HORIZONTAL
5	765.26	30.20	3.03	33.23	46.00	-12.77	Peak	HORIZONTAL
6	914.64	30.87	4.75	35.62	46.00	-10.38	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	174.53	33.45	-9.33	24.12	43.50	-19.38	Peak	VERTICAL
2	239.52	34.87	-10.03	24.84	46.00	-21.16	Peak	VERTICAL
3	459.71	31.16	-3.23	27.93	46.00	-18.07	Peak	VERTICAL
4	632.37	29.97	0.40	30.37	46.00	-15.63	Peak	VERTICAL
5	742.95	39.53	2.37	41.90	46.00	-4.10	Peak	VERTICAL
6	926.28	29.59	5.01	34.60	46.00	-11.40	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	191.99	41.08	-11.21	29.87	43.50	-13.63	Peak	HORIZONTAL
2	239.52	41.43	-10.03	31.40	46.00	-14.60	Peak	HORIZONTAL
3	429.64	31.44	-4.05	27.39	46.00	-18.61	Peak	HORIZONTAL
4	633.34	30.27	0.42	30.69	46.00	-15.31	Peak	HORIZONTAL
5	740.04	36.70	2.24	38.94	46.00	-7.06	Peak	HORIZONTAL
6	916.58	30.30	4.80	35.10	46.00	-10.90	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE g mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	143.87	31.50	-8.79	22.71	43.50	-20.79	Peak	VERTICAL
2	313.01	32.02	-7.10	24.92	46.00	-21.08	Peak	VERTICAL
3	441.20	30.33	-3.67	26.66	46.00	-19.34	Peak	VERTICAL
4	622.55	32.68	0.25	32.93	46.00	-13.07	Peak	VERTICAL
5	775.57	30.76	2.97	33.73	46.00	-12.27	Peak	VERTICAL
6	920.21	32.10	4.90	37.00	46.00	-9.00	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE g mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	191.93	41.13	-11.21	29.92	43.50	-13.58	Peak	HORIZONTAL
2	239.07	41.87	-10.03	31.84	46.00	-14.16	Peak	HORIZONTAL
3	447.77	30.47	-3.51	26.96	46.00	-19.04	Peak	HORIZONTAL
4	592.16	32.45	-0.47	31.98	46.00	-14.02	Peak	HORIZONTAL
5	761.57	32.54	2.94	35.48	46.00	-10.52	Peak	HORIZONTAL
6	937.64	30.52	5.02	35.54	46.00	-10.46	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC g mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	143.19	33.94	-8.79	25.15	43.50	-18.35	Peak	VERTICAL
2	288.00	31.57	-7.99	23.58	46.00	-22.42	Peak	VERTICAL
3	458.12	30.27	-3.28	26.99	46.00	-19.01	Peak	VERTICAL
4	616.65	30.19	0.18	30.37	46.00	-15.63	Peak	VERTICAL
5	745.76	33.60	2.48	36.08	46.00	-9.92	Peak	VERTICAL
6	915.10	31.21	4.75	35.96	46.00	-10.04	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC g mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	192.06	41.72	-11.21	30.51	43.50	-12.99	Peak	HORIZONTAL
2	239.76	40.36	-10.03	30.33	46.00	-15.67	Peak	HORIZONTAL
3	464.25	31.34	-3.12	28.22	46.00	-17.78	Peak	HORIZONTAL
4	620.42	30.98	0.21	31.19	46.00	-14.81	Peak	HORIZONTAL
5	767.47	32.81	3.03	35.84	46.00	-10.16	Peak	HORIZONTAL
6	927.50	31.70	5.01	36.71	46.00	-9.29	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE g mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	163.96	32.53	-8.54	23.99	43.50	-19.51	Peak	VERTICAL
2	303.51	32.64	-7.62	25.02	46.00	-20.98	Peak	VERTICAL
3	466.71	30.59	-3.10	27.49	46.00	-18.51	Peak	VERTICAL
4	575.54	31.17	-0.98	30.19	46.00	-15.81	Peak	VERTICAL
5	756.10	28.15	2.83	30.98	46.00	-15.02	Peak	VERTICAL
6	904.69	30.62	4.52	35.14	46.00	-10.86	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE g mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	192.43	39.52	-11.21	28.31	43.50	-15.19	Peak	HORIZONTAL
2	239.50	40.35	-10.03	30.32	46.00	-15.68	Peak	HORIZONTAL
3	452.18	32.43	-3.42	29.01	46.00	-16.99	Peak	HORIZONTAL
4	615.91	28.56	0.17	28.73	46.00	-17.27	Peak	HORIZONTAL
5	774.84	28.49	2.96	31.45	46.00	-14.55	Peak	HORIZONTAL
6	945.30	29.77	5.21	34.98	46.00	-11.02	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC g mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	159.51	31.13	-8.45	22.68	43.50	-20.82	Peak	VERTICAL
2	239.07	35.54	-10.03	25.51	46.00	-20.49	Peak	VERTICAL
3	455.66	31.69	-3.32	28.37	46.00	-17.63	Peak	VERTICAL
4	629.10	29.91	0.33	30.24	46.00	-15.76	Peak	VERTICAL
5	746.08	37.44	2.48	39.92	46.00	-6.08	Peak	VERTICAL
6	922.00	31.16	4.94	36.10	46.00	-9.90	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC g mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	192.30	39.41	-11.21	28.20	43.50	-15.30	Peak	HORIZONTAL
2	239.62	42.58	-10.03	32.55	46.00	-13.45	Peak	HORIZONTAL
3	452.50	29.53	-3.39	26.14	46.00	-19.86	Peak	HORIZONTAL
4	625.09	29.00	0.31	29.31	46.00	-16.69	Peak	HORIZONTAL
5	742.30	38.79	2.32	41.11	46.00	-4.89	Peak	HORIZONTAL
6	937.57	28.07	5.02	33.09	46.00	-12.91	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE g mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	155.97	33.48	-8.39	25.09	43.50	-18.41	Peak	VERTICAL
2	323.92	31.37	-6.90	24.47	46.00	-21.53	Peak	VERTICAL
3	421.49	30.30	-4.30	26.00	46.00	-20.00	Peak	VERTICAL
4	620.71	29.99	0.21	30.20	46.00	-15.80	Peak	VERTICAL
5	784.51	28.48	2.91	31.39	46.00	-14.61	Peak	VERTICAL
6	901.75	32.77	4.38	37.15	46.00	-8.85	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE g mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	192.20	39.43	-11.21	28.22	43.50	-15.28	Peak	HORIZONTAL
2	239.74	43.18	-10.03	33.15	46.00	-12.85	Peak	HORIZONTAL
3	447.87	30.97	-3.51	27.46	46.00	-18.54	Peak	HORIZONTAL
4	620.22	28.89	0.19	29.08	46.00	-16.92	Peak	HORIZONTAL
5	765.27	28.21	3.03	31.24	46.00	-14.76	Peak	HORIZONTAL
6	914.24	30.12	4.75	34.87	46.00	-11.13	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC g mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	174.65	32.35	-9.33	23.02	43.50	-20.48	Peak	VERTICAL
2	239.37	36.67	-10.03	26.64	46.00	-19.36	Peak	VERTICAL
3	459.71	32.08	-3.23	28.85	46.00	-17.15	Peak	VERTICAL
4	632.04	29.66	0.40	30.06	46.00	-15.94	Peak	VERTICAL
5	743.32	38.59	2.37	40.96	46.00	-5.04	Peak	VERTICAL
6	926.02	28.22	5.01	33.23	46.00	-12.77	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC g mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	191.60	41.36	-11.21	30.15	43.50	-13.35	Peak	HORIZONTAL
2	239.33	41.73	-10.03	31.70	46.00	-14.30	Peak	HORIZONTAL
3	429.20	32.42	-4.05	28.37	46.00	-17.63	Peak	HORIZONTAL
4	633.45	30.39	0.42	30.81	46.00	-15.19	Peak	HORIZONTAL
5	739.83	35.12	2.24	37.36	46.00	-8.64	Peak	HORIZONTAL
6	916.88	31.96	4.80	36.76	46.00	-9.24	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	143.25	32.91	-8.79	24.12	43.50	-19.38	Peak	VERTICAL
2	313.00	30.63	-7.10	23.53	46.00	-22.47	Peak	VERTICAL
3	441.26	31.23	-3.67	27.56	46.00	-18.44	Peak	VERTICAL
4	622.81	31.07	0.25	31.32	46.00	-14.68	Peak	VERTICAL
5	775.79	29.74	2.97	32.71	46.00	-13.29	Peak	VERTICAL
6	920.27	31.15	4.90	36.05	46.00	-9.95	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBUV	Factor dB/m	Level dBUV/m	Limit dBUV/m	Margin dB	Remark	Pol V/H
1	191.96	41.29	-11.21	30.08	43.50	-13.42	Peak	HORIZONTAL
2	239.21	40.44	-10.03	30.41	46.00	-15.59	Peak	HORIZONTAL
3	448.53	32.17	-3.51	28.66	46.00	-17.34	Peak	HORIZONTAL
4	592.47	29.96	-0.47	29.49	46.00	-16.51	Peak	HORIZONTAL
5	761.64	29.40	2.94	32.34	46.00	-13.66	Peak	HORIZONTAL
6	937.69	30.08	5.02	35.10	46.00	-10.90	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	143.59	34.23	-8.79	25.44	43.50	-18.06	Peak	VERTICAL
2	287.95	30.61	-7.99	22.62	46.00	-23.38	Peak	VERTICAL
3	457.62	30.37	-3.28	27.09	46.00	-18.91	Peak	VERTICAL
4	617.25	28.85	0.18	29.03	46.00	-16.97	Peak	VERTICAL
5	746.14	37.09	2.48	39.57	46.00	-6.43	Peak	VERTICAL
6	914.36	29.91	4.75	34.66	46.00	-11.34	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	192.37	39.22	-11.21	28.01	43.50	-15.49	Peak	HORIZONTAL
2	239.96	42.49	-10.03	32.46	46.00	-13.54	Peak	HORIZONTAL
3	464.24	32.05	-3.12	28.93	46.00	-17.07	Peak	HORIZONTAL
4	620.90	31.07	0.21	31.28	46.00	-14.72	Peak	HORIZONTAL
5	767.26	30.44	3.03	33.47	46.00	-12.53	Peak	HORIZONTAL
6	926.79	31.52	5.01	36.53	46.00	-9.47	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	164.06	34.03	-8.54	25.49	43.50	-18.01	Peak	VERTICAL
2	303.54	32.86	-7.62	25.24	46.00	-20.76	Peak	VERTICAL
3	466.04	30.36	-3.10	27.26	46.00	-18.74	Peak	VERTICAL
4	575.05	34.00	-0.98	33.02	46.00	-12.98	Peak	VERTICAL
5	756.74	30.34	2.83	33.17	46.00	-12.83	Peak	VERTICAL
6	904.89	31.00	4.52	35.52	46.00	-10.48	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBUV	Factor dB/m	Level dBUV/m	Limit dBUV/m	Margin dB	Remark	Pol V/H
1	191.95	42.23	-11.21	31.02	43.50	-12.48	Peak	HORIZONTAL
2	239.69	40.41	-10.03	30.38	46.00	-15.62	Peak	HORIZONTAL
3	452.43	30.43	-3.42	27.01	46.00	-18.99	Peak	HORIZONTAL
4	615.38	30.60	0.17	30.77	46.00	-15.23	Peak	HORIZONTAL
5	774.70	31.04	2.96	34.00	46.00	-12.00	Peak	HORIZONTAL
6	946.18	30.89	5.21	36.10	46.00	-9.90	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	159.93	34.17	-8.45	25.72	43.50	-17.78	Peak	VERTICAL
2	239.82	36.25	-10.03	26.22	46.00	-19.78	Peak	VERTICAL
3	456.28	30.38	-3.32	27.06	46.00	-18.94	Peak	VERTICAL
4	629.34	33.64	0.33	33.97	46.00	-12.03	Peak	VERTICAL
5	745.79	35.01	2.48	37.49	46.00	-8.51	Peak	VERTICAL
6	921.99	31.58	4.94	36.52	46.00	-9.48	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	191.77	39.60	-11.21	28.39	43.50	-15.11	Peak	HORIZONTAL
2	239.57	40.01	-10.03	29.98	46.00	-16.02	Peak	HORIZONTAL
3	452.90	32.19	-3.39	28.80	46.00	-17.20	Peak	HORIZONTAL
4	624.37	28.50	0.31	28.81	46.00	-17.19	Peak	HORIZONTAL
5	741.58	36.41	2.32	38.73	46.00	-7.27	Peak	HORIZONTAL
6	938.09	30.48	5.02	35.50	46.00	-10.50	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	156.29	32.97	-8.39	24.58	43.50	-18.92	Peak	VERTICAL
2	324.02	32.64	-6.90	25.74	46.00	-20.26	Peak	VERTICAL
3	421.47	32.52	-4.30	28.22	46.00	-17.78	Peak	VERTICAL
4	620.26	31.65	0.21	31.86	46.00	-14.14	Peak	VERTICAL
5	784.96	28.81	2.91	31.72	46.00	-14.28	Peak	VERTICAL
6	902.04	30.12	4.38	34.50	46.00	-11.50	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	191.71	41.62	-11.21	30.41	43.50	-13.09	Peak	HORIZONTAL
2	239.63	43.46	-10.03	33.43	46.00	-12.57	Peak	HORIZONTAL
3	448.08	31.94	-3.51	28.43	46.00	-17.57	Peak	HORIZONTAL
4	620.21	28.94	0.19	29.13	46.00	-16.87	Peak	HORIZONTAL
5	764.94	31.19	3.03	34.22	46.00	-11.78	Peak	HORIZONTAL
6	914.94	31.33	4.75	36.08	46.00	-9.92	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	174.46	35.04	-9.33	25.71	43.50	-17.79	Peak	VERTICAL
2	239.06	36.33	-10.03	26.30	46.00	-19.70	Peak	VERTICAL
3	459.80	33.14	-3.23	29.91	46.00	-16.09	Peak	VERTICAL
4	632.48	28.72	0.40	29.12	46.00	-16.88	Peak	VERTICAL
5	743.21	40.28	2.37	42.65	46.00	-3.35	Peak	VERTICAL
6	926.71	30.85	5.01	35.86	46.00	-10.14	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	192.39	39.55	-11.21	28.34	43.50	-15.16	Peak	HORIZONTAL
2	239.76	41.26	-10.03	31.23	46.00	-14.77	Peak	HORIZONTAL
3	430.01	32.08	-4.05	28.03	46.00	-17.97	Peak	HORIZONTAL
4	633.53	32.10	0.42	32.52	46.00	-13.48	Peak	HORIZONTAL
5	739.76	35.25	2.24	37.49	46.00	-8.51	Peak	HORIZONTAL
6	916.33	29.90	4.80	34.70	46.00	-11.30	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE HE20 mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	143.49	32.65	-8.79	23.86	43.50	-19.64	Peak	VERTICAL
2	313.24	32.01	-7.10	24.91	46.00	-21.09	Peak	VERTICAL
3	441.28	32.23	-3.67	28.56	46.00	-17.44	Peak	VERTICAL
4	622.67	30.78	0.25	31.03	46.00	-14.97	Peak	VERTICAL
5	775.93	30.03	2.97	33.00	46.00	-13.00	Peak	VERTICAL
6	920.46	30.40	4.90	35.30	46.00	-10.70	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE HE20 mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	191.99	41.73	-11.21	30.52	43.50	-12.98	Peak	HORIZONTAL
2	239.52	41.76	-10.03	31.73	46.00	-14.27	Peak	HORIZONTAL
3	448.07	31.51	-3.51	28.00	46.00	-18.00	Peak	HORIZONTAL
4	592.60	31.14	-0.47	30.67	46.00	-15.33	Peak	HORIZONTAL
5	761.38	30.72	2.94	33.66	46.00	-12.34	Peak	HORIZONTAL
6	937.92	30.20	5.02	35.22	46.00	-10.78	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC HE20 mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	143.49	32.61	-8.79	23.82	43.50	-19.68	Peak	VERTICAL
2	288.02	32.40	-7.99	24.41	46.00	-21.59	Peak	VERTICAL
3	457.77	31.43	-3.28	28.15	46.00	-17.85	Peak	VERTICAL
4	616.85	30.82	0.18	31.00	46.00	-15.00	Peak	VERTICAL
5	745.86	35.16	2.48	37.64	46.00	-8.36	Peak	VERTICAL
6	914.64	30.21	4.75	34.96	46.00	-11.04	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC HE20 mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	191.99	41.14	-11.21	29.93	43.50	-13.57	Peak	HORIZONTAL
2	239.52	41.57	-10.03	31.54	46.00	-14.46	Peak	HORIZONTAL
3	464.56	30.89	-3.12	27.77	46.00	-18.23	Peak	HORIZONTAL
4	620.73	30.56	0.21	30.77	46.00	-15.23	Peak	HORIZONTAL
5	767.20	30.99	3.03	34.02	46.00	-11.98	Peak	HORIZONTAL
6	927.25	30.14	5.01	35.15	46.00	-10.85	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE HE20 mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	163.86	32.86	-8.54	24.32	43.50	-19.18	Peak	VERTICAL
2	303.54	32.21	-7.62	24.59	46.00	-21.41	Peak	VERTICAL
3	466.50	30.51	-3.10	27.41	46.00	-18.59	Peak	VERTICAL
4	575.14	32.23	-0.98	31.25	46.00	-14.75	Peak	VERTICAL
5	756.53	30.10	2.83	32.93	46.00	-13.07	Peak	VERTICAL
6	904.94	30.42	4.52	34.94	46.00	-11.06	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE HE20 mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBUV	Factor dB/m	Level dBUV/m	Limit dBUV/m	Margin dB	Remark	Pol V/H
1	191.99	41.40	-11.21	30.19	43.50	-13.31	Peak	HORIZONTAL
2	239.52	41.23	-10.03	31.20	46.00	-14.80	Peak	HORIZONTAL
3	451.95	30.93	-3.42	27.51	46.00	-18.49	Peak	HORIZONTAL
4	615.88	30.26	0.17	30.43	46.00	-15.57	Peak	HORIZONTAL
5	774.96	30.38	2.96	33.34	46.00	-12.66	Peak	HORIZONTAL
6	945.68	30.42	5.21	35.63	46.00	-10.37	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC HE20 mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	159.98	32.98	-8.45	24.53	43.50	-18.97	Peak	VERTICAL
2	239.52	35.13	-10.03	25.10	46.00	-20.90	Peak	VERTICAL
3	455.83	31.15	-3.32	27.83	46.00	-18.17	Peak	VERTICAL
4	629.46	31.79	0.33	32.12	46.00	-13.88	Peak	VERTICAL
5	745.86	36.34	2.48	38.82	46.00	-7.18	Peak	VERTICAL
6	922.40	30.48	4.94	35.42	46.00	-10.58	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC HE20 mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	191.99	41.03	-11.21	29.82	43.50	-13.68	Peak	HORIZONTAL
2	239.52	41.46	-10.03	31.43	46.00	-14.57	Peak	HORIZONTAL
3	452.92	30.83	-3.39	27.44	46.00	-18.56	Peak	HORIZONTAL
4	624.61	30.20	0.31	30.51	46.00	-15.49	Peak	HORIZONTAL
5	741.98	37.27	2.32	39.59	46.00	-6.41	Peak	HORIZONTAL
6	937.92	29.63	5.02	34.65	46.00	-11.35	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE HE20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	156.10	32.28	-8.39	23.89	43.50	-19.61	Peak	VERTICAL
2	323.91	31.08	-6.90	24.18	46.00	-21.82	Peak	VERTICAL
3	421.88	32.00	-4.30	27.70	46.00	-18.30	Peak	VERTICAL
4	620.73	30.46	0.21	30.67	46.00	-15.33	Peak	VERTICAL
5	784.66	30.43	2.91	33.34	46.00	-12.66	Peak	VERTICAL
6	902.03	30.96	4.38	35.34	46.00	-10.66	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE HE20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	191.99	41.10	-11.21	29.89	43.50	-13.61	Peak	HORIZONTAL
2	239.52	41.46	-10.03	31.43	46.00	-14.57	Peak	HORIZONTAL
3	448.07	32.14	-3.51	28.63	46.00	-17.37	Peak	HORIZONTAL
4	619.76	30.69	0.19	30.88	46.00	-15.12	Peak	HORIZONTAL
5	765.26	30.20	3.03	33.23	46.00	-12.77	Peak	HORIZONTAL
6	914.64	30.87	4.75	35.62	46.00	-10.38	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC HE20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	174.53	33.45	-9.33	24.12	43.50	-19.38	Peak	VERTICAL
2	239.52	34.87	-10.03	24.84	46.00	-21.16	Peak	VERTICAL
3	459.71	31.16	-3.23	27.93	46.00	-18.07	Peak	VERTICAL
4	632.37	29.97	0.40	30.37	46.00	-15.63	Peak	VERTICAL
5	742.95	39.53	2.37	41.90	46.00	-4.10	Peak	VERTICAL
6	926.28	29.59	5.01	34.60	46.00	-11.40	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC HE20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	191.99	41.08	-11.21	29.87	43.50	-13.63	Peak	HORIZONTAL
2	239.52	41.43	-10.03	31.40	46.00	-14.60	Peak	HORIZONTAL
3	429.64	31.44	-4.05	27.39	46.00	-18.61	Peak	HORIZONTAL
4	633.34	30.27	0.42	30.69	46.00	-15.31	Peak	HORIZONTAL
5	740.04	36.70	2.24	38.94	46.00	-7.06	Peak	HORIZONTAL
6	916.58	30.30	4.80	35.10	46.00	-10.90	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE Colocationh Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	137.88	31.78	-9.44	22.34	43.50	-21.16	Peak	VERTICAL
2	238.81	36.70	-10.03	26.67	46.00	-19.33	Peak	VERTICAL
3	458.34	30.81	-3.28	27.53	46.00	-18.47	Peak	VERTICAL
4	624.45	31.75	0.31	32.06	46.00	-13.94	Peak	VERTICAL
5	785.17	31.46	2.91	34.37	46.00	-11.63	Peak	VERTICAL
6	921.38	28.80	4.92	33.72	46.00	-12.28	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE Colocationh Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	192.35	42.68	-11.21	31.47	43.50	-12.03	Peak	HORIZONTAL
2	240.15	42.12	-10.03	32.09	46.00	-13.91	Peak	HORIZONTAL
3	457.80	29.07	-3.28	25.79	46.00	-20.21	Peak	HORIZONTAL
4	621.09	33.97	0.21	34.18	46.00	-11.82	Peak	HORIZONTAL
5	771.79	28.05	3.02	31.07	46.00	-14.93	Peak	HORIZONTAL
6	945.12	29.53	5.17	34.70	46.00	-11.30	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC Colocationh Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	156.62	30.59	-8.39	22.20	43.50	-21.30	Peak	VERTICAL
2	321.83	31.01	-6.95	24.06	46.00	-21.94	Peak	VERTICAL
3	455.74	33.09	-3.32	29.77	46.00	-16.23	Peak	VERTICAL
4	600.78	29.08	-0.28	28.80	46.00	-17.20	Peak	VERTICAL
5	729.65	40.54	2.01	42.55	46.00	-3.45	Peak	VERTICAL
6	931.93	30.35	4.99	35.34	46.00	-10.66	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC Colocationh Tested by : Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	191.73	40.86	-11.21	29.65	43.50	-13.85	Peak	HORIZONTAL
2	239.05	40.20	-10.03	30.17	46.00	-15.83	Peak	HORIZONTAL
3	467.86	30.51	-3.10	27.41	46.00	-18.59	Peak	HORIZONTAL
4	603.96	31.05	-0.19	30.86	46.00	-15.14	Peak	HORIZONTAL
5	746.00	38.73	2.48	41.21	46.00	-4.79	Peak	HORIZONTAL
6	944.44	32.02	5.17	37.19	46.00	-8.81	Peak	HORIZONTAL

7.4.2 Radiated Spurious Emission Measurement Result (above 1GHz)


International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Tx Low Ch Tested by : Barry Lee



International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	28.89	7.41	36.30	74.00	-37.70	Peak	HORIZONTAL
2	7342.00	34.42	12.55	46.97	74.00	-27.03	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	30.60	7.41	38.01	74.00	-35.99	Peak	VERTICAL
2	7424.00	32.82	12.50	45.32	74.00	-28.68	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	31.74	7.41	39.15	74.00	-34.85	Peak	HORIZONTAL
2	7357.00	33.83	12.55	46.38	74.00	-27.62	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	31.30	7.65	38.95	74.00	-35.05	Peak	VERTICAL
2	7446.00	34.44	12.47	46.91	74.00	-27.09	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	29.50	7.65	37.15	74.00	-36.85	Peak	HORIZONTAL
2	7378.00	32.60	12.55	45.15	74.00	-28.85	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	32.74	7.65	40.39	74.00	-33.61	Peak	VERTICAL
2	7299.00	34.54	12.52	47.06	74.00	-26.94	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	31.20	7.65	38.85	74.00	-35.15	Peak	HORIZONTAL
2	7344.00	35.23	12.54	47.77	74.00	-26.23	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	32.26	7.84	40.10	74.00	-33.90	Peak	VERTICAL
2	7334.00	33.06	12.53	45.59	74.00	-28.41	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBUV	Factor dB/m	Level dBUV/m	Limit dBUV/m	Margin dB	Remark	Pol V/H
1	4924.00	31.11	7.84	38.95	74.00	-35.05	Peak	HORIZONTAL
2	7364.00	33.32	12.54	45.86	74.00	-28.14	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	31.54	7.84	39.38	74.00	-34.62	Peak	VERTICAL
2	7304.00	34.35	12.53	46.88	74.00	-27.12	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	32.42	7.84	40.26	74.00	-33.74	Peak	HORIZONTAL
2	7359.00	31.94	12.55	44.49	74.00	-29.51	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	28.77	7.41	36.18	74.00	-37.82	Peak	VERTICAL
2	7341.00	35.07	12.55	47.62	74.00	-26.38	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	29.61	7.41	37.02	74.00	-36.98	Peak	HORIZONTAL
2	7381.00	31.74	12.55	44.29	74.00	-29.71	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	30.38	7.41	37.79	74.00	-36.21	Peak	VERTICAL
2	7380.00	31.16	12.50	43.66	74.00	-30.34	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	29.83	7.41	37.24	74.00	-36.76	Peak	HORIZONTAL
2	7406.00	32.14	12.55	44.69	74.00	-29.31	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	30.00	7.65	37.65	74.00	-36.35	Peak	VERTICAL
2	7456.00	32.89	12.47	45.36	74.00	-28.64	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBUV	Factor dB/m	Level dBUV/m	Limit dBUV/m	Margin dB	Remark	Pol V/H
1	4874.00	30.42	7.65	38.07	74.00	-35.93	Peak	HORIZONTAL
2	7391.00	33.62	12.55	46.17	74.00	-27.83	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	31.31	7.65	38.96	74.00	-35.04	Peak	VERTICAL
2	7305.00	33.19	12.52	45.71	74.00	-28.29	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	28.60	7.65	36.25	74.00	-37.75	Peak	HORIZONTAL
2	7334.00	33.21	12.54	45.75	74.00	-28.25	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	30.35	7.84	38.19	74.00	-35.81	Peak	VERTICAL
2	7316.00	31.88	12.53	44.41	74.00	-29.59	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	30.60	7.84	38.44	74.00	-35.56	Peak	HORIZONTAL
2	7346.00	32.95	12.54	45.49	74.00	-28.51	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	30.60	7.84	38.44	74.00	-35.56	Peak	VERTICAL
2	7324.00	31.99	12.53	44.52	74.00	-29.48	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	32.26	7.84	40.10	74.00	-33.90	Peak	HORIZONTAL
2	7405.00	33.69	12.55	46.24	74.00	-27.76	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE g mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	30.46	7.41	37.87	74.00	-36.13	Peak	VERTICAL
2	7348.00	33.75	12.55	46.30	74.00	-27.70	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE g mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	29.00	7.41	36.41	74.00	-37.59	Peak	HORIZONTAL
2	7366.00	33.46	12.55	46.01	74.00	-27.99	Peak	HORIZONTAL

Date: 2024-10-15


Test Mode : CC g mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	29.77	7.41	37.18	74.00	-36.82	Peak	VERTICAL
2	7414.00	32.87	12.50	45.37	74.00	-28.63	Peak	VERTICAL


International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC g mode Tx Low Ch Tested by : Barry Lee




International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE g mode Tx Mid Ch Tested by : Barry Lee



Date: 2024-10-15


Test Mode : EE g mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	32.05	7.65	39.70	74.00	-34.30	Peak	HORIZONTAL
2	7380.00	31.00	12.55	43.55	74.00	-30.45	Peak	HORIZONTAL

Date: 2024-10-15

Test Mode : CC g mode Tx Mid Ch Tested by : Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	30.78	7.65	38.43	74.00	-35.57	Peak	VERTICAL
2	7288.00	32.45	12.52	44.97	74.00	-29.03	Peak	VERTICAL

Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57


Test Mode : CC g mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	29.58	7.65	37.23	74.00	-36.77	Peak	HORIZONTAL
2	7355.00	34.53	12.54	47.07	74.00	-26.93	Peak	HORIZONTAL

Date: 2024-10-15


Test Mode : EE g mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	32.66	7.84	40.50	74.00	-33.50	Peak	VERTICAL
2	7313.00	31.03	12.53	43.56	74.00	-30.44	Peak	VERTICAL

Date: 2024-10-15


Test Mode : EE g mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	31.63	7.84	39.47	74.00	-34.53	Peak	HORIZONTAL
2	7346.00	34.04	12.54	46.58	74.00	-27.42	Peak	HORIZONTAL


International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC g mode Tx High Ch Tested by : Barry Lee



International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. :	24LR0141	Temp.(°C)/RH(%) :	24/57
Test Mode :	CC g mode Tx High Ch	Tested by :	Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	30.38	7.84	38.22	74.00	-35.78	Peak	HORIZONTAL
2	7405.00	33.35	12.55	45.90	74.00	-28.10	Peak	HORIZONTAL

Date: 2024-10-15


Test Mode : EE HE20 mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	29.65	7.41	37.06	74.00	-36.94	Peak	VERTICAL
2	7290.00	33.56	12.55	46.11	74.00	-27.89	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141	Temp.(°C)/RH(%) : 24/57
Test Mode : EE HE20 mode Tx Low Ch	Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	30.05	7.41	37.46	74.00	-36.54	Peak	HORIZONTAL
2	7290.00	32.51	12.55	45.06	74.00	-28.94	Peak	HORIZONTAL

Date: 2024-10-15


Test Mode : CC HE20 mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	30.59	7.41	38.00	74.00	-36.00	Peak	VERTICAL
2	7324.00	33.00	12.50	45.50	74.00	-28.50	Peak	VERTICAL

Date: 2024-10-15


Test Mode : CC HE20 mode Tx Low Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4824.00	31.40	7.41	38.81	74.00	-35.19	Peak	HORIZONTAL
2	7307.00	32.77	12.55	45.32	74.00	-28.68	Peak	HORIZONTAL

Date: 2024-10-15

Test Mode : EE HE20 mode Tx Mid Ch Tested by : Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	30.83	7.65	38.48	74.00	-35.52	Peak	VERTICAL
2	7358.00	33.35	12.47	45.82	74.00	-28.18	Peak	VERTICAL

Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57


Test Mode : EE HE20 mode Tx Mid Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	30.88	7.65	38.53	74.00	-35.47	Peak	HORIZONTAL
2	7307.00	32.88	12.55	45.43	74.00	-28.57	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141	Temp.(°C)/RH(%) : 24/57
Test Mode : CC HE20 mode Tx Mid Ch	Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	31.26	7.65	38.91	74.00	-35.09	Peak	VERTICAL
2	7222.00	32.72	12.52	45.24	74.00	-28.76	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141	Temp.(°C)/RH(%) : 24/57
Test Mode : CC HE20 mode Tx Mid Ch	Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4874.00	30.18	7.65	37.83	74.00	-36.17	Peak	HORIZONTAL
2	7273.00	33.49	12.54	46.03	74.00	-27.97	Peak	HORIZONTAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE HE20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	31.75	7.84	39.59	74.00	-34.41	Peak	VERTICAL
2	7239.00	32.67	12.53	45.20	74.00	-28.80	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE HE20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	31.27	7.84	39.11	74.00	-34.89	Peak	HORIZONTAL
2	7273.00	33.55	12.54	46.09	74.00	-27.91	Peak	HORIZONTAL

Date: 2024-10-15


Test Mode : CC HE20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	30.32	7.84	38.16	74.00	-35.84	Peak	VERTICAL
2	7239.00	32.37	12.53	44.90	74.00	-29.10	Peak	VERTICAL

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC HE20 mode Tx High Ch Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4924.00	31.69	7.84	39.53	74.00	-34.47	Peak	HORIZONTAL
2	7307.00	33.10	12.55	45.65	74.00	-28.35	Peak	HORIZONTAL

Date: 2024-10-15


Test Mode : EE Colocation Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4968.00	30.90	7.84	38.74	74.00	-35.26	Peak	VERTICAL
2	7257.00	31.03	12.53	43.56	74.00	-30.44	Peak	VERTICAL


Date: 2024-10-15

Test Mode : EE Colocation Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4961.00	30.26	7.84	38.10	74.00	-35.90	Peak	HORIZONTAL
2	7309.00	34.79	12.54	47.33	74.00	-26.67	Peak	HORIZONTAL


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC Colocation Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4885.00	31.27	7.84	39.11	74.00	-34.89	Peak	VERTICAL
2	7252.00	30.50	12.53	43.03	74.00	-30.97	Peak	VERTICAL

Date: 2024-10-15

Test Mode : CC Colocation Tested by : Barry Lee



No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	4949.00	30.30	7.84	38.14	74.00	-35.86	Peak	HORIZONTAL
2	7314.00	33.87	12.55	46.42	74.00	-27.58	Peak	HORIZONTAL

8. 100kHz Bandwidth of Band Edges Measurement

8.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

According to RSS-247 issue 2, §5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(d), the attenuation required shall be 30 dB instead of 20dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

8.2 Measurement Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW=1MHz, VBW $\geq$ 3*RBW (for Peak); VBW $\geq$ 1/T_{on} (for Average), Sweep = auto.
5. Mark Peak, 2.390GHz and 2.4835GHz and record the max. level.
6. Repeat above procedures until all frequency measured were complete.

8.3 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:


$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

8.4 Measurement Result

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Bandedge Low Ch Tested by : Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Bandedge Low Ch Tested by : Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	48.99	-1.64	47.35	74.00	-26.65	Peak	HORIZONTAL
2	2400.00	51.35	-1.52	49.83	77.05	-27.22	Peak	HORIZONTAL
3	2411.02	98.55	-1.50	97.05	F	--	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE g mode Bandedge Low Ch Tested by : Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	48.92	-1.64	47.28	54.00	-6.72	Average	VERTICAL
2	2390.00	61.40	-1.64	59.76	74.00	-14.24	Peak	VERTICAL
3	2400.00	73.46	-1.52	71.94	83.11	-11.17	Peak	VERTICAL
4	2413.49	104.61	-1.50	103.11	F	--	Peak	VERTICAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
 Company Address: No. 120, Lane 180, Hsin Ho Rd.
 Lung-Tan Dist., Tao Yuan City 325, Taiwan
 Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
 Test Mode : EE g mode Bandedge Low Ch Tested by : Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	43.48	-1.64	41.84	54.00	-12.16	Average	HORIZONTAL
2	2390.00	55.67	-1.64	54.03	74.00	-19.97	Peak	HORIZONTAL
3	2400.00	68.32	-1.52	66.80	78.45	-11.65	Peak	HORIZONTAL
4	2410.91	99.95	-1.50	98.45	F	--	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Bandedge Low Ch Tested by : Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	49.01	-1.64	47.37	54.00	-6.63	Average	VERTICAL
2	2390.00	61.33	-1.64	59.69	74.00	-14.31	Peak	VERTICAL
3	2400.00	73.89	-1.52	72.37	82.98	-10.61	Peak	VERTICAL
4	2413.94	104.48	-1.50	102.98	F	--	Peak	VERTICAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Bandedge Low Ch Tested by : Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	44.02	-1.64	42.38	54.00	-11.62	Average	HORIZONTAL
2	2390.00	56.34	-1.64	54.70	74.00	-19.30	Peak	HORIZONTAL
3	2400.00	68.11	-1.52	66.59	78.58	-11.99	Peak	HORIZONTAL
4	2410.13	100.09	-1.51	98.58	F	--	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE HE20 mode Bandedge Low Ch Tested by :
Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE HE20 mode Bandedge Low Ch Tested by :
Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Bandedge Low Ch Tested by : Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Bandedge Low Ch Tested by : Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	49.92	-1.64	48.28	74.00	-25.72	Peak	HORIZONTAL
2	2400.00	64.09	-1.52	62.57	78.71	-16.14	Peak	HORIZONTAL
3	2413.26	100.21	-1.50	98.71	F	--	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC g mode Bandedge Low Ch Tested by : Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	45.81	-1.64	44.17	54.00	-9.83	Average	VERTICAL
2	2390.00	58.22	-1.64	56.58	74.00	-17.42	Peak	VERTICAL
3	2400.00	67.35	-1.52	65.83	70.07	-4.24	Peak	VERTICAL
4	2413.60	91.57	-1.50	90.07	F	--	Peak	VERTICAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC g mode Bandedge Low Ch Tested by : Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	54.91	-1.64	53.27	54.00	-0.73	Average	HORIZONTAL
2	2390.00	68.97	-1.64	67.33	74.00	-6.67	Peak	HORIZONTAL
3	2400.00	79.40	-1.52	77.88	80.36	-2.48	Peak	HORIZONTAL
4	2414.27	101.86	-1.50	100.36	F	--	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Bandedge Low Ch Tested by :
Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Bandedge Low Ch Tested by :
Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	54.90	-1.64	53.26	54.00	-0.74	Average	HORIZONTAL
2	2390.00	70.18	-1.64	68.54	74.00	-5.46	Peak	HORIZONTAL
3	2400.00	79.92	-1.52	78.40	80.30	-1.90	Peak	HORIZONTAL
4	2411.14	101.80	-1.50	100.30	F	--	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC HE20 mode Bandedge Low Ch Tested by :
Barry Lee




Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan

Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC HE20 mode Bandedge Low Ch Tested by :
Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2390.00	52.17	-1.64	50.53	54.00	-3.47	Average	HORIZONTAL
2	2390.00	66.67	-1.64	65.03	74.00	-8.97	Peak	HORIZONTAL
3	2400.00	73.27	-1.52	71.75	81.22	-9.47	Peak	HORIZONTAL
4	2413.71	102.72	-1.50	101.22	F	--	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Bandedge High Ch Tested by : Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE b mode Bandedge High Ch Tested by : Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2460.88	95.84	-1.51	94.33	F	---	Peak	HORIZONTAL
2	2483.50	48.78	-1.28	47.50	74.00	-26.50	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE g mode Bandedge High Ch Tested by : Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE g mode Bandedge High Ch Tested by : Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2461.02	97.22	-1.51	95.71	F	---	Peak	HORIZONTAL
2	2483.50	41.20	-1.28	39.92	54.00	-14.08	Average	HORIZONTAL
3	2483.50	58.49	-1.28	57.21	74.00	-16.79	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Bandedge High Ch Tested by :
Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE n20 mode Bandedge High Ch Tested by :
Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE HE20 mode Bandedge High Ch Tested by :
Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2463.66	106.36	-1.47	104.89	F	---	Peak	VERTICAL
2	2483.50	43.73	-1.28	42.45	54.00	-11.55	Average	VERTICAL
3	2483.50	60.66	-1.28	59.38	74.00	-14.62	Peak	VERTICAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : EE HE20 mode Bandedge High Ch Tested by :
Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Bandedge High Ch Tested by : Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC b mode Bandedge High Ch Tested by : Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC g mode Bandedge High Ch Tested by : Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address: No. 120, Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC g mode Bandedge High Ch Tested by : Barry Lee




No	Freq MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol V/H
1	2460.98	102.19	-1.51	100.68	F	---	Peak	HORIZONTAL
2	2483.50	52.93	-1.28	51.65	54.00	-2.35	Average	HORIZONTAL
3	2483.50	69.47	-1.28	68.19	74.00	-5.81	Peak	HORIZONTAL

Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Bandedge High Ch Tested by :
Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC n20 mode Bandedge High Ch Tested by :
Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15


Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC HE20 mode Bandedge High Ch Tested by :
Barry Lee



Note: "F" denotes fundamental frequency.

International Standard Laboratory Corp.
Company Address:No.120,Lane 180, Hsin Ho Rd.
Lung-Tan Dist., Tao Yuan City 325, Taiwan
Date: 2024-10-15

Project Number. : 24LR0141 Temp.(°C)/RH(%) : 24/57
Test Mode : CC HE20 mode Bandedge High Ch Tested by :
Barry Lee



Note: "F" denotes fundamental frequency.

9. 6dB Bandwidth

9.1 Standard Applicable

According to §15.247(a)(2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500kHz.

According to RSS-247 issue 2, §5.2

(a)The minimum 6 dB bandwidth shall be 500 kHz.


9.2 Measurement Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as
 - RBW = 100 kHz.
 - VBW $\geq 3 \times$ RBW.
 - Detector = Peak.
 - Trace mode = max hold.
 - Sweep = auto couple.
 - Allow the trace to stabilize.
 - Use 6-dB BW measurement function
4. Repeat above procedures until all frequency measured were complete.


9.3 Measurement Result

Band	Frequency (MHz)	6dB Bandwidth (MHz)	6dB BW Limit (kHz)
802.11b	2412	9.077	≥ 500
	2437	9.084	≥ 500
	2462	9.094	≥ 500
802.11g	2412	15.120	≥ 500
	2437	15.120	≥ 500
	2462	15.113	≥ 500
802.11n HT20	2412	15.131	≥ 500
	2437	15.132	≥ 500
	2462	15.109	≥ 500
802.11ax HE20	2412	18.142	≥ 500
	2437	18.101	≥ 500
	2462	18.142	≥ 500


Test Data: Ant1 b 2412MHz




Test Data: Ant1 b 2437MHz




Test Data: Ant1 b 2462MHz




Test Data: Ant1 g 2412MHz




Test Data: Ant1 g 2437MHz




Test Data: Ant1 g 2462MHz




Test Data: Ant1 HT20 2412MHz




Test Data: Ant1 HT20 2437MHz




Test Data: Ant1 HT20 2462MHz




Test Data: Ant1 HE20 2412MHz



Test Data: Ant1 HE20 2437MHz



Test Data: Ant1 HE20 2462MHz



10. Peak Power Spectral Density

10.1 Standard Applicable

According to §15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

According to RSS-247 issue 2, §5.2

(2)The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of Section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

10.2 Measurement Procedure


1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW =3kHz, VBW = 10kHz, Set the span to 1.5 DTS bandwidth., Sweep=Auto
4. Record the max. reading.
5. Repeat above procedures until all frequency measured were complete.

10.3 Measurement Result

CDD mode

Mode	Freq. (MHz)	PSD (dBm/3kHz)				Duty Factor (dB)	Total PSD (dBm/MHz)	PSD Limit (dBm/MHz)
		Chain 0	Chain 1	Chain 2	Chain 3			
802.11b	2412	-15.174				-----	-15.174	8
	2437	-11.255				-----	-11.255	8
	2462	-14.814				-----	-14.814	8
802.11g	2412	-17.885				-----	-17.885	8
	2437	-14.327				-----	-14.327	8
	2462	-18.731				-----	-18.731	8
802.11n HT20	2412	-15.872				-----	-15.872	8
	2437	-12.909				-----	-12.909	8
	2462	-16.991				-----	-16.991	8
802.11ax HE20	2412	-17.899				-----	-17.899	8
	2437	-13.536				-----	-13.536	8
	2462	-18.206				-----	-18.206	8


Test Data: Ant1 b 2412MHz




Test Data: Ant1 b 2437MHz




Test Data: Ant1 b 2462MHz




Test Data: Ant1 g 2412MHz




Test Data: Ant1 g 2437MHz




Test Data: Ant1 g 2462MHz




Test Data: Ant1 HT20 2412MHz




Test Data: Ant1 HT20 2437MHz




Test Data: Ant1 HT20 2462MHz




Test Data: Ant1 HE20 2422MHz



Test Data: Ant1 HE20 2437MHz



Test Data: Ant1 HE20 2452MHz



11. Appendix

11.1 Appendix A: Equipment List

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction 03	EMI Receiver 19	R&S	ESR3	102460	04/24/2024	04/24/2025
Conduction 03	Chamber05_01 Cable	WOKEN	CFD 300-NL	Chamber05-1 Cable	08/02/2024	08/02/2025
Conduction 03	LISN 15	R&S	ENV216	101335	11/24/2023	11/24/2024
Conduction 03	LISN_22	ROHDE & SCHWARZ	ENV216	101478	10/14/2024	10/14/2025
Conduction 03	ISN T8 CAT6A_03	SCHWARZBECK	NTFM 8158	NTFM 8158-00367	06/20/2024	06/20/2025
Conduction 03	ISN T4_06	TESEQ	ISN T400A	28574	09/12/2024	09/12/2025
Conduction 03	ISN T8_09	TESEQ	ISN T800	36190	08/28/2024	08/28/2025
Conduction 03	CDN ISN ST08A_01	TESEQ	CDN ISN ST08A	43352	09/06/2024	09/06/2025
Conduction 03	Capacitive Voltage Probe_01	SCHAFFNER	CVP 2200A	18711	02/05/2024	02/05/2025
Conduction 03	Current Probe_01	SCHAFFNER	SMZ 11	18030	01/30/2024	01/30/2025
Conduction 03 (>16A)	LISN_25	SCHWARZBECK	NNLK 8121	8121-807	06/21/2024	06/21/2025

Location Conducted	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Chamber 19	Spectrum analyzer	R&S	FSV40	101919	07/13/2024	07/13/2025
Chamber 19	EMI Receiver	R&S	ESR3	102461	05/08/2024	05/08/2025
Chamber 19	Loop Antenna	EM	EM-6879	271	09/25/2024	09/25/2025
Chamber 19	Bilog Antenna (30MHz-1GHz)	Schwarzbeck	VULB9168 w 6dB Att.	9168-736	03/08/2024	03/08/2025
Chamber 19	Horn antenna (1GHz-18GHz)	ETS • LINDGREN	3117	00218718	10/04/2024	10/04/2025
Chamber 19	Horn antenna (18GHz-26GHz)	Com-power	AH-826	081001	11/24/2023	11/24/2024
Chamber 19	Horn antenna (26GHz-40GHz)	Com-power	AH-640	100A	03/19/2024	03/19/2025
Chamber 19	Preamplifier (9kHz-3GHz)	EM	EM330	060822	01/08/2024	01/08/2025
Chamber 19	Preamplifier (1GHz-26GHz)	HP	8449B	3008A02471	10/23/2024	10/23/2025
Chamber 19	Preamplifier (26GHz-40GHz)	MITEQ	JS4-26004000-27-5A	818471	05/13/2024	05/13/2025
Chamber 19	RF Cable (9kHz-26.5GHz)	Huber Suhner	Sucoflex 104A	MY1394/4A & 50886/4A	07/15/2024	07/15/2025
Chamber 19	RF Cable (18GHz-40GHz)	HUBER SUHNER	Sucoflex 102	27963/2&37421/2	11/22/2023	11/22/2024
Chamber 19	MXG Vector Signal Generator	Keysight	N5182B	MY53052399	12/26/2023	12/26/2024
Chamber 19	Test Software	Audix	E3 Ver:6.120203b	N/A	N/A	N/A

Location Conducted	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conducted	Power Meter	Anritsu	ML2495A	1116010	09/26/2024	09/26/2025
Conducted	Power Sensor	Anritsu	MA2411B	34NKF50	09/26/2024	09/26/2025
Conducted	Temperature Chamber	KSON	THS-B4H100	2287	05/10/2024	05/09/2025
Conducted	DC Power supply	ABM	8185D	N/A	01/03/2024	01/03/2025
Conducted	AC Power supply	EXTECH	CFC105W	NA	N/A	N/A
Conducted	Spectrum analyzer	Keysight	N9010A	MY56070257	09/25/2024	09/25/2025
Conducted	Test Software	DARE	Radiation Ver:2013.1.23	NA	NA	NA
Conducted	Wideband Radio Comm. Tester	R&S	CMW500	1201.002K501087 93-JG	10/26/2024	10/26/2025
Conducted	Radio Communication Test Station	Anritsu	MT8000A	6272539604	08/29/2024	08/29/2025
Conducted	MT8000A Test Software	Anritsu	MX800000A Application Launcher V10.10.34.0	NA	NA	NA
Conducted	BT Simulator	Agilent	N4010A	MY48100200	NA	NA
Conducted	MXG Vector Signal Generator	Keysight	N5182B	MY53052399	12/26/2023	12/26/2024
Conducted (TS8997)	Wideband Radio Comm. Tester	R&S	CMW500	168811	09/25/2024	09/25/2025
Conducted (TS8997)	UP/DOWN converter	R&S	CMW-Z800A	100566	09/25/2024	09/25/2025
Conducted (TS8997)	Signal Generator	R&S	SMB100A	183701	09/10/2024	09/10/2025
Conducted (TS8997)	Vector Signal Generator	R&S	SMM100A	101908	09/10/2024	09/10/2025
Conducted (TS8997)	Signal analyzer 40GHz	R&S	FSV40	101884	09/11/2024	09/11/2025
Conducted (TS8997)	OSP150 extension unit CAM-BUS	R&S	OSP150	101107	09/11/2024	09/11/2025
Conducted (TS8997)	Test Software	R&S	EMC32 Ver: 12.00.00	NA	NA	NA

11.2 Appendix B: Uncertainty of Measurement

ISO/IEC 17025 requires that an estimate of measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).


Parameter	Uncertainty (k=2)
Conducted Emission (AC power line)	± 1.6 dB
Spurious emissions, radiated	± 4.78 dB
RF power, conducted	± 2.20 dB
Power Density	± 2.21 dB
RF Frequency	± 1.43 %
DC Voltage	± 2.12 %

AC Line Conduced Emission Test Setup


-
- The diagram illustrates a conducted emission test setup. A test table is positioned on a vertical reference ground plane. On the table, there is a Current probe (CVP) connected to a Cable to AE. A Cable 0.04 m from VRGP is also connected to the CVP. The EUT/AE PSU is connected to the EUT and EUT/AE. Dimensions include 0.1 m for the distance from the CVP to the EUT/AE PSU, 0.3 m for the distance from the EUT/AE PSU to the EUT, and 0.8 m for the distance from the EUT/AE PSU to the EUT/AE. The EUT and EUT/AE are separated by 0.1 m. The table height is 0.8 m. The distance from the table to the vertical reference ground plane is 0.4 m. The distance from the table to the AMN / LISN is 0.8 m. The distance from the table to the AMN / LISN is 0.4 m. The distance from the table to the AMN / LISN is 0.8 m. The distance from the table to the AMN / LISN is 0.4 m.

Radiated Spurious Emission Test & 100kHz Bandwidth of Band Edges Measurement Test Setup

(A) Radiated Emission Test Setup for frequency below 1000MHz



(B) Radiated Emission Test Setup for frequency above 1 GHz



RF Conducted Measurement Test Setup

