

FCC §15.247 (I) & §1.1307 (B) (3) & §2.1091- MPE-BASED EXEMPTION

Applicable Standard

According to subpart 1.1307 (b) (3) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

Result

Mode	Frequency (MHz)	Tune up conducted power	Antenna Gain		ERP		Evaluation Distance (m)	ERP Limit (W)
		(dBm)	(dBi)	(dBd)	(dBm)	(W)		
Bluetooth	2402-2480	3.0	2.46	0.31	3.31	0.002	0.2	0.768
BLE	2402-2480	1.0	2.46	0.31	1.31	0.001	0.2	0.768
2.4G Wi-Fi	2412-2462	21.0	2.46	0.31	21.31	0.135	0.2	0.768
5G Wi-Fi	5150-5250	16.0	2.94	0.79	16.79	0.048	0.2	0.768
	5250-5350	16.0	2.94	0.79	16.79	0.048	0.2	0.768
	5470-5725	13.0	2.94	0.79	13.79	0.024	0.2	0.768
	5725-5850	15.0	2.94	0.79	15.79	0.038	0.2	0.768

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.

2. The Bluetooth/BLE/Wi-Fi can't simultaneous transmitting.

3. 0dBd=2.15dBi

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.