



TEST REPORT

For Bluetooth-EDR

Report No..... : CHTW25050058

Project No : SHT2502040501W

FCC ID : XAK436HDB

Applicant's name : AudioCodes Ltd.

Address : 6 Ofra Haza Street Oryehuda Israel

Product Name : IP Phone

Trade Mark..... : 

Model No..... : C436HD

Listed Model(s) : -

Standard : **FCC CFR Title 47 Part 15 Subpart C § 15.247**


Date of receipt of test sample..... : 2025/3/6


Date of testing..... : 2025/3/6- 2025/5/20


Date of issue..... : 2025/5/21

Result..... : **Pass**



Compiled by
(Position+Printed name+Signature) : File administrator Xiaodong Zhao 

Supervised by
(Position+Printed name+Signature) : Project Engineer Kiki Kong 

Approved by
(Position+Printed name+Signature) : RF Manager Xu Yang 

Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address : Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China

Test Report Form No. : R0054

Test Report Form(s) Originator : Shenzhen Huatongwei International Inspection Co., Ltd.

Master TRF : Dated 2025-04

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. The test report merely correspond to the test sample. The authenticity of this Test Report and its contents can be verified by contacting the Laboratory, responsible for this Test Report.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Radio Specification Description	5
3.4.	Testing Laboratory Information	6
<u>4.</u>	<u>TEST CONFIGURATION</u>	<u>7</u>
4.1.	Test frequency list	7
4.2.	Descriptions of Test mode	7
4.3.	Test mode	7
4.4.	Test sample information	8
4.5.	Support unit used in test configuration and system	8
4.6.	Testing environmental condition	8
4.7.	Statement of the measurement uncertainty	9
4.8.	Equipment Used during the Test	10
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>12</u>
5.1.	Antenna Requirement	12
5.2.	AC Conducted Emission	13
5.3.	Peak Output Power	15
5.4.	20 dB Bandwidth	16
5.5.	99% Occupied Bandwidth	17
5.6.	Carrier Frequencies Separation	18
5.7.	Hopping Channel Number	19
5.8.	Dwell Time	20
5.9.	Duty Cycle Correction Factor (DCCF)	21
5.10.	Pseudorandom Frequency Hopping Sequence	22
5.11.	Conducted Band edge and Spurious Emission	23
5.12.	Radiated Band edge Emission	24
5.13.	Radiated Spurious Emission	26
<u>6.</u>	<u>TEST SETUP PHOTOS</u>	<u>31</u>
<u>7.</u>	<u>EXTERNAL AND INTERNAL PHOTOS</u>	<u>33</u>
7.1.	External Photos	33
7.2.	Internal Photos	36
<u>8.</u>	<u>APPENDIX REPORT</u>	<u>39</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

- [FCC CFR Title 47 Part 15 Subpart C § 15.247](#): Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
- [ANSI C63.10:2020](#): American National Standard for Testing Unlicensed Wireless Devices
- [KDB 558074 D01 15.247 Meas Guidance v05r02](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

Revision No.	Date of issue	Description
N/A	2025-05-21	Original

2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result	Test Engineer
5.1	Antenna Requirement	15.203/15.247 (c)	PASS	Xiangyu Wei
5.2	AC Conducted Emission	15.207	PASS	YATING.CHEN
5.3	Peak Output Power	15.247 (b)(1)	PASS	Xiangyu Wei
5.4	20 dB Bandwidth	15.247 (a)(1)	PASS	Xiangyu Wei
5.5	99% Occupied Bandwidth	-	PASS*1	Xiangyu Wei
5.6	Carrier Frequency Separation	15.247 (a)(1)	PASS	Xiangyu Wei
5.7	Hopping Channel Number	15.247 (a)(1)	PASS	Xiangyu Wei
5.8	Dwell Time	15.247 (a)(1)	PASS	Xiangyu Wei
5.9	Duty Cycle Correction Factor	-	PASS*1	Xiangyu Wei
5.10	Pseudorandom Frequency Hopping Sequence	15.247(b)(4)	PASS	Xiangyu Wei
5.11	Conducted Band Edge and Spurious Emission	15.247(d)/15.205	PASS	Xiangyu Wei
5.12	Radiated Band Edge Emission	15.205/15.209	PASS	Yifan Wang
5.13	Radiated Spurious Emission	15.247(d)/15.205/15.209	PASS	Yifan Wang

Note:

- The measurement uncertainty is not included in the test result.
- *1: No requirement on standard, only report these test data.

3. SUMMARY

3.1. Client Information

Applicant:	AudioCodes Ltd.
Address:	6 Ofra Haza Street Oryehuda Israel
Manufacturer:	AudioCodes Ltd.
Address:	6 Ofra Haza Street Oryehuda Israel
Factory:	SerNet (Suzhou) Technologies Corp
Address:	No. 8 Tangzhuang Road, Suzhou Industrial Park, Jiangsu, Suzhou, 215021, CN

3.2. Product Description

Main unit information:	
Product Name:	IP Phone
Trade Mark:	
Model No.:	C436HD
Listed Model(s):	-
Power supply:	DC 12.0V from adapter or 48V POE
Hardware version:	GGWV00810
Software version:	2.7.372
Accessory unit information:	
Adapter information:	Model:RD1201000-C55-26MG Input:100-240Va.c., 50/60Hz 0.6MAX Output:12.0Vd.c.,1.0A

3.3. Radio Specification Description

Bluetooth version:	V5.0
Support function:	EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	FPC Antenna
Antenna gain:	3.72dBi

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China	
Contact information:	Tel: 400-963-0755 E-mail: cs@szhtw.com.cn http://www.szhtw.com.cn	
Qualifications	Type	Accreditation Number
	FCC Registration Number	762235
	FCC Designation Number	CN1181

4. TEST CONFIGURATION

4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

Channel	Frequency (MHz)
00	2402
01	2403
:	:
39	2441
:	:
77	2479
78	2480

4.2. Descriptions of Test mode

Preliminary tests were performed in different data rates and recorded the RF output power in the clause 5.3

Note:

- 1) The manufacturer declare that the maximum power value of the product is set as a default value in the enter test mode software.
- 2) All the test data for each data rate were verified, found 8DPSK Modulation which is worse case mode

4.3. Test mode

For RF test items:			
The engineering test program was provided and enabled to make EUT continuous transmitting.			
Test Item	Modulation / Data Rate		
	GFSK 1Mbps	$\pi/4$ DQPSK 2Mbps	8DPSK 3Mbps
Conducted test item	✓	✓	✓
Radiated test item	-	-	✓
Remark:			
- For radiated test item, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests. - The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.			

4.4. Test sample information

Test item	HTW sample no.
RF Conducted test items	Refer to the description in the appendix report
RF Radiated test items	YPHT25020405002
EMI test items	YPHT25020405001

Note:

RF Conducted test items: Peak Output Power, 20 dB Bandwidth, 99% Occupied Bandwidth, Carrier Frequency Separation, Hopping Channel Number, Dwell Time, Duty Cycle Correction Factor, Pseudorandom Frequency Hopping Sequence, Conducted Band Edge and Spurious Emission

RF Radiated test items: Radiated Band Edge Emission, Radiated Spurious Emission

EMI test items: AC Conducted Emission

4.5. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?			
✓ No			
Item	Equipment	Trade Name	Model No.
1			
2			

4.6. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

4.7. Statement of the measurement uncertainty

No.	Test Items	Measurement Uncertainty
1	AC Conducted Emission	3.21dB
2	Peak Output Power	1.07
3	Power Spectral Density	1.07
4	6dB Bandwidth	0.002%
5	99% Occupied Bandwidth	0.002%
6	Duty cycle	-
7	Conducted Band Edge and Spurious Emission	1.68dB
8	Radiated Band Edge Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz
9	Radiated Spurious Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4.8. Equipment Used during the Test

● RF Conducted test item							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	HTWE0242	FSV40	100048	2024/08/27	2025/08/26
●	Signal & Spectrum Analyzer	R&S	HTWE0262	FSW26	103440	2024/08/21	2025/08/20
●	Vector signal generator	R&S	HTWE0244	SMBV100A	260790	2025/03/13	2026/03/12
●	Test software	Tonscend	N/A	JS1120	N/A	N/A	N/A

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2024/08/12	2025/08/11
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2024/08/12	2025/08/11
●	Protection Network	SCHWARZBECK	HTWE0567	VTSD9561FN	00899	2024/08/12	2025/08/11
●	ISN	FCC	HTWE0148	FCC-TLISN-T2-02	20371	2024/08/12	2025/08/11
●	ISN	FCC	HTWE0150	FCC-TLISN-T8-02	20375	2024/08/12	2025/08/11
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated Emission – 9kHz~30MHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2023/04/06	2026/04/05
●	EMI Test Receiver	R&S	HTWE0099	ESCI 7	100900	2024/08/12	2025/08/11
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2024/04/08	2027/04/07
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated Emission - 30MHz~1GHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2023/04/06	2026/04/05
●	EMI Test Receiver	R&S	HTWE0099	ESCI 7	100900	2024/08/12	2025/08/11
●	Ultra-Broadband Antenna	SCHWARZBEC K	HTWE0119	VULB9163	546	2023/02/22	2026/02/21
●	Pre-Amplifier	SCHWARZBEC K	HTWE0295	BBV 9742	/	2024/05/24	2025/05/23
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated emission- Above 1GHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	C11121	2023/04/17	2026/04/16
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2024/08/12	2025/08/11
●	Spectrum Analyzer	R&S	HTWE0385	N9020A	MY54486658	2024/08/12	2025/0811
●	Horn Antenna	SCHWARZBECK	HTWE0126	BBHA 9120D	1011	2023/02/14	2026/02/13
●	Pre-Amplifier	CD	HTWE0071	PAP-0102	12004	2024/06/06	2025/06/05
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0551	SCU18F	100855	2024/06/06	2025/06/05
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

REQUIREMENT

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

The antenna type is a FPC antenna, Refer to the below antenna photo.



5.2. AC Conducted Emission


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE


Refer to the clause 4.3

TEST RESULT

☒ Passed ☐ Not Applicable

Test Line:

L




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.527500	42.79	---	56.00	13.21	L1	10.4
0.539500	---	32.49	46.00	13.51	L1	10.4
0.807500	---	23.80	46.00	22.20	L1	10.5
0.855500	---	22.23	46.00	23.77	L1	10.5
1.011500	32.42	---	56.00	23.58	L1	10.5
1.039500	34.62	---	56.00	21.38	L1	10.5
1.047500	---	21.89	46.00	24.11	L1	10.5
1.064500	---	21.69	46.00	24.31	L1	10.5
1.071500	31.50	---	56.00	24.50	L1	10.5
1.107500	33.86	---	56.00	22.14	L1	10.5
1.467500	---	21.91	46.00	24.09	L1	10.5
1.479500	33.39	---	56.00	22.61	L1	10.5

Test Line:

N



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.531500	---	29.81	46.00	16.19	N	10.2
0.535500	38.46	---	56.00	17.54	N	10.2
0.791500	---	20.16	46.00	25.84	N	10.2
1.467500	---	19.86	46.00	26.14	N	10.2
3.803500	---	20.82	46.00	25.18	N	10.3
10.255500	---	23.69	50.00	26.31	N	10.4
11.791500	33.56	---	60.00	26.44	N	10.4
11.919500	33.41	---	60.00	26.59	N	10.4
12.139500	33.35	---	60.00	26.65	N	10.4
12.535500	34.11	---	60.00	25.89	N	10.4
13.927500	34.01	---	60.00	25.99	N	10.4
14.047500	---	26.07	50.00	23.93	N	10.4


5.3. Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1):

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.
For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the pathloss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
RBW $\geq$ the 20 dB bandwidth of the emission being measured, VBW $\geq$ RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE

Refer to the clause 4.3

TEST RESULT

☒ Passed ☐ Not Applicable

TEST DATA


Refer to the appendix report

5.4. 20 dB Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW $\geq$ 1% of the 20 dB bandwidth, VBW $\geq$ RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE

Refer to the clause 4.3

TEST RESULT

☒ Passed ☐ Not Applicable

TEST DATA


Refer to the appendix report

5.5. 99% Occupied Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = channel center frequency
Span $\geq 1.5 \times \text{OBW}$
RBW = 1%~5%OBW
VBW $\geq 3 \times \text{RBW}$
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

TEST MODE

Refer to the clause 4.3

TEST RESULT

☒ Passed ☐ Not Applicable

TEST DATA

Refer to the appendix report


5.6. Carrier Frequencies Separation

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels
RBW $\geq$ 1% of the span, VBW $\geq$ RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE

Refer to the clause 4.3

TEST RESULTS

☒ Passed ☐ Not Applicable

TEST DATA

Refer to the appendix report


5.7. Hopping Channel Number

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least **15** channels.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = the frequency band of operation
RBW $\geq$ 1% of the span, VBW $\geq$ RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE

Refer to the clause 4.3

TEST RESULTS

☒ Passed ☐ Not Applicable

TEST DATA


Refer to the appendix report

5.8. Dwell Time

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1): The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel, RBW= 1 MHz, VBW $\geq$ RBW
Sweep = as necessary to capture the entire dwell time per hopping channel,
Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE

Refer to the clause 4.3

TEST RESULTS

☒ Passed ☐ Not Applicable

TEST DATA


Refer to the appendix report

5.9. Duty Cycle Correction Factor (DCCF)

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel, RBW= 1 MHz, VBW $\geq$ RBW
Sweep = as necessary to capture the entire dwell time per hopping channel,
Detector function = peak, Trigger mode
4. Measure and record the duty cycle data

TEST MODE

Refer to the clause 4.3

TEST DATA

Refer to the appendix report

5.10. Pseudorandom Frequency Hopping Sequence


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

TEST RESULTS


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.


The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

5.11. Conducted Band edge and Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Emission level measurement
Set the center frequency and span to encompass frequency range to be measured
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum amplitude level.
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.

TEST MODE

Refer to the clause 4.3

TEST RESULT

☒ Passed ☐ Not Applicable

TEST DATA

Refer to the appendix report


5.12. Radiated Band edge Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
5. Use the following spectrum analyzer settings:
 - a) Span shall wide enough to fully capture the emission being measured
 - b) Set RBW=100kHz for <1GHz, VBW=3*RBW, Sweep time=auto, Detector=peak, Trace=max hold
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement: use duty cycle correction factor method (DCCF)
 Averager level = Peak level + DCCF

TEST MODE

Refer to the clause 4.3

TEST RESULT

☒ Passed ☐ Not Applicable

Note:

- 1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level– Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).

Test channel:		CH00		Polarity			Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	45.20	27.86	3.95	41.18	35.83	74.00	-38.17	Peak
2	2390.03	46.18	27.54	4.08	41.11	36.69	74.00	-37.31	Peak
Test channel:		CH00		Polarity			Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	45.62	27.86	3.95	41.18	36.25	74.00	-37.75	Peak
2	2390.03	50.16	27.54	4.08	41.11	40.67	74.00	-33.33	Peak

Test channel:		CH78		Polarity			Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	55.70	27.33	4.18	41.04	46.17	74.00	-27.83	Peak
2	2500.00	49.93	27.30	4.20	41.02	40.41	74.00	-33.59	Peak
Test channel:		CH78		Polarity			Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	45.26	27.33	4.18	41.04	35.73	74.00	-38.27	Peak
2	2500.00	45.31	27.30	4.20	41.02	35.79	74.00	-38.21	Peak

5.13. Radiated Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 40*log(300/3)= Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m +40*log(30/3)= Limit dBuV/m @30m + 40.


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


- 9 kHz ~ 30 MHz



- 30 MHz ~ 1 GHz



- Above 1 GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1 GHz:

RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;

If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement: use duty cycle correction factor method (DCCF)

Averager level = Peak level + DCCF

TEST MODE

Refer to the clause 4.3

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

Note:

- 1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level– Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.

For 9 kHz ~ 30 MHz


The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.

For 30 MHz ~ 1000 MHz

Have pre-scan all test channel, found CH39 which it was worst case, so only show the worst case's data on this report.

Polarization:


Horizontal

**Final Result**

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
104.3263	25.77	43.50	17.73	300.0	H	268.0	-10.2
128.8188	27.06	43.50	16.44	300.0	H	94.0	-13.3
175.6213	30.82	43.50	12.68	100.0	H	82.0	-12.4
296.9925	30.56	46.00	15.44	100.0	H	216.0	-7.0
850.0138	33.51	46.00	12.49	100.0	H	310.0	5.8
948.3475	38.30	46.00	7.70	300.0	H	12.0	7.5

Polarization:

Vertical

**Final Result**

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
58.1300	30.72	40.00	9.28	100.0	V	0.0	-9.2
116.9363	30.10	43.50	13.40	100.0	V	317.0	-11.9
135.0025	35.75	43.50	7.75	100.0	V	152.0	-13.8
175.5000	35.81	43.50	7.69	100.0	V	109.0	-12.4
495.1150	36.16	46.00	9.84	100.0	V	208.0	-1.5
948.4688	39.00	46.00	7.00	100.0	V	11.0	7.5

For 1 GHz ~ 25 GHz



Test channel		CH00			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2987.92	52.51	28.50	4.53	40.96	44.58	74.00	-29.42	Peak
2	4809.50	46.46	31.28	5.89	40.28	43.35	74.00	-30.65	Peak
3	4983.99	46.85	31.34	5.99	40.21	43.97	74.00	-30.03	Peak
4	9611.66	42.95	39.12	8.60	39.82	50.85	74.00	-23.15	Peak
Test channel		CH00			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	3003.17	57.24	28.51	4.54	40.95	49.34	74.00	-24.66	Peak
2	4267.18	50.80	30.07	5.81	40.49	46.19	74.00	-27.81	Peak
3	4996.69	50.96	31.39	6.00	40.20	48.15	74.00	-25.85	Peak
4	9611.66	42.45	39.12	8.60	39.82	50.35	74.00	-23.65	Peak

Test channel		CH39			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2995.54	49.07	28.50	4.53	40.95	41.15	74.00	-32.85	Peak
2	4983.99	46.79	31.34	5.99	40.21	43.91	74.00	-30.09	Peak
3	8022.46	42.11	37.00	8.04	39.93	47.22	74.00	-26.78	Peak
4	9611.66	42.13	39.12	8.60	39.82	50.03	74.00	-23.97	Peak
Test channel		CH39			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	3003.17	57.24	28.51	4.54	40.95	49.34	74.00	-24.66	Peak
2	4256.33	52.75	30.03	5.79	40.47	48.10	74.00	-25.90	Peak
3	4996.69	51.96	31.39	6.00	40.20	49.15	74.00	-24.85	Peak
4	9611.66	42.45	39.12	8.60	39.82	50.35	74.00	-23.65	Peak

Test channel		CH78			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	4004.08	45.83	29.81	5.44	40.31	40.77	74.00	-33.23	Peak
2	4996.69	45.22	31.39	6.00	40.20	42.41	74.00	-31.59	Peak
3	7451.57	43.33	36.20	7.75	39.92	47.36	74.00	-26.64	Peak
4	11370.05	40.52	40.31	9.10	40.33	49.60	74.00	-24.40	Peak
Test channel		CH78			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2995.54	53.85	28.50	4.53	40.95	45.93	74.00	-28.07	Peak
2	3993.90	47.00	29.79	5.43	40.32	41.90	74.00	-32.10	Peak
3	4996.69	49.99	31.39	6.00	40.20	47.18	74.00	-26.82	Peak
4	6974.36	47.44	35.00	7.38	39.46	50.36	74.00	-23.64	Peak

6. TEST SETUP PHOTOS

Radiated Emission





AC Conducted Emission



7. EXTERNAL AND INTERNAL PHOTOS


7.1. External Photos












7.2. Internal Photos









8. APPENDIX REPORT

APPENDIX REPORT

Project No.	SHT2502040501W	Radio Specification	Bluetooth EDR
Test sample No.	YPHT25020405002	Model No.	C436HD
Start test date	2025-04-30	Finish date	2025-05-07
Temperature	23.1℃	Humidity	53%
Test Engineer	Xiangyu Wei	Auditor	Xiaodong Zhu

Appendix clause	Test item	Result
A	Peak Output Power	PASS
B	20 dB Bandwidth	PASS
C	99% Occupied Bandwidth	PASS
D	Carrier Frequencies Separation	PASS
E	Hopping Channel Number	PASS
F	Dwell Time	PASS
G	Duty Cycle Correction Factor (DCCF)	PASS
H	Band edge and Spurious Emissions(coducted)	PASS


Appendix A: Peak Output Power

Modulation type	Channel	Peak Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
GFSK	00	4.13	4.01	≤ 30.00	Pass
	39	4.18	4.04		
	78	3.61	3.43		
$\pi/4$ DQPSK	00	6.25	6.02	≤ 21.00	Pass
	39	5.99	5.73		
	78	5.08	4.89		
8DPSK	00	6.78	6.57	≤ 21.00	Pass
	39	6.52	6.42		
	78	5.66	5.52		


Modulation Type:

GFSK


CH00



CH39




CH78




Modulation Type:

π /4DQPSK


CH00



CH39




CH78




Modulation Type:

8DPSK


CH00



CH39



CH78




Appendix B : 20 dB Bandwidth

Modulation type	Channel	20 dB Bandwidth (kHz)	Limit (kHz)	Result
GFSK	00	985.00	-	Pass
	39	972.00		
	78	963.00		
$\pi/4$ DQPSK	00	1320.00	-	Pass
	39	1305.00		
	78	1315.00		
8DPSK	00	1293.00	-	Pass
	39	1325.00		
	78	1302.00		


Modulation Type:

GFSK


CH00



CH39




CH78




Modulation Type:

$\pi/4$ DQPSK


CH00



CH39




CH78




Modulation Type:

8DPSK


CH00



CH39



CH78



Appendix C: 99% Occupied Bandwidth


Modulation type	Channel	99% Occupied Bandwidth (MHz)	Limit (MHz)	Result
GFSK	00	0.91	-	Pass
	39	0.89		
	78	0.89		
$\pi/4$ DQPSK	00	1.18	-	Pass
	39	1.18		
	78	1.18		
8DPSK	00	1.18	-	Pass
	39	1.18		
	78	1.18		

Modulation Type: GFSK	
CH00	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 30 kHz Att 30 dB SWT 63.1 μs VBW 100 kHz Mode Auto FFT Count 300/300 1Pk View M1[1] 2.64 dBm 2.40200500 GHz 909.090909091 kHz Occ Bw T1 T2 CF 2.402 GHz 1001 pts Span 2.5 MHz Date: 27 APR 2025 22:26:09
CH39	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 30 kHz Att 30 dB SWT 63.1 μs VBW 100 kHz Mode Auto FFT Count 300/300 1Pk View M1[1] 2.61 dBm 2.44116230 GHz 889.110889111 kHz Occ Bw T1 T2 CF 2.441 GHz 1001 pts Span 2.5 MHz Date: 27 APR 2025 22:27:52
CH78	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 30 kHz Att 30 dB SWT 63.1 μs VBW 100 kHz Mode Auto FFT Count 300/300 1Pk View M1[1] 2.42 dBm 2.47983270 GHz 891.608391608 kHz Occ Bw T1 T2 CF 2.48 GHz 1001 pts Span 2.5 MHz Date: 27 APR 2025 22:29:25

Modulation Type:


$\pi/4$ DQPSK

CH00




Date: 27 APR 2025 22:31:06

CH39



Date: 27 APR 2025 22:32:46

CH78




Date: 27 APR 2025 22:34:13

Modulation Type:


8DPSK

CH00




Date: 27 APR 2025 22:55:52

CH39



Date: 27 APR 2025 22:57:22

CH78



Date: 27 APR 2025 22:58:42

Appendix D: Carrier Frequencies Separation

Modulation type	Channel	Carrier Frequencies Separation (MHz)	Limit (kHz) *	Result
GFSK	39	1.00	≥985.00	Pass
π/4DQPSK	39	1.00	≥880.00	Pass
8DPSK	39	1.17	≥883.33	Pass

Note:

*: GFSK limit = The maximum 20 dB Bandwidth for GFSK modulation on the appendix B.

π/4DQPSK limit = $\frac{2}{3}$ * The maximum 20 dB Bandwidth for π/4DQPSK modulation on the appendix B.


8DPSK limit = $\frac{2}{3}$ * The maximum 20 dB Bandwidth for 8DPSK modulation on the appendix B

GFSK	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 30 kHz Att 30 dB SWT 63.2 μs VBW 100 kHz Mode Auto FFT Count 100/100 1Pk View M1[1] 5.74 dBm 2.44116522 GHz 0.10 dB 1.00000 MHz D1[1] D1 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm Start 2.44 GHz 691 pts Stop 2.443 GHz Date: 27 APR 2025 22:41:06
π /4DQPSK	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 30 kHz Att 30 dB SWT 63.2 μs VBW 100 kHz Mode Auto FFT Count 100/100 1Pk View M1[1] 1.91 dBm 2.44098696 GHz 0.05 dB 1.00000 MHz D1[1] D1 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm Start 2.44 GHz 691 pts Stop 2.443 GHz Date: 27 APR 2025 22:44:09
8DPSK	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 30 kHz Att 30 dB SWT 63.2 μs VBW 100 kHz Mode Auto FFT Count 100/100 1Pk View M1[1] 1.84 dBm 2.44098696 GHz 0.15 dB 1.16957 MHz D1[1] D1 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm Start 2.44 GHz 691 pts Stop 2.443 GHz Date: 27 APR 2025 22:46:43


Appendix E: Hopping Channel Number

Modulation type	Channel number	Limit	Result
GFSK	79	≥15.00	Pass
π/4DQPSK	79		
8DPSK	79		


GFSK



$\pi/4$ DQPSK



8DPSK




Appendix F: Dwell Time

Modulation type	Packet	Burst Width [ms]	Total Hops[hop*ch]	Dwell time (Second)	Limit (Second)	Result
GFSK	DH1	0.38	318.00	0.12	≤ 0.40	Pass
	DH3	1.64	156.00	0.26		
	DH5	2.89	99.00	0.29		
$\pi/4$ DQPSK	2DH1	0.39	317.00	0.12	≤ 0.40	Pass
	2DH3	1.14	170.00	0.19		
	2DH5	2.13	100.00	0.21		
8DPSK	3DH1	0.39	319.00	0.12	≤ 0.40	Pass
	3DH3	1.64	158.00	0.26		
	3DH5	2.66	134.00	0.36		


Modulation Type:

GFSK


DH1
Burst width



DH1
Burst number



DH3
Burst width




Appendix report page: 20 of 41


Modulation Type:

$\pi/4$ DQPSK


2DH1
Burst width






2DH1
Burst number



2DH3
Burst width




2DH3 Burst number	
2DH5 Burst width	
2DH5 Burst number	


Modulation Type:

8DPSK


3DH1
Burst width






3DH1
Burst number




3DH3
Burst width



3DH3 Burst number	 The spectrum plot shows a dense signal across the frequency range. The y-axis represents power in dBm, ranging from -70 to 10. The x-axis represents time in seconds, ranging from 0 to 3.16 s. The plot is titled 'Spectrum' and includes parameters: Ref Level 20.00 dBm, Att 30 dB, RBW 500 kHz, SGL TRG:VID, and IAP Clrw. A red trigger line is set at 2.000 dBm. The date is 27 APR 2025 23:01:07.
3DH5 Burst width	 The spectrum plot shows a signal burst. The y-axis represents power in dBm, ranging from -70 to 10. The x-axis represents time in seconds, ranging from 0 to 1.0 ms. The plot is titled 'Spectrum' and includes parameters: Ref Level 20.00 dBm, Att 30 dB, RBW 1 MHz, SGL TRG:VID, and IAP Clrw. A red trigger line is set at 5.000 dBm. The plot also shows measurement results: M1[1] 2.94 dBm, D1[1] -200.00 µs, and a duration of 2.66000 ms. The date is 27 APR 2025 23:01:26.
3DH5 Burst number	 The spectrum plot shows a dense signal across the frequency range. The y-axis represents power in dBm, ranging from -70 to 10. The x-axis represents time in seconds, ranging from 0 to 3.16 s. The plot is titled 'Spectrum' and includes parameters: Ref Level 20.00 dBm, Att 30 dB, RBW 500 kHz, SGL TRG:VID, and IAP Clrw. A red trigger line is set at 2.000 dBm. The date is 27 APR 2025 23:01:59.


Appendix G: Duty Cycle Correction Factor (DCCF)

DCCF Calculate Formula					
$DCCF = 20 * \text{Log}(\text{duty cycle}) = 20 * \text{Log}(T_{\text{on time}} / T_{\text{period}})$					
Modulation type	Test Frequency (MHz)	$T_{\text{on time}}$ for single burst [ms]	T_{period} [ms]	Burst Quantity	DCCF [dB]
GFSK	2441	2.87	100	1.00	
$\pi/4$ DQPSK	2441	2.87	100	2.00	
8DPSK	2441	2.87	100	1.00	




Test Item:	Band edge	Modulation type:	GFSK																																										
CH00 No hopping mode	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep Count 300/300 1Pk Max M1[1] 3.85 dBm 2.40204 GHz M2[1] -51.78 dBm 2.400000 GHz D1 -16.150 dBm Start 2.31 GHz 691 pts Stop 2.405 GHz Marker <table border="1"> <thead> <tr> <th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr> </thead> <tbody> <tr> <td>M1</td><td>1</td><td></td><td>2.40204 GHz</td><td>3.85 dBm</td><td></td><td></td></tr> <tr> <td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-51.78 dBm</td><td></td><td></td></tr> <tr> <td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-55.94 dBm</td><td></td><td></td></tr> <tr> <td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-54.09 dBm</td><td></td><td></td></tr> <tr> <td>M5</td><td>1</td><td></td><td>2.399906 GHz</td><td>-52.23 dBm</td><td></td><td></td></tr> </tbody> </table> Date: 27 APR 2025 22:26:30			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.40204 GHz	3.85 dBm			M2	1		2.4 GHz	-51.78 dBm			M3	1		2.39 GHz	-55.94 dBm			M4	1		2.31 GHz	-54.09 dBm			M5	1		2.399906 GHz	-52.23 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.40204 GHz	3.85 dBm																																									
M2	1		2.4 GHz	-51.78 dBm																																									
M3	1		2.39 GHz	-55.94 dBm																																									
M4	1		2.31 GHz	-54.09 dBm																																									
M5	1		2.399906 GHz	-52.23 dBm																																									
CH00 Hopping mode	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep Count 500/500 1Pk Max M1[1] 3.52 dBm 2.40287 GHz M2[1] -54.80 dBm 2.400000 GHz D1 -16.460 dBm Start 2.31 GHz 691 pts Stop 2.405 GHz Marker <table border="1"> <thead> <tr> <th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr> </thead> <tbody> <tr> <td>M1</td><td>1</td><td></td><td>2.40287 GHz</td><td>3.52 dBm</td><td></td><td></td></tr> <tr> <td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-54.80 dBm</td><td></td><td></td></tr> <tr> <td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-54.22 dBm</td><td></td><td></td></tr> <tr> <td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-55.10 dBm</td><td></td><td></td></tr> <tr> <td>M5</td><td>1</td><td></td><td>2.39188 GHz</td><td>-52.43 dBm</td><td></td><td></td></tr> </tbody> </table> Date: 27 APR 2025 22:42:09			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.40287 GHz	3.52 dBm			M2	1		2.4 GHz	-54.80 dBm			M3	1		2.39 GHz	-54.22 dBm			M4	1		2.31 GHz	-55.10 dBm			M5	1		2.39188 GHz	-52.43 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.40287 GHz	3.52 dBm																																									
M2	1		2.4 GHz	-54.80 dBm																																									
M3	1		2.39 GHz	-54.22 dBm																																									
M4	1		2.31 GHz	-55.10 dBm																																									
M5	1		2.39188 GHz	-52.43 dBm																																									
CH78 No hopping mode	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 56.9 μs VBW 300 kHz Mode Auto FFT Count 300/300 1Pk Max M1[1] 3.56 dBm 2.479990 GHz M2[1] -58.16 dBm 2.4835000 GHz D1 -16.440 dBm Start 2.478 GHz 691 pts Stop 2.5 GHz Marker <table border="1"> <thead> <tr> <th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr> </thead> <tbody> <tr> <td>M1</td><td>1</td><td></td><td>2.47999 GHz</td><td>3.56 dBm</td><td></td><td></td></tr> <tr> <td>M2</td><td>1</td><td></td><td>2.4835 GHz</td><td>-58.16 dBm</td><td></td><td></td></tr> <tr> <td>M3</td><td>1</td><td></td><td>2.5 GHz</td><td>-59.60 dBm</td><td></td><td></td></tr> <tr> <td>M4</td><td>1</td><td></td><td>2.4842174 GHz</td><td>-57.00 dBm</td><td></td><td></td></tr> </tbody> </table> Date: 27 APR 2025 22:29:46			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.47999 GHz	3.56 dBm			M2	1		2.4835 GHz	-58.16 dBm			M3	1		2.5 GHz	-59.60 dBm			M4	1		2.4842174 GHz	-57.00 dBm									
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.47999 GHz	3.56 dBm																																									
M2	1		2.4835 GHz	-58.16 dBm																																									
M3	1		2.5 GHz	-59.60 dBm																																									
M4	1		2.4842174 GHz	-57.00 dBm																																									

CH78
Hopping mode




Test Item:	Band edge	Modulation type:	$\pi/4$ DQPSK																																										
CH00 No hopping mode	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep Count 500/500 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] M2[1] D1 -15.550 dBm M3 M4 M5 4.45 dBm 2.401770 GHz -52.16 dBm 2.400000 GHz Start 2.31 GHz 691 pts Stop 2.405 GHz Marker <table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td></td><td>1</td><td>2.40177 GHz</td><td>4.45 dBm</td><td></td><td></td></tr><tr><td>M2</td><td></td><td>1</td><td>2.4 GHz</td><td>-52.16 dBm</td><td></td><td></td></tr><tr><td>M3</td><td></td><td>1</td><td>2.39 GHz</td><td>-54.87 dBm</td><td></td><td></td></tr><tr><td>M4</td><td></td><td>1</td><td>2.31 GHz</td><td>-54.55 dBm</td><td></td><td></td></tr><tr><td>M5</td><td></td><td>1</td><td>2.399493 GHz</td><td>-51.45 dBm</td><td></td><td></td></tr></table> Date: 27 APR 2025 22:31:27			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1		1	2.40177 GHz	4.45 dBm			M2		1	2.4 GHz	-52.16 dBm			M3		1	2.39 GHz	-54.87 dBm			M4		1	2.31 GHz	-54.55 dBm			M5		1	2.399493 GHz	-51.45 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1		1	2.40177 GHz	4.45 dBm																																									
M2		1	2.4 GHz	-52.16 dBm																																									
M3		1	2.39 GHz	-54.87 dBm																																									
M4		1	2.31 GHz	-54.55 dBm																																									
M5		1	2.399493 GHz	-51.45 dBm																																									
CH00 Hopping mode	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep Count 500/500 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] M2[1] D1 -15.940 dBm M3 M4 M5 4.06 dBm 2.404240 GHz -51.87 dBm 2.400000 GHz Start 2.31 GHz 691 pts Stop 2.405 GHz Marker <table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td></td><td>1</td><td>2.40424 GHz</td><td>4.06 dBm</td><td></td><td></td></tr><tr><td>M2</td><td></td><td>1</td><td>2.4 GHz</td><td>-51.87 dBm</td><td></td><td></td></tr><tr><td>M3</td><td></td><td>1</td><td>2.39 GHz</td><td>-55.29 dBm</td><td></td><td></td></tr><tr><td>M4</td><td></td><td>1</td><td>2.31 GHz</td><td>-55.06 dBm</td><td></td><td></td></tr><tr><td>M5</td><td></td><td>1</td><td>2.335746 GHz</td><td>-52.82 dBm</td><td></td><td></td></tr></table> Date: 27 APR 2025 22:45:08			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1		1	2.40424 GHz	4.06 dBm			M2		1	2.4 GHz	-51.87 dBm			M3		1	2.39 GHz	-55.29 dBm			M4		1	2.31 GHz	-55.06 dBm			M5		1	2.335746 GHz	-52.82 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1		1	2.40424 GHz	4.06 dBm																																									
M2		1	2.4 GHz	-51.87 dBm																																									
M3		1	2.39 GHz	-55.29 dBm																																									
M4		1	2.31 GHz	-55.06 dBm																																									
M5		1	2.335746 GHz	-52.82 dBm																																									
CH78 No hopping mode	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 56.9 μs VBW 300 kHz Mode Auto FFT Count 500/500 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] M2[1] D1 -16.470 dBm M3 M4 M5 3.53 dBm 2.4798310 GHz -57.35 dBm 2.4835000 GHz Start 2.478 GHz 691 pts Stop 2.5 GHz Marker <table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td></td><td>1</td><td>2.479831 GHz</td><td>3.53 dBm</td><td></td><td></td></tr><tr><td>M2</td><td></td><td>1</td><td>2.4835 GHz</td><td>-57.35 dBm</td><td></td><td></td></tr><tr><td>M3</td><td></td><td>1</td><td>2.5 GHz</td><td>-59.63 dBm</td><td></td><td></td></tr><tr><td>M4</td><td></td><td>1</td><td>2.4882348 GHz</td><td>-57.16 dBm</td><td></td><td></td></tr></table> Date: 27 APR 2025 22:34:34			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1		1	2.479831 GHz	3.53 dBm			M2		1	2.4835 GHz	-57.35 dBm			M3		1	2.5 GHz	-59.63 dBm			M4		1	2.4882348 GHz	-57.16 dBm									
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1		1	2.479831 GHz	3.53 dBm																																									
M2		1	2.4835 GHz	-57.35 dBm																																									
M3		1	2.5 GHz	-59.63 dBm																																									
M4		1	2.4882348 GHz	-57.16 dBm																																									




CH78
Hopping mode









Test Item:	Band edge	Modulation type:	8DPSK																																									
CH00 No hopping mode	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep Count 500/500 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] M2[1] D1 -15.520 dBm M3 M4 4.48 dBm 2.401770 GHz -50.88 dBm 2.400000 GHz Start 2.31 GHz 691 pts Stop 2.405 GHz Marker <table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td></td><td>1</td><td>2.40177 GHz</td><td>4.48 dBm</td><td></td><td></td></tr><tr><td>M2</td><td></td><td>1</td><td>2.4 GHz</td><td>-50.88 dBm</td><td></td><td></td></tr><tr><td>M3</td><td></td><td>1</td><td>2.39 GHz</td><td>-55.53 dBm</td><td></td><td></td></tr><tr><td>M4</td><td></td><td>1</td><td>2.31 GHz</td><td>-55.21 dBm</td><td></td><td></td></tr><tr><td>M5</td><td></td><td>1</td><td>2.399768 GHz</td><td>-51.83 dBm</td><td></td><td></td></tr></table> Date: 27 APR 2025 22:56:13	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1		1	2.40177 GHz	4.48 dBm			M2		1	2.4 GHz	-50.88 dBm			M3		1	2.39 GHz	-55.53 dBm			M4		1	2.31 GHz	-55.21 dBm			M5		1	2.399768 GHz	-51.83 dBm			
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																						
M1		1	2.40177 GHz	4.48 dBm																																								
M2		1	2.4 GHz	-50.88 dBm																																								
M3		1	2.39 GHz	-55.53 dBm																																								
M4		1	2.31 GHz	-55.21 dBm																																								
M5		1	2.399768 GHz	-51.83 dBm																																								
CH00 Hopping mode	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep Count 500/500 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] M2[1] D1 -15.630 dBm M3 M4 4.37 dBm 2.403140 GHz -54.94 dBm 2.400000 GHz Start 2.31 GHz 691 pts Stop 2.405 GHz Marker <table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td></td><td>1</td><td>2.40314 GHz</td><td>4.37 dBm</td><td></td><td></td></tr><tr><td>M2</td><td></td><td>1</td><td>2.4 GHz</td><td>-54.94 dBm</td><td></td><td></td></tr><tr><td>M3</td><td></td><td>1</td><td>2.39 GHz</td><td>-55.16 dBm</td><td></td><td></td></tr><tr><td>M4</td><td></td><td>1</td><td>2.31 GHz</td><td>-54.46 dBm</td><td></td><td></td></tr><tr><td>M5</td><td></td><td>1</td><td>2.387101 GHz</td><td>-52.66 dBm</td><td></td><td></td></tr></table> Date: 27 APR 2025 22:47:02	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1		1	2.40314 GHz	4.37 dBm			M2		1	2.4 GHz	-54.94 dBm			M3		1	2.39 GHz	-55.16 dBm			M4		1	2.31 GHz	-54.46 dBm			M5		1	2.387101 GHz	-52.66 dBm			
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																						
M1		1	2.40314 GHz	4.37 dBm																																								
M2		1	2.4 GHz	-54.94 dBm																																								
M3		1	2.39 GHz	-55.16 dBm																																								
M4		1	2.31 GHz	-54.46 dBm																																								
M5		1	2.387101 GHz	-52.66 dBm																																								
CH78 No hopping mode	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 56.9 μs VBW 300 kHz Mode Auto FFT Count 500/500 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] M2[1] D1 -16.470 dBm M3 M4 3.55 dBm 2.4798310 GHz -59.14 dBm 2.4835000 GHz Start 2.478 GHz 691 pts Stop 2.5 GHz Marker <table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td></td><td>1</td><td>2.479831 GHz</td><td>3.55 dBm</td><td></td><td></td></tr><tr><td>M2</td><td></td><td>1</td><td>2.4835 GHz</td><td>-59.14 dBm</td><td></td><td></td></tr><tr><td>M3</td><td></td><td>1</td><td>2.5 GHz</td><td>-59.93 dBm</td><td></td><td></td></tr><tr><td>M4</td><td></td><td>1</td><td>2.485971 GHz</td><td>-56.13 dBm</td><td></td><td></td></tr></table> Date: 27 APR 2025 22:59:03	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1		1	2.479831 GHz	3.55 dBm			M2		1	2.4835 GHz	-59.14 dBm			M3		1	2.5 GHz	-59.93 dBm			M4		1	2.485971 GHz	-56.13 dBm										
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																						
M1		1	2.479831 GHz	3.55 dBm																																								
M2		1	2.4835 GHz	-59.14 dBm																																								
M3		1	2.5 GHz	-59.93 dBm																																								
M4		1	2.485971 GHz	-56.13 dBm																																								

CH78
Hoppig mode









Test Item:	Spurious Emission	Modulation type:	GFSK
CH00 Reference level			
CH00 30MHz~1000MHz			
CH00 1GHz~26GHz			




CH39 Reference level	
CH39 30MHz~1000MHz	
CH39 1GHz~26GHz	




CH78 Reference level	 The spectrum plot for CH78 Reference level shows a single sharp peak at 2.4799570 GHz. The peak power is 2.84 dBm. The plot is centered at 2.48 GHz with a span of 30.0 MHz. The y-axis ranges from -80 dBm to 10 dBm. The x-axis ranges from 2.4799570 GHz to 2.4800430 GHz. The plot includes a grid and a peak marker labeled M1[1].
CH78 30MHz~1000MHz	 The spectrum plot for CH78 30MHz~1000MHz shows a noise floor at -52.07 dBm. The plot is centered at 864.4470 MHz with a span of 1.0 GHz. The y-axis ranges from -80 dBm to 10 dBm. The x-axis ranges from 30.0 MHz to 1000.0 MHz. The plot includes a grid and a peak marker labeled M1[1].
CH78 1GHz~26GHz	 The spectrum plot for CH78 1GHz~26GHz shows a noise floor at -42.48 dBm. The plot is centered at 15.826667 GHz with a span of 26.0 GHz. The y-axis ranges from -80 dBm to 10 dBm. The x-axis ranges from 1.0 GHz to 26.0 GHz. The plot includes a grid and a peak marker labeled M1[1].




Test Item:	Spurious Emission	Modulation type:	$\pi/4$ DQPSK
CH00 Reference level	Spectrum Ref Level 20.50 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 75.9 μs VBW 300 kHz Mode Auto FFT Count 100/100 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] 2.56 dBm 2.4018260 GHz CF 2.402 GHz 691 pts Span 30.0 MHz Date: 27 APR 2025 22:31:32		
CH00 30MHz~1000MHz	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] -51.90 dBm 841.7500 MHz D1 -17.440 dBm Start 30.0 MHz 30001 pts Stop 1.0 GHz Date: 27 APR 2025 22:31:47		
CH00 1GHz~26GHz	Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] -43.86 dBm 16.805833 GHz D1 -17.440 dBm Start 1.0 GHz 30001 pts Stop 26.0 GHz Date: 27 APR 2025 22:32:03		

CH39 Reference level	 Spectrum Ref Level 20.50 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 75.9 μs VBW 300 kHz Mode Auto FFT Count 100/100 IPk Max M1[1] 3.15 dBm 2.4408260 GHz CF 2.441 GHz 691 pts Span 30.0 MHz Date: 27 APR 2025 22:32:59
CH39 30MHz~1000MHz	 Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10 IPk Max M1[1] -51.83 dBm 910.4230 MHz D1 -16.850 dBm Start 30.0 MHz 30001 pts Stop 1.0 GHz Date: 27 APR 2025 22:33:14
CH39 1GHz~26GHz	 Spectrum Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10 IPk Max M1[1] -43.15 dBm 15.552500 GHz D1 -16.850 dBm Start 1.0 GHz 30001 pts Stop 26.0 GHz Date: 27 APR 2025 22:33:29

CH78 Reference level	
CH78 30MHz~1000MHz	
CH78 1GHz~26GHz	

Test Item:	Spurious Emission	Modulation type:	8DPSK
CH00 Reference level			
CH00 30MHz~1000MHz			
CH00 1GHz~26GHz			

CH39 Reference level	
CH39 30MHz~1000MHz	
CH39 1GHz~26GHz	

CH78 Reference level	
CH78 30MHz~1000MHz	
CH78 1GHz~26GHz	

-----End of Report-----