HAC TEST REPORT

Applicant	ecom instruments GmbH
FCC ID	XAM500080GR01
Product	Featurephone
Brand	ecom
Model	Ex-Handy 10
Report No.	R1906H0306-H2
Issue Date	October 24, 2019

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **ANSI C63.19-2011**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Yu Wang Guangchang Fan

Performed by: Yu Wang *Approved by: Guangchang Fan*

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

1 Test Laboratory 3
1.1 Notes of the Test Report 3
1.2 Testing Location 4
1.3 Laboratory Environment 4
2 Statement of Compliance 5
3 Description of Equipment under Test 6
4 Test Specification and Operational Conditions 9
4.1 Test Specification 9
5 Test Information 10
5.1 Operational Conditions during Test 10
5.1.1 General Description of Test Procedures 10
5.2 T-Coil Measurements System Configuration 10
5.2.1 T-coil Measurement Set-up 10
5.2.2 AM1D Probe 13
5.2.3 Audio Magnetic Measurement Instrument (AMMI) 14
5.2.4 Helmholtz Calibration Coil (AMCC) 15
5.2.5 Test Arch Phantom & Phone Positioner 15
5.3 T-Coil measurement points and reference plane 16
5.4 T-Coil Test Procedueres 17
6 T-Coil Performance Requirements 19
6.1 T-Coil coupling field intensity 19
6.2 Frequency response 19
6.3 Signal quality 20
7 T-Coil testing for GSM 21
8 T-Coil testing for WCDMA 21
9 T-Coil testing for VoLTE 22
10 T-Coil testing for VoWIFI 24
11 Summary Test Results 26
12 Measurement Uncertainty 29
13 Main Test Instruments 30
ANNEX A: Test Layout 31
ANNEX B: Graph Results 32
ANNEX C: Probe Calibration Certificate 125
ANNEX D: DAE4 Calibration Certificate 128
ANNEX E: The EUT Appearances and Test Configuration 133

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd).**The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

1.2 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.

Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

City: Shanghai

Post code: 201201

Country: P. R. China

Contact: Xu Kai

Telephone: +86-021-50791141/2/3

Fax: +86-021-50791141/2/3-8000

Website: http://www.ta-shanghai.com

E-mail: xukai@ta-shanghai.com

1.3 Laboratory Environment

Temperature	Min. = 18°C, Max. = 28 °C
Relative humidity	Min. = 0%, Max. = 80%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

2 Statement of Compliance

Table 2.1: T-Coil signal quality categories of each tested Mode

Band	Category
GSM 850	**T3**
GSM 1900	**T3**
WCDMA Band II	**T4**
WCDMA Band IV	**T4**
WCDMA Band V	**T4**
LTE Band 2	**T4**
LTE Band 4	**T4**
LTE Band 5	**T4**
LTE Band 7	**T4**
LTE Band 12	**T4**
LTE Band 13	**T4**
LTE Band 25	**T4**
LTE Band 26	**T4**
LTE Band 41	**T4**
LTE Band 66	**T4**
LTE Band 71	**T4**
Wi-Fi 2.4G 802.11b	**T4**
Wi-Fi 2.4G 802.11g	**T4**
Wi-Fi 5G (U-NII-1)	**T4**
Wi-Fi 5G (U-NII-2A)	**T4**
Wi-Fi 5G (U-NII-2C)	**T4**
Wi-Fi 5G (U-NII-3)	**T4**
The Total T-Coil rating is T3	
Date of Testing: June 18, 2019~ July 3, 2019	
Note: LTE and Wi-Fi mode do not support voice function.	

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

3 Description of Equipment under Test

Client Information

Applicant	ecom instruments GmbH
Applicant address	Industriestrasse 2, 97959 Assamstadt, Germany
Manufacturer	Pepperl+Fuchs GmbH
Manufacturer address	Lilienthalstrasse 200, 68307 Mannheim, Germany

General Technologies

Device Type:	Portable Device	
EUT Stage	Production Unit	
Model	Ex-Handy 10	
IMEI:	004403100005430	
Hardware Version	HW3	
Software Version	SAIPH_ROW_M_018_260219	
Antenna Type	Internal Antenna	
Power Class:	GSM 850: 4 GSM 1900: 1 WCDMA Band II/IV/V: 3 LTE FDD 2/4/5/7/12/13/25/26:3 LTE TDD 41/66/71:3	
Power Level	GSM 850: level 5 GSM 1900: level 0 WCDMA Band II/IV/V: All up bits LTE FDD 2/4/5/7/12/13/25/26:max power LTE TDD 41/66/71: max power	
Test Modulation:	(GSM)GMSK;(WCDMA) QPSK; (LTE) QPSK, 16QAM; (Wi-Fi) DSSS,OFDM	
Operating Frequency Range(s):	Mode	Tx (MHz)
	GSM 850	824 ~ 849
	GSM 1900	1850 ~ 1910
	WCDMA Band II	1850 ~ 1910
	WCDMA Band IV	1710 ~ 1755
	WCDMA Band V	824 ~ 849
	LTE Band 2	1850 ~ 1910
	LTE Band 4	1710 ~ 1755
	LTE Band 5	824 ~ 849
	LTE Band 7	2500 ~ 2570
	LTE Band 12	699 ~ 716
	LTE Band 13	777~787
	LTE Band 25	1850 ~ 1915

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

	LTE Band 26	824 ~ 849
	LTE Band 41	2496 ~ 2690
	LTE Band 66	1710 ~ 1780
	LTE Band 71	663 ~ 698
	Bluetooth:	2402 ~ 2480
	WIFI 2.4G:	2412 ~ 2462
	WIFI 5G(U-NII-1):	5150 ~ 5250
	WIFI 5G(U-NII-2A):	5250 ~ 5350
	WIFI 5G(U-NII-2C):	5470 ~ 5725
	WIFI 5G(U-NII-3):	5725 ~ 5850
Accessory Equipment		
Adapter	Manufacturer: TEN PAO INTERNATIONAL LTD. Model: S008ACM0500200	
Battery	Manufacturer: ecom instruments GmbH Model: EX-BP H10C	
USB Cable	Manufacturer: Dongguan YongGu Electronics Prouduction Co., Ltd. 120cm Cable, Shielded	

Air-Interface	Band (MHz)	Type	ANSI C63.19 tested	Simultaneous Transmissions	Voice over Digital Transport OTT Capability	Name of Voice Service	Power Reduction
GSM	850	VO	Yes	Yes BT or Wi-Fi	N/A	#	No
	1900						
	GPRS/EGPRS	DT	No		No		
WCDMA	Band II	VO	Yes	Yes BT or Wi-Fi	N/A	#	No
	Band IV						
	Band V						
	HSPA	DT	No		No		
LTE	Band 2	VD	Yes	Yes BT or Wi-Fi	No	Yes##	No
	Band 4						
	Band 5						
	Band 12						
	Band 13						
	Band 25						
	Band 26						
	Band 41						
	Band 66						
	Band 71						
Wi-Fi	2450	VD	Yes	Yes GSM, WCDMA,	No	Wi-Fi Calling	No

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

				LTE,			
Wi-Fi	U-NII-1,U-NII-2A, U-NII-2C, U-NII-3	VD	Yes	Yes GSM, WCDMA, LTE,	No	Wi-Fi Calling	No
Bluetooth (BT)	2450	DT	No	Yes GSM, WCDMA, LTE,	N/A	NA	No

VO= legacy Cellular Voice Service from Table 7.1 in 7.4.2.1 of ANSI C63.19-2011
DT= Digital Transport only (no voice)
VD= IP voice service over digital transport.
#: Ref Lev in accordance with 7.4.2.1 of ANSI C63.19-2011
##: Ref Lev in accordance with the July 2012 VoLTE interpretation.
Remark:
1. It applies the low power exemption based on ANSI C63.19-2011

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

4 Test Specification and Operational Conditions

4.1 Test Specification

The tests documented in this report were performed in accordance with the following:

FCC CFR47 Part 20.19
ANSI C63.19-2011
285076 D01 HAC Guidance v05
285076 D02 T-Coil Testing v03

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5 Test Information

5.1 Operational Conditions during Test

5.1.1 General Description of Test Procedures

The phone was tested in all normal configurations for the ear use. The EUT is mounted in the device holder equivalent as for classic dosimeter measurements. The acoustic output of the EUT shall coincide with the center point of the area formed by the dielectric wire and the middle bar of the arch's top frame The EUT shall be moved vertically upwards until it touches the frame. The fine adjustment is possible by sliding the complete. EUT holder on the yellow base plate of the Test Arch phantom. During the test, the EUT is selected on T-Coil mode, the LCD backlight is turn off and volume is adjusted to maximum level.

A communication link is set up with a System Simulator (SS) by RF cable, and a call is established. The Absolute Radio Frequency Channel Number (ARFCN) is allocated to Ch Middle respectively in the case of Band. T-Coil configurations is measured using System Simulator (SS) of CMU200/ CMW 500, at the same time the EUT shall be operated at its maximum RF output power setting.

5.2 T-Coil Measurements System Configuration

5.2.1 T-coil Measurement Set-up

These measurements are performed using the DASY5 automated dosimetric assessment system. It is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland. It consists of high precision robotics system (Stäubli), robot controller, Intel Core computer, near-field probe, probe alignment sensor. The robot is a six-axis industrial robot performing precise movements. Cell controller systems contain the power supply, robot controller, teach pendant (Joystick) and remote control, and are used to drive the robot motors. The Stäubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification; signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



Figure 1 T-Coil Test Measurement Set-up

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



Figure 2 T-Coil Test Measurement Set-up

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.2.2 AM1D Probe

The AM1D probe is an active probe with a single sensor. It is fully RF-shielded and has a rounded tip 6mm in diameter incorporating a pickup coil with its center offset 3mm from the tip and the sides. The symmetric signal preamplifier in the probe is fed via the shielded symmetric output cable from the AMMI with a 48V “phantom” voltage supply. The 7-pin connector on the back in the axis of the probe does not carry any signals. It is mounted to the DAE for the correct orientation of the sensor. If the probe axis is tilted 54.7 degree from the vertical, the sensor is approximately vertical when the signal connector is at the underside of the probe (cable hanging downwards).

Specification

frequency range	0.1 - 20 kHz (RF sensitivity <-100 dB, fully RF shielded)
sensitivity	<-50 dB A/m @ 1 kHz
pre-amplifier	40 dB, symmetric
dimensions	tip diameter / length: 6 / 290 mm, sensor according to ANSI-C63.19

Figure 3 AM1D Probe

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.2.3 Audio Magnetic Measurement Instrument (AMMI)

The Audio Magnetic Measuring Instrument (AMMI) is a desktop 19-inch unit containing a sampling unit, a waveform generator for test and calibration signals, and a USB interface.

Figure 4 AMMI front panel

Port description:

Audio Out	BNC, audio signal to the base station simulator, for >500Ohm load
Coil Out	BNC, test and calibration signal to the AMCC (top connector), for 50Ohm load
Coil In	XLR, monitor signal from the AMCC BNO connector, 600 Ohm
Probe In	XLR, probe signal and phantom supply to the probe Lemo connector

Figure 5 AMMI rear side

Sampling rate	48 kHz / 24 bit
Dynamic range	85 dB
Test signal generation	User selectable and predefined (vis PC)
Calibration	Auto-calibration / full system calibration using AMCC with monitor output
Dimensions	482 x 65 x 270 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.2.4 Helmholtz Calibration Coil (AMCC)

The Audio Magnetic Calibration coil is a Helmholtz Coil designed for calibration of the AM1D probe. The two horizontal coils generate a homogeneous magnetic field in the z direction. The DC input resistance is adjusted by a series resistor to approximately 50Ohm, and a shunt resistor of 10Ohm permits monitoring the current with a scale of 1:10



Figure 6 AMCC

Port description:

Signal	**Connector**	**Resistance**
Coil In	BNC	Typically 50Ohm
Coil Monitor	BNO	10Ohm±1% (100mV corresponding to 1 A/m)

Specification:

Dimensions	370 x 370 x 196 mm, according to ANSI-C63.19

5.2.5 Test Arch Phantom & Phone Positioner

The Test Arch phantom should be positioned horizontally on a stable surface. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. It enables easy and well defined positioning of the phone and validation dipoles as well as simple teaching of the robot (Dimensions: 370 x 370 x 370 mm).
The Device reference point is set for the EUT at 6.3 mm, the Grid reference point is on the upper surface at the origin of the coordinates, and the “user point \Height Check 0.5 mm” is 0.5mm above the center, allowing verication of the gap of 0.5mm while the probe is positioned there.

The Phone Positioner supports accurate and reliable positioning of any phone with effect on near field <±0.5 dB.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Figure 7 T-coil Phantom & Device Holder

5.3 T-Coil measurement points and reference plane

The following figure illustrates the standard probe orientations. Position 1 is the perpendicular orientation of the probe coil; orientation 2 is the transverse orientation. The space between the measurement positions is not fixed. It is recommended that a scan of the WD be performed for each probe coil orientation and that the maximum level recorded be used as the reading for that orientation of the probe coil.

1) The reference plane is the planar area that contains the highest point in the area of the phone that normally rests against the user's ear. It is parallel to the centerline of the receiver area of the phone and is defined by the points of the receiver-end of the EUT handset, which, in normal handset use, rest against the ear.

2) The measurement plane is parallel to, and 10 mm in front of, the reference plane.

3) The reference axis is normal to the reference plane and passes through the center of the receiver speaker section (or the center of the hole array); or may be centered on a secondary inductive source. The actual location of the measurement point shall be noted in the test report as the measurement reference point.

4) The measurement points may be located where the axial and radial field intensity measurements are optimum with regard to the requirements. However, the measurement points should be near the acoustic output of the EUT and shall be located in the same half of the phone as the EUT receiver. In a EUT handset with a centered receiver and a circularly symmetrical magnetic field, the measurement axis and the reference axis would coincide.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5) The relative spacing of each measurement orientation is not fixed. The axial and two radial orientations should be chosen to select the optimal position.

6) The measurement point for the axial position is located 10 mm from the reference plane on the measurement axis.

7) The actual location of the measurement point shall be noted in test reports and designated as the measurement reference point.



Figure 8 Axis and planes for EUT audio frequency magnetic field measurements

5.4 T-Coil Test Procedueres

The following illustrate a typical test scan over a wireless communications device:

1) Geometry and signal check: system probe alignment, proper operation of the field probe, probe measurement system, other instrumentation, and the positioning system was confirmed. A surface calibration was performed before each setup change to ensure repeatable spacing and proper maintenance of the measurement plane using the test Arch.

2) Set the reference drive level of signal voice defined in C63.19 per 7.4.2.1.

3) The ambient and test system background noise (dB A/m) was measured as well as ABM2 over the full measurement. The maximum noise level must be at least 10dB below the limit of C63.19 per 8.3.2.

4) The EUT was positioned in its intended test position, acoustic output point of the device perpendicular to the field probe.

5) The EUT operation for maximum rated RF output power was configured and connected by using of coaxial cable connection to the base station simulator at the test channel and other normal operating parameters as intended for the test. The battery was ensured to be fully charged before each test. The center sub-grid was centered over the center of the acoustic output (also audio band magnetic output, if applicable). The EUT audio output was positioned tangent (as physically possible) to the measurement plane.

6) The EUT's RF emission field was eliminated from T-coil results by using a well RF-shielding of the probe, AM1D, and by using of coaxial cable connection to a Base Station Simulator. One test channel was pre-measurement to avoid this possibility.

7) Determined the optimal measurement locations for the EUT by following the three steps, coarse

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

resolution scan, fine resolution scans, and point measurement, as described in C63.19 per 7.4.4.2. At each measurement locations, samples in the measurement window duration were evaluated to get ABM1 and the signal spectrum. The noise measurement was performed after the scan with the signal, the same happened, just with the voice signal switched off. The ABM2 was calculated from this second scan.

8) All results resulting from a measurement point in a T-Coil job were calculated from the signal samples during this window interval. ABM values were averaged over the sequence of there samples.

9) At an optimal point measurement, the SNR (ABM1/ABM2) was calculated for axial,radial transverse and radial longitudinal orientation, and the frequency response was measured in axial axis.

10) Corrected for the frequency response after the EUT measurement since the DASY5 system had known the spectrum of the input signal by using a reference job.

11) In SEMCAD postprocessing, the spectral points are in addition scaled with the high-pass (half-band) and the A-weighting, bandwidth compensated factor (BWC) and those results are final as shown in this report.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

6 T-Coil Performance Requirements

In order to be rated for T-Coil use, a EUT shall meet the requirements for signal level and signal quality contained in this part.

6.1 T-Coil coupling field intensity

When measured as specified in ANSI C63.19, the T-Coil signal shall be ≥ –18 dB (A/m) at 1 kHz, in a 1/3 octave band filter for all orientations.

6.2 Frequency response

The frequency response of the axial component of the magnetic field, measured in 1/3 octave bands, shall follow the response curve specified in this sub-clause, over the frequency range 300 Hz to 3000 Hz. The following figures provide the boundaries for the specified frequency. These response curves are for true field strength measurements of the T-Coil signal. Thus the 6 dB/octave probe response has been corrected from the raw readings.



NOTE—Frequency response is between 300 Hz and 3000 Hz.

Figure 9 Magnetic field frequency response for EUTs with a field ≤ –15 dB (A/m) at 1 kHz

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



NOTE—Frequency response is between 300 Hz and 3000 Hz.

Figure 10 Magnetic field frequency response for EUTs with a field that exceeds –15 dB(A/m) at 1 kHz

6.3 Signal quality

This part provides the signal quality requirement for the intended T-Coil signal from a EUT. Only the RF immunity of the hearing aid is measured in T-Coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. So, the only criteria that can be measured is the RF immunity in T-Coil mode. This is measured using the same procedure as for the audio coupling mode and at the same levels.

The worst signal quality of the twoT-Coil signal measurements shall be used to determine the T-Coil mode category per Table 1

Table 1: T-Coil signal quality categories

Category	Telephone parameters WD signal quality [(signal + noise) – to – noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

7 T-Coil testing for GSM

1. Codec investigation

An investigation was performed to determine the audio codec to be used for testing by SNR comparison. The FR V1 setting was used for the testing as the worst-case codec.

Codec Investigation - GSM					
Codec Setting	**FR V1**	**HR V1**	**Orientation**	**Band**	**Channel**
ABM1 (dBA/m)	**8.15**	9.69	z (Axial):	GSM 850	190
ABM2 (dBA/m)	**-32.35**	-31.01			
Frequency Response	**Pass**	Pass			
Signal Quality (dB)	**40.5**	40.7			

2. Air Interface Investigation

Using the worst case codec to test low/middle/high channels in each band.

8 T-Coil testing for WCDMA

1. Codec investigation

An investigation was performed to determine the audio codec to be used for testing by SNR comparison. The AMR 12.2kbps setting was used for the testing as the worst-case codec.

Codec Investigation - WCDMA						
Codec Setting	**AMR 12.2kbps**	**AMR 7.95kbps**	**AMR 4.75kbps**	**Orientation**	**Band**	**Channel**
ABM1 (dBA/m)	**7.91**	8.3	8.64	z (Axial):	Band II	9400
ABM2 (dBA/m)	**-41.18**	-41.8	-41.19			
Frequency Response	**Pass**	Pass	Pass			
Signal Quality (dB)	**49.09**	50.1	49.83			

2. Air Interface Investigation

Using the worst case codec to test low/middle/high channels in each band.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

9 T-Coil testing for VoLTE

I. Test setup for VoLTE over IMS T-coil Testing

1. Test setup

The general test setup used for VoLTE over IMS is shown below. The call box used when performing VoLTE over IMS T-coil measurement is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.



2. Audio level setting

According to the July 2012 interpretations by the C63 Committee regarding the appropriate audio levels to be used for VoLTE over IMS T-coil testing, -16dBm0 shall be used for the nomal speech input level. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -16dBm0 speech input level to the DUT for the VoLTE over IMS connection.

II. DUT configuration for VoLTE over IMS T-coil Testing

1.Radio configuration investigation

An investigation was performed to determine the modulation and RB configuration to be used for testing. QPSK, 1RB, 0RB offset was used for the testing as the worst-case configuration.

Radio Configuration Investigation

VOLTE over IMS SNNR by Radio Configuration								
Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Signal Quality [dB]
1880	**18900**	**20**	**QPSK**	**1**	**0**	**6.90**	**-39.95**	**46.85**
1880	18900	20	QPSK	1	50	8.15	-39.81	47.96
1880	18900	20	QPSK	1	99	8.17	-39.03	47.20
1880	18900	20	QPSK	50	0	8.78	-39.53	48.31

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

1880	18900	20	QPSK	50	25	8.64	-38.87	47.51
1880	18900	20	QPSK	50	50	7.22	-40.48	47.70
1880	18900	20	QPSK	100	0	8.23	-39.20	47.43
1880	18900	20	16QAM	1	0	8.20	-39.38	47.58
1880	18900	20	16QAM	1	50	8.70	-39.80	48.50
1880	18900	20	16QAM	1	99	7.64	-40.63	48.27
1880	18900	20	16QAM	50	0	8.68	-39.05	47.73
1880	18900	20	16QAM	50	25	7.66	-39.59	47.25
1880	18900	20	16QAM	50	50	7.40	-40.63	48.03
1880	18900	20	16QAM	100	0	8.04	-40.31	48.35

2.Codec investigation

An investigation was performed to determine the audio codec to be used for testing. The WB AMR 6.60kbps setting was used for the audio codec on the CMW500 for VoLTE over IMS T-coil testing.

AMR Codec Investigation - VoLTE over IMS							
Codec Setting	**WB AMR 23.85kbps**	**WB AMR 6.60 kbps**	**NB AMR 12.2 kbps**	**NB AMR 4.75 kbps**	**Orientation**	**Band /BW**	**Channel**
ABM1 (dBA/m)	6.9	**5.64**	5.75	7.46	z (Axial):	Band2/ 20MHz	18900
ABM2 (dBA/m)	-39.95	**-40.52**	-40.54	-39.11			
Frequency Response	Pass	**Pass**	Pass	Pass			
Signal Quality (dB)	46.85	**46.16**	45.6	45.32			

EVS Codec Investigation - VoLTE over IMS							
Codec Setting	**WB AMR 23.85kbps**	**WB AMR 6.60 kbps**	**NB AMR 12.2 kbps**	**NB AMR 4.75 kbps**	**Orientation**	**Band /BW**	**Channel**
ABM1 (dBA/m)	6.52	6.01	7.43	5.95	z (Axial):	Band2/ 20MHz	18900
ABM2 (dBA/m)	-41.53	-41.71	-38.96	-37			
Frequency Response	Pass	Pass	Pass	Pass			
Signal Quality (dB)	46.52	47.39	46.93	47.62			

3.Air Interface Investigation

The worst case band for each probe orientation is additionally tested on all bandwidth combination. LTE B2 at 20MHz is the worst case for the Axial and Radial probe orientation.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

10 T-Coil testing for VoWIFI

I. Test setup for VoWIFI over IMS T-coil Testing

1. Test setup

The general test setup used for VoWIFI over IMS, or CMRS WIFI calling, is shown below. The call box used when performing VoWIFI over IMS T-coil measurement is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.

2. Audio level setting

According to the KDB285076 D02, regarding the appropriate audio levels to be used for WIFI over IMS T-coil testing, -20dBm0 shall be used for the normal speech input level. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the VoWIFI over IMS connection.

II. DUT configuration for VoWIFI over IMS T-coil Testing

1. Radio configuration investigation

Investigate the lowest and highest data rates and modulation to determine worst radio configuration to be used for testing by SNR comparison.

802.11b Radio configuration investigation					
Mode	**Channel**	**Data Rate [Mbps]**	**ABM1 [dB(A/m)]**	**ABM2 [dB(A/m)]**	**Signal Quality [dB]**
802.11b	**6**	**1**	**0.67**	**-41.66**	**42.33**
802.11b	6	11	1.7	-41.48	43.18
802.11g Radio configuration investigation					
Mode	**Channel**	**Data Rate [Mbps]**	**ABM1 [dB(A/m)]**	**ABM2 [dB(A/m)]**	**Signal Quality [dB]**
802.11g	6	6	-5.23	-42.87	37.64
802.11g	6	54	-4.86	-42.08	37.22
802.11n HT20 Radio configuration investigation					
Mode	**Channel**	**Data Rate [Mbps]**	**ABM1 [dB(A/m)]**	**ABM2 [dB(A/m)]**	**Signal Quality [dB]**
802.11n HT20	6	MCS0	0.58	-43.63	44.21
802.11n HT20	6	MCS7	1.77	-43.03	44.8
802.11n HT40 Radio configuration investigation					
Mode	**Channel**	**Data Rate [Mbps]**	**ABM1 [dB(A/m)]**	**ABM2 [dB(A/m)]**	**Signal Quality [dB]**
802.11n HT40	6	MCS0	1.06	-43.51	44.57
802.11n HT40	6	MCS7	1.79	-44.23	46.02

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

2. Codec investigation

Determine the worst-case codec by SNR comparison.

The WB AMR 6.60kbps setting was used for the audio codec on the CMW500 for VoWIFI over IMS T-coil testing.

AMR Codec Investigation - VoWIFI over IMS								
Codec Setting	**WB AMR 23.85kbps**	**WB AMR 6.60 kbps**	**NB AMR 12.2 kbps**	**NB AMR 4.75 kbps**	**Orientation**	**Band**	**Standard**	**Channel**
ABM1 (dBA/m)	0.67	**0.26**	2.09	0.55	z (Axial):	2.4GHz	802.11b	6
ABM2 (dBA/m)	-41.66	**-41.68**	-40.53	-41.56				
Frequency Response	Pass	**Pass**	Pass	Pass				
Signal Quality (dB)	42.33	**41.94**	42.62	42.11				

EVS Codec Investigation - VoWIFI over IMS								
Codec Setting	**WB AMR 23.85kbps**	**WB AMR 6.60 kbps**	**NB AMR 12.2 kbps**	**NB AMR 4.75 kbps**	**Orientation**	**Band**	**Standard**	**Channel**
ABM1 (dBA/m)	0.69	0.41	0.94	0.59	z (Axial):	2.4GHz	802.11b	6
ABM2 (dBA/m)	-41.41	-42.7	-42.08	-43.33				
Frequency Response	Pass	Pass	Pass	Pass				
Signal Quality (dB)	42.1	43.11	43.02	43.92				

3. Air Interface Investigation

Using the worst case codec to proceed T-coil test of worst case mode for axial and radial orientations. (802.11b is the worst case mode)

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

11 Summary Test Results

Band	Channel /Frequency (MHz)	Probe Orientation	ABM1 [dB (A/m)]	ABM2 [dB (A/m)]	ABM SNR (dB)	Freq. Resp. Diff(dB)	Frequency Response	T-Rating	Plot No.
GSM 850 Voice Coder	190/836.6	y (Radial):	-9.95	-44.86	34.91	/	/	T4	1
		z (Axial):	-1.98	-26.57	24.59	2.00	Pass	T3	2
GSM 1900 Voice Coder	661/1880	y (Radial):	-9.99	-46.97	36.98	/	/	T4	3
		z (Axial):	-5.77	-35.56	29.79	2.00	Pass	T3	4
WCDMA Band II Voice Coder	9400/1880	y (Radial):	-9.84	-51.22	41.38	/	/	T4	5
		z (Axial):	-2.00	-46.45	44.45	2.00	Pass	T4	6
WCDMA Band IV Voice Coder	1413/1732.6	y (Radial):	-9.82	-50.31	40.49	/	/	T4	7
		z (Axial):	-2.14	-47.99	45.85	0.50	Pass	T4	8
WCDMA Band V Voice Coder	4183/836.6	y (Radial):	-9.99	-50.34	40.35	/	/	T4	9
		z (Axial):	-2.07	-46.90	44.83	2.00	Pass	T4	10

Note:
1. The LCD backlight is turn off and volume is adjusted to maximum level during T-Coil testing.
2. Signal strength measurement scan plots are presented in Annex B.

Air interface investigation for LTE B2										
Mode	Orientation	Bandwidth (MHz)	Channel	ABM1 [dB (A/m)]	ABM2 [dB (A/m)]	Ambient Noise [dB (A/m)]	Frequency Response Variation (dB)	Signal Quality (dB)	C63.19-2011 Rating	Plot No.
LTE Band 2	z (Axial):	**20**	**18900**	-2.46	-41.31	-58.53	2.00	38.85	**T4**	-
		15	18900	-2.96	-40.22	-58.53	1.96	37.26	T4	-
		10	18900	-1.65	-39.70	-58.53	2.00	38.05	T4	-
		5	18900	-1.99	-39.26	-58.53	2.00	37.27	T4	-
		3	18900	-2.14	-38.85	-58.53	1.98	36.71	T4	-
		1.4	18900	-1.37	-38.49	-58.53	1.95	37.12	T4	-
	y (Radial):	**20**	**18900**	-10.42	-48.56	-58.87	/	38.14	**T4**	-
		15	18900	-9.88	-47.69	-58.87	/	37.81	T4	-
		10	18900	-8.63	-46.81	-58.87	/	38.18	T4	-
		5	18900	-6.91	-46.22	-58.87	/	39.31	T4	-
		3	18900	-7.63	-46.57	-58.87	/	38.94	T4	-
		1.4	18900	-5.39	-45.66	-58.87	/	40.27	T4	-

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

T-coil - WB

Band	Channel /Frequency (MHz)	Probe Orientation	ABM1 [dB (A/m)]	ABM2 [dB (A/m)]	ABM SNR (dB)	Freq. Resp. Diff(dB)	Frequency Response	T-Rating	Plot No.
LTE FDD B2 Voice WB AMR Codec: 23.85kbit/s	18900/1880 (QPSK_20M_1RB_0offset)	y (Radial):	-9.42	-49.75	40.33	/	/	T4	11
		z (Axial):	-5.26	-45.27	40.01	1.84	Pass	T4	12
LTE FDD B4 Voice WB AMR Codec: 23.85kbit/s	20175/1732.5 (QPSK_20M_1RB_0offset)	y (Radial):	-9.47	-49.27	39.80	/	/	T4	13
		z (Axial):	-1.37	-41.58	40.21	1.94	Pass	T4	14
LTE FDD B5 Voice WB AMR Codec: 23.85kbit/s	20525/836.5 (QPSK_10M_1RB_0offset)	y (Radial):	-9.32	-50.48	41.16	/	/	T4	15
		z (Axial):	-1.34	-43.31	41.97	1.88	Pass	T4	16
LTE FDD B7 Voice WB AMR Codec: 23.85kbit/s	21100/2535 (QPSK_20M_1RB_0offset)	y (Radial):	-9.31	-48.18	38.87	/	/	T4	17
		z (Axial):	-1.20	-41.19	39.99	1.89	Pass	T4	18
LTE FDD B12 Voice WB AMR Codec: 23.85kbit/s	23095/707.5 (QPSK_10M_1RB_0offset)	y (Radial):	-8.96	-50.20	41.24	/	/	T4	19
		z (Axial):	-1.31	-42.77	41.46	1.96	Pass	T4	20
LTE FDD B13 Voice WB AMR Codec: 23.85kbit/s	23230/782 (QPSK_10M_1RB_0offset)	y (Radial):	-7.31	-49.44	42.13	/	/	T4	21
		z (Axial):	-1.49	-44.43	42.94	2.00	Pass	T4	22
LTE FDD B25 Voice WB AMR Codec: 12.20kbit/s	26365/1882.5 (QPSK_20M_1RB_0offset)	y (Radial):	-9.25	-48.80	39.55	/	/	T4	23
		z (Axial):	-2.93	-42.49	39.56	1.92	Pass	T4	24
LTE FDD B26 Voice WB AMR Codec: 23.85kbit/s	26865/831.5 (QPSK_15M_1RB_0offset)	y (Radial):	-6.78	-49.03	42.25	/	/	T4	25
		z (Axial):	-0.55	-42.28	41.73	1.98	Pass	T4	26
LTE TDD B41 Voice WB AMR Codec: 23.85kbit/s	40620/2593 (QPSK_20M_1RB_0offset)	y (Radial):	-6.84	-48.37	41.53	/	/	T4	27
		z (Axial):	-0.20	-41.43	41.23	1.95	Pass	T4	28
LTE TDD B41 Voice WB AMR Codec: 23.85kbit/s	40690/2600 (QPSK_20M_1RB_0offset)	y (Radial):	-6.77	-47.96	41.19	/	/	T4	29
		z (Axial):	-3.70	-44.29	40.59	1.96	Pass	T4	30
LTE FDD B66 Voice WB AMR Codec: 23.85kbit/s	132072/1720 (QPSK_20M_1RB_0offset)	y (Radial):	-6.87	-48.63	41.76	/	/	T4	31
		z (Axial):	-0.84	-41.72	40.88	1.96	Pass	T4	32
LTE TDD B71 Voice WB AMR Codec: 23.85kbit/s	133322/683 (QPSK_20M_1RB_0offset)	y (Radial):	-7.03	-49.41	42.38	/	/	T4	33
		z (Axial):	-0.88	-41.99	41.11	2.00	Pass	T4	34
WIFI2.4G: 802.11b Voice WB AMR Codec: 23.85kbit/s	6/2437 (BW:20M_Rate:11M)	y (Radial):	-8.10	-51.02	42.92	/	/	T4	35
		z (Axial):	-3.39	-47.82	44.43	0.63	Pass	T4	36

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

WIFI2.4G: 802.11g Voice WB AMR Codec: 23.85kbit/s	6/2437 (BW:20M_Rate:6M)	y (Radial):	-9.44	-51.97	42.53	/	/	T4	37
		z (Axial):	-1.32	-47.69	46.37	1.29	Pass	T4	38
WIFI5G: 802.11a (U-NII-1) Voice WB AMR Codec: 23.85kbit/s	44/5220 (BW:20M_Rate:6M)	y (Radial):	-9.17	-51.95	42.78	/	/	T4	39
		z (Axial):	-6.54	-50.29	43.75	1.08	Pass	T4	40
WIFI5G: 802.11a (U-NII-2A) Voice WB AMR Codec: 23.85kbit/s	60/5300 (BW:20M_Rate:6M)	y (Radial):	-9.21	-51.48	42.27	/	/	T4	41
		z (Axial):	-2.00	-48.73	46.73	1.23	Pass	T4	42
WIFI5G: 802.11a (U-NII-2C) Voice WB AMR Codec: 23.85kbit/s	132/5660 (BW:20M_Rate:6M)	y (Radial):	-8.89	-51.89	43.00	/	/	T4	43
		z (Axial):	-1.78	-48.59	46.81	0.84	Pass	T4	44
WIFI5G: 802.11a (U-NII-3) Voice WB AMR Codec: 23.85kbit/s	157/5785 (BW:20M_Rate:6M)	y (Radial):	-9.15	-52.01	42.86	/	/	T4	45
		z (Axial):	-5.86	-50.55	44.69	1.14	Pass	T4	46

Note:

1. The LCD backlight is turn off and volume is adjusted to maximum level during T-Coil testing.
2. Signal strength measurement scan plots are presented in Annex B.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

12 Measurement Uncertainty

Measurement uncertainty evaluation template for DUT HAC T-Coil test

Error source	Type	Uncertainty Value ai (%)	Prob. Dist.	k	ABM1c_i	ABM2c_i	Std. Unc. ABM1 (± %)	Std. Unc. ABM2 (± %)	Degree of freedom V_{eff} or v_i
Probe Sensitivity									
Reference Level	B	3.0	N	1	1	1	3.0	3.0	∞
AMCC Geometry	B	0.4	R	1.732	1	1	0.2	0.2	∞
AMCC Current	B	0.6	R	1.732	1	1	0.3	0.3	∞
Probe Positioning during Calibration	B	0.1	R	1.732	1	1	0.1	0.1	∞
Noise Contribution	B	0.7	R	1.732	0.0143	1	0.0	0.4	∞
Frequency Slope	B	5.9	R	1.732	0.1	1	0.3	3.4	∞
Probe System									
Repeatability / Drift	B	1.0	R	1.732	1	1	0.6	0.6	∞
Linearity / Dynamic Range	B	0.6	R	1.732	1	1	0.3	0.3	∞
Acoustic Noise	B	1.0	R	1.732	0.1	1	0.1	0.6	∞
Probe Angle	B	2.3	R	1.732	1	1	1.3	1.3	∞
Spectral Processing	B	0.9	R	1.732	1	1	0.5	0.5	∞
Integration Time	B	0.6	N	1	1	5	0.6	3.0	∞
Field Distribution	B	0.2	R	1.732	1	1	0.1	0.1	∞
Test Signal									
Ref.Signal Spectral Response	B	0.6	R	1.732	0	1	0.0	0.3	∞
Positioning									
Probe Positioning	B	1.9	R	1.732	1	1	1.1	1.1	∞
Phantom Thickness	B	0.9	R	1.732	1	1	0.5	0.5	∞
EUT Positioning	B	1.9	R	1.732	1	1	1.1	1.1	∞
External Contributions									
RF Interference	B	0.0	R	1.732	1	0.3	0.0	0.0	∞
Test Signal Variation	B	2.0	R	1.732	1	1	1.2	1.2	∞
Combined Std. Uncertainty (ABM Field)							4.0	6.1	
Expanded Std. Uncertainty							8.0	12.2	

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

13 Main Test Instruments

Name	Manufacturer	Type	Serial Number	Last Cal.	Cal. Due Date
Audio Magnetic 1D Field Probe	SPEAG	AM1DV3	3082	2018-03-26	2021-03-25
DAE	SPEAG	DAE4	1291	2018-12-04	2019-12-03
Universal Radio Communication Tester	R&S	CMU 200	118133	2019-05-19	2020-05-18
Universal Radio Communication Tester	R&S	CMW 500	146734	2019-05-19	2020-05-18
Audio Magnetic Calibration Coil	SPEAG	AMCC	1101	2017-11-22	2020-11-21
Audio Measuring Instrument	SPEAG	AMMI	1112	2017-11-22	2020-11-21
TMFS	SPEAG	SE UMS 021 AA	1018	2017-11-22	2020-11-21
Hygrothermograph	Anymetr	NT-311	20150731	2019-05-19	2020-05-18
HAC Phantom	SPEAG	SD HAC P01 BB	1117	2017-11-22	2020-11-21
Software for Test	Speag	DASY5	52.8.8.1222	/	/
Software for Tissue	Agilent	85070	E06.01.36	/	/

*******END OF REPORT *******

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

ANNEX A: Test Layout

Picture 1: HAC T-Coil System Layout

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

ANNEX B: Graph Results

Plot 1 T-Coil GSM 850 Y transversal

Date: 2019/6/18
Communication System: UID 0, GSM (0); Frequency: 836.6 MHz;Duty Cycle: 1:8.30042
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH GSM850 HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 34.91 dB
ABM1 comp = -9.95 dBA/m
BWC Factor = 0.17 dB
Location: 0, -8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 55.68 = 34.91 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 2 T-Coil GSM 850 Z Axial

Date: 2019/6/18
Communication System: UID 0, GSM (0); Frequency: 836.6 MHz;Duty Cycle: 1:8.30042
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH GSM850 HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 24.59 dB
ABM1 comp = -1.98 dBA/m
BWC Factor = 0.17 dB
Location: 0, 0, 3.7 mm

SAIPH GSM850 HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 2.00 dB
BWC Factor = 10.81 dB
Location: 0, 0, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 16.96 = 24.59 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 3 T-Coil GSM 1900 Y transversal

Date: 2019/6/18
Communication System: UID 0, GSM (0); Frequency: 1880 MHz;Duty Cycle: 1:8.30042
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH GSM1900 HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 36.98 dB
ABM1 comp = -9.99 dBA/m
BWC Factor = 0.16 dB
Location: 0, -8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 70.62 = 36.98 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 4 T-Coil GSM 1900 Z Axial

Date: 2019/6/18
Communication System: UID 0, GSM (0); Frequency: 1880 MHz;Duty Cycle: 1:8.30042
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH GSM1900 HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 29.79 dB
ABM1 comp = -5.77 dBA/m
BWC Factor = 0.16 dB
Location: -4.2, 0, 3.7 mm

SAIPH GSM1900 HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 2.00 dB
BWC Factor = 10.81 dB
Location: -4.2, 0, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 30.85 = 29.79 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 5 T-Coil WCDMA Band II Y transversal

Date: 2019/6/18
Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH WCDMA B2 HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 41.38 dB
ABM1 comp = -9.84 dBA/m
BWC Factor = 0.16 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 117.2 = 41.38 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 6 T-Coil WCDMA Band II Z Axial

Date: 2019/6/18
Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH WCDMA B2 HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 44.45 dB
ABM1 comp = -2.00 dBA/m
BWC Factor = 0.16 dB
Location: 0, 0, 3.7 mm

SAIPH WCDMA B2 HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 2.00 dB
BWC Factor = 10.81 dB
Location: 0, 0, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 166.9 = 44.45 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 7 T-Coil WCDMA Band IV Y transversal

Date: 2019/6/18
Communication System: UID 0, WCDMA IV (0); Frequency: 1732.6 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH WCDMA B4 HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 40.49 dB
ABM1 comp = -9.82 dBA/m
BWC Factor = 0.16 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 105.8 = 40.49 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 8 T-Coil WCDMA Band IV Z Axial

Date: 2019/6/18
Communication System: UID 0, WCDMA IV (0); Frequency: 1732.6 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH WCDMA B4 HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 45.85 dB
ABM1 comp = -2.14 dBA/m
BWC Factor = 0.16 dB
Location: 0, -4.2, 3.7 mm

SAIPH WCDMA B4 HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 2.00 dB
BWC Factor = 10.81 dB
Location: 0, -4.2, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 196.1 = 45.85 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 9 T-Coil WCDMA Band V Y transversal

Date: 2019/6/18
Communication System: UID 0, WCDMA V (0); Frequency: 836.6 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH WCDMA B5 HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 40.35 dB
ABM1 comp = -9.99 dBA/m
BWC Factor = 0.16 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 104.1 = 40.35 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 10 T-Coil WCDMA Band V Z Axial

Date: 2019/6/18
Communication System: UID 0, WCDMA V (0); Frequency: 836.6 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH WCDMA B5 HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 44.83 dB
ABM1 comp = -2.07 dBA/m
BWC Factor = 0.16 dB
Location: 0, 0, 3.7 mm

SAIPH WCDMA B5 HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 2.00 dB
BWC Factor = 10.81 dB
Location: 0, 0, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 174.4 = 44.83 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 11 T-Coil LTE Band 2 Y transversal

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B2 1RB HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 40.33 dB
ABM1 comp = -9.42 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 103.9 = 40.33 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 12 T-Coil LTE Band 2 Z Axial

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B2 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 40.01 dB
ABM1 comp = -5.26 dBA/m
BWC Factor = 0.17 dB
Location: -4.2, -4.2, 3.7 mm

SAIPH LTE B2 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 1.84 dB
BWC Factor = 10.81 dB
Location: -4.2, -4.2, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 100.1 = 40.01 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 13 T-Coil LTE Band 4 Y transversal

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 1732.5 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B4 1RB HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 39.80 dB
ABM1 comp = -9.47 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 97.77 = 39.80 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 14 T-Coil LTE Band 4 Z Axial

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 1732.5 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B4 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 40.21 dB
ABM1 comp = -1.37 dBA/m
BWC Factor = 0.17 dB
Location: 0, -4.2, 3.7 mm

SAIPH LTE B4 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 1.94 dB
BWC Factor = 10.81 dB
Location: 0, -4.2, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 102.4 = 40.21 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 15 T-Coil LTE Band 5 Y transversal

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 836.5 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B5 1RB HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 41.16 dB
ABM1 comp = -9.32 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 114.2 = 41.16 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 16 T-Coil LTE Band 5 Z Axial

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 836.5 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B5 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 41.97 dB
ABM1 comp = -1.34 dBA/m
BWC Factor = 0.17 dB
Location: 0, 0, 3.7 mm

SAIPH LTE B5 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 1.88 dB
BWC Factor = 10.81 dB
Location: 0, 0, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 125.5 = 41.97 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 17 T-Coil LTE Band 7 Y transversal

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 2535 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B7 1RB HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 38.87 dB
ABM1 comp = -9.31 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 87.81 = 38.87 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 18 T-Coil LTE Band 7 Z Axial

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 2535 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 4mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B7 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 39.99 dB
ABM1 comp = -1.20 dBA/m
BWC Factor = 0.17 dB
Location: 0, 0, 3.7 mm

SAIPH LTE B7 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 1.89 dB
BWC Factor = 10.81 dB
Location: 0, 0, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 99.93 = 39.99 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 19 T-Coil LTE Band 12 Y transversal

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 707.5 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B12 1RB HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 41.24 dB
ABM1 comp = -8.96 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 115.4 = 41.24 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 20 T-Coil LTE Band 12 Z Axial

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 707.5 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B12 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 41.46 dB
ABM1 comp = -1.31 dBA/m
BWC Factor = 0.17 dB
Location: 0, -4.2, 3.7 mm

SAIPH LTE B12 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 1.96 dB
BWC Factor = 10.81 dB
Location: 0, -4.2, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 118.3 = 41.46 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 21 T-Coil LTE Band 13 Y transversal

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 782 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B13 1RB HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 42.13 dB
ABM1 comp = -7.31 dBA/m
BWC Factor = 0.17 dB
Location: 4.2, 4.2, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 127.7 = 42.13 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 22 T-Coil LTE Band 13 Z Axial

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 782 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B13 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 42.94 dB
ABM1 comp = -1.49 dBA/m
BWC Factor = 0.17 dB
Location: 0, 0, 3.7 mm

SAIPH LTE B13 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 2.00 dB
BWC Factor = 10.81 dB
Location: 0, 0, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 140.4 = 42.94 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 23 T-Coil LTE Band 25 Y transversal

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 1882.5 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B25 1RB HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 39.55 dB
ABM1 comp = -9.25 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 94.92 = 39.55 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 24 T-Coil LTE Band 25 Z Axial

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 1882.5 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B25 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 39.56 dB
ABM1 comp = -2.93 dBA/m
BWC Factor = 0.17 dB
Location: 0, -4.2, 3.7 mm

SAIPH LTE B25 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 1.92 dB
BWC Factor = 10.81 dB
Location: 0, -4.2, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 95.11 = 39.56 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 25 T-Coil LTE Band 26 Y transversal

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 831.5 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B26 1RB HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 42.25 dB
ABM1 comp = -6.78 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 129.6 = 42.25 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 26 T-Coil LTE Band 26 Z Axial

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 831.5 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B26 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 41.73 dB
ABM1 comp = -0.55 dBA/m
BWC Factor = 0.17 dB
Location: 0, 0, 3.7 mm

SAIPH LTE B26 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 1.98 dB
BWC Factor = 10.81 dB
Location: 0, -4.2, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 122.0 = 41.73 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 27 T-Coil LTE Band 41 Y transversal CH40620

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 2593 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B41 1RB HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 41.53 dB
ABM1 comp = -6.84 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 119.2 = 41.53 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 28 T-Coil LTE Band 41 Z Axial CH40620

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 2593 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B41 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 41.23 dB
ABM1 comp = -0.20 dBA/m
BWC Factor = 0.17 dB
Location: 0, 0, 3.7 mm

SAIPH LTE B41 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 1.96 dB
BWC Factor = 10.81 dB
Location: 0, -4.2, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 115.2 = 41.23 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 29 T-Coil LTE Band 41 Y transversal CH40690

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 2600 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B41 1RB HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 41.19 dB
ABM1 comp = -6.77 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 114.7 = 41.19 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 30 T-Coil LTE Band 41 Z Axial CH40690

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 2600 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B41 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 40.59 dB
ABM1 comp = -3.70 dBA/m
BWC Factor = 0.17 dB
Location: -4.2, 0, 3.7 mm

SAIPH LTE B41 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 1.95 dB
BWC Factor = 10.81 dB
Location: 0, -4.2, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 107.0 = 40.59 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 31 T-Coil LTE Band 66 Y transversal

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 1720 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B66 1RB HAC_TCoil_WD_Emission.da52/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 41.76 dB
ABM1 comp = -6.87 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 122.4 = 41.76 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 32 T-Coil LTE Band 66 Z Axial

Date: 2019/7/3
Communication System: UID 0, LTE (0); Frequency: 1720 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B66 1RB HAC_TCoil_WD_Emission.da52/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 40.88 dB
ABM1 comp = -0.84 dBA/m
BWC Factor = 0.17 dB
Location: 0, -4.2, 3.7 mm

SAIPH LTE B66 1RB HAC_TCoil_WD_Emission.da52/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 1.96 dB
BWC Factor = 10.81 dB
Location: 0, -4.2, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 110.6 = 40.88 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 33 T-Coil LTE Band 71 Y transversal

Date: 2019/6/18
Communication System: UID 0, LTE (0); Frequency: 698 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B71 1RB HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 42.38 dB
ABM1 comp = -7.03 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 1.000 = 0.00 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 34 T-Coil LTE Band 71 Z Axial

Date: 2019/6/18
Communication System: UID 0, LTE (0); Frequency: 698 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1317; Calibrated: 2019/4/23
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH LTE B71 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 41.11 dB
ABM1 comp = -0.88 dBA/m
BWC Factor = 0.17 dB
Location: 0, -4.2, 3.7 mm

SAIPH LTE B71 1RB HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 2.00 dB
BWC Factor = 10.81 dB
Location: 0, -4.2, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 113.6 = 41.11 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 35 T-Coil WIFI2.4G: 802.11b Y transversal

Date: 2019/6/18
Communication System: UID 0, 802.11b (0); Frequency: 2437 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH 802.11b HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 42.92 dB
ABM1 comp = -8.10 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 140.0 = 42.92 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 36 T-Coil WIFI2.4G: 802.11b Z Axial

Date: 2019/6/18
Communication System: UID 0, 802.11b (0); Frequency: 2437 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 4mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH 802.11b HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 44.43 dB
ABM1 comp = -3.39 dBA/m
BWC Factor = 0.17 dB
Location: 0, 4.2, 3.7 mm

SAIPH 802.11b HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 0.63 dB
BWC Factor = 10.81 dB
Location: 0, 4.2, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 166.5 = 44.43 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 37 T-Coil WIFI2.4G: 802.11g Y transversal

Date: 2019/6/18
Communication System: UID 0, 802.11b (0); Frequency: 2437 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 4mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH 802.11g HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 42.53 dB
ABM1 comp = -9.44 dBA/m
BWC Factor = 0.17 dB
Location: 4.2, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 133.8 = 42.53 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 38 T-Coil WIFI2.4G: 802.11g Z Axial

Date: 2019/6/18
Communication System: UID 0, 802.11b (0); Frequency: 2437 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH 802.11g HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 46.37 dB
ABM1 comp = -1.32 dBA/m
BWC Factor = 0.17 dB
Location: 0, -4.2, 3.7 mm

SAIPH 802.11g HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 1.29 dB
BWC Factor = 10.81 dB
Location: 0, -4.2, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 208.2 = 46.37 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 39 T-Coil WIFI5G U-NII-1: 802.11a Y transversal

Date: 2019/6/18
Communication System: UID 0, 802.11a (0); Frequency: 5220 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH 802.11a HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 42.78 dB
ABM1 comp = -9.17 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 137.7 = 42.78 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 40 T-Coil WIFI5G U-NII-1: 802.11a Z Axial

Date: 2019/6/18
Communication System: UID 0, 802.11a (0); Frequency: 5220 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH 802.11a HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 43.75 dB
ABM1 comp = -6.54 dBA/m
BWC Factor = 0.17 dB
Location: -4.2, -4.2, 3.7 mm

SAIPH 802.11a HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 1.08 dB
BWC Factor = 10.81 dB
Location: -4.2, -4.2, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 154.1 = 43.75 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 41 T-Coil WIFI5G U-NII-2A: 802.11a Y transversal

Date: 2019/6/18
Communication System: UID 0, 802.11a (0); Frequency: 5300 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH 802.11a HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 42.27 dB
ABM1 comp = -9.21 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 129.8 = 42.27 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 42 T-Coil WIFI5G U-NII-2A: 802.11a Z Axial

Date: 2019/6/18
Communication System: UID 0, 802.11a (0); Frequency: 5300 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH 802.11a HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 46.73 dB
ABM1 comp = -2.00 dBA/m
BWC Factor = 0.17 dB
Location: 0, 0, 3.7 mm

SAIPH 802.11a HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 1.23 dB
BWC Factor = 10.81 dB
Location: 0, 0, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 217.0 = 46.73 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 43 T-Coil WIFI5G U-NII-2C: 802.11a Y transversal

Date: 2019/6/18
Communication System: UID 0, 802.11a (0); Frequency: 5660 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH 802.11a HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 43.00 dB
ABM1 comp = -8.89 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 141.3 = 43.00 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 44 T-Coil WIFI5G U-NII-2C: 802.11a Z Axial

Date: 2019/6/18
Communication System: UID 0, 802.11a (0); Frequency: 5660 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH 802.11a HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 46.81 dB
ABM1 comp = -1.78 dBA/m
BWC Factor = 0.17 dB
Location: 0, 0, 3.7 mm

SAIPH 802.11a HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 0.84 dB
BWC Factor = 10.81 dB
Location: 0, 0, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 219.1 = 46.81 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 45 T-Coil WIFI5G U-NII-3: 802.11a Y transversal

Date: 2019/6/18
Communication System: UID 0, 802.11a (0); Frequency: 5785 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃
Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH 802.11a HAC_TCoil_WD_Emission/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 42.86 dB
ABM1 comp = -9.15 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 139.0 = 42.86 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Plot 46 T-Coil WIFI5G U-NII-3: 802.11a Z Axial

Date: 2019/6/18
Communication System: UID 0, 802.11a (0); Frequency: 5785 MHz;Duty Cycle: 1:1
Ambient Temperature:22.3 ℃ Phantom section: TCoil Section
DASY5 Configuration:
Sensor-Surface: 0mm (Mechanical Surface Detection)
Probe: AM1DV3 - 3082; ; Calibrated: 2018/3/26
Electronics: DAE4 Sn1291; Calibrated: 2018/12/4
Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA
Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

SAIPH 802.11a HAC_TCoil_WD_Emission/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 33.76
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
ABM1/ABM2 = 44.69 dB
ABM1 comp = -5.86 dBA/m
BWC Factor = 0.17 dB
Location: -4.2, -4.2, 3.7 mm

SAIPH 802.11a HAC_TCoil_WD_Emission/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 66.12
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.81 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:
Diff = 1.14 dB
BWC Factor = 10.81 dB
Location: -4.2, -4.2, 3.7 mm

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



0 dB = 171.5 = 44.69 dB



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

ANNEX C: Probe Calibration Certificate

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client: TA-SH (Auden)

Certificate No: AM1DV3-3082_Mar18

CALIBRATION CERTIFICATE

Object	AM1DV3 - SN: 3082
Calibration procedure(s)	QA CAL-24.v4 Calibration procedure for AM1D magnetic field probes and TMFS in the audio range
Calibration date:	March 26, 2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Keithley Multimeter Type 2001	SN: 0810278	31-Aug-17 (No. 21092)	Aug-18
Reference Probe AM1DV3	SN: 3000	24-Aug-17 (No. AM1DV3-3000_Aug17)	Aug-18
DAE4	SN: 781	17-Jan-18 (No. DAE4-781_Jan18)	Jan-19

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
AMCC	SN: 1050	01-Oct-13 (in house check Oct-17)	Oct-19
AMMI Audio Measuring Instrument	SN: 1062	26-Sep-12 (in house check Oct-17)	Oct-19

	Name	Function	Signature
Calibrated by:	Jeton Kastrati	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: March 26, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: AM1DV3-3082_Mar18 Page 1 of 3

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

[References

[1] ANSI-C63.19-2007
American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
[2] ANSI-C63.19-2011
American National Standard, Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
[3] DASY5 manual, Chapter: Hearing Aid Compatibility (HAC) T-Coil Extension

Description of the AM1D probe

The AM1D Audio Magnetic Field Probe is a fully shielded magnetic field probe for the frequency range from 100 Hz to 20 kHz. The pickup coil is compliant with the dimensional requirements of [1+2]. The probe includes a symmetric low noise amplifier for the signal available at the shielded 3 pin connector at the side. Power is supplied via the same connector (phantom power supply) and monitored via the LED near the connector. The 7 pin connector at the end of the probe does not carry any signals, but determines the angle of the sensor when mounted on the DAE. The probe supports mechanical detection of the surface.
The single sensor in the probe is arranged in a tilt angle allowing measurement of 3 orthogonal field components when rotating the probe by 120° around its axis. It is aligned with the perpendicular component of the field, if the probe axis is tilted nominally 35.3° above the measurement plane, using the connector rotation and sensor angle stated below.
The probe is fully RF shielded when operated with the matching signal cable (shielded) and allows measurement of audio magnetic fields in the close vicinity of RF emitting wireless devices according to [1+2] without additional shielding.

Handling of the item

The probe is manufactured from stainless steel. In order to maintain the performance and calibration of the probe, it must not be opened. The probe is designed for operation in air and shall not be exposed to humidity or liquids. For proper operation of the surface detection and emergency stop functions in a DASY system, the probe must be operated with the special probe cup provided (larger diameter).

Methods Applied and Interpretation of Parameters

- *Coordinate System:* The AM1D probe is mounted in the DASY system for operation with a HAC Test Arch phantom with AMCC Helmholtz calibration coil according to [3], with the tip pointing to "southwest" orientation.
- *Functional Test:* The functional test preceding calibration includes test of
  Noise level
  RF immunity (1kHz AM modulated signal). The shield of the probe cable must be well connected.
  Frequency response verification from 100 Hz to 10 kHz.
- *Connector Rotation:* The connector at the end of the probe does not carry any signals and is used for fixation to the DAE only. The probe is operated in the center of the AMCC Helmholtz coil using a 1 kHz magnetic field signal. Its angle is determined from the two minima at nominally +120° and –120° rotation, so the sensor in the tip of the probe is aligned to the vertical plane in z-direction, corresponding to the field maximum in the AMCC Helmholtz calibration coil.
- *Sensor Angle:* The sensor tilting in the vertical plane from the ideal vertical direction is determined from the two minima at nominally +120° and –120°. DASY system uses this angle to align the sensor for radial measurements to the x and y axis in the horizontal plane.

Sensitivity: With the probe sensor aligned to the z-field in the AMCC, the output of the probe is compared to the magnetic field in the AMCC at 1 kHz. The field in the AMCC Helmholtz coil is given by the geometry and the current through the coil, which is monitored on the precision shunt resistor of the coil.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

AM1D probe identification and configuration data

Item	**AM1DV3** Audio Magnetic 1D Field Probe
Type No	SP AM1 001 BA
Serial No	**3082**

Overall length	296 mm
Tip diameter	6.0 mm (at the tip)
Sensor offset	3.0 mm (centre of sensor from tip)
Internal Amplifier	20 dB

Manufacturer / Origin	Schmid & Partner Engineering AG, Zurich, Switzerland
Manufacturing date	May 28, 2010

Calibration data

Connector rotation angle	(in DASY system)	**7.6 °**	+/- 3.6 ° (k=2)
Sensor angle	(in DASY system)	**0.24 °**	+/- 0.5 ° (k=2)
Sensitivity at 1 kHz	(in DASY system)	**0.00739 V / (A/m)**	+/- 2.2 % (k=2)

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

ANNEX D: DAE4 Calibration Certificate

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client TA-SH (Auden)

Certificate No: DAE4-1291_Dec18

CALIBRATION CERTIFICATE

Object	DAE4 - SD 000 D04 BM - SN: 1291
Calibration procedure(s)	QA CAL-06.v29 Calibration procedure for the data acquisition electronics (DAE)
Calibration date:	December 04, 2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Keithley Multimeter Type 2001	SN: 0810278	03-Sep-18 (No:23488)	Sep-19
Secondary Standards	**ID #**	**Check Date (in house)**	**Scheduled Check**
Auto DAE Calibration Unit	SE UWS 053 AA 1001	04-Jan-18 (in house check)	In house check: Jan-19
Calibrator Box V2.1	SE UMS 006 AA 1002	04-Jan-18 (in house check)	In house check: Jan-19

	Name	Function	Signature
Calibrated by:	Dominique Steffen	Laboratory Technician	
Approved by:	Sven Kühn	Deputy Manager	i.v.

Issued: December 4, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: DAE4-1291_Dec18 Page 1 of 5

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Glossary

DAE	data acquisition electronics
Connector angle	information used in DASY system to align probe sensor X to the robot coordinate system.

Methods Applied and Interpretation of Parameters

- *DC Voltage Measurement:* Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle*: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
  - *DC Voltage Measurement Linearity:* Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
  - *Common mode sensitivity:* Influence of a positive or negative common mode voltage on the differential measurement.
  - *Channel separation:* Influence of a voltage on the neighbor channels not subject to an input voltage.
  - *AD Converter Values with inputs shorted:* Values on the internal AD converter corresponding to zero input voltage
  - *Input Offset Measurement*: Output voltage and statistical results over a large number of zero voltage measurements.
  - *Input Offset Current:* Typical value for information; Maximum channel input offset current, not considering the input resistance.
  - *Input resistance:* Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
  - *Low Battery Alarm Voltage:* Typical value for information. Below this voltage, a battery alarm signal is generated.
  - *Power consumption:* Typical value for information. Supply currents in various operating modes.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

DC Voltage Measurement

A/D - Converter Resolution nominal

High Range: 1LSB = 6.1μV , full range = -100...+300 mV

Low Range: 1LSB = 61nV , full range = -1.....+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Calibration Factors	X	Y	Z
High Range	402.580 ± 0.02% (k=2)	403.249 ± 0.02% (k=2)	403.163 ± 0.02% (k=2)
Low Range	3.97560 ± 1.50% (k=2)	3.97886 ± 1.50% (k=2)	3.97558 ± 1.50% (k=2)

Connector Angle

Connector Angle to be used in DASY system	164.5 ° ± 1 °

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Appendix (Additional assessments outside the scope of SCS0108)

1. DC Voltage Linearity

High Range		Reading (µV)	Difference (µV)	Error (%)
Channel X	+ Input	200038.51	1.95	0.00
Channel X	+ Input	20006.61	1.29	0.01
Channel X	- Input	-20003.34	2.94	-0.01
Channel Y	+ Input	200036.77	0.05	0.00
Channel Y	+ Input	20003.65	-1.54	-0.01
Channel Y	- Input	-20006.11	0.22	-0.00
Channel Z	+ Input	200035.08	-1.41	-0.00
Channel Z	+ Input	20002.62	-2.58	-0.01
Channel Z	- Input	-20006.40	-0.06	0.00

Low Range		Reading (µV)	Difference (µV)	Error (%)
Channel X	+ Input	2001.29	0.31	0.02
Channel X	+ Input	201.13	0.32	0.16
Channel X	- Input	-198.59	0.30	-0.15
Channel Y	+ Input	2000.40	-0.49	-0.02
Channel Y	+ Input	200.21	-0.66	-0.33
Channel Y	- Input	-199.89	-0.99	0.50
Channel Z	+ Input	2000.44	-0.41	-0.02
Channel Z	+ Input	199.70	-1.05	-0.52
Channel Z	- Input	-200.88	-1.78	0.89

2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Common mode Input Voltage (mV)	High Range Average Reading (µV)	Low Range Average Reading (µV)
Channel X	200	10.02	7.91
	- 200	-6.52	-8.20
Channel Y	200	14.18	13.58
	- 200	-15.10	-15.62
Channel Z	200	-17.07	-17.23
	- 200	14.74	14.83

3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Input Voltage (mV)	Channel X (µV)	Channel Y (µV)	Channel Z (µV)
Channel X	200	-	-0.01	-4.47
Channel Y	200	7.58	-	0.48
Channel Z	200	11.17	4.87	-

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	High Range (LSB)	Low Range (LSB)
Channel X	16117	16241
Channel Y	15930	16718
Channel Z	16177	17128

5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec
Input 10MΩ

	Average (µV)	min. Offset (µV)	max. Offset (µV)	Std. Deviation (µV)
Channel X	-0.59	-1.81	0.89	0.47
Channel Y	1.17	-0.04	2.05	0.45
Channel Z	-1.12	-2.70	0.51	0.57

6. Input Offset Current

Nominal Input circuitry offset current on all channels: <25fA

7. Input Resistance (Typical values for information)

	Zeroing (kOhm)	Measuring (MOhm)
Channel X	200	200
Channel Y	200	200
Channel Z	200	200

8. Low Battery Alarm Voltage (Typical values for information)

Typical values	Alarm Level (VDC)
Supply (+ Vcc)	+7.9
Supply (- Vcc)	-7.6

9. Power Consumption (Typical values for information)

Typical values	Switched off (mA)	Stand by (mA)	Transmitting (mA)
Supply (+ Vcc)	+0.01	+6	+14
Supply (- Vcc)	–0.01	-8	-9

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

ANNEX E: The EUT Appearances and Test Configuration

a: EUT

b: Adapter

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

c: USB Cable

Picture 2: Constituents of EUT

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Picture 3: Test Setup

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.