

FCC and IC Test report for parts 15.207, 15.209, 15.247, RSS-247, RSS-Gen

Product name : Wireless ergonomic Bluetooth mouse small size
Applicant : Hippus N.V.
FCC ID : XBBHSM-SHIFT
IC ID : 10466A-HSM SHIFT

Test report No. : 200500625 001 V1.10

Laboratory information

Accreditation

Telefication complies with the accreditation criteria for test laboratories as laid down in ISO/IEC 17025:2017. The accreditation covers the quality system of the laboratory as well as the specific activities as described in the authorized annex bearing the accreditation number L021 and is granted on 30 November 1990 by the Dutch Council For Accreditation (RvA: Raad voor Accreditatie).

Telefication is designated by the FCC as an Accredited Test Firm for compliance testing of equipment subject to Certification under Parts 15 & 18. The Designation number is: NL0001.

Telefication is a Wireless Device Testing laboratory recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements.

The Industry Canada registration number for the 3 meter test chamber of Telefication is: 4173A-1.

Telefication is a registered Conformity Assessment body (CAB) under the Japan-EC MRA (Agreement on Mutual Recognition between Japan and the European Community). The registration number is: 201.

Documentation

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at Telefication Netherlands.

Testing Location

Test Site	Telefication BV
Test Site location	Edisonstraat 12a 6902 PK Zevenaar The Netherlands Tel. +31316583180 Fax. +31316583189
Test Site FCC	NL0001

Revision History

Version	Date	Remarks	By
v0.50	1-10-2020	First draft	PS
v1.00	7-10-2020	Initial issue	PS
V1.10	23-03-2021	Second issue • Second dash in IC ID removed	PS

Table of Contents

Revision History	2
Summary of Test results.....	5
1 General Description.....	6
1.1 Applicant.....	6
1.2 Manufacturer	6
1.3 Tested Equipment Under Test (EUT)	6
1.4 Product specifications of Equipment under test	7
1.5 Environmental conditions.....	7
1.6 Measurement standards	7
1.7 Applicable standards	7
1.8 Observation and remarks	7
1.9 Conclusions.....	8
2 Test configuration of the Equipment Under Test	9
2.1 Test mode	9
2.2 Test setups.....	9
2.3 Equipment used in the test configuration.....	10
3 Test results.....	11
3.1 Radiated spurious emissions	11
3.1.1 Limit.....	11
3.1.2 Measurement instruments	11
3.1.3 Test setup.....	11
3.1.4 Test procedure	11
3.1.5 Measurement Uncertainty.....	11
3.1.6 Plots of the Radiated Spurious Emissions Measurement.....	12
3.2 6dB bandwidth Measurement.....	21
3.2.1 Limit.....	21
3.2.2 Measurement instruments	21
3.2.3 Test setup.....	21
3.2.4 Test procedure	21
3.2.5 Test Results of the 6 dB bandwidth Measurement.....	21
3.3 99% Occupied Bandwidth.....	22
3.3.1 Limit.....	22
3.3.2 Measurement instruments	22
3.3.3 Test setup.....	22
3.3.4 Test procedure	22
3.3.5 Test results of the 99% occupied bandwidth measurement.....	22
3.3.6 Plots of the 99% occupied bandwidth measurement	23

3.4	Output Power Measurement	25
3.4.1	Limit.....	25
3.4.2	Measurement instruments	25
3.4.3	Test setup.....	25
3.4.4	Test procedure	25
3.4.5	Test results of Output Power Measurement.....	25
3.5	Power Spectral Density.....	26
3.5.1	Limit.....	26
3.5.2	Measurement instruments	26
3.5.3	Test setup.....	26
3.5.4	Test procedure	26
3.5.5	Test results of Power Spectral Density Measurement	26
3.6	Band edge Measurement	27
3.6.1	Limit.....	27
3.6.2	Measurement instruments	27
3.6.3	Test setup.....	27
3.6.4	Test procedure	27
3.6.5	Measurement Uncertainty.....	27
3.6.6	Results of the band edge measurement	27
3.6.7	Plots of the Band edge Measurements.....	27
3.7	Conducted emissions.....	29
3.7.1	Limit.....	29
3.7.2	Measurement instruments	29
3.7.3	Test setup.....	29
3.7.4	Test procedure	29
3.7.5	Test results and plots of the AC mains conducted measurement	29
3.7.6	Measurement uncertainty	29
3.7.7	Plots of the AC mains conducted spurious measurement	30
4	Sample calculations	31

Summary of Test results

FCC	ISED	Description	Section in report	Verdict
15.247(d) 15.209 (a)	RSS-Gen 8.9	Radiated spurious emissions	3.1	Pass
15.205 (a)	RSS Gen 8.10	Spurious emissions in the restricted bands	3.1	Pass
15.247 (a)	RSS-247 5.2(a)	6 dB bandwidth	3.2	Pass
--	RSS-Gen 6.7	99% bandwidth	3.3	Pass
15.247 (b)	RSS-247 5.4 (d)	RF output power	3.4	Pass
15.247 (e)	RSS-247 5.2 (b)	Power spectral density	3.5	Pass
15.247 (d)	RSS-247 5.5	Band edge	3.6	Pass
15.207 (c)	RSS-Gen 8.8	Conducted spurious emissions on AC mains	3.7	Pass

1 General Description

1.1 Applicant

Client name:	Hippus N.V.
Address	Stationsstraat 1K
Zip code:	2371 SH Roelofarendsveen
Telephone:	+44 1872 562-715
E-mail:	eisma@handshoemouse.com
Contact name:	Sjoerd Eisma

1.2 Manufacturer

Manufacturer name:	Hippus N.V.
Address:	Stationsstraat 1K
Zip code:	2371 SH Roelofarendsveen
Telephone:	+44 1872 562-715
E-mail:	eisma@handshoemouse.com
Contact name:	Sjoerd Eisma

1.3 Tested Equipment Under Test (EUT)

Product name:	Wireless ergonomic Bluetooth mouse small size
Brand name:	HandshoeMouse
FCC ID:	XBBHSM-SHIFT
IC ID:	10466A-HSMSHIFT
Product type:	2.4 GHz wideband data transmission equipment
Model(s):	ShiftHSMs+
Variant Model(s):	ShiftHSMm+, ShiftHSMI+
Batch and/or serial No.	--
Software version:	--
Hardware version:	--
Date of receipt	16-07-2020
Tests started:	16-07-2020
Testing ended:	22-07-2020

1.4 Product specifications of Equipment under test

Tx Frequency:	BLE: 2400 – 2483.5 MHz
Rx frequency:	BLE: 2400 – 2483.5 MHz
Antenna type	Meander inverted F-antenna (MIFA)
Antenna gain:	1.6 dBi (typical)
Type of modulation:	BLE: GFSK
Emission designator	1M00F1D

1.5 Environmental conditions

Test date	16-07-2020	22-07-2020
Ambient temperature	24.6 °C	24.3 °C
Humidity	47.4 % RH	42.1 % RH

1.6 Measurement standards

- ANSI C63.10:2013

1.7 Applicable standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.207
- FCC Part 15 Subpart C §15.209
- FCC Part 15 Subpart C §15.247
- RSS-Gen Issue 5
- RSS-247 Issue 2

1.8 Observation and remarks

The RF power was set to -8 dBm during the measurements.

1.9 Conclusions

The sample of the product showed NO NON-COMPLIANCES to the specifications stated in paragraph 1.7 of this report.

The results of the test as stated in this report, are exclusively applicable to the product items as identified in this report. Telefication accepts no responsibility for any properties of product items in this test report, which are not supported by the tests as specified in paragraph 1.7 "*Applicable standards*".

All conducted tests are performed by:

Name : ing P.A. Suringa

Review of test methods and report by:

Name : ing R. van Barneveld

The above conclusions have been verified by the following signatory:

Date : 23-05-2021

Name : ing R. van Barneveld

Function : Test Engineer

Signature :

A handwritten signature in blue ink, consisting of a large, stylized 'R' followed by a horizontal line and a diagonal stroke.


2 Test configuration of the Equipment Under Test

2.1 Test mode


The applicant provided test mode firmware for the BLE radio, in which it was possible to configure the radio to transmit continuously.

2.2 Test setups

Radiated emissions test setup 30 MHz - 1 GHz




Radiated emissions test setup above 1 GHz



Conducted emissions test setup

Emissions test on AC mains



2.3 Equipment used in the test configuration

Test Setup	Test setup number*)	Used at paragraphs:
Radiated emissions	TS00004	3.1
Conducted emissions	TS00005	3.7

*) Test setup numbers represent a complete test system; the individual equipment whereof are included in the Telefication equipment database.

Description	Manufacturer	Model	ID	Used at Par.
Spectrum analyzer	Rohde & Schwarz	FSV40	TE01269	3.2 – 3.6
High pass filter	Wainwright	WHK3.0/18G-10EF	TE01140	3.1
Programmable AC source	Chroma	61601	TE02001	3.7

3 Test results

3.1 Radiated spurious emissions

3.1.1 Limit

15.247(d)

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance(m)
30 -88	100	40	3
88 - 216	150	43,5	3
216-960	200	46	3
Above 960	500	54	3

3.1.2 Measurement instruments

The measurement instruments are listed in chapter 2.3 of this report.

3.1.3 Test setup

The test setup is as shown in chapter 2.2 of this report.

3.1.4 Test procedure

30 MHz to 26.5 GHz: According to ANSI C63.4-2014, section 8.3

30 MHz to 1 GHz: IRN 026 – Method 1

1 GHz to 18 GHz: IRN 026 – Method 2

18 to 26.5 GHz: IRN 026 – Method 3

3.1.5 Measurement Uncertainty


Frequency range	Polarization	Uncertainty
30 – 200 MHz	Horizontal	± 4.5 dB
	Vertical	± 5.4 dB
200 -1000 MHz	Horizontal	± 3.6 dB
	Vertical	± 4.6 dB
1 – 18 GHz	Horizontal	± 5.7 dB
	Vertical	± 5.7 dB
18 – 26.5 GHz	Horizontal	± 4.9 dB
	Vertical	± 4.9 dB

3.1.6 Plots of the Radiated Spurious Emissions Measurement


30 -1000 MHz

Ch 37

Vertical polarization




Horizontal polarization



Ch 17


Vertical polarization

RadiMation



Horizontal polarization


RadiMation



Ch 39


Vertical polarization

RadiMation



Horizontal polarization


RadiMation




1 -18 GHz

Ch 37

Vertical polarization




Horizontal polarization



Ch 17


Vertical polarization

RadiMation



Horizontal polarization


RadiMation



Ch 39


Vertical polarization

RadiMation



Horizontal polarization

RadiMation




18 – 26 GHz

Ch 37


Vertical polarization

RadiMation



Horizontal polarization


RadiMation



Ch 17


Vertical polarization

RadiMation



Horizontal polarization


RadiMation



Ch 39


Vertical polarization

RadiMation



Horizontal polarization

RadiMation



3.2 6dB bandwidth Measurement

3.2.1 Limit

The minimum 6 dB Bandwidth shall be at least 500 kHz.

3.2.2 Measurement instruments

The measurement instruments are listed in chapter 2.3 of this report.

3.2.3 Test setup

The test setup is as shown in chapter 2.2 of this report.

3.2.4 Test procedure

Tests according to ANSI C63.10

IRN 017 - Occupied bandwidth (Hz) Method 4 – DTS Bandwidth.

3.2.5 Test Results of the 6 dB bandwidth Measurement

Technology Std.	Channel	Frequency (MHz)	Data rate	6dB bandwidth (kHz)
Bluetooth Low energy	37	2402	2 Mbps	725.6
	17	2440	2 Mbps	725.6
	39	2480	2 Mbps	737.8
Uncertainty	+/-36 kHz			

3.3 99% Occupied Bandwidth

3.3.1 Limit

No limit applies.

3.3.2 Measurement instruments

The measurement instruments are listed in chapter 2.3 of this report.

3.3.3 Test setup

The test setup is as shown in chapter 2.2 of this report.

3.3.4 Test procedure

IRN 017 - Occupied bandwidth (Hz) Method 1 – XX % power bandwidth.


1. Set the centre frequency to the nominal EUT channel centre frequency
2. Set span = 1.5 times to 0.5 times the Occupied Bandwidth
3. Set VBW $\geq$ 3x RBW
4. Video averaging is not permitted. Where practical, detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.

3.3.5 Test results of the 99% occupied bandwidth measurement

Technology Std.	Channel	Frequency (MHz)	Data rate	99% bandwidth (kHz)
Bluetooth Low energy	37	2402	2 Mbps	1070
	17	2440	2 Mbps	1080
	39	2480	2 Mbps	1080
Uncertainty	+/- 58 kHz			


3.3.6 Plots of the 99% occupied bandwidth measurement

Channel 37




Date: 16.SEP.2020 12:13:05

Channel 17



Date: 16.SEP.2020 12:15:28

Channel 39



Date: 16.SEP.2020 12:17:11

3.4 Output Power Measurement

3.4.1 Limit

For systems using digital modulation in the 2400-2483.5 MHz, the limit for the peak output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point to point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.4.2 Measurement instruments

The measurement instruments are listed in chapter 2.3 of this report.

3.4.3 Test setup

The test setup is as shown in chapter 2.2 of this report.

3.4.4 Test procedure

The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05.

IRN 014 - RF power (W) - Method 1 – AVGSA (DTS) according to ANSI C63.10.

3.4.5 Test results of Output Power Measurement

Technology Std.	Channel	Frequency (MHz)	Data rate	Output power (dBm)
Bluetooth Low Energy	37	2402	2 Mbps	-8.56
	17	2440	2 Mbps	-8.95
	39	2480	2 Mbps	-9.16
Uncertainty	+/-0.71 dB			

3.5 Power Spectral Density

3.5.1 Limit

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.

3.5.2 Measurement instruments

The measurement instruments are listed in chapter 2.3 of this report.

3.5.3 Test setup

The test setup is as shown in chapter 2.2 of this report.

3.5.4 Test procedure

The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05.

IRN 030 - Spectral power density (W per n.Hz) - Method 5 – Peak method PKPSD (PSD in 3 kHz band)

3.5.5 Test results of Power Spectral Density Measurement

Peak Power spectral density				
Technology Std.	Channel	Frequency (MHz)	Data rate	PSD (dBm/100 kHz)
Bluetooth Low Energy	37	2402	2 Mbps	-8.67
	17	2440	2 Mbps	-9.03
	39	2480	2 Mbps	-9.53
Uncertainty	+/-0.71 dB			

3.6 Band edge Measurement

3.6.1 Limit

Band edge:

At the edge of the authorized band the RF power shall be at least 20 dB down.

3.6.2 Measurement instruments

The measurement instruments are listed in chapter 2.3 of this report.

3.6.3 Test setup

The test setup is as shown in chapter 2.2 of this report.

3.6.4 Test procedure

The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05, sections 11.3 and 12.1.
IRN 026 - Radiated electrical disturbance (V per m) Method 6 – Radiated electrical disturbance at the Authorized band edge.

3.6.5 Measurement Uncertainty

± 2.5 dB


3.6.6 Results of the band edge measurement

Technology Std.	Channel	Frequency (MHz)	Data rate	dB down
Bluetooth Low Energy	37	2402	2 Mbps	44.8
	39	2480	2 Mbps	53.9


3.6.7 Plots of the Band edge Measurements

See next page

BLE Lower band edge (Channel 37)



BLE Upper band edge (Channel 39)



3.7 Conducted emissions

3.7.1 Limit

According to 15.207 (c)

Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.

3.7.2 Measurement instruments

The measurement instruments are listed in chapter 2.3 of this report.

3.7.3 Test setup

The test setup is as shown in chapter 2.2 of this report.

3.7.4 Test procedure

According to ANSI C63.4: 2014, section 13.3

IRN 029 – Method 1

3.7.5 Test results and plots of the AC mains conducted measurement


See next page.

3.7.6 Measurement uncertainty


+/- 3.6 dB

3.7.7 Plots of the AC mains conducted spurious measurement

Phase



Neutral



4 Sample calculations

Field Strength Measurement:

$$E \text{ (dB}\mu\text{V/m)} = U \text{ (dB}\mu\text{V)} + AF \text{ (dB/m)} + \text{Corr. (dB)}$$

Where:

E = Electric field strength

U = Measuring receiver voltage

AF = Antenna factor

CL = Cable loss

Corr. = sum of single correction factors of used cable and amplifier (if applicable).

Linear interpolation will be used for frequencies in between the values in the table.

Tables shows an extract of the values.

Frequency (MHz)	AF (dB/m)	Cable loss (dB)	Corr. (dB)
	TE 00967 Chase CBL6112A SN: 2308	Id: SAR cable	
30	18,6	0,68	19,28
100	10,7	1,15	11,85
150	10,6	1,41	12,01
200	9,3	1,63	10,93
250	12,6	1,93	14,53
300	13,3	2,12	15,42
350	14,6	2,2	16,8
400	15,5	2,29	17,79
450	16,9	2,53	19,43
500	17,5	2,67	20,17
550	18,4	2,9	21,3
600	18,8	3,02	21,82
650	19,2	3,09	22,29
700	19	3,22	22,22
750	19,8	3,56	23,36
800	19,7	3,69	23,39
900	20,4	3,81	24,21
950	20,8	3,91	24,71
1000	21,2	4,3	25,5

Frequency (MHz)	AF (dB/m)	Gain (dB)	Cable loss (dB)	Corr. (dB)
	TE 00531 Emco 3115 SN: 9412-4377	TE 11132 Miteq JS4-18004000-30-8P-A1	TE 01315	
1000	23,6	40,4	2,0	66
1500	25,1	40,5	2,4	68
2000	27,1	40,5	2,7	70,3
2500	28,6	40,7	3,2	72,5
3000	30,5	40,7	3,2	74,4
3500	31,2	40,7	3,4	75,3
4000	32,7	40,9	4,9	78,5
4500	32,4	40,9	4,4	77,7
5000	33,2	40,7	4,6	78,5
5500	34,0	40,5	4,5	79
6000	34,6	40,0	5,2	79,8
6500	34,3	39,4	5,9	79,6
7000	35,2	38,6	5,7	79,5
7500	36,4	39,2	5,9	81,5
8000	37,0	38,9	6,3	82,2
8500	37,5	38,4	6,4	82,3
9000	38,1	37,4	6,5	82
9500	37,8	37,0	7,1	81,9
10000	38,2	36,5	7,3	82
10500	38,1	36,7	7,6	82,4
11000	38,3	36,9	8,3	83,5
11500	38,5	37,6	8,1	84,2
12000	39,1	38,3	8,4	85,8
12500	38,7	38,5	8,3	85,5
13000	39,2	38,9	9,2	87,3
13500	40,5	40,2	8,3	89
14000	41,1	40,0	8,2	89,3
14500	41,4	40,1	8,2	89,7
15000	40,2	41,4	8,3	89,9
15500	37,9	41,4	8,6	87,9
16000	37,5	42,8	9,2	89,5
16500	38,6	42,3	8,8	89,7
17000	41,1	43,1	9,4	93,6
17500	42,7	43,2	9,4	95,3
18000	44,0	44,2	9,8	98

Frequency (MHz)	AF (dB/m)	Gain (dB)	Cable loss (dB)	Corr. (dB)
	TE 00531 Emco 3115 SN: 9412-4377	TE 11132 Miteq JS4-18004000-30-8P-A1	TE 01315	
18000	31,3	26,2	9,8	67,3
19000	31,5	26,1	9,6	67,2
20000	31,7	25,9	11	68,6
21000	31,9	24,3	10,7	66,9
22000	32,1	18,3	10,5	60,9
23000	32,2	18,9	10,8	61,9
24000	32,3	23,6	11,4	67,3
25000	32,4	24,5	11,6	68,5
26000	32,5	25,3	11,7	69,5