



TEST REPORT

Report Reference No...... : **TRE1710005401** R/C.....: 84827
FCC ID..... : **XBE-LA18S**
Applicant's name..... : **LINAK A/S**
Address..... : Smedevaenget 8,Guderup,Deskline - 6430 Nordborg,Denmark
Manufacturer..... : LINAK US Inc
Address..... : 2200 Stanley Gault Parkway, Louisville KY 40223, USA
Test item description : **LA18 Actuator**
Trade Mark : LINAK
Model/Type reference..... : LA18S
Listed Model(s)..... : -
Standard : **FCC CFR Title 47 Part 15 Subpart C Section 15.247**
Date of receipt of test sample..... : Oct.12,2017
Date of testing..... : Oct.13,2017- Oct.25,2017
Date of issue..... : Oct.26,2017
Result..... : **PASS**

Compiled by
(Position+Printed name+Signature) : File administrators Candy Liu

Supervised by
(Position+Printed name+Signature) : Project Engineer John Qiao

Approved by
(Position+Printed name+Signature) : RF Manager Hans Hu

Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address..... : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road,
Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Operation state	6
3.4.	EUT configuration	6
3.5.	Modifications	6
<u>4.</u>	<u>TEST ENVIRONMENT</u>	<u>7</u>
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Environmental conditions	8
4.4.	Statement of the measurement uncertainty	8
4.5.	Equipments Used during the Test	9
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>10</u>
5.1.	Antenna Requirement	10
5.2.	Conducted Emissions (AC Main)	11
5.3.	Conducted Peak Output Power	14
5.4.	Power Spectral Density	15
5.5.	6dB bandwidth	17
5.6.	Restricted band	19
5.7.	Band edge and Spurious Emissions (conducted)	21
5.8.	Spurious Emissions (radiated)	29
<u>6.</u>	<u>TEST SETUP PHOTOS</u>	<u>33</u>
<u>7.</u>	<u>EXTERANAL AND INTERNAL PHOTOS</u>	<u>35</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

[ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 558074 D01 DTS Meas Guidance v04](#): Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating under §15.247

1.2. Report version

Version No.	Date of issue	Description
00	Oct.26,2017	Original

2. TEST DESCRIPTION

Test Item	FCC Rule	Result	Test Engineer
Antenna requirement	15.203/15.247(c)	Pass	William Wang
Line Conducted Emissions (AC Main)	15.207	Pass	William Wang
Conducted Peak Output Power	15.247(b)(3)	Pass	William Wang
Power Spectral Density	15.247(e)	Pass	William Wang
6dB Bandwidth	15.247(a)(2)	Pass	William Wang
Restricted band	15.247(d)/15.205	Pass	William Wang
Spurious Emissions	15.247(d)/15.209	Pass	William Wang

Note: The measurement uncertainty is not included in the test result.

3. SUMMARY

3.1. Client Information

Applicant:	LINAK A/S
Address:	Smedevaenget 8,Guderup,Deskline - 6430 Nordborg,Denmark
Manufacturer:	LINAK US Inc
Address:	2200 Stanley Gault Parkway, Louisville KY 40223, USA

3.2. Product Description

Name of EUT:	LA18 Actuator
Trade Mark:	LINAK
Model No.:	LA18S
Listed Model(s):	-
Power supply:	DC 24V
Adapter information:	Input : 120V~,60Hz,1.2A Output: 24V, 2A
Hardware version:	10907691-B
Software version:	03002010ver0.4
Bluetooth	
Version:	Supported BT4.0+BLE
Modulation:	GFSK
Operation frequency:	2402MHz~2480MHz
Channel number:	40
Channel separation:	2MHz
Antenna type:	Intergral Antenna
Antenna gain:	3.3 dBi

3.3. Operation state

➤ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

Channel	Frequency (MHz)
00	2402
01	2404
⋮	⋮
19	2440
⋮	⋮
38	2478
39	2480

➤ Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit (duty cycle>98%).
For AC power line conducted emissions:
The EUT was set to connect with the Bluetooth instrument under large package sizes transmission.
For RF test axis
EUT in each of three orthogonal axis emissions had been tested ,but only the worst case (X axis) data Recorded in the report.

3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

●	AC Adapter	Model No.:	LINAK
		Input:	120V~,60Hz,1.2A
		Output	24V, 2A
	/	Manufacturer:	/
		Model No.:	/

3.5. Modifications

No modifications were implemented to meet testing criteria.

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

4.2. Test Facility

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files.

IC-Registration No.:5377B-1

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No.: 5377B-1.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors in calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd. quality system according to ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Here after the best measurement capability for Shenzhen Huatongwei International Inspection Co., Ltd. is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emissions 9kHz~40GHz	1.60 dB	(1)
Radiated spurious emissions 9kHz~40GHz	2.20 dB	(1)
Conducted Emissions 9kHz~30MHz	3.39 dB	(1)
Radiated Emissions 30~1000MHz	4.24 dB	(1)
Radiated Emissions 1~18GHz	5.16 dB	(1)
Radiated Emissions 18~40GHz	5.54 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

4.5. Equipments Used during the Test

Conducted Emissions					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	Artificial Mains	Rohde&Schwarz	ESH2-Z5	100028	2016/11/13
2	EMI Test Receiver	Rohde&Schwarz	ESCI3	100038	2016/11/13
3	Pulse Limiter	Rohde&Schwarz	ESHSZ2	100044	2016/11/13
4	EMI Test Software	Rohde&Schwarz	ES-K1 V1.71	-	-

Radiated Emissions					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI test receiver	Rohde&Schwarz	ESI 26	100009	2016/11/13
2	Loop Antenna	Rohde&Schwarz	HFH2-Z2	100020	2016/11/13
3	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	2016/11/13
4	Horn antenna	ShwarzBeck	9120D	1011	2016/11/13
5	Horn Antenna	SCHWARZBECK	BBHA9170	25841	2016/11/13
6	Amplifier	Sonoma	310N	E009-13	2016/11/13
7	JS Amplifier	Rohde&Schwarz	JS4-00101800-28-5A	F201504	2016/11/13
8	Amplifier	Compliance Direction systems	PAP1-4060	120	2016/11/13
9	High pass filter	Compliance Direction systems	BSU-6	34202	2016/11/13
10	EMI test Software	Rohde&Schwarz	ESK1	-	-
11	EMI test Software	Audix	E3	-	-
12	TURNTABLE	MATURO	TT2.0	-	-
13	ANTENNA MAST	MATURO	TAM-4.0-P	-	-

RF Conducted methods					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	Spectrum Analyzer	Rohde&Schwarz	FSP	1164.4391.40	2016/11/13
2	Power Meter	Anritsu	ML2480B	100798	2016/11/13
3	MXA Signal Analyzer	Agilent Technologies	N9020A	MY5050187	2016/11/13

The Cal.Interval was one year.

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST RESULTS

☒ Passed ☐ Not Applicable

The directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



5.2. Conducted Emissions (AC Main)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS


☒ Passed ☐ Not Applicable

Note:

- 1) Transd = Cable lose + Pulse Limiter Factor + Artificial Mains Factor
- 2) Margin = Limit - Level

Test Line:


L



Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	40.90	10.4	66	25.1	QP	L1	GND
0.568500	30.50	10.2	56	25.5	QP	L1	GND
2.152500	31.10	10.2	56	24.9	QP	L1	GND
3.219000	31.20	10.2	56	24.8	QP	L1	GND
6.963000	33.70	10.3	60	26.3	QP	L1	GND
23.127000	36.80	10.7	60	23.2	QP	L1	GND
Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
3.250500	32.00	10.3	46	14.0	AV	L1	GND
19.500000	34.40	10.5	50	15.6	AV	L1	GND
20.431500	32.40	10.6	50	17.6	AV	L1	GND
21.358500	35.60	10.6	50	14.4	AV	L1	GND
22.285500	34.70	10.6	50	15.3	AV	L1	GND
27.856500	34.90	10.8	50	15.1	AV	L1	GND

Test Line:

N




Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	42.60	10.4	66	23.4	QP	N	GND
0.555000	36.30	10.2	56	19.7	QP	N	GND
1.990500	30.60	10.2	56	25.4	QP	N	GND
2.724000	30.20	10.2	56	25.8	QP	N	GND
21.345000	36.20	10.6	60	23.8	QP	N	GND
23.127000	37.50	10.7	60	22.5	QP	N	GND
Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
3.246000	30.40	10.3	46	15.6	AV	N	GND
4.177500	31.80	10.3	46	14.2	AV	N	GND
20.418000	35.30	10.6	50	14.7	AV	N	GND
21.345000	35.80	10.6	50	14.2	AV	N	GND
22.272000	33.80	10.6	50	16.2	AV	N	GND
27.843000	34.70	10.8	50	15.3	AV	N	GND

5.3. Conducted Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): **30 dBm**

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10: 2013 and KDB 558074 D01 for compliance to FCC 47 CFR 15.247 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.
4. Record the measurement data.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable


Type	Channel	Output power (dBm)	Limit (dBm)	Result
BT-BLE	00	-3.701	≤30.00	Pass
	19	-3.343		
	39	-4.264		

5.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:
Center frequency=DTS channel center frequency
Span =1.5 times the DTS bandwidth
RBW = 3 kHz ≤ RBW ≤ 100 kHz, VBW ≥ 3 × RBW
Sweep time = auto couple
Detector = peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

Type	Channel	Power Spectral Density(dBm/RBW)	Limit (dBm/RBW)	Result
BT-BLE	00	-18.326	≤8.00	Pass
	19	-18.055		
	39	-18.937		

Test plot as follows:


CH00	
CH19	
CH39	

5.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
 Center Frequency = DTS channel center frequency
 Span = 2 x DTS bandwidth
 RBW = 100 kHz, VBW $\geq 3 \times$ RBW
 Sweep time = auto couple
 Detector = Peak
 Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

Type	Channel	6dB Bandwidth(MHz)	Limit (MHz)	Result
BT-BLE	00	0.6915	≥ 500	Pass
	19	0.7169		
	39	0.7088		

Test plot as follows:

CH00	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.402000000 GHz Center Freq: 2.402000000 GHz Trig: Free Run Avg/Hold: 1/1 Radio Std: None Radio Device: BTS Ref Offset 0.5 dB Ref 10.50 dBm Mkr1 2.4019908 GHz -3.7907 dBm Center 2.402 GHz #Res BW 100 kHz #VBW 300 kHz Span 2 MHz Sweep 1.067 ms Occupied Bandwidth 1.5962 MHz Total Power 3.49 dBm Transmit Freq Error -20.867 kHz OBW Power 99.00 % x dB Bandwidth 691.5 kHz x dB -6.00 dB Frequency Center Freq 2.402000000 GHz CF Step 200.000 kHz Auto Man Freq Offset 0 Hz
CH19	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.440000000 GHz Center Freq: 2.440000000 GHz Trig: Free Run Avg/Hold: 1/1 Radio Std: None Radio Device: BTS Ref Offset 0.5 dB Ref 10.50 dBm Mkr1 2.4399733 GHz -3.5684 dBm Center 2.44 GHz #Res BW 100 kHz #VBW 300 kHz Span 2 MHz Sweep 1.067 ms Occupied Bandwidth 1.5732 MHz Total Power 3.58 dBm Transmit Freq Error -37.686 kHz OBW Power 99.00 % x dB Bandwidth 716.9 kHz x dB -6.00 dB Frequency Center Freq 2.440000000 GHz CF Step 200.000 kHz Auto Man Freq Offset 0 Hz
CH39	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.480000000 GHz Center Freq: 2.480000000 GHz Trig: Free Run Avg/Hold: 1/1 Radio Std: None Radio Device: BTS Ref Offset 0.5 dB Ref 10.50 dBm Mkr1 2.48 GHz -4.4863 dBm Center 2.48 GHz #Res BW 100 kHz #VBW 300 kHz Span 2 MHz Sweep 1.067 ms Occupied Bandwidth 1.5502 MHz Total Power 2.61 dBm Transmit Freq Error -22.532 kHz OBW Power 99.00 % x dB Bandwidth 708.8 kHz x dB -6.00 dB Frequency Center Freq 2.480000000 GHz CF Step 200.000 kHz Auto Man Freq Offset 0 Hz

CH00									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.50	44.23	27.26	6.83	37.87	40.45	74.00	-33.55	Vertical	Peak
2500.00	41.78	27.20	6.84	37.87	37.95	74.00	-36.05	Vertical	Peak
2483.50	50.99	27.26	6.83	37.87	47.21	74.00	-26.79	Horizontal	Peak
2500.00	34.19	27.20	6.84	37.87	30.36	74.00	-43.64	Horizontal	Peak
2310.00	29.18	28.05	6.62	37.65	26.20	54.00	-27.80	Vertical	Average
2390.03	29.70	27.65	6.75	37.87	26.23	54.00	-27.77	Vertical	Average
2310.00	27.07	28.05	6.62	37.65	24.09	54.00	-29.91	Horizontal	Average
2390.03	26.51	27.65	6.75	37.87	23.04	54.00	-30.96	Horizontal	Average


CH39									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	35.61	28.05	6.62	37.65	32.63	74.00	-41.37	Vertical	Peak
2390.03	39.52	27.65	6.75	37.87	36.05	74.00	-37.95	Vertical	Peak
2310.00	35.06	28.05	6.62	37.65	32.08	74.00	-41.92	Horizontal	Peak
2390.03	40.03	27.65	6.75	37.87	36.56	74.00	-37.44	Horizontal	Peak
2483.50	40.55	27.26	6.83	37.87	36.77	54.00	-17.23	Vertical	Average
2500.00	29.59	27.20	6.84	37.87	25.76	54.00	-28.24	Vertical	Average
2483.50	38.18	27.26	6.83	37.87	34.40	54.00	-19.60	Horizontal	Average
2500.00	26.31	27.20	6.84	37.87	22.48	54.00	-31.52	Horizontal	Average

5.7. Band edge and Spurious Emissions (conducted)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure
Center frequency=DTS channel center frequency
The span = 1.5 times the DTS bandwidth.
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum PSD level

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

3. Emission level measurement
Set the center frequency and span to encompass frequency range to be measured
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.



TEST MODE:


Please refer to the clause 3.3



TEST RESULTS


☒ Passed ☐ Not Applicable



Test Item:	Band edge																																													
CH00	Agilent Spectrum Analyzer - Sweep SA Center Freq 2.357500000 GHz Ref Offset 0.5 dB Ref 10.50 dBm Mkr4 2.337 776 GHz -44.559 dBm Start 2.31000 GHz #Res BW 100 kHz #VBW 300 kHz Stop 2.40500 GHz Sweep 9.600 ms (8001 pts) <table><tr><th>MNR</th><th>MODE</th><th>TRC</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.401 996 GHz</td><td>-3.701 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.400 000 GHz</td><td>-43.587 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.390 000 GHz</td><td>-40.696 dBm</td><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.337 776 GHz</td><td>-44.559 dBm</td><td></td><td></td><td></td></tr></table> Frequency Auto Tune Center Freq 2.357500000 GHz Start Freq 2.310000000 GHz Stop Freq 2.405000000 GHz CF Step 9.500000 MHz Man Freq Offset 0 Hz	MNR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.401 996 GHz	-3.701 dBm				2	N	1	f	2.400 000 GHz	-43.587 dBm				3	N	1	f	2.390 000 GHz	-40.696 dBm				4	N	1	f	2.337 776 GHz	-44.559 dBm			
MNR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																						
1	N	1	f	2.401 996 GHz	-3.701 dBm																																									
2	N	1	f	2.400 000 GHz	-43.587 dBm																																									
3	N	1	f	2.390 000 GHz	-40.696 dBm																																									
4	N	1	f	2.337 776 GHz	-44.559 dBm																																									
CH39	Agilent Spectrum Analyzer - Sweep SA Center Freq 2.489000000 GHz Ref Offset 0.5 dB Ref 10.50 dBm Mkr4 2.483 706 25 GHz -45.174 dBm Start 2.47800 GHz #Res BW 100 kHz #VBW 300 kHz Stop 2.50000 GHz Sweep 2.133 ms (8001 pts) <table><tr><th>MNR</th><th>MODE</th><th>TRC</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.480 007 50 GHz</td><td>-4.374 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.483 500 00 GHz</td><td>-47.724 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.500 000 00 GHz</td><td>-60.345 dBm</td><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.483 706 25 GHz</td><td>-45.174 dBm</td><td></td><td></td><td></td></tr></table> Frequency Auto Tune Center Freq 2.489000000 GHz Start Freq 2.478000000 GHz Stop Freq 2.500000000 GHz CF Step 2.200000 MHz Man Freq Offset 0 Hz	MNR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.480 007 50 GHz	-4.374 dBm				2	N	1	f	2.483 500 00 GHz	-47.724 dBm				3	N	1	f	2.500 000 00 GHz	-60.345 dBm				4	N	1	f	2.483 706 25 GHz	-45.174 dBm			
MNR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																						
1	N	1	f	2.480 007 50 GHz	-4.374 dBm																																									
2	N	1	f	2.483 500 00 GHz	-47.724 dBm																																									
3	N	1	f	2.500 000 00 GHz	-60.345 dBm																																									
4	N	1	f	2.483 706 25 GHz	-45.174 dBm																																									


Test Item:	SE
CH00 Reference level	 The screenshot shows an Agilent Spectrum Analyzer interface. The main display shows a signal spectrum with a peak at 2.402 GHz. The center frequency is 2.402000000 GHz, and the span is 4.000 MHz. The resolution bandwidth is 100 kHz, and the sweep time is 1.067 ms. The signal level is -3.819 dBm. The reference level is 10.50 dBm. The frequency range is from 2.400000000 GHz to 2.404000000 GHz. The CF step is 400.000 kHz. The frequency offset is 0 Hz.
CH00 30MHz~3GHz	 The screenshot shows an Agilent Spectrum Analyzer interface. The main display shows a signal spectrum with a peak at 2.630 GHz. The center frequency is 1.515000000 GHz, and the span is 284.3 ms. The resolution bandwidth is 100 kHz, and the sweep time is 284.3 ms. The signal level is -56.110 dBm. The reference level is 20.50 dBm. The frequency range is from 30.00000000 MHz to 3.000 GHz. The CF step is 297.000000 MHz. The frequency offset is 0 Hz.
CH00 3GHz~5GHz	 The screenshot shows an Agilent Spectrum Analyzer interface. The main display shows a signal spectrum with a peak at 4.804 GHz. The center frequency is 4.000000000 GHz, and the span is 191.5 ms. The resolution bandwidth is 100 kHz, and the sweep time is 191.5 ms. The signal level is -44.979 dBm. The reference level is 20.50 dBm. The frequency range is from 3.000 GHz to 5.000 GHz. The CF step is 200.000000 MHz. The frequency offset is 0 Hz.



CH19 Reference level	 Agilent Spectrum Analyzer - Sweep SA Center Freq 2.44000000 GHz Ref Offset 0.5 dB Ref 10.50 dBm Mkr1 2.439 980 0 GHz -3.610 dBm Center 2.440000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 1.067 ms (8001 pts) Span 4.000 MHz Frequency Auto Tune Center Freq 2.44000000 GHz Start Freq 2.438000000 GHz Stop Freq 2.442000000 GHz CF Step 400.000 MHz Freq Offset 0 Hz	
CH19 30MHz~3GHz	 Agilent Spectrum Analyzer - Sweep SA Center Freq 1.515000000 GHz Ref Offset 0.5 dB Ref 20.50 dBm Mkr2 2.332 0 GHz -51.829 dBm Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 284.3 ms (8001 pts) Stop 3.000 GHz Frequency Auto Tune Center Freq 1.515000000 GHz Start Freq 30.0000000 MHz Stop Freq 3.000000000 GHz CF Step 297.000000 MHz Freq Offset 0 Hz	
CH19 3GHz~5GHz	 Agilent Spectrum Analyzer - Sweep SA Center Freq 4.000000000 GHz Ref Offset 0.5 dB Ref 20.50 dBm Mkr1 4.879 50 GHz -47.159 dBm Start 3.000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 191.5 ms (8001 pts) Stop 5.000 GHz Frequency Auto Tune Center Freq 4.000000000 GHz Start Freq 3.000000000 GHz Stop Freq 5.000000000 GHz CF Step 200.000000 MHz Freq Offset 0 Hz	



CH39 Reference level	 Agilent Spectrum Analyzer - Sweep SA Center Freq 2.48000000 GHz Ref Offset 0.5 dB Ref 10.50 dBm Mkr1 2.480 004 0 GHz -4.544 dBm Center 2.480000 GHz #Res BW 100 kHz #VBW 300 kHz Span 4.000 MHz Sweep 1.067 ms (8001 pts)	Frequency Auto Tune Center Freq 2.48000000 GHz Start Freq 2.478000000 GHz Stop Freq 2.482000000 GHz CF Step 400.000 MHz Auto Freq Offset 0 Hz
CH39 30MHz~3GHz	 Agilent Spectrum Analyzer - Sweep SA Center Freq 1.515000000 GHz Ref Offset 0.5 dB Ref 20.50 dBm Mkr2 2.630 2 GHz -46.226 dBm Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Stop 3.000 GHz Sweep 284.3 ms (8001 pts)	Frequency Auto Tune Center Freq 1.515000000 GHz Start Freq 30.0000000 MHz Stop Freq 3.000000000 GHz CF Step 297.000000 MHz Auto Freq Offset 0 Hz
CH39 3GHz~5GHz	 Agilent Spectrum Analyzer - Sweep SA Center Freq 4.000000000 GHz Ref Offset 0.5 dB Ref 20.50 dBm Mkr1 4.959 50 GHz -51.077 dBm Start 3.000 GHz #Res BW 100 kHz #VBW 300 kHz Stop 5.000 GHz Sweep 191.5 ms (8001 pts)	Frequency Auto Tune Center Freq 4.000000000 GHz Start Freq 3.000000000 GHz Stop Freq 5.000000000 GHz CF Step 200.000000 MHz Auto Freq Offset 0 Hz



5.8. Spurious Emissions (radiated)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


- 9 kHz ~ 30 MHz



- 30 MHz ~ 1 GHz



- Above 1 GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1 GHz, RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) Above 1GHz, RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**


Note:

- 1) Above 1GHz Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
 - 2) The emission levels of other frequencies are very lower than the limit and not show in test report.
- **9 kHz ~ 30 MHz**
The EUT was pre-scanned the frequency band (9 kHz ~ 30 MHz), found the radiated level lower than the limit, so don't show on the report.
- **30 MHz ~ 1000 MHz**
Have pre-scan all modulation mode, found the BT-BLE mode CH39 which it was worst case, so only the worst case's data on the test report.

➤ 30 MHz ~ 1 GHz

Polarization:

Vertical


**MEASUREMENT RESULT: "GM1710196157_red"**

10/20/2017 12:09AM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	28.10	-13.3	40.0	11.9	QP	100.0	38.00	VERTICAL
45.520000	26.60	-8.8	40.0	13.4	QP	100.0	0.00	VERTICAL
74.620000	33.70	-14.8	40.0	6.3	QP	100.0	191.00	VERTICAL
144.460000	24.40	-13.9	43.5	19.1	QP	100.0	191.00	VERTICAL
544.100000	29.10	-0.9	46.0	16.9	QP	100.0	292.00	VERTICAL
934.040000	37.60	7.1	46.0	8.4	QP	100.0	127.00	VERTICAL

Polarization:

Horizontal

**MEASUREMENT RESULT: "GM1710196158_red"**

10/20/2017 12:12AM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
45.520000	22.70	-8.8	40.0	17.3	QP	300.0	213.00	HORIZONTAL
59.100000	22.80	-9.8	40.0	17.2	QP	300.0	190.00	HORIZONTAL
130.880000	27.00	-13.4	43.5	16.5	QP	300.0	103.00	HORIZONTAL
214.300000	22.00	-10.3	43.5	21.5	QP	100.0	277.00	HORIZONTAL
540.220000	28.90	-1.0	46.0	17.1	QP	100.0	76.00	HORIZONTAL
941.800000	38.50	7.2	46.0	7.5	QP	300.0	13.00	HORIZONTAL

➤ Above 1 GHz

CH00									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1495.10	48.31	25.80	5.27	36.58	42.80	74.00	-31.20	Vertical	Peak
2761.20	42.72	28.10	7.28	38.26	39.84	74.00	-34.16	Vertical	Peak
3625.67	39.67	29.30	8.30	38.26	39.01	74.00	-34.99	Vertical	Peak
4809.50	36.20	31.58	9.55	36.93	40.40	74.00	-33.60	Vertical	Peak
1724.17	46.52	25.25	5.81	36.98	40.60	74.00	-33.40	Horizontal	Peak
2987.92	46.01	28.59	7.47	38.24	43.83	74.00	-30.17	Horizontal	Peak
4809.50	41.76	31.58	9.55	36.93	45.96	74.00	-28.04	Horizontal	Peak
7209.02	37.52	36.21	11.87	35.07	50.53	74.00	-23.47	Horizontal	Peak

CH19									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1044.22	47.37	25.34	4.31	36.65	40.37	74.00	-33.63	Vertical	Peak
1795.84	46.73	25.39	5.95	37.13	40.94	74.00	-33.06	Vertical	Peak
2972.75	46.17	28.57	7.47	38.25	43.96	74.00	-30.04	Vertical	Peak
4996.69	38.84	31.50	9.67	36.41	43.60	74.00	-30.40	Vertical	Peak
1786.72	43.36	25.37	5.93	37.11	37.55	74.00	-36.45	Horizontal	Peak
3873.75	38.88	29.67	8.60	38.19	38.96	74.00	-35.04	Horizontal	Peak
4883.52	37.73	31.43	9.59	36.73	42.02	74.00	-31.98	Horizontal	Peak
7319.96	36.92	36.30	11.99	34.92	50.29	74.00	-23.71	Horizontal	Peak

CH39									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1498.91	44.90	25.80	5.28	36.59	39.39	74.00	-34.61	Vertical	Peak
3200.50	41.15	28.80	7.72	38.20	39.47	74.00	-34.53	Vertical	Peak
4958.68	39.41	31.46	9.64	36.52	43.99	74.00	-30.01	Vertical	Peak
7451.57	36.82	36.20	12.24	34.86	50.40	74.00	-23.60	Vertical	Peak
1487.51	44.51	25.81	5.25	36.57	39.00	74.00	-35.00	Horizontal	Peak
2097.51	42.33	26.69	6.35	37.32	38.05	74.00	-35.95	Horizontal	Peak
3283.02	45.99	28.30	7.82	38.35	43.76	74.00	-30.24	Horizontal	Peak
4958.68	43.11	31.46	9.64	36.52	47.69	74.00	-26.31	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit (54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.


6. TEST SETUP PHOTOS

Conducted Emissions (AC Mains)




Radiated Emissions







7. EXTERNAL AND INTERNAL PHOTOS


External photos of the EUT















Internal photos of the EUT



.....End of Report.....