



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 449-822
Tel: +82-31-323-6008 Fax: +82-31-323-6010
<http://www.ltalab.com>



Dates of Tests : May 7 ~ 19, 2010 2010
Test Report S/N: LR500191005B
Test Site : LTA CO., LTD

CERTIFICATION OF COMPLIANCE

FCC ID.

XBQ-N5

APPLICANT

YUKYUNG TECHNOLOGIES INC.

Equipment Class	:	Part 15 Spread Spectrum Transmitter (DSS)
Manufacturing Description	:	MID(MOBILE INTERNET DEVICE)
Manufacturer	:	YUKYUNG TECHNOLOGIES INC.
Model name	:	N5
Test Device Serial No.:	:	Identical prototype
Rule Part(s)	:	FCC Part 15.247 Subpart C; ANSI C-63.4-2003
Frequency Range	:	2402 ~ 2480MHz
RF power	:	Max 3.17dBm - Conducted
Data of issue	:	May 24, 2010

This test report is issued under the authority of:

Kyung-Taek LEE, Technical Manager

The test was supervised by:

Hyun-Chae You, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. This report must not be used by the applicant to claim product endorsement by any agency.



NVLAP LAB Code.: 200723-0

TABLE OF CONTENTS

1. GENERAL INFORMATION'S	3
2. INFORMATION'S ABOUT TEST ITEM	4
3. TEST REPORT	5
3.1 SUMMARY OF TESTS	5
3.2 TECHNICAL CHARACTERISTICS TEST	6
3.2.1 CARRIER FREQUENCY SEPARATION	6
3.2.2 NUMBER OF HOPPING FREQUENCIES	8
3.2.3 20 dB BANDWIDTH	10
3.2.4 TIME OF OCCUPANCY (Dwell Time)	17
3.2.5 TRANSMITTER OUTPUT POWER	22
3.2.6 BAND – EDGE & SPURIOUS	26
3.2.7 FIELD STRENGTH OF HARMONICS	32
3.2.8 AC CONDUCTED EMISSIONS	36
 APPENDIX	
APPENDIX TEST EQUIPMENT USED FOR TESTS	41

1. General information's

1-1 Test Performed

Company name : LTA Co., Ltd.
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2010-09-30	ECT accredited Lab.
RRL	KOREA	KR0049	2011-06-20	EMC accredited Lab.
FCC	U.S.A	610755	2011-04-22	FCC filing
VCCI	JAPAN	R2133, C2307	2011-06-21	VCCI registration
IC	CANADA	IC5799	2012-05-14	IC filing

2. Information's about test item

2-1 Client & Manufacturer

Company name : YUKYUNG TECHNOLOGIES INC.
 Address : 200-11, Anyang-Dong, Manan-Ku, Anyang-Si, Kyunggi-Do, Korea
 Tel / Fax : TEL No : +82-31-463-6906 / FAX No : +82-31-445-5995

2-2 Equipment Under Test (EUT)

Trade name : MID(MOBILE INTERNET DEVICE)
 FCC ID : XBQ-N5
 Model name : N5
 Serial number : Identical prototype
 Date of receipt : May 7, 2010
 EUT condition : Pre-production, not damaged
 Antenna type : Chip antenna with Max. 2.0 dBi gain
 Frequency Range : 2402 ~ 2480MHz
 RF output power : Max 3.17dBm - Conducted
 Number of channels : 79
 Channel spacing : 1MHz
 Channel Access Protocol : Frequency Hopping Spread Spectrum (FHSS)
 Type of Modulation : Basic Mode(GFSK), EDR Mode(Pi/4 DQPSK, 8DPSK)
 Power Source for Batt. : Battery Pack: 3.7V (Polymer Lithium Ion Battery)
 Power Source for Adaptor. : Input: 100-240VAC, 0.4A Output: 5.0VDC, 3A

2-3 Tested frequency

	LOW	MID	HIGH
Frequency (MHz)	2402	2441	2480

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
PC	HP Compaq dx2200	CNG6500RWK	HP
MONITOR	HPL1710	CNC816QH92	HP
Keyboard	SK-8115	68A-04Q6	DELL
Mouse	MO56UOA	F0J00NOL	DELL
PRINTER	STYLUS C65	N/A	EPSON
EARPHONE	N/A	N/A	N/A
SD CARD	N/A	N/A	SAN DISK
USB Memories	UM4	902RLRZN18670	LG

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	> 15 hops		C
15.247(a)	20 dB Bandwidth 99% Bandwidth	> 1.5 MHz		C
15.247	Dwell Time	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 250 mWatt		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.249 / 15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)	Radiated	C
15.109	Field Strength	-		C
15.207 / 15.107	AC Conducted Emissions	EN 55022	Line Conducted	C
15.203	Antenna requirement	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

→ Antenna Requirement

The YUKYUNG TECHNOLOGIES INC. FCC ID: XBQ-N5 unit complies with the requirement of §15.203. The antenna is connected to inside of EUT. And type is Chip antenna.

The sample was tested according to the following specification:

FCC Parts 15.247; ANSI C-63.4-2003

3.2 Transmitter requirements

3.2.1 Carrier Frequency Separation

Procedure:

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 10 kHz (1% of the span or more) Sweep = auto

VBW = 10 kHz Detector function = peak

Trace = max hold

Measurement Data:

Test Results	
Carrier Frequency Separation (MHz)	Result
0.99	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of 20dB bandwidth of the hopping channel, whichever is greater.

Measurement Setup





Figure 1: Measurement setup for the carrier frequency separation



Carrier Frequency Separation
Basic Mode



EDR Mode



Number of Hopping Frequencies



3.2.3 20 dB Bandwidth

Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 3 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 30 kHz

Sweep = auto

VBW = 30 kHz (VBW $\geq$ RBW)

Detector function = peak

Trace = max hold

dB/Div = 5dB

Measurement Data: Basic Mode

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20dB Bandwidth	99% Bandwidth
2402	0	0.97	0.91
2441	39	0.99	0.91
2480	78	0.99	0.90

Measurement Data: EDR Mode

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20dB Bandwidth	99% Bandwidth
2402	0	1.28	1.19
2441	39	1.30	1.19
2480	78	1.29	1.18

- See next pages for actual measured spectrum plots.


Minimum Standard:

N/A

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Channel 1 of basic mode
20 dB Bandwidth



99% Bandwidth



Channel 2 of basic mode
20 dB Bandwidth



99% Bandwidth



Channel 3 of basic mode
20 dB Bandwidth



99% Bandwidth




Channel 1 at EDR mode
20 dB Bandwidth




99% Bandwidth



Channel 2 at EDR mode
20 dB Bandwidth




99% Bandwidth



Channel 3 at EDR mode
20 dB Bandwidth



99% Bandwidth



3.2.4 Time of Occupancy (Dwell Time)

Procedure:

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz

VBW = 1 MHz (VBW $\geq$ RBW)

Trace = max hold

Detector function = peak

Measurement Data:

Mode	Number of transmission in a 31.6s (79Hopping*0.4)	Length of Transmission Time (msec)	Result (msec)	Limit (msec)
DH1	31(Times / 3sec) *10.533 = 326.52	0.528	172.4	400
DH3	15(Times / 3sec) *10.533 = 158.00	1.762	278.4	400
DH5	10(Times / 3sec) *10.533 = 105.33	3.045	320.7	400
EDR 3Mbps DH5	10(Times / 3sec) *10.533 = 105.33	3.049	321.2	400



- See next pages for actual measured spectrum plots.
- dwell time = {(number of hopping per second / number of slot) x duration time per channel} x 0.4 ms

Minimum Standard:



0.4 seconds within a 30 second period per any frequency



Measurement Setup


Same as the Chapter 3.2.1 (Figure 1)

DH1 at basic mode

DH3 at basic mode



DH5 at basic mode

DH5 at EDR mode with 3Mbps

3.2.5 Transmitter Output Power

Procedure:

The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 20 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 3 MHz (greater than the 20dB bandwidth of the emission being measured)

VBW = 3 MHz (VBW $\geq$ RBW)

Detector function = peak

Trace = max hold

Sweep = auto

Measurement Data: Basic Mode

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	3.17	2.07	Complies
2441	39	2.56	1.80	Complies
2480	78	1.92	1.56	Complies

Measurement Data: EDR Mode

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	1.64	1.46	Complies
2441	39	0.94	1.24	Complies
2480	78	0.10	1.02	Complies


- See next pages for actual measured spectrum plots.

Minimum Standard:	< 250 mW
-------------------	----------


Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Channel 1
Basic mode




EDR mode




Channel 2


Basic mode




EDR mode



Channel 3
Basic mode



EDR mode



3.2.6 Band Edge

Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

VBW = 100 kHz

Span = 10 MHz

Detector function = peak

Trace = max hold

Sweep = auto

Measurement Data: Complies

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

Minimum Standard:	> 20 dBc
--------------------------	----------

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Lower edge



Band-edges in the restricted band 2310-2390 MHz measurement


Frequency	Reading [dBuV/m]		Pol.	Correction			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
				Factor								
[MHz]	AV / Peak			Antenna	Amp. Gain	Cable	AV / Peak		AV / Peak		AV / Peak	
2390	44.19	57.38	V	26.0	36.5	8.2	54.0	74.0	41.9	55.1	12.1	18.9

Band-edges in the restricted band 2483.5-2500 MHz measurement


Frequency	Reading		Pol.	Correction			Limits		Result		Margin	
	[dBuV/m]			Factor			[dBuV/m]		[dBuV/m]		[dB]	
[MHz]	AV / Peak			Antenna	Amp. Gain	Cable	AV / Peak		AV / Peak		AV / Peak	
2483.5	52.08	66.66	V	26.0	36.5	8.2	54.0	74.0	49.8	64.4	4.2	9.6

Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented.


Unwanted Emission – Low channel
Frequency Range = 30 MHz ~ 26.5 GHz



Unwanted Emission – Middle channel
Frequency Range = 30 MHz ~ 26.5 GHz



Unwanted Emission – High channel
Frequency Range = 30 MHz ~ 26.5 GHz



3.2.7 Field Strength of Harmonics

Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10th harmonic.

RBW = 100 kHz (30MHz ~ 1 GHz)

= 1 MHz (1 GHz ~ 10th harmonic)

Span = 100 MHz

Trace = max hold

Peak:VBW $\geq$ RBW

Average:VBW=10Hz

Detector function = Peak and Average

Sweep = auto

Measurement Data: Complies

- Refer to the next page.
- No other emissions were detected at a level greater than 10dB below limit.
- The three antennas were used with this EUT during the Testing.

Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

Measurement Data:

Frequency [MHz]	Reading [dBuV/m] AV / Peak		Pol.	Correction Factor Antenna Amp.Gain Cable			Limits [dBuV/m] AV / Peak		Result [dBuV/m] AV / Peak		Margin [dB] AV / Peak	
4804	36.5	40.8	H	31.4	36.0	8.7	54.0	74.0	40.6	44.9	13.4	29.1
Frequency [MHz]	Reading [dBuV/m] AV / Peak		Pol.	Correction Factor Antenna Amp.Gain Cable			Limits [dBuV/m] AV / Peak		Result [dBuV/m] AV / Peak		Margin [dB] AV / Peak	
4882.00	40.5	43.2	H	31.4	36.0	8.7	54.0	74.0	44.6	47.3	9.4	26.7
Frequency [MHz]	Reading [dBuV/m] AV / Peak		Pol.	Correction Factor Antenna Amp.Gain Cable			Limits [dBuV/m] AV / Peak		Result [dBuV/m] AV / Peak		Margin [dB] AV / Peak	
4960	39.1	43.0	H	31.4	36.0	8.7	54.0	74.0	43.2	47.1	10.8	26.9

No other emissions were detected at a level greater than 20dB below limit.

Radiated Emissions – PC Mode

243 Jubug-ni, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel :+82-31-3236008,9
Fax:+82-31-3236010

EUT/Model No.: N5

TEST MODE: PC mode


Temp Humi : 15 / 31

Tested by: KIM.K.I

Data: 41

Level (dBuV/m)

Date: 2010-05-07



	Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
	MHz	dBuV/m	dB/m	dBuV/m	QP	dB	cm	deg	
1	108.64	39.59	-15.02	24.57	33.00	8.43	250	136	HORIZONTAL
2	168.12	37.50	-11.68	25.82	33.00	7.18	400	127	HORIZONTAL
3	215.91	35.90	-11.73	24.17	33.00	8.83	358	214	HORIZONTAL
4	263.82	41.51	-9.75	31.76	35.60	3.84	308	322	HORIZONTAL
5	694.00	33.34	-1.11	32.23	35.60	3.37	186	75	HORIZONTAL
6	801.24	31.80	0.81	32.61	35.60	2.99	100	73	VERTICAL


Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions – BT Mode



243 Jubug-ni, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel :+82-31-3236008,9
Fax:+82-31-3236010

EUT/Model No.: N5 TEST MODE: BT mode
Temp Humi : 15 / 31 Tested by: KIM.K.I



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	132.16	41.50	-12.86	28.64	33.00	4.36	302	98 HORIZONTAL
2	168.50	40.60	-11.68	28.92	33.00	4.08	400	132 HORIZONTAL
3	215.82	35.60	-11.73	23.87	33.00	9.13	289	148 HORIZONTAL
4	264.25	41.20	-9.73	31.47	35.60	4.13	350	183 HORIZONTAL
5	765.03	30.80	0.19	30.99	35.60	4.61	341	29 HORIZONTAL
6	801.20	30.90	0.81	31.71	35.60	3.89	100	261 VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

3.2.8 AC Conducted Emissions

Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

Measurement Data: Complies

- See next pages for actual measured spectrum plots.
- No emissions were detected at a level greater than 10dB below limit.

Minimum Standard: FCC Part 15.207(a)/EN 55022

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50


* Decreases with the logarithm of the frequency

AC Conducted Emissions – PC– Line

243 Jubug-ni, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel +82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No.:	N5	Phase	: LINE
Test Mode	: PC mode	Test Power	: 120 / 60
Temp./Humi.	: 21 / 35	Test Engineer	: PARK H W

Data: 84 File: C:\Conducted Data\2010\LTA_Conduction_1004_1.EMI (160) Date: 05-10-2010
Level (dBuV)




Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV		QP	AV	QP	AV	QP	AV
	dBuV	dBuV	dB	dBuV	dBuV	dBuV	dBuV	dB	dB
0.180	29.19	22.09	9.65	38.84	31.74	64.49	54.49	25.64	22.74
0.893	20.55	18.65	9.78	30.33	28.43	56.00	46.00	25.67	17.57
1.192	20.75	18.65	9.79	30.54	28.44	56.00	46.00	25.46	17.56
1.550	20.05	16.65	9.80	29.85	26.45	56.00	46.00	26.15	19.55
3.100	22.24	18.14	9.85	32.09	27.99	56.00	46.00	23.91	18.01
3.275	23.24	18.44	9.86	33.10	28.30	56.00	46.00	22.90	17.70

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

AC Conducted Emissions – PC – Neutral

243 Jibug-ni, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel +82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No. : N5	Phase : NEUTRAL
Test Mode : PC mode	Test Power : 120 / 60
Temp./Humi. : 21 / 35	Test Engineer : PARK H W




Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
0.179	29.19	19.29	9.66	38.85	28.95	64.53	54.53	25.68	25.58
0.534	19.15	14.05	9.68	28.83	23.73	56.00	46.00	27.17	22.27
0.654	18.84	13.54	9.75	28.59	23.29	56.00	46.00	27.41	22.71
0.776	15.44	12.74	9.77	25.22	22.52	56.00	46.00	30.78	23.48
3.101	23.24	17.94	9.85	33.09	27.79	56.00	46.00	22.91	18.21
3.280	21.74	16.84	9.86	31.60	26.70	56.00	46.00	24.40	19.30

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

AC Conducted Emissions – BLUETOOTH – Line

243 Jibug-ni, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel +82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No. : N5	Phase : LINE
Test Mode : BT mode	Test Power : 120 / 60
Temp./Humi. : 21 / 35	Test Engineer : PARK H W



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
0.180	30.49	22.59	9.65	40.14	32.24	64.49	54.49	24.34	22.24
0.479	19.95	17.05	9.67	29.62	26.72	56.36	46.36	26.74	19.64
0.534	20.65	16.75	9.69	30.33	26.43	56.00	46.00	25.67	19.57
2.924	20.74	16.74	9.84	30.59	26.59	56.00	46.00	25.41	19.41
3.045	22.64	17.24	9.85	32.49	27.09	56.00	46.00	23.51	18.91
3.405	23.74	16.04	9.86	33.60	25.90	56.00	46.00	22.40	20.10


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

AC Conducted Emissions – BLUETOOTH – Neutral



243 Jubug-ni, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel +82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No.:	N5	Phase	: NEUTRAL
Test Mode	: BT mode	Test Power	: 120 / 60
Temp./Humi.	: 21 / 35	Test Engineer	: PARK H W



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
0.152	20.50	12.90	9.66	30.16	22.56	65.89	55.89	35.73	33.33
0.175	27.69	18.09	9.66	37.35	27.75	64.72	54.72	27.37	26.97
0.537	18.24	15.04	9.68	27.93	24.73	56.00	46.00	28.07	21.27
0.652	18.94	13.64	9.75	28.69	23.39	56.00	46.00	27.31	22.61
3.102	21.74	16.54	9.85	31.59	26.39	56.00	46.00	24.41	19.61
3.279	22.04	16.44	9.86	31.90	26.30	56.00	46.00	24.10	19.70

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

APPENDIX

TEST EQUIPMENT USED FOR TESTS

	Description	Model No.	Serial No.	Manufacturer	Next Cal. Date
1	Spectrum Analyzer	FSV-30	100757	R&S	Feb-11
2	Spectrum Analyzer	8563E	3425A02505	HP	Mar-11
3	Spectrum Analyzer	8594E	3710A04074	HP	Oct-10
4	Signal Generator	8648C	3623A02597	HP	Mar-11
5	Signal Generator	83711B	US34490456	HP	Mar-11
6	Attenuator (3dB)	8491A	37822	HP	Oct-10
7	Attenuator (10dB)	8491A	63196	HP	Oct-10
8	Attenuator (30dB)	8498A	1801A06689	HP	Oct-10
9	EMI Test Receiver	ESVD	843748/001	R&S	Mar-11
10	Horn Antenna(18 ~ 40GHz)	SAS-574	154	Schwarzbeck	Nov-10
11	Horn Antenna(18 ~ 40GHz)	SAS-574	155	Schwarzbeck	Nov-10
12	RF Amplifier	8447D	2949A02670	HP	Oct-10
13	RF Amplifier	8449B	3008A02126	HP	Mar-11
14	Test Receiver	ESHS10	828404/009	R&S	Mar-11
15	TRILOG Antenna	VULB 9160	9160-3212	SCHWARZBECK	Apr-11
16	Log.-Per. Antenna	VULP 9118	9118 A 401	SCHWARZBECK	Apr-11
17	Biconical Antenna	BBA 9106	VHA 9103-2315	SCHWARZBECK	Apr-11
18	Horn Antenna	3115	00055005	ETS LINDGREN	Mar-11
19	Horn Antenna	BBHA 9120D	9120D122	SCHWARZBECK	Dec-11
20	Dipole Antenna	VHA9103	2116	SCHWARZBECK	Nov-10
21	Dipole Antenna	VHA9103	2117	SCHWARZBECK	Nov-10
22	Dipole Antenna	VHA9105	2261	SCHWARZBECK	Nov-10
23	Dipole Antenna	VHA9105	2262	SCHWARZBECK	Nov-10
24	Hygro-Thermograph	THB-36	0041557-01	ISUZU	Mar-11
25	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-
26	RF Switch	MP59B	6200414971	ANRITSU	-
27	Power Divider	11636A	6243	HP	Oct-10
28	DC Power Supply	6622A	3448A03079	HP	Oct-10
29	Frequency Counter	5342A	2826A12411	HP	Mar-11
30	Power Meter	EPM-441A	GB32481702	HP	Mar-11
31	Power Sensor	8481A	2702A64048	HP	Mar-11
32	Audio Analyzer	8903B	3729A18901	HP	Oct-10
33	Modulation Analyzer	8901B	3749A05878	HP	Oct-10
34	TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	Oct-10
35	LOOP-ANTENNA	FMZB 1516	151602/94	SCHWARZBECK	Mar-11
36	Stop Watch	HS-3	601Q09R	CASIO	Mar-11
37	LISN	ENV216	100408	R&S	Oct-10
38	UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	May-12