

REV.	MARK	ECR/ECN NO.	DATE	UPDATE DESCRIPTION	SIGNATURE
0.0	N/A	N/A	2013.12.21	First Release	Cun
0.1			2014.03.04	update PTT label	Cun

Factory ID list

=====

(100544-836) FUHONG PRECISION COMPONENT (BAC GIANG) LTD
DINH TRAM INDUSTRY PARK
VIET YEN DISTRICT VIET NAM

Factory ID: Y

=====

(100568-850) NANNING FUGUI PRECISION INDUSTRIAL CO LTD
18 ZONGBU RD
NEW & HIGH-TECH INDUSTRIAL
DEVELOPMENT ZONE
NANNING GUANGXI CHINA

Factory ID: N

=====

(128685-001) AMBIT MICROSYSTEMS (SHANGHAI) LTD
1925 NAN-LE RD
SONGJIANG EXPORT PROCESSING ZONE
SHANGHAI
201613 CHINA

Factory ID: E

=====

(223850-001) HONG FU JIN PRECISION INDUSTRY
(SHENZHEN) CO LTD
10TH YOUSONG INDUSTRIAL DISTRICT
2ND DONGHUAN RD NO 2
BAO'AN LONGHUA TOWN
SHENZHEN 518109 GUANGDONG CHINA


Factory ID: F

=====




Vendor code


PTT label 500.01679.005 42*40mm



Scale:1/1
Vendor Provide



packaging style



"X": UL Factory ID,
please see the list, if the manufacturer
is not in the list, please confirm with
PM or Compliance Engineer.
Foxconn printing
Arial, 5pt

Foxconn printing
Arial, 7pt

- NOTES:
- 1.Material: #50 Mylar + 25# PET(matte, printable)
 - 2.Adhesive: 壓花膠
 - 3.Adhesive thickness :
50#Mylar: 0.030+/-0.003mm
25#PET: 0.018+/-0.003mm
 - 4.Printing Color:Black
 - 5.Background: White
 - 6.Liner:Glassine release paper
 - 7.Packaging Style: Reel
 - 8.The part must be RoHS compliant
 - 9.Mark UL logo and vender code on out packing.
 - 10.Adhesion to steel(180°磨鋼粘著力): >=1.22 Kg/inch
 - 11.Initial Tack(初粘力): >=6 #/boll
 - 12.Holding power(保持力):>=10 hr/Kg/20mm²

MATERIAL (SPEC.)										SCALE	FOXCONN			
FINISH										SHEET 1/1	HON HAI PRECISION IND. CO., LTD. CNSBG			
Select								*		UNIT	PART NAME			
Dim. Tol.	A	B	C	EPS	EPE	BAG	CTN	Label	USR	MM	PTT Label			
0~6	0.05	0.05	0.10					0.20						
6~30	0.10	0.15	0.20	0.50	0.50	3.00		0.20		SIZE	MODEL		PART NO.	DESIGNED
30~120	0.15	0.20	0.30	0.50	0.50	5.00	2.00	0.25		A4	U10C091.81		500.01679.005	Zhou Cun
120~300	0.20	0.30	0.40	1.00	1.00	10.00	3.00	0.30						
300~450	0.25	0.40	0.50	2.00	2.00	15.00	5.00	0.50						
450~600	0.30	0.50	0.60	3.00	3.00	20.00	5.00	0.80			CUSTOMER MODEL		CUSTOMER PART NO.	APPROVED
DRAFT TOLERANCE				±0.2°		CRITICAL DIM. MARK			*					Yanli Yu