

TEST REPORT

Applicant: Hansong(Nanjing) Technology Ltd.
Address: 8th Kangping Road Jiangning Economy and Technology Development Zone, Nanjing, 211106, China.
Equipment Type: Bluetooth Module
Model Name: HSBT5181
Brand Name: Platin
FCC ID: XCO-HSBT5181
ISED Number: 7756A-HSBT5181
Test Standard: 47 CFR Part 15 Subpart C
RSS-Gen Issue 5
RSS-247 Issue 4
(refer to section 3.1)
Sample Arrival Date: Sep. 18, 2025
Test Date: Sep. 26, 2025 - Oct. 15, 2025
Date of Issue: Nov. 13, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** He Yuyang**Checked by:** Ye Hongji**Approved by:** Sunny Zou
(Technical Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Nov. 13, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information.....	5
2.3	General Description for Equipment under Test (EUT).....	5
2.4	Technical Information	6
3	SUMMARY OF TEST RESULTS	8
3.1	Test Standards	8
3.2	Test Verdict	9
4	GENERAL TEST CONFIGURATIONS	10
4.1	Test Environments.....	10
4.2	Test Equipment List.....	10
4.3	Test Software List.....	10
4.4	Measurement Uncertainty.....	11
4.5	Description of Test Setup	11
4.6	Measurement Results Explanation Example.....	14
5	TEST ITEMS	15
5.1	Antenna Requirements	15
5.2	Output Power	16
5.3	Occupied Bandwidth.....	18
5.4	Conducted Spurious Emission.....	19
5.5	Band Edge (Authorized-band band-edge).....	21

5.6	Conducted Emission.....	23
5.7	Radiated Spurious Emission.....	24
5.8	Band Edge (Restricted-band band-edge).....	29
5.9	Power Spectral density (PSD)	30
ANNEX A	TEST RESULT	31
A.1	Output Power, E.I.R.P	31
A.2	Occupied Bandwidth.....	34
A.3	Conducted Spurious Emissions	39
A.4	Band Edge (Authorized-band band-edge).....	46
A.5	Conducted Emissions	49
A.6	Radiated Spurious Emission.....	60
A.7	Band Edge (Restricted-band band-edge).....	80
A.8	Power Spectral Density (PSD).....	82
ANNEX B	TEST SETUP PHOTOS	85
ANNEX C	EUT EXTERNAL PHOTOS.....	85
ANNEX D	EUT INTERNAL PHOTOS.....	85

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Hansong(Nanjing) Technology Ltd.
Address	8th Kangping Road Jiangning Economy and Technology Development Zone, Nanjing, 211106, China.

2.2 Manufacturer Information

Manufacturer	Hansong(Nanjing) Technology Ltd.
Address	8th Kangping Road Jiangning Economy and Technology Development Zone, Nanjing, 211106, China.

2.3 General Description for Equipment under Test (EUT)

EUT Name	Bluetooth Module
Model Name Under Test	HSBT5181
Series Model Name	N/A
Description of Model name differentiation	N/A
Serial Number	H23X518100001
Hardware Version	V1.0
Software Version	V1.0
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE)
-----------------------------------	------------------------

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology		DTS
Modulation Type		GFSK
Product Type		☒ Mobile ☐ Portable ☐ Fix Location
Transfer Rate		1 Mbps, 2 Mbps
Frequency Range		The frequency range used is 2400 MHz to 2483.5 MHz.
Number of Channel		40 (at intervals of 2 MHz) ^{Note 1}
Tested Channel		1 Mbps: 0 (2402 MHz), 19 (2440 MHz), 39 (2480 MHz) 2 Mbps: 1 (2404 MHz), 19 (2440 MHz), 38 (2478 MHz)
Antenna Type		FPC Antenna
		PCB-onboard Antenna
		PCB-External Antenna
		Dipole Antenna
		Copper Tube Antenna
Antenna Gain	FPC Antenna	3.43 dBi
	PCB-onboard Antenna	1.97 dBi
	PCB-External Antenna	4.20 dBi
	Dipole Antenna	2.00 dBi
	Copper Tube Antenna	3.20 dBi
Antenna Impedance		50Ω
Antenna System (MIMO Smart Antenna)		N/A
Note 1: 2 Mbps does not support Channel 0, Channel 12, and Channel 39.		

All channel was listed on the following table:

BLE 1M:

Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

BLE 2M:

Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)
\	\	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	\	\	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	\	\

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional radiators of radio frequency equipment
2	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
3	RSS-247 Issue 4	Digital Transmission Systems, Frequency Hopping Systems and Licence Exempt Local Area Network Devices in 902-928 MHz, 2400-2483.5 MHz, 5150-5350 MHz, and 5470-5895 MHz bands
4	ANSI C63.10-2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
5	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Test Verdict

No.	Description	FCC Part No.	ISED Part No.	Channel	Test Result	Verdict
1	Antenna Requirement	15.203	RSS-247, 5.4 (f)	N/A	--	Pass ^{Note1}
2	Output Power	15.247(b)	RSS-247, 5.4 (d)	Low/Middle/High	ANNEX A.1	Pass
3	Occupied Bandwidth	15.247(a)	RSS-GEN, 6.7; RSS-247, 5.2 (a)	Low/Middle/High	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	RSS-247, 5.5	Low/Middle/High	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.247(d)	RSS-247, 5.5;	Low/High	ANNEX A.4	Pass
6	Conducted Emission	15.207	RSS-GEN, 8.8	Low/Middle/High	ANNEX A.5	Pass
7	Radiated Spurious Emission	15.209 15.247(d)	RSS-247, 5.5	Low/Middle/High	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	RSS-247, 5.5	Low/High	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247(e)	RSS-247, 5.2 (b)	Low/Middle/High	ANNEX A.8	Pass
10	Receiver Spurious Emissions	--	RSS-Gen, 7.4	--	N/A	N/A ^{Note2}

Note 1: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note 2: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% to 67%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+20.8℃ to +25.1℃
Working Voltage of the EUT	NV (Normal Voltage)	5.0V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY46471071	2025.06.16	2026.06.15
Spectrum Analyzer	KEYSIGHT	N9020A	MY50531259	2025.06.16	2026.06.15
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	02460	2024.05.16	2027.05.15
Test Antenna-Horn	A-INFO	LB-180400KF	J211060273	2024.06.15	2027.06.14
Anechoic Chamber	RAINFORD	9m*6m*6m	140	2024.07.28	2027.07.27
Amplifier	COM-MV	LSCX_LNA1-12G-01	7210214	2025.06.17	2026.06.16
Amplifier	COM-MV	XKu_LNA7-18G-01	7210209	2025.06.17	2026.06.16
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2025.06.16	2026.06.15
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9168	9168-01162	2023.08.04	2026.08.03
Test Antenna-Loop	SCHWARZBECK	FMZB 1519	1519-037	2024.01.23	2027.01.22
Amplifier	COM-MV	ZT30-1000M	B2018054558	2024.11.28	2025.11.27
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	130	2024.07.13	2027.07.12
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2025.06.16	2026.06.15
LISN	SCHWARZBECK	NSLK 8127	8127-687	2025.04.29	2026.04.28
Shielded Enclosure	YiHeng Electronic Co., Ltd	3.5m*3.1m*2.8m	112	2025.02.14	2028.02.13

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V22.930	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.8°C
Humidity	4%


4.5 Description of Test Setup

4.5.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.5.2 For AC Power Supply Port Test




(Diagram 2)

4.5.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.5.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.5.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.6 Measurement Results Explanation Example

4.6.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.6.2 For radiated band edges and spurious emission test:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (f)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

RSS-247, 5.4 (d)

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(5), the e.i.r.p. shall not exceed 4 W.

5.2.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

a) Maximum peak conducted output power

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Set the RBW $\geq$ DTS bandwidth.

Set VBW $\geq 3 \times$ RBW.

Set span $\geq 3 \times$ RBW

Sweep time = auto couple.

Detector = peak.

Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

b) Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set RBW $\geq$ OBW if possible; otherwise, set RBW to the largest available value.

Set VBW $\geq$ RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 Occupied Bandwidth

5.3.1 Limit

FCC §15.247(a); RSS-247, 5.2 (a); RSS-GEN, 6.7

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement:

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement:

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.5.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.9; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dB $\mu\text{V/m}$) = $20 \times \log[\text{Field Strength } (\mu\text{V/m})]$.
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dB $\mu\text{V/m}$ @3m (AV) and 74dB $\mu\text{V/m}$ @3m (PK).

5.7.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements

for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands:

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure:

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW $\geq 3 \times$ RBW.

- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction:

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x , of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW $\geq 3 \times$ RBW.
- e) Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.

2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.

3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain:

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test:

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the

Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.10; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(e); RSS-247, 5.2 (b)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of Section 5.4(4), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

5.9.2 Test Setup

See section 4.5.1 (Diagram 1) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT

A.1 Output Power, E.I.R.P

Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	GFSK (BLE 1Mbps)		dBm	mW	
	dBm	mW			
Low Channel	6.85	4.85	30	1000	Pass
Middle Channel	6.43	4.39			Pass
High Channel	5.69	3.70			Pass

Channel	Measured Output Peak Power		Limit		Verdict
	GFSK (BLE 2Mbps)		dBm	mW	
	dBm	mW			
Low Channel	6.95	4.96	30	1000	Pass
Middle Channel	6.53	4.49			Pass
High Channel	5.85	3.84			Pass

E.I.R.P Test Data (For ISCED)

Channel	E.I.R.P		Limit		Verdict
	GFSK (BLE 1Mbps)		dBm	mW	
	dBm	mW			
Low Channel	10.28	10.68	36	4000	Pass
Middle Channel	9.86	9.68			Pass
High Channel	9.12	8.16			Pass

Channel	E.I.R.P		Limit		Verdict
	GFSK (BLE 2Mbps)		dBm	mW	
	dBm	mW			
Low Channel	10.38	10.92	36	4000	Pass
Middle Channel	9.96	9.90			Pass
High Channel	9.28	8.46			Pass

Test Plots

GFSK (BLE 1Mbps) LOW CHANNEL



GFSK (BLE 1Mbps) MIDDLE CHANNEL




GFSK (BLE 1Mbps) HIGH CHANNEL



GFSK (BLE 2Mbps) LOW CHANNEL



GFSK (BLE 2Mbps) MIDDLE CHANNEL



GFSK (BLE 2Mbps) HIGH CHANNEL



A.2 Occupied Bandwidth

Test Data

Test Mode	GFSK (BLE 1Mbps)		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (kHz)	6 dB Bandwidth Limits (kHz)
Low Channel	735.100	1029.500	≥500
Middle Channel	720.000	1046.300	≥500
High Channel	712.600	1042.500	≥500

Test Mode	GFSK (BLE 2Mbps)		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (kHz)	6 dB Bandwidth Limits (kHz)
Low Channel	1260.000	2.069	≥500
Middle Channel	1260.000	2.058	≥500
High Channel	1215.000	2.064	≥500

Test Plots

6 dB Bandwidth

GFSK (BLE 1Mbps) LOW CHANNEL



GFSK (BLE 1Mbps) MIDDLE CHANNEL



GFSK (BLE 1Mbps) HIGH CHANNEL



GFSK (BLE 2Mbps) LOW CHANNEL



GFSK (BLE 2Mbps) MIDDLE CHANNEL



GFSK (BLE 2Mbps) HIGH CHANNEL



99% Bandwidth

GFSK (BLE 1Mbps) LOW CHANNEL



GFSK (BLE 1Mbps) MIDDLE CHANNEL



GFSK (BLE 1Mbps) HIGH CHANNEL



GFSK (BLE 2Mbps) LOW CHANNEL



GFSK (BLE 2Mbps) MIDDLE CHANNEL



GFSK (BLE 2Mbps) HIGH CHANNEL



A.3 Conducted Spurious Emissions

Test Data

GFSK (BLE 1Mbps)				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-36.88	6.55	-13.45	Pass
Middle Channel	-36.21	6.22	-13.78	Pass
High Channel	-36.93	5.52	-14.48	Pass


GFSK (BLE 2Mbps)				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-36.85	6.49	-13.52	Pass
Middle Channel	-35.35	6.09	-13.91	Pass
High Channel	-35.76	5.49	-14.51	Pass

Test Plots


GFSK (BLE 1Mbps) LOW CHANNEL,
CARRIER LEVEL



GFSK (BLE 1Mbps) LOW CHANNEL,
SPURIOUS 30 MHz ~ 3 GHz




GFSK (BLE 1Mbps) LOW CHANNEL,
SPURIOUS 2 GHz ~ 25 GHz




GFSK (BLE 1Mbps) MIDDLE CHANNEL, CARRIER LEVEL



GFSK (BLE 1Mbps) MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK (BLE 1Mbps) MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




GFSK (BLE 1Mbps) HIGH CHANNEL, CARRIER LEVEL



GFSK (BLE 1Mbps) HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK (BLE 1Mbps) HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




GFSK (BLE 2Mbps) LOW CHANNEL, CARRIER LEVEL



GFSK (BLE 2Mbps) LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK (BLE 2Mbps) LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




GFSK (BLE 2Mbps) MIDDLE CHANNEL, CARRIER LEVEL



GFSK (BLE 2Mbps) MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK (BLE 2Mbps) MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




GFSK (BLE 2Mbps) HIGH CHANNEL, CARRIER LEVEL



GFSK (BLE 2Mbps) HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



GFSK (BLE 2Mbps) HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



A.4 Band Edge (Authorized-band band-edge)

Note: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Test Data

GFSK (BLE 1Mbps)				
Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-45.87	6.55	-13.45	Pass
High Channel	-48.49	5.52	-14.48	Pass


GFSK (BLE 2Mbps)				
Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-48.56	6.49	-13.52	Pass
High Channel	-49.25	5.49	-14.51	Pass

Test Plots

GFSK (BLE 1Mbps) LOW CHANNEL, CARRIER LEVEL




GFSK (BLE 1Mbps) LOW CHANNEL, BAND EDGE



GFSK (BLE 1Mbps) HIGH CHANNEL, CARRIER LEVEL



GFSK (BLE 1Mbps) HIGH CHANNEL, BAND EDGE



GFSK (BLE 2Mbps) LOW CHANNEL, CARRIER LEVEL



GFSK (BLE 2Mbps) LOW CHANNEL, BAND EDGE



GFSK (BLE 2Mbps) HIGH CHANNEL, CARRIER LEVEL



GFSK (BLE 2Mbps) HIGH CHANNEL, BAND EDGE



A.5 Conducted Emissions

Note ¹: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.

Note ²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.


Note ³: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

FPC Antenna

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.182	41.18	9.84	64.39	23.21	Peak	L	Pass
1**	0.182	25.71	9.84	54.39	28.68	AV	L	Pass
2	0.240	38.31	9.83	62.10	23.79	Peak	L	Pass
2**	0.240	25.83	9.83	52.10	26.27	AV	L	Pass
3	0.936	40.99	10.16	56.00	15.01	Peak	L	Pass
3**	0.936	35.26	10.16	46.00	10.74	AV	L	Pass
4	8.630	39.43	10.47	60.00	20.57	Peak	L	Pass
4**	8.630	27.92	10.47	50.00	22.08	AV	L	Pass
5	12.538	39.08	10.77	60.00	20.92	Peak	L	Pass
5**	12.538	27.28	10.77	50.00	22.72	AV	L	Pass
6	15.976	38.18	10.65	60.00	21.82	Peak	L	Pass
6**	15.976	25.22	10.65	50.00	24.78	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C




No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.166	41.51	9.85	65.16	23.65	Peak	N	Pass
1**	0.166	27.61	9.85	55.16	27.55	AV	N	Pass
2	0.240	39.04	9.83	62.10	23.06	Peak	N	Pass
2**	0.240	24.64	9.83	52.10	27.46	AV	N	Pass
3	0.936	41.83	10.16	56.00	14.17	Peak	N	Pass
3**	0.936	35.41	10.16	46.00	10.59	AV	N	Pass
4	1.254	37.25	10.51	56.00	18.75	Peak	N	Pass
4**	1.254	26.77	10.51	46.00	19.23	AV	N	Pass
5	2.048	37.04	10.54	56.00	18.96	Peak	N	Pass
5**	2.048	26.36	10.54	46.00	19.64	AV	N	Pass
6	3.654	38.01	10.43	56.00	17.99	Peak	N	Pass
6**	3.654	25.79	10.43	46.00	20.21	AV	N	Pass

PCB-onboard Antenna

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.190	39.80	9.84	64.04	24.24	Peak	L	Pass
1**	0.190	26.78	9.84	54.04	27.26	AV	L	Pass
2	0.304	38.79	9.90	60.13	21.34	Peak	L	Pass
2**	0.304	24.69	9.90	50.13	25.44	AV	L	Pass
3	0.362	38.56	10.77	58.68	20.12	Peak	L	Pass
3**	0.362	25.57	10.77	48.68	23.11	AV	L	Pass
4	0.970	41.01	10.17	56.00	14.99	Peak	L	Pass
4**	0.970	34.00	10.17	46.00	12.00	AV	L	Pass
5	4.718	36.92	10.18	56.00	19.08	Peak	L	Pass
5**	4.718	24.64	10.18	46.00	21.36	AV	L	Pass
6	8.118	36.27	10.21	60.00	23.73	Peak	L	Pass
6**	8.118	24.18	10.21	50.00	25.82	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C




No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.156	40.76	9.86	65.67	24.91	Peak	N	Pass
1**	0.156	27.63	9.86	55.67	28.04	AV	N	Pass
2	0.332	38.06	10.46	59.40	21.34	Peak	N	Pass
2**	0.332	24.83	10.46	49.40	24.57	AV	N	Pass
3	0.913	41.47	10.18	56.00	14.53	Peak	N	Pass
3**	0.913	36.22	10.18	46.00	9.78	AV	N	Pass
4	1.758	36.22	10.21	56.00	19.78	Peak	N	Pass
4**	1.758	24.42	10.21	46.00	21.58	AV	N	Pass
5	5.452	36.83	10.19	60.00	23.17	Peak	N	Pass
5**	5.452	25.40	10.19	50.00	24.60	AV	N	Pass
6	20.290	37.44	11.10	60.00	22.56	Peak	N	Pass
6**	20.290	25.24	11.10	50.00	24.76	AV	N	Pass

Dipole Antenna

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.176	43.44	9.85	64.67	21.23	Peak	L	Pass
1**	0.176	28.44	9.85	54.67	26.23	AV	L	Pass
2	0.228	38.85	9.83	62.52	23.67	Peak	L	Pass
2**	0.228	26.14	9.83	52.52	26.38	AV	L	Pass
3	0.368	37.05	10.74	58.55	21.50	Peak	L	Pass
3**	0.368	26.13	10.74	48.55	22.42	AV	L	Pass
4	0.930	41.79	10.17	56.00	14.21	Peak	L	Pass
4**	0.930	35.75	10.17	46.00	10.25	AV	L	Pass
5	2.834	37.29	9.97	56.00	18.71	Peak	L	Pass
5**	2.834	23.78	9.97	46.00	22.22	AV	L	Pass
6	9.006	39.50	10.54	60.00	20.50	Peak	L	Pass
6**	9.006	25.88	10.54	50.00	24.12	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C




No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.158	43.14	9.86	65.57	22.43	Peak	N	Pass
1**	0.158	27.13	9.86	55.57	28.44	AV	N	Pass
2	0.208	41.37	9.83	63.28	21.91	Peak	N	Pass
2**	0.208	26.31	9.83	53.28	26.97	AV	N	Pass
3	0.580	36.46	10.17	56.00	19.54	Peak	N	Pass
3**	0.580	25.64	10.17	46.00	20.36	AV	N	Pass
4	0.936	41.55	10.16	56.00	14.45	Peak	N	Pass
4**	0.936	34.39	10.16	46.00	11.61	AV	N	Pass
5	2.616	37.50	9.93	56.00	18.50	Peak	N	Pass
5**	2.616	24.62	9.93	46.00	21.38	AV	N	Pass
6	8.598	39.40	10.56	60.00	20.60	Peak	N	Pass
6**	8.598	29.91	10.56	50.00	20.09	AV	N	Pass

Copper Tube Antenna

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.192	40.86	9.84	63.95	23.09	Peak	L	Pass
1**	0.192	25.40	9.84	53.95	28.55	AV	L	Pass
2	0.930	42.54	10.17	56.00	13.46	Peak	L	Pass
2**	0.930	36.40	10.17	46.00	9.60	AV	L	Pass
3	1.906	38.20	10.71	56.00	17.80	Peak	L	Pass
3**	1.906	27.63	10.71	46.00	18.37	AV	L	Pass
4	3.588	37.14	10.39	56.00	18.86	Peak	L	Pass
4**	3.588	25.41	10.39	46.00	20.59	AV	L	Pass
5	8.574	39.69	10.51	60.00	20.31	Peak	L	Pass
5**	8.574	31.47	10.51	50.00	18.53	AV	L	Pass
6	24.382	38.31	10.86	60.00	21.69	Peak	L	Pass
6**	24.382	26.87	10.86	50.00	23.13	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C




No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.328	39.66	10.38	59.50	19.84	Peak	N	Pass
1**	0.328	26.87	10.38	49.50	22.63	AV	N	Pass
2	0.438	38.88	10.21	57.10	18.22	Peak	N	Pass
2**	0.438	27.13	10.21	47.10	19.97	AV	N	Pass
3	0.928	42.68	10.18	56.00	13.32	Peak	N	Pass
3**	0.928	37.39	10.18	46.00	8.61	AV	N	Pass
4	2.982	38.18	10.31	56.00	17.82	Peak	N	Pass
4**	2.982	26.18	10.31	46.00	19.82	AV	N	Pass
5	5.462	40.02	10.24	60.00	19.98	Peak	N	Pass
5**	5.462	29.11	10.24	50.00	20.89	AV	N	Pass
6	8.616	41.76	10.51	60.00	18.24	Peak	N	Pass
6**	8.616	31.72	10.51	50.00	18.28	AV	N	Pass

PCB-External Antenna

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.174	42.57	9.85	64.77	22.20	Peak	L	Pass
1**	0.174	27.85	9.85	54.77	26.92	AV	L	Pass
2	0.698	38.16	10.70	56.00	17.84	Peak	L	Pass
2**	0.698	25.70	10.70	46.00	20.30	AV	L	Pass
3	0.930	41.21	10.17	56.00	14.79	Peak	L	Pass
3**	0.930	35.00	10.17	46.00	11.00	AV	L	Pass
4	1.256	37.81	10.51	56.00	18.19	Peak	L	Pass
4**	1.256	26.44	10.51	46.00	19.56	AV	L	Pass
5	2.050	37.48	10.51	56.00	18.52	Peak	L	Pass
5**	2.050	25.99	10.51	46.00	20.01	AV	L	Pass
6	8.240	38.75	10.60	60.00	21.25	Peak	L	Pass
6**	8.240	29.57	10.60	50.00	20.43	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.152	46.48	9.86	65.89	19.41	Peak	N	Pass
1**	0.152	27.73	9.86	55.89	28.16	AV	N	Pass
2	0.346	37.07	10.74	59.06	21.99	Peak	N	Pass
2**	0.346	25.43	10.74	49.06	23.63	AV	N	Pass
3	0.926	41.87	10.18	56.00	14.13	Peak	N	Pass
3**	0.926	36.14	10.18	46.00	9.86	AV	N	Pass
4	1.866	36.96	10.38	56.00	19.04	Peak	N	Pass
4**	1.866	27.93	10.38	46.00	18.07	AV	N	Pass
5	8.508	40.71	10.41	60.00	19.29	Peak	N	Pass
5**	8.508	29.88	10.41	50.00	20.12	AV	N	Pass
6	10.592	39.33	10.70	60.00	20.67	Peak	N	Pass
6**	10.592	28.67	10.70	50.00	21.33	AV	N	Pass

A.6 Radiated Spurious Emission

Note ¹: The symbol of "--" in the table which means not application.

Note ²: For the test data above 1 GHz, according the ANSI C63.10-2020, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note ³: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


Note ⁴: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and BLE 2M-Low channel mode is the worst.

Note ⁵: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

Test Data and Plots

FPC Antenna


30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	127.946	16.36	-27.47	33.0	16.64	Peak	0.00	200	Horizontal	Pass
2	300.805	21.20	-25.44	35.5	14.30	Peak	276.00	200	Horizontal	Pass
3	421.297	25.47	-22.02	35.5	10.03	Peak	42.00	200	Horizontal	Pass
4	810.897	30.47	-12.49	35.5	5.03	Peak	226.00	100	Horizontal	Pass
5	909.328	30.38	-10.95	35.5	5.12	Peak	204.00	100	Horizontal	Pass
6	971.635	30.33	-9.36	43.5	13.17	Peak	297.00	200	Horizontal	Pass

30 MHz to 1 GHz, ANT V

10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	30.970	15.77	-26.88	29.5	13.73	Peak	204.00	100	Vertical	Pass
2	166.493	16.21	-26.33	33.0	16.79	Peak	0.00	100	Vertical	Pass
3	298.865	19.74	-25.46	35.5	15.76	Peak	0.00	200	Vertical	Pass
4	421.297	22.21	-22.02	35.5	13.29	Peak	264.00	100	Vertical	Pass
5	940.360	29.69	-9.88	35.5	5.81	Peak	286.00	100	Vertical	Pass
6	999.030	31.22	-8.91	43.5	12.28	Peak	0.00	200	Vertical	Pass

Note ¹: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note ²: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1449.200	43.25	74.0	30.75	Peak	209.00	200	Horizontal	Pass
1**	1449.200	32.48	54.0	21.52	AV	209.00	200	Horizontal	Pass
2	2479.800	96.53	74.0	-22.53	Peak	297.00	150	Horizontal	N/A
2**	2479.800	95.95	54.0	-41.95	AV	297.00	150	Horizontal	N/A
3	2969.700	51.54	74.0	22.46	Peak	190.00	100	Horizontal	Pass
3**	2969.700	47.68	54.0	6.32	AV	190.00	100	Horizontal	Pass
4	4905.750	49.86	74.0	24.14	Peak	59.00	200	Horizontal	Pass
4**	4905.750	40.02	54.0	13.98	AV	59.00	200	Horizontal	Pass
5	7160.000	53.82	74.0	20.18	Peak	119.00	100	Horizontal	Pass
5**	7160.000	43.46	54.0	10.54	AV	119.00	100	Horizontal	Pass
6	12450.513	53.36	74.0	20.64	Peak	147.00	300	Horizontal	Pass
6**	12450.513	44.02	54.0	9.98	AV	147.00	300	Horizontal	Pass


GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1595.800	46.41	74.0	27.59	Peak	79.00	100	Vertical	Pass
1**	1595.800	33.11	54.0	20.89	AV	79.00	100	Vertical	Pass
2	2479.800	91.39	74.0	-17.39	Peak	185.00	200	Vertical	N/A
2**	2479.800	90.60	54.0	-36.60	AV	185.00	200	Vertical	N/A
3	2969.900	53.20	74.0	20.80	Peak	275.00	100	Vertical	Pass
3**	2969.900	48.49	54.0	5.51	AV	275.00	100	Vertical	Pass
4	4803.250	49.40	74.0	24.60	Peak	199.00	100	Vertical	Pass
4**	4803.250	39.84	54.0	14.16	AV	199.00	100	Vertical	Pass
5	7191.250	53.89	74.0	20.11	Peak	360.00	200	Vertical	Pass
5**	7191.250	43.89	54.0	10.11	AV	360.00	200	Vertical	Pass
6	12999.113	53.24	74.0	20.76	Peak	24.00	200	Vertical	Pass
6**	12999.113	44.01	54.0	9.99	AV	24.00	200	Vertical	Pass

PCB-onboard PCB Antenna

30 MHz to 1 GHz, ANT H


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	127.946	14.70	-27.47	33.0	18.30	Peak	0.00	200	Horizontal	Pass
2	287.956	19.60	-25.91	35.5	15.90	Peak	325.00	200	Horizontal	Pass
3	359.960	29.70	-23.72	35.5	5.80	Peak	0.00	200	Horizontal	Pass
4	407.963	30.92	-22.57	35.5	4.58	Peak	0.00	200	Horizontal	Pass
5	455.966	26.63	-21.09	35.5	8.87	Peak	199.00	200	Horizontal	Pass
6	971.635	32.08	-9.36	43.5	11.42	Peak	117.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V

10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	30.970	14.99	-26.88	29.5	14.51	Peak	128.00	100	Vertical	Pass
2	62.487	13.19	-27.69	29.5	16.31	Peak	0.00	200	Vertical	Pass
3	287.956	18.26	-25.91	35.5	17.24	Peak	2.00	200	Vertical	Pass
4	407.963	20.28	-22.57	35.5	15.22	Peak	308.00	200	Vertical	Pass
5	918.055	29.35	-10.40	35.5	6.15	Peak	167.00	200	Vertical	Pass
6	979.150	30.29	-9.43	43.5	13.21	Peak	330.00	200	Vertical	Pass

Note ¹: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note ²: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1597.100	43.57	74.0	30.43	Peak	360.00	300	Horizontal	Pass
1**	1597.100	31.87	54.0	22.13	AV	360.00	300	Horizontal	Pass
2	2480.300	99.25	74.0	-25.25	Peak	153.00	200	Horizontal	N/A
2**	2480.300	98.98	54.0	-44.98	AV	153.00	200	Horizontal	N/A
3	4813.200	48.78	74.0	25.22	Peak	155.00	150	Horizontal	Pass
3**	4813.200	39.16	54.0	14.84	AV	155.00	150	Horizontal	Pass
4	7439.300	47.37	74.0	26.63	Peak	315.00	150	Horizontal	Pass
4**	7439.300	42.19	54.0	11.81	AV	315.00	150	Horizontal	Pass
5	11900.724	48.24	74.0	25.76	Peak	287.00	100	Horizontal	Pass
5**	11900.724	38.34	54.0	15.66	AV	287.00	100	Horizontal	Pass
6	17401.238	50.50	74.0	23.50	Peak	264.00	100	Horizontal	Pass
6**	17401.238	41.05	54.0	12.95	AV	264.00	100	Horizontal	Pass


GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1595.300	43.79	74.0	30.21	Peak	20.00	300	Vertical	Pass
1**	1595.300	34.72	54.0	19.28	AV	20.00	300	Vertical	Pass
2	2480.200	88.83	74.0	-14.83	Peak	129.00	150	Vertical	N/A
2**	2480.200	88.28	54.0	-34.28	AV	129.00	150	Vertical	N/A
3	4966.800	48.52	74.0	25.48	Peak	293.00	200	Vertical	Pass
3**	4966.800	39.22	54.0	14.78	AV	293.00	200	Vertical	Pass
4	7440.737	49.45	74.0	24.55	Peak	241.00	150	Vertical	Pass
4**	7440.737	45.88	54.0	8.12	AV	241.00	150	Vertical	Pass
5	11312.213	47.02	74.0	26.98	Peak	217.00	100	Vertical	Pass
5**	11312.213	37.74	54.0	16.26	AV	217.00	100	Vertical	Pass
6	16803.787	50.49	74.0	23.51	Peak	319.00	400	Vertical	Pass
6**	16803.787	40.88	54.0	13.12	AV	319.00	400	Vertical	Pass

Dipole Antenna

30 MHz to 1 GHz, ANT H


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	127.946	16.03	-27.47	33.0	16.97	Peak	140.00	100	Horizontal	Pass
2	300.805	20.68	-25.44	35.5	14.82	Peak	117.00	200	Horizontal	Pass
3	399.963	21.87	-22.92	35.5	13.63	Peak	360.00	200	Horizontal	Pass
4	810.897	32.20	-12.49	35.5	3.30	Peak	238.00	100	Horizontal	Pass
5	860.112	31.27	-11.77	35.5	4.23	Peak	216.00	100	Horizontal	Pass
6	984.726	30.18	-9.37	43.5	13.32	Peak	259.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V

10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	147.341	17.41	-26.24	33.0	15.59	Peak	254.00	100	Vertical	Pass
2	298.865	20.51	-25.46	35.5	14.99	Peak	360.00	200	Vertical	Pass
3	421.297	22.26	-22.02	35.5	13.24	Peak	319.00	100	Vertical	Pass
4	659.615	26.75	-15.86	35.5	8.75	Peak	143.00	200	Vertical	Pass
5	842.657	28.40	-11.75	35.5	7.10	Peak	360.00	200	Vertical	Pass
6	984.241	30.63	-9.39	43.5	12.87	Peak	287.00	100	Vertical	Pass

Note ¹: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note ²: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1290.500	40.49	74.0	33.51	Peak	336.00	100	Horizontal	Pass
1**	1290.500	30.94	54.0	23.06	AV	336.00	100	Horizontal	Pass
2	2480.200	105.28	74.0	-31.28	Peak	86.00	100	Horizontal	N/A
2**	2480.200	104.59	54.0	-50.59	AV	86.00	100	Horizontal	N/A
3	4672.800	48.43	74.0	25.57	Peak	360.00	100	Horizontal	Pass
3**	4672.800	38.09	54.0	15.91	AV	360.00	100	Horizontal	Pass
4	7439.587	44.74	74.0	29.26	Peak	315.00	150	Horizontal	Pass
4**	7439.587	41.03	54.0	12.97	AV	315.00	150	Horizontal	Pass
5	11287.487	47.52	74.0	26.48	Peak	268.00	300	Horizontal	Pass
5**	11287.487	38.28	54.0	15.72	AV	268.00	300	Horizontal	Pass
6	16731.600	50.69	74.0	23.31	Peak	360.00	100	Horizontal	Pass
6**	16731.600	40.63	54.0	13.37	AV	360.00	100	Horizontal	Pass


GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1598.300	43.57	74.0	30.43	Peak	56.00	200	Vertical	Pass
1**	1598.300	36.72	54.0	17.28	AV	56.00	200	Vertical	Pass
2	2480.200	90.32	74.0	-16.32	Peak	116.00	100	Vertical	N/A
2**	2480.200	89.85	54.0	-35.85	AV	116.00	100	Vertical	N/A
3	4968.200	49.05	74.0	24.95	Peak	42.00	200	Vertical	Pass
3**	4968.200	38.39	54.0	15.61	AV	42.00	200	Vertical	Pass
4	7441.025	48.35	74.0	25.65	Peak	241.00	150	Vertical	Pass
4**	7441.025	41.89	54.0	12.11	AV	241.00	150	Vertical	Pass
5	11904.463	47.27	74.0	26.73	Peak	72.00	200	Vertical	Pass
5**	11904.463	38.30	54.0	15.70	AV	72.00	200	Vertical	Pass
6	14238.638	50.95	74.0	23.05	Peak	241.00	200	Vertical	Pass
6**	14238.638	40.10	54.0	13.90	AV	241.00	200	Vertical	Pass

Copper Tube Antenna

30 MHz to 1 GHz, ANT H


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	287.956	19.87	-25.91	35.5	15.63	Peak	112.00	200	Horizontal	Pass
2	366.021	22.31	-23.74	35.5	13.19	Peak	0.00	200	Horizontal	Pass
3	421.055	23.00	-22.03	35.5	12.50	Peak	0.00	200	Horizontal	Pass
4	712.709	30.44	-14.83	35.5	5.06	Peak	232.00	100	Horizontal	Pass
5	811.003	31.69	-12.49	35.5	3.81	Peak	232.00	129	Horizontal	N/A
5*	811.003	29.57	-12.49	35.5	5.93	QP	232.00	129	Horizontal	Pass
6	860.112	32.43	-11.77	35.5	3.07	Peak	232.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V

10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	30.970	18.46	-26.88	29.5	11.04	Peak	176.00	100	Vertical	Pass
2	147.341	18.94	-26.24	33.0	14.06	Peak	221.00	100	Vertical	Pass
3	232.437	18.70	-28.70	35.5	16.80	Peak	0.00	100	Vertical	Pass
4	300.562	19.40	-25.45	35.5	16.10	Peak	210.00	100	Vertical	Pass
5	755.379	26.70	-13.38	35.5	8.80	Peak	248.00	200	Vertical	Pass
6	958.300	30.45	-9.78	35.5	5.05	Peak	226.00	200	Vertical	Pass

Note ¹: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note ²: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1332.900	41.21	74.0	32.79	Peak	114.00	100	Horizontal	Pass
1**	1332.900	31.75	54.0	22.25	AV	114.00	100	Horizontal	Pass
2	2480.100	104.58	74.0	-30.58	Peak	224.00	100	Horizontal	N/A
2**	2480.100	103.70	54.0	-49.70	AV	224.00	100	Horizontal	N/A
3	4795.800	48.36	74.0	25.64	Peak	12.00	200	Horizontal	Pass
3**	4795.800	38.76	54.0	15.24	AV	12.00	200	Horizontal	Pass
4	7439.875	46.81	74.0	27.19	Peak	23.00	150	Horizontal	Pass
4**	7439.875	43.07	54.0	10.93	AV	23.00	150	Horizontal	Pass
5	11275.987	47.00	74.0	27.00	Peak	95.00	200	Horizontal	Pass
5**	11275.987	37.72	54.0	16.28	AV	95.00	200	Horizontal	Pass
6	16144.650	50.11	74.0	23.89	Peak	187.00	400	Horizontal	Pass
6**	16144.650	41.76	54.0	12.24	AV	187.00	400	Horizontal	Pass


GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1329.400	41.85	74.0	32.15	Peak	236.00	300	Vertical	Pass
1**	1329.400	31.86	54.0	22.14	AV	236.00	300	Vertical	Pass
2	2480.300	92.62	74.0	-18.62	Peak	184.00	150	Vertical	N/A
2**	2480.300	90.80	54.0	-36.80	AV	184.00	150	Vertical	N/A
3	4977.800	49.16	74.0	24.84	Peak	153.00	100	Vertical	Pass
3**	4977.800	39.53	54.0	14.47	AV	153.00	100	Vertical	Pass
4	7441.025	46.32	74.0	27.68	Peak	241.00	150	Vertical	Pass
4**	7441.025	44.21	54.0	9.79	AV	241.00	150	Vertical	Pass
5	11899.000	47.28	74.0	26.72	Peak	45.00	200	Vertical	Pass
5**	11899.000	38.24	54.0	15.76	AV	45.00	200	Vertical	Pass
6	15579.487	50.67	74.0	23.33	Peak	105.00	300	Vertical	Pass
6**	15579.487	41.21	54.0	12.79	AV	105.00	300	Vertical	Pass

PCB-External Antenna

30 MHz to 1 GHz, ANT H


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	127.946	15.83	-27.47	33.0	17.17	Peak	360.00	200	Horizontal	Pass
2	287.956	20.47	-25.91	35.5	15.03	Peak	118.00	200	Horizontal	Pass
3	420.812	24.22	-22.05	35.5	11.28	Peak	297.00	200	Horizontal	Pass
4	712.709	31.61	-14.83	35.5	3.89	Peak	244.00	100	Horizontal	Pass
5	810.897	31.22	-12.49	35.5	4.28	Peak	249.00	100	Horizontal	Pass
6	958.300	30.91	-9.78	35.5	4.59	Peak	211.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V

10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	35.576	14.48	-27.05	29.5	15.02	Peak	194.00	100	Vertical	Pass
2	162.857	20.22	-26.25	33.0	12.78	Peak	318.00	200	Vertical	Pass
3	301.047	20.63	-25.44	35.5	14.87	Peak	302.00	100	Vertical	Pass
4	727.498	27.01	-14.01	35.5	8.49	Peak	42.00	100	Vertical	Pass
5	909.328	30.35	-10.95	35.5	5.15	Peak	150.00	200	Vertical	Pass
6	983.514	30.52	-9.42	43.5	12.98	Peak	11.00	100	Vertical	Pass

Note ¹: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note ²: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK (BLE 1Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1336.801	44.92	74.0	29.08	Peak	318.00	300	Horizontal	Pass
1**	1336.801	31.61	54.0	22.39	AV	318.00	300	Horizontal	Pass
2	2974.826	53.26	74.0	20.74	Peak	155.00	400	Horizontal	Pass
2**	2974.826	41.93	54.0	12.07	AV	155.00	400	Horizontal	Pass
3	4914.178	49.31	74.0	24.69	Peak	347.00	200	Horizontal	Pass
3**	4914.178	44.57	54.0	9.43	AV	347.00	200	Horizontal	Pass
4	7628.339	56.23	74.0	17.77	Peak	156.00	300	Horizontal	Pass
4**	7628.339	39.92	54.0	14.08	AV	156.00	300	Horizontal	Pass
5	12472.707	54.63	74.0	19.37	Peak	204.00	200	Horizontal	Pass
5**	12472.707	45.51	54.0	8.49	AV	204.00	200	Horizontal	Pass
6	16860.034	52.48	74.0	21.52	Peak	3.00	300	Horizontal	Pass
6**	16860.034	42.39	54.0	11.61	AV	3.00	300	Horizontal	Pass

GFSK (BLE 1Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1467.783	42.03	74.0	31.97	Peak	66.00	100	Vertical	Pass
1**	1467.783	32.47	54.0	21.53	AV	66.00	100	Vertical	Pass
2	2993.489	49.67	74.0	24.33	Peak	193.00	100	Vertical	Pass
2**	2993.489	37.11	54.0	16.89	AV	193.00	100	Vertical	Pass
3	4824.546	50.37	74.0	23.63	Peak	106.00	200	Vertical	Pass
3**	4824.546	40.80	54.0	13.20	AV	106.00	200	Vertical	Pass
4	7967.386	58.02	74.0	15.98	Peak	314.00	400	Vertical	Pass
4**	7967.386	43.61	54.0	10.39	AV	314.00	400	Vertical	Pass
5	12441.511	49.26	74.0	24.74	Peak	277.00	400	Vertical	Pass
5**	12441.511	44.80	54.0	9.20	AV	277.00	400	Vertical	Pass
6	17459.046	56.38	74.0	17.62	Peak	22.00	400	Vertical	Pass
6**	17459.046	46.88	54.0	7.12	AV	22.00	400	Vertical	Pass

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1335.818	44.70	74.0	29.30	Peak	170.00	200	Horizontal	Pass
1**	1335.818	27.59	54.0	26.41	AV	170.00	200	Horizontal	Pass
2	2976.129	53.12	74.0	20.88	Peak	141.00	400	Horizontal	Pass
2**	2976.129	39.25	54.0	14.75	AV	141.00	400	Horizontal	Pass
3	4917.352	52.90	74.0	21.10	Peak	223.00	200	Horizontal	Pass
3**	4917.352	41.19	54.0	12.81	AV	223.00	200	Horizontal	Pass
4	7629.229	56.67	74.0	17.33	Peak	302.00	300	Horizontal	Pass
4**	7629.229	37.58	54.0	16.42	AV	302.00	300	Horizontal	Pass
5	12472.553	51.30	74.0	22.70	Peak	140.00	300	Horizontal	Pass
5**	12472.553	41.49	54.0	12.51	AV	140.00	300	Horizontal	Pass
6	16853.724	55.30	74.0	18.70	Peak	264.00	200	Horizontal	Pass
6**	16853.724	44.02	54.0	9.98	AV	264.00	200	Horizontal	Pass

GFSK (BLE 1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1469.008	40.97	74.0	33.03	Peak	299.00	300	Vertical	Pass
1**	1469.008	28.27	54.0	25.73	AV	299.00	300	Vertical	Pass
2	2992.916	50.19	74.0	23.81	Peak	106.00	300	Vertical	Pass
2**	2992.916	40.77	54.0	13.23	AV	106.00	300	Vertical	Pass
3	4822.705	52.10	74.0	21.90	Peak	86.00	200	Vertical	Pass
3**	4822.705	43.93	54.0	10.07	AV	86.00	200	Vertical	Pass
4	7969.333	57.58	74.0	16.42	Peak	143.00	100	Vertical	Pass
4**	7969.333	44.11	54.0	9.89	AV	143.00	100	Vertical	Pass
5	12446.157	53.29	74.0	20.71	Peak	90.00	300	Vertical	Pass
5**	12446.157	45.36	54.0	8.64	AV	90.00	300	Vertical	Pass
6	17455.340	53.25	74.0	20.75	Peak	114.00	100	Vertical	Pass
6**	17455.340	46.34	54.0	7.66	AV	114.00	100	Vertical	Pass

GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1335.596	44.23	74.0	29.77	Peak	349.00	400	Horizontal	Pass
1**	1335.596	30.39	54.0	23.61	AV	349.00	400	Horizontal	Pass
2	2970.291	48.81	74.0	25.19	Peak	334.00	300	Horizontal	Pass
2**	2970.291	43.40	54.0	10.60	AV	334.00	300	Horizontal	Pass
3	4915.378	48.55	74.0	25.45	Peak	264.00	200	Horizontal	Pass
3**	4915.378	43.76	54.0	10.24	AV	264.00	200	Horizontal	Pass
4	7628.009	53.85	74.0	20.15	Peak	324.00	200	Horizontal	Pass
4**	7628.009	42.61	54.0	11.39	AV	324.00	200	Horizontal	Pass
5	12473.733	55.05	74.0	18.95	Peak	130.00	300	Horizontal	Pass
5**	12473.733	43.53	54.0	10.47	AV	130.00	300	Horizontal	Pass
6	16853.566	55.66	74.0	18.34	Peak	146.00	300	Horizontal	Pass
6**	16853.566	43.10	54.0	10.90	AV	146.00	300	Horizontal	Pass

GFSK (BLE 1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1467.894	45.51	74.0	28.49	Peak	86.00	200	Vertical	Pass
1**	1467.894	28.56	54.0	25.44	AV	86.00	200	Vertical	Pass
2	2995.045	50.22	74.0	23.78	Peak	277.00	400	Vertical	Pass
2**	2995.045	36.90	54.0	17.10	AV	277.00	400	Vertical	Pass
3	4823.800	50.11	74.0	23.89	Peak	354.00	200	Vertical	Pass
3**	4823.800	43.28	54.0	10.72	AV	354.00	200	Vertical	Pass
4	7964.494	57.90	74.0	16.10	Peak	150.00	400	Vertical	Pass
4**	7964.494	43.05	54.0	10.95	AV	150.00	400	Vertical	Pass
5	12446.547	49.13	74.0	24.87	Peak	67.00	100	Vertical	Pass
5**	12446.547	43.34	54.0	10.66	AV	67.00	100	Vertical	Pass
6	17458.822	58.14	74.0	15.86	Peak	176.00	100	Vertical	Pass
6**	17458.822	45.80	54.0	8.20	AV	176.00	100	Vertical	Pass

GFSK (BLE 2Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1284.494	43.98	74.0	30.02	Peak	76.00	200	Horizontal	Pass
1**	1284.494	35.64	54.0	18.36	AV	76.00	200	Horizontal	Pass
2	2772.593	50.49	74.0	23.51	Peak	169.00	300	Horizontal	Pass
2**	2772.593	45.05	54.0	8.95	AV	169.00	300	Horizontal	Pass
3	5165.421	53.01	74.0	20.99	Peak	130.00	200	Horizontal	Pass
3**	5165.421	43.52	54.0	10.48	AV	130.00	200	Horizontal	Pass
4	6807.599	53.58	74.0	20.42	Peak	63.00	100	Horizontal	Pass
4**	6807.599	47.68	54.0	6.32	AV	63.00	100	Horizontal	Pass
5	13463.886	54.71	74.0	19.29	Peak	233.00	400	Horizontal	Pass
5**	13463.886	47.66	54.0	6.34	AV	233.00	400	Horizontal	Pass
6	17464.895	54.89	74.0	19.11	Peak	88.00	300	Horizontal	Pass
6**	17464.895	46.97	54.0	7.03	AV	88.00	300	Horizontal	Pass

GFSK (BLE 2Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1287.149	41.77	74.0	32.23	Peak	201.00	400	Vertical	Pass
1**	1287.149	31.47	54.0	22.53	AV	201.00	400	Vertical	Pass
2	2767.399	51.67	74.0	22.33	Peak	355.00	400	Vertical	Pass
2**	2767.399	44.56	54.0	9.44	AV	355.00	400	Vertical	Pass
3	5168.675	53.54	74.0	20.46	Peak	259.00	200	Vertical	Pass
3**	5168.675	41.14	54.0	12.86	AV	259.00	200	Vertical	Pass
4	6810.170	52.18	74.0	21.82	Peak	50.00	300	Vertical	Pass
4**	6810.170	45.75	54.0	8.25	AV	50.00	300	Vertical	Pass
5	13463.791	52.69	74.0	21.31	Peak	175.00	100	Vertical	Pass
5**	13463.791	44.96	54.0	9.04	AV	175.00	100	Vertical	Pass
6	17464.280	55.39	74.0	18.61	Peak	107.00	400	Vertical	Pass
6**	17464.280	46.74	54.0	7.26	AV	107.00	400	Vertical	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1289.482	40.16	74.0	33.84	Peak	269.00	100	Horizontal	Pass
1**	1289.482	31.13	54.0	22.87	AV	269.00	100	Horizontal	Pass
2	2770.656	51.76	74.0	22.24	Peak	28.00	200	Horizontal	Pass
2**	2770.656	43.40	54.0	10.60	AV	28.00	200	Horizontal	Pass
3	5166.893	50.13	74.0	23.87	Peak	103.00	200	Horizontal	Pass
3**	5166.893	42.55	54.0	11.45	AV	103.00	200	Horizontal	Pass
4	6806.009	57.76	74.0	16.24	Peak	318.00	300	Horizontal	Pass
4**	6806.009	47.01	54.0	6.99	AV	318.00	300	Horizontal	Pass
5	13469.531	55.66	74.0	18.34	Peak	131.00	300	Horizontal	Pass
5**	13469.531	44.02	54.0	9.98	AV	131.00	300	Horizontal	Pass
6	17469.718	55.80	74.0	18.20	Peak	157.00	400	Horizontal	Pass
6**	17469.718	49.04	54.0	4.96	AV	157.00	400	Horizontal	Pass

GFSK (BLE 2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1284.961	42.10	74.0	31.90	Peak	355.00	400	Vertical	Pass
1**	1284.961	34.54	54.0	19.46	AV	355.00	400	Vertical	Pass
2	2767.014	52.27	74.0	21.73	Peak	237.00	200	Vertical	Pass
2**	2767.014	40.04	54.0	13.96	AV	237.00	200	Vertical	Pass
3	5171.233	53.30	74.0	20.70	Peak	206.00	200	Vertical	Pass
3**	5171.233	40.99	54.0	13.01	AV	206.00	200	Vertical	Pass
4	6802.697	53.37	74.0	20.63	Peak	336.00	200	Vertical	Pass
4**	6802.697	44.19	54.0	9.81	AV	336.00	200	Vertical	Pass
5	13463.255	57.33	74.0	16.67	Peak	260.00	100	Vertical	Pass
5**	13463.255	47.35	54.0	6.65	AV	260.00	100	Vertical	Pass
6	17467.067	53.36	74.0	20.64	Peak	233.00	300	Vertical	Pass
6**	17467.067	45.86	54.0	8.14	AV	233.00	300	Vertical	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1289.245	44.26	74.0	29.74	Peak	207.00	200	Horizontal	Pass
1**	1289.245	32.45	54.0	21.55	AV	207.00	200	Horizontal	Pass
2	2766.929	54.64	74.0	19.36	Peak	344.00	400	Horizontal	Pass
2**	2766.929	45.65	54.0	8.35	AV	344.00	400	Horizontal	Pass
3	5389.011	54.64	74.0	19.36	Peak	200.00	200	Horizontal	Pass
3**	5389.011	41.23	54.0	12.77	AV	200.00	200	Horizontal	Pass
4	6514.113	56.36	74.0	17.64	Peak	265.00	300	Horizontal	Pass
4**	6514.113	41.93	54.0	12.07	AV	265.00	300	Horizontal	Pass
5	13349.474	56.28	74.0	17.72	Peak	344.00	200	Horizontal	Pass
5**	13349.474	49.94	54.0	4.06	AV	344.00	200	Horizontal	Pass
6	17444.048	55.93	74.0	18.07	Peak	134.00	100	Horizontal	Pass
6**	17444.048	45.64	54.0	8.36	AV	134.00	100	Horizontal	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1285.727	43.78	74.0	30.22	Peak	158.00	400	Vertical	Pass
1**	1285.727	30.55	54.0	23.45	AV	158.00	400	Vertical	Pass
2	2771.476	54.11	74.0	19.89	Peak	45.00	300	Vertical	Pass
2**	2771.476	44.89	54.0	9.11	AV	45.00	300	Vertical	Pass
3	5290.184	55.27	74.0	18.73	Peak	320.00	200	Vertical	Pass
3**	5290.184	43.84	54.0	10.16	AV	320.00	200	Vertical	Pass
4	6655.209	53.02	74.0	20.98	Peak	183.00	300	Vertical	Pass
4**	6655.209	43.22	54.0	10.78	AV	183.00	300	Vertical	Pass
5	13310.344	55.35	74.0	18.65	Peak	59.00	100	Vertical	Pass
5**	13310.344	45.63	54.0	8.37	AV	59.00	100	Vertical	Pass
6	17421.643	56.60	74.0	17.40	Peak	254.00	400	Vertical	Pass
6**	17421.643	45.36	54.0	8.64	AV	254.00	400	Vertical	Pass

A.7 Band Edge (Restricted-band band-edge)

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note ²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note ³: According the ANSI C63.10-2020, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note ⁴: The Level (dBuV/m) has been corrected by factor.

Note ⁵: Both horizontal and vertical directions were pre tested, only the worst configuration has been reported in this report.

Test Data

FPC Antenna

GFSK (BLE 1Mbps) HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	56.97	74.0	17.03	Peak	272.00	100	Horizontal	Pass
1**	2483.500	43.54	54.0	10.46	AV	272.00	100	Horizontal	Pass
2	2483.800	56.57	74.0	17.43	Peak	304.00	150	Horizontal	Pass
2**	2483.800	43.61	54.0	10.39	AV	304.00	150	Horizontal	Pass

PCB-onboard Antenna

GFSK (BLE 1Mbps) HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	58.43	74.0	15.57	Peak	115.00	200	Horizontal	Pass
1**	2483.500	43.74	54.0	10.26	AV	115.00	200	Horizontal	Pass
2	2483.800	57.91	74.0	16.09	Peak	162.00	150	Horizontal	Pass
2**	2483.800	43.60	54.0	10.40	AV	162.00	150	Horizontal	Pass

Dipole Antenna

GFSK (BLE 1Mbps) LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.550	62.95	74.0	11.05	Peak	249.00	100	Horizontal	Pass
1**	2483.550	45.24	54.0	8.76	AV	249.00	100	Horizontal	Pass
2	2483.750	62.58	74.0	11.42	Peak	257.00	100	Horizontal	Pass
2**	2483.750	45.39	54.0	8.61	AV	257.00	100	Horizontal	Pass

Copper Tube Antenna

GFSK (BLE 1Mbps) HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.550	62.33	74.0	11.67	Peak	7.00	150	Horizontal	Pass
1**	2483.550	45.00	54.0	9.00	AV	7.00	150	Horizontal	Pass
2	2483.750	61.02	74.0	12.98	Peak	30.00	100	Horizontal	Pass
2**	2483.750	44.57	54.0	9.43	AV	30.00	100	Horizontal	Pass

PCB-External Antenna

GFSK (BLE 1Mbps) LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2320.941	57.52	74.0	16.48	Peak	272.00	200	Horizontal	Pass
1**	2320.941	43.98	54.0	10.02	AV	272.00	200	Horizontal	Pass
2	2390.000	55.2	74.0	18.80	Peak	231.00	300	Horizontal	Pass
2**	2390.000	44.39	54.0	9.61	AV	231.00	300	Horizontal	Pass

GFSK (BLE 1Mbps) HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	56.06	74.0	17.94	Peak	268.00	100	Horizontal	Pass
1**	2483.500	42.94	54.0	11.06	AV	268.00	100	Horizontal	Pass
2	2493.930	58.46	74.0	15.54	Peak	333.00	200	Horizontal	Pass
2**	2493.930	44.93	54.0	9.07	AV	333.00	200	Horizontal	Pass

GFSK (BLE 2Mbps) LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2317.372	55.81	74.0	18.19	Peak	200.00	100	Horizontal	Pass
1**	2317.372	45.18	54.0	8.82	AV	200.00	100	Horizontal	Pass
2	2390.000	53.65	74.0	20.35	Peak	341.00	100	Horizontal	Pass
2**	2390.000	44.78	54.0	9.22	AV	341.00	100	Horizontal	Pass

GFSK (BLE 2Mbps) HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	56.56	74.0	17.44	Peak	161.00	200	Horizontal	Pass
1**	2483.500	45.16	54.0	8.84	AV	161.00	200	Horizontal	Pass
2	2392.896	53.07	74.0	20.93	Peak	18.00	100	Horizontal	Pass
2**	2392.896	43.14	54.0	10.86	AV	18.00	100	Horizontal	Pass

A.8 Power Spectral Density (PSD)


Test Data

GFSK (BLE 1Mbps)			
Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low Channel	-8.78	8	Pass
Middle Channel	-9.21	8	Pass
High Channel	-9.86	8	Pass

GFSK (BLE 2Mbps)			
Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low Channel	-12.28	8	Pass
Middle Channel	-12.77	8	Pass
High Channel	-13.36	8	Pass

Test Plots

GFSK (BLE 1Mbps) LOW CHANNEL




GFSK (BLE 1Mbps) MIDDLE CHANNEL




GFSK (BLE 1Mbps) HIGH CHANNEL



GFSK (BLE 2Mbps) LOW CHANNEL



GFSK (BLE 2Mbps) MIDDLE CHANNEL



GFSK (BLE 2Mbps) HIGH CHANNEL



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2591045-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2591045-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2591045-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--