

TEST REPORT

Applicant: Hansong(Nanjing) Technology Ltd.
Address: 8th Kangping Road Jiangning Economy and Technology Development Zone, Nanjing, 211106, China.
Equipment Type: Bluetooth Module
Model Name: HSBT3095-EA (refer to section 2.3)
Brand Name: Platin
FCC ID: XCO-QCC3095
ISED Number: 7756A-QCC3095
Test Standard: 47 CFR Part 15 Subpart C
RSS-Gen Issue 5
RSS-247 Issue 3
(refer to section 3.1)
Sample Arrival Date: Aug. 02, 2025
Test Date: Aug. 18, 2025 - Sep. 05, 2025
Date of Issue: Sep. 25, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Yang Wenxuan**Checked by:** Ye Hongji**Approved by:** Sunny Zou
(Technical Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Sep. 25, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Technical Information	6
3	SUMMARY OF TEST RESULTS	8
3.1	Test Standards	8
3.2	Test Verdict	9
4	GENERAL TEST CONFIGURATIONS	10
4.1	Test Environments	10
4.2	Test Equipment List	10
4.3	Test Software List	10
4.4	Measurement Uncertainty	11
4.5	Description of Test Setup	11
4.6	Measurement Results Explanation Example	14
5	TEST ITEMS	15
5.1	Antenna Requirements	15
5.2	Frequency Hopping Systems	16
5.3	Number of Hopping Frequencies	18
5.4	Peak Output Power and E.I.R.P.	19
5.5	Occupied Bandwidth	20

5.6	Carrier Frequency Separation	21
5.7	Time of Occupancy (Dwell time)	22
5.8	Conducted Spurious Emission & Authorized-band band-edge	24
5.9	Conducted Emission	25
5.10	Radiated Spurious Emission	26
5.11	Band Edge (Restricted-band band-edge).....	28
ANNEX A	TEST RESULT	29
A.1	Number of Hopping Frequency	29
A.2	Peak Output Power and E.I.R.P	30
A.3	20 dB and 99% bandwidth	33
A.4	Hopping Frequency Separation.....	38
A.5	Average Time of Occupancy	39
A.6	Conducted Spurious Emissions & Authorized-band band-edge	42
A.7	Conducted Emissions.....	49
A.8	Radiated Spurious Emission	55
A.9	Band Edge (Restricted-band band-edge).....	69
ANNEX B	TEST SETUP PHOTOS	71
ANNEX C	EUT EXTERNAL PHOTOS	71
ANNEX D	EUT INTERNAL PHOTOS	71

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Hansong(Nanjing) Technology Ltd.
Address	8th Kangping Road Jiangning Economy and Technology Development Zone, Nanjing, 211106, China.

2.2 Manufacturer Information

Manufacturer	Hansong(Nanjing) Technology Ltd.
Address	8th Kangping Road Jiangning Economy and Technology Development Zone, Nanjing, 211106, China.

2.3 General Description for Equipment under Test (EUT)

EUT Name	Bluetooth Module
Model Name Under Test	HSBT3095-EA
Series Model Name	HSBT3095-IA
Description of Model name differentiation	HSBT3095-EA is equipped with an external antenna, while HSBT3095-IA is designed with an internal antenna. The Circuit, PCB Layout, Electrical Parts, and appearance of the following product(s) are identical to the basic model. (this information provided by the applicant)
Serial Number	H259QCC309500001
Hardware Version	V1_0
Software Version	V1.02
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE)
-----------------------------------	------------------------

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Product Type	☒ Mobile ☐ Portable ☐ Fix Location
Transfer Rate	DH5: 1 Mbps 2DH5: 2 Mbps 3DH5: 3 Mbps
Frequency Range	The frequency range used is 2400 MHz to 2483.5 MHz.
Number of Channel	79 (at intervals of 1 MHz)
Tested Channel	0 (2402 MHz), 39 (2441 MHz), 78 (2480 MHz)
Antenna Type	PCB Antenna FPC Antenna Dipole Antenna
Antenna Gain	PCB Antenna 4.20 dBi FPC Antenna 3.43 dBi Dipole Antenna 2.10 dBi
Antenna Impedance	50 Ω
Antenna System (MIMO Smart Antenna)	N/A

All channel was listed on the following table:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
0	2402	21	2423	42	2444	63	2465
1	2403	22	2424	43	2445	64	2466
2	2404	23	2425	44	2446	65	2467
3	2405	24	2426	45	2447	66	2468
4	2406	25	2427	46	2448	67	2469
5	2407	26	2428	47	2449	68	2470
6	2408	27	2429	48	2450	69	2471
7	2409	28	2430	49	2451	70	2472
8	2410	29	2431	50	2452	71	2473
9	2411	30	2432	51	2453	72	2474
10	2412	31	2433	52	2454	73	2475
11	2413	32	2434	53	2455	74	2476
12	2414	33	2435	54	2456	75	2477
13	2415	34	2436	55	2457	76	2478
14	2416	35	2437	56	2458	77	2479
15	2417	36	2438	57	2459	78	2480
16	2418	37	2439	58	2460	-	-
17	2419	38	2440	59	2461	-	-
18	2420	39	2441	60	2462	-	-
19	2421	40	2442	61	2463	-	-
20	2422	41	2443	62	2464	-	-

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional radiators of radio frequency equipment
2	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
3	RSS-247 Issue 3	Digital Transmission Systems (DTSs), Frequency Hopping Systems(FHSs) and Licence-Exemp Local Area Network (LE-LAN) Devices
4	ANSI C63.10-2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
5	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Test Verdict

No.	Description	FCC Part No.	ISED Part No.	Channel	Test Result	Verdict	Remark
1	Antenna Requirement	15.203	RSS-247, 5.4 (f)	N/A	--	Pass	Note ¹
2	Number of Hopping Frequencies	15.247(a)	RSS-247, 5.1 (d)	Hopping Mode	ANNEX A.1	Pass	Note ²
3	Peak Output Power and E.I.R.P	15.247(b)	RSS-247, 5.4 (b)	Low/Middle/High	ANNEX A.2	Pass	--
4	Occupied Bandwidth	15.247(a)	RSS-247, 5.1 (a)	Low/Middle/High	ANNEX A.3	Pass	--
5	Carrier Frequency Separation	15.247(a)	RSS-247, 5.1 (b)	Hopping Mode	ANNEX A.4	Pass	Note ²
6	Time of Occupancy (Dwell time)	15.247(a)	RSS-247, 5.1 (d)	Hopping Mode	ANNEX A.5	Pass	Note ²
7	Conducted Spurious Emission & Authorized-band band-edge	15.247(d)	RSS-247, 5.5	Hopping Mode; Low/Middle/High	ANNEX A.6	Pass	Note ²
8	Conducted Emission	15.207	RSS-GEN, 8.8	Low/Middle/High	ANNEX A.7	Pass	Note ²
9	Radiated Spurious Emission	15.209 15.247(d)	RSS-247, 5.5	Low/Middle/High	ANNEX A.8	Pass	Note ²
10	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	RSS-247, 5.5	Low/High	ANNEX A.9	Pass	Note ²
11	Receiver Spurious Emissions	--	RSS-Gen, 7.3	--	--	N/A	Note ³

Note ¹: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note ²: $\pi/4$ -DQPSK is the EDR 2M rate mode, 8-DPSK is the EDR 3M rate mode. The consistency of test results in $\pi/4$ -DQPSK and 8-DPSK is very high. So we chose 8-DPSK as a typical representative to appear on the report. Another we will show all the modes on the RF output power test item.

Note ³: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	46% to 69%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+20.8°C to +25.1°C
Working Voltage of the EUT	NV (Normal Voltage)	5 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-40	101544	2024.12.16	2025.12.15
Spectrum Analyzer	KEYSIGHT	N9020A	MY50330200	2025.04.28	2026.04.27
Spectrum Analyzer	KEYSIGHT	N9020A	MY46471071	2025.06.16	2026.06.15
Signaling Unit	ROHDE&SCHWARZ	CMW500	142028	2025.04.28	2026.04.27
Power Sensor	KEYSIGHT	U2063XA	MY58000247	2025.06.16	2026.06.15
Spectrum Analyzer	KEYSIGHT	N9020A	MY52510065	2025.06.16	2026.06.15
Signaling Unit	ROHDE&SCHWARZ	CMW500	171150	2025.04.28	2026.04.27
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	01631	2025.02.22	2028.02.21
Test Antenna-Horn	A-INFO	LB-180400KF	J211060273	2024.06.15	2027.06.14
Anechoic Chamber	RAINFORD	9m*6m*6m	144	2025.01.04	2028.01.03
Amplifier	COM-MV	LSCX_LNA1-12G-01	180602	2025.06.17	2026.06.16
Amplifier	COM-MV	XKu_LNA7-18G-01	180601	2025.06.17	2026.06.16
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2025.06.16	2026.06.15
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9168	9168-01162	2023.08.04	2026.08.03
Test Antenna-Loop	SCHWARZBECK	FMZB 1519	1519-037	2024.01.23	2027.01.22
Amplifier	COM-MV	ZT30-1000M	B2018054558	2024.11.28	2025.11.27
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	130	2024.07.13	2027.07.12
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2025.06.16	2026.06.15
LISN	SCHWARZBECK	NSLK 8127	8127-687	2025.04.29	2026.04.28
Shielded Enclosure	YiHeng Electronic Co., Ltd	3.5m*3.1m*2.8 m	112	2025.02.14	2028.02.13

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V22.930	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.8°C
Humidity	4%


4.5 Description of Test Setup

4.5.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.5.2 For AC Power Supply Port Test




(Diagram 2)

4.5.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.5.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.5.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.6 Measurement Results Explanation Example

4.6.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (f)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Frequency Hopping Systems

5.2.1 Relevant Standards

FCC §15.247(a) (1) (i) (ii) (iii) (iv); FCC §15.247(g); FCC §15.247(h)

Describe how the hopping sequence is generated. Provide an example of the hopping sequence channels, to demonstrate that the sequence meets the requirement specified in the definition of an FHSS system. Per the definition in Section 2.1(c), the hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.

Describe how each individual EUT meets the requirement that each of its hopping channels is used equally on average (e.g., that each new transmission event begins on the next channel in the hopping sequence after the final channel used in the previous transmission event).

Describe how the associated receiver(s) complies with the requirement that the input bandwidth (either RF or IF) matches the bandwidth of the transmitted signal.

Describe how the associated receiver(s) has the ability to shift frequencies in synchronization with the transmitted signals.


For short burst systems, describe how the EUT complies with the requirement that it be designed to be capable of operating as a true frequency hopping system. Specifically, the device shall comply with the equal frequency use and pseudorandom hopping sequence requirement when transmitting in short bursts, and shall be designed to comply when presented with continuous data (or information) stream.

Describe how the EUT complies with the requirement that it not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

5.2.2 Description of the systems

1. According to the preset procedure of the whole network, all the stations in the automatic control network synchronously change the frequency multiple times within one second, and temporarily stay on each frequency hopping channel. Periodic synchronization signaling is sent from the primary station, instructing all slaves to simultaneously change the operating frequency, then the hopping sequence is generated.
2. The hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.

Reference Documents



3. Channels are classified into two categories, used and unused, where used channels are part of the hopping sequence and unused channels are replaced in the hopping sequence by used channels in a pseudo-random way. Make each individual EUT meets the requirement that each of its hopping channels is used equally on average.
4. The input bandwidth and transmitted bandwidth are both 1MHz, the associated receiver(s) complies with the requirement that the input bandwidth matches the bandwidth of the transmitted signal.
5. Connected devices communicate on the same physical channel by synchronizing with a common clock and hopping sequence.
6. EUT isn't short burst systems.
7. EUT can't have the ability to be coordinated with other FHSS systems in an effort.

5.3 Number of Hopping Frequencies

5.3.1 Limit

FCC §15.247(a) (1) (iii); RSS-247, 5.1 (d)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

5.3.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = The frequency band of operation

RBW = To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.3.4 Test Result

Please refer to ANNEX A.1.

5.4 Peak Output Power and E.I.R.P

5.4.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

RSS-247, 5.4 (b)

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W and the e.i.r.p. shall not exceed 4 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W and the e.i.r.p. shall not exceed 0.5 W if the hopset uses less than 75 hopping channels (see Section 5.4(5) for exceptions).

5.4.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

EIRP= Maximum peak conducted output power +Antenna Gain.

5.4.4 Test Result

Please refer to ANNEX A.2.

5.5 Occupied Bandwidth

5.5.1 Limit

FCC §15.247(a); RSS-247, 5.1 (a)

Measurement of the 20dB bandwidth of the modulated signal.

5.5.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = in the range of 1% to 5% of the OBW

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

5.5.4 Test Result

Please refer to ANNEX A.3.

5.6 Carrier Frequency Separation

5.6.1 Limit

FCC §15.247(a); RSS-247, 5.1 (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 2/3 of the 20 dB bandwidth of the hopping channel, whichever is greater.

5.6.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span

Video (or Average) Bandwidth (VBW) $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

5.6.4 Test Result

Please refer to ANNEX A.4.

5.7 Time of Occupancy (Dwell time)

5.7.1 Limit

FCC §15.247(a); RSS-247, 5.1 (d)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.7.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

Span: Zero span, centered on a hopping channel

RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected dwell time per channel

Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel

Detector function: Peak

Trace: Max hold

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

The average time of occupancy on any channel within the Period can be calculated with formulas:

For GFSK and 8-DPSK:

For DH1 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 2) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH3 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 4) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH5 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For AFH Mode:

For DH1 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (800 / 2) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$

For DH3 package type

$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (800 / 4) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$

$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$

For DH5 package type

$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (800 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$

$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

5.7.4 Test Result

Please refer to ANNEX A.5.

5.8 Conducted Spurious Emission & Authorized-band band-edge

5.8.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.8.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW = 300 kHz

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.8.4 Test Result

Please refer to ANNEX A.6.

5.9 Conducted Emission

5.9.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.9.2 Test Setup

See section 4.5.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.9.4 Test Result

Please refer to ANNEX A.7.

5.10 Radiated Spurious Emission

5.10.1 Limit

FCC §15.209&15.247(d); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.10.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.10.4 Test Result

Please refer to ANNEX A.8.

5.11 Band Edge (Restricted-band band-edge)

5.11.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.11.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.11.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.11.4 Test Result

Please refer to ANNEX A.9.

ANNEX A TEST RESULT


A.1 Number of Hopping Frequency

Test Data


Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	79	15	Pass
8-DPSK	2400 - 2483.5	79	15	Pass

Test Plots


GFSK 2.4 GHz ~ 2.4415 GHz



GFSK 2.4415 GHz ~ 2.4835 GHz



8-DPSK 2.4 GHz ~ 2.4415 GHz



8-DPSK 2.4415 GHz ~ 2.4835 GHz



A.2 Peak Output Power and E.I.R.P

Peak Power Test Data

Channel	Measured Output Peak Power						Limit		Verdict
	GFSK		$\pi/4$ -DQPSK		8-DPSK		dBm	mW	
	dBm	mW	dBm	mW	dBm	mW			
Low	2.51	1.78	5.13	3.26	5.77	3.77	21	125	Pass
Middle	2.06	1.61	4.69	2.95	5.31	3.40			Pass
High	1.92	1.56	4.55	2.85	5.13	3.25			Pass

E.I.R.P Test Data (For ISSED)

PCB Antenna

FOD Antenna									
Channel	E.I.R.P						Limit		Verdict
	GFSK		$\pi/4$ -DQPSK		8-DPSK		dBm	mW	
	dBm	mW	dBm	mW	dBm	mW			
Low	6.71	4.69	9.33	8.57	9.97	9.92	36	4000	Pass
Middle	6.26	4.23	8.89	7.75	9.51	8.94			Pass
High	6.12	4.09	8.75	7.49	9.33	8.56			Pass

FPC Antenna


Channel	E.I.R.P						Limit		Verdict
	GFSK		$\pi/4$ -DQPSK		8-DPSK		dBm	mW	
	dBm	mW	dBm	mW	dBm	mW			
Low	5.94	3.93	8.56	7.18	9.20	8.31	36	4000	Pass
Middle	5.49	3.54	8.12	6.49	8.74	7.49			Pass
High	5.35	3.43	7.98	6.28	8.56	7.17			Pass

Dipole Antenna


Channel	E.I.R.P						Limit		Verdict
	GFSK		$\pi/4$ -DQPSK		8-DPSK		dBm	mW	
	dBm	mW	dBm	mW	dBm	mW			
Low	4.61	2.89	7.23	5.29	7.87	6.12	36	4000	Pass
Middle	4.16	2.61	6.79	4.78	7.41	5.51			Pass
High	4.02	2.52	6.65	4.62	7.23	5.28			Pass

Test Plots


GFSK LOW CHANNEL




GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



$\pi/4$ -DQPSK LOW CHANNEL



$\pi/4$ -DQPSK MIDDLE CHANNEL




$\pi/4$ -DQPSK HIGH CHANNEL




8-DPSK LOW CHANNEL



8-DPSK MIDDLE CHANNEL



8-DPSK HIGH CHANNEL



A.3 20 dB and 99% bandwidth

Test Data

GFSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	0.967500	0.879610
Middle	0.967500	0.881890
High	0.967500	0.877660
$\pi/4$ -DQPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.342500	1.186900
Middle	1.350100	1.187700
High	1.350100	1.187200
8-DPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.312500	1.186400
Middle	1.312500	1.187100
High	1.312500	1.186500

Test Plots

20 dB Bandwidth

GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL

 $\pi/4$ -DQPSK LOW CHANNEL $\pi/4$ -DQPSK MIDDLE CHANNEL

$\pi/4$ -DQPSK HIGH CHANNEL



8-DPSK LOW CHANNEL



8-DPSK MIDDLE CHANNEL



8-DPSK HIGH CHANNEL



99% Bandwidth



GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL

 $\pi/4$ -DQPSK LOW CHANNEL $\pi/4$ -DQPSK MIDDLE CHANNEL

$\pi/4$ -DQPSK HIGH CHANNEL



8-DPSK LOW CHANNEL



8-DPSK MIDDLE CHANNEL



8-DPSK HIGH CHANNEL




A.4 Hopping Frequency Separation

Test Data

Mode	Frequency separation (MHz)	2/3 of the 20 dB Bandwidth (MHz)	Verdict
GFSK	1.000	0.645	Pass
8-DPSK	1.000	0.875	Pass

Test Plots

GFSK



8-DPSK



A.5 Average Time of Occupancy

Test Data

GFSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.379	121.344	0.4	Pass
DH 3	1.638	262.080	0.4	Pass
DH 5	2.880	307.200	0.4	Pass
8-DPSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
3DH 1	0.382	122.368	0.4	Pass
3DH 3	1.631	260.960	0.4	Pass
3DH 5	2.892	308.480	0.4	Pass
AFH Mode				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.381	60.928	0.4	Pass
DH 3	1.631	130.480	0.4	Pass
DH 5	2.892	154.240	0.4	Pass

Test Plots


GFSK DH1



GFSK DH3




GFSK DH5




8-DPSK 3DH1




8-DPSK 3DH3




8-DPSK 3DH5




AFH Mode DH1



AFH Mode DH3



AFH Mode DH5



A.6 Conducted Spurious Emissions & Authorized-band band-edge

Test Data

GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-34.70	2.38	-17.62	Pass
Middle	-33.33	1.92	-18.08	Pass
High	-34.15	1.79	-18.21	Pass
8-DPSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-33.70	2.61	-17.39	Pass
Middle	-34.13	1.94	-18.06	Pass
High	-33.61	1.96	-18.04	Pass


Hopping Mode				
Mode	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
GFSK	-33.96	2.37	-17.63	Pass
8-DPSK	-33.93	2.42	-17.58	Pass

Test Plots


GFSK LOW CHANNEL, CARRIER LEVEL




GFSK LOW CHANNEL, BAND EDGE




GFSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




GFSK MIDDLE CHANNEL, CARRIER LEVEL




GFSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




GFSK HIGH CHANNEL, CARRIER LEVEL




GFSK HIGH CHANNEL, BAND EDGE




GFSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



8-DPSK LOW CHANNEL, CARRIER LEVEL




8-DPSK LOW CHANNEL, BAND EDGE




8-DPSK LOW CHANNEL, SPURIOUS

30 MHz ~ 3 GHz




8-DPSK LOW CHANNEL, SPURIOUS


3 GHz ~ 25 GHz




8-DPSK MIDDLE CHANNEL, CARRIER LEVEL




8-DPSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




8-DPSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




8-DPSK HIGH CHANNEL, CARRIER LEVEL




8-DPSK HIGH CHANNEL, BAND EDGE




8-DPSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




8-DPSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz






GFSK HOPPING, CARRIER LEVEL




GFSK HOPPING BAND EDGE (LOW)




GFSK HOPPING BAND EDGE (HIGH)

GFSK Hopping Mode, SPURIOUS
30 MHz ~ 3 GHzGFSK Hopping Mode, SPURIOUS
3GHz ~ 25 GHz


8-DPSK HOPPING, CARRIER LEVEL



8-DPSK Hopping BAND EDGE (LOW)



8-DPSK Hopping BAND EDGE (HIGH)

8-DPSK Hopping Mode, SPURIOUS
30 MHz ~ 3 GHz8-DPSK Hopping Mode, SPURIOUS
3GHz ~ 25 GHz

A.7 Conducted Emissions

Note ¹: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.

Note ²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.


Note ³: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

PCB Antenna

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.360	40.26	10.78	58.73	18.47	Peak	L	Pass
1**	0.360	26.04	10.78	48.73	22.69	AV	L	Pass
2	0.716	41.83	10.55	56.00	14.17	Peak	L	Pass
2**	0.716	27.63	10.55	46.00	18.37	AV	L	Pass
3	1.126	38.13	10.28	56.00	17.87	Peak	L	Pass
3**	1.126	26.35	10.28	46.00	19.65	AV	L	Pass
4	2.136	37.77	10.18	56.00	18.23	Peak	L	Pass
4**	2.136	24.74	10.18	46.00	21.26	AV	L	Pass
5	7.798	37.55	10.36	60.00	22.45	Peak	L	Pass
5**	7.798	24.72	10.36	50.00	25.28	AV	L	Pass
6	13.834	36.99	10.59	60.00	23.01	Peak	L	Pass
6**	13.834	24.70	10.59	50.00	25.30	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C




No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.350	41.09	10.82	58.96	17.87	Peak	N	Pass
1**	0.350	26.81	10.82	48.96	22.15	AV	N	Pass
2	0.712	41.59	10.59	56.00	14.41	Peak	N	Pass
2**	0.712	27.02	10.59	46.00	18.98	AV	N	Pass
3	1.304	37.83	10.52	56.00	18.17	Peak	N	Pass
3**	1.304	24.76	10.52	46.00	21.24	AV	N	Pass
4	2.308	38.30	10.31	56.00	17.70	Peak	N	Pass
4**	2.308	24.61	10.31	46.00	21.39	AV	N	Pass
5	3.330	38.14	10.46	56.00	17.86	Peak	N	Pass
5**	3.330	24.93	10.46	46.00	21.07	AV	N	Pass
6	4.318	37.77	10.27	56.00	18.23	Peak	N	Pass
6**	4.318	25.23	10.27	46.00	20.77	AV	N	Pass

FPC Antenna

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.306	39.05	9.94	60.08	21.03	Peak	L	Pass
1**	0.306	25.47	9.94	50.08	24.61	AV	L	Pass
2	0.666	40.39	10.41	56.00	15.61	Peak	L	Pass
2**	0.666	27.30	10.41	46.00	18.70	AV	L	Pass
3	0.874	39.54	10.47	56.00	16.46	Peak	L	Pass
3**	0.874	25.59	10.47	46.00	20.41	AV	L	Pass
4	1.400	39.37	9.80	56.00	16.63	Peak	L	Pass
4**	1.400	24.38	9.80	46.00	21.62	AV	L	Pass
5	2.076	37.55	10.21	56.00	18.45	Peak	L	Pass
5**	2.076	23.94	10.21	46.00	22.06	AV	L	Pass
6	4.112	38.24	10.29	56.00	17.76	Peak	L	Pass
6**	4.112	24.98	10.29	46.00	21.02	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C




No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.478	39.22	10.06	56.37	17.15	Peak	N	Pass
1**	0.478	25.53	10.06	46.37	20.84	AV	N	Pass
2	0.624	42.13	10.24	56.00	13.87	Peak	N	Pass
2**	0.624	28.28	10.24	46.00	17.72	AV	N	Pass
3	0.880	40.36	10.42	56.00	15.64	Peak	N	Pass
3**	0.880	27.90	10.42	46.00	18.10	AV	N	Pass
4	1.714	39.48	10.24	56.00	16.52	Peak	N	Pass
4**	1.714	24.42	10.24	46.00	21.58	AV	N	Pass
5	2.724	38.93	10.17	56.00	17.07	Peak	N	Pass
5**	2.724	24.85	10.17	46.00	21.15	AV	N	Pass
6	7.184	36.33	10.45	60.00	23.67	Peak	N	Pass
6**	7.184	24.76	10.45	50.00	25.24	AV	N	Pass

Dipole Antenna

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.198	38.18	9.84	63.69	25.51	Peak	L	Pass
1**	0.198	26.90	9.84	53.69	26.79	AV	L	Pass
2	0.398	41.17	10.62	57.90	16.73	Peak	L	Pass
2**	0.398	28.21	10.62	47.90	19.69	AV	L	Pass
3	0.520	41.96	10.06	56.00	14.04	Peak	L	Pass
3**	0.520	27.39	10.06	46.00	18.61	AV	L	Pass
4	0.776	41.38	10.42	56.00	14.62	Peak	L	Pass
4**	0.776	26.31	10.42	46.00	19.69	AV	L	Pass
5	2.396	37.52	10.35	56.00	18.48	Peak	L	Pass
5**	2.396	24.44	10.35	46.00	21.56	AV	L	Pass
6	25.616	38.33	10.98	60.00	21.67	Peak	L	Pass
6**	25.616	25.74	10.98	50.00	24.26	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.394	40.73	10.64	57.98	17.25	Peak	N	Pass
1**	0.394	26.54	10.64	47.98	21.44	AV	N	Pass
2	0.466	41.33	10.07	56.58	15.25	Peak	N	Pass
2**	0.466	25.56	10.07	46.58	21.02	AV	N	Pass
3	0.794	39.59	10.55	56.00	16.41	Peak	N	Pass
3**	0.794	26.71	10.55	46.00	19.29	AV	N	Pass
4	1.548	36.92	10.22	56.00	19.08	Peak	N	Pass
4**	1.548	24.30	10.22	46.00	21.70	AV	N	Pass
5	5.220	37.23	10.48	60.00	22.77	Peak	N	Pass
5**	5.220	27.00	10.48	50.00	23.00	AV	N	Pass
6	18.734	37.50	11.16	60.00	22.50	Peak	N	Pass
6**	18.734	25.32	11.16	50.00	24.68	AV	N	Pass

A.8 Radiated Spurious Emission

Note ¹: The symbol of "--" in the table which means not application.

Note ²: For the test data above 1 GHz, according the ANSI C63.10-2020, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note ³: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and DH5-Hopping mode is the worst.


Note ⁴: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Test Data and Plots

PCB Antenna


30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	55.941	25.12	-27.15	29.5	4.38	Peak	340.00	200	Horizontal	Pass
2	113.157	16.25	-28.74	33.0	16.75	Peak	360.00	200	Horizontal	Pass
3	127.946	16.61	-27.47	33.0	16.39	Peak	63.00	300	Horizontal	Pass
4	387.113	27.28	-23.06	35.5	8.22	Peak	0.00	300	Horizontal	Pass
5	826.656	29.01	-11.94	35.5	6.49	Peak	360.00	200	Horizontal	Pass
6	962.179	30.03	-9.48	43.5	13.47	Peak	296.00	300	Horizontal	Pass

30 MHz to 1 GHz, ANT V

10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	110.975	24.39	-28.91	33.0	8.61	Peak	37.00	400	Vertical	Pass
2	199.950	17.25	-29.18	33.0	15.75	Peak	204.00	100	Vertical	Pass
3	232.437	17.72	-28.70	35.5	17.78	Peak	0.00	100	Vertical	Pass
4	420.812	23.19	-22.05	35.5	12.31	Peak	358.00	400	Vertical	Pass
5	783.017	27.75	-12.95	35.5	7.75	Peak	0.00	300	Vertical	Pass
6	937.936	30.59	-9.72	35.5	4.91	Peak	360.00	200	Vertical	Pass

FPC Antenna

30 MHz to 1 GHz, ANT H


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	54.244	25.84	-27.10	29.5	3.66	Peak	360.00	400	Horizontal	Pass
2	64.426	20.93	-27.99	29.5	8.57	Peak	360.00	400	Horizontal	Pass
3	73.639	20.24	-29.45	29.5	9.26	Peak	360.00	400	Horizontal	Pass
4	300.562	21.49	-25.45	35.5	14.01	Peak	248.00	400	Horizontal	Pass
5	387.356	25.46	-23.06	35.5	10.04	Peak	0.00	300	Horizontal	Pass
6	972.119	30.38	-9.36	43.5	13.12	Peak	0.00	300	Horizontal	Pass

30 MHz to 1 GHz, ANT V

10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	73.639	17.91	-29.45	29.5	11.59	Peak	58.00	400	Vertical	Pass
2	126.006	15.13	-27.67	33.0	17.87	Peak	329.00	300	Vertical	Pass
3	199.465	16.78	-29.18	33.0	16.22	Peak	69.00	100	Vertical	Pass
4	300.805	20.70	-25.44	35.5	14.80	Peak	210.00	100	Vertical	Pass
5	421.297	24.85	-22.02	35.5	10.65	Peak	2.00	400	Vertical	Pass
6	920.722	29.70	-10.30	35.5	5.80	Peak	31.00	200	Vertical	Pass

Dipole Antenna

30 MHz to 1 GHz, ANT H


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	54.244	26.00	-27.10	29.5	3.50	Peak	0.00	200	Horizontal	Pass
2	56.668	25.58	-27.24	29.5	3.92	Peak	0.00	400	Horizontal	Pass
3	73.639	22.31	-29.45	29.5	7.19	Peak	205.00	400	Horizontal	Pass
4	127.946	17.52	-27.47	33.0	15.48	Peak	360.00	300	Horizontal	Pass
5	287.956	20.52	-25.91	35.5	14.98	Peak	237.00	200	Horizontal	Pass
6	390.507	27.15	-22.85	35.5	8.35	Peak	0.00	200	Horizontal	Pass

30 MHz to 1 GHz, ANT V

10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	54.971	15.38	-27.15	29.5	14.12	Peak	101.00	100	Vertical	Pass
2	73.639	19.77	-29.45	29.5	9.73	Peak	188.00	100	Vertical	Pass
3	115.824	14.85	-28.58	33.0	18.15	Peak	123.00	200	Vertical	Pass
4	199.708	17.46	-29.18	33.0	15.54	Peak	360.00	200	Vertical	Pass
5	300.562	20.19	-25.45	35.5	15.31	Peak	134.00	100	Vertical	Pass
6	987.151	31.15	-9.40	43.5	12.35	Peak	210.00	200	Vertical	Pass

Note ¹: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note ²: The spurious from 18GHz-25GHz is noise only, do not show on the report.

PCB Antenna

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1336.378	40.36	74.0	33.64	Peak	81.00	200	Horizontal	Pass
1**	1336.378	35.00	54.0	19.00	AV	81.00	200	Horizontal	Pass
2	2973.392	52.75	74.0	21.25	Peak	250.00	300	Horizontal	Pass
2**	2973.392	38.33	54.0	15.67	AV	250.00	300	Horizontal	Pass
3	4914.400	51.92	74.0	22.08	Peak	199.00	200	Horizontal	Pass
3**	4914.400	39.40	54.0	14.60	AV	199.00	200	Horizontal	Pass
4	7624.234	51.29	74.0	22.71	Peak	130.00	200	Horizontal	Pass
4**	7624.234	43.10	54.0	10.90	AV	130.00	200	Horizontal	Pass
5	12475.057	56.06	74.0	17.94	Peak	295.00	100	Horizontal	Pass
5**	12475.057	46.91	54.0	7.09	AV	295.00	100	Horizontal	Pass
6	16861.524	56.45	74.0	17.55	Peak	27.00	100	Horizontal	Pass
6**	16861.524	47.34	54.0	6.66	AV	27.00	100	Horizontal	Pass

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1464.157	44.55	74.0	29.45	Peak	16.00	300	Vertical	Pass
1**	1464.157	30.33	54.0	23.67	AV	16.00	300	Vertical	Pass
2	2991.439	48.37	74.0	25.63	Peak	266.00	200	Vertical	Pass
2**	2991.439	37.77	54.0	16.23	AV	266.00	200	Vertical	Pass
3	4822.144	49.77	74.0	24.23	Peak	53.00	200	Vertical	Pass
3**	4822.144	39.79	54.0	14.21	AV	53.00	200	Vertical	Pass
4	7965.357	54.42	74.0	19.58	Peak	346.00	200	Vertical	Pass
4**	7965.357	46.88	54.0	7.12	AV	346.00	200	Vertical	Pass
5	12445.475	56.07	74.0	17.93	Peak	70.00	300	Vertical	Pass
5**	12445.475	43.15	54.0	10.85	AV	70.00	300	Vertical	Pass
6	17456.551	57.30	74.0	16.70	Peak	108.00	200	Vertical	Pass
6**	17456.551	44.22	54.0	9.78	AV	108.00	200	Vertical	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1338.701	39.57	74.0	34.43	Peak	32.00	200	Horizontal	Pass
1**	1338.701	32.69	54.0	21.31	AV	32.00	200	Horizontal	Pass
2	2974.063	49.07	74.0	24.93	Peak	288.00	400	Horizontal	Pass
2**	2974.063	41.07	54.0	12.93	AV	288.00	400	Horizontal	Pass
3	4913.210	52.23	74.0	21.77	Peak	10.00	200	Horizontal	Pass
3**	4913.210	37.65	54.0	16.35	AV	10.00	200	Horizontal	Pass
4	7626.225	52.82	74.0	21.18	Peak	38.00	200	Horizontal	Pass
4**	7626.225	42.06	54.0	11.94	AV	38.00	200	Horizontal	Pass
5	12476.326	53.96	74.0	20.04	Peak	260.00	200	Horizontal	Pass
5**	12476.326	42.97	54.0	11.03	AV	260.00	200	Horizontal	Pass
6	16864.183	54.47	74.0	19.53	Peak	342.00	400	Horizontal	Pass
6**	16864.183	47.35	54.0	6.65	AV	342.00	400	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1461.801	43.16	74.0	30.84	Peak	26.00	200	Vertical	Pass
1**	1461.801	33.90	54.0	20.10	AV	26.00	200	Vertical	Pass
2	2989.178	52.76	74.0	21.24	Peak	337.00	200	Vertical	Pass
2**	2989.178	42.65	54.0	11.35	AV	337.00	200	Vertical	Pass
3	4817.865	51.73	74.0	22.27	Peak	338.00	200	Vertical	Pass
3**	4817.865	40.53	54.0	13.47	AV	338.00	200	Vertical	Pass
4	7968.507	50.65	74.0	23.35	Peak	333.00	300	Vertical	Pass
4**	7968.507	44.01	54.0	9.99	AV	333.00	300	Vertical	Pass
5	12444.227	52.84	74.0	21.16	Peak	140.00	300	Vertical	Pass
5**	12444.227	43.20	54.0	10.80	AV	140.00	300	Vertical	Pass
6	17454.796	54.40	74.0	19.60	Peak	184.00	400	Vertical	Pass
6**	17454.796	47.44	54.0	6.56	AV	184.00	400	Vertical	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1336.844	41.61	74.0	32.39	Peak	252.00	200	Horizontal	Pass
1**	1336.844	31.47	54.0	22.53	AV	252.00	200	Horizontal	Pass
2	2978.169	53.94	74.0	20.06	Peak	292.00	100	Horizontal	Pass
2**	2978.169	42.15	54.0	11.85	AV	292.00	100	Horizontal	Pass
3	4918.598	49.41	74.0	24.59	Peak	292.00	200	Horizontal	Pass
3**	4918.598	42.19	54.0	11.81	AV	292.00	200	Horizontal	Pass
4	7630.011	54.51	74.0	19.49	Peak	148.00	400	Horizontal	Pass
4**	7630.011	43.27	54.0	10.73	AV	148.00	400	Horizontal	Pass
5	12473.892	55.99	74.0	18.01	Peak	84.00	300	Horizontal	Pass
5**	12473.892	46.79	54.0	7.21	AV	84.00	300	Horizontal	Pass
6	16859.193	53.90	74.0	20.10	Peak	200.00	200	Horizontal	Pass
6**	16859.193	48.39	54.0	5.61	AV	200.00	200	Horizontal	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1465.139	40.57	74.0	33.43	Peak	260.00	100	Vertical	Pass
1**	1465.139	34.45	54.0	19.55	AV	260.00	100	Vertical	Pass
2	2988.237	48.03	74.0	25.97	Peak	238.00	300	Vertical	Pass
2**	2988.237	40.79	54.0	13.21	AV	238.00	300	Vertical	Pass
3	4819.673	49.45	74.0	24.55	Peak	296.00	200	Vertical	Pass
3**	4819.673	40.71	54.0	13.29	AV	296.00	200	Vertical	Pass
4	7967.517	54.63	74.0	19.37	Peak	322.00	200	Vertical	Pass
4**	7967.517	45.47	54.0	8.53	AV	322.00	200	Vertical	Pass
5	12445.782	55.97	74.0	18.03	Peak	10.00	100	Vertical	Pass
5**	12445.782	46.07	54.0	7.93	AV	10.00	100	Vertical	Pass
6	17452.640	52.60	74.0	21.40	Peak	220.00	200	Vertical	Pass
6**	17452.640	45.68	54.0	8.32	AV	220.00	200	Vertical	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1283.801	42.63	74.0	31.37	Peak	331.00	100	Horizontal	Pass
1**	1283.801	30.85	54.0	23.15	AV	331.00	100	Horizontal	Pass
2	2773.255	49.57	74.0	24.43	Peak	95.00	100	Horizontal	Pass
2**	2773.255	45.35	54.0	8.65	AV	95.00	100	Horizontal	Pass
3	5168.064	50.82	74.0	23.18	Peak	156.00	200	Horizontal	Pass
3**	5168.064	41.14	54.0	12.86	AV	156.00	200	Horizontal	Pass
4	6806.800	57.58	74.0	16.42	Peak	154.00	400	Horizontal	Pass
4**	6806.800	45.26	54.0	8.74	AV	154.00	400	Horizontal	Pass
5	13467.374	55.37	74.0	18.63	Peak	88.00	400	Horizontal	Pass
5**	13467.374	42.64	54.0	11.36	AV	88.00	400	Horizontal	Pass
6	17467.468	58.13	74.0	15.87	Peak	161.00	100	Horizontal	Pass
6**	17467.468	45.01	54.0	8.99	AV	161.00	100	Horizontal	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1283.487	46.41	74.0	27.59	Peak	233.00	400	Vertical	Pass
1**	1283.487	33.13	54.0	20.87	AV	233.00	400	Vertical	Pass
2	2772.401	52.00	74.0	22.00	Peak	207.00	300	Vertical	Pass
2**	2772.401	44.72	54.0	9.28	AV	207.00	300	Vertical	Pass
3	5163.602	53.77	74.0	20.23	Peak	154.00	200	Vertical	Pass
3**	5163.602	42.14	54.0	11.86	AV	154.00	200	Vertical	Pass
4	6801.619	52.76	74.0	21.24	Peak	92.00	400	Vertical	Pass
4**	6801.619	43.37	54.0	10.63	AV	92.00	400	Vertical	Pass
5	13467.292	53.76	74.0	20.24	Peak	277.00	100	Vertical	Pass
5**	13467.292	44.68	54.0	9.32	AV	277.00	100	Vertical	Pass
6	17459.691	59.64	74.0	14.36	Peak	242.00	100	Vertical	Pass
6**	17459.691	46.11	54.0	7.89	AV	242.00	100	Vertical	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1287.379	41.53	74.0	32.47	Peak	75.00	200	Horizontal	Pass
1**	1287.379	35.86	54.0	18.14	AV	75.00	200	Horizontal	Pass
2	2772.793	50.35	74.0	23.65	Peak	64.00	400	Horizontal	Pass
2**	2772.793	42.04	54.0	11.96	AV	64.00	400	Horizontal	Pass
3	5167.189	49.86	74.0	24.14	Peak	282.00	200	Horizontal	Pass
3**	5167.189	44.49	54.0	9.51	AV	282.00	200	Horizontal	Pass
4	6805.649	53.83	74.0	20.17	Peak	5.00	200	Horizontal	Pass
4**	6805.649	45.35	54.0	8.65	AV	5.00	200	Horizontal	Pass
5	13467.317	54.04	74.0	19.96	Peak	111.00	300	Horizontal	Pass
5**	13467.317	43.53	54.0	10.47	AV	111.00	300	Horizontal	Pass
6	17469.454	54.58	74.0	19.42	Peak	54.00	200	Horizontal	Pass
6**	17469.454	47.56	54.0	6.44	AV	54.00	200	Horizontal	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1287.592	46.07	74.0	27.93	Peak	199.00	200	Vertical	Pass
1**	1287.592	34.49	54.0	19.51	AV	199.00	200	Vertical	Pass
2	2773.359	52.90	74.0	21.10	Peak	317.00	100	Vertical	Pass
2**	2773.359	47.68	54.0	6.32	AV	317.00	100	Vertical	Pass
3	5160.559	55.63	74.0	18.37	Peak	71.00	200	Vertical	Pass
3**	5160.559	43.52	54.0	10.48	AV	71.00	200	Vertical	Pass
4	6805.520	49.90	74.0	24.10	Peak	299.00	400	Vertical	Pass
4**	6805.520	44.11	54.0	9.89	AV	299.00	400	Vertical	Pass
5	13467.944	52.89	74.0	21.11	Peak	84.00	300	Vertical	Pass
5**	13467.944	43.65	54.0	10.35	AV	84.00	300	Vertical	Pass
6	17466.040	57.68	74.0	16.32	Peak	314.00	300	Vertical	Pass
6**	17466.040	47.20	54.0	6.80	AV	314.00	300	Vertical	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1281.711	41.10	74.0	32.90	Peak	240.00	300	Horizontal	Pass
1**	1281.711	34.44	54.0	19.56	AV	240.00	300	Horizontal	Pass
2	2768.265	51.73	74.0	22.27	Peak	213.00	300	Horizontal	Pass
2**	2768.265	43.88	54.0	10.12	AV	213.00	300	Horizontal	Pass
3	5171.067	49.28	74.0	24.72	Peak	359.00	200	Horizontal	Pass
3**	5171.067	41.94	54.0	12.06	AV	359.00	200	Horizontal	Pass
4	6807.893	54.07	74.0	19.93	Peak	61.00	300	Horizontal	Pass
4**	6807.893	47.77	54.0	6.23	AV	61.00	300	Horizontal	Pass
5	13470.124	55.08	74.0	18.92	Peak	226.00	300	Horizontal	Pass
5**	13470.124	45.36	54.0	8.64	AV	226.00	300	Horizontal	Pass
6	17466.568	57.59	74.0	16.41	Peak	179.00	200	Horizontal	Pass
6**	17466.568	47.60	54.0	6.40	AV	179.00	200	Horizontal	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1280.345	43.49	74.0	30.51	Peak	101.00	400	Vertical	Pass
1**	1280.345	33.84	54.0	20.16	AV	101.00	400	Vertical	Pass
2	2769.226	55.73	74.0	18.27	Peak	313.00	200	Vertical	Pass
2**	2769.226	46.01	54.0	7.99	AV	313.00	200	Vertical	Pass
3	5167.682	52.23	74.0	21.77	Peak	247.00	200	Vertical	Pass
3**	5167.682	45.99	54.0	8.01	AV	247.00	200	Vertical	Pass
4	6803.423	55.66	74.0	18.34	Peak	144.00	300	Vertical	Pass
4**	6803.423	45.24	54.0	8.76	AV	144.00	300	Vertical	Pass
5	13469.669	54.40	74.0	19.60	Peak	211.00	400	Vertical	Pass
5**	13469.669	43.07	54.0	10.93	AV	211.00	400	Vertical	Pass
6	17460.580	61.31	74.0	12.69	Peak	122.00	400	Vertical	Pass
6**	17460.580	48.73	54.0	5.27	AV	122.00	400	Vertical	Pass

FPC Antenna**GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT H**

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1335.858	40.45	74.0	33.55	Peak	22.00	300	Horizontal	Pass
1**	1335.858	29.96	54.0	24.04	AV	22.00	300	Horizontal	Pass
2	2979.982	48.68	74.0	25.32	Peak	130.00	300	Horizontal	Pass
2**	2979.982	38.10	54.0	15.90	AV	130.00	300	Horizontal	Pass
3	4912.308	49.76	74.0	24.24	Peak	18.00	200	Horizontal	Pass
3**	4912.308	38.88	54.0	15.12	AV	18.00	200	Horizontal	Pass
4	7627.216	51.66	74.0	22.34	Peak	94.00	400	Horizontal	Pass
4**	7627.216	44.56	54.0	9.44	AV	94.00	400	Horizontal	Pass
5	12476.516	55.05	74.0	18.95	Peak	224.00	300	Horizontal	Pass
5**	12476.516	42.79	54.0	11.21	AV	224.00	300	Horizontal	Pass
6	16862.773	57.54	74.0	16.46	Peak	100.00	400	Horizontal	Pass
6**	16862.773	44.57	54.0	9.43	AV	100.00	400	Horizontal	Pass

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1459.252	42.81	74.0	31.19	Peak	234.00	300	Vertical	Pass
1**	1459.252	30.54	54.0	23.46	AV	234.00	300	Vertical	Pass
2	2991.489	50.80	74.0	23.20	Peak	211.00	100	Vertical	Pass
2**	2991.489	41.19	54.0	12.81	AV	211.00	100	Vertical	Pass
3	4823.589	49.45	74.0	24.55	Peak	340.00	200	Vertical	Pass
3**	4823.589	38.06	54.0	15.94	AV	340.00	200	Vertical	Pass
4	7969.365	55.04	74.0	18.96	Peak	343.00	300	Vertical	Pass
4**	7969.365	45.91	54.0	8.09	AV	343.00	300	Vertical	Pass
5	12444.886	52.01	74.0	21.99	Peak	295.00	300	Vertical	Pass
5**	12444.886	46.26	54.0	7.74	AV	295.00	300	Vertical	Pass
6	17455.871	57.63	74.0	16.37	Peak	314.00	400	Vertical	Pass
6**	17455.871	45.26	54.0	8.74	AV	314.00	400	Vertical	Pass

Dipole Antenna

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1007.900	44.38	74.0	29.62	Peak	120.00	400	Horizontal	Pass
1**	1007.900	36.35	54.0	17.65	AV	120.00	400	Horizontal	Pass
2	2440.800	97.34	74.0	-23.34	Peak	166.00	150	Horizontal	N/A
2**	2440.800	96.56	54.0	-42.56	AV	166.00	150	Horizontal	N/A
3	4887.000	50.00	74.0	24.00	Peak	0.00	200	Horizontal	Pass
3**	4887.000	39.97	54.0	14.03	AV	0.00	200	Horizontal	Pass
4	6898.000	54.06	74.0	19.94	Peak	16.00	200	Horizontal	Pass
4**	6898.000	44.67	54.0	9.33	AV	16.00	200	Horizontal	Pass
5	12490.888	54.96	74.0	19.04	Peak	0.00	100	Horizontal	Pass
5**	12490.888	44.41	54.0	9.59	AV	0.00	100	Horizontal	Pass
6	16859.437	55.36	74.0	18.64	Peak	280.00	200	Horizontal	Pass
6**	16859.437	45.58	54.0	8.42	AV	280.00	200	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1593.300	47.53	74.0	26.47	Peak	3.00	400	Vertical	Pass
1**	1593.300	33.03	54.0	20.97	AV	3.00	400	Vertical	Pass
2	2440.700	91.74	74.0	-17.74	Peak	193.00	100	Vertical	N/A
2**	2440.700	90.86	54.0	-36.86	AV	193.00	100	Vertical	N/A
3	4881.250	50.08	74.0	23.92	Peak	96.00	100	Vertical	Pass
3**	4881.250	39.76	54.0	14.24	AV	96.00	100	Vertical	Pass
4	7705.000	53.85	74.0	20.15	Peak	178.00	200	Vertical	Pass
4**	7705.000	44.11	54.0	9.89	AV	178.00	200	Vertical	Pass
5	12738.125	54.02	74.0	19.98	Peak	144.00	100	Vertical	Pass
5**	12738.125	43.28	54.0	10.72	AV	144.00	100	Vertical	Pass
6	16860.489	55.60	74.0	18.40	Peak	113.00	300	Vertical	Pass
6**	16860.489	46.49	54.0	7.51	AV	113.00	300	Vertical	Pass

A.9 Band Edge (Restricted-band band-edge)

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note ²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note ³: According the ANSI C63.10-2020, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note ⁴: The Level (dBuV/m) has been corrected by factor.

Test Data

PCB Antenna

GFSK LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2361.343	56.28	74.0	17.72	Peak	60.00	300	Horizontal	Pass
1**	2361.343	46.98	54.0	7.02	AV	60.00	300	Horizontal	Pass
2	2390.000	55.67	74.0	18.33	Peak	225.00	300	Horizontal	Pass
2**	2390.000	47.71	54.0	6.29	AV	225.00	300	Horizontal	Pass

GFSK HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	57.56	74.0	16.44	Peak	246.00	300	Horizontal	Pass
1**	2483.500	45.96	54.0	8.04	AV	246.00	300	Horizontal	Pass
2	2484.522	56.59	74.0	17.41	Peak	44.00	100	Horizontal	Pass
2**	2484.522	47.01	54.0	6.99	AV	44.00	100	Horizontal	Pass

8-DPSK LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2363.443	59.35	74.0	14.65	Peak	114.00	200	Horizontal	Pass
1**	2363.443	43.8	54.0	10.20	AV	114.00	200	Horizontal	Pass
2	2390.000	56.27	74.0	17.73	Peak	353.00	300	Horizontal	Pass
2**	2390.000	46.64	54.0	7.36	AV	353.00	300	Horizontal	Pass

8-DPSK HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	55.33	74.0	18.67	Peak	325.00	300	Horizontal	Pass
1**	2483.500	48.53	54.0	5.47	AV	325.00	300	Horizontal	Pass
2	2485.207	57.53	74.0	16.47	Peak	111.00	200	Horizontal	Pass
2**	2485.207	47.75	54.0	6.25	AV	111.00	200	Horizontal	Pass

FPC Antenna**GFSK LOW CHANNEL**

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2363.937	56.55	74.0	17.45	Peak	199.00	200	Horizontal	Pass
1**	2363.937	46.95	54.0	7.05	AV	199.00	200	Horizontal	Pass
2	2390.000	55.42	74.0	18.58	Peak	348.00	200	Horizontal	Pass
2**	2390.000	46.63	54.0	7.37	AV	348.00	200	Horizontal	Pass

Dipole Antenna**GFSK LOW CHANNEL**

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2362.806	59.11	74.0	14.89	Peak	257.00	300	Horizontal	Pass
1**	2362.806	44	54.0	10.00	AV	257.00	300	Horizontal	Pass
2	2390.000	55.65	74.0	18.35	Peak	282.00	200	Horizontal	Pass
2**	2390.000	46.57	54.0	7.43	AV	282.00	200	Horizontal	Pass

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2580208-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2580208-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2580208-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--