

TEST REPORT

Applicant: Shenzhen Tinno Mobile Technology Corp.
Address: 27-001, South Side of Tianlong Mobile HQ Building,
Tongfa South Road, Xili Street, Nanshan District,
Shenzhen ,PRC
Equipment Type: onn 8.1" Core Tablet
Model Name: TBBLU36018340 (refer to section 2.3)
Brand Name: onn
FCC ID: XD6WM2508T
Test Standard: FCC 47 CFR Part 2.1093
(refer section 3.1)
Maximum SAR: Body (1 g@ 0mm): 1.23 W/kg
Sample Arrival Date: Nov. 03, 2025
Test Date: Nov. 21, 2025 – Nov. 24, 2025
Date of Issue: Dec. 26, 2025

ISSUED BY:

Shanghai Tejet Communications Technology Co., Ltd. Testing Center



Prepared by: Huang Xiaoqin

Reviewed by: Cai Xueguo

Approved by: Zhang Yanqing
(Laboratory Manager)

Huang Xiaoqin

Cai Xueguo

Zhang Yanqing

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Dec. 26, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
1.3	Test Environment Condition	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Ancillary Equipment	6
2.5	Technical Information	7
2.6	Antenna Location	8
3	SUMMARY OF TEST RESULT	9
3.1	Test Standards	9
3.2	Device Category and SAR Limit	10
3.3	Test Result Summary	11
3.4	Test Uncertainty	12
4	MEASUREMENT SYSTEM	15
4.1	Specific Absorption Rate (SAR) Definition	15
4.2	DASY SAR System	16
5	SYSTEM VERIFICATION	23
5.1	Purpose of System Check	23
5.2	System Check Setup	23
6	TEST POSITION CONFIGURATIONS	24
6.1	Body-worn Position Conditions	24

6.2	Hotspot Mode Exposure Position Conditions	25
6.3	Product Specific 10g Exposure Consideration	25
7	MEASUREMENT PROCEDURE	26
7.1	Measurement Process Diagram.....	26
7.2	SAR Scan General Requirement.....	27
7.3	Measurement Procedure	28
7.4	Area & Zoom Scan Procedure	28
8	CONDUCTED RF OUPUT POWER	29
8.1	WIFI.....	29
8.2	Bluetooth.....	32
9	TEST RESULT	33
9.1	Bluetooth.....	33
9.2	WIFI 2.4G	33
9.3	WIFI 5G	34
10	SAR Measurement Variability	36
11	SIMULTANEOUS TRANSMISSION	37
11.1	Simultaneous Transmission Mode Consider.....	37
11.2	Sum SAR of Simultaneous Transmission.....	37
12	TEST EQUIPMENTS LIST	38
ANNEX A	SIMULATING LIQUID VERIFICATION RESULT	39
ANNEX B	SYSTEM CHECK RESULT	40
ANNEX C	TEST DATA	45
ANNEX D	EUT EXTERNAL PHOTOS	45
ANNEX E	SAR TEST SETUP PHOTOS	45
ANNEX F	CALIBRATION REPORT	45

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Address	1-2/F., Building 1, No.222, Xuanlan Road, Xuanqiao, Pudong New District, Shanghai, China

1.2 Test Location

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Location	1-2/F., Building 1, No.222, Xuanlan Road, Xuanqiao, Pudong New District, Shanghai, China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1352. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 29671.

1.3 Test Environment Condition

Ambient Temperature	18°C to 25°C
Ambient Relative Humidity	30% to 70%

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Shenzhen Tinno Mobile Technology Corp.
Address	27-001, South Side of Tianlong Mobile HQ Building, Tongfa South Road, Xili Street, Nanshan District, Shenzhen ,PRC

2.2 Manufacturer Information

Manufacturer	Shenzhen Tinno Mobile Technology Corp.
Address	27-001, South Side of Tianlong Mobile HQ Building, Tongfa South Road, Xili Street, Nanshan District, Shenzhen ,PRC

2.3 General Description for Equipment under Test (EUT)

EUT Name	onn 8.1" Core Tablet
Model Name Under Test	TBBLU36018340
Series Model Name	TBBRN36018340,TBPNK36018340,TBSIL36018340
Description of Model name differentiation	Only with different model name and color
Sample number	SC-SZ2580421-S22,SC-SZ2580421-S21,SC-SZ2580421-S19,SC-SZ2580421-S24
Hardware Version	V1.0
Software Version	TTA.28
Dimensions (Approx.)	L: 188.9 mm* W: 130 mm* H: 7.0 mm
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Ancillary Equipment 1	Battery1	
	Brand Name	UTL
	Model No.	TT500K1
	Serial No.	N/A
	Capacity	5000mAh
	Rated Voltage	3.80V
	Limit Charge Voltage	4.35V

Ancillary Equipment 2	Battery2	
	Brand Name	Fenghua
	Model No.	TT500K1
	Serial No.	N/A
	Capacity	5000mAh
	Rated Voltage	3.80V
	Limit Charge Voltage	4.35V

Note: The EUT has two type batterys, they are same with electrical parameters, but only differ in Manufacturer and battery cell. By comparing the test data of two Batteries, battery1 can produce a more conservative SAR values. The battery1 of the Brand Name is UTL as the main for test in this report.

2.5 Technical Information


Network and Wireless connectivity	Bluetooth (BR+EDR+BLE) 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20) 5G WIFI 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40/80)
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	WIFI, Bluetooth	
Frequency Range	2.4G WIFI	2412 ~ 2462 MHz
	5G WIFI	5150 ~ 5250 MHz
		5250 ~ 5350 MHz
		5470 ~ 5725 MHz
		5725 ~ 5850 MHz
	Bluetooth	2402 ~ 2480 MHz
Antenna Type	WIFI: PIFA Antenna Bluetooth: PIFA Antenna	
DTM	N/A	
Hotspot Function	Support	
Exposure Category	General Population/Uncontrolled exposure	
Product Type	Portable Device	
EUT Type	☒ Production unit	☐ Identical prototype

2.6 Antenna Location

ANT:2.4G+5G WIFI (unit:mm)



Antenna	Support Band
Ant	2.4G WIFI/5G WIFI/BT

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	ANSI C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	IEEE Std. 1528-2013	IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate(SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	KDB 447498 D04 v01	447498 D04 Interim General RF Exposure Guidance v01
5	KDB 941225 D06 v02r01	SAR EVALUATION PROCEDURES FOR PORTABLE DEVICES WITH WIRELESS ROUTER CAPABILITIES
6	KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
7	KDB 865664 D02 v01r02	RF Exposure Reporting
8	KDB 648474 D04 v01r03	SAR EVALUATION CONSIDERATIONS FOR WIRELESS HANDSETS
9	KDB 248227 D01 v02r02	SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user.

Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Table of Exposure Limits:

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ Controlled Exposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:

General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure. In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Test Result Summary

3.3.1 Highest SAR Values

Frequency Band		Maximum Scaled SAR	Maximum Report SAR
		1 g(W/kg)	1 g(W/kg)
		Body	Body
		(Separation 0mm)	(Separation 0mm)
WIFI	2.4G	0.81	1.23
	5G	1.23	
Bluetooth	DH5	0.08	
Limits (W/kg)		1.6	1.6
Test Verdict		PASS	PASS

3.3.2 Highest Simultaneous Transmission SAR Values

Simultaneous Transmission	Maximum Scaled SAR (W/kg)
	Body 1g (0mm)
5G WIFI+ Bluetooth	1.31
Limit (W/kg)	1.60
Verdict	PASS

Note: The highest simultaneous SAR please refer section 11.2

3.4 Test Uncertainty

3.4.1 Measurement uncertainty evaluation for SAR test

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEC/IEEE 62209-1528. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

1) System Measurement Uncertainty (Frequency range from 300 MHz to 3 GHz)

DASY5 Uncertainty Budget (Frequency band: 300 MHz - 3 GHz range)								
Symbol	Error Description	Uncert. value	Prob Dist.	Div	(c _i) 1g	(c _i) 10g	Std. Unc. (1g)	Std. Unc. (10g)
Measurement System Errors								
CF	Probe Calibration	±12.0%	N	2	1	1	±6.0%	±6.0%
CF _{drift}	Probe Calibration Drift	±1.0%	N	1	1	1	±1.0%	±1.0%
LIN	Probe Linearity	±4.7%	R	√3	1	1	±2.7%	±2.7%
BBS	Broadband Signal	±3.0%	N	2	1	1	±1.5%	±1.5%
ISO	Probe Isotropy	±7.6%	R	√3	1	1	±4.4%	±4.4%
DAE	Data Acquisition	±0.3%	N	1	1	1	±0.3%	±0.3%
AMB	RF Ambient	±1.8%	N	1	1	1	±1.8%	±1.8%
Δ _{sys}	Probe Positioning	±0.2%	N	1	0.1 4	0.14	±0%	±0%
DAT	Data Processing	±1.2%	N	1	1	1	±1.2%	±1.2%
Phantom and Device Errors								
LIQ(σ)	Conductivity (meas.) ^{DAK}	±2.5%	N	1	0.7 8	0.71	±2.0%	±1.8%
LIQ(T _σ)	Conductivity (temp.) ^{BB}	±3.3%	R	√3	0.7 8	0.71	±1.5%	±1.4%
EPS	Phantom Permittivity	±14.0%	R	√3	0	0	±0%	±0%
DAS	Distance DUT - TSL	±2.1%	N	1	2	2	±4.2%	±4.2%
H	Device Holder	±3.8%	N	1	1	1	±3.8%	±3.8%
MOD	DUT Modulation ^m	±2.4%	R	√3	1	1	±1.4%	±1.4%
TAS	Time-average SAR	±2.6%	R	√3	1	1	±1.5%	±1.5%
RF _{drift}	DUT drift	±5.0%	R	√3	1	1	±2.9%	±2.9%
Correction to the SAR results								
C(ε, σ)	Deviation to Target	±1.9%	N	1	1	0.84	±1.9%	±1.6%
C(R)	SAR scaling ^p	±0%	R	√3	1	1	±0%	±0%
u(ΔSAR)	Combined Uncertainty	/	/	/	/	/	±11.2%	±11.0%

U	Expanded Uncertainty	/	/	/	/	/	±22.3%	±22.2%
---	----------------------	---	---	---	---	---	--------	--------

2) System Measurement Uncertainty (Frequency range from 3 GHz to 6 GHz)

DASY5 Uncertainty Budget								
(Frequency band: 3 GHz - 6 GHz range)								
Symbol	Error Description	Uncert. value	Prob Dist.	Div	(ci) 1g	(ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)
Measurement System Errors								
CF	Probe Calibration	±14.0%	N	2	1	1	±7.0%	±7.0%
CF _{drift}	Probe Calibration Drift	±1.0%	N	1	1	1	±1.0%	±1.0%
LIN	Probe Linearity	±4.7%	R	√3	1	1	±2.7%	±2.7%
BBS	Broadband Signal	±3.0%	N	2	1	1	±1.5%	±1.5%
ISO	Probe Isotropy	±7.6%	R	√3	1	1	±4.4%	±4.4%
DAE	Data Acquisition	±0.3%	N	1	1	1	±0.3%	±0.3%
AMB	RF Ambient	±1.8%	N	1	1	1	±1.8%	±1.8%
Δ _{sys}	Probe Positioning	±0.2%	N	1	0.3 3	0.33	±0.1%	±0.1%
DAT	Data Processing	±2.3%	N	1	1	1	±2.3%	±2.3%
Phantom and Device Errors								
LIQ(σ)	Conductivity (meas.) ^{DAK}	±2.5%	N	1	0.7 8	0.71	±2.0%	±1.8%
LIQ(T _σ)	Conductivity (temp.) ^{BB}	±3.4%	R	√3	0.7 8	0.71	±1.5%	±1.4%
EPS	Phantom Permittivity	±14.0%	R	√3	0.2 5	0.25	±2.0%	±2.0%
DAS	Distance DUT - TSL	±2.1%	N	1	2	2	±4.2%	±4.2%
H	Device Holder	±3.8%	N	1	1	1	±3.8%	±3.8%
MOD	DUT Modulation ^m	±2.4%	R	√3	1	1	±1.4%	±1.4%
TAS	Time-average SAR	±2.6%	R	√3	1	1	±1.5%	±1.5%
RF _{drift}	DUT drift	±5.0%	R	√3	1	1	±2.9%	±2.9%
Correction to the SAR results								
C(ε, σ)	Deviation to Target	±1.9%	N	1	1	0.84	±1.9%	±1.6%
C(R)	SAR scaling ^p	±0%	R	√3	1	1	±0%	±0%
u(ΔSAR)	Combined Uncertainty	/	/	/	/	/	±12.1%	±12.0%
U	Expanded Uncertainty	/	/	/	/	/	±24.2%	±24.0%

3.4.2 Measurement uncertainty evaluation for system check

This measurement uncertainty budget is suggested by IEC/IEEE 62209-1528. The breakdown of the individual uncertainties is as follows:

DASY5 Uncertainty Budget (Frequency band: 300 MHz - 6 GHz range)								
Symbol	Error Description	Uncert. value	Prob. Dist.	Div.	(c _i) 1g	(c _i) 10g	Std. Unc. (1g)	Std. Unc. (10g)
Measurement System Errors								
CF	Probe Calibration	±14.0%	N	2	1	1	±7.0%	±7.0%
CF _{drift}	Probe Calibration Drift	±1.0%	N	1	1	1	±1.0%	±1.0%
LIN	Probe Linearity	±4.7%	R	√3	1	1	±2.7%	±2.7%
BBS	Broadband Signal	±0.0%	N	2	1	1	±0.0%	±0.0%
ISO	Probe Isotropy	±7.6%	R	√3	1	1	±4.4%	±4.4%
DAE	Data Acquisition	±0.3%	N	1	1	1	±0.3%	±0.3%
AMB	RF Ambient	±1.8%	N	1	1	1	±1.8%	±1.8%
Δ _{sys}	Probe Positioning	±0.2%	N	1	0.33	0.33	±0%	±0%
Phantom and Device Errors								
LIQ(σ)	Conductivity (meas.) ^{DAK}	±2.5%	N	1	0.78	0.71	±2.0%	±1.8%
LIQ(T _σ)	Conductivity (temp.) ^{BB}	±3.4%	R	√3	0.78	0.71	±1.5%	±1.4%
EPS	Phantom Permittivity	±14.0%	R	√3	0.25	0.25	±2.0%	±2.0%
DAS	Distance DUT - TSL	±1.0%	N	1	2	2	±2.0%	±2.0%
VAL	Validation antenna	±0.0%	R	√3	1	1	±0.0%	±0.0%
P _{in}	Accepted power	±1.2%	N	1	1	1	±1.2%	±1.2%
RF _{drift}	DUT drift	±5.0%	R	√3	1	1	±2.9%	±2.9%
Correction to the SAR results								
C(ε, σ)	Deviation to Target	±1.9%	N	1	1	0.84	±1.9%	±1.6%
u(ΔSAR)	Combined Uncertainty	/	/	/	/	/	±10.4%	±10.3%
U	Expanded Uncertainty	/	/	/	/	/	±20.7%	±20.5%

4 MEASUREMENT SYSTEM

4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$\text{SAR} = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,

ρ is the mass density of the tissue and E is the RMS electrical field strength.

4.2 DASY SAR System

4.2.1 DASY SAR System Diagram




The DASY5 system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. A unit to operate the optical surface detector which is connected to the EOC.
5. The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
6. The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.
7. DASY5 software and SEMCAD data evaluation software.
8. Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
9. The generic twin phantom enabling the testing of left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. System validation dipoles allowing to validate the proper functioning of the system.

4.2.2 Robot

The Dasy SAR system uses the high precision robots. Symmetrical design with triangular core Built-in optical fiber for surface detection system For the 6-axis controller system, Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents). The robot series have many features that are important for our application:



- High precision
(repeatability ± 0.02 mm)
- High reliability
(industrial design)
- Low maintenance costs
(virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements
(brush less synchron motors; no stepper motors)
- Low ELF interference
(motor control _elds shielded via the closed metallic construction shields)

4.2.3 E-Field Probe

The probe is specially designed and calibrated for use in liquids with high permittivities for the measurements the Specific Dosimetric E-Field Probe EX3DV4 with following specifications is used.

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., glycoether)
Calibration	ISO/IEC 17025 calibration service available
Frequency	4 MHz to 10 GHz; Linearity: ± 0.2 dB
Directivity	± 0.2 dB in HSL (rotation around probe axis) ; ± 0.4 dB in HSL (rotation normal to probe axis)
Dynamic range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 9 mm) Tip diameter: 2.5 mm (Body: 10 mm) Distance from probe tip to dipole centers: 1.0 mm
Application	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms (EX3DV4)



E-Field Probe Calibration Process

Probe calibration is realized, in compliance with IEC/IEEE 62209-1528 and IEEE 1528 std, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the IEC/IEEE 62209-1528 annexe technique using reference guide at the five frequencies.

4.2.4 Data Acquisition Electronics


The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converte and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.



- Input Impedance: 200M Ω m
- The Inputs: Symmetrical and Floating
- Commom Mode Rejection: Above 80dB

4.2.5 Phantoms

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



- Left head
- Right head
- Flat phantom

Photo of Phantom SN1857



Serial Number	Material	Length	Height
SN 1857 SAM1	Vinylester, glass fiber reinforced	1000	500

4.2.6 Device Holder

The DASY5 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65° . The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA's only. If necessary an additional support of polystyrene material is used. Larger DUT's (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values. Therefore those devices are normally only tested at the flat part of the SAM.




The positioning system allows obtaining cheek and tilting position with a very good accuracy. Incompliance with CENELEC, the tilt angle uncertainty is lower than 1° .

4.2.7 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.

Head Liquid Depth



Body Liquid Depth



The following table gives the recipes for tissue simulating liquid.

TSL	Manufacturer / Model	Freq Range (MHz)	Main Ingredients
Head WideBand	SPEAG HBBL600-10000V6	600-10000	Ethanediol, Sodium petroleum sulfonate, Hexylene Glycol / 2-Methyl-pentane-2.4-diol, Alkoxylated alcohol


5 SYSTEM VERIFICATION

5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.2 System Check Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



6 TEST POSITION CONFIGURATIONS


According to KDB 648474 D04 Handset, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

6.1 Body-worn Position Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory.


Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required. A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance ≤ 5 mm to support compliance.



6.2 Hotspot Mode Exposure Position Conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).




6.3 Product Specific 10g Exposure Consideration

According with FCC KDB 648474 D04, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, unless it is confirmed otherwise through KDB inquiries, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance;

The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

7 MEASUREMENT PROCEDURE

7.1 Measurement Process Diagram



7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

			≤3GHz	>3GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5±1 mm	½·δ·ln(2)±0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30°±1°	20°±1°
Maximum area scan spatial resolution: Δx Area , Δy Area			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3–4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom			≤ 2 GHz: ≤ 8 mm 2 –3 GHz: ≤ 5 mm*	3–4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: Δz Zoom (n)		≤ 5 mm	3–4 GHz: ≤ 4 mm
				4–5 GHz: ≤ 3 mm
				5–6 GHz: ≤ 2 mm
	graded grid	Δz Zoom (1): between 1st two points closest to phantom surface	≤ 4 mm	3–4 GHz: ≤ 3 mm
				4–5 GHz: ≤ 2.5 mm
		Δz Zoom (n>1): between subsequent points	≤ 1.5·Δz Zoom (n-1)	
Minimum zoom scan volume	x, y, z		≥30 mm	3–4 GHz: ≥ 28 mm
				4–5 GHz: ≥ 25 mm
				5–6 GHz: ≥ 22 mm

Note:

1. δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.
2. * When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

8 CONDUCTED RF OUTPUT POWER

8.1 WIFI

8.1.1 2.4G WIFI

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Limit (dBm)	SAR Test Require.
2.4 (2.4~2.4835)	802.11b	1	2412	19.96	21.00	Yes
		6	2437	19.69	20.50	Yes
		11	2462	19.83	21.00	Yes
	802.11g	1	2412	16.95	18.00	No
		6	2437	19.72	20.50	No
		11	2462	15.55	16.50	No
	802.11n(HT20)	1	2412	15.54	16.50	No
		6	2437	19.55	20.50	No
		11	2462	15.39	16.50	No

Note: When multiple channel bandwidth configurations in a frequency band have the same maximum tune-up output power, the test configuration is determined by applying the following steps sequentially.

- 1) The largest channel bandwidth configuration is selected between the multiple configurations in a frequency band with the same maximum tune-up output power.
- 2) When multiple transmission modes (802.11b/g/n) have the same maximum tune-up output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11b is chosen over 802.11g, and 802.11g chosen over 802.11n.
- 3) According KDB 247228, when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, OFDM SAR test is not required.
Adjusted SAR = $0.807 * (112.20\text{mW}/125.89\text{mW}) = 0.719\text{W/kg}$, so 2.4G OFDM SAR test is not required.

8.1.2 5G WIFI

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Limit (dBm)	SAR Test Require.
5.2 (5.15~5.25)	802.11a	36	5180	14.01	15.00	No
		44	5220	14.17	15.00	No
		48	5240	14.33	15.50	No
	802.11n(HT20)	36	5180	13.97	15.00	No
		44	5220	14.18	15.00	No
		48	5240	14.15	15.00	No
	802.11n(HT40)	38	5190	14.19	15.00	Yes
		46	5230	14.89	16.00	Yes
	802.11ac(VHT20)	36	5180	13.79	15.00	No
		44	5220	14.04	15.00	No

		48	5240	14.16	15.00	No
	802.11ac(VHT40)	38	5190	14.68	15.50	No
		46	5230	14.39	15.50	No
	802.11ac(VHT80)	42	5210	12.70	13.50	No
5.3 (5.25~5.35)	802.11a	52	5260	17.08	18.00	No
		60	5300	17.39	18.00	No
		64	5320	17.45	18.00	No
	802.11n(HT20)	52	5260	16.94	18.00	No
		60	5300	17.23	18.00	No
		64	5320	17.27	18.00	No
	802.11n(HT40)	54	5270	17.81	18.50	Yes
		62	5310	15.00	16.00	Yes
	802.11ac(VHT20)	52	5260	14.88	16.00	No
		60	5300	15.19	16.00	No
		64	5320	15.11	16.00	No
	802.11ac(VHT40)	54	5270	14.64	15.50	No
		62	5310	14.93	16.00	No
	802.11ac(VHT80)	58	5290	15.59	16.50	No
5.6 (5.47~5.725)	802.11a	100	5500	14.86	16.00	No
		116	5580	15.66	16.50	No
		140	5700	14.32	15.50	No
	802.11n(HT20)	100	5500	14.84	16.00	No
		116	5580	15.66	16.50	No
		140	5700	11.98	13.00	No
	802.11n(HT40)	102	5510	15.80	16.50	Yes
		118	5590	16.54	17.50	Yes
		134	5670	16.38	17.00	Yes
	802.11ac(VHT20)	100	5500	14.81	16.00	No
		116	5580	15.61	16.50	No
		140	5700	14.30	15.50	No
	802.11ac(VHT40)	102	5510	15.79	17.00	No
		118	5590	16.52	17.50	No
		134	5670	16.37	17.00	No
	802.11ac(VHT80)	106	5530	13.49	14.50	No
		122	5690	16.22	17.00	No
5.8 (5.725~5.850)	802.11a	149	5745	14.21	15.00	No
		157	5785	14.09	15.00	No
		165	5825	13.81	15.00	No
	802.11n(HT20)	149	5745	14.19	15.00	No

		157	5785	14.07	15.00	No
		165	5825	13.78	15.00	No
	802.11n(HT40)	151	5755	15.07	16.00	Yes
		159	5795	14.89	15.50	Yes
	802.11ac(VHT20)	149	5745	14.25	15.50	No
		157	5785	14.13	15.00	No
		165	5825	13.85	15.00	No
	802.11ac(VHT40)	151	5755	14.46	15.50	No
		159	5795	14.37	15.50	No
	802.11ac(VHT80)	155	5775	14.76	15.50	No


Note: When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

8.2 Bluetooth

Mode	GFSK			$\pi/4$ -DQPSK		
Channel	0	39	78	0	39	78
Frequency (MHz)	2402	2441	2480	2402	2441	2480
EIRP (dBm)	11.17	11.24	9.90	10.57	10.65	9.48
Tune-Up Limit (dBm)	12.00	12.00	11.00	11.50	11.50	10.50
SAR Test Require	YES	YES	YES	NO	NO	NO
Mode	8-DPSK			/		
Channel	0	39	78	/	/	/
Frequency (MHz)	2402	2441	2480	/	/	/
EIRP (dBm)	10.99	11.03	9.80	/	/	/
Tune-Up Limit (dBm)	11.50	11.50	11.00	/		
SAR Test Require	NO	NO	NO	/	/	/
Mode	BLE-1Mbps			/		
Channel	0	19	39	/	/	/
Frequency (MHz)	2402	2440	2480	/	/	/
EIRP (dBm)	6.47	6.68	5.94	/	/	/
Tune-Up Limit (dBm)	7.50	7.50	7.00	/		
SAR Test Require	NO	NO	NO	/	/	/

Note 1: Since bluetooth BR mode is the maximum output power mode, SAR measurements were performed with test software using DH5 modulation, and SAR measurement is not required for the EDR and LE. When the secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode.

Note: The Bluetooth duty cycle is 77.08% as following figure, according to 2016 Oct. TCB workshop for Bluetooth SAR scaling need further consideration and the maximum duty cycle is 100%, therefore the actual duty cycle will be scaled up to 100% for Bluetooth reported SAR calculation.



9 TEST RESULT

Note: Refer to ANNEX C for the detailed test data for each test configuration.

9.1 Bluetooth

Number	Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1 g Meas SAR(W/kg)	Meas. Power (dBm)	Max. tune-up power(dBm)	Scaling Factor	Duty cycle (%)	Duty Factor	1g Scaled SAR (W/kg)	Meas. No.
SC-SZ2580421-S22 SN: AHGW2542000060	DH5	Back side	0	39	2441	0.18	0.018	11.24	12.00	1.191	77.08	1.297	0.028	
		Left Edge		39	2441	0.17	0.035	11.24	12.00	1.191	77.08	1.297	0.054	
		Right Edge		39	2441	-0.01	0.026	11.24	12.00	1.191	77.08	1.297	0.040	
		Top Edge		39	2441	0.09	0.053	11.24	12.00	1.191	77.08	1.297	0.082	1
		Bottom Edge		39	2441	-0.06	0.010	11.24	12.00	1.191	77.08	1.297	0.015	
		Top Edge		0	2402	0.09	0.048	11.17	12.00	1.211	77.08	1.297	0.075	
		Top Edge		78	2480	0.17	0.040	9.90	11.00	1.288	77.08	1.297	0.067	

9.2 WIFI 2.4G

Number	Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1 g Meas SAR(W/kg)	Meas. Power (dBm)	Max. tune-up power(dBm)	Scaling Factor	Duty cycle (%)	Duty Factor	1g Scaled SAR (W/kg)	Meas. No.
SC-SZ2580421-S22 SN: AHGW2542000060	802.11b	Back side	0	1	2412	0.17	0.118	19.96	21.00	1.271	98.70	1.013	0.152	
		Left Edge		1	2412	-0.18	0.326	19.96	21.00	1.271	98.70	1.013	0.420	
		Right Edge		1	2412	0.01	0.022	19.96	21.00	1.271	98.70	1.013	0.028	
		Top Edge		1	2412	-0.09	0.627	19.96	21.00	1.271	98.70	1.013	0.807	2
		Bottom Edge		1	2412	-0.05	0.025	19.96	21.00	1.271	98.70	1.013	0.032	
		Top Edge		6	2437	0.09	0.580	19.69	20.50	1.205	98.70	1.013	0.708	
		Top Edge		11	2462	0.12	0.600	19.83	21.00	1.309	98.70	1.013	0.796	

9.3 WIFI 5G

WIFI 5.2G

Number	Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1 g Meas SAR(W/kg)	Meas. Power (dBm)	Max. tune-up power(dB m)	Scaling Factor	Duty cycle (%)	Duty Factor	1g Scaled SAR (W/kg)	Meas. No.
SC-SZ2580421-S22 SN: AHGW2542000060	802.11n 40	Back side	0	46	5230	0.02	0.128	14.89	16.00	1.291	94.65	1.057	0.175	
		Left Edge		46	5230	0.09	0.879	14.89	16.00	1.291	94.65	1.057	1.200	3
		Left Edge		46	5230	0.02	0.850	14.89	16.00	1.291	94.65	1.057	1.160	repeat
		Right Edge		46	5230	-0.11	0.099	14.89	16.00	1.291	94.65	1.057	0.135	
		Top Edge		46	5230	0.12	0.617	14.89	16.00	1.291	94.65	1.057	0.842	
		Bottom Edge		46	5230	0.11	0.032	14.89	16.00	1.291	94.65	1.057	0.044	
		Left Edge		38	5190	-0.13	0.760	14.19	15.00	1.205	94.65	1.057	0.968	

WIFI 5.3G

Number	Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1 g Meas SAR(W/k g)	Meas. Power (dBm)	Max. tune-up power(dB m)	Scaling Factor	Duty cycle (%)	Duty Factor	1g Scaled SAR (W/kg)	Meas. No.
SC-SZ2580421-S22 SN: AHGW2542000060	802.11 n40	Back side	0	54	5270	0.07	0.163	17.81	18.50	1.172	94.65	1.057	0.202	
		Left Edge		54	5270	0.12	0.899	17.81	18.50	1.172	94.65	1.057	1.114	4
		Left Edge		54	5270	0.1	0.846	17.81	18.50	1.172	94.65	1.057	1.048	repeat
		Right Edge		54	5270	0.19	0.073	17.81	18.50	1.172	94.65	1.057	0.090	
		Top Edge		54	5270	-0.14	0.760	17.81	18.50	1.172	94.65	1.057	0.941	
		Bottom Edge		54	5270	-0.09	0.029	17.81	18.50	1.172	94.65	1.057	0.036	
		Left Edge		62	5310	-0.1	0.580	15.00	16.00	1.259	94.65	1.057	0.772	

WIFI 5.6G

Number	Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1 g Meas SAR(W/ kg)	Meas. Power (dBm)	Max. tune- up power(dB m)	Scaling Factor	Duty cycle (%)	Duty Factor	1g Scaled SAR (W/kg)	Meas. No.
SC-SZ2580421-S22 SN: AHGW2542000060	802.11 n40	Back side	0	118	5590	-0.09	0.129	16.54	17.50	1.247	94.65	1.057	0.170	
		Left Edge		118	5590	-0.02	0.503	16.54	17.50	1.247	94.65	1.057	0.663	
		Right Edge		118	5590	0.04	0.061	16.54	17.50	1.247	94.65	1.057	0.080	
		Top Edge		118	5590	0.05	0.931	16.54	17.50	1.247	94.65	1.057	1.228	5
		Top Edge		118	5590	0.02	0.913	16.54	17.50	1.247	94.65	1.057	1.204	repeat
		Bottom Edge		118	5590	-0.03	0.022	16.54	17.50	1.247	94.65	1.057	0.029	
		Top Edge		102	5510	-0.07	0.900	15.80	16.50	1.175	94.65	1.057	1.118	
		Top Edge		134	5670	0.13	0.910	16.38	17.00	1.153	94.65	1.057	1.109	
SC-SZ2580421-S21 SN:AHGW25420000425	802.11 n40	Top Edge	0	118	5590	0.02	0.855	16.54	17.50	1.247	94.65	1.057	1.127	
SC-SZ2580421-S24		Top Edge		118	5590	0.06	0.914	16.54	17.50	1.247	94.65	1.057	1.205	

SN:AHGW2542000484														
SC-SZ2580421-S19 SN:AHGW2542000047		Top Edge		118	5590	0.12	0.801	16.54	17.50	1.247	94.65	1.057	1.056	

WIFI 5.8G

Number	Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1 g Meas SAR(W/kg)	Meas. Power (dBm)	Max. tune-up power(dB m)	Scaling Factor	Duty cycle (%)	Duty Factor	1g Scaled SAR (W/kg)	Meas. No.
SC-SZ2580421-S22 SN: AHGW2542000060	802.11 n40	Back side	0	159	5795	-0.09	0.112	15.07	16.00	1.239	94.65	1.057	0.147	
		Left Edge		159	5795	-0.01	0.317	15.07	16.00	1.239	94.65	1.057	0.415	
		Right Edge		159	5795	-0.03	0.169	15.07	16.00	1.239	94.65	1.057	0.221	
		Top Edge		159	5795	-0.05	0.890	15.07	16.00	1.239	94.65	1.057	1.165	
		Bottom Edge		159	5795	-0.01	0.029	15.07	16.00	1.239	94.65	1.057	0.038	
		Top Edge		151	5755	0.08	0.994	14.89	15.50	1.151	94.65	1.057	1.209	6
		Top Edge		151	5755	0.18	0.955	14.89	15.50	1.151	94.65	1.057	1.162	repeat

Note: There are 4 test prototypes. The main prototype for testing is numbered SC-SZ2580421-S22 SN: AHGW2542000060, and the other prototypes are numbered SC-SZ2580421-S21 SN: HGW2542000425, SC-SZ2580421-S24 SN: AHGW2542000484, SC-SZ2580421-S19 SN: AHGW2542000047. The prototypes are supplied by different manufacturers for materials compared to SC-SZ2580421-S22 SN: AHGW2542000060, but because the device specifications and materials are the same, and the battery differs, the worst-case SAR scenario was tested.

10 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Frequency Band (MHz)	Wireless Band	RF Exposure Conditions	Test Position	Highest Measured SAR (W/kg)	Repeated SAR (Yes/No)	Repeated ^{1st} Measured SAR (W/kg)	Largest to Smallest SAR Ratio
5200	WLAN 5.2G	Body	Left Edge	0.879	Yes	0.850	1.03
5200	WLAN 5.3G	Body	Left Edge	0.899	Yes	0.846	1.06
5600	WLAN 5.6G	Body	Top Edge	0.931	Yes	0.913	1.02
5800	WLAN 5.8G	Body	Top Edge	0.994	Yes	0.955	1.04

Note: The ratio of largest to smallest SAR for the original and first repeated measurements is < 1.20 , the second repeated measurement. is not required.

11 SIMULTANEOUS TRANSMISSION

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

11.1 Simultaneous Transmission Mode Consider

No.	Simultaneous Tx Combination	Body
1	WIFI 5G+BT	Yes
Note: The maximum SAR summation is calculated based on the same configuration and test position.		

11.2 Sum SAR of Simultaneous Transmission

11.2.1 Body-worn Simultaneous Transmission SAR Evaluation for WIFI and Bluetooth

Band	Antenna	Position	1	2	SUM SAR
			5G WIFI	Bluetooth	1+2
WIFI5G&BT	Ant	Back Side	0.202	0.028	0.230
		Left Edge	1.200	0.054	1.254
		Right Edge	0.221	0.040	0.261
		Top Edge	1.228	0.082	1.310
		Bottom Edge	0.044	0.015	0.059
Note:					
1: The highest Summed 10g SAR is 1.310 W/Kg < 1.6 W/kg, so Simultaneous Transmission SAR test is not required.					

12 TEST EQUIPMENTS LIST

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
PC	Dell	N/A	N/A	N/A	N/A
Test Software	Speag	DASY5	52.10.4.1535	N/A	N/A
2450MHz Validation Dipole	Speag	D2450V2	1065	2024/09/05	2027/09/05
5GHz Validation Dipole	Speag	D5GHzV2	1333	2024/09/04	2027/09/04
Data Acquisition Electronics	Speag	DAE4	SN: 540	2025/04/21	2026/04/20
E-Field Probe	Speag	EX3DV4	SN: 3748	2025/04/24	2026/04/23
Signal Generator	R&S	SMB100A	182635	2025/02/12	2026/02/12
Power Meter	R&S	E4419B	MY45104512	2025/02/11	2026/02/11
Power Sensor	Agilent	E9304A	MY41499059	2025/02/11	2026/02/11
Power Sensor	Agilent	E9304A	MY41499060	2025/02/11	2026/02/11
Network Analyzer	Agilent	E5071C	MY56301409	2025/02/12	2026/02/12
Thermometer	CEM	DT-322	210402350	2025/01/22	2026/01/22
Thermometer	Elitech	RC-4HC	EF7247001275	2025/01/22	2026/01/22
Power Amplifier	COM-MW	PAO.4	201704001	N/A	N/A
Dielectric Probe Kit	Keysight	85070E	MY44300524	N/A	N/A
Phantom	Speag	SAM	1857	N/A	N/A
Attenuator	COM-MW	ZA-S1-31	1305003187	N/A	N/A
Directional coupler	AA-MCS	AAMCS-UDC	000272	N/A	N/A

Note: For dipole antennas, Tejet has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss in within 20% of calibrated measurement.
4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.

ANNEX A SIMULATING LIQUID VERIFICATION RESULT

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an 85070E Dielectric Probe Kit.

Head Liquid

Date	Liquid Type	Fre. (MHz)	Temp. (°C)	Meas. Conductivity (σ) (S/m)	Meas. Permittivity (ϵ)	Target Conductivity (σ) (S/m)	Target Permittivity (ϵ)	Conductivity Tolerance (%)	Permittivity Tolerance (%)
2025.11.21	Head	2450	21.3	1.82	38.44	1.80	39.20	1.11	-1.94
2025.11.22	Head	5200	21.4	4.55	35.21	4.66	35.99	-2.36	-2.17
2025.11.23	Head	5600	21.2	4.98	34.59	5.07	35.53	-1.78	-2.65
2025.11.24	Head	5800	20.9	5.17	34.19	5.27	35.30	-1.90	-3.14
Note: The tolerance limit of Conductivity and Permittivity is $\pm 5\%$.									

ANNEX B SYSTEM CHECK RESULT

Comparing to the original SAR value provided by Speag, the validation data should be within its specification of 10 %.

Head liquid 1g

Date	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)
2025.11.21	2450	100	5.460	54.60	52.60	3.80
2025.11.22	5200	100	7.230	72.30	77.80	-7.07
2025.11.23	5600	100	8.520	85.20	82.80	2.90
2025.11.24	5800	100	7.460	74.60	78.50	-4.97

System Performance Check Data(2450MHz)

Date: 2025/11/21

Communication System Band: D2450 (2450.0 MHz); Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.82$ S/m; $\epsilon_r = 38.441$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature:22.4°C Liquid Temperature:21.3°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3748; ConvF(6.9, 6.9, 6.9); Calibrated: 2025/4/24
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn540; Calibrated: 2025/4/21
- Phantom: Twin-SAM Right V5.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: 1857
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

2450/Area Scan (71x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 9.53 W/kg

2450/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 58.18 V/m; Power Drift = -0.04 dB


Peak SAR (extrapolated) = 11.5 W/kg

SAR(1 g) = 5.46 W/kg; SAR(10 g) = 2.5 W/kg

Smallest distance from peaks to all points 3 dB below = 8.5 mm

Ratio of SAR at M2 to SAR at M1 = 47.9%

Maximum value of SAR (measured) = 9.17 W/kg



0 dB = 9.17 W/kg

System Performance Check Data(5200MHz)

Date: 2025/11/22

Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5200 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5200$ MHz; $\sigma = 4.55$ S/m; $\epsilon_r = 35.21$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.3°C Liquid Temperature: 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3748; ConvF(5, 5, 5); Calibrated: 2025/4/24
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn540; Calibrated: 2025/4/21
- Phantom: Twin-SAM Right V5.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: 1857
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

CW 5200/Area Scan (61x81x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 15.3 W/kg

CW 5200/Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 29.03 V/m; Power Drift = -0.20 dB


Peak SAR (extrapolated) = 30.3 W/kg

SAR(1 g) = 7.23 W/kg; SAR(10 g) = 2.07 W/kg

Smallest distance from peaks to all points 3 dB below = 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 53.6%

Maximum value of SAR (measured) = 15.1 W/kg



0 dB = 15.1 W/kg

System Performance Check Data(5600MHz)

Date: 2025/11/23

Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5600$ MHz; $\sigma = 4.975$ S/m; $\epsilon_r = 34.59$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.2°C Liquid Temperature: 21.2°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3748; ConvF(4.39, 4.39, 4.39); Calibrated: 2025/4/24
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn540; Calibrated: 2025/4/21
- Phantom: Twin-SAM Right V5.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: 1857
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

CW 5600/Area Scan (81x101x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 18.1 W/kg

CW 5600/Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 16.65 V/m; Power Drift = -0.15 dB


Peak SAR (extrapolated) = 39.2 W/kg

SAR(1 g) = 8.52 W/kg; SAR(10 g) = 2.4 W/kg

Smallest distance from peaks to all points 3 dB below = 7.4 mm

Ratio of SAR at M2 to SAR at M1 = 50.5%

Maximum value of SAR (measured) = 18.2 W/kg



0 dB = 18.2 W/kg

System Performance Check Data(5800MHz)

Date: 2025/11/24

Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5800 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5800$ MHz; $\sigma = 5.169$ S/m; $\epsilon_r = 34.189$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.1°C Liquid Temperature: 20.9°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3748; ConvF(4.41, 4.41, 4.41); Calibrated: 2025/4/24
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn540; Calibrated: 2025/4/21
- Phantom: Twin-SAM Right V5.0 (20deg probe tilt); Type: QD 000 P40 CD; Serial: 1857
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

CW 5800/Area Scan (81x101x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 15.9 W/kg

CW 5800/Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 15.38 V/m; Power Drift = -0.10 dB


Peak SAR (extrapolated) = 36.2 W/kg

SAR(1 g) = 7.46 W/kg; SAR(10 g) = 2.09 W/kg

Smallest distance from peaks to all points 3 dB below = 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 49%

Maximum value of SAR (measured) = 16.2 W/kg



0 dB = 16.2 W/kg

ANNEX C TEST DATA

Please refer the document “BL-SZ25A1264-ATD.pdf”.

ANNEX D EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ25A1264-AW.pdf”.

ANNEX E SAR TEST SETUP PHOTOS

Please refer the document “BL-SZ25A1264-AS.pdf”.

ANNEX F CALIBRATION REPORT

Please refer the document “BL-SZ25A1264-AC.pdf”.

Statement

1. The Testing Center guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. For the report with Accreditation Symbol, the items marked with "☆" are not within the accredited scope.
3. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the test report stamp.
4. The test data and results are only valid for the tested samples provided by the customer.
5. This report shall not be partially reproduced without the written permission of the Testing Center.
6. Any objection shall be raised to the Testing Center within 30 days after receiving the report.

--END OF REPORT--