

## TEST REPORT

**Applicant:** Shenzhen Xinguodu Technology Co.,Ltd.

**Address:** 17B JinSong Mansion, Terra Industrial & Trade Park  
Chegongmiao, Futian District, Shenzhen,Guangdong, China.

**Product Name:** POS terminal

**FCC ID:** XDQEF20-01

**Standard(s):** 47 CFR Part 15, Subpart E(15.407)  
ANSI C63.10-2020  
KDB 789033 D02 General U-NII Test Procedures New Rules  
v02r01

**Report Number:** 2502Z37110E-RF-00D

**Report Date:** 2025/12/30

The above device has been tested and found compliant with the requirement of the relevant standards by Bay Area Compliance Laboratories Corp. (Dongguan).

*Alice Tan*

**Reviewed By:** Alice Tan

Title: RF Engineer

*Pedro Yun*

**Approved By:** Pedro Yun

Title: RF Supervisor

---

**Bay Area Compliance Laboratories Corp. (Dongguan)**  
No.12, Pulong East 1<sup>st</sup> Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

[www.baclcorp.com.cn](http://www.baclcorp.com.cn)

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

## CONTENTS

|                                                              |           |
|--------------------------------------------------------------|-----------|
| <b>DOCUMENT REVISION HISTORY .....</b>                       | <b>4</b>  |
| <b>1. GENERAL INFORMATION .....</b>                          | <b>5</b>  |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) ..... | 5         |
| 1.2 ACCESSORY INFORMATION .....                              | 6         |
| 1.3 ANTENNA INFORMATION DETAIL ▲ .....                       | 6         |
| 1.4 EQUIPMENT MODIFICATIONS .....                            | 6         |
| <b>2. SUMMARY OF TEST RESULTS .....</b>                      | <b>7</b>  |
| <b>3. DESCRIPTION OF TEST CONFIGURATION .....</b>            | <b>8</b>  |
| 3.1 OPERATION FREQUENCY DETAIL .....                         | 8         |
| 3.2 EUT OPERATION CONDITION .....                            | 9         |
| 3.3 SUPPORT EQUIPMENT LIST AND DETAILS .....                 | 10        |
| 3.4 SUPPORT CABLE LIST AND DETAILS .....                     | 10        |
| 3.5 BLOCK DIAGRAM OF TEST SETUP .....                        | 11        |
| 3.6 TEST FACILITY .....                                      | 13        |
| 3.7 MEASUREMENT UNCERTAINTY .....                            | 13        |
| <b>4. REQUIREMENTS AND TEST PROCEDURES .....</b>             | <b>14</b> |
| 4.1 AC LINE CONDUCTED EMISSIONS .....                        | 14        |
| 4.1.1 Applicable Standard .....                              | 14        |
| 4.1.2 EUT Setup .....                                        | 15        |
| 4.1.3 EMI Test Receiver Setup .....                          | 15        |
| 4.1.4 Test Procedure .....                                   | 16        |
| 4.1.5 Corrected Amplitude & Margin Calculation .....         | 16        |
| 4.1.6 Test Result .....                                      | 16        |
| 4.2 RADIATION SPURIOUS EMISSIONS .....                       | 17        |
| 4.2.1 Applicable Standard .....                              | 17        |
| 4.2.2 EUT Setup .....                                        | 18        |
| 4.2.3 EMI Test Receiver & Spectrum Analyzer Setup .....      | 20        |
| 4.2.4 Test Procedure .....                                   | 20        |
| 4.2.5 Corrected Result & Margin Calculation .....            | 21        |
| 4.2.6 Test Result .....                                      | 21        |
| 4.3 EMISSION BANDWIDTH .....                                 | 22        |
| 4.3.1 Applicable Standard .....                              | 22        |
| 4.3.2 EUT Setup .....                                        | 22        |
| 4.3.3 Test Procedure .....                                   | 22        |
| 4.3.4 Test Result .....                                      | 23        |
| 4.4 MAXIMUM CONDUCTED OUTPUT POWER .....                     | 24        |
| 4.4.1 Applicable Standard .....                              | 24        |
| 4.4.2 EUT Setup .....                                        | 24        |
| 4.4.3 Test Procedure .....                                   | 25        |
| 4.4.4 Test Result .....                                      | 25        |
| 4.5 MAXIMUM POWER SPECTRAL DENSITY .....                     | 26        |
| 4.5.1 Applicable Standard .....                              | 26        |
| 4.5.2 EUT Setup .....                                        | 26        |

|                                                 |            |
|-------------------------------------------------|------------|
| 4.5.3 Test Procedure.....                       | 27         |
| 4.5.4 Test Result.....                          | 27         |
| <b>4.6 DUTY CYCLE.....</b>                      | <b>28</b>  |
| 4.6.1 EUT Setup.....                            | 28         |
| 4.6.2 Test Procedure.....                       | 28         |
| 4.6.3 Judgment .....                            | 28         |
| <b>4.7 ANTENNA REQUIREMENT .....</b>            | <b>29</b>  |
| 4.7.1 Applicable Standard .....                 | 29         |
| 4.7.2 Judgment .....                            | 29         |
| <b>5. TEST DATA AND RESULTS .....</b>           | <b>30</b>  |
| 5.1 AC LINE CONDUCTED EMISSIONS .....           | 30         |
| 5.2 RADIATION SPURIOUS EMISSIONS.....           | 33         |
| 5.3 EMISSION BANDWIDTH .....                    | 94         |
| 5.4 99% OCCUPIED BANDWIDTH .....                | 104        |
| 5.5 MAXIMUM CONDUCTED OUTPUT POWER .....        | 114        |
| 5.6 POWER SPECTRAL DENSITY .....                | 117        |
| 5.7 DUTY CYCLE.....                             | 127        |
| <b>EXHIBIT A - EUT PHOTOGRAPHS.....</b>         | <b>129</b> |
| <b>EXHIBIT B - TEST SETUP PHOTOGRAPHS .....</b> | <b>130</b> |

DOCUMENT REVISION HISTORY

| Revision Number | Report Number      | Description of Revision | Date of Revision |
|-----------------|--------------------|-------------------------|------------------|
| 1.0             | 2502Z37110E-RF-00D | Original Report         | 2025/12/30       |

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test (EUT)

|                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EUT Name:</b>                               | POS terminal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>EUT Model:</b>                              | EF20                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Operation Frequency:</b>                    | 5150-5250MHz:<br>5180-5240 MHz(802.11a/n ht20/ac vht20)<br>5190-5230 MHz(802.11n ht40/ac vht40)<br>5210 MHz(802.11ac vht80)<br>5250-5350MHz:<br>5260-5320 MHz (802.11a/n ht20/ac vht20)<br>5270-5310 MHz(802.11n ht40/ac vht40)<br>5290 MHz(802.11ac vht80)<br>5470-5725MHz:<br>5500-5720 MHz (802.11a/n ht20/ac vht20)<br>5510-5710 MHz(802.11n ht40/ac vht40)<br>5530-5690MHz(802.11ac vht80)<br>5725-5850MHz:<br>5745-5825 MHz (802.11a/n ht20/ac vht20)<br>5755-5795 MHz(802.11n ht40/ac vht40)<br>5775 MHz(802.11ac vht80) |
| <b>Maximum Average Conducted Output Power:</b> | 13.54dBm for 5150-5250MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|                                                | 13.64dBm for 5250-5350MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|                                                | 12.35dBm for 5470-5725MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|                                                | 14.08dBm for 5725-5850MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Modulation Type:</b>                        | 802.11a/n/ac: OFDM-BPSK, QPSK, 16QAM, 64QAM,256QAM                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Rated Input Voltage:</b>                    | 3.85Vdc from battery or 5V/9V/12V/3.3-5.9V/3.3-11Vdc from adapter                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Serial Number:</b>                          | For AC Line Conducted Emissions and Radiated Spurious Emission:<br>3CX7-1<br>RF Conducted: 3CX7-6                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>EUT Received Date:</b>                      | 2025/11/19                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>EUT Received Status:</b>                    | Good                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

The device has five Samples, and their differences are as follows:

| EUT Sample | PN | SN     | SIM slot | Battery         | Memory   | SD Card | eSIM | PSAM |
|------------|----|--------|----------|-----------------|----------|---------|------|------|
| Sample 1#  | W1 | 3CX7-1 | Double   | Dual battery    | 2GB+32GB | ×       | ×    | √    |
| Sample 2#  | W7 | 3CX7-4 | Single   | Dual battery    | 4GB+64GB | ×       | √    | √    |
| Sample 3#  | W6 | 3CX7-3 | Double   | Dual battery    | 2GB+32GB | √       | ×    | ×    |
| Sample 4#  | W3 | 3CX7-2 | Double   | Single battery  | 2GB+32GB | ×       | ×    | √    |
| Sample 5#  | WK | 3CX7-5 | Double   | Without battery | 2GB+32GB | ×       | ×    | √    |

Note: Per 15B report, Sample 1#+ Adapter 1# was the worst for AC Line Conducted Emissions and Radiated Spurious Emission, so only performed it this report.

## 1.2 Accessory Information

| Accessory Description | Manufacturer                           | Model            | Parameters                                                                                                                                       |
|-----------------------|----------------------------------------|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Adapter 1#            | Jiangxi Jian Aohai Technology Co.,Ltd  | A319-050200U-US2 | Input: 100-240Vac 50/60Hz 0.3A<br>Output: 5.0Vdc 2000mA                                                                                          |
| Adapter 2#            | Shenzhen Aoda Power Technology Co.,Ltd | A829-120167C-US1 | Input: 100-240Vac~50/60Hz 0.5A<br>Output: 5.0Vdc 3A 15W/9Vdc 2.23A<br>20.07W/12Vdc 1.67A 20.4W/3.3-5.9Vdc 3A<br>17.7W MAX/3.3-11Vdc 2.2A 20W MAX |
| Type C+ Type C Cable  | /                                      | /                | /                                                                                                                                                |
| USB+ Type C Cable     | /                                      | /                | /                                                                                                                                                |

## 1.3 Antenna Information Detail ▲

| Antenna Type                                                                                                                                                                                                                                                                                                                                                                                         | input impedance (Ohm) | Frequency Range | Antenna Gain |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------|--------------|
| FPC                                                                                                                                                                                                                                                                                                                                                                                                  | 50                    | 5.15~5.25GHz    | 0.43dBi      |
|                                                                                                                                                                                                                                                                                                                                                                                                      |                       | 5.25~5.35 GHz   | 0.38dBi      |
|                                                                                                                                                                                                                                                                                                                                                                                                      |                       | 5.47~5.725 GHz  | 1.44dBi      |
|                                                                                                                                                                                                                                                                                                                                                                                                      |                       | 5.725~5.85 GHz  | 1.35dBi      |
| <b>The design of compliance with §15.203:</b><br><div><input checked="" type="checkbox"/> Unit uses a permanently attached antenna.<br/><input type="checkbox"/> Unit uses a unique coupling to the intentional radiator.<br/><input type="checkbox"/> Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.</div> |                       |                 |              |

## 1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

## 2. SUMMARY OF TEST RESULTS

| Standard(s) Section                | Test Items                     | Result    |
|------------------------------------|--------------------------------|-----------|
| §15.207(a)                         | AC line conducted emissions    | Compliant |
| FCC§15.205& §15.209<br>&§15.407(b) | Radiated Spurious Emissions    | Compliant |
| FCC§15.407(a) (e)                  | Emission Bandwidth             | Compliant |
| FCC§15.407(a)                      | Maximum Conducted Output Power | Compliant |
| FCC§15.407 (a)                     | Power Spectral Density         | Compliant |
| §15.203                            | Antenna Requirement            | Compliant |

### 3. DESCRIPTION OF TEST CONFIGURATION

#### 3.1 Operation Frequency Detail

**For 802.11a/n ht20/ac vht20:**

| 5150-5250MHz Band |                 | 5250-5350 MHz Band |                 | 5470-5725 MHz Band |                 | 5725-5850MHz Band |                 |
|-------------------|-----------------|--------------------|-----------------|--------------------|-----------------|-------------------|-----------------|
| Channel           | Frequency (MHz) | Channel            | Frequency (MHz) | Channel            | Frequency (MHz) | Channel           | Frequency (MHz) |
| 36                | <b>5180</b>     | 52                 | <b>5260</b>     | 100                | <b>5500</b>     | 149               | <b>5745</b>     |
| 40                | <b>5200</b>     | 56                 | <b>5280</b>     | 104                | 5520            | 153               | 5765            |
| 44                | 5220            | 60                 | 5300            | 108                | 5540            | 157               | <b>5785</b>     |
| 48                | <b>5240</b>     | 64                 | <b>5320</b>     | 112                | 5560            | 161               | 5805            |
| /                 | /               | /                  | /               | 116                | 5580            | 165               | <b>5825</b>     |
| /                 | /               | /                  | /               | 120                | <b>5600</b>     | /                 | /               |
| /                 | /               | /                  | /               | 124                | 5620            | /                 | /               |
| /                 | /               | /                  | /               | 128                | 5640            | /                 | /               |
| /                 | /               | /                  | /               | 132                | 5660            | /                 | /               |
| /                 | /               | /                  | /               | 136                | 5680            | /                 | /               |
| /                 | /               | /                  | /               | 140                | <b>5700</b>     | /                 | /               |
| /                 | /               | /                  | /               | 144*               | <b>5720</b>     | /                 | /               |

**For 802.11n ht40/ac vht40:**

| 5150-5250MHz |                 | 5250-5350 MHz |                 | 5470-5725 MHz |                 | 5725-5850MHz |                 |
|--------------|-----------------|---------------|-----------------|---------------|-----------------|--------------|-----------------|
| Channel      | Frequency (MHz) | Channel       | Frequency (MHz) | Channel       | Frequency (MHz) | Channel      | Frequency (MHz) |
| 38           | <b>5190</b>     | 54            | <b>5270</b>     | 102           | <b>5510</b>     | 151          | <b>5755</b>     |
| 46           | <b>5230</b>     | 62            | <b>5310</b>     | 110           | 5550            | 159          | <b>5795</b>     |
| /            | /               | /             | /               | 118           | <b>5590</b>     | /            | /               |
| /            | /               | /             | /               | 126           | 5630            | /            | /               |
| /            | /               | /             | /               | 134           | <b>5670</b>     | /            | /               |
| /            | /               | /             | /               | 142*          | <b>5710</b>     | /            | /               |

**For 802.11ac vht80:**

| 5150-5250MHz |                 | 5250-5350 MHz |                 | 5470-5725 MHz |                 | 5725-5850MHz |                 |
|--------------|-----------------|---------------|-----------------|---------------|-----------------|--------------|-----------------|
| Channel      | Frequency (MHz) | Channel       | Frequency (MHz) | Channel       | Frequency (MHz) | Channel      | Frequency (MHz) |
| 42           | <b>5210</b>     | 58            | <b>5290</b>     | 106           | <b>5530</b>     | 155          | <b>5775</b>     |
| /            | /               | /             | /               | 122           | <b>5610</b>     | /            | /               |
| /            | /               | /             | /               | 138*          | <b>5690</b>     | /            | /               |

Note:

\*: Additional channels cross the band 5470-5725MHz and 5725-5850 MHz, Conducted output power/ Power Spectral Density/bandwidth test with the additional channel to compliance with stricter limit of the two bands(5470-5725MHz more stricter).

### 3.2 EUT Operation Condition

The system was configured for testing in Engineering Mode, which was provided by the manufacturer. The EUT configuration is below:

| EUT Exercise Software:                                                                                                         |               | Engineering Mode |           |                     |
|--------------------------------------------------------------------------------------------------------------------------------|---------------|------------------|-----------|---------------------|
| The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer ▲: |               |                  |           |                     |
| 5150-5250 MHz Band:                                                                                                            |               |                  |           |                     |
| Test Modes                                                                                                                     | Test Channels | Test Frequency   | Data rate | Power Level Setting |
| 802.11a                                                                                                                        | Lowest        | 5180             | 6Mbps     | 16.5                |
|                                                                                                                                | Middle        | 5200             | 6Mbps     | 16.5                |
|                                                                                                                                | Highest       | 5240             | 6Mbps     | 16.5                |
| 802.11n ht20                                                                                                                   | Lowest        | 5180             | MCS0      | 16                  |
|                                                                                                                                | Middle        | 5200             | MCS0      | 16                  |
|                                                                                                                                | Highest       | 5240             | MCS0      | 16                  |
| 802.11n ht40                                                                                                                   | Lowest        | 5190             | MCS0      | 16                  |
|                                                                                                                                | Highest       | 5230             | MCS0      | 16                  |
| 802.11ac vht80                                                                                                                 | Middle        | 5210             | MCS0      | 16                  |
| 5250-5350 MHz Band:                                                                                                            |               |                  |           |                     |
| Test Modes                                                                                                                     | Test Channels | Test Frequency   | Data rate | Power Level Setting |
| 802.11a                                                                                                                        | Lowest        | 5260             | 6Mbps     | 16.5                |
|                                                                                                                                | Middle        | 5280             | 6Mbps     | 16.5                |
|                                                                                                                                | Highest       | 5320             | 6Mbps     | 16.5                |
| 802.11n ht20                                                                                                                   | Lowest        | 5260             | MCS0      | 16                  |
|                                                                                                                                | Middle        | 5280             | MCS0      | 16                  |
|                                                                                                                                | Highest       | 5320             | MCS0      | 16                  |
| 802.11n ht40                                                                                                                   | Lowest        | 5270             | MCS0      | 16                  |
|                                                                                                                                | Highest       | 5310             | MCS0      | 16                  |
| 802.11ac vht80                                                                                                                 | Middle        | 5290             | MCS0      | 16                  |
| 5470-5725 MHz Band:                                                                                                            |               |                  |           |                     |
| Test Modes                                                                                                                     | Test Channels | Test Frequency   | Data rate | Power Level Setting |
| 802.11a                                                                                                                        | Lowest        | 5500             | 6Mbps     | 15                  |
|                                                                                                                                | Middle        | 5600             | 6Mbps     | 15                  |
|                                                                                                                                | Highest       | 5700             | 6Mbps     | 15                  |
|                                                                                                                                | Cross         | 5720             | 6Mbps     | 15                  |
| 802.11n ht20                                                                                                                   | Lowest        | 5500             | MCS0      | 15                  |
|                                                                                                                                | Middle        | 5600             | MCS0      | 15                  |
|                                                                                                                                | Highest       | 5700             | MCS0      | 15                  |
|                                                                                                                                | Cross         | 5720             | MCS0      | 15                  |
| 802.11n ht40                                                                                                                   | Lowest        | 5510             | MCS0      | 14                  |
|                                                                                                                                | Middle        | 5590             | MCS0      | 14                  |
|                                                                                                                                | Highest       | 5670             | MCS0      | 14                  |
|                                                                                                                                | Cross         | 5710             | MCS0      | 14                  |
| 802.11ac vht80                                                                                                                 | Lowest        | 5530             | MCS0      | 14                  |
|                                                                                                                                | Highest       | 5610             | MCS0      | 14                  |
|                                                                                                                                | Cross         | 5690             | MCS0      | 14                  |

| 5725-5850 MHz Band: |               |                |           |                     |
|---------------------|---------------|----------------|-----------|---------------------|
| Test Modes          | Test Channels | Test Frequency | Data rate | Power Level Setting |
| 802.11a             | Lowest        | 5745           | 6Mbps     | 16.5                |
|                     | Middle        | 5785           | 6Mbps     | 16.5                |
|                     | Highest       | 5825           | 6Mbps     | 16.5                |
| 802.11n ht20        | Lowest        | 5745           | MCS0      | 16                  |
|                     | Middle        | 5785           | MCS0      | 16                  |
|                     | Highest       | 5825           | MCS0      | 16                  |
| 802.11n ht40        | Lowest        | 5755           | MCS0      | 16                  |
|                     | Highest       | 5795           | MCS0      | 16                  |
| 802.11ac vht80      | Middle        | 5775           | MCS0      | 16                  |

Note:

1. The system support 802.11a/n ht20/n ht40/ac vht20/ac vht40/ac vht80, the ac vht20/ac vht40 were reduced since the identical parameters with 802.11 n ht20/n ht40.
2. The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.
3. For AC line conducted emissions, the maximum output power channel was tested.
4. For Radiated Spurious Emissions 9kHz~1GHz and 18~40GHz, the maximum output power channel was tested.

### 3.3 Support Equipment List and Details


| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|-------|---------------|
| /            | /           | /     | /             |

### 3.4 Support Cable List and Details


| Cable Description    | Shielding Type | Ferrite Core | Length (m) | From Port | To  |
|----------------------|----------------|--------------|------------|-----------|-----|
| Type C+ Type C Cable | no             | no           | 1.2        | Adapter   | EUT |

3.5 Block Diagram of Test Setup


AC line conducted emissions:



Spurious Emissions:  
Below 1GHz:



Above 1GHz:



### 3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

### 3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

| Parameter                         | Measurement Uncertainty                                                                                                          |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Occupied Channel Bandwidth        | ±5 %                                                                                                                             |
| RF output power, conducted        | ±0.55 dB                                                                                                                         |
| Power Spectral Density, conducted | ±0.55 dB                                                                                                                         |
| Unwanted Emissions, radiated      | 9kHz~30MHz: 3.06dB, 30MHz~1GHz: 6.13 dB, 1GHz~6GHz: 4.79 dB, 6GHz~18GHz: 4.63 dB, 18GHz~26.5GHz: 4.79 dB, 26.5GHz~40GHz: 4.63 dB |
| Unwanted Emissions, conducted     | ±2.47 dB                                                                                                                         |
| Temperature                       | ±1 °C                                                                                                                            |
| Humidity                          | ±5%                                                                                                                              |
| DC and low frequency voltages     | ±0.4%                                                                                                                            |
| Duty Cycle                        | 1%                                                                                                                               |
| AC Power Lines Conducted Emission | 2.83 dB (150 kHz to 30 MHz)                                                                                                      |

## 4. REQUIREMENTS AND TEST PROCEDURES

### 4.1 AC Line Conducted Emissions

#### 4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN).

Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

| Frequency of emission (MHz) | Conducted limit (dB $\mu$ V) |           |
|-----------------------------|------------------------------|-----------|
|                             | Quasi-peak                   | Average   |
| 0.15-0.5                    | 66 to 56*                    | 56 to 46* |
| 0.5-5                       | 56                           | 46        |
| 5-30                        | 60                           | 50        |

\*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000  $\mu$ V within the frequency band 535-1705 kHz, as measured using a 50  $\mu$ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

#### 4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

#### 4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

#### 4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

#### 4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

#### 4.1.6 Test Result

Please refer to section 5.1.

## 4.2 Radiation Spurious Emissions

### 4.2.1 Applicable Standard

FCC §15.407 (b);

*Undesirable emission limits.* Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating solely in the 5.725-5.850 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.

(8) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

(9) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in § 15.207.


(10) The provisions of § 15.205 apply to intentional radiators operating under this section.

(11) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.


(c) The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

## 4.2.2 EUT Setup


9kHz~30MHz:




30MHz~1GHz:



### 1-18GHz:



### 18-40GHz:



The radiated emission tests were performed in the semi-anechoic chamber, using the setup accordance with the ANSI C63.10-2020. The specification used was FCC 15.209, FCC 15.407 limits.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

#### 4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

| Frequency Range  | Measurement | RBW     | Video B/W | IF B/W | Detector |
|------------------|-------------|---------|-----------|--------|----------|
| 9 kHz – 150 kHz  | QP/AV       | 200 Hz  | 1 kHz     | 200 Hz | QP/AV    |
| 150 kHz – 30 MHz | QP/AV       | 9 kHz   | 30 kHz    | 9 kHz  | QP/AV    |
| 30MHz – 1000 MHz | PK          | 120 kHz | 500 kHz   | /      | PK       |
|                  | QP          | /       | /         | 120kHz | QP       |

1GHz- 40GHz:

Pre-scan:

| Frequency Range | Measurement | RBW  | Video B/W | Detector |
|-----------------|-------------|------|-----------|----------|
| Above 1 GHz     | Peak        | 1MHz | 3 MHz     | PK       |
|                 | AV          | 1MHz | 5kHz      | PK       |

Final measurement for emission identified during the pre-scan:

| Measurement | Detector | Duty cycle | RBW  | Video B/W  |
|-------------|----------|------------|------|------------|
| PK          | PK       | Any        | 1MHz | 3 MHz      |
| Ave.        | PK       | >98%       | 1MHz | 10 Hz      |
|             |          | <98%       | 1MHz | $\geq 1/T$ |

Note: T is minimum transmission duration

#### 4.2.4 Test Procedure

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz -1 GHz, except 9-90 kHz, 110-490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

If the maximized peak measured value is under the QP/Average limit by more than 6dB, then it is unnecessary to perform an QP/Average measurement.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as:  $E [dB\mu V/m] = EIRP[dBm] + 95.2$ , for  $d = 3$  meters.

All emissions under the average limit and under the noise floor have not recorded in the report.

For Radiated 18-40GHz test, which was performed at 1 m distance, according to C63.10, the test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1m  
Distance extrapolation Factor =  $20 \log (\text{specific distance } [3m] / \text{test distance } [1m])$  dB= 9.54 dB

#### 4.2.5 Corrected Result & Margin Calculation

$$E_{Log} = 20 \times \log_{10}(E_{Linear})$$

$E_{Linear}$  is the field strength of the emission, in  $\mu\text{V/m}$

$E_{Log}$  is the field strength of the emission, in  $\text{dB}\mu\text{V/m}$

For 9kHz-30MHz test, test distance is 3m, extrapolation limit shall be calculated using Equation:

$$E_{\text{limit-measure}} = E_{\text{limit-Standard}} + 40 \times \log_{10} (d_{\text{standard}}/d_{\text{measure}})$$

The basic equation except 18-40GHz test is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

For Radiated 18-40GHz test:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Distance extrapolation Factor}$$

$$\text{Result} = \text{Reading} + \text{Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Result}$$

#### 4.2.6 Test Result

Please refer to section 5.2.

## 4.3 Emission Bandwidth

### 4.3.1 Applicable Standard


FCC §15.407 (a),(h)

(h)(2) Radar Detection Function of Dynamic Frequency Selection (DFS). U-NII devices operating with any part of its 26 dB emission bandwidth in the 5.25-5.35 GHz and 5.47-5.725 GHz bands shall employ a DFS radar detection mechanism to detect the presence of radar systems and to avoid co-channel operation with radar systems.

FCC §15.407 (e)

Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

### 4.3.2 EUT Setup



### 4.3.3 Test Procedure

#### 26dB Emission Bandwidth:

According to ANSI C63.10-2020 Section 12.5.2

- Set RBW = shall be in the range of 1% to 5% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.

#### 6 dB emission bandwidth:

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW)  $\geq 3$  RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described in this section. For devices that use channel aggregation refer to III.A and III.C for determining emission bandwidth.

### **99% Occupied Bandwidth:**

According to ANSI C63.10-2020 Section 12.5.3&6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (OBW/RBW)]$  below the reference level. Specific guidance is given in 4.1.6.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

### **4.3.4 Test Result**

Please refer to section 5.3 and section 5.4.

## 4.4 Maximum Conducted Output Power

### 4.4.1 Applicable Standard

#### FCC §15.407(a) (1)(iv)

For client devices in the 5.15 – 5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


#### FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

### 4.4.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

#### **4.4.3 Test Procedure**

According to ANSI C63.10-2020 Section 12.4.3.2

Method PM-G is measurement using a gated RF average power meter.

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

#### **4.4.4 Test Result**

Please refer to section 5.5.

## 4.5 Maximum Power Spectral Density

### 4.5.1 Applicable Standard

#### FCC §15.407(a) (1)(iv)

For client devices in the 5.15 – 5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


#### FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

### 4.5.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

#### 4.5.3 Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

**Duty cycle  $\geq 98\%$**

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-1 should be applied.

**Duty cycle  $< 98\%$ , duty cycle variations are less than  $\pm 2\%$**

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-2 should be applied.

**Duty cycle  $< 98\%$ , duty cycle variations exceed  $\pm 2\%$**


KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-3 should be applied.

#### 4.5.4 Test Result

Please refer to section 5.6.

## 4.6 Duty Cycle

### 4.6.1 EUT Setup



### 4.6.2 Test Procedure

According to ANSI C63.10-2020 Section 12.2

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set  $RBW \geq OBW$  if possible; otherwise, set RBW to the largest available value.
- 3) Set  $VBW \geq RBW$ . Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if  $T \leq 16.7 \mu s$ .)

### 4.6.3 Judgment

Report Only. Please refer to section 5.7.

## **4.7 Antenna Requirement**

### **4.7.1 Applicable Standard**

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

### **4.7.2 Judgment**

**Compliant.** Please refer to the Antenna Information detail in Section 1.3.

5. TEST DATA AND RESULTS

5.1 AC Line Conducted Emissions

|                |          |              |              |
|----------------|----------|--------------|--------------|
| Serial Number: | 3CX7-1   | Test Date:   | 2025/11/27   |
| Test Site:     | CE       | Test Mode:   | Transmitting |
| Tester:        | Yolo Fan | Test Result: | Pass         |

Environmental Conditions:

|                      |      |                              |    |                        |       |
|----------------------|------|------------------------------|----|------------------------|-------|
| Temperature:<br>(°C) | 20.6 | Relative<br>Humidity:<br>(%) | 37 | ATM Pressure:<br>(kPa) | 101.6 |
|----------------------|------|------------------------------|----|------------------------|-------|

Test Equipment List and Details:

| Manufacturer | Description       | Model  | Serial<br>Number | Calibration Date | Calibration Due<br>Date |
|--------------|-------------------|--------|------------------|------------------|-------------------------|
| R&S          | LISN              | ENV216 | 101614           | 2025/6/25        | 2026/6/24               |
| Unknown      | Coaxial Cable     | RG 142 | C-0200-05        | 2025/5/6         | 2026/5/5                |
| R&S          | EMI Test Receiver | ESCI   | 100224           | 2025/6/25        | 2026/6/24               |
| Audix        | Test Software     | E3     | 191218 V9        | N/A              | N/A                     |

\* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Please refer to the below plots.

Note: 802.11a 5825MHz was tested.

Project No.: 2502Z37110E-RF  
Port: Line  
Test Mode: Transmitting  
IF B/W 9kHz PK/AV


Serial No.: 3CX7-1  
Tester: Yolo Fan  
Note: 5G WIFI



| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB) | Result (dBμV) | Limit (dBμV) | Margin (dB) | Measurement |
|-----|-----------------|----------------|-------------|---------------|--------------|-------------|-------------|
| 1   | 0.626           | 28.21          | 10.48       | 38.69         | 56.00        | 17.31       | QP          |
| 2   | 0.626           | 21.92          | 10.48       | 32.40         | 46.00        | 13.60       | Average     |
| 3   | 0.689           | 27.48          | 10.42       | 37.90         | 56.00        | 18.10       | QP          |
| 4   | 0.689           | 20.03          | 10.42       | 30.45         | 46.00        | 15.55       | Average     |
| 5   | 1.311           | 24.46          | 10.97       | 35.43         | 56.00        | 20.57       | QP          |
| 6   | 1.311           | 16.64          | 10.97       | 27.61         | 46.00        | 18.39       | Average     |
| 7   | 13.951          | 31.50          | 10.99       | 42.49         | 60.00        | 17.51       | QP          |
| 8   | 13.951          | 18.75          | 10.99       | 29.74         | 50.00        | 20.26       | Average     |
| 9   | 16.019          | 30.46          | 11.14       | 41.60         | 60.00        | 18.40       | QP          |
| 10  | 16.019          | 19.20          | 11.14       | 30.34         | 50.00        | 19.66       | Average     |
| 11  | 17.602          | 29.78          | 11.22       | 41.00         | 60.00        | 19.00       | QP          |
| 12  | 17.602          | 18.32          | 11.22       | 29.54         | 50.00        | 20.46       | Average     |

Project No.: 2502Z37110E-RF  
Port: Neutral  
Test Mode: Transmitting  
IF B/W 9kHz PK/AV

Serial No.: 3CX7-1  
Tester: Yolo Fan  
Note: 5G WIFI



| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB) | Result<br>(dBμV) | Limit<br>(dBμV) | Margin<br>(dB) | Measurement |
|-----|--------------------|-------------------|----------------|------------------|-----------------|----------------|-------------|
| 1   | 0.628              | 29.77             | 10.45          | 40.22            | 56.00           | 15.78          | QP          |
| 2   | 0.628              | 21.21             | 10.45          | 31.66            | 46.00           | 14.34          | Average     |
| 3   | 0.714              | 26.65             | 10.43          | 37.08            | 56.00           | 18.92          | QP          |
| 4   | 0.714              | 19.11             | 10.43          | 29.54            | 46.00           | 16.46          | Average     |
| 5   | 0.868              | 23.97             | 10.69          | 34.66            | 56.00           | 21.34          | QP          |
| 6   | 0.868              | 15.65             | 10.69          | 26.34            | 46.00           | 19.66          | Average     |
| 7   | 1.331              | 23.11             | 11.01          | 34.12            | 56.00           | 21.88          | QP          |
| 8   | 1.331              | 14.75             | 11.01          | 25.76            | 46.00           | 20.24          | Average     |
| 9   | 1.664              | 21.56             | 11.11          | 32.67            | 56.00           | 23.33          | QP          |
| 10  | 1.664              | 12.79             | 11.11          | 23.90            | 46.00           | 22.10          | Average     |
| 11  | 3.278              | 23.20             | 10.95          | 34.15            | 56.00           | 21.85          | QP          |
| 12  | 3.278              | 14.88             | 10.95          | 25.83            | 46.00           | 20.17          | Average     |

5.2 Radiation Spurious Emissions

1) 9kHz - 1GHz

|                |            |              |              |
|----------------|------------|--------------|--------------|
| Serial Number: | 3CX7-1     | Test Date:   | 2025/11/25   |
| Test Site:     | Chamber A  | Test Mode:   | Transmitting |
| Tester:        | Jayce Wang | Test Result: | Pass         |

|                           |      |                           |    |                        |       |
|---------------------------|------|---------------------------|----|------------------------|-------|
| Environmental Conditions: |      |                           |    |                        |       |
| Temperature:<br>(°C)      | 20.7 | Relative Humidity:<br>(%) | 39 | ATM Pressure:<br>(kPa) | 101.4 |

Test Equipment List and Details:

| Manufacturer   | Description          | Model     | Serial Number | Calibration Date | Calibration Due Date |
|----------------|----------------------|-----------|---------------|------------------|----------------------|
| EMCO           | Passive Loop Antenna | 6512      | 9706-1206     | 2023/10/25       | 2026/10/24           |
| Sunol Sciences | Hybrid Antenna       | JB3       | A060611-2     | 2024/4/16        | 2027/4/15            |
| Narda          | Coaxial Attenuator   | 757C-6dB  | 34010         | 2024/4/16        | 2027/4/15            |
| Unknown        | Coaxial Cable        | C-NJNJ-50 | C-0075-01     | 2025/7/1         | 2026/6/30            |
| Unknown        | Coaxial Cable        | C-NJNJ-50 | C-0400-01     | 2025/7/1         | 2026/6/30            |
| Unknown        | Coaxial Cable        | C-NJNJ-50 | C-1400-01     | 2025/7/1         | 2026/6/30            |
| Sonoma         | Amplifier            | 310N      | 372193        | 2025/7/30        | 2026/7/29            |
| R&S            | EMI Test Receiver    | ESCI      | 100035        | 2025/6/25        | 2026/6/24            |
| Audix          | Test Software        | E3        | 191218 V9     | N/A              | N/A                  |

\* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below plots.  
After pre-scan in the X, Y and Z axes of orientation, the worst case is refer to plots.


Note: 802.11a 5825MHz was tested.

9kHz~30MHz

Three antenna orientations (parallel, perpendicular, and ground-parallel) was measured, the worst orientations was below:


Project No.: 2502Z37110E-RF  
Polarization: Parallel  
Test Mode: Transmitting  
Note: 5G  
RBW: 200Hz, VBW: 1kHz

Serial No.: 3CX7-1  
Tester: Jayce Wang



Project No.: 2502Z37110E-RF  
 Polarization: Parallel  
 Test Mode: Transmitting  
 Note: 5G  
 RBW:9kHz,VBW:30kHz


Serial No.: 3CX7-1  
 Tester: Jayce Wang



30MHz-1GHz

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 5G  
RBW:120kHz,VBW:500kHz


Serial No.: 3CX7-1  
Tester: Jayce Wang



| No. | Frequency (MHz) | Reading (dBUV) | Factor (dB/m) | Result (dBUV/m) | Limit (dBUV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 30.97           | 36.50          | -4.58         | 31.92           | 40.00          | 8.08        | Peak        |
| 2   | 73.65           | 43.13          | -16.53        | 26.60           | 40.00          | 13.40       | Peak        |
| 3   | 106.63          | 42.77          | -11.84        | 30.93           | 43.50          | 12.57       | Peak        |
| 4   | 120.21          | 41.78          | -10.20        | 31.58           | 43.50          | 11.92       | Peak        |
| 5   | 136.70          | 40.83          | -10.55        | 30.28           | 43.50          | 13.22       | Peak        |
| 6   | 264.74          | 37.29          | -9.57         | 27.72           | 46.00          | 18.28       | Peak        |

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 5G  
RBW:120kHz,VBW:500kHz

Serial No.: 3CX7-1  
Tester: Jayce Wang



2) 1-40GHz:

|                |           |              |                       |
|----------------|-----------|--------------|-----------------------|
| Serial Number: | 3CX7-1    | Test Date:   | 2025/11/25~2025/11/26 |
| Test Site:     | Chamber B | Test Mode:   | Transmitting          |
| Tester:        | Leo Xiao  | Test Result: | Pass                  |

|                           |           |                           |       |                        |       |
|---------------------------|-----------|---------------------------|-------|------------------------|-------|
| Environmental Conditions: |           |                           |       |                        |       |
| Temperature:<br>(°C)      | 23.1~23.6 | Relative Humidity:<br>(%) | 28~29 | ATM Pressure:<br>(kPa) | 101.4 |

Test Equipment List and Details:

| Manufacturer          | Description                                            | Model                     | Serial Number     | Calibration Date | Calibration Due Date |
|-----------------------|--------------------------------------------------------|---------------------------|-------------------|------------------|----------------------|
| ETS-Lindgren          | Horn Antenna                                           | 3115                      | 000 527 35        | 2023/9/7         | 2026/9/6             |
| Ducommun Technologies | Horn Antenna                                           | ARH-4223-02               | 1007726-02 1304   | 2023/2/22        | 2026/2/21            |
| Ducommun Technologies | Horn Antenna                                           | ARH-2823-02               | 1007726-01 1302   | 2023/2/22        | 2026/2/21            |
| Xinhang Macrowave     | Coaxial Cable                                          | XH750A-N/J-SMA/J-10M      | 20231117004 #0001 | 2025/11/17       | 2026/11/16           |
| Xinhang Macrowave     | Coaxial Cable                                          | XH360A-2.92/J-2.92/J-6M-A | 20231208001 #0001 | 2024/12/9        | 2025/12/8            |
| AH                    | Preamplifier                                           | PAM-0118P                 | 469               | 2025/4/11        | 2026/4/10            |
| AH                    | Preamplifier                                           | PAM-1840VH                | 191               | 2025/9/4         | 2026/9/3             |
| R&S                   | Spectrum Analyzer                                      | FSV40                     | 101944            | 2025/8/8         | 2026/8/7             |
| Audix                 | Test Software                                          | E3                        | 191218 V9         | N/A              | N/A                  |
| Decentest             | Multiplex Switch Test Control Set & Filter Switch Unit | DT7220SCU & DT7220FCU     | DC79902 & DC79905 | 2025/8/25        | 2026/8/24            |

\* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Please refer to the below plots.




After pre-scan in the X, Y and Z axes of orientation, the worst case is refer to plots.

1-18GHz:  
5150-5250MHz:


802.11a, Low Channel, 5180MHz, Horizontal






802.11a, Low Channel, 5180MHz, Vertical




802.11a, Middle Channel, 5200MHz, Horizontal






802.11a, Middle Channel, 5200MHz, Vertical




802.11a, High Channel, 5240MHz, Horizontal






802.11a, High Channel, 5240MHz, Vertical




802.11n20, Low Channel, 5180MHz, Horizontal






802.11n20, Low Channel, 5180MHz, Vertical




802.11n20, Middle Channel, 5200MHz,Horizontal






802.11n20, Middle Channel, 5200MHz, Vertical




802.11n20, High Channel, 5240MHz, Horizontal






802.11n20, High Channel, 5240MHz, Vertical




802.11n40, Low Channel, 5190MHz, Horizontal






802.11n40, Low Channel, 5190MHz,Vertical




802.11n40, High Channel, 5230MHz, Horizontal






802.11n40, High Channel, 5230MHz, Vertical



802.11ac80, Middle Channel, 5210MHz,  
Horizontal




802.11ac80, Middle Channel, 5210MHz,  
Vertical






5250-5350MHz:


802.11a, Low Channel, 5260MHz, Horizontal






802.11a, Low Channel, 5260MHz, Vertical




802.11a, Middle Channel, 5280MHz, Horizontal






802.11a, Middle Channel, 5280MHz, Vertical




802.11a, High Channel, 5320MHz, Horizontal






802.11a, High Channel, 5320MHz, Vertical




802.11n20, Low Channel, 5260MHz, Horizontal






802.11n20, Low Channel, 5260MHz, Vertical




802.11n20, Middle Channel, 5280MHz,Horizontal






802.11n20, Middle Channel, 5280MHz, Vertical




802.11n20, High Channel, 5320MHz, Horizontal






802.11n20, High Channel, 5320MHz, Vertical




802.11n40, Low Channel, 5270MHz, Horizontal






802.11n40, Low Channel, 5270MHz,Vertical




802.11n40, High Channel, 5310MHz, Horizontal






802.11n40, High Channel, 5310MHz, Vertical



802.11ac80, Middle Channel, 5290MHz,  
Horizontal




802.11ac80, Middle Channel, 5290MHz,  
Vertical






5470-5725MHz:


802.11a, Low Channel, 5500MHz, Horizontal






802.11a, Low Channel, 5500MHz, Vertical




802.11a, Middle Channel, 5600MHz, Horizontal






802.11a, Middle Channel, 5600MHz, Vertical




802.11a, High Channel, 5700MHz, Horizontal






802.11a, High Channel, 5700MHz, Vertical




802.11n20, Low Channel, 5500MHz, Horizontal






802.11n20, Low Channel, 5500MHz, Vertical




802.11n20, Middle Channel, 5600MHz, Horizontal






802.11n20, Middle Channel, 5600MHz, Vertical




802.11n20, High Channel, 5700MHz, Horizontal






802.11n20, High Channel, 5700MHz, Vertical




802.11n40, Low Channel, 5510MHz, Horizontal






802.11n40, Low Channel, 5510MHz,Vertical




802.11n40, Middle Channel, 5590MHz, Horizontal






802.11n40, Middle Channel, 5590MHz, Vertical




802.11n40, High Channel, 5670MHz, Horizontal






802.11n40, High Channel, 5670MHz, Vertical




802.11ac80, Low Channel, 5530MHz, Horizontal






802.11ac80, Low Channel, 5530MHz, Vertical



802.11ac80, High Channel, 5610MHz, Horizontal




802.11ac80, High Channel, 5610MHz, Vertical






5725-5850MHz:


802.11a, Low Channel, 5745MHz, Horizontal






802.11a, Low Channel, 5745MHz, Vertical




802.11a, Middle Channel, 5785MHz, Horizontal






802.11a, Middle Channel, 5785MHz, Vertical




802.11a, High Channel, 5825MHz, Horizontal






802.11a, High Channel, 5825MHz, Vertical



802.11n20, Low Channel, 5745MHz, Horizontal



802.11n20, Low Channel, 5745MHz, Vertical




## 802.11n20, Middle Channel, 5785MHz, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-3 middle channel 5785MHz  
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao

Date: 2025-11-25




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 6000.60         | 49.80          | 0.45          | 50.25           | 68.20          | 17.95       | Peak        |

## 802.11n20, Middle Channel, 5785MHz, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-3 middle channel 5785MHz  
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao

Date: 2025-11-25




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 6166.70         | 49.82          | 0.19          | 50.01           | 68.20          | 18.19       | Peak        |

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-3 middle channel 5785MHz  
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao

Date: 2025-11-25




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 11570.00        | 47.10          | 3.31          | 50.41           | 74.00          | 23.59       | Peak        |
| 2   | 17355.00        | 48.93          | 7.10          | 56.03           | 68.20          | 12.18       | Peak        |
| 3   | 17972.40        | 47.89          | 11.09         | 58.98           | 74.00          | 15.02       | Peak        |
| 4   | 17972.40        | 36.47          | 11.09         | 47.56           | 54.00          | 6.44        | Average     |

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-3 middle channel 5785MHz  
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 3CX7-1  
Tester: Leo Xiao

Date: 2025-11-25






| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 11570.00        | 47.51          | 3.31          | 50.82           | 74.00          | 23.18       | Peak        |
| 2   | 17355.00        | 48.67          | 7.10          | 55.77           | 68.20          | 12.43       | Peak        |
| 3   | 17951.70        | 47.59          | 10.96         | 58.55           | 74.00          | 15.45       | Peak        |
| 4   | 17951.70        | 36.30          | 10.96         | 47.26           | 54.00          | 6.74        | Average     |


802.11n20, High Channel, 5825MHz, Horizontal






802.11n20, High Channel, 5825MHz, Vertical




802.11n40, Low Channel, 5755MHz, Horizontal






802.11n40, Low Channel, 5755MHz, Vertical




802.11n40, High Channel, 5795MHz, Horizontal






802.11n40, High Channel, 5795MHz, Vertical



802.11ac80, Middle Channel, 5775MHz,  
Horizontal




802.11ac80, Middle Channel, 5775MHz,  
Vertical






18-40GHz:

No Emission was detected in the range 18-40GHz, test was performed on the mode and channel which with the maximum power.

802.11a 5825MHz, Horizontal




802.11a 5825MHz, Vertical




Bandedge:  
5150-5250MHz:


802.11a, 5180MHz, Bandedge, Horizontal




802.11a, 5180MHz, Bandedge, Vertical



802.11a, 5240MHz, Bandedge, Horizontal




802.11a, 5240MHz, Bandedge, Vertical



## 802.11n20, 5180MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-1 low channel 5180MHz  
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5150.00         | 55.84          | 7.47          | 63.31           | 74.00          | 10.69       | Peak        |
| 2   | 5150.00         | 37.38          | 7.47          | 44.85           | 54.00          | 9.15        | Average     |

## 802.11n20, 5180MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-1 low channel 5180MHz  
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5150.00         | 56.88          | 7.47          | 64.35           | 74.00          | 9.65        | Peak        |
| 2   | 5150.00         | 38.27          | 7.47          | 45.74           | 54.00          | 8.26        | Average     |

## 802.11n20, 5240MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-1 high channel 5240MHz  
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5350.00         | 50.35          | 8.01          | 58.36           | 74.00          | 15.64       | Peak        |
| 2   | 5350.00         | 36.31          | 8.01          | 44.32           | 54.00          | 9.68        | Average     |

## 802.11n20, 5240MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-1 high channel 5240MHz  
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5350.00         | 49.88          | 8.01          | 57.89           | 74.00          | 16.11       | Peak        |
| 2   | 5350.00         | 36.29          | 8.01          | 44.30           | 54.00          | 9.70        | Average     |

### 802.11n40, 5190MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n40\_U-NII-1 low channel 5190MHz  
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5150.00         | 58.79          | 7.47          | 66.26           | 74.00          | 7.74        | Peak        |
| 2   | 5150.00         | 37.38          | 7.47          | 44.85           | 54.00          | 9.15        | Average     |

### 802.11n40, 5190MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n40\_U-NII-1 low channel 5190MHz  
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5150.00         | 62.33          | 7.47          | 69.80           | 74.00          | 4.20        | Peak        |
| 2   | 5150.00         | 37.83          | 7.47          | 45.30           | 54.00          | 8.70        | Average     |

### 802.11n40, 5230MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n40\_U-NII-1 high channel 5230MHz  
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5350.00         | 49.82          | 8.01          | 57.83           | 74.00          | 16.17       | Peak        |
| 2   | 5350.00         | 36.43          | 8.01          | 44.44           | 54.00          | 9.56        | Average     |

### 802.11n40, 5230MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n40\_U-NII-1 high channel 5230MHz  
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5350.00         | 49.58          | 8.01          | 57.59           | 74.00          | 16.41       | Peak        |
| 2   | 5350.00         | 36.42          | 8.01          | 44.43           | 54.00          | 9.57        | Average     |

802.11ac80, 5210MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11ac80\_U-NII-1 middle channel 5210MHz  
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5150.00         | 56.52          | 7.47          | 63.99           | 74.00          | 10.01       | Peak        |
| 2   | 5150.00         | 37.98          | 7.47          | 45.45           | 54.00          | 8.55        | Average     |
| 3   | 5350.00         | 49.23          | 8.01          | 57.24           | 74.00          | 16.76       | Peak        |
| 4   | 5350.00         | 36.89          | 8.01          | 44.90           | 54.00          | 9.10        | Average     |

802.11ac80, 5210MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11ac80\_U-NII-1 middle channel 5210MHz  
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz


Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5143.92         | 59.89          | 7.43          | 67.32           | 74.00          | 6.68        | Peak        |
| 2   | 5143.92         | 39.40          | 7.43          | 46.83           | 54.00          | 7.17        | Average     |
| 3   | 5150.00         | 57.40          | 7.47          | 64.87           | 74.00          | 9.13        | Peak        |
| 4   | 5150.00         | 39.38          | 7.47          | 46.85           | 54.00          | 7.15        | Average     |
| 5   | 5350.00         | 51.15          | 8.01          | 59.16           | 74.00          | 14.84       | Peak        |
| 6   | 5350.00         | 36.43          | 8.01          | 44.44           | 54.00          | 9.56        | Average     |

5250-5350MHz:


802.11a, 5260MHz, Bandedge, Horizontal




802.11a, 5260MHz, Bandedge, Vertical



802.11a, 5320MHz, Bandedge, Horizontal



802.11a, 5320MHz, Bandedge, Vertical




## 802.11n20, 5260MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-2A low channel 5260MHz  
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao

Date: 2025-11-26




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5150.00         | 49.63          | 7.47          | 57.10           | 74.00          | 16.90       | Peak        |
| 2   | 5150.00         | 36.46          | 7.47          | 43.93           | 54.00          | 10.07       | Average     |

## 802.11n20, 5260MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-2A low channel 5260MHz  
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao

Date: 2025-11-26




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5150.00         | 50.40          | 7.47          | 57.87           | 74.00          | 16.13       | Peak        |
| 2   | 5150.00         | 37.21          | 7.47          | 44.68           | 54.00          | 9.32        | Average     |

## 802.11n20, 5320MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-2A high channel 5320MHz  
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao

Date: 2025-11-26




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5350.00         | 53.27          | 8.01          | 61.28           | 74.00          | 12.72       | Peak        |
| 2   | 5350.00         | 36.34          | 8.01          | 44.35           | 54.00          | 9.65        | Average     |

## 802.11n20, 5320MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-2A high channel 5320MHz  
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 3CX7-1  
Tester: Leo Xiao

Date: 2025-11-26




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5350.00         | 58.14          | 8.01          | 66.15           | 74.00          | 7.85        | Peak        |
| 2   | 5350.00         | 37.31          | 8.01          | 45.32           | 54.00          | 8.68        | Average     |


802.11n40, 5270MHz, Bandedge, Horizontal




802.11n40, 5270MHz, Bandedge, Vertical



802.11n40, 5310MHz, Bandedge, Horizontal




802.11n40, 5310MHz, Bandedge, Vertical



802.11ac80, 5290MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11ac80\_U-NII-2A middle channel 5290MHz  
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5150.00         | 50.08          | 7.47          | 57.55           | 74.00          | 16.45       | Peak        |
| 2   | 5150.00         | 36.20          | 7.47          | 43.67           | 54.00          | 10.33       | Average     |
| 3   | 5350.00         | 56.34          | 8.01          | 64.35           | 74.00          | 9.65        | Peak        |
| 4   | 5350.00         | 38.89          | 8.01          | 46.90           | 54.00          | 7.10        | Average     |

802.11ac80, 5290MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11ac80\_U-NII-2A middle channel 5290MHz  
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz


Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5150.00         | 49.85          | 7.47          | 57.32           | 74.00          | 16.68       | Peak        |
| 2   | 5150.00         | 36.59          | 7.47          | 44.06           | 54.00          | 9.94        | Average     |
| 3   | 5350.00         | 60.14          | 8.01          | 68.15           | 74.00          | 5.85        | Peak        |
| 4   | 5350.00         | 42.43          | 8.01          | 50.44           | 54.00          | 3.56        | Average     |

5470-5725MHz:


802.11a, 5500MHz, Bandedge, Horizontal




802.11a, 5500MHz, Bandedge, Vertical



802.11a, 5700MHz, Bandedge, Horizontal




802.11a, 5700MHz, Bandedge, Vertical



802.11n20, 5500MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-2C low channel 5500MHz  
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5460.00         | 50.88          | 8.29          | 59.17           | 74.00          | 14.83       | Peak        |
| 2   | 5460.00         | 36.46          | 8.29          | 44.75           | 54.00          | 9.25        | Average     |
| 3   | 5470.00         | 51.15          | 8.35          | 59.50           | 68.20          | 8.70        | Peak        |

802.11n20, 5500MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-2C low channel 5500MHz  
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5460.00         | 53.06          | 8.29          | 61.35           | 74.00          | 12.65       | Peak        |
| 2   | 5460.00         | 37.67          | 8.29          | 45.96           | 54.00          | 8.04        | Average     |
| 3   | 5470.00         | 53.49          | 8.35          | 61.84           | 68.20          | 6.36        | Peak        |

802.11n20, 5700MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-2C high channel 5700MHz  
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5725.00         | 52.12          | 8.93          | 61.05           | 68.20          | 7.15        | Peak        |
| 2   | 5727.40         | 54.69          | 8.92          | 63.61           | 68.20          | 4.59        | Peak        |

802.11n20, 5700MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-2C high channel 5700MHz  
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5725.00         | 53.69          | 8.93          | 62.62           | 68.20          | 5.58        | Peak        |
| 2   | 5726.54         | 55.81          | 8.92          | 64.73           | 68.20          | 3.47        | Peak        |

**802.11n40, 5510MHz, Bandedge, Horizontal**

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n40\_U-NII-2C low channel 5510MHz  
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5460.00         | 51.20          | 8.29          | 59.49           | 74.00          | 14.51       | Peak        |
| 2   | 5460.00         | 36.35          | 8.29          | 44.64           | 54.00          | 9.36        | Average     |
| 3   | 5470.00         | 53.25          | 8.35          | 61.60           | 68.20          | 6.60        | Peak        |

**802.11n40, 5510MHz, Bandedge, Vertical**

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n40\_U-NII-2C low channel 5510MHz  
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5460.00         | 54.25          | 8.29          | 62.54           | 74.00          | 11.46       | Peak        |
| 2   | 5460.00         | 37.24          | 8.29          | 45.53           | 54.00          | 8.47        | Average     |
| 3   | 5470.00         | 56.36          | 8.35          | 64.71           | 68.20          | 3.49        | Peak        |

**802.11n40, 5670MHz, Bandedge, Horizontal**

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n40\_U-NII-2C high channel 5670MHz  
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5725.00         | 50.39          | 8.93          | 59.32           | 68.20          | 8.88        | Peak        |

**802.11n40, 5670MHz, Bandedge, Vertical**

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n40\_U-NII-2C high channel 5670MHz  
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5725.00         | 51.29          | 8.93          | 60.22           | 68.20          | 7.98        | Peak        |

### 802.11ac80, 5530MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11ac80\_U-NII-2C low channel 5530MHz  
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5460.00         | 50.65          | 8.29          | 58.94           | 74.00          | 15.06       | Peak        |
| 2   | 5460.00         | 37.56          | 8.29          | 45.85           | 74.00          | 8.15        | Average     |
| 3   | 5470.00         | 53.27          | 8.35          | 61.62           | 68.20          | 6.58        | Peak        |

### 802.11ac80, 5530MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11ac80\_U-NII-2C low channel 5530MHz  
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5456.02         | 53.82          | 8.27          | 62.09           | 74.00          | 11.91       | Peak        |
| 2   | 5456.02         | 37.45          | 8.27          | 45.72           | 74.00          | 8.28        | Average     |
| 3   | 5460.00         | 53.32          | 8.29          | 61.61           | 74.00          | 12.39       | Peak        |
| 4   | 5460.00         | 37.77          | 8.29          | 46.06           | 74.00          | 7.94        | Average     |
| 5   | 5470.00         | 55.79          | 8.35          | 64.14           | 68.20          | 4.06        | Peak        |

### 802.11ac80, 5610MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11ac80\_U-NII-2C high channel 5610MHz  
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5725.00         | 50.51          | 8.93          | 59.44           | 68.20          | 8.76        | Peak        |
| 2   | 5750.55         | 52.07          | 9.00          | 61.07           | 68.20          | 7.13        | Peak        |

### 802.11ac80, 5610MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11ac80\_U-NII-2C high channel 5610MHz  
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5725.00         | 50.83          | 8.93          | 59.76           | 68.20          | 8.44        | Peak        |

5725-5850MHz:

802.11a, 5745MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11a,U-NII-3 low channel 5745MHz  
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5650.00         | 49.56          | 8.82          | 58.38           | 68.20          | 9.82        | Peak        |
| 2   | 5700.00         | 50.27          | 8.85          | 59.12           | 105.20         | 46.08       | Peak        |
| 3   | 5720.00         | 58.66          | 8.91          | 67.57           | 110.80         | 43.23       | Peak        |
| 4   | 5725.00         | 62.31          | 8.93          | 71.24           | 122.20         | 50.96       | Peak        |

802.11a, 5745MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11a,U-NII-3 low channel 5745MHz  
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5650.00         | 50.88          | 8.82          | 59.70           | 68.20          | 8.50        | Peak        |
| 2   | 5700.00         | 53.12          | 8.85          | 61.97           | 105.20         | 43.23       | Peak        |
| 3   | 5720.00         | 63.72          | 8.91          | 72.63           | 110.80         | 38.17       | Peak        |
| 4   | 5725.00         | 68.36          | 8.93          | 77.29           | 122.20         | 44.91       | Peak        |

802.11a, 5825MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11a,U-NII-3 high channel 5825MHz  
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5850.00         | 56.57          | 9.10          | 65.67           | 122.20         | 56.53       | Peak        |
| 2   | 5855.00         | 53.02          | 9.12          | 62.14           | 110.80         | 48.66       | Peak        |
| 3   | 5875.00         | 51.20          | 9.16          | 60.36           | 105.20         | 44.84       | Peak        |
| 4   | 5925.00         | 50.32          | 9.24          | 59.56           | 68.20          | 8.64        | Peak        |

802.11a, 5825MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11a,U-NII-3 high channel 5825MHz  
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5850.00         | 58.13          | 9.10          | 67.23           | 122.20         | 54.97       | Peak        |
| 2   | 5855.00         | 54.21          | 9.12          | 63.33           | 110.80         | 47.47       | Peak        |
| 3   | 5875.00         | 51.39          | 9.16          | 60.55           | 105.20         | 44.65       | Peak        |
| 4   | 5925.00         | 50.17          | 9.24          | 59.41           | 68.20          | 8.79        | Peak        |

**802.11n20, 5745MHz, Bandedge, Horizontal**

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-3 low channel 5745MHz  
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5650.00         | 50.35          | 8.82          | 59.17           | 68.20          | 9.03        | Peak        |
| 2   | 5700.00         | 51.17          | 8.85          | 60.02           | 105.20         | 45.18       | Peak        |
| 3   | 5720.00         | 56.27          | 8.91          | 65.18           | 110.80         | 45.62       | Peak        |
| 4   | 5725.00         | 61.64          | 8.93          | 70.57           | 122.20         | 51.63       | Peak        |

**802.11n20, 5745MHz, Bandedge, Vertical**

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-3 low channel 5745MHz  
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5650.00         | 50.02          | 8.82          | 58.84           | 68.20          | 9.36        | Peak        |
| 2   | 5700.00         | 50.40          | 8.85          | 59.25           | 105.20         | 45.95       | Peak        |
| 3   | 5720.00         | 58.93          | 8.91          | 67.84           | 110.80         | 42.96       | Peak        |
| 4   | 5725.00         | 63.48          | 8.93          | 72.41           | 122.20         | 49.79       | Peak        |

**802.11n20, 5825MHz, Bandedge, Horizontal**

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-3 high channel 5825MHz  
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5850.00         | 56.44          | 9.10          | 65.54           | 122.20         | 56.66       | Peak        |
| 2   | 5855.00         | 52.24          | 9.12          | 61.36           | 110.80         | 49.44       | Peak        |
| 3   | 5875.00         | 50.64          | 9.16          | 59.80           | 105.20         | 45.40       | Peak        |
| 4   | 5925.00         | 50.23          | 9.24          | 59.47           | 68.20          | 8.73        | Peak        |

**802.11n20, 5825MHz, Bandedge, Vertical**

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n20\_U-NII-3 high channel 5825MHz  
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5850.00         | 59.33          | 9.10          | 68.43           | 122.20         | 53.77       | Peak        |
| 2   | 5855.00         | 54.36          | 9.12          | 63.48           | 110.80         | 47.32       | Peak        |
| 3   | 5875.00         | 50.33          | 9.16          | 59.49           | 105.20         | 45.71       | Peak        |
| 4   | 5925.00         | 49.86          | 9.24          | 59.10           | 68.20          | 9.10        | Peak        |

## 802.11n40, 5755MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n40\_U-NII-3 low channel 5755MHz  
Peak: RBW: 1MHz, VBW: 3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5650.00         | 50.34          | 8.82          | 59.16           | 68.20          | 9.04        | Peak        |
| 2   | 5700.00         | 50.64          | 8.85          | 59.49           | 105.20         | 45.71       | Peak        |
| 3   | 5720.00         | 61.64          | 8.91          | 70.55           | 110.80         | 40.25       | Peak        |
| 4   | 5721.03         | 61.63          | 8.92          | 70.55           | 113.15         | 42.60       | Peak        |
| 5   | 5725.00         | 59.78          | 8.93          | 68.71           | 122.20         | 53.49       | Peak        |

## 802.11n40, 5755MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n40\_U-NII-3 low channel 5755MHz  
Peak: RBW: 1MHz, VBW: 3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5650.00         | 50.03          | 8.82          | 58.85           | 68.20          | 9.35        | Peak        |
| 2   | 5700.00         | 51.76          | 8.85          | 60.61           | 105.20         | 44.59       | Peak        |
| 3   | 5720.00         | 65.21          | 8.91          | 74.12           | 110.80         | 36.68       | Peak        |
| 4   | 5721.10         | 65.20          | 8.92          | 74.12           | 113.32         | 39.20       | Peak        |
| 5   | 5725.00         | 63.65          | 8.93          | 72.58           | 122.20         | 49.62       | Peak        |

## 802.11n40, 5795MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11n40\_U-NII-3 high channel 5795MHz  
Peak: RBW: 1MHz, VBW: 3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5850.00         | 51.90          | 9.10          | 61.00           | 122.20         | 61.20       | Peak        |
| 2   | 5855.00         | 50.59          | 9.12          | 59.71           | 110.80         | 51.09       | Peak        |
| 3   | 5875.00         | 50.04          | 9.16          | 59.20           | 105.20         | 46.00       | Peak        |
| 4   | 5925.00         | 50.27          | 9.24          | 59.51           | 68.20          | 8.69        | Peak        |

## 802.11n40, 5795MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11n40\_U-NII-3 high channel 5795MHz  
Peak: RBW: 1MHz, VBW: 3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5850.00         | 52.90          | 9.10          | 62.00           | 122.20         | 60.20       | Peak        |
| 2   | 5855.00         | 50.62          | 9.12          | 59.74           | 110.80         | 51.06       | Peak        |
| 3   | 5875.00         | 50.38          | 9.16          | 59.54           | 105.20         | 45.66       | Peak        |
| 4   | 5925.00         | 50.40          | 9.24          | 59.64           | 68.20          | 8.56        | Peak        |

802.11ac80, 5775MHz, Bandedge, Horizontal

Project No.: 2502Z37110E-RF  
Polarization: Horizontal  
Test Mode: Transmitting  
Note: 802.11ac80\_U-NII-3 middle channel 5775MHz  
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5650.00         | 50.32          | 8.82          | 59.14           | 68.20          | 9.06        | Peak        |
| 2   | 5700.00         | 54.96          | 8.85          | 63.81           | 105.20         | 41.39       | Peak        |
| 3   | 5714.17         | 58.99          | 8.90          | 67.89           | 109.17         | 41.28       | Peak        |
| 4   | 5720.00         | 58.17          | 8.91          | 67.08           | 110.80         | 43.72       | Peak        |
| 5   | 5725.00         | 58.25          | 8.93          | 67.18           | 122.20         | 55.02       | Peak        |
| 6   | 5850.00         | 52.94          | 9.10          | 62.04           | 122.20         | 60.16       | Peak        |
| 7   | 5855.00         | 53.72          | 9.12          | 62.84           | 110.80         | 47.96       | Peak        |
| 8   | 5875.00         | 50.77          | 9.16          | 59.93           | 105.20         | 45.27       | Peak        |
| 9   | 5925.00         | 49.71          | 9.24          | 58.95           | 68.20          | 9.25        | Peak        |

802.11ac80, 5775MHz, Bandedge, Vertical

Project No.: 2502Z37110E-RF  
Polarization: Vertical  
Test Mode: Transmitting  
Note: 802.11ac80\_U-NII-3 middle channel 5775MHz  
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3CX7-1  
Tester: Leo Xiao



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Measurement |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|-------------|
| 1   | 5650.00         | 50.20          | 8.82          | 59.02           | 68.20          | 9.18        | Peak        |
| 2   | 5700.00         | 57.28          | 8.85          | 66.13           | 105.20         | 39.07       | Peak        |
| 3   | 5720.00         | 60.45          | 8.91          | 69.36           | 110.80         | 41.44       | Peak        |
| 4   | 5725.00         | 61.79          | 8.93          | 70.72           | 122.20         | 51.48       | Peak        |
| 5   | 5850.00         | 55.26          | 9.10          | 64.36           | 122.20         | 57.84       | Peak        |
| 6   | 5855.00         | 56.29          | 9.12          | 65.41           | 110.80         | 45.39       | Peak        |
| 7   | 5875.00         | 50.69          | 9.16          | 59.85           | 105.20         | 45.35       | Peak        |
| 8   | 5925.00         | 50.15          | 9.24          | 59.39           | 68.20          | 8.81        | Peak        |

5.3 Emission Bandwidth

Test Information:

|             |          |              |                       |
|-------------|----------|--------------|-----------------------|
| Serial No.: | 3CX7-6   | Test Date:   | 2025/12/20~2025/12/22 |
| Test Site:  | RF       | Test Mode:   | Transmitting          |
| Tester:     | Conor Fu | Test Result: | Pass                  |

Environmental Conditions:

|                      |           |                              |       |                        |       |
|----------------------|-----------|------------------------------|-------|------------------------|-------|
| Temperature:<br>(°C) | 24.1-24.5 | Relative<br>Humidity:<br>(%) | 52-59 | ATM Pressure:<br>(kPa) | 101.4 |
|----------------------|-----------|------------------------------|-------|------------------------|-------|

Test Equipment List and Details:

| Manufacturer | Description        | Model  | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------|--------|---------------|------------------|----------------------|
| Narda        | Coaxial Attenuator | 773-10 | F-08-EM511    | 2025/06/06       | 2026/06/05           |
| R&S          | Spectrum Analyzer  | FSV40  | 101461        | 2025/08/03       | 2026/08/02           |

\* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

26dB Emission Bandwidth  
5150-5250MHz

| Mode       | Test Frequency<br>(MHz) | Result<br>(MHz) |
|------------|-------------------------|-----------------|
| 802.11a    | 5180                    | 20.291          |
|            | 5200                    | 20.291          |
|            | 5240                    | 19.920          |
| 802.11n20  | 5180                    | 20.441          |
|            | 5200                    | 20.543          |
|            | 5240                    | 20.595          |
| 802.11n40  | 5190                    | 41.141          |
|            | 5230                    | 40.641          |
| 802.11ac80 | 5210                    | 81.682          |

**5250-5350MHz**

| Mode       | Test Frequency (MHz) | Result (MHz) |
|------------|----------------------|--------------|
| 802.11a    | 5260                 | 19.970       |
|            | 5280                 | 19.820       |
|            | 5320                 | 19.970       |
| 802.11n20  | 5260                 | 20.544       |
|            | 5280                 | 20.544       |
|            | 5320                 | 20.544       |
| 802.11n40  | 5270                 | 41.141       |
|            | 5310                 | 40.941       |
| 802.11ac80 | 5290                 | 81.481       |

**5470-5725MHz**


| Mode       | Test Frequency (MHz) | Result (MHz) |
|------------|----------------------|--------------|
| 802.11a    | 5500                 | 20.291       |
|            | 5600                 | 20.240       |
|            | 5700                 | 19.970       |
|            | 5720                 | 20.392       |
| 802.11n20  | 5500                 | 20.493       |
|            | 5600                 | 20.595       |
|            | 5700                 | 20.748       |
|            | 5720                 | 20.595       |
| 802.11n40  | 5510                 | 41.041       |
|            | 5590                 | 41.141       |
|            | 5670                 | 40.841       |
|            | 5710                 | 40.841       |
| 802.11ac80 | 5530                 | 81.281       |
|            | 5610                 | 81.682       |
|            | 5690                 | 81.481       |

**6dB Emission Bandwidth  
5725-5850MHz**

| Mode       | Test Frequency (MHz) | Result (MHz) | Limit (MHz) | Verdict |
|------------|----------------------|--------------|-------------|---------|
| 802.11a    | 5745                 | 15.215       | 0.5         | Pass    |
|            | 5785                 | 15.215       | 0.5         | Pass    |
|            | 5825                 | 15.165       | 0.5         | Pass    |
| 802.11n20  | 5745                 | 15.215       | 0.5         | Pass    |
|            | 5785                 | 15.215       | 0.5         | Pass    |
|            | 5825                 | 15.265       | 0.5         | Pass    |
| 802.11n40  | 5755                 | 35.235       | 0.5         | Pass    |
|            | 5795                 | 35.335       | 0.5         | Pass    |
| 802.11ac80 | 5775                 | 75.475       | 0.5         | Pass    |


5150-5250MHz

802.11a\_5180MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:42:25

802.11a\_5200MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:43:55

802.11a\_5240MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:45:11

802.11n20\_5180MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:46:45

802.11n20\_5200MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:48:12

802.11n20\_5240MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:49:42

802.11n40\_5190MHz



ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:51:21


802.11n40\_5230MHz



ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:52:32


5250-5350MHz

802.11ac80\_5210MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:54:47

802.11a\_5260MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:12:28

802.11a\_5280MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:13:57

802.11a\_5320MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:15:26

802.11n20\_5260MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:17:12

802.11n20\_5280MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:18:41

802.11n20\_5320MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:20:06

802.11n40\_5270MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:21:43

802.11n40\_5310MHz



ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:22:49


802.11ac80\_5290MHz



ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:25:11


5470-5725MHz

802.11a\_5500MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:12:26

802.11a\_5600MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:14:02

802.11a\_5700MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:15:29

802.11a\_5720MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:17:03

802.11n20\_5500MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:19:58

802.11n20\_5600MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:21:38

802.11n20\_5700MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:23:20

802.11n20\_5720MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:24:58

802.11n40\_5510MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:27:23

802.11n40\_5590MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:29:20

802.11n40\_5670MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:30:43

802.11n40\_5710MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:31:58

802.11ac80\_5530MHz



ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:40:30


802.11ac80\_5610MHz



ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:41:20


5725-5850MHz

802.11ac80\_5690MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:42:38

802.11a\_5745MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 21:15:04

802.11a\_5785MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 21:16:35

802.11a\_5825MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 21:18:02

802.11n20\_5745MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 21:19:31

802.11n20\_5785MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 21:21:05

802.11n20\_5825MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 21:22:33

802.11n40\_5755MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 21:23:58

802.11n40\_5795MHz



ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 21:25:11

802.11ac80\_5775MHz



ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 21:27:10

5.4 99% Occupied Bandwidth

Test Information:

|             |          |              |                       |
|-------------|----------|--------------|-----------------------|
| Serial No.: | 3CX7-6   | Test Date:   | 2025/12/20~2025/12/22 |
| Test Site:  | RF       | Test Mode:   | Transmitting          |
| Tester:     | Conor Fu | Test Result: | N/A                   |

Environmental Conditions:

|                      |           |                           |       |                        |       |
|----------------------|-----------|---------------------------|-------|------------------------|-------|
| Temperature:<br>(°C) | 24.1-24.5 | Relative Humidity:<br>(%) | 52-59 | ATM Pressure:<br>(kPa) | 101.4 |
|----------------------|-----------|---------------------------|-------|------------------------|-------|

Test Equipment List and Details:

| Manufacturer | Description        | Model  | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------|--------|---------------|------------------|----------------------|
| Narda        | Coaxial Attenuator | 773-10 | F-08-EM511    | 2025/06/06       | 2026/06/05           |
| R&S          | Spectrum Analyzer  | FSV40  | 101461        | 2025/08/03       | 2026/08/02           |

*\* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

5150-5250MHz

| Mode       | Test Frequency<br>(MHz) | 99% OBW<br>(MHz) |
|------------|-------------------------|------------------|
| 802.11a    | 5180                    | 16.450           |
|            | 5200                    | 16.450           |
|            | 5240                    | 16.500           |
| 802.11n20  | 5180                    | 17.550           |
|            | 5200                    | 17.600           |
|            | 5240                    | 17.550           |
| 802.11n40  | 5190                    | 36.200           |
|            | 5230                    | 36.300           |
| 802.11ac80 | 5210                    | 75.200           |

Note:

The 99% Occupied Bandwidth have not fall into the band 5250-5350MHz, please refer to the test plots of 99% Occupied Bandwidth.

**5250-5350MHz**

| Mode       | Test Frequency (MHz) | 99% OBW (MHz) |
|------------|----------------------|---------------|
| 802.11a    | 5260                 | 16.450        |
|            | 5280                 | 16.450        |
|            | 5320                 | 16.450        |
| 802.11n20  | 5260                 | 17.600        |
|            | 5280                 | 17.550        |
|            | 5320                 | 17.550        |
| 802.11n40  | 5270                 | 36.200        |
|            | 5310                 | 36.200        |
| 802.11ac80 | 5290                 | 75.200        |

**5470-5725MHz**

| Mode       | Test Frequency (MHz) | 99% OBW (MHz) |
|------------|----------------------|---------------|
| 802.11a    | 5500                 | 16.400        |
|            | 5600                 | 16.500        |
|            | 5700                 | 16.450        |
|            | 5720                 | 16.450        |
| 802.11n20  | 5500                 | 17.550        |
|            | 5600                 | 17.600        |
|            | 5700                 | 17.600        |
|            | 5720                 | 17.600        |
| 802.11n40  | 5510                 | 36            |
|            | 5590                 | 36.100        |
|            | 5670                 | 36.100        |
|            | 5710                 | 36.100        |
| 802.11ac80 | 5530                 | 75.200        |
|            | 5610                 | 75.200        |
|            | 5690                 | 75.200        |

**5725-5850MHz**


| Mode       | Test Frequency (MHz) | 99% OBW (MHz) |
|------------|----------------------|---------------|
| 802.11a    | 5745                 | 16.500        |
|            | 5785                 | 16.500        |
|            | 5825                 | 16.500        |
| 802.11n20  | 5745                 | 17.550        |
|            | 5785                 | 17.600        |
|            | 5825                 | 17.600        |
| 802.11n40  | 5755                 | 36.200        |
|            | 5795                 | 36.200        |
| 802.11ac80 | 5775                 | 75.200        |

**Note:**

The 99% Occupied Bandwidth have not fall into the band 5470-5725MHz, please refer to the test plots of 99% Occupied Bandwidth.


5150-5250MHz

802.11a\_5180MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:42:50

802.11a\_5200MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:44:17

802.11a\_5240MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:45:32

802.11n20\_5180MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:47:09

802.11n20\_5200MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:48:34

802.11n20\_5240MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:50:07

802.11n40\_5190MHz



ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:51:36


802.11n40\_5230MHz



ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:52:46


5250-5350MHz

802.11ac80\_5210MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 19:53:56

802.11a\_5260MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:12:51

802.11a\_5280MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:14:22

802.11a\_5320MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:15:49

802.11n20\_5260MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:17:34

802.11n20\_5280MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:19:05

802.11n20\_5320MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:20:31

802.11n40\_5270MHz




ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:21:58

802.11n40\_5310MHz



ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:23:04


802.11ac80\_5290MHz



ProjectNo.:2502237110E-RF Tester:Conor Fu  
Date: 20.DEC.2025 20:24:20


5470-5725MHz

802.11a\_5500MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:12:52

802.11a\_5600MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:14:25

802.11a\_5700MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:15:56

802.11a\_5720MHz




ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:17:26

802.11n20\_5500MHz



ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:20:25

802.11n20\_5600MHz



ProjectNo.:2502Z37110E-RF Tester:Conor Fu  
Date: 22.DEC.2025 19:22:02