

FCC SAR TEST REPORT

Applicant: Shenzhen Xinguodu Technology Co.,Ltd.

Address: 17B JinSong Mansion, Tairan 4th Road, Shatou Street, Futian District, Shenzhen, Guangdong, China.

Product Name: POS terminal

Brand Name: NEXGO

FCC ID: XDQN86PRO-01

Standard(s): 47 CFR Part 2(2.1093)

Report Number: 2502Q44141E-20A1

Report Date: 2026/10/09

The above device has been tested and found compliant with the requirement of the relevant standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Rocky Xiao

Reviewed By: Rocky Xiao
Title: RF Supervisor

Brave Lu

Approved By: Brave Lu
Title: SAR Supervisor

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888
Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

SAR TEST RESULTS SUMMARY

Body SAR:

Mode		Max. Reported SAR Level(s) (W/kg)	Limit (W/kg)
GSM 850	1g Body SAR	0.38	1.6
PCS 1900	1g Body SAR	0.08	
WCDMA Band 2	1g Body SAR	0.11	
WCDMA Band 5	1g Body SAR	0.13	
LTE Band 2	1g Body SAR	0.15	
LTE Band 4	1g Body SAR	0.24	
LTE Band 5	1g Body SAR	0.13	
LTE Band 7	1g Body SAR	0.43	
LTE Band 38	1g Body SAR	0.35	
WLAN 2.4G	1g Body SAR	0.16	
WLAN 5.2G	1g Body SAR	0.65	
WLAN 5.3G	1g Body SAR	0.52	
WLAN 5.6G	1g Body SAR	0.39	
WLAN 5.8G	1g Body SAR	0.19	
Simultaneous	1g Body SAR	1.08	

Limb SAR:

Mode		Max. Reported SAR Level(s) (W/kg)	Limit (W/kg)
GSM 850	10g Extremity SAR	1.28	4.0
PCS 1900	10g Extremity SAR	1.46	
WCDMA Band 2	10g Extremity SAR	1.90	
WCDMA Band 5	10g Extremity SAR	0.56	
LTE Band 2	10g Extremity SAR	2.09	
LTE Band 4	10g Extremity SAR	1.72	
LTE Band 5	10g Extremity SAR	0.52	
LTE Band 7	10g Extremity SAR	1.02	
LTE Band 38	10g Extremity SAR	0.66	
WLAN 2.4G	10g Extremity SAR	0.47	
WLAN 5.2G	10g Extremity SAR	0.53	
WLAN 5.3G	10g Extremity SAR	0.54	
WLAN 5.6G	10g Extremity SAR	0.57	
WLAN 5.8G	10g Extremity SAR	0.36	
Simultaneous	10g Extremity SAR	2.66	

Note: Except WLAN(Wi-Fi), the test results of other bands, please refer to the SAR report: 2502Q44141E-20, which was issued by Bay Area Compliance Laboratories Corp.(Dongguan).

Applicable Standards	FCC 47 CFR part 2.1093 Radiofrequency radiation exposure evaluation: portable devices
	IEEE1528:2013 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
	RF Exposure Procedures: TCB Workshop April 2019
	KDB procedures KDB 447498 D01 General RF Exposure Guidance v06 KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04 KDB 865664 D02 RF Exposure Reporting v01r02 KDB 941225 D01 3G SAR Procedures v03r01 KDB 941225 D05 SAR for LTE Devices v02r05 KDB 248227 D01 802.11 Wi-Fi SAR v02r02 KDB 775926 D01 SAR Testing for Irregular Shaped Devices v01
Note: This wireless device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in FCC 47 CFR part 2.1093 and has been tested in accordance with the measurement procedures specified in IEEE 1528-2013 and RF exposure KDB procedures. The results and statements contained in this report pertain only to the device(s) evaluated.	

CONTENTS

SAR TEST RESULTS SUMMARY	2
DOCUMENT REVISION HISTORY	6
1. GENERAL INFORMATION	7
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	7
2. REFERENCE, STANDARDS, AND GUIDELINES	9
2.1 SAR LIMITS.....	9
2.2 TEST FACILITY	10
3. DESCRIPTION OF TEST SYSTEM.....	11
4. EQUIPMENT LIST AND CALIBRATION	16
4.1 EQUIPMENTS LIST & CALIBRATION INFORMATION	16
5. SAR MEASUREMENT SYSTEM VERIFICATION	17
5.1 LIQUID VERIFICATION.....	17
5.2 LIQUID VERIFICATION RESULTS	17
5.3 SYSTEM ACCURACY VERIFICATION	19
5.4 SYSTEM ACCURACY CHECK RESULTS.....	19
5.5 SAR SYSTEM VALIDATION DATA	21
6. EUT TEST STRATEGY AND METHODOLOGY	27
6.1 TEST POSITIONS FOR BODY-WORN AND OTHER CONFIGURATIONS	27
6.2 TEST DISTANCE FOR SAR EVALUATION.....	27
7. CONDUCTED OUTPUT POWER MEASUREMENT.....	28
7.1 TEST PROCEDURE	28
7.2 RADIO CONFIGURATION	28
7.3 MAXIMUM TARGET OUTPUT POWER	34
7.4 TEST RESULTS:.....	35
8. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	42
8.1 ANTENNAS LOCATION:	42
8.2 ANTENNA DISTANCE TO EDGE.....	42
8.3 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	42
8.4 STANDALONE SAR ESTIMATION:	44
8.5 SAR TEST EXCLUSION FOR THE EUT EDGE CONSIDERATIONS RESULT	44
9. SAR MEASUREMENT RESULTS.....	46
9.1 SAR TEST DATA	46
10. MEASUREMENT VARIABILITY	54
11. DUT HOLDER PERTURBATIONS.....	55
12. SAR SIMULTANEOUS TRANSMISSION DESCRIPTION	56
12.1 SIMULTANEOUS TRANSMISSION:.....	56

12.2 SIMULTANEOUS SAR TEST EXCLUSION CONSIDERATIONS:	56
APPENDIX A - MEASUREMENT UNCERTAINTY	57
APPENDIX B - SAR PLOTS	58
APPENDIX C - EUT TEST POSITION PHOTOS	59
APPENDIX D - PROBE CALIBRATION CERTIFICATES	60
APPENDIX E - DIPOLE CALIBRATION CERTIFICATES	61
APPENDIX F - RETURN LOSS AND IMPEDANCE MEASUREMENT	62

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2502Q44141E-20	Original Report	2025/03/26
2.0	2502Q44141E-20A1	Amended Report	2026/10/09

Note: This is the amended report application which was based on the original report. The differences between them are as follows:

1. Change the applicant's address to 17B JinSong Mansion, Tairan 4th Road, Shatou Street, Futian District, Shenzhen, Guangdong, China.
2. Add one configuration (Sample 3#).
3. Change the WCN antenna for Sample 3#.
4. Remove one adapter (Model: STC-A520A-Z).
5. Add one Charging Base.

The change between the previous equipment and the current equipment is stated and guaranteed by the manufacturer. The difference between them will affect the test results of WLAN(Wi-Fi/BT), we will perform full test WLAN(Wi-Fi), spot check was performed for the worst case of WWAN(GSM/WCDMA/LTE), the results almost the same as the original report. So the final results of WWAN(GSM/WCDMA/LTE), please refer to the original SAR report, report number: 2502Q44141E-20, which was issued by Bay Area Compliance Laboratories Corp.(Dongguan).

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	POS terminal
EUT Model:	N86 Pro
Brand Name:	NEXGO
Device Type:	Portable
Exposure Category:	Population / Uncontrolled
Antenna Type(s):	Internal Antenna
Body-Worn Accessories:	None
Proximity Sensor:	None
Carrier Aggregation:	None
Operation Modes:	GPRS/EGPRS Data, WCDMA(R99 (Data), HSUPA/HSDPA/HSPA+), FDD-LTE, TDD-LTE,WLAN, Bluetooth, BLE and NFC
Frequency Band:	GSM 850: 824-849 MHz(TX); 869-894 MHz(RX)
	PCS 1900: 1850-1910 MHz(TX); 1930-1990 MHz(RX)
	WCDMA Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX)
	WCDMA Band 5: 824-849 MHz(TX); 869-894 MHz(RX)
	LTE Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX)
	LTE Band 4: 1710-1755 MHz(TX); 2110-2155 MHz(RX)
	LTE Band 5: 824-849 MHz(TX); 869-894 MHz(RX)
	LTE Band 7: 2500-2570 MHz(TX); 2620-2690 MHz(RX)
	LTE Band 38: 2570-2620 MHz(TX); 2570-2620 MHz(RX)
	Wi-Fi 2.4G: 2412-2462 MHz/2422-2452 MHz(TX/RX)
	Wi-Fi 5.2G: 5150-5250 MHz(TX/RX)
	Wi-Fi 5.3G: 5250-5350 MHz(TX/RX)
	Wi-Fi 5.6G: 5470-5725 MHz(TX/RX)
	Wi-Fi 5.8G: 5725-5850 MHz(TX/RX)
	Bluetooth: 2402-2480MHz(TX/RX)
	BLE 1M:2402-2480MHz(TX/RX)
	NFC:13.56MHz
Dimensions (L*W*H):	195mm (L) *77mm (W) *71mm (H)
Power Source:	DC 7.2V from Rechargeable Battery
Serial Number:	3TKV-1
Normal Operation:	Body and Limbs
EUT Received Date:	2026/09/14
Test Date:	2026/09/19 ~ 2026/09/20
EUT Received Status:	Good

EUT Information:

Sample	Parameters
Sample 1#	(1GB RAM+8GB ROM) +Front camera 2MP+Back camera 2MP+Double SIM+ Screen 1# (Tianshan)
Sample 2#	(2GB RAM+32GB ROM)+Front camera 2MP+Back camera 5MP+Single ESIM+Single SIM + Screen 2# (Hongzhan) + Flash lamp
Sample 3# (New)	EMCP Memory(2GB RAM+16GB ROM) + Front camera 2MP + Back camera 5MP + Flash lamp + Single ESIM + Single SIM+ Screen 1# (Tianshan)

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
Adapter 1# (Remove)	SHENZHEN RUIJING INDUSTRIAL CO LTD	STC-A520A-Z	Input: 100-240Vac 50/60Hz 400Ma Output: 5.0Vdc 2000Ma
Adapter 2#	Jiangxi Jian Aohai Technology Co.,Ltd.	A319-050200U-US2	Input: 100-240Vac 50/60Hz 0.3A Output: 5.0Vdc 2000Ma
Battery 1#	Zhengzhou BAK Battery Co.,Ltd.	GX11	Nominal Voltage: 7.2V Typical Capacity: 2600mAh Rated Capacity: 2500mAh Typical Energy: 18.72Wh Nominal Energy: 18Wh
Battery 2#	Zhengzhou BAK Battery Co.,Ltd.	GX12	Nominal Voltage: 7.2V Typical Capacity: 3300mAh Rated Capacity: 3200mAh Typical Energy: 23.76Wh Nominal Energy: 23.04Wh
Charging Base (New)	/	/	/

Note: The Sample 3# with Battery 2# was selected to test in this SAR report, for the test results of Sample 1# and 2#, please refer to the original SAR report: 2502Q44141E-20, which was issued by Bay Area Compliance Laboratories Corp.(Dongguan).

2. REFERENCE, STANDARDS, AND GUIDELINES

FCC:

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g average over 1 gram of tissue mass.

2.1 SAR Limits

FCC Limit

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1 g of tissue)	1.6	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that maybe incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

General Population/Uncontrolled environments Spatial Peak limit 1.6 W/kg(FCC) for 1g Body SAR ,limit 4 W/kg(FCC) for 10g Extremity SAR applied to the EUT.

2.2 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. :829273, the FCC Designation No. : CN5044.


3. DESCRIPTION OF TEST SYSTEM

These measurements were performed with the automated near-field scanning system DASY5 from Schmid & Partner Engineering AG (SPEAG) which is the Fifth generation of the system shown in the figure hereinafter:



DASY5 System Description

The DASY5 system for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal application, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7 professional operating system and the DASY52 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

DASY5 Measurement Server

The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz Intel ULV Celeron, 128MB chip-disk and 128MB RAM. The necessary circuits for communication with the DAE4 (or DAE3) electronics box, as well as the 16 bit AD-converter system for optical detection and digital I/O interface are contained on the DASY5 I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized point out, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.



Data Acquisition Electronics

The data acquisition electronics (DAE4) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of both the DAE4 as well as of the DAE3 box is 200M Ω ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

EX3DV4 E-Field Probes

Frequency	4 MHz–10 GHz Linearity: ± 0.2 dB (30 MHz–10 GHz)
Directivity(typical)	± 0.1 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μ W/g – > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Applications	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
Compatibility	DASY3, DASY4, DASY52, DASY6, DASY8, EASY6, EASY4/MRI

SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region, where shell thickness

increases to 6 mm). The phantom has three measurement areas:

- _ Left Head
- _ Right Head
- _ Flat phantom

The phantom table for the DASY systems based on the robots have the size of 100 x 50 x 85 cm (L x W x H). For easy dislocation these tables have fork lift cut outs at the bottom.

The bottom plate contains three pairs of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. Only one device holder is necessary if two phantoms are used (e.g., for different liquids)



A white cover is provided to cover the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on top of this phantom cover are possible.

Three reference marks are provided on the phantom counter. These reference marks are used to teach the absolute phantom position relative to the robot.

Robots

The DASY5 system uses the high precision industrial robot. The robot offers the same features important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchrony motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)

The above mentioned robots are controlled by the Staubli CS7MB robot controllers. All information regarding the use and maintenance of the robot arm and the robot controller is contained on the CDs delivered along with the robot. Paper manuals are available upon request direct from Staubli.

Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 15mm 2 step integral, with 1.5mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the DASY5 software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m³ is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1g cube is 10mm, with the side length of the 10g cube is 21.5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 7 x7 x 7 (5mmx5mmx5mm) providing a volume of 30 mm in the X & Y & Z axis.

Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE1528:2013

Recommended Tissue Dielectric Parameters for Head liquid

Table 3—Target dielectric properties of head tissue-equivalent material in the 300 MHz to 6000 MHz frequency range

Frequency (MHz)	Relative permittivity (ϵ_r)	Conductivity (σ) (S/m)
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1500	40.4	1.23
1640	40.2	1.31
1750	40.1	1.37
1800	40.0	1.40
1900	40.0	1.40
2000	40.0	1.40
2100	39.8	1.49
2300	39.5	1.67
2450	39.2	1.80
2600	39.0	1.96
3000	38.5	2.40
3500	37.9	2.91
4000	37.4	3.43
4500	36.8	3.94
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27
6000	35.1	5.48

NOTE—For convenience, permittivity and conductivity values at some frequencies that are not part of the original data from Drossos et al. [B60] or the extension to 5800 MHz are provided (i.e., the values shown in italics). These values were linearly interpolated between the values in this table that are immediately above and below these values, except the values at 6000 MHz that were linearly extrapolated from the values at 3000 MHz and 5800 MHz.

4. EQUIPMENT LIST AND CALIBRATION


4.1 Equipments List & Calibration Information

Equipment	Model	S/N	Calibration Date	Calibration Due Date
DASY5 Test Software	DASY52.10	N/A	NCR	NCR
DASY5 Measurement Server	DASY5 4.5.12	1470	NCR	NCR
Data Acquisition Electronics	DAE4	1562	2026/1/12	2027/1/11
E-Field Probe	EX3DV4	7329	2026/5/28	2027/5/27
Mounting Device	MD4HHTV5	SD 000 H01 KA	NCR	NCR
Twin SAM	Twin SAM V5.0	1097	NCR	NCR
Dipole, 1900 MHz	D1900V2	543	2025/10/13	2028/10/12
Dipole, 2450 MHz	D2450V2	971	2024/6/15	2027/6/14
Dipole, 2600 MHz	D2600V2	1132	2025/10/14	2028/10/13
Dipole, 5 GHz	D5GHzV2	1246	2025/10/14	2028/10/13
Simulated Tissue Liquid Head	HBBL600-10000V6	SL AAH U126 CA (Batch:250429-1)	N/A	N/A
Network Analyzer	8753C +85047A	3029A01355 +3033A02857	2026/6/15	2027/6/14
Dielectric assessment kit	DAK-3.5	1253	NCR	NCR
Signal Generator	8665B	3438a00584	2026/7/8	2027/7/7
EPM Series Power Meter	E4419B	MY45103907	2026/7/8	2027/7/7
Power Sensor	8482A	US37296108	2026/6/15	2027/6/14
Power Meter	EPM-441A	GB37481494	2026/6/15	2027/6/14
Power Amplifier	ZHL-5W-202-S+	416402204	NCR	NCR
Power Amplifier	ZVE-6W-83+	637202210	NCR	NCR
Directional Coupler	520Z	441493	NCR	NCR
Directional Coupler	1818	0955-0101	NCR	NCR
Attenuator	20dB, 100W	LN749	NCR	NCR
Attenuator	6dB, 150W	2754	NCR	NCR
Thermometer	DTM3000	3635	2026/7/10	2027/7/9
Hygrothermograph	HTC-2	EM072	2026/7/31	2027/7/30
Wireless Communication Test Set	8960	MY50266471	2026/7/8	2027/7/7
Wideband Radio Communication Tester	CMW500	147473	2026/7/8	2027/7/7
Spectrum Analyzer	FSV40	101461	2026/8/3	2027/8/2

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

5. SAR MEASUREMENT SYSTEM VERIFICATION

5.1 Liquid Verification



5.2 Liquid Verification Results

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
1860	Simulated Tissue Liquid Head	40.798	1.386	40	1.4	2.00	-1.00	± 5
1880	Simulated Tissue Liquid Head	40.581	1.395	40	1.4	1.45	-0.36	± 5
1900	Simulated Tissue Liquid Head	40.365	1.404	40	1.4	0.91	0.29	± 5

*Liquid Verification above was performed on 2026/09/20.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
2437	Simulated Tissue Liquid Head	38.095	1.748	39.23	1.79	-2.89	-2.35	± 5
2450	Simulated Tissue Liquid Head	38.007	1.762	39.2	1.8	-3.04	-2.11	± 5

*Liquid Verification above was performed on 2026/09/20.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
2535	Simulated Tissue Liquid Head	40.305	1.839	39.09	1.89	3.11	-2.70	± 5
2600	Simulated Tissue Liquid Head	40.022	1.928	39	1.96	2.62	-1.63	± 5

*Liquid Verification above was performed on 2026/09/19.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
5210	Simulated Tissue Liquid Head	36.977	4.679	35.99	4.67	2.74	0.19	± 5
5250	Simulated Tissue Liquid Head	36.737	4.704	35.95	4.71	2.19	-0.13	± 5
5280	Simulated Tissue Liquid Head	36.556	4.723	35.92	4.74	1.77	-0.36	± 5

*Liquid Verification above was performed on 2026/09/20.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
5600	Simulated Tissue Liquid Head	36.109	5.021	35.5	5.07	1.72	-0.97	± 5
5610	Simulated Tissue Liquid Head	36.079	5.030	35.49	5.08	1.66	-0.98	± 5

*Liquid Verification above was performed on 2026/09/20.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
5785	Simulated Tissue Liquid Head	35.135	5.218	35.32	5.26	-0.52	-0.80	± 5
5800	Simulated Tissue Liquid Head	35.056	5.245	35.3	5.27	-0.69	-0.47	± 5

*Liquid Verification above was performed on 2026/09/20.


5.3 System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of $\pm 10\%$. The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

The spacing distances in the **System Verification Setup Block Diagram** is given by the following:

- $s = 15 \text{ mm} \pm 0,2 \text{ mm}$ for $300 \text{ MHz} \leq f \leq 1\,000 \text{ MHz}$;
- $s = 10 \text{ mm} \pm 0,2 \text{ mm}$ for $1\,000 \text{ MHz} < f \leq 3\,000 \text{ MHz}$;
- $s = 10 \text{ mm} \pm 0,2 \text{ mm}$ for $3\,000 \text{ MHz} < f \leq 6\,000 \text{ MHz}$.
- $s = 0 \text{ mm}$ for $f = 150 \text{ MHz}$ (Loop Antenna).

System Verification Setup Block Diagram



5.4 System Accuracy Check Results

Date	Frequency Band (MHz)	Liquid Type	Input Power (mW)	Measured SAR (W/kg)	Normalized to 1W (W/kg)	Target Value (W/Kg)	Delta (%)	Tolerance (%)
2026/09/20	1900	Simulated Tissue Liquid Head	100	1g 3.95	39.5	39.9	-1.00	± 10
2026/09/20	2450	Simulated Tissue Liquid Head	100	1g 4.97	49.7	52.7	-5.69	± 10
2026/09/19	2600	Simulated Tissue Liquid Head	100	1g 5.34	53.4	55.2	-3.26	± 10
2026/09/20	5250	Simulated Tissue Liquid Head	100	1g 7.89	78.9	79.3	-0.50	± 10
2026/09/20	5600	Simulated Tissue Liquid Head	100	1g 8.16	81.6	81.1	0.62	± 10
2026/09/20	5800	Simulated Tissue Liquid Head	100	1g 7.67	76.7	77.9	-1.54	± 10

Note: All the SAR values are normalized to 1Watt forward power.

Date	Frequency Band (MHz)	Liquid Type	Input Power (mW)	Measured SAR (W/kg)	Normalized to 1W (W/kg)	Target Value (W/Kg)	Delta (%)	Tolerance (%)
2026/09/20	1900	Simulated Tissue Liquid Head	100	10g 2.13	21.3	21	1.43	±10
2026/09/20	2450	Simulated Tissue Liquid Head	100	10g 2.41	24.1	24.8	-2.82	±10
2026/09/19	2600	Simulated Tissue Liquid Head	100	10g 2.56	25.6	25	2.40	±10
2026/09/20	5250	Simulated Tissue Liquid Head	100	10g 2.29	22.9	22.1	3.62	±10
2026/09/20	5600	Simulated Tissue Liquid Head	100	10g 2.33	23.3	22.5	3.56	±10
2026/09/20	5800	Simulated Tissue Liquid Head	100	10g 2.26	22.6	21.4	5.61	±10

Note: All the SAR values are normalized to 1Watt forward power.

5.5 SAR SYSTEM VALIDATION DATA

System Performance 1900MHz Head

DUT: D1900V2; Type: 1900 MHz; Serial: 543

Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 1900$ MHz; $\sigma = 1.404$ S/m; $\epsilon_r = 40.365$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(8.25, 8.25, 8.25) @ 1900 MHz; Calibrated: 2026/5/28
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 2026/1/12
- Phantom: Twin SAM V5.0; Type: QD000P40CC; Serial: TP:1097
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

1900MHz System Check/1900MHz/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 4.30 W/kg

1900MHz System Check/1900MHz/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 55.69 V/m; Power Drift = 0.03 dB


Peak SAR (extrapolated) = 7.06 W/kg

SAR(1 g) = 3.95 W/kg; SAR(10 g) = 2.13 W/kg

Smallest distance from peaks to all points 3 dB below = 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 56.2%

Maximum value of SAR (measured) = 5.88 W/kg



System Performance 2450MHz Head**DUT: D2450V2; Type: 2450 MHz; Serial: 971**

Communication System: UID 0, CW (0); Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.762$ S/m; $\epsilon_r = 38.007$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(7.77, 7.77, 7.77) @ 2450 MHz; Calibrated: 2026/5/28
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 2026/1/12
- Phantom: Twin SAM V5.0; Type: QD000P40CC; Serial: TP:1097
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

2450MHz System Check/2450MHz/Area Scan (7x11x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 7.24 W/kg**2450MHz System Check/2450MHz/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 54.42 V/m; Power Drift = 0.11 dB


Peak SAR (extrapolated) = 9.67 W/kg

SAR(1 g) = 4.97 W/kg; SAR(10 g) = 2.41 W/kg

Smallest distance from peaks to all points 3 dB below = 9 mm

Ratio of SAR at M2 to SAR at M1 = 52.3%

Maximum value of SAR (measured) = 7.93 W/kg



System Performance 2600MHz Head**DUT: D2600V2; Type: 2600MHz; Serial: 1132**

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2600$ MHz; $\sigma = 1.928$ S/m; $\epsilon_r = 40.022$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(7.6, 7.6, 7.6) @ 2600 MHz; Calibrated: 2026/5/28
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 2026/1/12
- Phantom: Twin SAM V5.0; Type: QD000P40CC; Serial: TP:1097
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

2600MHz System Check/2600MHz/Area Scan (7x11x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 8.83 W/kg

2600MHz System Check/2600MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 56.19 V/m; Power Drift = 0.01 dB


Peak SAR (extrapolated) = 10.4 W/kg

SAR(1 g) = 5.34 W/kg; SAR(10 g) = 2.56 W/kg

Smallest distance from peaks to all points 3 dB below = 10 mm

Ratio of SAR at M2 to SAR at M1 = 51.9%

Maximum value of SAR (measured) = 8.52 W/kg



System Performance 5250MHz Head**DUT: D5GHzV2; Type: 5250MHz; Serial:1246**

Communication System: UID 0, CW (0); Frequency: 5250 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5250$ MHz; $\sigma = 4.704$ S/m; $\epsilon_r = 36.737$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(5.42, 5.42, 5.42) @ 5250 MHz; Calibrated: 2026/5/28
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 2026/1/12
- Phantom: Twin SAM V5.0; Type: QD000P40CC; Serial: TP:1097
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

5250MHz System Check/5250 MHz/Area Scan (8x9x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 15.5 W/kg

5250MHz System Check/5250 MHz/Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 43.65 V/m; Power Drift = 0.08 dB


Peak SAR (extrapolated) = 29.4 W/kg

SAR(1 g) = 7.89 W/kg; SAR(10 g) = 2.29 W/kg

Smallest distance from peaks to all points 3 dB below = 6.8 mm

Ratio of SAR at M2 to SAR at M1 = 57.1%

Maximum value of SAR (measured) = 17.7 W/kg



System Performance 5600MHz Head**DUT: D5GHzV2; Type: 5600MHz; Serial:1246**

Communication System: UID 0, CW (0); Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5600$ MHz; $\sigma = 5.021$ S/m; $\epsilon_r = 36.109$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(4.8, 4.8, 4.8) @ 5600 MHz; Calibrated: 2026/5/28
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 2026/1/12
- Phantom: Twin SAM V5.0; Type: QD000P40CC; Serial: TP:1097
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

5600MHz System Check/5600 MHz/Area Scan (10x10x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 17.4 W/kg

5600MHz System Check/5600 MHz/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 39.37 V/m; Power Drift = 0.05 dB


Peak SAR (extrapolated) = 34.8 W/kg

SAR(1 g) = 8.16 W/kg; SAR(10 g) = 2.33 W/kg

Smallest distance from peaks to all points 3 dB below = 7.1 mm

Ratio of SAR at M2 to SAR at M1 = 52.7%

Maximum value of SAR (measured) = 21.0 W/kg



System Performance 5800MHz Head**DUT: D5GHzV2; Type: 5800MHz; Serial:1246**

Communication System: UID 0, CW (0); Frequency: 5800 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 5800$ MHz; $\sigma = 5.245$ S/m; $\epsilon_r = 35.056$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(4.91, 4.91, 4.91) @ 5800 MHz; Calibrated: 2026/5/28
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 2026/1/12
- Phantom: Twin SAM V5.0; Type: QD000P40CC; Serial: TP:1097
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

5800MHz System Check/5800 MHz/Area Scan (10x9x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 16.2 W/kg

5800MHz System Check/5800 MHz/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 39.64 V/m; Power Drift = 0.02 dB


Peak SAR (extrapolated) = 29.6 W/kg

SAR(1 g) = 7.67 W/kg; SAR(10 g) = 2.26 W/kg

Smallest distance from peaks to all points 3 dB below = 7.3 mm

Ratio of SAR at M2 to SAR at M1 = 55.3%

Maximum value of SAR (measured) = 18.4 W/kg



0 dB = 18.4 W/kg = 12.65 dBW/kg

6. EUT TEST STRATEGY AND METHODOLOGY

6.1 Test positions for body-worn and other configurations

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.




Figure 5 – Test positions for body-worn devices

6.2 Test Distance for SAR Evaluation


For Body mode(1g Body SAR) the EUT(Equipment Under Test) is set 5mm away from the phantom, the test distance is 5mm;

For Limb mode(10g Extremity SAR) the EUT is set 0mm away from the phantom, the test distance is 0mm.


7. CONDUCTED OUTPUT POWER MEASUREMENT

7.1 Test Procedure

The RF output of the transmitter was connected to the input of the Wireless Communication Test Set through Attenuator.



The RF output of the transmitter was connected to the input port of the Power Meter through Attenuator.



7.2 Radio Configuration

The power measurement was configured by the Wireless Communication Test Set.

GPRS/EGPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900

Press Connection control to choose the different menus

Press RESET > choose all the reset all settings

Connection Press Signal Off to turn off the signal and change settings

Network Support > GSM + GPRS or GSM + EGSM

Main Service > Packet Data

Service selection > Test Mode A – Auto Slot Config. off

MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting

- > Slot configuration > Uplink/Gamma

- > 33 dBm for GPRS 850

- > 30 dBm for GPRS 1900

- > 27 dBm for EGPRS 850

- > 26 dBm for EGPRS 1900

BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel

Frequency Offset > + 0 Hz

Mode > BCCH and TCH

BCCH Level > -85 dBm (May need to adjust if link is not stable)

BCCH Channel > choose desired test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off

P0 > 4 dB

Slot Config > Unchanged (if already set under MS signal)

TCH > choose desired test channel

Hopping > Off

Main Timeslot > 3

Network Coding Scheme > CS4 (GPRS) and MCS5 (EGPRS)

Bit Stream > 2E9-1 PSR Bit Stream

AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input

Connection Press Signal on to turn on the signal and change settings

WCDMA Release 99

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP

TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP

TS34.121-1 specification.

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subset	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	$\beta_d(\text{SF})$	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR(dB)	0	0	0.5	0.5
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	Ahs= β_{hs}/β_c	30/15			

HSUPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c/β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
	MPR(dB)	0	2	1	2	0
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	$A_{hs}=\beta_{hs}/\beta_c$	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_FCI	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO4 E-TFCI 71 E-TFCI 92 E-TFCI PO 18	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27

HSPA+

Sub-test	β_c (Note3)	β_d	β_{HS} (Note1)	β_{ec}	β_{ed} (2xSF2) (Note 4)	β_{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	β_{ed1} : 30/15 β_{ed2} : 30/15	β_{ed3} : 24/15 β_{ed4} : 24/15	3.5	2.5	14	105	105
Note 1: Δ_{ACK}, Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0). Note 3: DPDCH is not configured, therefore the β_c is set to 1 and $\beta_d = 0$ by default. Note 4: β_{ed} can not be set directly; it is set by Absolute Grant Value. Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.											

The following tests were conducted according to the test requirements in Table C.11.1.4 of 3GPP TS 34.121-1

FDD-LTE

For UE Power Class 1 and 3, the allowed Maximum Power Reduction (MPR) for the maximum output power in Table 6.2.2-1 due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1 and 3

Modulation	Channel bandwidth / Transmission bandwidth (N_{RB})						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

For UE Power Class 1 and 3 the specific requirements and identified sub clauses are specified in Table 6.2.4-1 along with the allowed A-MPR values that may be used to meet these requirements. The allowed A-MPR values specified below in Table 6.2.4.-1 to 6.2.4-15 are in addition to the allowed MPR requirements specified in sub clause 6.2.3.

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (subclause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	N/A
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
NS_05	6.6.3.3.1	1	10, 15, 20	Table 6.2.4-4	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	N/A
NS_07	6.6.2.2.3 6.6.3.3.2	13	10	Table 6.2.4-2	
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	
NS_11	6.6.2.2.1	23	1.4, 3, 5, 10, 15, 20	Table 6.2.4-5	
NS_12	6.6.3.3.5	26	1.4, 3, 5	Table 6.2.4-6	
NS_13	6.6.3.3.6	26	5	Table 6.2.4-7	
NS_14	6.6.3.3.7	26	10, 15	Table 6.2.4-8	
NS_15	6.6.3.3.8	26	1.4, 3, 5, 10, 15	Table 6.2.4-9 Table 6.2.4-10	
NS_16	6.6.3.3.9	27	3, 5, 10	Table 6.2.4-11, Table 6.2.4-12, Table 6.2.4-13	
NS_17	6.6.3.3.10	28	5, 10	Table 5.6-1	N/A
NS_18	6.6.3.3.11	28	5	≥ 2	≤ 1
			10, 15, 20	≥ 1	≤ 4
NS_19	6.6.3.3.12	44	10, 15, 20	Table 6.2.4-14	
NS_20	6.2.2 6.6.2.2.1 6.6.3.2	23	5, 10, 15, 20	Table 6.2.4-15	
...					
NS_32	-	-	-	-	-

TDD-LTE

LTE TDD Band 41 supports 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations and Table 4.2-1 for Special subframe configurations.

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$			$7680 \cdot T_s$		
5	$6592 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$20480 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-	-	-
9	$13168 \cdot T_s$			-	-	-

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Calculated Duty Cycle

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-point Periodicity	Subframe Number										Calculated Duty Cycle (%)
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	63.33
1	5 ms	D	S	U	U	D	D	S	U	U	D	43.33
2	5 ms	D	S	U	D	D	D	S	U	D	D	23.33
3	10 ms	D	S	U	U	U	D	D	D	D	D	31.67
4	10 ms	D	S	U	U	D	D	D	D	D	D	21.67
5	10 ms	D	S	U	D	D	D	D	D	D	D	11.67
6	5 ms	D	S	U	U	U	D	S	U	U	D	53.33

We used configuration 0 for LTE Band 38 SAR test, that is 63.33%(1:1.58) for duty cycle.

7.3 Maximum Target Output Power

Mode/Band	Max Target Power(dBm)			
	Channel			
	Low	Middle	High	Additional
LTE Band 2 1RB	22	22	22	/
LTE Band 2 50%RB	21	21	21	/
LTE Band 2 100%RB	21	21	21	/
LTE Band 7 1RB	23	23	23	/
LTE Band 7 50%RB	22	22	22	/
LTE Band 7 100%RB	22	22	22	/
WLAN 2.4G(802.11b)	11	11	11	/
WLAN 2.4G(802.11g)	13	13	13	/
WLAN 2.4G(802.11n ht20)	12	12	12	/
WLAN 2.4G(802.11n ht40)	9	9	9	/
WLAN 5.2G(802.11a)	12	12	12.5	/
WLAN 5.2G(802.11n20)	12	12	12.4	/
WLAN 5.2G(802.11n40)	12	/	12	/
WLAN 5.2G(802.11ac80)	/	13	/	/
WLAN 5.3G(802.11a)	12.5	12.5	12.5	/
WLAN 5.3G(802.11n20)	12.4	12.4	12.4	/
WLAN 5.3G(802.11n40)	12.4	/	12.4	/
WLAN 5.3G(802.11ac80)	/	12.4	/	/
WLAN 5.6G(802.11a)	12.5	12.5	12.5	12.5
WLAN 5.6G(802.11n20)	12	12	12	12
WLAN 5.6G(802.11n40)	12	12	12	12
WLAN 5.6G(802.11ac80)	13	/	13	13
WLAN 5.8G(802.11a)	12.5	12.5	12	/
WLAN 5.8G(802.11n20)	12.4	12.4	12.4	/
WLAN 5.8G(802.11n40)	12.4	/	12.4	/
WLAN 5.8G(802.11ac80)	/	12.4	/	/
Bluetooth BDR	2.5	2.5	3	/
Bluetooth EDR	2	2	2	/
BLE 1M	0.5	0.5	0.5	/

Note:

1. The Maximum Target Power for LTE bands corresponds to their maximum power in QPSK modes with maximum bandwidth.
2. The Additional channel frequencies of WLAN 5.6G are 5690MHz/5710MHz/5720MHz.

7.4 Test Results:**LTE Band 2:**

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	1@0	21.82	21.19	21.36
		1@3	21.88	21.43	21.37
		1@5	21.81	21.42	21.38
		3@0	21.83	21.35	21.36
		3@1	21.85	21.36	21.38
		3@3	21.68	21.22	21.19
		6@0	20.76	20.39	20.38
	16-QAM	1@0	20.55	20.08	20.07
		1@3	20.56	20.17	20.09
		1@5	20.44	19.99	20.01
		3@0	20.33	20.42	20.19
		3@1	20.50	20.50	20.39
		3@3	20.44	20.44	20.41
		6@0	19.25	19.52	19.48
3M	QPSK	1@0	21.51	21.15	21.37
		1@8	21.20	21.31	21.50
		1@14	21.10	21.38	21.31
		8@0	20.26	20.37	20.15
		8@4	20.19	20.27	20.22
		8@7	20.22	20.22	20.23
		15@0	20.22	20.33	20.22
	16-QAM	1@0	20.08	20.34	20.36
		1@8	19.90	20.25	20.69
		1@14	19.88	20.20	20.52
		8@0	19.07	19.47	19.49
		8@4	19.37	19.37	19.35
		8@7	19.20	19.41	19.34
		15@0	19.24	19.24	19.09
5M	QPSK	1@0	21.07	21.10	21.08
		1@12	21.32	21.48	21.37
		1@24	21.18	21.26	21.25
		12@0	20.19	20.26	20.02
		12@7	20.23	20.24	20.37
		12@13	20.35	20.30	20.03
		25@0	20.18	20.20	20.13
	16-QAM	1@0	20.19	20.29	20.68
		1@12	20.49	20.53	20.81
		1@24	20.08	20.20	20.62
		12@0	19.33	19.40	19.10
		12@7	19.41	19.34	19.41
		12@13	19.31	19.29	19.34
		25@0	19.33	19.27	19.28

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	1@0	21.20	21.27	21.47
		1@25	21.26	21.41	21.57
		1@49	21.03	21.13	21.34
		25@0	20.25	20.44	20.40
		25@12	20.27	20.38	20.06
		25@25	20.19	20.37	20.30
		50@0	20.18	20.30	20.26
	16-QAM	1@0	19.91	20.15	20.67
		1@25	20.15	20.53	20.71
		1@49	19.85	20.15	20.53
		25@0	19.23	19.47	19.31
		25@12	19.22	19.37	19.19
		25@25	19.36	19.28	19.38
		50@0	19.25	19.32	19.14
15M	QPSK	1@0	21.33	21.32	21.37
		1@37	21.45	21.33	21.53
		1@74	21.35	21.18	21.34
		36@0	20.20	20.47	20.38
		36@20	20.36	20.33	20.32
		36@39	20.14	20.33	20.16
		75@0	20.34	20.37	20.41
	16-QAM	1@0	20.06	20.21	20.56
		1@37	20.34	20.30	20.58
		1@74	20.24	20.11	20.43
		36@0	19.19	19.49	19.22
		36@20	19.29	19.33	19.31
		36@39	19.23	19.24	19.19
		75@0	19.34	19.30	19.36
20M	QPSK	1@0	20.95	21.38	20.99
		1@49	21.87	21.83	21.82
		1@99	20.89	21.53	20.90
		50@0	20.12	20.40	20.10
		50@24	20.33	20.37	20.22
		50@50	20.29	20.37	20.22
		100@0	20.23	20.23	20.37
	16-QAM	1@0	20.31	20.55	20.30
		1@49	20.52	20.95	20.57
		1@99	20.29	20.64	20.18
		50@0	19.14	19.19	19.26
		50@24	19.08	19.30	19.10
		50@50	19.19	19.28	19.24
		100@0	19.15	19.24	19.24

LTE Band 7:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	1@0	21.54	21.43	21.44
		1@12	21.81	21.80	21.82
		1@24	21.58	21.49	21.40
		12@0	20.72	20.82	20.66
		12@7	20.86	20.79	20.81
		12@13	20.71	20.63	20.73
		25@0	20.58	20.61	20.79
	16-QAM	1@0	21.05	20.51	20.62
		1@12	21.36	20.75	20.82
		1@24	21.09	20.52	20.50
		12@0	19.85	19.71	19.60
		12@7	19.77	19.76	19.66
		12@13	19.79	19.75	19.57
		25@0	19.67	19.62	19.59
10M	QPSK	1@0	21.57	21.90	21.39
		1@25	21.65	21.89	21.67
		1@49	21.54	21.83	21.42
		25@0	20.47	20.70	20.55
		25@12	20.72	20.79	20.60
		25@25	20.73	20.60	20.59
		50@0	20.71	20.53	20.59
	16-QAM	1@0	20.64	21.05	20.29
		1@25	20.74	21.25	20.38
		1@49	20.39	21.05	20.23
		25@0	19.80	19.81	19.69
		25@12	19.85	19.72	19.62
		25@25	19.86	19.70	19.86
		50@0	19.76	19.60	19.76
15M	QPSK	1@0	21.58	21.53	21.91
		1@37	21.75	21.67	21.91
		1@74	21.63	21.54	21.76
		36@0	20.59	20.83	20.57
		36@20	20.56	20.72	20.79
		36@39	20.59	20.74	20.60
		75@0	20.68	20.63	20.62
	16-QAM	1@0	20.59	20.48	20.92
		1@37	20.85	20.75	21.14
		1@74	20.48	20.33	20.91
		36@0	19.41	19.57	19.64
		36@20	19.66	19.64	19.61
		36@39	19.52	19.64	19.62
		75@0	19.66	19.62	19.66

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
20M	QPSK	1@0	22.11	22.36	22.25
		1@49	22.54	22.77	22.69
		1@99	22.16	22.39	22.43
		50@0	21.57	21.55	21.64
		50@24	21.46	21.56	21.54
		50@50	21.54	21.49	21.76
		100@0	21.49	21.57	21.70
	16-QAM	1@0	21.35	21.47	21.64
		1@49	21.87	21.91	21.83
		1@99	21.45	21.62	21.69
		50@0	20.54	20.47	20.59
		50@24	20.66	20.56	20.59
		50@50	20.54	20.56	20.56
		100@0	20.63	20.56	20.58

WLAN 2.4G:

Mode	Channel frequency (MHz)	Data Rate	Duty cycle (%)	RF Output Power (dBm)
802.11b	2412	1Mbps	100	10.41
	2437			10.87
	2462			10.27
802.11g	2412	6Mbps	/	12.51
	2437			12.69
	2462			12.22
802.11n ht20	2412	MCS0	/	11.26
	2437			11.63
	2462			11.22
802.11n ht40	2422	MCS0	/	8.74
	2437			8.60
	2452			8.45

Note: The duty cycle plots, please refer to the SAR report: 2502Q44141E-20, which was issued by Bay Area Compliance Laboratories Corp. (Dongguan).

WLAN 5.2G:

Mode	Channel frequency (MHz)	Data Rate	Duty cycle (%)	RF Output Power (dBm)
802.11a	5180	6Mbps	/	11.62
	5200			11.67
	5240			12.07
802.11n20	5180	MCS0	/	11.28
	5200			11.43
	5240			12.05
802.11n40	5190	MCS0	/	11.41
	5230			11.94
802.11ac80	5210	MCS0	88.1	12.72

Note:

1. The duty cycle plots, please refer to the SAR report: 2502Q44141E-20, which was issued by Bay Area Compliance Laboratories Corp. (Dongguan).

2. The system support 802.11a/n20/n40/ac20/ac40/ac80, the 802.11ac20/802.11ac40 were reduced since the identical parameters with 802.11n20 and 802.11n40.

WLAN 5.3G:

Mode	Channel frequency (MHz)	Data Rate	Duty cycle (%)	RF Output Power (dBm)
802.11a	5260	6Mbps	96	12.13
	5280			12.28
	5320			12.23
802.11n20	5260	MCS0	/	12.08
	5280			12.32
	5320			12.34
802.11n40	5270	MCS0	/	12.05
	5310			12.27
802.11ac80	5290	MCS0	/	12.05

Note:

1. The duty cycle plots, please refer to the SAR report: 2502Q44141E-20, which was issued by Bay Area Compliance Laboratories Corp. (Dongguan).

2. The system support 802.11a/n20/n40/ac20/ac40/ac80, the 802.11ac20/802.11ac40 were reduced since the identical parameters with 802.11n20 and 802.11n40.

WLAN 5.6G:

Mode	Channel frequency (MHz)	Data Rate	Duty cycle (%)	RF Output Power (dBm)
802.11a	5500	6Mbps	/	12.08
	5580			11.94
	5700			11.77
	5720			12.05
802.11n20	5500	MCS0	/	11.95
	5580			11.62
	5700			11.36
	5720			11.72
802.11n40	5510	MCS0	/	11.81
	5590			11.63
	5670			11.33
	5710			11.37
802.11ac80	5530	MCS0	88.1	12.62
	5610			12.34
	5690			11.97

Note:

1. The duty cycle plots, please refer to the SAR report: 2502Q44141E-20, which was issued by Bay Area Compliance Laboratories Corp. (Dongguan).

2. The system support 802.11a/n20/n40/ac20/ac40/ac80, the 802.11ac20/802.11ac40 were reduced since the identical parameters with 802.11n20 and 802.11n40.

WLAN 5.8G:

Mode	Channel frequency (MHz)	Data Rate	Duty cycle (%)	RF Output Power (dBm)
802.11a	5745	6Mbps	96	12.28
	5785			12.11
	5825			11.91
802.11n20	5745	MCS0	/	12.11
	5785			12.04
	5825			11.74
802.11n40	5755	MCS0	/	12.09
	5795			11.87
802.11ac80	5775	MCS0	/	12.02

Note:

1. The duty cycle plots, please refer to the SAR report: 2502Q44141E-20, which was issued by Bay Area Compliance Laboratories Corp. (Dongguan).


2. The system support 802.11a/n20/n40/ac20/ac40/ac80, the 802.11ac20/802.11ac40 were reduced since the identical parameters with 802.11n20 and 802.11n40.

Bluetooth:

Mode	Channel frequency (MHz)	RF Output Power (dBm)
BDR(GFSK)	2402	2.16
	2441	2.31
	2480	2.71
EDR($\pi/4$ -DQPSK)	2402	1.38
	2441	1.59
	2480	1.85
EDR(8DPSK)	2402	1.45
	2441	1.73
	2480	1.87
BLE 1Mbps	2402	-0.18
	2440	0.04
	2480	0.17

8. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS

8.1 Antennas Location:



8.2 Antenna Distance To Edge

Antenna Distance To Edge(mm)						
Antenna	Back	Front	Left	Right	Top	Bottom
WWAN Antenna(GSM/WCDMA/LTE)	< 5	< 5	62	< 5	15	141
WLAN/BT Antenna	< 5	< 5	9	47	11	139

8.3 Standalone SAR test exclusion considerations

Body

Mode	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Distance (mm)	Calculated value	Threshold (1-g)	SAR Test Exclusion
WLAN 2.4G	2462	13	19.95	5	6.3	3.0	NO
WLAN 5.2G	5240	13	19.95	5	9.1	3.0	NO
WLAN 5.3G	5320	12.5	17.78	5	8.2	3.0	NO
WLAN 5.6G	5720	13	19.95	5	9.5	3.0	NO
WLAN 5.8G	5825	12.5	17.78	5	8.6	3.0	NO
Bluetooth	2480	3	2.00	5	0.6	3.0	YES

Limb

Mode	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Distance (mm)	Calculated value	Threshold (10-g)	SAR Test Exclusion
WLAN 2.4G	2462	13	19.95	0	6.3	7.5	YES
WLAN 5.2G	5240	13	19.95	0	9.1	7.5	NO
WLAN 5.3G	5320	12.5	17.78	0	8.2	7.5	NO
WLAN 5.6G	5720	13	19.95	0	9.5	7.5	NO
WLAN 5.8G	5825	12.5	17.78	0	8.6	7.5	NO
Bluetooth	2480	3	2.00	0	0.6	7.5	YES

Note:

1. The WLAN based average power for calculation. and bluetooth based peak output power for calculation.
2. The Limb SAR of WLAN 2.4G was selected to test

NOTE:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

According to KDB447498 D01 General RF Exposure Guidance v06: 4.3. General SAR test exclusion guidance

c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):

- 1) For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by $[1 + \log(100/f(\text{MHz}))]$
- 2) For test separation distances ≤ 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$
- 3) SAR measurement procedures are not established below 100 MHz

Measurement Result:

For NFC, the power of EUT: E Field@3m is 73.07dBuV/m = -22.13 dBm (0.006mW)

Note: $E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] + 95.2$ for $d = 3$ m.

SAR test exclusion threshold for NFC(13.56MHz) separation distance < 50 mm

$$= [474 * (1 + \log(100/f(\text{MHz}))) / 2]$$

$$= 443\text{mW}$$

$$> 0.006\text{mW}$$

Conclusion:

The NFC SAR evaluation can be exempted.

Note:

1. The E Field value of NFC, please refer to the report: 2502Q44141E-RF-00G, which was issued by Bay Area Compliance Laboratories Corp. (Dongguan).

8.4 Standalone SAR Estimation:**Body**

Mode	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Distance (mm)	Estimated 1-g (W/kg)
BT	2480	3	2.00	5	0.08@1-g

Limb

Mode	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Distance (mm)	Estimated 10-g (W/kg)
BT	2480	3	2.00	0	0.03@10-g

Note: The bluetooth based peak power for calculation.

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})/x}]$$

W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR, $x = 18.75$ for 10-g SAR

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

8.5 SAR test exclusion for the EUT edge considerations Result

Mode	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Test Exclusion Distance (mm)
LTE Band 2	1900	22	158.49	29.1
LTE Band 7	2560	23	199.53	42.5
WLAN 2.4G	2462	13	19.95	4.1
WLAN 5.2G	5240	13	19.95	6.0
WLAN 5.3G	5320	12.5	17.78	5.4
WLAN 5.6G	5720	13	19.95	6.3
WLAN 5.8G	5825	12.5	17.78	5.7

Mode	Front Edge	Back Edge	Left Edge	Right Edge	Top Edge	Bottom Edge
WWAN(GSM/WCDMA/LTE)	Required	Required	Exclusion	Required	Required	Exclusion
WLAN 2.4G/5G	Required	Required	Required	Exclusion	Required	Exclusion
Bluetooth	Exclusion*	Exclusion*	Exclusion*	Exclusion*	Exclusion*	Exclusion*

Note:

Required: The distance is less than **Test Exclusion Distance**, the SAR test is required.

Exclusion: The distance is large than **Test Exclusion Distance**, SAR test is not required.

Exclusion*: SAR test exclusion evaluation has been done above.

SAR test exclusion for the EUT edge considerations detail:**Distance < 50mm(To Edges)**

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.
5. The Time based average Power is used for calculation

Distance > 50mm (To Edges)

At 100 MHz to 6 GHz and for *test separation distances* > 50 mm, the SAR test exclusion threshold is determined according to the following:

- a) $[\text{Power allowed at numeric threshold for } 50 \text{ mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]$ mW, at 100 MHz to 1500 MHz
- b) $[\text{Power allowed at numeric threshold for } 50 \text{ mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot 10]$ mW at > 1500 MHz and ≤ 6 GHz.

9. SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation.

9.1 SAR Test Data

Environmental Temperature:	21.8-22.3℃	21.6-22.2℃
Relative Humidity:	42%	44%
ATM Pressure:	101.4kPa	101.8kPa
Test Date:	2026/09/19	2026/09/20

Testing was performed by Mikasa Mo and Code Luo.

WLAN 2.4G:**Body Mode:**

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Body Back (5mm)	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	10.87	11	1.03	1	0.155	0.16	1#
	2462	802.11b	/	/	/	/	/	/	/

Limb Mode:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	10g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Limb Front (0mm)	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	10.87	11	1.03	1	0.019	0.02	
	2462	802.11b	/	/	/	/	/	/	/
Limb Back (0mm)	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	10.87	11	1.03	1	0.454	0.47	2#
	2462	802.11b	/	/	/	/	/	/	/
Limb Left (0mm)	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	10.87	11	1.03	1	0.096	0.10	/
	2462	802.11b	/	/	/	/	/	/	/
Limb Top (0mm)	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	10.87	11	1.03	1	0.028	0.03	/
	2462	802.11b	/	/	/	/	/	/	/

Note:

1. When the SAR value is less than half of the limit, testing for other channels are optional.
2. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
3. According to KDB 248227 D01, for SAR testing of WLAN with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)".

2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements**Body Mode:**

Mode	Target Output Power (dBm)	Target Output Power (mW)	Reported SAR(W/kg)	Adjusted SAR(W/kg)	Limit(W/kg)	SAR Test Exclusion
802.11b(DSSS)	11	12.59	0.16	/	/	/
802.11g(OFDM)	13	19.95	/	0.26	1.2	Yes
802.11n ht20(OFDM)	12	15.85	/	0.21	1.2	Yes
802.11n ht40(OFDM)	9	7.94	/	0.11	1.2	Yes

Limb Mode:

Mode	Target Output Power (dBm)	Target Output Power (mW)	Reported SAR(W/kg)	Adjusted SAR(W/kg)	Limit(W/kg)	SAR Test Exclusion
802.11b(DSSS)	11	12.59	0.47	/	/	/
802.11g(OFDM)	13	19.95	/	0.75	1.2	Yes
802.11n ht20(OFDM)	12	15.85	/	0.60	1.2	Yes
802.11n ht40(OFDM)	9	7.94	/	0.30	1.2	Yes

Per KDB 248227 D01, When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (see 5.3, including subclauses). SAR is not required for the following 2.4 GHz OFDM conditions.

- When KDB Publication 447498 D01 SAR test exclusion applies to the OFDM configuration.
- When the highest *reported* SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

WLAN 5.2G:**Body Mode:**

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Body Back (5mm)	5210	802.11ac80	12.72	13	1.067	1.14	0.531	0.65	3#

Limb Mode:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	10g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Limb Front (0mm)	5210	802.11ac80	12.72	13	1.067	1.14	0.00827	0.01	/
Limb Back (0mm)	5210	802.11ac80	12.72	13	1.067	1.14	0.435	0.53	4#
Limb Left (0mm)	5210	802.11ac80	12.72	13	1.067	1.14	0.111	0.14	/
Limb Top (0mm)	5210	802.11ac80	12.72	13	1.067	1.14	0.021	0.03	/

Note:

1. When the SAR value is less than half of the limit, testing for other channels are optional.
2. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
3. For 802.11ac80 mode power is the largest among 802.11a/n/ac, 802.11ac80 mode as initial test configuration is selected to test.
4. According to KDB 248227 D01, for SAR testing of WLAN with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)".

WLAN 5.3G:**Body Mode:**

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Body Back (5mm)	5260	802.11a	/	/	/	/	/	/	/
	5280	802.11a	12.28	12.5	1.052	1.04	0.471	0.52	5#
	5320	802.11a	/	/	/	/	/	/	/

Limb Mode:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	10g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Limb Front (0mm)	5260	802.11a	/	/	/	/	/	/	/
	5280	802.11a	12.28	12.5	1.052	1.04	0.012	0.01	/
	5320	802.11a	/	/	/	/	/	/	/
Limb Back (0mm)	5260	802.11a	/	/	/	/	/	/	/
	5280	802.11a	12.28	12.5	1.052	1.04	0.492	0.54	6#
	5320	802.11a	/	/	/	/	/	/	/
Limb Left (0mm)	5260	802.11a	/	/	/	/	/	/	/
	5280	802.11a	12.28	12.5	1.052	1.04	0.080	0.09	/
	5320	802.11a	/	/	/	/	/	/	/
Limb Top (0mm)	5260	802.11a	/	/	/	/	/	/	/
	5280	802.11a	12.28	12.5	1.052	1.04	0.050	0.06	/
	5320	802.11a	/	/	/	/	/	/	/

Note:

1. When the SAR value is less than half of the limit, testing for other channels are optional.
2. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
3. For 802.11a mode power is the largest among 802.11a/n/ac, 802.11a mode as initial test configuration is selected to test.
4. According to KDB 248227 D01, for SAR testing of WLAN with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)".

WLAN 5.6G:**Body Mode:**

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Body Back (5mm)	5530	802.11ac80	/	/	/	/	/	/	/
	5610	802.11ac80	12.34	13	1.164	1.14	0.295	0.39	7#
	5690	802.11ac80	/	/	/	/	/	/	/

Limb Mode:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	10g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Limb Front (0mm)	5530	802.11ac80	/	/	/	/	/	/	/
	5610	802.11ac80	12.34	13	1.164	1.14	0.015	0.02	/
	5690	802.11ac80	/	/	/	/	/	/	/
Limb Back (0mm)	5530	802.11ac80	/	/	/	/	/	/	/
	5610	802.11ac80	12.34	13	1.164	1.14	0.430	0.57	8#
	5690	802.11ac80	/	/	/	/	/	/	/
Limb Left (0mm)	5530	802.11ac80	/	/	/	/	/	/	/
	5610	802.11ac80	12.34	13	1.164	1.14	0.031	0.04	/
	5690	802.11ac80	/	/	/	/	/	/	/
Limb Top (0mm)	5530	802.11ac80	/	/	/	/	/	/	/
	5610	802.11ac80	12.34	13	1.164	1.14	0.035	0.05	/
	5690	802.11ac80	/	/	/	/	/	/	/

Note:

1. When the SAR value is less than half of the limit, testing for other channels are optional.
2. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
3. For 802.11 ac80 mode power is the largest among 802.11a/n/ac, 802.11 ac80 mode as initial test configuration is selected to test.
4. According to KDB 248227 D01, for SAR testing of WLAN with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)".

WLAN 5.8G:**Body Mode:**

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Body Back (5mm)	5745	802.11a	/	/	/	/	/	/	/
	5785	802.11a	12.11	12.5	1.094	1.04	0.165	0.19	9#
	5825	802.11a	/	/	/	/	/	/	/

Limb Mode:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	10g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Limb Front (0mm)	5745	802.11a	/	/	/	/	/	/	/
	5785	802.11a	12.11	12.5	1.094	1.04	0.012	0.01	/
	5825	802.11a	/	/	/	/	/	/	/
Limb Back (0mm)	5745	802.11a	/	/	/	/	/	/	/
	5785	802.11a	12.11	12.5	1.094	1.04	0.314	0.36	10#
	5825	802.11a	/	/	/	/	/	/	/
Limb Left (0mm)	5745	802.11a	/	/	/	/	/	/	/
	5785	802.11a	12.11	12.5	1.094	1.04	0.021	0.02	/
	5825	802.11a	/	/	/	/	/	/	/
Limb Top (0mm)	5745	802.11a	/	/	/	/	/	/	/
	5785	802.11a	12.11	12.5	1.094	1.04	0.029	0.03	/
	5825	802.11a	/	/	/	/	/	/	/

Note:

1. When the SAR value is less than half of the limit, testing for other channels are optional.
2. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
3. For 802.11a mode power is the largest among 802.11a/n/ac, 802.11a mode as initial test configuration is selected to test.
4. According to KDB 248227 D01, for SAR testing of WLAN with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)".

Spot Check for WWAN:**LTE Band 2:****Limb Mode:**

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	10g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Limb Right (0mm)	1860	20	1RB	21.87	22	1.03	1.67	1.72	/
	1880	20	1RB	21.83	22	1.04	1.92	2.00	/
	1900	20	1RB	21.82	22	1.042	2.01	2.09	11#
	1880	20	50%RB	20.40	21	1.148	1.66	1.91	/
	1900	20	100%RB	20.37	21	1.156	1.67	1.93	/

LTE Band 7:**Body Mode:**

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (5mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	22.77	23	1.054	0.202	0.21	12#
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	21.56	22	1.107	0.168	0.19	/

Note:

1. LTE Band 7 is the worst band of body mode, and LTE Band 2 is the worst band of limb mode

10. MEASUREMENT VARIABILITY

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz v01. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Note: The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

The Highest Measured SAR Configuration in Each Frequency Band

Body

SAR probe calibration point	Frequency Band	Freq.(MHz)	EUT Position	1g Meas. SAR (W/kg)		Largest to Smallest SAR Ratio
				Original	Repeated	
/	/	/	/	/	/	/

Limb

SAR probe calibration point	Frequency Band	Freq.(MHz)	EUT Position	10g Meas. SAR (W/kg)		Largest to Smallest SAR Ratio
				Original	Repeated	
1900MHz	LTE Band 2	1900	Limb Right	2.01	1.97	1.02

Note:

1. The measured SAR results **do not** have to be scaled to the maximum tune-up tolerance to determine if repeated measurements are required.
2. SAR measurement variability must be assessed for each frequency band, which is determined by the **SAR probe calibration point and tissue-equivalent medium** used for the device measurements.

11. DUT HOLDER PERTURBATIONS

In accordance with TCB workshop October 2016:

- 1) SAR perturbation due to test device holders, depending on antenna locations, buttons locations on phones or device, form factor (e.g. dongles etc.), the measured SAR could be influenced by the relative positions of the test device and its holder
- 2) SAR measurement standards have included protocols to evaluate this with a flat phantom, with and without the device holder
- 3) When the highest reported SAR of an antenna is > 1.2 W/kg, holder perturbation verification is required for each antenna, using the highest SAR configuration among all applicable frequency bands in the same exact device and holder positions used for head and body SAR measurements; i.e. same device/button locations in the holder

Per IEEE 1528: 2013/Annex E/E.4.1.1: Device holder perturbation tolerance for a specific test device: Type B

When it is unknown if a device holder perturbs the fields of a test device, the SAR uncertainty shall be assessed with a flat phantom (see Clause 5) by comparing the SAR with and without the device holder according to the following tests:

The SAR tolerance for device holder disturbance is computed using Equation (E.21) and entered in the corresponding row of the appropriate uncertainty table with an assumed rectangular probability distribution and $\nu_i = \infty$ degrees of freedom:

$$SAR_{\text{tolerance}}[\%] = 100 \times \left(\frac{SAR_{\text{w/ holder}} - SAR_{\text{w/o holder}}}{SAR_{\text{w/o holder}}} \right) \quad (\text{E.21})$$

The Highest Measured SAR Configuration among all applicable Frequency Band

Frequency Band	Freq.(MHz)	EUT Position	10g Meas. SAR (W/kg)		The Device holder perturbation uncertainty
			With holder	Without holder	
LTE Band 2	1900	Limb Right	2.01	1.98	1.52%

12. SAR SIMULTANEOUS TRANSMISSION DESCRIPTION

12.1 Simultaneous Transmission:

Description of Simultaneous Transmit Capabilities		
Transmitter Combination	Simultaneous?	Hotspot?
WWAN(GSM/WCDMA/LTE) + WLAN 2.4G + NFC	√	×
WWAN(GSM/WCDMA/LTE) + WLAN 5G + NFC	√	×
WWAN(GSM/WCDMA/LTE) + Bluetooth+ NFC	√	×
WLAN 2.4G+ Bluetooth+ NFC	×	×
WLAN 5G + Bluetooth+ NFC	×	×
WLAN 2.4G + WLAN 5G+ NFC	×	×

Note:

1.For the EIRP of NFC is 0.006mW, per KDB447498 D01 clause 4.3, the estimated SAR is so lower, so the NFC almost have no influence on the results of simultaneous transmission.

12.2 Simultaneous SAR test exclusion considerations:

Body SAR:

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		ΣSAR < 1.6W/kg
		SAR1	SAR2	
WWAN(GSM/WCDMA/LTE) + WLAN 2.4G	Body	0.43	0.16	0.59
WWAN(GSM/WCDMA/LTE) + WLAN 5G	Body	0.43	0.65	1.08
WWAN(GSM/WCDMA/LTE) + Bluetooth	Body	0.43	0.08	0.51

Conclusion:

Sum of SAR:ΣSAR ≤1.6 W/kg, therefore simultaneous transmission SAR with Volume Scans is **not required**.

Limb SAR:

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		ΣSAR < 4.0W/kg
		SAR1	SAR2	
WWAN(GSM/WCDMA/LTE) + WLAN 2.4G	Limb	2.09	0.47	2.56
WWAN(GSM/WCDMA/LTE) + WLAN 5G	Limb	2.09	0.57	2.66
WWAN(GSM/WCDMA/LTE) + Bluetooth	Limb	2.09	0.03	2.12

Conclusion:

Sum of SAR:ΣSAR ≤4.0 W/kg, therefore simultaneous transmission SAR with Volume Scans is **not required**.

APPENDIX A - MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.

Measurement uncertainty evaluation for IEEE1528-2013 SAR test

Uncertainty component	Tolerance/uncertainty ± %	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty ± %, (1 g)	Standard uncertainty ± %, (10 g)
Measurement system							
Probe calibration(k=1)	6.55	N	1	1	1	6.6	6.6
Axial isotropy	4.5	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	1.8	1.8
Hemispherical isotropy	9.1	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	3.7	3.7
Boundary effect	2.0	R	$\sqrt{3}$	1	1	1.2	1.2
Linearity	4.4	R	$\sqrt{3}$	1	1	2.5	2.5
System detection limits	0.98	R	$\sqrt{3}$	1	1	0.6	0.6
Modulation response	4.6	R	$\sqrt{3}$	1	1	2.7	2.7
Readout electronics	0.5	N	1	1	1	0.5	0.5
Response time	0.6	R	$\sqrt{3}$	1	1	0.3	0.3
Integration time	2.6	R	$\sqrt{3}$	1	1	1.5	1.5
RF ambient conditions-noise	1.3	R	$\sqrt{3}$	1	1	0.8	0.8
RF ambient conditions-reflections	2.6	R	$\sqrt{3}$	1	1	1.5	1.5
Probe positioner mech.tolerance	0.8	R	$\sqrt{3}$	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	$\sqrt{3}$	1	1	3.9	3.9
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	4.0	R	$\sqrt{3}$	1	1	2.3	2.3
Test sample related							
Test sample positioning	3.3	N	1	1	1	3.3	3.3
Device holder uncertainty	1.5	N	1	1	1	1.5	1.5
Output power variation –SAR draft measurement	5.0	R	$\sqrt{3}$	1	1	2.9	2.9
SAR scaling	2.8	R	$\sqrt{3}$	1	1	1.6	1.6
Phantom and tissue parameters							
Phantom shell uncertainty–shape, thickness and permittivity	7.6	R	$\sqrt{3}$	1	1	4.4	4.4
Uncertainty in SAR correction for deviations in permittivity and conductivity	4.8	N	1	1	0.84	4.8	4.0
Liquid conductivity meas.	2.5	N	1	0.78	0.71	2.0	1.8
Liquid permittivity meas.	2.5	N	1	0.23	0.26	0.6	0.7
Liquid conductivity – temperature uncertainty	3.65	R	$\sqrt{3}$	0.78	0.71	1.6	1.5
Liquid permittivity – temperature uncertainty	0.99	R	$\sqrt{3}$	0.23	0.26	0.1	0.1
Combined standard uncertainty		RSS				13.2	12.9
Expanded uncertainty (95 % confidence interval)		k=2				26.4	25.8

APPENDIX B - SAR PLOTS

Please refer to the attachment.

APPENDIX C - EUT TEST POSITION PHOTOS

Please refer to the attachment.

APPENDIX D - PROBE CALIBRATION CERTIFICATES

Please refer to the attachment.

APPENDIX E - DIPOLE CALIBRATION CERTIFICATES

Please refer to the attachment.

APPENDIX F - RETURN LOSS AND IMPEDANCE MEASUREMENT

Please refer to the attachment.

*******END OF REPORT*******