

Label details (physical)

The product label consists of a tear-resistant matt chrome metallic finished polyester film which is dimensionally stable with good chemical resistance and tolerance to temperature range. The information on the label is printed via compatible thermal transfer ribbon using a Zebra ZT410. The adhesive used is S8015, which is suitable for difficult substrates including low surface energy plastics and coatings.

The UL file number for the base label is MH27538.

Label details (printed information)

MAGiCARD[®] 美吉卡有限公司 Magicard Ltd. Weymouth, Dorset DT4 9XD, UK Serial No. / No. de Serie / 编号 73461625 4500-0024K/2 MAGICARD K MAG DUO SMART PRINTER COLOUR CARD PRINTER (彩色卡片打印机) INPUT (输入) 24V $\overline{\text{---}}$ 3.75A This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: 1. This device may not cause harmful Interference, and 2. This device must accept any Interference received, including interference that may cause undesired operation. INFORMATION TECHNOLOGY EQUIPMENT MANUFACTURED IN THE UK (英国制造) US patent No 5,990,918 European Patent Spec EP 0 817 726 b1 International patent PCT/GB2004/003889 FCC ID: XDW4500-0001 Contains FCC ID: WP5TWN4F3 仅适用于非热带气候条件下安全使用	CE RoHS ✓   Pb-Free   LISTED E171341 I.T.E. 
--	--

Label details (location on product)

The label is applied to the underside of the product enclosure in a slightly recessed location designed to accommodate it.

