

Appendix 5

RF Exposure Information

FCC ID: XEK-MHANDH3

Maximum transmitter power:

Frequency (MHz)	Maximum peak output power (dBm)	Output power(mW)
2402	5.58	3.61
2441	6.72	4.69
2480	7.43	5.53

According to KDB 447498 D01:

Standalone SAR test exclusion considerations:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$$

for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

Result:

$$(3.61/5) \cdot \sqrt{2.402} = 1.119 < 3.0$$

$$(4.69/5) \cdot \sqrt{2.441} = 1.466 < 3.0$$

$$(5.53/5) \cdot \sqrt{2.480} = 1.742 < 3.0$$

Conclusion:

It is qualified for standalone SAR test exclusion. Please refer to test report# FA6O1207 issued by SPORTON INTERNATINAL INC. for Simultaneous transmission SAR consideration (If any).