




FCC PART 15.247 TEST REPORT

For

Logic Instrument SA

43, Avenue de l'Europe P.O. Box BP 60012, DOMONT, 95330 ,France

FCC ID: XGIFBF1

Report Type: Original Report	Product Name: Mobile Phone
Test Engineer: <u>Lorin Bian</u> 	
Report Number: <u>RBJ160829050C</u>	
Report Date: <u>2016-11-01</u>	
Reviewed By: <u>Henry Ding</u>  EMC Leader	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Chengdu) 5040, HuiLongWan Plaza, No. 1, ShaWan Road, JinNiu District, ChengDu, China Tel: 028-65523123, Fax: 028-65525125 www.baclcorp.com	

Note: This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu). Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This report was valid only with a valid digital signature.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT CABLE LIST AND DETAILS.....	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE.....	8
APPLICABLE STANDARD.....	8
FCC §15.203 - ANTENNA REQUIREMENT	9
APPLICABLE STANDARD.....	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS.....	10
APPLICABLE STANDARD.....	10
MEASUREMENT UNCERTAINTY	10
EUT SETUP.....	10
EMI TEST RECEIVER SETUP	11
TEST PROCEDURE	11
CORRECTED AMPLITUDE & MARGIN CALCULATION	11
TEST EQUIPMENT LIST AND DETAILS	12
TEST RESULTS SUMMARY	12
TEST DATA	12
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	15
APPLICABLE STANDARD.....	15
MEASUREMENT UNCERTAINTY	15
EUT SETUP.....	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST PROCEDURE	17
TEST EQUIPMENT LIST AND DETAILS	18
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST RESULTS SUMMARY	18
TEST DATA	18
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	25
APPLICABLE STANDARD.....	25
TEST EQUIPMENT LIST AND DETAILS	25
TEST PROCEDURE	25
TEST DATA	25
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING	31
APPLICABLE STANDARD.....	31

TEST PROCEDURE	31
TEST EQUIPMENT LIST AND DETAILS	31
TEST DATA	31
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST EQUIPMENT LIST AND DETAILS	37
TEST DATA	37
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST EQUIPMENT LIST AND DETAILS	41
TEST DATA	41
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	57
APPLICABLE STANDARD	57
TEST PROCEDURE	57
TEST EQUIPMENT LIST AND DETAILS	57
TEST DATA	57
FCC §15.247(d) - BAND EDGES TESTING	63
APPLICABLE STANDARD	63
TEST PROCEDURE	63
TEST EQUIPMENT LIST AND DETAILS	63
TEST DATA	63

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The **Logic Instrument SA**'s product, model number: **Fieldbook F1 (FCC ID: XGIFBF1)** (the "EUT") in this report was a **Mobile Phone**, which was measured approximately: 17.7 cm (L) x 8.9 cm (W) x 1.1cm (H), rated input voltage: DC 3.7V from rechargeable Li-ion battery or DC 5V from adapter.

Adapter information:

MODEL: HKA01105021-XE

INPUT: 100-240V ~ 50/60Hz 0.5A

OUTPUT: DC 5.0V, 2.1A

**All measurement and test data in this report was gathered from final production sample, serial number: 160829050 (assigned by the BACL, Chengdu). It may have deviation from any other sample. The EUT supplied by the applicant was received on 2016-08-28, and EUT conformed to test requirement.*

Objective

This report is prepared on behalf of **Logic Instrument SA** in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: XGIFBF1.

FCC Part 22H, 24E, 27 PCE submissions with FCC ID: XGIFBF1.

FCC Part 15C DTS submissions with FCC ID: XGIFBF1.

FCC Part 15E NII submissions with FCC ID: XGIFBF1.

FCC Part 15.225 DXX submissions with FCC ID: XGIFBF1.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Chengdu). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

The uncertainty of any RF tests which use conducted method measurement is ± 3.17 dB, the uncertainty of any radiation on emissions measurement is:

30M~200MHz: ± 4.7 dB;

200M~1GHz: ± 6.0 dB;

1G~6GHz: ± 5.13 dB;

6G~25GHz: ± 5.47 dB;

And the uncertainty will not be taken into consideration for all test data recorded in the report.

Test Facility

The test site used by BACL to collect test data is located in the 5040, HuiLongWan Plaza, No. 1, ShaWan Road, JinNiu District, ChengDu, China

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on April 24, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 560332. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

No software was made to the EUT tested.


Equipment Modifications

No modification was made to the EUT.

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Adapter cable	Yes	No	1.2	Adapter	EUT
Earphone Cable	No	No	1.6	EUT	Earphone

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v05r02:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The maximum output power including tolerance is -1.5 dBm (0.71mW)

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 0.71/5 \cdot (\sqrt{2.480}) = 0.2 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement for WLAN/ BT, and the max antenna gain is -3.4 dBi, fulfill the requirement of this section, please refer to the EUT photos.

Result: Compliance

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisprr} of Table 1, then:

–compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
 –non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisprr} of Table 1, then:


–compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisprr})$, exceeds the disturbance limit;
 –non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisprr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2:2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Chengdu) is ± 3.17 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cisprr}

Measurement	U_{cisprr}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS 30	836858/0016	2015-12-02	2016-12-01
Rohde & Schwarz	L.I.S.N.	ENV216	3560.6550.06	2015-12-02	2016-12-01
N/A	Conducted Cable	NO.5	N/A	2015-11-10	2016-11-09

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data


Environmental Conditions

Temperature:	28.6 °C
Relative Humidity:	60 %
ATM Pressure:	101.1 kPa

The testing was performed by Lorin Bian on 2016-10-26.

Test Mode: Transmitting
AC 120V/60Hz:


Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.192030	45.0	9.000	L1	9.7	19.0	64.0	Compliance
0.387164	37.6	9.000	L1	9.7	20.5	58.1	Compliance
0.581275	40.1	9.000	L1	9.7	15.9	56.0	Compliance
0.726569	37.2	9.000	L1	9.7	18.8	56.0	Compliance
0.805868	36.5	9.000	L1	9.7	19.5	56.0	Compliance
1.951564	32.8	9.000	L1	9.7	23.2	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.190505	37.8	9.000	L1	9.7	16.2	54.0	Compliance
0.384091	33.0	9.000	L1	9.7	15.2	48.2	Compliance
0.567545	34.7	9.000	L1	9.7	11.3	46.0	Compliance
0.715082	31.6	9.000	L1	9.7	14.4	46.0	Compliance
0.805868	30.4	9.000	L1	9.7	15.6	46.0	Compliance
1.249088	29.9	9.000	L1	9.7	16.1	46.0	Compliance

Neutral:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.563041	32.9	9.000	N	9.6	23.1	56.0	Compliance
0.703777	29.6	9.000	N	9.6	26.4	56.0	Compliance
3.098088	28.5	9.000	N	9.7	27.5	56.0	Compliance
9.759114	32.7	9.000	N	9.8	27.3	60.0	Compliance
15.867293	35.9	9.000	N	10.0	24.1	60.0	Compliance
16.251162	36.1	9.000	N	10.0	23.9	60.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.192030	33.4	9.000	N	9.6	20.5	53.9	Compliance
0.581275	27.3	9.000	N	9.6	18.7	46.0	Compliance
0.715082	23.9	9.000	N	9.6	22.1	46.0	Compliance
8.321464	27.4	9.000	N	9.8	22.6	50.0	Compliance
15.867293	32.9	9.000	N	10.0	17.1	50.0	Compliance
16.251162	33.2	9.000	N	10.0	16.8	50.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

–compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
–non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:

–compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
–non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Chengdu) is:

30M~200MHz: ± 4.7 dB ;

200M~1GHz: ± 6.0 dB ;

1G-6GHz: ± 5.13 dB;


6G~25GHz: ± 5.47 dB;

Table 1 – Values of U_{cisp}


Measurement	U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Av

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Amplifier	8447D	2944A10442	2015-12-02	2016-12-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2015-12-02	2016-12-01
Sunol Sciences	Broadband Antenna	JB3	A101808	2016-04-10	2019-04-09
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2015-12-02	2016-12-01
EM TEST	Horn Antenna	3115	003-6076	2015-12-02	2016-12-01
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-0113024	2014-06-16	2017-06-15
Mini-circuits	Amplifier	ZVA-213-S+	771001215	2016-05-20	2017-05-19
HP	Amplifier	8449B	3008A00277	2015-12-02	2016-12-01
EMCT	Semi-Anechoic Chamber	966	N/A	2015-04-24	2018-04-23
N/A	RF Cable (below 1GHz)	NO.1	N/A	2015-11-10	2016-11-09
N/A	RF Cable (below 1GHz)	NO.4	N/A	2015-11-10	2016-11-09
N/A	RF Cable (above 1GHz)	NO.2	N/A	2015-11-10	2016-11-09

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, and section 15.205, 15.209 and 15.247.

Test Data


Environmental Conditions

Temperature:	28.6 °C
Relative Humidity:	60 %
ATM Pressure:	101.1 kPa

Test Mode: Transmitting


30MHz-1GHz(the BDR middle channel was the worst)

Horizontal



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
34.8500	32.83	QP	-2.63	30.20	40.00	9.80
131.8500	26.64	QP	-5.84	20.80	43.50	22.70
189.0800	29.60	QP	-8.30	21.30	43.50	22.20
208.4800	30.13	QP	-8.93	21.20	43.50	22.30
250.1900	29.47	QP	-7.67	21.80	46.00	24.20
532.4600	29.02	QP	-1.42	27.60	46.00	18.40

Vertical



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
30.0000	24.55	QP	0.95	25.50	40.00	14.50
191.9900	32.64	QP	-8.14	24.50	43.50	19.00
353.0100	29.22	QP	-4.62	24.60	46.00	21.40
434.4900	28.72	QP	-2.92	25.80	46.00	20.20
462.6200	28.25	QP	-1.95	26.30	46.00	19.70
531.4900	36.82	QP	-1.42	35.40	46.00	10.60

1-25GHz:

BDR Mode (GFSK):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	64.59	PK	H	23.53	3.00	0.00	91.12	N/A	N/A
2402	52.69	AV	H	23.53	3.00	0.00	79.22	N/A	N/A
2402	58.97	PK	V	23.53	3.00	0.00	85.50	N/A	N/A
2402	47.69	AV	V	23.53	3.00	0.00	74.22	N/A	N/A
2390	33.95	PK	H	23.57	3.00	0.00	60.52	74.00	13.48
2390	20.14	AV	H	23.57	3.00	0.00	46.71	54.00	7.29
4804	34.59	PK	H	30.77	5.12	26.87	43.61	74.00	30.39
4804	22.18	AV	H	30.77	5.12	26.87	31.20	54.00	22.80
7206	34.25	PK	H	34.71	6.16	26.35	48.77	74.00	25.23
7206	22.17	AV	H	34.71	6.16	26.35	36.69	54.00	17.31
3131	34.29	PK	H	24.93	3.63	26.46	36.39	74.00	37.61
3131	23.64	AV	H	24.93	3.63	26.46	25.74	54.00	28.26
531.49	36.82	QP	V	18.41	1.69	28.83	28.09	46.00	17.91
Middle Channel: 2441 MHz									
2441	64.95	PK	H	23.40	3.00	0.00	91.35	N/A	N/A
2441	52.67	AV	H	23.40	3.00	0.00	79.07	N/A	N/A
2441	58.74	PK	V	23.40	3.00	0.00	85.14	N/A	N/A
2441	49.26	AV	V	23.40	3.00	0.00	75.66	N/A	N/A
4882	34.29	PK	H	31.02	5.09	26.87	43.53	74.00	30.47
4882	22.74	AV	H	31.02	5.09	26.87	31.98	54.00	22.02
7323	33.96	PK	H	34.95	6.22	26.40	48.73	74.00	25.27
7323	22.84	AV	H	34.95	6.22	26.40	37.61	54.00	16.39
3131	36.49	PK	H	24.93	3.63	26.46	38.59	74.00	35.41
3131	23.06	AV	H	24.93	3.63	26.46	25.16	54.00	28.84
3693	34.75	PK	H	27.77	4.47	26.57	40.42	74.00	33.58
3693	20.96	AV	H	27.77	4.47	26.57	26.63	54.00	27.37
531.49	36.74	QP	V	18.41	1.69	28.83	28.01	46.00	17.99
30	24.55	QP	V	22.70	0.31	28.57	18.99	40.00	21.01
High Channel: 2480 MHz									
2480	63.78	PK	H	23.27	2.99	0.00	90.04	N/A	N/A
2480	49.81	AV	H	23.27	2.99	0.00	76.07	N/A	N/A
2480	58.71	PK	V	23.27	2.99	0.00	84.97	N/A	N/A
2480	48.14	AV	V	23.27	2.99	0.00	74.40	N/A	N/A
2483.5	32.14	PK	H	23.26	2.99	0.00	58.39	74.00	15.61
2483.5	18.71	AV	H	23.26	2.99	0.00	44.96	54.00	9.04
4960	36.54	PK	H	31.27	5.05	26.88	45.98	74.00	28.02
4960	24.26	AV	H	31.27	5.05	26.88	33.70	54.00	20.30
7440	34.28	PK	H	35.18	6.27	26.45	49.28	74.00	24.72
7440	23.64	AV	H	35.18	6.27	26.45	38.64	54.00	15.36
3131	35.47	PK	H	24.93	3.63	26.46	37.57	74.00	36.43
3131	23.69	AV	H	24.93	3.63	26.46	25.79	54.00	28.21
531.49	37.48	QP	V	18.41	1.69	28.83	28.75	46.00	17.25

EDR Mode ($\pi/4$ -DQPSK):

Frequency	Receiver		Rx Antenna		Cable	Amplifier	Corrected	FCC 15.247	
(MHz)	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	62.18	PK	H	23.53	3.00	0.00	88.71	N/A	N/A
2402	50.12	AV	H	23.53	3.00	0.00	76.65	N/A	N/A
2402	57.14	PK	V	23.53	3.00	0.00	83.67	N/A	N/A
2402	45.26	AV	V	23.53	3.00	0.00	71.79	N/A	N/A
2390	36.57	PK	H	23.57	3.00	0.00	63.14	74.00	10.86
2390	24.52	AV	H	23.57	3.00	0.00	51.09	54.00	2.91
4804	35.64	PK	H	30.77	5.12	26.87	44.66	74.00	29.34
4804	23.69	AV	H	30.77	5.12	26.87	32.71	54.00	21.29
7206	34.71	PK	H	34.71	6.16	26.35	49.23	74.00	24.77
7206	23.67	AV	H	34.71	6.16	26.35	38.19	54.00	15.81
2950	35.29	PK	H	24.10	3.39	26.46	36.32	74.00	37.68
2950	23.67	AV	H	24.10	3.39	26.46	24.70	54.00	29.30
531.49	36.47	QP	V	18.41	1.69	28.83	27.74	46.00	18.26
Middle Channel: 2441 MHz									
2441	63.87	PK	H	23.40	3.00	0.00	90.27	N/A	N/A
2441	52.17	AV	H	23.40	3.00	0.00	78.57	N/A	N/A
2441	58.74	PK	V	23.40	3.00	0.00	85.14	N/A	N/A
2441	47.15	AV	V	23.40	3.00	0.00	73.55	N/A	N/A
4882	36.29	PK	H	31.02	5.09	26.87	45.53	74.00	28.47
4882	23.57	AV	H	31.02	5.09	26.87	32.81	54.00	21.19
7323	35.18	PK	H	34.95	6.22	26.40	49.95	74.00	24.05
7323	22.48	AV	H	34.95	6.22	26.40	37.25	54.00	16.75
2135	34.96	PK	H	24.44	3.03	26.84	35.59	74.00	38.41
2135	23.69	AV	H	24.44	3.03	26.84	24.32	54.00	29.68
3693	34.25	PK	H	27.77	4.47	26.57	39.92	74.00	34.08
3693	22.47	AV	H	27.77	4.47	26.57	28.14	54.00	25.86
531.49	37.47	QP	V	18.41	1.69	28.83	28.74	46.00	17.26
30	25.64	QP	V	22.70	0.31	28.57	20.08	40.00	19.92
High Channel: 2480 MHz									
2480	62.58	PK	H	23.27	2.99	0.00	88.84	N/A	N/A
2480	50.16	AV	H	23.27	2.99	0.00	76.42	N/A	N/A
2480	57.59	PK	V	23.27	2.99	0.00	83.85	N/A	N/A
2480	45.96	AV	V	23.27	2.99	0.00	72.22	N/A	N/A
2483.5	31.29	PK	H	23.26	2.99	0.00	57.54	74.00	16.46
2483.5	16.75	AV	H	23.26	2.99	0.00	43.00	54.00	11.00
4960	37.25	PK	H	31.27	5.05	26.88	46.69	74.00	27.31
4960	23.47	AV	H	31.27	5.05	26.88	32.91	54.00	21.09
7440	34.26	PK	H	35.18	6.27	26.45	49.26	74.00	24.74
7440	22.34	AV	H	35.18	6.27	26.45	37.34	54.00	16.66
2135	37.25	PK	H	24.44	3.03	26.84	37.88	74.00	36.12
2135	23.94	AV	H	24.44	3.03	26.84	24.57	54.00	29.43
531.49	35.47	QP	V	18.41	1.69	28.83	26.74	46.00	19.26

EDR Mode (8-DPSK):

Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	FCC 15.247	
(MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB)				Limit (dBµV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	63.95	PK	H	23.53	3.00	0.00	90.48	N/A	N/A
2402	52.67	AV	H	23.53	3.00	0.00	79.20	N/A	N/A
2402	57.69	PK	V	23.53	3.00	0.00	84.22	N/A	N/A
2402	46.54	AV	V	23.53	3.00	0.00	73.07	N/A	N/A
2390	33.26	PK	H	23.57	3.00	0.00	59.83	74.00	14.17
2390	23.64	AV	H	23.57	3.00	0.00	50.21	54.00	3.79
4804	36.75	PK	H	30.77	5.12	26.87	45.77	74.00	28.23
4804	24.69	AV	H	30.77	5.12	26.87	33.71	54.00	20.29
7206	34.21	PK	H	34.71	6.16	26.35	48.73	74.00	25.27
7206	22.99	AV	H	34.71	6.16	26.35	37.51	54.00	16.49
3250	36.47	PK	H	25.60	3.81	26.50	39.38	74.00	34.62
3250	22.79	AV	H	25.60	3.81	26.50	25.70	54.00	28.30
531.49	36.75	QP	V	18.41	1.69	28.83	28.02	46.00	17.98
Middle Channel: 2441 MHz									
2441	63.47	PK	H	23.40	3.00	0.00	89.87	N/A	N/A
2441	52.64	AV	H	23.40	3.00	0.00	79.04	N/A	N/A
2441	57.29	PK	V	23.40	3.00	0.00	83.69	N/A	N/A
2441	46.85	AV	V	23.40	3.00	0.00	73.25	N/A	N/A
4882	35.75	PK	H	31.02	5.09	26.87	44.99	74.00	29.01
4882	23.67	AV	H	31.02	5.09	26.87	32.91	54.00	21.09
7323	34.77	PK	H	34.95	6.22	26.40	49.54	74.00	24.46
7323	22.69	AV	H	34.95	6.22	26.40	37.46	54.00	16.54
3250	34.79	PK	H	25.60	3.81	26.50	37.70	74.00	36.30
3250	23.58	AV	H	25.60	3.81	26.50	26.49	54.00	27.51
3693	33.99	PK	H	27.77	4.47	26.57	39.66	74.00	34.34
3693	22.37	AV	H	27.77	4.47	26.57	28.04	54.00	25.96
531.49	38.55	QP	V	18.41	1.69	28.83	29.82	46.00	16.18
30	27.47	QP	V	22.70	0.31	28.57	21.91	40.00	18.09
High Channel: 2480 MHz									
2480	62.17	PK	H	23.27	2.99	0.00	88.43	N/A	N/A
2480	49.89	AV	H	23.27	2.99	0.00	76.15	N/A	N/A
2480	56.72	PK	V	23.27	2.99	0.00	82.98	N/A	N/A
2480	44.69	AV	V	23.27	2.99	0.00	70.95	N/A	N/A
2483.5	31.25	PK	H	23.26	2.99	0.00	57.50	74.00	16.50
2483.5	16.77	AV	H	23.26	2.99	0.00	43.02	54.00	10.98
4960	34.69	PK	H	31.27	5.05	26.88	44.13	74.00	29.87
4960	22.75	AV	H	31.27	5.05	26.88	32.19	54.00	21.81
7440	36.52	PK	H	35.18	6.27	26.45	51.52	74.00	22.48
7440	23.74	AV	H	35.18	6.27	26.45	38.74	54.00	15.26
3250	34.57	PK	H	25.60	3.81	26.50	37.48	74.00	36.52
3250	23.69	AV	H	25.60	3.81	26.50	26.60	54.00	27.40
531.49	37.89	QP	V	18.41	1.69	28.83	29.16	46.00	16.84

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	29.8 °C
Relative Humidity:	39 %
ATM Pressure:	101.2 kPa

* The testing was performed by Lorin Bian on 2016-10-30.

Test Result: Compliance.

Please refer to following tables and plots


Test Mode: Transmitting

Mode	Channel	Frequency	Channel Separation	Limit	Result
		MHz	MHz	MHz	
BDR (GFSK)	Low	2402	1.002	0.62	Compliance
		2403			
	Middle	2441	1.002	0.62	
		2442			
	High	2479	0.998	0.63	
		2480			
EDR ($\pi/4$ -DQPSK)	Low	2402	1.002	0.85	Compliance
		2403			
	Middle	2441	1.002	0.85	
		2442			
	High	2479	0.994	0.85	
		2480			
EDR (8DPSK)	Low	2402	1.002	0.85	Compliance
		2403			
	Middle	2441	1.002	0.87	
		2442			
	High	2479	0.998	0.89	
		2480			


Note: Limit= (2/3)*20dB bandwidth

BDR Mode (GFSK):


Low Channel



Middle Channel




High Channel




EDR Mode ($\pi/4$ -DQPSK):


Low Channel



Middle Channel




High Channel




EDR Mode (8-DPSK):


Low Channel



Middle Channel



High Channel



FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	29.8 °C
Relative Humidity:	39 %
ATM Pressure:	101.2 kPa

* The testing was performed by Lorin Bian on 2016-10-30.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting


Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.93
	Middle	2441	0.93
	High	2480	0.94
EDR Mode ($\pi/4$ -DQPSK):	Low	2402	1.27
	Middle	2441	1.28
	High	2480	1.28
EDR Mode (8-DPSK):	Low	2402	1.27
	Middle	2441	1.30
	High	2480	1.33

Please refer to the following plots.


BDR Mode (GFSK):



Middle Channel




High Channel




EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 30.OCT.2016 10:10:46

Middle Channel




Date: 30.OCT.2016 10:11:53

High Channel




EDR Mode (8-DPSK):


Low Channel



Middle Channel



High Channel



FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	29.8 °C
Relative Humidity:	39 %
ATM Pressure:	101.2 kPa

* The testing was performed by Lorin Bian on 2016-10-30.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting


BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15



EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 * channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s
Hop rate=1600/s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	29.8 °C
Relative Humidity:	39 %
ATM Pressure:	101.2 kPa

* The testing was performed by Lorin Bian on 2016-10-30.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting


BDR Mode (GFSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.379	0.121	0.4	Pass
	Middle	0.387	0.124	0.4	Pass
	High	0.387	0.124	0.4	Pass
	Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s				
DH3	Low	1.647	0.264	0.4	Pass
	Middle	1.647	0.264	0.4	Pass
	High	1.647	0.264	0.4	Pass
	Note: Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s				
DH5	Low	2.896	0.309	0.4	Pass
	Middle	2.906	0.310	0.4	Pass
	High	2.896	0.309	0.4	Pass
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s				

DH1: Low Channel




DH1: Middle Channel




Date: 30.OCT.2016 10:38:11

DH1: High Channel




Date: 30.OCT.2016 10:38:20


DH3: Low Channel




DH3: Middle Channel




DH3: High Channel




DH5: Low Channel



DH5: Middle Channel




DH5: High Channel



EDR Mode ($\pi/4$ -DQPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.385	0.123	0.4	Pass
	Middle	0.391	0.125	0.4	Pass
	High	0.391	0.125	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
DH3	Low	1.647	0.264	0.4	Pass
	Middle	1.647	0.264	0.4	Pass
	High	1.647	0.264	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
DH5	Low	2.906	0.310	0.4	Pass
	Middle	2.906	0.310	0.4	Pass
	High	2.906	0.310	0.4	Pass
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				

DH1: Low Channel




Date: 30.OCT.2016 10:50:03


DH3: Low Channel




DH3: Middle Channel




DH3: High Channel




DH5: Low Channel




DH5: Middle Channel



DH5: High Channel




DH1: Middle Channel




Date: 30.OCT.2016 10:55:01

DH1: High Channel




Date: 30.OCT.2016 10:55:11


DH3: Low Channel




DH3: Middle Channel




DH3: High Channel



DH5: Low Channel




DH5: Middle Channel



Date: 30.OCT.2016 11:10:42

DH5: High Channel



Date: 30.OCT.2016 11:00:54

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	29.8 °C
Relative Humidity:	39 %
ATM Pressure:	101.2 kPa


* The testing was performed by Lorin Bian on 2016-10-30.

Test Result: Compliance.


Test Mode: Transmitting

Mode	Frequency (MHz)	Conducted Output Power (dBm)	Limit (dBm)
BDR Mode (GFSK)	2402	-1.77	30
	2441	-1.55	30
	2480	-3.62	30
EDR Mode ($\pi/4$ -DQPSK)	2402	-2.24	30
	2441	-1.89	30
	2480	-3.84	30
EDR Mode (8-DPSK)	2402	-2.13	30
	2441	-1.77	30
	2480	-3.84	30


BDR Mode (GFSK):



Output Power, Middle Channel




Output Power, High Channel




EDR Mode ($\pi/4$ -DQPSK):

Output Power, Low Channel




Date: 30.OCT.2016 10:11:11

Output Power, Middle Channel




Date: 30.OCT.2016 10:12:19

Output Power, High Channel




EDR Mode (8-DPSK):

Output Power, Low Channel




Output Power, Middle Channel



Date: 30.OCT.2016 10:16:18

Output Power, High Channel



Date: 30.OCT.2016 10:17:32

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2016-09-21	2017-09-20
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	29.8 °C
Relative Humidity:	39 %
ATM Pressure:	101.2 kPa

* The testing was performed by Lorin Bian on 2016-10-30.


Test Result: Compliance

BDR Mode (GFSK):

Band Edge, Left Side




Band Edge, Right Side




EDR Mode ($\pi/4$ -DQPSK):

Band Edge, Left Side




Band Edge, Right Side




EDR Mode (8-DPSK):

Band Edge, Left Side



Date: 30.OCT.2016 10:15:22

Band Edge, Right Side



Date: 30.OCT.2016 10:17:57

***** END OF REPORT *****