



# **MAXIMUM PERMISSIBLE EXPOSURE REPORT**

**FOR THE**

**FCC ID: XGLMD015**

**IC: 8272A-MD015**

**MODEL NUMBER: MD015A**

**DATE OF ISSUE: JULY 20, 2009**

**PREPARED FOR:**

Cellynx Group, Inc.  
5047 Robert J. Matthews  
El Dorado Hills, CA 95762

**PREPARED BY:**

Joyce Walker  
CKC Laboratories, Inc.  
5046 Sierra Pines Drive  
Mariposa, CA 95338

W.O. No.: 89227

**Report No.: FC09-113-R**

## Purpose of Test:

To demonstrate compliance with United States and Canada RF Exposure requirements for Mobile Equipment (devices used >20cm from the body), where Maximum Permissible Exposure (MPE) Calculations apply.

## United States MPE Limits in accordance with 1.1310:

### *Occupational / Controlled Exposure*

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minutes) |
|-----------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| 0.3-3.0               | 614                           | 1.63                          | *(100)                              | 6                        |
| 3.0-30                | 1842/f                        | 4.89/f                        | *(900/f <sup>2</sup> )              | 6                        |
| 30-300                | 61.4                          | 0.163                         | 1                                   | 6                        |
| 300-1500              | ---                           | ---                           | f/300                               | 6                        |
| 1500-100,000          | ---                           | ---                           | 5                                   | 6                        |

### *General Population / Uncontrolled Exposure*

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minutes) |
|-----------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| 0.3-1.34              | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34-30               | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30-300                | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1500              | ---                           | ---                           | f/1500                              | 30                       |
| 1500-100,000          | ---                           | ---                           | 1                                   | 30                       |

*Note: Limit is calculated based on the mid-band frequency used in the operating frequency range.*

**Canadian MPE Limits in accordance with RSS-102:**

***Occupational / Controlled Exposure:***

| Frequency Range (MHz) | Electric Field (V/M rms) | Magnetic Field (A/m rms)     | Power Density (W/m <sup>2</sup> ) | Time Averaging (min) |
|-----------------------|--------------------------|------------------------------|-----------------------------------|----------------------|
| 0.003-1               | 600                      | 4.9                          | -                                 | 6                    |
| 1-10                  | $600 / f$                | $4.9 / f$                    | -                                 | 6                    |
| 10-30                 | 60                       | $4.9 / f$                    | -                                 | 6                    |
| 30-300                | 60                       | 0.163                        | 10 <sup>*</sup>                   | 6                    |
| 300-1500              | $3.54 f^{0.5}$           | $0.0094 f^{0.5}$             | $f / 30$                          | 6                    |
| 1500-15000            | 137                      | 0.364                        | 50                                | 6                    |
| 15000-150000          | 137                      | 0.364                        | 50                                | $616000 / f^{1.2}$   |
| 150000-300000         | $0.354 f^{0.5}$          | $9.4 \times 10^{-4} f^{0.5}$ | $3.33 \times 10^{-4} f$           | $616000 / f^{1.2}$   |

***General Population / Uncontrolled Exposure***

| Frequency Range (MHz) | Electric Field (V/M rms) | Magnetic Field (A/m rms)      | Power Density (W/m <sup>2</sup> ) | Time Averaging (min) |
|-----------------------|--------------------------|-------------------------------|-----------------------------------|----------------------|
| 0.003-1               | 280                      | 2.19                          | -                                 | 6                    |
| 1-10                  | $280 / f$                | $2.19 / f$                    | -                                 | 6                    |
| 10-30                 | 28                       | $2.19 / f$                    | -                                 | 6                    |
| 30-300                | 28                       | 0.073                         | 2 <sup>*</sup>                    | 6                    |
| 300-1 500             | $1.585 f^{0.5}$          | $0.0042 f^{0.5}$              | $f / 150$                         | 6                    |
| 1 500-15 000          | 61.4                     | 0.163                         | 10                                | 6                    |
| 15 000-150 000        | 61.4                     | 0.163                         | 10                                | $616000 / f^{1.2}$   |
| 150 000-300 000       | $0.158 f^{0.5}$          | $4.21 \times 10^{-4} f^{0.5}$ | $6.67 \times 10^{-5} f$           | $616000 / f^{1.2}$   |

**Note:**  $f$  is frequency in MHz

\* Power density limit is applicable at frequencies greater than 100 MHz



### Equipment operational details:

| <i>Operating Frequency (MHz)</i> | <i>Measured Output Power (dBm)</i> | <i>Maximum Mobile Antenna Gain (dBi)</i> | <i>Maximum EIRP (dBm)</i> |
|----------------------------------|------------------------------------|------------------------------------------|---------------------------|
| 1850-1910                        | 26.73                              | 5.91                                     | 33.01                     |
| 1930-1990                        | 25.12                              | 7.93                                     | 33.01                     |

Measurements based from EMC Test Report: FC09-113.

### **Device and Antenna Operating Configuration:**

Device operating at maximum output power with continuous transmission of modulated data.

### **Test Procedure:**

This equipment is evaluated in accordance with the guidelines set forth in OET Guide 65 & ANSI C95.1 for the US and Health Canada Safety Code 6 & RSS 102 for Canada.

### **Other Considerations:**

The maximum EIRP is chosen such that the power output requirements of 24.232 are met. The maximum allowable antenna gain is calculated assuming the maximum EIRP allowed for mobile equipment under this rule part.

### **MPE Calculations:**

#### **Limit used:**

Occupational / Controlled Exposure  
 X General Population / Uncontrolled Exposure

$$\text{MPE Limit} = 1 \text{ (mW/cm}^2\text{)}$$

$$\text{PowerDensity(mW / cm}^2\text{)} = \frac{\text{EIRP}}{4\pi d^2}$$

Given: **EIRP** in *mW* and **d** in *cm*

| EIRP (mW) | Distance (cm) | Power Density (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) | Power Density (W/m <sup>2</sup> ) | Limit (W/m <sup>2</sup> ) |
|-----------|---------------|-------------------------------------|-----------------------------|-----------------------------------|---------------------------|
| 33.01     | 20            | 0.398                               | 1                           | 3.98                              | 10                        |
| 33.01     | 20            | 0.398                               | 1                           | 3.98                              | 10                        |

**Statement of Compliance:**

This device demonstrates compliance under the operating conditions specified in this document. Under normal operating conditions, the antenna is designed to be installed in accordance with the manufacturer's instructions in such a manner to maintain the minimum separation distance. The MPE calculations shown above demonstrate compliance to the provisions of US and Canadian requirements.

As can be seen from the MPE results, this device passes the specified limits at a distance of 20cm at the maximum output power under normal operating conditions.