



FCC RADIO TEST REPORT

FCC ID : XGS-DS3
Equipment : DS310
Brand Name : ORBCOMM
Model Name : DS310
Marketing Name : DS 310
Applicant : ORBCOMM Canada Inc.
750 Palladium Drive Suite 100, Ottawa ON K2V 1C7
Manufacturer : ORBCOMM Inc.
395 W Passaic Street, Suite 325, Rochelle Park, NJ 07662 USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on Sep. 16, 2025 and testing was performed from Sep. 22, 2025 to Oct. 07, 2025. We, Sporton International (USA) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International (USA) Inc., the test report shall not be reproduced except in full.

Approved by: Neil Kao

Sporton International (USA) Inc.
1175 Montague Expressway, Milpitas, CA 95035



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	5
2 Test Configuration of Equipment Under Test.....	6
2.1 Carrier Frequency Channel	6
2.2 Test Mode.....	7
2.3 Connection Diagram of Test System.....	8
2.4 EUT Operation Test Setup	8
2.5 Measurement Results Explanation Example.....	8
3 Test Result.....	9
3.1 6dB and 99% Bandwidth Measurement	9
3.2 Output Power Measurement.....	10
3.3 Power Spectral Density Measurement	11
3.4 Conducted Band Edges and Spurious Emission Measurement	12
3.5 Radiated Band Edges and Spurious Emission Measurement	13
3.6 Antenna Requirements.....	17
4 List of Measuring Equipment	18
5 Measurement Uncertainty	19
Appendix A. Conducted Test Results	
Appendix B. Radiated Spurious Emission Test Result	
Appendix C. Duty Cycle Plots	
Appendix D. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR250915008	01	Initial issue of report	Oct. 30, 2025
FR250915008	02	Revise Summary of Test Result This report is an updated version, replacing the report issued on Oct. 30, 2025.	Nov. 04, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	-
-	15.207	AC Conducted Emission	Not Required	-
3.6	15.203	Antenna Requirement	Pass	-

Note: The power source method of the EUT is to use DC power source, and there is no other AC power port, after assessing, AC Conduction Emission test is not required.

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature		
General Specs Bluetooth-LE		
Antenna Type Bluetooth: Inverted F Antenna build on PCB		
Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	1.8

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International (USA) Inc.
Test Site Location	1175 Montague Expressway, Milpitas, CA 95035 TEL : 408 9043300
Test Site No.	Sporton Site No.
	TH01-CA, 03CH01-CA

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: US1250

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2020

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-


2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
Conducted Test Cases	Bluetooth – LE / GFSK
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
Remark: - For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power. - The detailed Radiated test modes are shown in Appendix B.	

2.3 Connection Diagram of Test System



2.4 EUT Operation Test Setup

The RF test items, utility “Tera Term 4.88” was installed in EUT which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth VBW $\geq 3 * RBW$. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth, and set the Video bandwidth (VBW) $\geq 3 * RBW$.
5. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = No faster than coupled (auto) time, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.6 Antenna Requirements

3.6.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.6.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	6111D	54683	30MHz~1GHz	Nov. 15, 2024	Oct. 06, 2025~ Oct. 07, 2025	Nov. 14, 2025	Radiation (03CH01-CA)
Horn Antenna	SCHWARZBECK	BBHA 9120D	02115	1GHz~18GHz	Aug. 08, 2025	Oct. 06, 2025~ Oct. 07, 2025	Aug. 07, 2026	Radiation (03CH01-CA)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA9170	00841	18GHz~40GHz	Aug. 08, 2025	Oct. 06, 2025~ Oct. 07, 2025	Aug. 07, 2026	Radiation (03CH01-CA)
Preamplifier	SONOMA	310N	372241	9kHz~1GHz	Apr. 14, 2025	Oct. 06, 2025~ Oct. 07, 2025	Apr. 13, 2026	Radiation (03CH01-CA)
Preamplifier	E-instrument	ERA-100M-18G-56-01-A70	EC1900252	1GHz~18GHz	Apr. 14, 2025	Oct. 06, 2025~ Oct. 07, 2025	Apr. 13, 2026	Radiation (03CH01-CA)
Preamplifier	EMEC	EMC18G40G	060726	18G-40G	Apr. 15, 2025	Oct. 06, 2025~ Oct. 07, 2025	Apr. 14, 2026	Radiation (03CH01-CA)
Filter	Wainwright	WHKX12-2700-3000-18000-60ST	SN9	3GHz High Pass Filter	Jun. 03, 2025	Oct. 06, 2025~ Oct. 07, 2025	Jun. 02, 2026	Radiation (03CH01-CA)
Filter	Wainwright	WLK12-1200-1272-11000-40SS	SN1	1.2GHz Low Pass Filter	Jun. 03, 2025	Oct. 06, 2025~ Oct. 07, 2025	Jun. 02, 2026	Radiation (03CH01-CA)
EMI Test Receiver	R&S	ESU26	100049	20Hz~26.5GHz	Apr. 14, 2025	Oct. 06, 2025~ Oct. 07, 2025	Apr. 13, 2026	Radiation (03CH01-CA)
Spectrum Analyzer	Keysight	N9010B	MY63440343	10Hz - 44GHz	Jan. 29, 2025	Oct. 06, 2025~ Oct. 07, 2025	Jan. 28, 2026	Radiation (03CH01-CA)
RF Cable	HUBER+SUHNER	SUCOFLEX 102	8015932/2,80 15762/2, 805882/2	NA	Jul. 30, 2025	Oct. 06, 2025~ Oct. 07, 2025	Jul. 29, 2026	Radiation (03CH01-CA)
Hygrometer	TESTO	608-H1	45142559	NA	Aug. 08, 2025	Oct. 06, 2025~ Oct. 07, 2025	Aug. 07, 2026	Radiation (03CH01-CA)
Controller	Chaintek	EM-1000	060881	Control Turn Table & Antenna Mast	N/A	Oct. 06, 2025~ Oct. 07, 2025	N/A	Radiation (03CH01-CA)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Oct. 06, 2025~ Oct. 07, 2025	N/A	Radiation (03CH01-CA)
Test Software	Audix E3	E3 230621 Sporton US,V9	PK-002093	N/A	N/A	Oct. 06, 2025~ Oct. 07, 2025	N/A	Radiation (03CH01-CA)
Hygrometer	Testo	608-H1	45141354	N/A	Aug. 08, 2025	Sep. 22, 2025	Aug. 07, 2026	Conducted (TH01-CA)
Power Sensor	DARE Instruments	RPR3006W	RPR6W-1901024	10MHz~6GHz	Apr. 17, 2025	Sep. 22, 2025	Apr. 16, 2026	Conducted (TH01-CA)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101545	10Hz~40GHz	Apr. 17, 2025	Sep. 22, 2025	Apr. 16, 2026	Conducted (TH01-CA)
Switch Box	EM Electronics	EMSW26	1090304	N/A	Sep. 15, 2025	Sep. 22, 2025	Sep. 14, 2026	Conducted (TH01-CA)

5 Measurement Uncertainty

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7 dB
--	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Venkata Kondepudi	Temperature:	23.9	°C
Test Date:	2025/9/22	Relative Humidity:	58.7	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.049	0.697	0.50	Pass
BLE	1Mbps	1	19	2440	1.051	0.712	0.50	Pass
BLE	1Mbps	1	39	2480	1.051	0.717	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	6.35	30.00	1.80	8.15	36.00	Pass
BLE	1Mbps	1	19	2440	6.33	30.00	1.80	8.13	36.00	Pass
BLE	1Mbps	1	39	2480	5.30	30.00	1.80	7.10	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	6.38	-9.09	1.80	8.00	Pass
BLE	1Mbps	1	19	2440	6.41	-8.93	1.80	8.00	Pass
BLE	1Mbps	1	39	2480	5.44	-9.60	1.80	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	2.049	1.146	0.50	Pass
BLE5.0	2Mbps	1	19	2440	2.058	1.149	0.50	Pass
BLE5.0	2Mbps	1	39	2480	2.061	1.138	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE5.0	2Mbps	1	0	2402	6.33	30.00	1.80	8.13	36.00	Pass
BLE5.0	2Mbps	1	19	2440	6.25	30.00	1.80	8.05	36.00	Pass
BLE5.0	2Mbps	1	39	2480	5.23	30.00	1.80	7.03	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	6.33	-11.66	1.80	8.00	Pass
BLE5.0	2Mbps	1	19	2440	6.39	-11.61	1.80	8.00	Pass
BLE5.0	2Mbps	1	39	2480	5.34	-12.78	1.80	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.




Number of TX = 1, Ant. 1 (Measured)


6dB Bandwidth

<1M>


6 dB Bandwidth Plot on Channel 0



6 dB Bandwidth Plot on Channel 19




6 dB Bandwidth Plot on Channel 39






<2M>


6 dB Bandwidth Plot on Channel 0



6 dB Bandwidth Plot on Channel 19






6 dB Bandwidth Plot on Channel 39



**99% Occupied Bandwidth**


<1M>

99% Occupied Bandwidth Plot on Channel 0**99% Occupied Bandwidth Plot on Channel 19****99% Occupied Bandwidth Plot on Channel 39**




<2M>


99% Occupied Bandwidth Plot on Channel 0



99% Occupied Bandwidth Plot on Channel 19






99% Occupied Bandwidth Plot on Channel 39



**Power Spectral Density (dBm/3kHz)**


<1M>

Power Density (dBm/3kHz) Plot Channel 0**Power Density (dBm/3kHz) Plot Channel 19****Power Density (dBm/3kHz) Plot Channel 39**




<2M>


Power Density (dBm/3kHz) Plot Channel 0







Power Density (dBm/3kHz) Plot Channel 19




Power Density (dBm/3kHz) Plot Channel 39



Band Edge and Conducted Spurious Emission
<1M>
Channel 0
100kHz PSD reference Level Plot

Plot on Channel 0

Spurious Emission 30MHz~1GHz Plot

Spurious Emission 1GHz~26.5GHz Plot



Channel 19

100kHz PSD reference Level Plot




Plot on Channel 19

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 39


100kHz PSD reference Level Plot




Plot on Channel 39



Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






<2M>




Channel 19

100kHz PSD reference Level Plot




Plot on Channel 19

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 39


100kHz PSD reference Level Plot




Plot on Channel 39



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot





Appendix B. Radiated Spurious Emission Test Data

Test Engineer :	Leo Liu	Relative Humidity :	45.7~49.9%
		Temperature :	20.8~22.6°C

Note symbol

-L	Low channel location
-R	High channel location

B1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	1TX	Bluetooth-LE GSKF	00	2402	1Mbps	-	-
Mode 2	2400-2483.5	1TX	Bluetooth-LE GSKF	19	2440	1Mbps	-	-
Mode 3	2400-2483.5	1TX	Bluetooth-LE GSKF	39	2480	1Mbps	-	-
Mode 4	2400-2483.5	1TX	Bluetooth-LE GSKF	00	2402	2Mbps	-	-
Mode 5	2400-2483.5	1TX	Bluetooth-LE GSKF	19	2440	2Mbps	-	-
Mode 6	2400-2483.5	1TX	Bluetooth-LE GSKF	39	2480	2Mbps	-	-
Mode 7	2400-2483.5	1TX	Bluetooth-LE GSKF	19	2440	1Mbps	-	LF
Mode 8	2400-2483.5	1TX	Bluetooth-LE GSKF	19	2440	1Mbps	-	SHF

B2. Summary of each worse mode





Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
1	Bluetooth-LE GSKF	00	2362.07	47.47	54.00	-6.53	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE GSKF	00	7206.00	55.39	74.00	-18.61	V	Peak	Pass	-	Harmonic
2	Bluetooth-LE GSKF	19	2496.04	47.03	54.00	-6.97	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE GSKF	19	7320.00	51.57	54.00	-2.43	V	Avg.	Pass	-	Harmonic
3	Bluetooth-LE GSKF	39	2483.62	47.52	54.00	-6.48	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE GSKF	39	7440.00	51.04	54.00	-2.96	V	Avg.	Pass	-	Harmonic
4	Bluetooth-LE GSKF	00	2361.70	47.02	54.00	-6.98	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE GSKF	00	7206.00	55.12	74.00	-18.88	V	Peak	Pass	-	Harmonic
5	Bluetooth-LE GSKF	19	2495.74	47.24	54.00	-6.76	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE GSKF	19	7320.00	49.71	54.00	-4.29	H	Avg.	Pass	-	Harmonic
6	Bluetooth-LE GSKF	39	2483.52	50.70	54.00	-3.30	H	Avg.	Pass	-	Band Edge

**FCC RADIO TEST REPORT**





Report No. : FR250915008

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
6	Bluetooth-LE GSKF	39	7440.00	50.23	54.00	-3.77	V	Avg.	Pass	-	Harmonic
7	LF	19	636.25	34.22	46.00	-11.78	V	Peak	Pass	-	LF
8	SHF	19	24300.00	43.43	74.00	-30.57	V	Peak	Pass	-	SHF





Mode	1																																																																																								
	Band Edge																																																																																								
	2400-2483.5_Bluetooth-LE GSKF_CH00_2402MHz																																																																																								
ANT	1TX																																																																																								
Pol.	Horizontal						Fundamental																																																																																		
Peak	 Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level Factor</th><th>Ant Loss Factor</th><th>Cable Loss Factor</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2385.53</td><td>55.80</td><td>74.00</td><td>-18.20</td><td>41.57</td><td>27.58</td><td>7.30</td><td>30.63</td><td>9.98</td><td>180</td><td>360</td><td>PEAK</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level Factor	Ant Loss Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2385.53	55.80	74.00	-18.20	41.57	27.58	7.30	30.63	9.98	180	360	PEAK	 Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level Factor</th><th>Ant Loss Factor</th><th>Cable Preamp Loss Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>105.67</td><td>-----</td><td>-----</td><td>91.32</td><td>27.66</td><td>7.33</td><td>30.62</td><td>9.98</td><td>180</td><td>360</td><td>PEAK</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level Factor	Ant Loss Factor	Cable Preamp Loss Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2402.00	105.67	-----	-----	91.32	27.66	7.33	30.62	9.98	180	360	PEAK
		Freq	Level	Limit	Line Margin	Read Level Factor	Ant Loss Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																														
1	2385.53	55.80	74.00	-18.20	41.57	27.58	7.30	30.63	9.98	180	360	PEAK																																																																													
	Freq	Level	Limit	Line Margin	Read Level Factor	Ant Loss Factor	Cable Preamp Loss Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																														
1	2402.00	105.67	-----	-----	91.32	27.66	7.33	30.62	9.98	180	360	PEAK																																																																													
Avg	 Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level Factor</th><th>Ant Loss Factor</th><th>Cable Preamp Loss Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2362.07</td><td>47.47</td><td>54.00</td><td>-6.53</td><td>33.41</td><td>27.46</td><td>7.26</td><td>30.64</td><td>9.98</td><td>180</td><td>360</td><td>AVERAGE</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level Factor	Ant Loss Factor	Cable Preamp Loss Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2362.07	47.47	54.00	-6.53	33.41	27.46	7.26	30.64	9.98	180	360	AVERAGE	 Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level Factor</th><th>Ant Loss Factor</th><th>Cable Preamp Loss Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>105.15</td><td>-----</td><td>-----</td><td>90.80</td><td>27.66</td><td>7.33</td><td>30.62</td><td>9.98</td><td>180</td><td>360</td><td>AVERAGE</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level Factor	Ant Loss Factor	Cable Preamp Loss Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2402.00	105.15	-----	-----	90.80	27.66	7.33	30.62	9.98	180	360	AVERAGE	
		Freq	Level	Limit	Line Margin	Read Level Factor	Ant Loss Factor	Cable Preamp Loss Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																														
1	2362.07	47.47	54.00	-6.53	33.41	27.46	7.26	30.64	9.98	180	360	AVERAGE																																																																													
	Freq	Level	Limit	Line Margin	Read Level Factor	Ant Loss Factor	Cable Preamp Loss Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																														
1	2402.00	105.15	-----	-----	90.80	27.66	7.33	30.62	9.98	180	360	AVERAGE																																																																													



Mode	1																																																																																																	
	Band Edge																																																																																																	
	2400-2483.5_Bluetooth-LE GSKF_CH00_2402MHz																																																																																																	
ANT	1TX																																																																																																	
Pol.	Vertical						Fundamental																																																																																											
Peak																																																																																																		
	Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2357.29</td><td>55.58</td><td>74.00</td><td>-18.42</td><td>41.71</td><td>27.28</td><td>7.25</td><td>30.64</td><td>9.98</td><td>386 47 PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2357.29	55.58	74.00	-18.42	41.71	27.28	7.25	30.64	9.98	386 47 PEAK	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>102.37</td><td>-----</td><td>-----</td><td>88.14</td><td>27.54</td><td>7.33</td><td>30.62</td><td>9.98</td><td>386 47 PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	102.37	-----	-----	88.14	27.54	7.33	30.62	9.98
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2357.29	55.58	74.00	-18.42	41.71	27.28	7.25	30.64	9.98	386 47 PEAK																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2402.00	102.37	-----	-----	88.14	27.54	7.33	30.62	9.98	386 47 PEAK																																																																																								
Avg																																																																																																		
	Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2378.00</td><td>45.89</td><td>54.00</td><td>-8.11</td><td>31.87</td><td>27.38</td><td>7.29</td><td>30.63</td><td>9.98</td><td>386 47 AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2378.00	45.89	54.00	-8.11	31.87	27.38	7.29	30.63	9.98	386 47 AVERAGE	Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>101.81</td><td>-----</td><td>-----</td><td>87.58</td><td>27.54</td><td>7.33</td><td>30.62</td><td>9.98</td><td>386 47 AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	101.81	-----	-----	87.58	27.54	7.33	30.62	9.98
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2378.00	45.89	54.00	-8.11	31.87	27.38	7.29	30.63	9.98	386 47 AVERAGE																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2402.00	101.81	-----	-----	87.58	27.54	7.33	30.62	9.98	386 47 AVERAGE																																																																																								







Mode	1																																																																																																																																
	Harmonic																																																																																																																																
	2400-2483.5_Bluetooth-LE GSKF_CH00_2402MHz																																																																																																																																
ANT	1TX																																																																																																																																
Pol.	Horizontal						Vertical																																																																																																																										
Peak Avg																																																																																																																																	
	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250808 HORIZONTAL						Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250808 VERTICAL																																																																																																																										
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4804.00</td><td>43.54</td><td>74.00</td><td>-30.46</td><td>67.37</td><td>32.52</td><td>9.81</td><td>66.76</td><td>0.60</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7206.00</td><td>54.50</td><td>74.00</td><td>-19.50</td><td>69.72</td><td>36.91</td><td>12.13</td><td>64.62</td><td>0.36</td><td>319</td><td>181</td><td>PEAK</td></tr></table>														Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4804.00	43.54	74.00	-30.46	67.37	32.52	9.81	66.76	0.60	--	--	PEAK	2	7206.00	54.50	74.00	-19.50	69.72	36.91	12.13	64.62	0.36	319	181	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4804.00</td><td>43.32</td><td>74.00</td><td>-30.68</td><td>67.13</td><td>32.54</td><td>9.81</td><td>66.76</td><td>0.60</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7206.00</td><td>55.39</td><td>74.00</td><td>-18.61</td><td>70.60</td><td>36.92</td><td>12.13</td><td>64.62</td><td>0.36</td><td>102</td><td>290</td><td>PEAK</td></tr></table>				Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4804.00	43.32	74.00	-30.68	67.13	32.54	9.81	66.76	0.60	--	--	PEAK	2	7206.00	55.39	74.00	-18.61	70.60	36.92	12.13	64.62	0.36	102	290	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																							
1	4804.00	43.54	74.00	-30.46	67.37	32.52	9.81	66.76	0.60	--	--	PEAK																																																																																																																					
2	7206.00	54.50	74.00	-19.50	69.72	36.91	12.13	64.62	0.36	319	181	PEAK																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																							
1	4804.00	43.32	74.00	-30.68	67.13	32.54	9.81	66.76	0.60	--	--	PEAK																																																																																																																					
2	7206.00	55.39	74.00	-18.61	70.60	36.92	12.13	64.62	0.36	102	290	PEAK																																																																																																																					



Mode	1	
	Harmonic	
	2400-2483.5_Bluetooth-LE GSKF_CH00_2402MHz	
ANT	1TX	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Level (dBuV/m) Frequency (MHz) Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250008 HORIZONTAL	Level (dBuV/m) Frequency (MHz) Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250008 VERTICAL







Mode	2																																																																																																			
	Band Edge - L																																																																																																			
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																																																																																			
ANT	1TX																																																																																																			
Pol.	Horizontal						Fundamental																																																																																													
Peak	 Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2359.53</td><td>55.54</td><td>74.00</td><td>-18.46</td><td>41.49</td><td>27.45</td><td>7.26</td><td>30.64</td><td>9.98</td><td>355</td><td>185</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2359.53	55.54	74.00	-18.46	41.49	27.45	7.26	30.64	9.98	355	185	PEAK	 Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>101.92</td><td>-----</td><td>-----</td><td>87.34</td><td>27.82</td><td>7.39</td><td>30.61</td><td>9.98</td><td>355</td><td>185</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	101.92	-----	-----	87.34	27.82	7.39	30.61	9.98	355	185	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2359.53	55.54	74.00	-18.46	41.49	27.45	7.26	30.64	9.98	355	185	PEAK																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2440.00	101.92	-----	-----	87.34	27.82	7.39	30.61	9.98	355	185	PEAK																																																																																								
Avg	 Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2383.84</td><td>46.98</td><td>54.00</td><td>-7.02</td><td>32.76</td><td>27.57</td><td>7.30</td><td>30.63</td><td>9.98</td><td>355</td><td>185</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2383.84	46.98	54.00	-7.02	32.76	27.57	7.30	30.63	9.98	355	185	AVERAGE	 Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>101.32</td><td>-----</td><td>-----</td><td>86.74</td><td>27.82</td><td>7.39</td><td>30.61</td><td>9.98</td><td>355</td><td>185</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	101.32	-----	-----	86.74	27.82	7.39	30.61	9.98	355	185	AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2383.84	46.98	54.00	-7.02	32.76	27.57	7.30	30.63	9.98	355	185	AVERAGE																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2440.00	101.32	-----	-----	86.74	27.82	7.39	30.61	9.98	355	185	AVERAGE																																																																																								





Mode	2																																													
	Band Edge - R																																													
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																													
ANT	1TX																																													
Pol.	Horizontal	Fundamental																																												
Peak	Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2489.14</td><td>57.14</td><td>74.00</td><td>-16.86</td><td>42.29</td><td>27.98</td><td>7.46</td><td>30.57</td><td>9.98</td><td>355</td><td>185</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2489.14	57.14	74.00	-16.86	42.29	27.98	7.46	30.57	9.98	355	185	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																				
1	2489.14	57.14	74.00	-16.86	42.29	27.98	7.46	30.57	9.98	355	185	PEAK																																		
Avg	Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2496.04</td><td>47.03</td><td>54.00</td><td>-6.97</td><td>32.14</td><td>28.00</td><td>7.47</td><td>30.56</td><td>9.98</td><td>355</td><td>185</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2496.04	47.03	54.00	-6.97	32.14	28.00	7.47	30.56	9.98	355	185	AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																				
1	2496.04	47.03	54.00	-6.97	32.14	28.00	7.47	30.56	9.98	355	185	AVERAGE																																		





Mode	2																																																																																															
	Band Edge - L																																																																																															
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																																																																															
ANT	1TX																																																																																															
Pol.	Vertical						Fundamental																																																																																									
Peak																																																																																																
	Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2338.86</td><td>55.33</td><td>74.00</td><td>-18.67</td><td>41.54</td><td>27.23</td><td>7.22</td><td>30.64</td><td>9.98</td><td>374</td><td>233 PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2338.86	55.33	74.00	-18.67	41.54	27.23	7.22	30.64	9.98	374	233 PEAK	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>101.30</td><td>-----</td><td>-----</td><td>86.72</td><td>27.82</td><td>7.39</td><td>30.61</td><td>9.98</td><td>374</td><td>233 PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	101.30	-----	-----	86.72	27.82	7.39	30.61	9.98	374
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2338.86	55.33	74.00	-18.67	41.54	27.23	7.22	30.64	9.98	374	233 PEAK																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2440.00	101.30	-----	-----	86.72	27.82	7.39	30.61	9.98	374	233 PEAK																																																																																					
Avg																																																																																																
	Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2344.06</td><td>45.63</td><td>54.00</td><td>-8.37</td><td>31.82</td><td>27.24</td><td>7.23</td><td>30.64</td><td>9.98</td><td>374</td><td>233 AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2344.06	45.63	54.00	-8.37	31.82	27.24	7.23	30.64	9.98	374	233 AVERAGE	Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>100.76</td><td>-----</td><td>-----</td><td>86.18</td><td>27.82</td><td>7.39</td><td>30.61</td><td>9.98</td><td>374</td><td>233 AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	100.76	-----	-----	86.18	27.82	7.39	30.61	9.98	374
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2344.06	45.63	54.00	-8.37	31.82	27.24	7.23	30.64	9.98	374	233 AVERAGE																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2440.00	100.76	-----	-----	86.18	27.82	7.39	30.61	9.98	374	233 AVERAGE																																																																																					



Mode	2																																																							
	Band Edge - R																																																							
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																																							
ANT	1TX																																																							
Pol.	Vertical						Fundamental																																																	
Peak	 Level (dBuV/m) Frequency (MHz) PEAK_BE_74 1 Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2497.66</td><td>56.43</td><td>74.00</td><td>-17.57</td><td>41.47</td><td>28.06</td><td>7.48</td><td>30.56</td><td>9.98</td><td>374</td><td>233</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2497.66	56.43	74.00	-17.57	41.47	28.06	7.48	30.56	9.98	374	233	PEAK	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2497.66	56.43	74.00	-17.57	41.47	28.06	7.48	30.56	9.98	374	233	PEAK																																												
Avg	 Level (dBuV/m) Frequency (MHz) AVG_BE_54 Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2497.30</td><td>46.46</td><td>54.00</td><td>-7.54</td><td>31.50</td><td>28.06</td><td>7.48</td><td>30.56</td><td>9.98</td><td>374</td><td>233</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2497.30	46.46	54.00	-7.54	31.50	28.06	7.48	30.56	9.98	374	233	AVERAGE	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2497.30	46.46	54.00	-7.54	31.50	28.06	7.48	30.56	9.98	374	233	AVERAGE																																												



Mode	2																																																																																															
	Harmonic																																																																																															
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																																																																															
ANT	1TX																																																																																															
Pol.	Horizontal						Vertical																																																																																									
Peak Avg																																																																																																
	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250808 HORIZONTAL						Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250808 VERTICAL																																																																																									
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>45.41</td><td>74.00</td><td>-28.59</td><td>68.98</td><td>32.80</td><td>9.92</td><td>66.80</td><td>0.51</td><td>103</td><td>115</td><td>PEAK</td></tr><tr><td>2</td><td>4880.00</td><td>38.75</td><td>54.00</td><td>-15.25</td><td>62.32</td><td>32.80</td><td>9.92</td><td>66.80</td><td>0.51</td><td>103</td><td>115</td><td>Average</td></tr><tr><td>3</td><td>7320.00</td><td>55.54</td><td>74.00</td><td>-18.46</td><td>72.01</td><td>36.93</td><td>12.27</td><td>66.05</td><td>0.38</td><td>319</td><td>186</td><td>PEAK</td></tr><tr><td>4</td><td>7320.00</td><td>50.72</td><td>54.00</td><td>-3.28</td><td>67.19</td><td>36.93</td><td>12.27</td><td>66.05</td><td>0.38</td><td>319</td><td>186</td><td>Average</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	45.41	74.00	-28.59	68.98	32.80	9.92	66.80	0.51	103	115	PEAK	2	4880.00	38.75	54.00	-15.25	62.32	32.80	9.92	66.80	0.51	103	115	Average	3	7320.00	55.54	74.00	-18.46	72.01	36.93	12.27	66.05	0.38	319	186	PEAK	4	7320.00	50.72	54.00	-3.28	67.19	36.93	12.27	66.05	0.38	319	186	Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	4880.00	45.41	74.00	-28.59	68.98	32.80	9.92	66.80	0.51	103	115	PEAK																																																																																				
2	4880.00	38.75	54.00	-15.25	62.32	32.80	9.92	66.80	0.51	103	115	Average																																																																																				
3	7320.00	55.54	74.00	-18.46	72.01	36.93	12.27	66.05	0.38	319	186	PEAK																																																																																				
4	7320.00	50.72	54.00	-3.28	67.19	36.93	12.27	66.05	0.38	319	186	Average																																																																																				



Mode	2	
	Harmonic	
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz	
ANT	1TX	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Level (dBuV/m) Frequency (MHz) Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250008 HORIZONTAL	Level (dBuV/m) Frequency (MHz) Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250008 VERTICAL





Mode	3																																																																																									
	Band Edge																																																																																									
	2400-2483.5_Bluetooth-LE GSKF_CH39_2480MHz																																																																																									
ANT	1TX																																																																																									
Pol.	Horizontal	Fundamental																																																																																								
Peak	Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.56</td><td>57.08</td><td>74.00</td><td>-16.92</td><td>42.25</td><td>27.97</td><td>7.46</td><td>30.58</td><td>9.98</td><td>100</td><td>182</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.56	57.08	74.00	-16.92	42.25	27.97	7.46	30.58	9.98	100	182	PEAK	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>104.58</td><td>-----</td><td>-----</td><td>89.76</td><td>27.97</td><td>7.45</td><td>30.58</td><td>9.98</td><td>100</td><td>182</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	104.58	-----	-----	89.76	27.97	7.45	30.58	9.98	100	182	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2483.56	57.08	74.00	-16.92	42.25	27.97	7.46	30.58	9.98	100	182	PEAK																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2480.00	104.58	-----	-----	89.76	27.97	7.45	30.58	9.98	100	182	PEAK																																																																														
Avg	Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.62</td><td>47.52</td><td>54.00</td><td>-6.48</td><td>32.69</td><td>27.97</td><td>7.46</td><td>30.58</td><td>9.98</td><td>100</td><td>182</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.62	47.52	54.00	-6.48	32.69	27.97	7.46	30.58	9.98	100	182	AVERAGE	Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>104.02</td><td>-----</td><td>-----</td><td>89.20</td><td>27.97</td><td>7.45</td><td>30.58</td><td>9.98</td><td>100</td><td>182</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	104.02	-----	-----	89.20	27.97	7.45	30.58	9.98	100	182	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2483.62	47.52	54.00	-6.48	32.69	27.97	7.46	30.58	9.98	100	182	AVERAGE																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2480.00	104.02	-----	-----	89.20	27.97	7.45	30.58	9.98	100	182	AVERAGE																																																																														



Mode	3																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_Bluetooth-LE GSKF_CH39_2480MHz																																																																																																			
ANT	1TX																																																																																																			
Pol.	Vertical						Fundamental																																																																																													
Peak	Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.82</td><td>56.55</td><td>74.00</td><td>-17.45</td><td>41.64</td><td>28.04</td><td>7.46</td><td>30.57</td><td>9.98</td><td>356</td><td>229</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.82	56.55	74.00	-17.45	41.64	28.04	7.46	30.57	9.98	356	229	PEAK	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>100.56</td><td>-----</td><td>-----</td><td>85.69</td><td>28.02</td><td>7.45</td><td>30.58</td><td>9.98</td><td>356</td><td>229</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	100.56	-----	-----	85.69	28.02	7.45	30.58	9.98	356	229	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2480.82	56.55	74.00	-17.45	41.64	28.04	7.46	30.57	9.98	356	229	PEAK																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2480.00	100.56	-----	-----	85.69	28.02	7.45	30.58	9.98	356	229	PEAK																																																																																								
Avg	Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.86</td><td>46.63</td><td>54.00</td><td>-7.37</td><td>31.74</td><td>28.03</td><td>7.46</td><td>30.58</td><td>9.98</td><td>356</td><td>229</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.86	46.63	54.00	-7.37	31.74	28.03	7.46	30.58	9.98	356	229	AVERAGE	Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>99.86</td><td>-----</td><td>-----</td><td>84.99</td><td>28.02</td><td>7.45</td><td>30.58</td><td>9.98</td><td>356</td><td>229</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	99.86	-----	-----	84.99	28.02	7.45	30.58	9.98	356	229	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2483.86	46.63	54.00	-7.37	31.74	28.03	7.46	30.58	9.98	356	229	AVERAGE																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2480.00	99.86	-----	-----	84.99	28.02	7.45	30.58	9.98	356	229	AVERAGE																																																																																								







Mode	3																																																																																																																																																																							
	Harmonic																																																																																																																																																																							
	2400-2483.5_Bluetooth-LE GSKF_CH39_2480MHz																																																																																																																																																																							
ANT	1TX																																																																																																																																																																							
Pol.	Horizontal	Vertical																																																																																																																																																																						
Peak Avg	 Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250808 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4960.00</td><td>46.56</td><td>74.00</td><td>-27.44</td><td>70.00</td><td>33.04</td><td>10.03</td><td>66.93</td><td>0.42</td><td>108</td><td>44</td><td>PEAK</td></tr><tr><td>2</td><td>4960.00</td><td>40.92</td><td>54.00</td><td>-13.08</td><td>64.36</td><td>33.04</td><td>10.03</td><td>66.93</td><td>0.42</td><td>108</td><td>44</td><td>Average</td></tr><tr><td>3</td><td>7440.00</td><td>55.79</td><td>74.00</td><td>-18.21</td><td>72.60</td><td>36.61</td><td>12.39</td><td>66.23</td><td>0.42</td><td>254</td><td>198</td><td>PEAK</td></tr><tr><td>4</td><td>7440.00</td><td>50.85</td><td>54.00</td><td>-3.15</td><td>67.66</td><td>36.61</td><td>12.39</td><td>66.23</td><td>0.42</td><td>254</td><td>198</td><td>Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	46.56	74.00	-27.44	70.00	33.04	10.03	66.93	0.42	108	44	PEAK	2	4960.00	40.92	54.00	-13.08	64.36	33.04	10.03	66.93	0.42	108	44	Average	3	7440.00	55.79	74.00	-18.21	72.60	36.61	12.39	66.23	0.42	254	198	PEAK	4	7440.00	50.85	54.00	-3.15	67.66	36.61	12.39	66.23	0.42	254	198	Average	 Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250808 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4960.00</td><td>48.65</td><td>74.00</td><td>-25.35</td><td>72.06</td><td>33.07</td><td>10.03</td><td>66.93</td><td>0.42</td><td>304</td><td>176</td><td>PEAK</td></tr><tr><td>2</td><td>4960.00</td><td>42.65</td><td>54.00</td><td>-11.35</td><td>66.06</td><td>33.07</td><td>10.03</td><td>66.93</td><td>0.42</td><td>304</td><td>176</td><td>Average</td></tr><tr><td>3</td><td>7440.00</td><td>56.25</td><td>74.00</td><td>-17.75</td><td>73.04</td><td>36.63</td><td>12.39</td><td>66.23</td><td>0.42</td><td>386</td><td>94</td><td>PEAK</td></tr><tr><td>4</td><td>7440.00</td><td>51.04</td><td>54.00</td><td>-2.96</td><td>67.83</td><td>36.63</td><td>12.39</td><td>66.23</td><td>0.42</td><td>386</td><td>94</td><td>Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	48.65	74.00	-25.35	72.06	33.07	10.03	66.93	0.42	304	176	PEAK	2	4960.00	42.65	54.00	-11.35	66.06	33.07	10.03	66.93	0.42	304	176	Average	3	7440.00	56.25	74.00	-17.75	73.04	36.63	12.39	66.23	0.42	386	94	PEAK	4	7440.00	51.04	54.00	-2.96	67.83	36.63	12.39	66.23	0.42	386	94	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																														
1	4960.00	46.56	74.00	-27.44	70.00	33.04	10.03	66.93	0.42	108	44	PEAK																																																																																																																																																												
2	4960.00	40.92	54.00	-13.08	64.36	33.04	10.03	66.93	0.42	108	44	Average																																																																																																																																																												
3	7440.00	55.79	74.00	-18.21	72.60	36.61	12.39	66.23	0.42	254	198	PEAK																																																																																																																																																												
4	7440.00	50.85	54.00	-3.15	67.66	36.61	12.39	66.23	0.42	254	198	Average																																																																																																																																																												
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																														
1	4960.00	48.65	74.00	-25.35	72.06	33.07	10.03	66.93	0.42	304	176	PEAK																																																																																																																																																												
2	4960.00	42.65	54.00	-11.35	66.06	33.07	10.03	66.93	0.42	304	176	Average																																																																																																																																																												
3	7440.00	56.25	74.00	-17.75	73.04	36.63	12.39	66.23	0.42	386	94	PEAK																																																																																																																																																												
4	7440.00	51.04	54.00	-2.96	67.83	36.63	12.39	66.23	0.42	386	94	Average																																																																																																																																																												







Mode	3	
	Harmonic	
	2400-2483.5_Bluetooth-LE GSKF_CH39_2480MHz	
ANT	1TX	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Level (dBuV/m) Frequency (MHz) Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250008 HORIZONTAL	Level (dBuV/m) Frequency (MHz) Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250008 VERTICAL



Mode	4																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_Bluetooth-LE GSKF_CH00_2402MHz																																																																																																			
ANT	1TX																																																																																																			
Pol.	Horizontal						Fundamental																																																																																													
Peak	 Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2361.98</td><td>56.15</td><td>74.00</td><td>-17.85</td><td>42.09</td><td>27.46</td><td>7.26</td><td>30.64</td><td>9.98</td><td>119</td><td>271</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2361.98	56.15	74.00	-17.85	42.09	27.46	7.26	30.64	9.98	119	271	PEAK	 Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>104.92</td><td>-----</td><td>-----</td><td>90.57</td><td>27.66</td><td>7.33</td><td>30.62</td><td>9.98</td><td>119</td><td>271</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	104.92	-----	-----	90.57	27.66	7.33	30.62	9.98	119	271	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2361.98	56.15	74.00	-17.85	42.09	27.46	7.26	30.64	9.98	119	271	PEAK																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	104.92	-----	-----	90.57	27.66	7.33	30.62	9.98	119	271	PEAK																																																																																								
Avg	 Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3.300kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2361.70</td><td>47.02</td><td>54.00</td><td>-6.98</td><td>32.96</td><td>27.46</td><td>7.26</td><td>30.64</td><td>9.98</td><td>119</td><td>271</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2361.70	47.02	54.00	-6.98	32.96	27.46	7.26	30.64	9.98	119	271	AVERAGE	 Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3.300kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>103.59</td><td>-----</td><td>-----</td><td>89.24</td><td>27.66</td><td>7.33</td><td>30.62</td><td>9.98</td><td>119</td><td>271</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	103.59	-----	-----	89.24	27.66	7.33	30.62	9.98	119	271	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2361.70	47.02	54.00	-6.98	32.96	27.46	7.26	30.64	9.98	119	271	AVERAGE																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	103.59	-----	-----	89.24	27.66	7.33	30.62	9.98	119	271	AVERAGE																																																																																								



Mode	4																																																																																																		
	Band Edge																																																																																																		
	2400-2483.5_Bluetooth-LE GSKF_CH00_2402MHz																																																																																																		
ANT	1TX																																																																																																		
Pol.	Vertical						Fundamental																																																																																												
Peak																																																																																																			
	Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2351.95</td><td>55.68</td><td>74.00</td><td>-18.32</td><td>41.84</td><td>27.26</td><td>7.24</td><td>30.64</td><td>9.98</td><td>386</td><td>230</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2351.95	55.68	74.00	-18.32	41.84	27.26	7.24	30.64	9.98	386	230	PEAK	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>101.65</td><td>-----</td><td>-----</td><td>87.42</td><td>27.54</td><td>7.33</td><td>30.62</td><td>9.98</td><td>386</td><td>230</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	101.65	-----	-----	87.42	27.54	7.33	30.62	9.98	386	230
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2351.95	55.68	74.00	-18.32	41.84	27.26	7.24	30.64	9.98	386	230	PEAK																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2402.00	101.65	-----	-----	87.42	27.54	7.33	30.62	9.98	386	230	PEAK																																																																																							
Avg																																																																																																			
	Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3.300kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2378.45</td><td>46.24</td><td>54.00</td><td>-7.76</td><td>32.22</td><td>27.38</td><td>7.29</td><td>30.63</td><td>9.98</td><td>386</td><td>230</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2378.45	46.24	54.00	-7.76	32.22	27.38	7.29	30.63	9.98	386	230	AVERAGE	Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3.300kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>100.33</td><td>-----</td><td>-----</td><td>86.10</td><td>27.54</td><td>7.33</td><td>30.62</td><td>9.98</td><td>386</td><td>230</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	100.33	-----	-----	86.10	27.54	7.33	30.62	9.98	386	230
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2378.45	46.24	54.00	-7.76	32.22	27.38	7.29	30.63	9.98	386	230	AVERAGE																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2402.00	100.33	-----	-----	86.10	27.54	7.33	30.62	9.98	386	230	AVERAGE																																																																																							







Mode	4																																																																																																																	
	Harmonic																																																																																																																	
	2400-2483.5_Bluetooth-LE GSKF_CH00_2402MHz																																																																																																																	
ANT	1TX																																																																																																																	
Pol.	Horizontal	Vertical																																																																																																																
Peak Avg	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250808 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4804.00</td><td>41.87</td><td>74.00</td><td>-32.13</td><td>65.70</td><td>32.52</td><td>9.81</td><td>66.76</td><td>0.60</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7206.00</td><td>55.10</td><td>74.00</td><td>-18.90</td><td>70.32</td><td>36.91</td><td>12.13</td><td>64.62</td><td>0.36</td><td>100</td><td>112</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4804.00	41.87	74.00	-32.13	65.70	32.52	9.81	66.76	0.60	--	PEAK	2	7206.00	55.10	74.00	-18.90	70.32	36.91	12.13	64.62	0.36	100	112	PEAK	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250808 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4804.00</td><td>44.37</td><td>74.00</td><td>-29.63</td><td>68.18</td><td>32.54</td><td>9.81</td><td>66.76</td><td>0.60</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7206.00</td><td>55.12</td><td>74.00</td><td>-18.88</td><td>70.33</td><td>36.92</td><td>12.13</td><td>64.62</td><td>0.36</td><td>322</td><td>359</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4804.00	44.37	74.00	-29.63	68.18	32.54	9.81	66.76	0.60	--	PEAK	2	7206.00	55.12	74.00	-18.88	70.33	36.92	12.13	64.62	0.36	322	359	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																								
1	4804.00	41.87	74.00	-32.13	65.70	32.52	9.81	66.76	0.60	--	PEAK																																																																																																							
2	7206.00	55.10	74.00	-18.90	70.32	36.91	12.13	64.62	0.36	100	112	PEAK																																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																								
1	4804.00	44.37	74.00	-29.63	68.18	32.54	9.81	66.76	0.60	--	PEAK																																																																																																							
2	7206.00	55.12	74.00	-18.88	70.33	36.92	12.13	64.62	0.36	322	359	Peak																																																																																																						



Mode	4	
	Harmonic	
	2400-2483.5_Bluetooth-LE GSKF_CH00_2402MHz	
ANT	1TX	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Level (dBuV/m) Frequency (MHz) Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250008 HORIZONTAL	Level (dBuV/m) Frequency (MHz) Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250008 VERTICAL







Mode	5																																																																																															
	Band Edge - L																																																																																															
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																																																																															
ANT	1TX																																																																																															
Pol.	Horizontal						Fundamental																																																																																									
Peak																																																																																																
	Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2349.91</td><td>55.61</td><td>74.00</td><td>-18.39</td><td>41.63</td><td>27.40</td><td>7.24</td><td>30.64</td><td>9.98</td><td>265</td><td>0 PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2349.91	55.61	74.00	-18.39	41.63	27.40	7.24	30.64	9.98	265	0 PEAK	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>105.54</td><td>-----</td><td>-----</td><td>90.96</td><td>27.82</td><td>7.39</td><td>30.61</td><td>9.98</td><td>265</td><td>0 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	105.54	-----	-----	90.96	27.82	7.39	30.61	9.98	265
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2349.91	55.61	74.00	-18.39	41.63	27.40	7.24	30.64	9.98	265	0 PEAK																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2440.00	105.54	-----	-----	90.96	27.82	7.39	30.61	9.98	265	0 PEAK																																																																																					
Avg																																																																																																
	Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3.300kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2383.84</td><td>46.79</td><td>54.00</td><td>-7.21</td><td>32.57</td><td>27.57</td><td>7.30</td><td>30.63</td><td>9.98</td><td>265</td><td>0 AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2383.84	46.79	54.00	-7.21	32.57	27.57	7.30	30.63	9.98	265	0 AVERAGE	Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3.300kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>104.15</td><td>-----</td><td>-----</td><td>89.57</td><td>27.82</td><td>7.39</td><td>30.61</td><td>9.98</td><td>265</td><td>0 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	104.15	-----	-----	89.57	27.82	7.39	30.61	9.98	265
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2383.84	46.79	54.00	-7.21	32.57	27.57	7.30	30.63	9.98	265	0 AVERAGE																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2440.00	104.15	-----	-----	89.57	27.82	7.39	30.61	9.98	265	0 AVERAGE																																																																																					





Mode	5																																																						
	Band Edge - R																																																						
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																																						
ANT	1TX																																																						
Pol.	Horizontal						Fundamental																																																
Peak	Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250808 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2488.78</td><td>56.13</td><td>74.00</td><td>-17.87</td><td>41.28</td><td>27.98</td><td>7.46</td><td>30.57</td><td>9.98</td><td>265</td><td>0</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2488.78	56.13	74.00	-17.87	41.28	27.98	7.46	30.57	9.98	265	0	PEAK	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2488.78	56.13	74.00	-17.87	41.28	27.98	7.46	30.57	9.98	265	0	PEAK																																											
Avg	Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250808 HORIZONTAL : RBW:1000.000kHz VBW:3.300kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2495.74</td><td>47.24</td><td>54.00</td><td>-6.76</td><td>32.35</td><td>28.00</td><td>7.47</td><td>30.56</td><td>9.98</td><td>265</td><td>0</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2495.74	47.24	54.00	-6.76	32.35	28.00	7.47	30.56	9.98	265	0	AVERAGE	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																													
1	2495.74	47.24	54.00	-6.76	32.35	28.00	7.47	30.56	9.98	265	0	AVERAGE																																											





Mode	5																																																																																														
	Band Edge - L																																																																																														
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																																																																														
ANT	1TX																																																																																														
Pol.	Vertical						Fundamental																																																																																								
Peak	 Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2361.74</td><td>55.43</td><td>74.00</td><td>-18.57</td><td></td><td>41.53</td><td>27.30</td><td>7.26</td><td>30.64</td><td>9.98</td><td>300</td><td>304</td><td>PEAK</td></tr></tbody></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg		1	2361.74	55.43	74.00	-18.57		41.53	27.30	7.26	30.64	9.98	300	304	PEAK	 Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>100.53</td><td>-----</td><td>-----</td><td></td><td>85.95</td><td>27.82</td><td>7.39</td><td>30.61</td><td>9.98</td><td>300</td><td>304</td><td>PEAK</td></tr></tbody></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg		1	2440.00	100.53	-----	-----		85.95	27.82	7.39	30.61	9.98	300	304	PEAK
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																		
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg																																																																																			
1	2361.74	55.43	74.00	-18.57		41.53	27.30	7.26	30.64	9.98	300	304	PEAK																																																																																		
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																		
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg																																																																																			
1	2440.00	100.53	-----	-----		85.95	27.82	7.39	30.61	9.98	300	304	PEAK																																																																																		
Avg	 Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3.300kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2375.91</td><td>46.11</td><td>54.00</td><td>-7.89</td><td>32.10</td><td>27.37</td><td>7.29</td><td>30.63</td><td>9.98</td><td>300</td><td>304</td><td></td><td>AVERAGE</td></tr></tbody></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg		1	2375.91	46.11	54.00	-7.89	32.10	27.37	7.29	30.63	9.98	300	304		AVERAGE	 Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3.300kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>99.20</td><td>-----</td><td>-----</td><td></td><td>84.62</td><td>27.82</td><td>7.39</td><td>30.61</td><td>9.98</td><td>300</td><td>304</td><td>AVERAGE</td></tr></tbody></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg		1	2440.00	99.20	-----	-----		84.62	27.82	7.39	30.61	9.98	300	304	AVERAGE
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																		
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg																																																																																			
1	2375.91	46.11	54.00	-7.89	32.10	27.37	7.29	30.63	9.98	300	304		AVERAGE																																																																																		
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																		
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg																																																																																			
1	2440.00	99.20	-----	-----		84.62	27.82	7.39	30.61	9.98	300	304	AVERAGE																																																																																		





Mode	5																																																							
	Band Edge - R																																																							
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																																							
ANT	1TX																																																							
Pol.	Vertical						Fundamental																																																	
Peak	 Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2491.30</td><td>55.88</td><td>74.00</td><td>-18.12</td><td>40.96</td><td>28.04</td><td>7.47</td><td>30.57</td><td>9.98</td><td>300</td><td>304</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2491.30	55.88	74.00	-18.12	40.96	28.04	7.47	30.57	9.98	300	304	PEAK	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2491.30	55.88	74.00	-18.12	40.96	28.04	7.47	30.57	9.98	300	304	PEAK																																												
Avg	 Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3.300kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2488.90</td><td>46.82</td><td>54.00</td><td>-7.18</td><td>31.91</td><td>28.04</td><td>7.46</td><td>30.57</td><td>9.98</td><td>300</td><td>304</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2488.90	46.82	54.00	-7.18	31.91	28.04	7.46	30.57	9.98	300	304	AVERAGE	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2488.90	46.82	54.00	-7.18	31.91	28.04	7.46	30.57	9.98	300	304	AVERAGE																																												







Mode	5																																																																																																																																							
	Harmonic																																																																																																																																							
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																																																																																																																							
ANT	1TX																																																																																																																																							
Pol.	Horizontal	Vertical																																																																																																																																						
Peak Avg	 Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250808 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>42.23</td><td>74.00</td><td>-31.77</td><td>65.80</td><td>32.80</td><td>9.92</td><td>66.80</td><td>0.51</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7320.00</td><td>56.16</td><td>74.00</td><td>-17.84</td><td>72.63</td><td>36.93</td><td>12.27</td><td>66.05</td><td>0.38</td><td>255</td><td>266 PEAK</td></tr><tr><td>3</td><td>7320.00</td><td>49.71</td><td>54.00</td><td>-4.29</td><td>66.18</td><td>36.93</td><td>12.27</td><td>66.05</td><td>0.38</td><td>255</td><td>266 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	42.23	74.00	-31.77	65.80	32.80	9.92	66.80	0.51	--	PEAK	2	7320.00	56.16	74.00	-17.84	72.63	36.93	12.27	66.05	0.38	255	266 PEAK	3	7320.00	49.71	54.00	-4.29	66.18	36.93	12.27	66.05	0.38	255	266 Average	 Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250808 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>43.64</td><td>74.00</td><td>-30.36</td><td>67.19</td><td>32.82</td><td>9.92</td><td>66.80</td><td>0.51</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7320.00</td><td>54.58</td><td>74.00</td><td>-19.42</td><td>71.82</td><td>36.96</td><td>12.27</td><td>66.05</td><td>0.38</td><td>182</td><td>293 PEAK</td></tr><tr><td>3</td><td>7320.00</td><td>49.31</td><td>54.00</td><td>-4.69</td><td>65.75</td><td>36.96</td><td>12.27</td><td>66.05</td><td>0.38</td><td>182</td><td>293 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	43.64	74.00	-30.36	67.19	32.82	9.92	66.80	0.51	--	PEAK	2	7320.00	54.58	74.00	-19.42	71.82	36.96	12.27	66.05	0.38	182	293 PEAK	3	7320.00	49.31	54.00	-4.69	65.75	36.96	12.27	66.05	0.38	182	293 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																														
1	4880.00	42.23	74.00	-31.77	65.80	32.80	9.92	66.80	0.51	--	PEAK																																																																																																																													
2	7320.00	56.16	74.00	-17.84	72.63	36.93	12.27	66.05	0.38	255	266 PEAK																																																																																																																													
3	7320.00	49.71	54.00	-4.29	66.18	36.93	12.27	66.05	0.38	255	266 Average																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																														
1	4880.00	43.64	74.00	-30.36	67.19	32.82	9.92	66.80	0.51	--	PEAK																																																																																																																													
2	7320.00	54.58	74.00	-19.42	71.82	36.96	12.27	66.05	0.38	182	293 PEAK																																																																																																																													
3	7320.00	49.31	54.00	-4.69	65.75	36.96	12.27	66.05	0.38	182	293 Average																																																																																																																													







Mode	5	
	Harmonic	
	2400-2483.5_Bluetooth-LE GSKF _CH19_2440MHz	
ANT	1TX	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250008 HORIZONTAL	 Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250008 VERTICAL





		6																																																																																																							
Mode		Band Edge																																																																																																							
		2400-2483.5_Bluetooth-LE GSKF_CH39_2480MHz																																																																																																							
ANT		1TX																																																																																																							
Pol.		Horizontal						Fundamental																																																																																																	
Peak		 Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.92</td><td>59.25</td><td>74.00</td><td>-14.75</td><td>44.42</td><td>27.97</td><td>7.46</td><td>30.58</td><td>9.98</td><td>178</td><td>186</td><td>PEAK</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.92	59.25	74.00	-14.75	44.42	27.97	7.46	30.58	9.98	178	186	PEAK	 Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>105.20</td><td>-----</td><td>-----</td><td>90.38</td><td>27.97</td><td>7.45</td><td>30.58</td><td>9.98</td><td>178</td><td>186</td><td>PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	105.20	-----	-----	90.38	27.97	7.45	30.58	9.98	178	186	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																															
1	2483.92	59.25	74.00	-14.75	44.42	27.97	7.46	30.58	9.98	178	186	PEAK																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																															
1	2480.00	105.20	-----	-----	90.38	27.97	7.45	30.58	9.98	178	186	PEAK																																																																																													
Avg		 Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3.300kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.52</td><td>50.70</td><td>54.00</td><td>-3.30</td><td>35.87</td><td>27.97</td><td>7.46</td><td>30.58</td><td>9.98</td><td>178</td><td>186</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.52	50.70	54.00	-3.30	35.87	27.97	7.46	30.58	9.98	178	186	AVERAGE	 Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250000 HORIZONTAL : RBW:1000.000kHz VBW:3.300kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>103.79</td><td>-----</td><td>-----</td><td>88.97</td><td>27.97</td><td>7.45</td><td>30.58</td><td>9.98</td><td>178</td><td>186</td><td>AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	103.79	-----	-----	88.97	27.97	7.45	30.58	9.98	178	186	AVERAGE					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																															
1	2483.52	50.70	54.00	-3.30	35.87	27.97	7.46	30.58	9.98	178	186	AVERAGE																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																															
1	2480.00	103.79	-----	-----	88.97	27.97	7.45	30.58	9.98	178	186	AVERAGE																																																																																													



		6																																																																																																	
Mode	Band Edge																																																																																																		
	2400-2483.5_Bluetooth-LE GSKF_CH39_2480MHz																																																																																																		
ANT	1TX																																																																																																		
Pol.	Vertical						Fundamental																																																																																												
Peak	 Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.60</td><td>59.34</td><td>74.00</td><td>-14.66</td><td>44.45</td><td>28.03</td><td>7.46</td><td>30.58</td><td>9.98</td><td>357</td><td>228</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.60	59.34	74.00	-14.66	44.45	28.03	7.46	30.58	9.98	357	228	PEAK	 Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>99.97</td><td>-----</td><td>-----</td><td>85.10</td><td>28.02</td><td>7.45</td><td>30.58</td><td>9.98</td><td>357</td><td>228</td><td>PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	99.97	-----	-----	85.10	28.02	7.45	30.58	9.98	357	228	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2483.60	59.34	74.00	-14.66	44.45	28.03	7.46	30.58	9.98	357	228	PEAK																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2480.00	99.97	-----	-----	85.10	28.02	7.45	30.58	9.98	357	228	PEAK																																																																																							
Avg	 Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3.300kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.52</td><td>47.97</td><td>54.00</td><td>-6.03</td><td>33.08</td><td>28.03</td><td>7.46</td><td>30.58</td><td>9.98</td><td>357</td><td>228</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.52	47.97	54.00	-6.03	33.08	28.03	7.46	30.58	9.98	357	228	AVERAGE	 Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250000 VERTICAL : RBW:1000.000kHz VBW:3.300kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>98.61</td><td>-----</td><td>-----</td><td>83.74</td><td>28.02</td><td>7.45</td><td>30.58</td><td>9.98</td><td>357</td><td>228</td><td>AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	98.61	-----	-----	83.74	28.02	7.45	30.58	9.98	357	228	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2483.52	47.97	54.00	-6.03	33.08	28.03	7.46	30.58	9.98	357	228	AVERAGE																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2480.00	98.61	-----	-----	83.74	28.02	7.45	30.58	9.98	357	228	AVERAGE																																																																																							





Mode	6																																																																																									
	Harmonic																																																																																									
	2400-2483.5_Bluetooth-LE GSKF_CH39_2480MHz																																																																																									
ANT	1TX																																																																																									
Pol.	Horizontal						Vertical																																																																																			
Peak Avg																																																																																										
	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250808 HORIZONTAL						Site : 03CH01-CA Condition: PEAK_74 3m HORN_02115_250808 VERTICAL																																																																																			
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4960.00</td><td>46.10</td><td>74.00</td><td>-27.90</td><td>69.54</td><td>33.04</td><td>10.03</td><td>66.93</td><td>0.42</td><td>111</td><td>1 PEAK</td></tr><tr><td>2</td><td>4960.00</td><td>41.44</td><td>54.00</td><td>-12.56</td><td>64.88</td><td>33.04</td><td>10.03</td><td>66.93</td><td>0.42</td><td>111</td><td>1 Average</td></tr><tr><td>3</td><td>7440.00</td><td>55.05</td><td>74.00</td><td>-18.95</td><td>71.06</td><td>36.61</td><td>12.39</td><td>66.23</td><td>0.42</td><td>254</td><td>359 PEAK</td></tr><tr><td>4</td><td>7440.00</td><td>50.08</td><td>54.00</td><td>-3.92</td><td>66.09</td><td>36.61</td><td>12.39</td><td>66.23</td><td>0.42</td><td>254</td><td>359 Average</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	46.10	74.00	-27.90	69.54	33.04	10.03	66.93	0.42	111	1 PEAK	2	4960.00	41.44	54.00	-12.56	64.88	33.04	10.03	66.93	0.42	111	1 Average	3	7440.00	55.05	74.00	-18.95	71.06	36.61	12.39	66.23	0.42	254	359 PEAK	4	7440.00	50.08	54.00	-3.92	66.09	36.61	12.39	66.23	0.42	254	359 Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	4960.00	46.10	74.00	-27.90	69.54	33.04	10.03	66.93	0.42	111	1 PEAK																																																																															
2	4960.00	41.44	54.00	-12.56	64.88	33.04	10.03	66.93	0.42	111	1 Average																																																																															
3	7440.00	55.05	74.00	-18.95	71.06	36.61	12.39	66.23	0.42	254	359 PEAK																																																																															
4	7440.00	50.08	54.00	-3.92	66.09	36.61	12.39	66.23	0.42	254	359 Average																																																																															





Mode	6	
	Harmonic	
	2400-2483.5_Bluetooth-LE GSKF_CH39_2480MHz	
ANT	1TX	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Level (dBuV/m) Frequency (MHz) Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250008 HORIZONTAL	Level (dBuV/m) Frequency (MHz) Site : 03CH01-CA Condition: AVG_54 3m HORN_02115_250008 VERTICAL



Mode	7																																																																																																																																																																																																																							
	LF																																																																																																																																																																																																																							
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																																																																																																																																																																																																							
ANT	1TX																																																																																																																																																																																																																							
Pol.	Horizontal						Vertical																																																																																																																																																																																																																	
QPI Peak																																																																																																																																																																																																																								
	Site : 03CH01-CA Condition: QP 3m B1LOG_54683_241115 HORIZONTAL						Site : 03CH01-CA Condition: QP 3m B1LOG_54683_241115 VERTICAL																																																																																																																																																																																																																	
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>30.97</td><td>21.12</td><td>40.00</td><td>-18.88</td><td>27.97</td><td>24.57</td><td>0.92</td><td>32.41</td><td>0.07</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>106.63</td><td>18.51</td><td>43.50</td><td>-24.99</td><td>32.22</td><td>16.96</td><td>1.58</td><td>32.39</td><td>0.14</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>267.65</td><td>18.62</td><td>46.00</td><td>-27.38</td><td>28.86</td><td>19.60</td><td>2.43</td><td>32.43</td><td>0.16</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>510.15</td><td>23.75</td><td>46.00</td><td>-22.25</td><td>28.70</td><td>24.13</td><td>3.30</td><td>32.59</td><td>0.21</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>632.37</td><td>33.54</td><td>46.00</td><td>-12.46</td><td>35.86</td><td>26.35</td><td>3.68</td><td>32.61</td><td>0.26</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>946.65</td><td>31.45</td><td>46.00</td><td>-14.55</td><td>26.96</td><td>30.83</td><td>4.48</td><td>31.27</td><td>0.45</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	30.97	21.12	40.00	-18.88	27.97	24.57	0.92	32.41	0.07	--	Peak	2	106.63	18.51	43.50	-24.99	32.22	16.96	1.58	32.39	0.14	--	Peak	3	267.65	18.62	46.00	-27.38	28.86	19.60	2.43	32.43	0.16	--	Peak	4	510.15	23.75	46.00	-22.25	28.70	24.13	3.30	32.59	0.21	--	Peak	5	632.37	33.54	46.00	-12.46	35.86	26.35	3.68	32.61	0.26	--	Peak	6	946.65	31.45	46.00	-14.55	26.96	30.83	4.48	31.27	0.45	--	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>32.91</td><td>21.95</td><td>40.00</td><td>-18.05</td><td>29.73</td><td>23.63</td><td>0.94</td><td>32.41</td><td>0.06</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>123.12</td><td>16.56</td><td>43.50</td><td>-26.94</td><td>29.64</td><td>17.51</td><td>1.69</td><td>32.39</td><td>0.11</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>255.04</td><td>19.10</td><td>46.00</td><td>-26.90</td><td>29.53</td><td>19.45</td><td>2.38</td><td>32.42</td><td>0.16</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>500.45</td><td>24.31</td><td>46.00</td><td>-21.69</td><td>29.29</td><td>24.12</td><td>3.27</td><td>32.58</td><td>0.21</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>636.25</td><td>34.22</td><td>46.00</td><td>-11.78</td><td>36.45</td><td>26.42</td><td>3.69</td><td>32.60</td><td>0.26</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>947.62</td><td>32.98</td><td>46.00</td><td>-13.02</td><td>28.43</td><td>30.87</td><td>4.49</td><td>31.26</td><td>0.45</td><td>--</td><td>Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	32.91	21.95	40.00	-18.05	29.73	23.63	0.94	32.41	0.06	--	Peak	2	123.12	16.56	43.50	-26.94	29.64	17.51	1.69	32.39	0.11	--	Peak	3	255.04	19.10	46.00	-26.90	29.53	19.45	2.38	32.42	0.16	--	Peak	4	500.45	24.31	46.00	-21.69	29.29	24.12	3.27	32.58	0.21	--	Peak	5	636.25	34.22	46.00	-11.78	36.45	26.42	3.69	32.60	0.26	--	Peak	6	947.62	32.98	46.00	-13.02	28.43	30.87	4.49	31.26	0.45	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																														
1	30.97	21.12	40.00	-18.88	27.97	24.57	0.92	32.41	0.07	--	Peak																																																																																																																																																																																																													
2	106.63	18.51	43.50	-24.99	32.22	16.96	1.58	32.39	0.14	--	Peak																																																																																																																																																																																																													
3	267.65	18.62	46.00	-27.38	28.86	19.60	2.43	32.43	0.16	--	Peak																																																																																																																																																																																																													
4	510.15	23.75	46.00	-22.25	28.70	24.13	3.30	32.59	0.21	--	Peak																																																																																																																																																																																																													
5	632.37	33.54	46.00	-12.46	35.86	26.35	3.68	32.61	0.26	--	Peak																																																																																																																																																																																																													
6	946.65	31.45	46.00	-14.55	26.96	30.83	4.48	31.27	0.45	--	Peak																																																																																																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																														
1	32.91	21.95	40.00	-18.05	29.73	23.63	0.94	32.41	0.06	--	Peak																																																																																																																																																																																																													
2	123.12	16.56	43.50	-26.94	29.64	17.51	1.69	32.39	0.11	--	Peak																																																																																																																																																																																																													
3	255.04	19.10	46.00	-26.90	29.53	19.45	2.38	32.42	0.16	--	Peak																																																																																																																																																																																																													
4	500.45	24.31	46.00	-21.69	29.29	24.12	3.27	32.58	0.21	--	Peak																																																																																																																																																																																																													
5	636.25	34.22	46.00	-11.78	36.45	26.42	3.69	32.60	0.26	--	Peak																																																																																																																																																																																																													
6	947.62	32.98	46.00	-13.02	28.43	30.87	4.49	31.26	0.45	--	Peak																																																																																																																																																																																																													



Mode	8																																																																																															
	SHF																																																																																															
	2400-2483.5_Bluetooth-LE GSKF_CH19_2440MHz																																																																																															
ANT	1TX																																																																																															
Pol.	Horizontal						Vertical																																																																																									
Peak																																																																																																
	Site : 03CH01-CA Condition: PEAK_74 1m SHF_HORN_00041_250808 HORIZONTAL						Site : 03CH01-CA Condition: PEAK_74 1m SHF_HORN_00041_250808 VERTICAL																																																																																									
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>24349.00</td><td>42.41</td><td>74.00</td><td>-31.59</td><td>39.43</td><td>38.79</td><td>26.23</td><td>52.50</td><td>-9.54</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	24349.00	42.41	74.00	-31.59	39.43	38.79	26.23	52.50	-9.54	--	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>24300.00</td><td>43.43</td><td>74.00</td><td>-30.57</td><td>40.39</td><td>38.85</td><td>26.21</td><td>52.48</td><td>-9.54</td><td>--</td><td>Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	24300.00	43.43	74.00	-30.57	40.39	38.85	26.21	52.48	-9.54	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	24349.00	42.41	74.00	-31.59	39.43	38.79	26.23	52.50	-9.54	--	Peak																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	24300.00	43.43	74.00	-30.57	40.39	38.85	26.21	52.48	-9.54	--	Peak																																																																																					



Appendix C. Duty Cycle Plots

Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting
Bluetooth - LE for 1Mbps	48.00	600	1.80	3kHz
Bluetooth - LE for 2Mbps	49.68	310	3.30	10kHz

